

Hypertext marks in L^AT_EX

Sebastian Rahtz (deceased)

Heiko Oberdiek (inactive)

The L^AT_EX Project

<https://github.com/latex3/hyperref/issues>

2023-05-16 v7.00y

1 Documentation overview for `hyperref`

The documentation for package `hyperref` consists of several files:

Manual The **USER MANUAL** (also available as HTML).

ChangeLog This file records the version history.

Bookmark talk, slides Slides for the talk “PDF information and navigation elements with hyperref, pdfTeX and thumbpdf” at EuroTeX 1999.

Bookmark talk, paper The paper version of the talk.

Source code documentation:

☞ **hyperref.dtx** This is the source code documentation for hyperref (this file).

backref.dtx “Back referencing from bibliographical citations”

nameref.dtx “Section name references in L^AT_EX”

2 Contents

1 Documentation overview for hyperref	1
2 Contents	2
3 File hycheck.tex	7
4 Package options and setup	11
4.1 Save catcodes	11
4.2 Version check	13
4.3 Checks with regular expressions	14
4.4 Compatibility with format dumps	15
4.5 Switches	15
5 Common help macros	17
5.1 Macros for recursions	17
5.2 Babel's protection of shorthand characters	18
5.3 Coordinate transformations	18
6 Dealing with PDF strings	18
6.1 Description of PDF strings	18
6.2 Definition of \pdfstringdef	19
6.2.1 Preprocessing	20
6.2.2 Expansion	26
6.2.3 Postprocessing	27
6.3 Encodings	32
6.3.1 Xe _T E _X	32
6.3.2 Workaround for package linguex	32
6.3.3 Catcodes saving and restoring for .def files	32
6.3.4 PD1 encoding	33
6.3.5 PU encoding	34
6.4 Additional user commands	34
6.4.1 \texorpdfstring	34
6.4.2 Hooks for \pdfstringdef	35
6.5 Help macros for expansion	36
6.5.1 \ignorespaces	36
6.5.2 Babel languages	36
6.5.3 CJK patch	37
6.5.4 CJK bookmarks	37
6.5.5 CJK unicode	39
6.5.6 \inmathwarn-Patch	43
6.5.7 Unexpandable spaces	45
6.5.8 Marker for commands	45
6.5.9 \hspace fix	45
6.5.10 Fix for AMS classes	45
6.5.11 Reference commands	46
6.5.12 Redefining the defining commands	48
6.5.13 \ifnextchar	49
6.5.14 \protected@testopt\ifnextchar	50

6.6	Help macros for postprocessing	50
6.6.1	Generic warning.	50
6.6.2	Protecting spaces	50
6.6.3	Remove grouping braces	51
6.6.4	Catcode check	52
6.6.5	Check for wrong glyphs	56
6.6.6	Replacing tokens	57
6.6.7	Support for package <code>xspace</code>	58
6.6.8	Converting to Unicode	59
6.6.9	Support for UTF-8 input encoding	61
6.6.10	Support for die faces (<code>ifsym</code> et. al.)	65
6.6.11	Support for moon phases of package <code>china2e</code>	66
6.6.12	Support for package <code>pifont</code>	66
7	Support of other packages	68
7.1	Package <code>subfigure</code>	68
7.2	Package <code>xr</code> and <code>xr-hyper</code>	68
8	Help macros for links	69
9	Options	70
9.1	Help macros	71
9.2	Defining the options	74
10	Options for different drivers	79
11	Options to add extra features	83
12	Language options	85
13	Options to change appearance of links	94
14	Bookmarking	95
15	PDF-specific options	97
15.1	Package <code>xspace</code> support	111
15.2	Option <code>draft</code>	111
15.3	PDF/A	112
15.4	Patch for <code>babel</code> 's <code>\texttilde</code>	113
15.4.1	Driver loading	114
15.4.2	Bookmarks	118
16	User hypertext macros	121
16.1	Link box support for XeTeX	128
17	Underlying basic hypertext macros	129
18	Option ‘<code>destlabel</code>’	134

19 Forms creation	136
19.1 Field flags	136
19.1.1 Declarations of field flags	138
19.1.2 Set submit flags	140
19.1.3 Set annot flags in fields	141
19.1.4 Pushbutton field	141
19.1.5 Check box field	141
19.1.6 Radio button field	142
19.1.7 Text fields	142
19.1.8 Choice fields	143
19.2 Choice field	143
19.3 Forms	145
20 Setup	154
21 Low-level utility macros	154
22 Localized nullifying of package	155
23 Package nohyperref	156
24 The Mangling Of Aux and Toc Files	157
25 Title strings	158
26 Page numbers	160
27 Every page	160
27.1 PDF /PageLabels	160
27.1.1 pdfTeX and VTeX	164
27.1.2 xetex	166
27.1.3 pdfmarkbase, dvipdfm, xetex	167
28 Automated L^AT_EX hypertext cross-references	168
29 Package ifthen support	175
30 Package titlesec and titletoc support	175
31 Package varioref support	175
32 Package longtable support	176
33 Equations	177
34 Footnotes	180
35 Float captions	185
36 Bibliographic references	187
36.1 Package harvard	190
36.2 Package chicago	191

37	Page numbers	192
38	Table of contents	194
39	New counters	197
40	AMSIATEX compatibility	197
40.1	\addtoreset and \numberwithin patches	198
41	Included figures	199
42	hyperindex entries	199
43	Configuration files	208
43.1	PS/PDF strings	208
43.2	pdftex	209
43.2.1	Fix for problem with different nesting levels	223
43.3	hypertex	223
43.4	dviwindo	226
43.5	dvipdfm/xetex dvi to PDF converter	231
43.6	VTeX typesetting system	241
43.7	Fix for Adobe bug number 466320	255
43.8	Direct pdfmark support	255
43.9	Rokicki's dvips	270
43.10	VTeX's vtexpdfmark driver	273
43.11	Textures	274
43.12	dvipsone	279
43.13	TeX4ht	282
44	Driver-specific form support	285
44.1	pdfmarks	285
44.2	HyperTeX	294
44.3	TeX4ht	294
44.4	pdfTeX	297
44.5	dvipdfm, xetex	306
44.6	Common forms part	314
45	Bookmarks in the PDF file	322
45.1	Bookmarks	322
45.1.1	Rerun warning	325
45.1.2	Driver stuff	326
46	Encoding definition files for encodings of PDF strings	332
46.1	PD1 encoding	332
46.2	PU encoding	340
46.2.1	NFSS2 accents	340
46.2.2	Basic Latin: U+0000 to U+007F	343
46.2.3	Latin-1 Supplement: U+0080 to U+00FF	345
46.2.4	Latin Extended-A: U+0080 to U+017F	349
46.2.5	Latin Extended-B: U+0180 to U+024F	355
46.2.6	IPA Extensions: U+0250 to U+02AF	359

46.2.7	Spacing Modifier Letters: U+02B0 to U+02FF	365
46.2.8	Combining Diacritical Marks: U+0300 to U+036F	366
46.2.9	Greek and Coptic: U+0370 to U+03FF	366
46.2.10	Cyrillic: U+0400 to U+04FF	367
46.2.11	Hebrew: U+0590 to U+05FF	378
46.2.12	Thai: U+0E00 to U+0E7F	379
46.2.13	Phonetic Extensions: U+1D00 to U+1D7F	379
46.2.14	Phonetic Extensions Supplement: U+1D80 to U+1DBF . .	380
46.2.15	Latin Extended Additional: U+1E00 to U+1EFF	380
46.2.16	General Punctuation: U+2000 to U+206F	386
46.2.17	Superscripts and Subscripts: U+2070 to U+209F	388
46.2.18	Currency Symbols: U+20A0 to U+20CF	389
46.2.19	Letterlike Symbols: U+2100 to U+214F	390
46.2.20	Number Forms: U+2150 to U+218F	391
46.2.21	Arrows: U+2190 to U+21FF	391
46.2.22	Mathematical Operators: U+2200 to U+22FF	395
46.2.23	Miscellaneous Technical: U+2300 to U+23FF	406
46.2.24	Control Pictures: U+2400 to U+243F	407
46.2.25	Optical Character Recognition: U+2440 to U+245F . . .	408
46.2.26	Enclosed Alphanumerics: U+2460 to U+24FF	408
46.2.27	Box Drawing: U+2500 to 257F	411
46.2.28	Geometric Shapes: U+25A0 to U+25FF	411
46.2.29	Miscellaneous Symbols: U+2600 to U+26FF	412
46.2.30	Dingbats: U+2700 to U+27BF	416
46.2.31	Miscellaneous Mathematical Symbols-A: U+27C0 to U+27EF	419
46.2.32	Supplemental Arrows-A: U+27F0 to U+27FF	420
46.2.33	Supplemental Arrows-B: U+2900 to U+297F	420
46.2.34	Miscellaneous Mathematical Symbols-B: U+2980 to U+29FF	422
46.2.35	Supplemental Mathematical Operators: U+2A00 to U+2AFF	423
46.2.36	Miscellaneous Symbols and Arrows: U+2B00 to U+2BFF .	426
46.2.37	Latin Extended-C: U+2C60 to U+2C7F	426
46.2.38	Supplemental Punctuation: U+2E00 to U+2E7F	426
46.2.39	Modifier Tone Letters: U+A700 to U+A71F	426
46.2.40	Latin Extended-D: U+A720 to U+A7FF	427
46.2.41	Alphabetic Presentation Forms: U+FB00 to U+FB4F . .	427
46.2.42	Musical Symbols: U+1D100 to U+1D1FF	427
46.2.43	Miscellaneous Symbols and Pictographs: U+1F300 to U+1F5FF	427
46.2.44	Transport and Map Symbols: U+1F680 to U+1F6FF . .	428
46.2.45	Miscellaneous	428
46.2.46	Aliases	428
46.3	PU encoding, additions for VnTeX	429
46.4	PU encoding, additions for Arabi	431
47	End of file hycheck.tex	457
48	Index	458

3 File hycheck.tex

Many commands of L^AT_EX or other packages cannot be overloaded, but have to be redefined by hyperref directly. If these commands change in newer versions, these changes are not noticed by hyperref. With this test file this situation can be checked. It defines the command \checkcommand that is more powerful than L^AT_EX's \CheckCommand, because it takes \DeclareRobustCommand and optional parameters better into account.

```
1 <*check>
2 \documentclass{article}
3 \makeatletter

\checklatex Optional argument: release date of LATEX.
4 \newcommand*{\checklatex}[1]{%
5   \typeout{}%
6   \typeout{* Format: `LaTeX2e' #1}%
7   \typeout{\space\space Loaded: `fmtname' fmtversion}%
8 }%
```

\checkpackage The argument of \checkpackage is the package name without extension optionally followed by a release date.

```
9 \newcommand*{\checkpackage}[1]{%
10  \def\HyC@package{\#1}%
11  \let\HyC@date\empty
12  \@ifnextchar[\HyC@getDate\HyC@checkPackage
13 }
```

\HyC@getDate The release date is scanned.

```
14 \def\HyC@getDate[#1]{%
15  \def\HyC@date{\#1}%
16  \HyC@checkPackage
17 }
```

\HyC@checkPackage

```
18 \def\HyC@checkPackage{%
19  \typeout{}%
20  \begingroup
21  \edef\x{\endgroup
22  \noexpand\RequirePackage{\HyC@package}%
23  \ifx\HyC@date\empty\relax\else[\HyC@date]\fi%
24  }%
25 \x
26 \typeout{}%
27 \typeout{%
28  * Package `\\HyC@package'%
29  \ifx\HyC@date\empty
30  \else
31    \space\HyC@date
32  \fi
33 }%
34 \@ifundefined{ver@\HyC@package.sty}{%
35 }{%
36  \typeout{%
```

```

37     \space\space Loaded: `\'HyC@package' %
38     \csname ver@\HyC@package.sty\endcsname
39   }%
40 }%
41 }

```

\checkcommand The macro \checkcommand parses the next tokens as a L^AT_EX definition and compares this definition with the current meaning of that command.

```

42 \newcommand*\checkcommand[1]{%
43   \begingroup
44   \ifx\long#1\relax
45   \expandafter\HyC@checklong
46   \else
47   \def\HyC@defcmd{\#1}%
48   \expandafter\let\expandafter\HyC@next
49   \csname HyC@\expandafter\@gobble\string#1\endcsname
50   \expandafter\HyC@checkcommand
51   \fi
52 }

```

\HyC@checklong The definition command \def or \edef is read.

```

53 \def\HyC@checklong#1{%
54   \def\HyC@defcmd{\long#1}%
55   \expandafter\let\expandafter\HyC@next
56   \csname HyC@\expandafter\@gobble\string#1\endcsname
57   \HyC@checkcommand
58 }

```

\HyC@checkcommand The optional star of L^AT_EX's definitions is parsed.

```

59 \def\HyC@checkcommand{%
60   \ifx\HyC@next\relax
61   \PackageError{hycheck}{%
62     Unknown command `\'\expandafter\strip@prefix\meaning\HyC@cmd'%
63   }{\@ehd
64   \expandafter\endinput
65   \fi
66   \@ifstar{%
67   \def\HyC@star{*}%
68   \HyC@check
69   }{%
70   \let\HyC@star\@empty
71   \HyC@check
72   }%
73 }

```

\HyC@check The macro \HyC@check reads the definition command.

```

74 \def\HyC@check#1{%
75   \def\HyC@cmd{\#1}%
76   \let\HyC@org@cmd\#1%
77   \let#1\relax
78   \let\HyC@param\@empty
79   \HyC@Toks{}%
80   \let\HyC@org@optcmd\HyC@noValue
81   \let\HyC@org@robustcmd\HyC@noValue

```

```

82 \let\HyC@org@robustoptcmd\HyC@noValue
83 \HyC@next
84 }

\HyC@noValue
85 \def\HyC@noValue{NoValue}

```

\HyC@newcommand The code for \newcommand.

```

86 \def\HyC@newcommand{%
87   \let\HyC@@cmd\HyC@cmd
88   \@ifnextchar[\HyC@nc@opt\HyC@nc@noopt
89 }

```

\HyC@Toks A register for storing the default value of an optional argument.

```
90 \newtoks\HyC@Toks
```

\HyC@nc@noopt This macro \HyC@nc@noopt is called, if the parser has reached the definition text.

```

91 \long\def\HyC@nc@noopt#1{%
92   \edef\x{%
93     \expandafter\noexpand\HyC@defcmd
94     \HyC@star
95     \expandafter\noexpand\HyC@cmd
96     \HyC@param\the\HyC@Toks
97   }%
98   \x{#1}%
99   \HyC@doCheck
100 }

```

\HyC@nc@opt This macro scans the first optional argument of a L^AT_EX definition (number of arguments).

```

101 \def\HyC@nc@opt[#1]{%
102   \def\HyC@param{[{#1}]}%
103   \@ifnextchar[\HyC@nc@default\HyC@nc@noopt
104 }

```

\HyC@nc@default Macro \HyC@nc@default scans the default for an optional argument.

```

105 \def\HyC@nc@default[#1]{%
106   \HyC@Toks={[{#1}]}%
107   \edef\HyC@optcmd{%
108     \expandafter\noexpand
109     \csname\expandafter\string\HyC@@cmd\endcsname
110   }%
111   \expandafter\let\expandafter\HyC@org@optcmd\HyC@optcmd
112   \HyC@nc@noopt
113 }

```

\HyC@DeclareRobustCommand \DeclareRobustCommand{\cmd} makes the command \cmd robust, that then calls \cmd_ with an space at the end of the command name, defined by \newcommand. Therefore the further parsing is done by \HyC@nc@opt or \HyC@nc@noopt of the \HyC@newcommand chain.

```

114 \def\HyC@DeclareRobustCommand{%
115   \edef\HyC@robustcmd{%

```

```

116  \expandafter\noexpand
117  \csname\expandafter\expandafter\expandafter\expandafter\@gobble
118  \expandafter\string\HyC@cmd\space\endcsname
119 }%
120 \expandafter\let\expandafter\HyC@org@robustcmd\HyC@robustcmd
121 \expandafter\let\HyC@robustcmd\relax
122 \let\HyC@cmd\HyC@robustcmd
123 \@ifnextchar[\HyC@nc@opt\HyC@nc@noopt
124 }

```

\HyC@def The parameter text of \def or \edef is stored in the token register \HyC@Toks.

```

125 \def\HyC@def#1#{%
126   \HyC@Toks={#1}%
127   \HyC@nc@noopt
128 }
129 \let\HyC@edef\HyC@def

```

\HyC@doCheck This command performs the checks and prints the result.

```

130 \def\HyC@doCheck{%
131   \typeout{* Checking `\'\HyC@string\HyC@cmd':}%
132   \HyC@checkItem{cmd}%
133   \HyC@checkItem{robustcmd}%
134   \HyC@checkItem{optcmd}%
135   \HyC@checkItem{robustoptcmd}%
136   \endgroup
137 }

```

\HyC@checkItem A single check.

```

138 \def\HyC@checkItem#1{%
139   \expandafter\ifx\csname HyC@org@#1\endcsname\HyC@noValue
140   \else
141     \expandafter\expandafter\expandafter\ifx
142     \csname HyC@#1\expandafter\endcsname
143     \csname HyC@org@#1\endcsname
144     \expandafter\HyC@checkOk\csname HyC@#1\endcsname
145   \else
146     \expandafter\HyC@checkFailed
147     \csname HyC@#1\expandafter\endcsname
148     \csname HyC@org@#1\endcsname
149   \fi
150 \fi
151 }

```

\HyC@string Some shorthands.

```

152 \def\HyC@string#1{\expandafter\string#1}
153 \def\HyC@meaning#1{\expandafter\meaning#1}

```

\HyC@checkOk The result, if the check succeeds.

```

154 \def\HyC@checkOk#1{%
155   \typeout{\space\space`\'\HyC@string#1' ok.}%
156 }

```

\HyC@checkFailed The result, if the check fails.

```

157 \def\HyC@checkFailed#1#2{%
158   \typeout{\space\space`\\HyC@string#1' failed.}%
159   \typeout{\space\space* original: \meaning#2}%
160   \typeout{\space\space* expected: \HyC@meaning#1}%
161 }

162 % ****
163 </check>
164 <*package>

```

4 Package options and setup

4.1 Save catcodes

There are many packages that change the standard catcodes.

First we save the original meaning of ` and = in the token register \toks@, because we need the two characters in the macros \HyC@SetCatcodes and \HyC@RestoreCatcodes.

```

165 \begingroup
166   \@makeother\`%
167   \@makeother\=%
168   \edef\x{%
169     \edef\noexpand\x{%
170       \endgroup
171       \noexpand\toks@{%
172         \catcode 96=\noexpand\the\catcode`\noexpand\`\\relax
173         \catcode 61=\noexpand\the\catcode`\noexpand\=\\relax
174       }%
175     }%
176     \noexpand\x
177   }%
178 \x
179 \@makeother\`
180 \@makeother\=

```

\HyC@SetCatcodes

```

181 \def\HyC@SetCatcodes{%
182   \@makeother\`%
183   \@makeother\=%
184   \catcode`\$=3 %
185   \catcode`\&=4 %
186   \catcode`\^=7 %
187   \catcode`\_=8 %
188   \@makeother\|%
189   \@makeother\%%
190   \@makeother\(%%
191   \@makeother\)%%
192   \@makeother\[%
193   \@makeother\]%
194   \@makeother\/%%
195   \@makeother\!%
196   \@makeother\<%

```

```

197  \@makeother\>%
198  \@makeother\.% 
199  \@makeother\;% 
200  \@makeother\+%
201  \@makeother\-% 
202  \@makeother\%" 
203  \@makeother\%' 
204 }

\Hy@RestoreCatcodes

205 \begingroup
206  \def\x{\catcode`\noexpand#1=\the\catcode`#1\relax}%
207  \xdef\Hy@RestoreCatcodes{%
208    \the\toks@
209    \x\$%
210    \x&%
211    \x^%
212    \x_%
213    \x!%
214    \x:%
215    \x(%
216    \x)%
217    \x[%
218    \x]%
219    \x/%
220    \x!%
221    \x<%
222    \x>%
223    \x.% 
224    \x;%
225    \x+%
226    \x-%
227    \x%" 
228    \x%' 
229  }%
230 \endgroup

231 \Hy@SetCatcodes

```

change 2020-07-24: require newer pdftexcmds and remove fallback code for version older than 2010. change 2021-08-14: require expl3

```

232 \ifx\ExplSyntaxOn\undefined \RequirePackage{expl3}\fi
233 \RequirePackage{ltxcmds}[2010/11/12]
234 \RequirePackage{iftex}[2019/10/24]
235 \RequirePackage{pdftexcmds}[2018/09/10]

236 \RequirePackage{infwarerr}[2010/04/08]
237 \RequirePackage{keyval}[1997/11/10]
238 \RequirePackage{kvsetkeys}[2007/09/29]
239 \RequirePackage{kvdefinekeys}[2011/04/07]
240 \RequirePackage{pdfescape}[2007/11/11]
241 \RequirePackage{hycolor}
242 \RequirePackage{letltxmacro}[2008/06/13]
243 \RequirePackage{auxhook}[2009/12/14]
244 \RequirePackage{nameref}[2012/07/28]

```

```

245 \RequirePackage{etoolbox}
246 \def\Hy@Error{\@PackageError{hyperref}}
247 \def\Hy@Warning{\@PackageWarning{hyperref}}
248 \def\Hy@WarningNoLine{\@PackageWarningNoLine{hyperref}}
249 \def\Hy@Info{\@PackageInfo{hyperref}}
250 \def\Hy@InfoNoLine{\@PackageInfoNoLine{hyperref}}
251 \def\Hy@Message#1{%
252   \GenericWarning{%
253     (hyperref)\@spaces\@spaces\@spaces
254   }{%
255     Package hyperref Message: #1\ltx@gobble
256   }%
257 }

```

4.2 Version check

```

\Hy@VersionChecked
258 \chardef\Hy@VersionChecked=0 %

\Hy@VersionCheck
259 \def\Hy@VersionCheck#1{%
260   \begingroup
261   \ltx@ifundefined{ver@hyperref.sty}{%
262     \Hy@Error{%
263       This should not happen!\MessageBreak
264       Missing hyperref version%
265     }\@ehd
266   }{%
267     \ltx@ifundefined{ver@#1}{%
268       \Hy@Error{%
269         This should not happen!\MessageBreak
270         Missing version of `#1'%
271       }\@ehd
272     }{%
273       \def\x##1##2##3{%
274         \expandafter\expandafter\expandafter\Hy@@VersionCheck
275         \expandafter\expandafter\expandafter##2%
276         \csname ver@##3\endcsname##1##1\@nil
277       }%
278       \x{}\y{hyperref.sty}%
279       \x{}\z{#1}%
280       \ifx\y\z
281       \else
282         \edef\@a{#1}%
283         \edef\@b{\HyOpt@CustomDriver.def}%
284         \ifx\@a\@b
285           \Hy@WarningNoLine{%
286             Version mismatch (custom driver)!\MessageBreak
287             * \y: hyperref.sty\MessageBreak
288             * \z: \a
289           }%
290         \else
291           \Hy@Error{%
292             Version mismatch!\MessageBreak

```

```

293      * \y: hyperref.sty\MessageBreak
294      * \z: \a
295      }@\ehd
296      \fi
297      \fi
298      }%
299      }%
300  \endgroup
301  \chardef\Hy@VersionChecked=1 %
302 }

\Hy@VersionCheck
303 \def\Hy@VersionCheck #1#2 #3 #4@nil{%
304   \def#1{#2 #3}%
305 }

```

4.3 Checks with regular expressions

```

306 \ltx@ifundefined{pdfmatch}{%
307   \def\Hy@Match#1#2#3#4#5{%
308 }{%
309   \def\Hy@Match#1#2#3{%
310     \begingroup
311     \edef\~{\ltx@backslashchar string}\%
312     \edef.\{\ltx@backslashchar}\%
313     \edef[\{\ltx@backslashchar\}]\%
314     \edef$\{\ltx@backslashchar\$}\%
315     \edef(\{\ltx@backslashchar()\}%
316     \edef)\{\ltx@backslashchar)\}%
317     \edef|\{\ltx@backslashchar|\}%
318     \edef*\{\ltx@backslashchar*}\%
319     \edef+\{\ltx@backslashchar+\}%
320     \edef?\{\ltx@backslashchar?\}%
321     \edef{\{\ltx@backslashchar\ltx@leftbracechar}\%
322     \edef}\{\ltx@rightbracechar}\%
323     \edef\\{\ltx@backslashchar\ltx@backslashchar}\%
324     \let\ \ltx@space
325     \ifcase\pdfmatch#2{#3}{#1} %
326       \endgroup
327       \expandafter\ltx@secondoftwo
328     \or
329       \endgroup
330       \expandafter\ltx@firstoftwo
331     \else
332       \Hy@Warning{%
333         Internal error: Wrong pattern!\MessageBreak
334         --> #3 <--\MessageBreak
335         Pattern check ignored%
336       }%
337       \endgroup
338       \expandafter\ltx@firstoftwo
339     \fi
340   }%
341 }

```

4.4 Compatibility with format dumps

\AfterBeginDocument For use with pre-compiled formats, created using the `ldump` package, there needs to be 2 hooks for adding material delayed until `\begin{document}`. These are called `\AfterBeginDocument` and `\AtBeginDocument`. If `lDump` is not loaded, then a single hook suffices for normal L^AT_EX processing.

The default definition of `\AfterBeginDocument` cannot be done by `\let` because of problems with `xypic`.

```
342 \@ifundefined{AfterBeginDocument}{%
343   \def\AfterBeginDocument{\AtBeginDocument}%
344 }{}%
```

\Hy@AtBeginDocument For the case that package ‘hyperref’ is loaded using `\AtBeginDocument`, we have to wrap the calls of `\AtBeginDocument`/`\AfterBeginDocument` in `\AtEndOfPackage`. However, packages must be loaded in `\AtEndOfPackage` *before* package ‘kvoptions’ has to perform its option cleanup. Therefore we use a hook.

```
345 \def\Hy@AtBeginDocument{%
346   \ltx@LocalAppendToMacro\Hy@AtBeginDocumentHook
347 }
```

\Hy@AtEndOfPackage

```
348 \def\Hy@AtEndOfPackage{%
349   \ltx@LocalAppendToMacro\Hy@AtEndOfPackageHook
350 }
```

\Hy@AtBeginDocumentHook

```
351 \let\Hy@AtBeginDocumentHook\ltx@empty
```

\Hy@AtEndOfPackageHook

```
352 \let\Hy@AtEndOfPackageHook\ltx@empty
```

Install the hook, before package ‘kvoptions’ is loaded.

```
353 \AtEndOfPackage{%
354   \Hy@AtEndOfPackageHook
355   \let\Hy@AtEndOfPackageHook\@undefined
356   \AfterBeginDocument{%
357     \Hy@AtBeginDocumentHook{}%
358     \let\Hy@AtBeginDocumentHook\@undefined
359   }%
360 }
```

Package `kvoptions` is used for processing options that are given as key value pairs. The package provides `\ProcessKeyvalOptions`, formerly known as `\ProcessOptionsWithKV`.

```
361 \RequirePackage{kvoptions}[2009/07/21]
```

4.5 Switches

```
362 \newif\ifHy@stoppedearly
363 \newif\ifHy@typexml
364 \newif\ifHy@activeanchor
365 \newif\ifHy@backref
366 \newif\ifHy@bookmarks
```

```

367 \newif\ifHy@bookmarksnumbered
368 \newif\ifHy@bookmarksopen
369 \newif\ifHy@breaklinks
370 \newif\ifHy@pdfcenterwindow
371 \newif\ifHy@CJKbookmarks
372 \newif\ifHy@colorlinks
373 \newif\ifHy@destlabel
374 \newif\ifHy@draft
375 \let\Hy@finaltrue\Hy@draftfalse
376 \let\Hy@finalfalse\Hy@drafttrue
377 \newif\ifHy@pdfescapeform
378 \newif\ifHy@hyperfigures
379 \newif\ifHy@pdffitwindow
380 \newif\ifHy@frenchlinks
381 \newif\ifHy@hyperfootnotes
382 \newif\ifHy@hyperindex
383 \newif\ifHy@hypertexnames
384 \newif\ifHy@implicit
385 \newif\ifHy@linktocpage
386 \newif\ifHy@localanchorname
387 \newif\ifHy@pdfmenubar
388 \newif\ifHy@naturalnames
389 \newif\ifHy@nesting
390 \newif\ifHy@pdfnewwindowset
391 \newif\ifHy@pdfnewwindow
392 \newif\ifHy@ocgcolorlinks
393 \newif\ifHy@pageanchor
394 \newif\ifHy@pdfpagelabels
395 \newif\ifHy@pdfstring
396 \newif\ifHy@plainpages
397 \newif\ifHy@psize
398 \newif\ifHy@raiselinks
399 \newif\ifHy@seminarslides
400 \newif\ifHy@setpagesize
401 \newif\ifHy@texht
402 \newif\ifHy@psdextra
403 \newif\ifHy@pdftoolbar
404 \newif\ifHy@unicode
405 \newif\ifHy@pdfusetitle
406 \newif\ifHy@verbose
407 \let\Hy@debugtrue\Hy@verbosetrue
408 \let\Hy@debugfalse\Hy@verbosefalse
409 \newif\ifHy@pdfwindowui
410 \newif\ifHy@pdfdisplaydoctitle
411 \newif\ifHy@pdfa

```

Defaults for the switches are now set.

```

412 \Hy@backreffeal
413 \Hy@bookmarksnumberedfalse
414 \Hy@bookmarksopenfalse
415 \Hy@bookmarkstrue
416 \Hy@breaklinksfalse
417 \Hy@pdfcenterwindowfalse
418 \Hy@CJKbookmarksfalse
419 \Hy@destlabelfalse

```

```

420 \Hy@pdfescapeformfalse
421 \Hy@hyperfiguresfalse
422 \Hy@pdffitwindowfalse
423 \Hy@hyperfootnotestrue
424 \Hy@hyperindextrue
425 \Hy@hypertexnamestrue
426 \Hy@implicittrue
427 \Hy@linktocpagefalse
428 \Hy@localanchornamefalse
429 \Hy@pdfmenubartrue
430 \Hy@naturalnamesfalse
431 \Hy@nestingfalse
432 \Hy@pdfnewwindowsetfalse
433 \Hy@pdfnewwindowfalse
434 \Hy@pageanchortrue
435 \Hy@pdfpagelabeltrue
436 \Hy@pdfstringfalse
437 \Hy@plainpagesfalse
438 \Hy@raiselinksfalse
439 \Hy@setpagesizetrue
440 \Hy@texhtfalse
441 \Hy@psdextrafalse
442 \Hy@pdftoolbartrue
443 \Hy@unicodetrue
444 \ifx\kanjiskip\@undefined
445 \else
446   \ifx\forcecjktoken\@undefined
447     \Hy@unicodedfalse
448   \fi
449 \fi
450 \Hy@pdfusetitlefalse
451 \Hy@verbosefalse
452 \Hy@pdfwindowuitrue
453 \Hy@pdfdisplaydoctitlefalse
454 \Hy@pdfafalse

```

5 Common help macros

```

\Hy@StepCount
455 \def\Hy@StepCount#1{\advance#1 by 1 }%

\Hy@GlobalStepCount
456 \def\Hy@GlobalStepCount#1{\global\advance#1 by 1 }%

457 \newdimen\@linkdim
458 \let\Hy@driver\ltx@empty
459 \let\MaybeStopEarly\relax
460 \newcount\Hy@linkcounter
461 \newcount\Hy@pagecounter
462 \Hy@linkcounter0
463 \Hy@pagecounter0

```

5.1 Macros for recursions

```

464 \let\Hy@ReturnEnd\empty
465 \long\def\Hy@ReturnAfterFiFiEnd#1\f\#2\Hy@ReturnEnd{\f\f\#1}
466 \long\def\Hy@ReturnAfterElseFiFiEnd#1\else#2\Hy@ReturnEnd{\f\f\#1}

```

5.2 Babel's protection of shorthand characters

`\Hy@safe@activestrue` Babel's switch setting commands cannot be used directly, because they can be undefined if babel is not loaded.

```

467 \def\Hy@safe@activestrue{\csname @safe@activestrue\endcsname}
468 \def\Hy@safe@activesfalse{\csname @safe@activesfalse\endcsname}

```

5.3 Coordinate transformations

At some places numbers in pdf units are expected (eg: FitBH, ...). The following macros perform the transformation from TeX units (pt) to PDF units (bp).

`\hypercalcbp` The user macro `\hypercalcbp` can be used, for example, inside option values:

```
pdfstartview={FitBH \hypercalcbp{\paperheight-\topmargin-1in}}
```

- It cannot be used inside `\usepackage`, because LaTeX expands the options before package hyperref is loaded and `\hypercalcbp` is defined.
- With the now required e-TeX extensions an expandable implementation is very easy; `\hypercalcbp` can be used everywhere and is expanded at use.

Example (TeX):

```

\usepackage{hyperref}
\hypersetup{
  pdfstartview={FitBH \hypercalcbp{\paperheight-\topmargin-1in
    -\headheight-\headsep}}
}

\hypercalcbp
469 \def\hypercalcbp#1{%
470   \strip@pt\dimexpr 0.99626401\dimexpr#1\relax\relax
471 }%
472 \def\hypercalcbpdef{\def}%

```

6 Dealing with PDF strings

The PDF string stuff done by Heiko Oberdiek.

Naming convention: All internal commands that are only needed by `\pdfstringdef` are prefixed with `\HyPsd@`.

6.1 Description of PDF strings

The PDF specification defines several places to hold text strings (bookmark names, document information, text annotations, etc.). The PDF strings have following properties:

- They are surrounded by parentheses. The hexadecimal form is not supported.

- Like PostScript language strings they use the same escaping mechanism:

\\"\\	the backslash itself
\\", \\(unbalanced parentheses
\n, \r, \t, \b, \f	special white space escape sequences
\ddd	octal character code <i>ddd</i>
- Strings are stored either in PDFDocEncoding, which is a superset of ISO-Latin1 and is compatible with Unicode with character codes below 256, or in Unicode.

6.2 Definition of \pdfstringdef

The central macro for dealing with PDF strings is `\pdfstringdef`. It defines a command `#1` to be the result of the conversion from the string in `#2` to a legal PDFDocEncoded string. Currently the definition is global, but this can be changed in the future.

Important: In `\TeX`'s view PDF strings are written to a file and are expanded only in its mouth. Stomach commands that cannot be expanded further aren't executed, they are written verbatim. But the PDF reader that reads such a string isn't a `\TeX` interpreter!

The macro `\pdfstringdef` consists of three main parts:

1. Preprocessing. Here the expansion is prepared. The encoding is set and many commands are redefined, so that they work appropriate.
2. Expansion. The `\TeX` string is expanded the first time to get a PDF string.
3. Postprocessing. The result of the expansion is checked and converted to the final form.

`\MakeUppercase` and `\MakeLowercase` do not work by expansion in legacy code but if the `expl3` code is available we can handle them. If a current babel or polyglossia is used we can also make use of the language.

```
uppercaseUnsupportedInPdfStrings
uppercaseUnsupportedInPdfStrings
473 \providecommand*\BCPdata[1]{}%
474 \ExplSyntaxOn
475 \@ifundefined{text_uppercase:n}{}%
476 {
477   \def\MakeUppercaseUnsupportedInPdfStrings#1
478     {\use:c
479       {\exp_args:N
480         \text_uppercase:nn{\BCPdata {casing }}{#1}}
481     }
482   }
483 \def\MakeLowercaseUnsupportedInPdfStrings#1
484   {\use:c
485     {\exp_args:N
486       \text_lowercase:nn{\BCPdata {casing }}{#1}}
487   }
488 }
489 }
490 \ExplSyntaxOff
```

```
\pdfstringdef \pdfstringdef works on the tokens in #2 and converts them to a PDF string as far as possible:
```

- The result should obey the rules of the PDF specification for strings.
- The string can safely processed by \TeX , because the tokens have only catcodes 10 until 12.

The result is stored in the command token given in #1.

```
491 \def\pdfstringdef#1#2{%
```

Many redefinitions are needed, so all the work is done in a group.

```
492 \begingroup
```

6.2.1 Preprocessing

Octal escape sequences. To avoid problems with eight bit or non printable characters, the octal escape notation is supported. So most glyphs in the encoding definitions for PD1 and PU produce these octal escape sequences. All three octal digits have to be used:

- Wrong results are avoided, if digits follow that are not part of the octal sequence.
- Macros rely on the fact that the octal sequences always consist of three digits (vtex driver, Unicode support).

The escape sequences start with a backslash. By \backslash string it will be printed. Therefore it is ensured that the \TeX escape character indeed prints as a normal backslash. Eventually this line can be removed, because this is standard \LaTeX behaviour.

```
493 \escapechar`\\%
```

From the view of \TeX a octal sequence consists of the command tokens $\backslash 0$ until $\backslash 3$ and two digits. For saving tokens $\backslash 0$, $\backslash 1$, $\backslash 2$, and $\backslash 3$ are directly used without a preceding \backslash string in the glyph definitions. This is done here locally by defining the $\backslash 0$ until $\backslash 3$ commands. So the user can use octal escape sequences directly, the disadvantage is that a previous definition of this short commands does not apply.

```
494 \edef\0{\string\0}%
495 \edef\1{\string\1}%
496 \edef\2{\string\2}%
497 \edef\3{\string\3}%
```

Setting font encoding. The unicode encoding uses $\backslash 8$ and $\backslash 9$ as marker for the higher byte. $\backslash 8$ is an abbreviation for the higher bytes 0 until 7 that can be expressed by one digit. $\backslash 8$ will be converted to $\backslash 00$. However $\backslash 9$ only marks the next three digits as higher byte and will be removed later.

The encoding is set by \backslash enc@update for optimizing reasons.

```
498 \ifHy@unicode
499 \edef\8{\string\8}%
500 \edef\9{\string\9}%
501 \fontencoding{PU}%
```

```

502   \HyPsd@UTFviii
503   \def\ifpdfstringunicode##1##2{##1}%
504 \else
505   \fontencoding{PD1}%
506   \def\ifpdfstringunicode##1##2{##2}%
507 \fi
508 \let\utf@viii@undeferr\HyPsd@utf@viii@undeferr
509 \enc@update

```

Internal encoding commands. `\pdfstringdef` interpretes text strings which are not allowed to contain mathematical stuff. The text glyph commands will produce a warning, if called in math mode. But this warning disturbs while expanding. Therefore we check for math mode here, before `\@inmathwarn` will be disabled (see below).

```
510  \@inmathwarn\pdfstringdef
```

If a glyph is used, that isn't in the PD1/PU encoding there will be an infinite error loop, because the NFSS encoding stuff have to be expanded unprotected (`\edef`), so that the assignments of `\@changed@cmd` don't take place. To patch this behaviour I only found `\@inmathwarn` as a usable hook. While an `\edef` a warning message by `\@inmathwarn` or `\TextSymbolUnavailable` cannot be give out, so `\@inmathwarn` should be disabled. And with the help of it the assignments in `\@changed@cmd` can easily be caught (see below).

```
511  \let\@inmathwarn\HyPsd@inmathwarn
```

Unknown composite characters are built with `\add@accent`, so it is redefined to provide a warning.

```
512  \let\add@accent\HyPsd@add@accent
```

Commands that don't use NFSS directly. There are several commands that prints characters in the printable ASCII area that don't obey the NFSS, so they have to be redefined here. UF 29.09.2017: added a mapping for `\noboundary`, see issue #37 <https://github.com/latex3/hyperref/issues/37> No test for PU, if some definition for PD1 is added it will work too.

```

513  \let\{\textbraceleft
514  \let\}\textbraceright
515  \let\\textbackslash
516  \let#\textnumbersign
517  \let$\textdollar
518  \let%\textpercent
519  \let\&\textampersand
520 %  \let\~\textasciitilde
521  \let\_textunderscore
522  \let\P\textparagraph
523  \let\ldots\textellipsis
524  \let\ldots\textellipsis
525  \ltx@ifundefined{textEncodingNoboundary}%
526    {}{\let\noboundary{textEncodingNoboundary}}%

```

Newline `\newline` or `\%` do not work in bookmarks, in text annotations they should expand to `\r`. In pdf strings `\%` stands for a backslash. Therefore the

commands are disabled now. The user can redefine them for a result what he want:

```
backslash: \pdfstringdefDisableCommands{\let\\textbackslash}
new line: \pdfstringdefDisableCommands{\let\\textCR}
disabled: \pdfstringdefDisableCommands{\let\\empty}
```

At any case, however, the optional argument or the star cannot be scanned in a 100% sure manner.

```
527   \def\f\pdfstringdefWarn\\%
528   \def\newline\f\pdfstringdefWarn\newline\\%
```

Logos. Because the box shifting used in the TeX logo does not work while writing to a file, the standard TeX logos are redefined. We use the direct PU code to avoid problems if \textepsilon is not defined.

```
529   \def\TeX{\TeX}%
530   \def\LaTeX{\LaTeX}%
531   \def\LaTeXef{%
532     \LaTeX2%
533     \ifHy@unicode\83\265\else e\fi
534   }%
535   \def\eTeX{%
536     \ifHy@unicode\83\265\else e\fi
537     -\TeX%
538   }%
539   \def\SliTeX{\SliTeX}%
540   \def\MF{Metafont}%
541   \def\MP{Metapost}%
```

Standard font commands. Because font changes do not work, the standard font switching commands are disabled.

```
542   \let\fontencoding@gobble
543   \let\fontfamily@gobble
544   \let\fontseries@gobble
545   \let\fontshape@gobble
546   \let\fontsize@gobbletwo
547   \let\selectfont@empty
548   \let\usefont@gobblefour
549   \let\emph@firstofone
550   \let\textnormal@firstofone
551   \let\textrm@firstofone
552   \let\textsf@firstofone
553   \let\texttt@firstofone
554   \let\textbf@firstofone
555   \let\textmd@firstofone
556   \let\textit@firstofone
557   \let\textsc@firstofone
558   \let\textsl@firstofone
559   \let\textup@firstofone
560   \let\normalfont@empty
561   \let\rmfamily@empty
```

```

562  \let\sffamily\@empty
563  \let\ttfamily\@empty
564  \let\bfseries\@empty
565  \let\mdseries\@empty
566  \let\itshape\@empty
567  \let\scshape\@empty
568  \let\slshape\@empty
569  \let\upshape\@empty
570  \let\em\@empty
571  \let\rm\@empty
572  \let\Huge\@empty
573  \let\Large\@empty
574  \let\footnotesize\@empty
575  \let\huge\@empty
576  \let\large\@empty
577  \let\normalsize\@empty
578  \let\scriptsize\@empty
579  \let\small\@empty
580  \let\tiny\@empty
582  \let\mathversion\@gobble
583  \let\phantom\@gobble
584  \let\vphantom\@gobble
585  \let\hphantom\@gobble

```

Package pifont.

```

586  \let\ding\HyPsd@ding
587  \let\Cube\HyPsd@DieFace
588 %* \HyPsd@DieFace -> \epsdice (epsdice)
589 %* \HyPsd@DieFace -> \fcdice (hhcount)

```

Environments.

```

590  \def\begin##1{\csname##1\endcsname}%
591  \def\end##1{\csname end##1\endcsname}%

```

Package color.

```

592  \def\textcolor##1##2{\@secondoftwo}%

```

Upper- and lowercase.

```

593  \def\MakeUppercase{\MakeUppercaseUnsupportedInPdfStrings}%
594  \def\MakeLowercase{\MakeLowercaseUnsupportedInPdfStrings}%

```

Support of math commands without prefix `text`. This is controlled by option “psdextra” and only activated with Unicode PDF strings.

```

595  \ifHy@psdextra
596    \ifHy@unicode
597      \csname psdmapshortnames\endcsname
598      \csname psdaliasnames\endcsname
599    \fi
600  \fi

```

Package babel. Wherever “naturalnames” is used, disable \textlatin (from Babel 3.6k). Thanks to Felix Neubauer (Email: Felix.Neubauer@gmx.net).

```
601  \let\foreignlanguage\@secondoftwo
602  \let\textlatin\@firstofone
603  \ltx@ifundefined{language@group}{}{%
604    \let\bb@info\@gobble
605    \csname HyPsd@babel@\language@group\endcsname
606  }%
607  \let\@safe@activestrue\relax
608  \let\@safe@activesfalse\relax

Disable \cyr, used in russianb.ldf.
609  \let\cyr\relax
```

Package german.

```
610  \let\glqq\textglqq
611  \let\grqq\textgrqq
612  \let\glq\textglq
613  \let\grq\textgrq
614  \let\fllqq\textfllqq
615  \let\frqq\textfrqq
616  \let\fllq\textfllq
617  \let\frq\textfrq
```

Package french. The support is deferred, because it needs \GenericError to be disabled (see below).

Package FrenchPro. This package uses:

```
\if@mid@expandable{not fully expandable code}{fully expandable
code}
618  \let\if@mid@expandable\@firstoftwo
```

AMS classes.

```
619  \HyPsd@AMSclassfix
```

Redefinition of \hspace \hspace don't work in bookmarks, the following fix tries to set a space if the argument is a positive length.

```
620  \let\hspace\HyPsd@hspace
```

Commands of referencing and indexing systems. Some L^AT_EX commands that are legal in \section commands have to be disabled here.

```
621  \let\label\@gobble
622  \let\index\@gobble
623  \let\glossary\@gobble
624  \let\href\HyPsd@href
625  \let\@mkboth\@gobbletwo
```

The `\ref` and `\pageref` is much more complicate because of their star form.

```
626 \let\ref\HyPsd@ref
627 \let\pageref\HyPsd@pageref
628 \let\nameref\HyPsd@nameref
629 \let\autoref\HyPsd@autoref
```

Miscellaneous commands.

```
630 \let\leavevmode\@empty
631 \let\mbox\@empty
\halign causes error messages because of the template character #.
632 \def\halign{\pdfstringdefWarn\halign\@gobble}%
633 \let\ignorespaces\HyPsd@ignorespaces
634 \let\Hy@SectionAnchorHref\@gobble
635 \let\ensuremath\@firstofone
```

Patch for cjk bookmarks.

```
636 \HyPsd@CJKhook
```

User hook. The switch `\Hy@pdfstring` is turned on. So user commands can detect that they are processed not to be typesetted within TeX's stomach, but to be expanded by the mouth to give a PDF string. At this place before interpreting the string in #2 additional redefinitions can be added by the hook `\pdfstringdefPreHook`.

The position in the middle of the redefinitions is a compromise: The user should be able to provide his own (perhaps better) redefinitions, but some commands should have their original meaning, because they can be used in the hook (`\bgroup`, or `\@protected@testopt`, and `\@ifnextchar` for `\renewcommand`).

```
637 \Hy@pdfstringtrue
638 \pdfstringdefPreHook
```

Spaces. For checking the token of the string, spaces must be masked, because they cannot be caught by undelimited arguments.

```
639 \HyPsd@LetUnexpandableSpace\space
640 \HyPsd@LetUnexpandableSpace\ %
641 \HyPsd@LetUnexpandableSpace~%
642 \HyPsd@LetUnexpandableSpace\nobreakspace
```

Package xspace.

```
643 \ltx@IfUndefined{@xspace}{%
644   \let\xspace\HyPsd@ITALCORR
645 }{%
646   \let\xspace\HyPsd@XSPACE
647 }%
648 \let\\HyPsd@ITALCORR
649 \let\bgroup\%
650 \let\egroup\%
```

Redefinitions of miscellaneous commands. Hyphenation does not make sense.

```
651 \let\discretionary\@gobbletwo
\@ifstar is defined in LATEX as follows:
```

\def\@ifstar#1{\@ifnextchar *{\@firstoftwo{#1}}}

\@ifnextchar doesn't work, because it uses stomach commands like \let and \futurelet. But it doesn't break. Whereas \@firstoftwo{#1} gives an error message because \@firstoftwo misses its second argument.

A mimicry of \@ifnextchar only with expandable commands would be very extensive and the result would be only an approximation. So here a cheaper solution follows in order to get rid of the error message at least:

```
652 \def\@ifnextchar{\HyPsd@\ifnextchar\@ifnextchar}%
653 \def\kernel\@ifnextchar{\HyPsd@\ifnextchar\kernel\@ifnextchar}%
654 \def\new\@ifnextchar{\HyPsd@\ifnextchar\new\@ifnextchar}%
655 \let\@protected@testopt\HyPsd@\protected@testopt
```

Support for package ‘xargs’:

```
656 \let\@protected@testopt\xargs\HyPsd@\protected@testopt
```

6.2.2 Expansion

There are several possibilities to expand tokens within LATEX:

\protected@edef: The weakest form isn't usable, because it does not expand the font encoding commands. They are made robust and protect themselves.

\csname: First the string is expanded within a \csname and \endcsname. Then the command name is converted to characters with catcode 12 by \string and the first escape character removed by \@gobble. This method has the great *advantage* that stomach tokens that aren't allowed in PDF strings are detected by TeX and reported as errors in order to force the user to write correct things. So he get no wrong results by forgetting the proofreading of his text. But the *disadvantage* is that old wrong code cannot processed without errors. Mainly the error message is very cryptic and for the normal user hard to understand. TeX provides no way to catch the error caused by \csname or allows to support the user with a descriptive error message. Therefore the experienced user had to enable this behaviour by an option `exactdef` in previous versions less or equal 6.50.

\edef This version uses this standard form for expansion. It is stronger than LATEX's \protected@edef. So the font encoding mechanism works and the glyph commands are converted to the correct tokens for PDF strings whith the definitions of the PD1 encoding. Because the protecting mechanism of LATEX doesn't work within an \edef, there are situations thinkable where code can break. For example, assignments and definitions aren't performed and so undefined command errors or argument parsing errors can occur. But this is only a compatibility problem with old texts. Now there are possibilities to write code that gives correct PDF strings (see \texorpdfstring). In the most cases unexpandable commands and tokens (math shift, grouping characters) remains. They don't cause an error like with \csname. However a PDF reader isn't TeX, so these tokens are viewed verbatim. So this

version detects them now, and removes them with an descriptive warning for the user. As additional features xspace support is possible and grouping characters can be used without problems, because they are removed silently.

Generic messages. While expanding via `\xdef` the `\Generic...` messages don't work and causes problems (error messages, invalid `.out` file). So they are disabled while expanding and removed silently, because a user warning would be too expensive (memory and runtime, `\pdfstringdef` is slow enough).

```
657 \begingroup
658   \let\GenericError\@gobblefour
659   \let\GenericWarning\@gobbletwo
660   \let\GenericInfo\@gobbletwo
```

Package french. This fix only works, if `\GenericError` is disabled.

```
661 \ifx\nofrenchguillemets\@undefined
662 \else
663   \nofrenchguillemets
664 \fi
```

Definition commands and expansion. Redefining the defining commands (see sec. 6.5.12). The original meaning of `\xdef` is saved in `\Hy@temp`.

```
665 \let\Hy@temp\xdef
666 \let\def\HyPsd@DefCommand
667 \let\gdef\HyPsd@DefCommand
668 \let\edef\HyPsd@DefCommand
669 \let\xdef\HyPsd@DefCommand
670 \let\futurelet\HyPsd@LetCommand
671 \let\let\HyPsd@LetCommand
672 \Hy@temp#1{#2}%
673 \endgroup
```

6.2.3 Postprocessing

If the string is empty time can be saved by omitting the postprocessing process.

```
674 \ifx#1\@empty
675 \else
```

Protecting spaces and removing grouping characters. In order to check the tokens we must separate them. This will be done with `TeX`'s argument parsing. With this method we must the following item takes into account, that makes makes things a litte more complicate:

- `TeX` does not accept a space as an undelimited argument, it cancels space tokens while looking for an undelimited argument. Therefore we must protect the spaces now.
- An argument can be a single token or a group of many tokens. And within curly braces tokens aren't find by `TeX`'s argument scanning process. Third curly braces as grouping characters cannot be expanded further, so they don't vanish by the string expansion above. So these characters with catcode

1 and 2 are removed in the following and replaced by an marker for the xspace support.

- TeX silently removes the outmost pair of braces of an argument. To prevent this on unwanted places, in the following the character | is appended to the string to make an outer brace to an inner one.

First the top level spaces are protected by replacing. Then the string is scanned to detect token groups. Each token group will now be space protected and again scanned for another token groups.

```
676  \HyPsd@ProtectSpaces#1%
677  \let\HyPsd@String\@empty
678  \expandafter\HyPsd@RemoveBraces\expandafter{#1|}%
679  \global\let#1\HyPsd@String
```

Check tokens. After removing the spaces and the grouping characters the string now should only consists of the following tokens/catcodes:

- 0 command names with start with an escape character.
- 3 math shift
- 4 alignment tabs
- 6 parameter, but this is unlikely.
- 7 superscript
- 8 subscript
- 11 letter
- 12 other
- 13 commands that are active characters.

After \HyPsd@CheckCatcodes the command \HyPsd@RemoveMask is reused to remove the group protection character |. This character is needed to ensure that the string at least consists of one token if \HyPsd@CheckCatcodes is called.

Because of internal local assignments and tabulars group braces are used.

```
680  \let\HyPsd@SPACEOPTI\relax
681  {%
682  \let\HyPsd@String\@empty
683  \expandafter\HyPsd@CheckCatcodes#1\HyPsd@End
684  \global\let#1\HyPsd@String
685  }%
686  \expandafter\HyPsd@RemoveMask\expandafter
687  |\expandafter\@empty#1\HyPsd@End#1%
```

\HyPsd@CheckCatcodes should no have removed the tokens with catcode 3, 4, 7, and 8. Because a parameter token (6) would cause to many errors before, there should now be only tokens with catcodes 11 or 12. So I think there is no need for a safety step like:

```
\xdef#1{\expandafter\strip@prefix\meaning#1}%
```

Looking for wrong glyphs. The case that glyphs aren't defined in the PD1 encoding is caught above in such a way, that the glyph name and a marker is inserted into the string. Now we can safely scan the string for this marker and provide a descriptive warning.

```
688  \expandafter
689  \HyPsd@Subst\expandafter{\HyPsd@GLYPHERR}{\relax}#1%
```

```

690 \let\HyPsd@String\@empty
691 \expandafter\HyPsd@GlyphProcess#1\relax\@empty
692 \global\let#1\HyPsd@String

```

Backslash. The double backslash disturbs parsing octal sequences, for example in an string like abc\\051 the sequence \\051 is detected although the second \\ belongs to the first backslash.

```
693 \HyPsd@StringSubst{\{\textbackslash}\#\{1%
```

Spaces. All spaces have already the form \\040. The last postprocessing step will be an optimizing of the spaces, so we already introduce already the necessary command \\HyPsd@SPACEOPTI. But first it is defined to be \\relax in order to prevent a too early expansion by an \\edef. Secondly a \\relax serves as a marker for a token that is detected by \\xspace.

The code of frenchb.lfd can produce an additional space before \\guillemetright, because \\lastskip and \\unskip do not work. Therefore it is removed here.

```

694 \ifHy@unicode
695   \expandafter\HyPsd@StringSubst\csname 80\040\endcsname
696   \HyPsd@SPACEOPTI#1%
697   \edef\Hy@temp@a{\HyPsd@SPACEOPTI\HyPsd@SPACEOPTI\80\273}%
698   \expandafter\HyPsd@Subst\expandafter{\Hy@temp@a}%
699   {\HyPsd@SPACEOPTI\80\273}#1%
700 \else
701   \HyPsd@StringSubst{\040}\HyPsd@SPACEOPTI#1%
702   \expandafter\HyPsd@Subst\expandafter{%
703     \expandafter\HyPsd@SPACEOPTI\expandafter\HyPsd@SPACEOPTI
704     \string\273}{\HyPsd@SPACEOPTI\273}#1%
705 \fi

```

Right parenthesis. Also \\xspace detects a right parenthesis. For the \\xspace support and the following parenthesis check the different parenthesis notations), \\), and \\051 are converted to one type \\) and before \\HyPsd@empty with the meaning of \\relax is introduced for \\xspace. By redefining to \\@empty \\HyPsd@empty can easily removed later.

```

706 \ifHy@unicode
707   \HyPsd@StringSubst{\}{\80\051}#1%
708   \HyPsd@Subst{\80\051}#1%
709   \let\HyPsd@empty\relax
710   \expandafter\HyPsd@StringSubst\csname 80\051\endcsname
711   {\HyPsd@empty\80\051}#1%
712 \else
713   \HyPsd@StringSubst{\}{\051}#1%
714   \HyPsd@Subst{\051}#1%
715   \let\HyPsd@empty\relax
716   \HyPsd@StringSubst{\051}{\HyPsd@empty\string\})}#1%
717 \fi

```

Support for package xspace. \\xspace looks for the next token and decides if it expands to a space or not. Following tokens prevent its transformation to a space: Beginning and end of group, handled above by replacing by an italic correction, several punctuation marks, a closing parentheses, and several spaces.

Without package `xspace` there are tokens with catcode 11 and 12, `\HyPsd@empty` and `\HyPsd@SPACEOPTI`. With package `xspace` marker for the italic correction `\/` and `\xspace` come with. In the package `xspace` case the two markers are replaced by commands and an `\edef` performs the `\xspace` processing.

In the opposite of the original `\xspace \HyPsd@xspace` uses an argument instead of a `\futurelet`, so we have to provide such an argument, if `\HyPsd@xspace` comes last. Because `\HyPsd@Subst` with several equal tokens (--) needs a safe last token, in both cases the string gets an additional `\HyPsd@empty`.

```

718      \expandafter\HyPsd@Subst\expandafter{\}/\HyPsd@empty#1%
719      \ltx@IfUndefined{@xspace}{%
720      }%
721      \let\HyPsd@xspace\relax
722      \expandafter\HyPsd@Subst\expandafter
723      {\HyPsd@XSPACE}\HyPsd@xspace#1%
724      \let\HyPsd@xspace\HyPsd@doxspace
725      }%
726      \xdef#1{#1\HyPsd@empty}%

```

Ligatures. `TeX` forms ligatures in its stomach, but the PDF strings are treated only by `TeX`'s mouth. The PDFDocEncoding contains some ligatures, but the current version 3 of the AcrobatReader lacks the `fi` and `fl` glyphs, and the Linux version lacks the `emdash` and `endash` glyphs. So the necessary code is provided here, but currently disabled, hoping that version 4 of the AcrobatReader is better. To break the ligatures the user can use an empty group, because it leads to an insertion of an `\HyPsd@empty`. If this ligature code will be enabled some day, then the italic correction should also break the ligatures. Currently this occurs only, if package `xspace` is loaded.

Since newer AcrobatReader versions now show the en- and emdash in a correct way (AR7/Linux, AR8/Linux), the substitution code for them is enabled starting with version 6.78l.

```

727      \HyPsd@Subst{---}\textemdash#1%
728      \HyPsd@Subst{--}\textendash#1%
729 %      \HyPsd@Subst{fi}\textfi#1%
730 %      \HyPsd@Subst{fl}\textfl#1%
731      \HyPsd@Subst{!`}\textexclamdown#1%
732      \HyPsd@Subst{?`}\textquestiondown#1%

```

With the next `\edef` we get rid of the token `\HyPsd@empty`.

```
733      \let\HyPsd@empty\empty
```

Left parentheses. Left parentheses are now converted to safe forms to avoid problems with unmatched ones (`\(`` with PDFDocEncoding, the octal sequence with Unicode).

An optimization is possible. Matched parentheses can be replaced by a `O` pair. But this code is removed to save `TeX` memory and time.

```

734      \ifHy@unicode
735      \HyPsd@StringSubst\(\textparenleft#1%
736      \HyPsd@Subst\(\textparenleft#1%
737      \else
738      \HyPsd@StringSubst\({\050}\#1%
739      \HyPsd@Subst\({\050}\#1%

```

```

740      \HyPsd@StringSubst{\050}{\string\()#1%
741      \fi

```

Optimizing spaces. Spaces are often used, but they have a very long form \040. They are converted back to real spaces, but not all, so that no space follows after another. In the bookmark case several spaces are written to the .out file, but if the entries are read back, several spaces are merged to a single one.

With Unicode the spaces are replaced by their octal sequences.

```

742      \ifHy@unicode
743          \edef\HyPsd@SPACEOPTI{\80\040}%
744      \else
745          \let\HyPsd@SPACEOPTI\HyPsd@spaceopti
746      \fi
747      \xdef#1{\#1\@empty}%
748  \fi

```

Converting to Unicode. At last the eight bit letters have to be converted to Unicode, the masks \8 and \9 are removed and the Unicode marker is added.

```

749  \endgroup
750  \begingroup
751  \ifHy@unicode
752      \HyPsd@ConvertToUnicode#1%

```

Try conversion back to PDFDocEncoding.

```

753  \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
754      \ltx@ifUndefined{StringEncodingConvertTest}{%
755      }{%
756          \EdefUnescapeString\HyPsd@temp#1%
757          \iftutex
758              \let\HyPsd@UnescapedString\HyPsd@temp
759              \StringEncodingConvertTest\HyPsd@temp\HyPsd@temp
760                  \utf16be\{ascii-print}\{%
761          \EdefEscapeString\HyPsd@temp\HyPsd@temp
762          \global\let#1\HyPsd@temp
763          \HyPsd@EscapeTeX#1%
764          \Hy@unicodedefalse
765      }{%
766          \HyPsd@EscapeTeX#1%
767      }%
768  \else
769      \StringEncodingConvertTest\HyPsd@temp\HyPsd@temp
770          \utf16be\{pdfdoc}\{%
771          \EdefEscapeString\HyPsd@temp\HyPsd@temp
772          \global\let#1\HyPsd@temp
773          \HyPsd@EscapeTeX#1%
774          \Hy@unicodedefalse
775      }{%
776      \fi
777  }%
778  \fi
779  \fi

```

User hook. The hook `\pdfstringdefPostHook` can be used for the purpose to postprocess the string further.

```

780   \pdfstringdefPostHook#1%
781   \endgroup
782 }

\Hy@pdfstringdef
783 \def\Hy@pdfstringdef#1#2{%
784   \pdfstringdef\Hy@gtemp{#2}%
785   \let#1\Hy@gtemp
786 }

```

6.3 Encodings

6.3.1 XeTeX

change 2020-05-13: the special code for XeTeX big chars has been removed as no longer needed.

6.3.2 Workaround for package linguex

```

787 \@ifpackageloaded{linguex}{%
788   \let\HyLinguex@OrgB\b
789   \let\HyLinguex@OrgC\c
790   \let\HyLinguex@OrgD\d
791   \def\HyLinguex@Restore{%
792     \let\b\HyLinguex@OrgB
793     \let\c\HyLinguex@OrgC
794     \let\d\HyLinguex@OrgD
795   }%
796   \Hy@AtEndOfPackage{%
797     \pdfstringdefDisableCommands{%
798       \ltx@ifundefined{oldb}{}{\let\b\oldb}%
799       \ltx@ifundefined{oldc}{}{\let\c\oldc}%
800       \ltx@ifundefined{oldd}{}{\let\d\oldd}%
801     }%
802   }%
803 }{%
804   \let\HyLinguex@Restore\relax
805 }

```

6.3.3 Catcodes saving and restoring for .def files

```

\Hy@SaveCatcodeSettings
806 \def\Hy@SaveCatcodeSettings#1{%
807   \expandafter\edef\csname Hy@cat@\#1\endcsname{%
808     \endlinechar=\the\endlinechar\relax
809     \catcode32 \the\catcode32\relax % (space)
810     \catcode34 \the\catcode34\relax % "
811     \catcode35 \the\catcode35\relax % #
812     \catcode37 \the\catcode37\relax % (percent)
813     \catcode40 \the\catcode40\relax % (
814     \catcode41 \the\catcode41\relax % )
815     \catcode42 \the\catcode42\relax % *

```

```

816  \catcode46 \the\catcode46\relax % .
817  \catcode58 \the\catcode58\relax % :
818  \catcode60 \the\catcode60\relax % <
819  \catcode61 \the\catcode61\relax % =
820  \catcode62 \the\catcode62\relax % >
821  \catcode64 \the\catcode64\relax % @
822  \catcode91 \the\catcode91\relax % [
823  \catcode92 \the\catcode92\relax % (backslash)
824  \catcode93 \the\catcode93\relax % ]
825  \catcode123 \the\catcode123\relax % {
826  \catcode124 \the\catcode124\relax % |
827  \catcode125 \the\catcode125\relax % }
828 }%
829 \endlinechar=-1 %
830 \catcode32 10 % (space)
831 \catcode34 12 % "
832 \catcode35 6 % #
833 \catcode37 14 % (percent)
834 \catcode40 12 % (
835 \catcode41 12 % )
836 \catcode42 12 % *
837 \catcode46 12 % .
838 \catcode58 12 % :
839 \catcode60 12 % <
840 \catcode61 12 % =
841 \catcode62 12 % >
842 \catcode91 12 % [
843 \catcode92 0 % (backslash)
844 \catcode93 12 % ]
845 \catcode123 1 % {
846 \catcode124 12 % |
847 \catcode125 2 % }
848 \makeatletter
849 }

```

```
\Hy@RestoreCatcodeSettings
850 \def\Hy@RestoreCatcodeSettings#1{%
851   \csname Hy@cat@#1\endcsname
852   \expandafter\let\csname Hy@cat@#1\endcsname\relax
853 }
```

6.3.4 PD1 encoding

The PD1 encoding implements the PDFDocEncoding for use with L^AT_EX 2 _{ε} 's NFSS. Because the informational strings are not set by T_EX's typesetting mechanism but for interpreting by the PDF reader, the glyphs of the PD1 encoding are implemented to be safely written to a file (PDF output file, .out file).

The PD1 encoding can be specified as an option of the 'fontenc' package or loaded here. It does not matter what font family is selected, as T_EX does not process it anyway. So use CM.

```

854 \@ifundefined{T@PD1}{%
855   \Hy@SaveCatcodeSettings{pd1}%
856   \input{pd1enc.def}%

```

```

857 \Hy@RestoreCatcodeSettings{pd1}%
858 \HyLingex@Restore
859 }{}%
860 \DeclareFontFamily{PD1}{pdf}{}%
861 \DeclareFontShape{PD1}{pdf}{m}{n}{\<- cmr10 }{}%
862 \DeclareFontSubstitution{PD1}{pdf}{m}{n}

```

6.3.5 PU encoding

The PU encoding implements the Unicode encoding for use with L^AT_EX's NFSS. Because of large memory requirements the encoding file for Unicode support is only loaded, if option `unicode` is specified as package option. change 2020-08-14: Starting with version v7.00f the file is always loaded and `unicode` is the default option.

`\HyPsd@LoadUnicode` Because the file `puenc.def` takes a lot of memory, the loading is defined in the macro `\HyPsd@LoadUnicode` called by the package option `unicode`.

```

863 \def\HyPsd@LoadUnicode{%
864   \ifundefined{T@PU}{%
865     \Hy@SaveCatcodeSettings{pu}%
866     \input{puenc.def}%
867     \Hy@RestoreCatcodeSettings{pu}%
868     \HyLingex@Restore
869   }{}%
870   \DeclareFontFamily{PU}{pdf}{}%
871   \DeclareFontShape{PU}{pdf}{m}{n}{\<- cmr10 }{}%
872   \DeclareFontSubstitution{PU}{pdf}{m}{n}%
873   \HyPsd@LoadExtra
874   \let\HyPsd@LoadUnicode\relax
875 }

```

`\HyPsd@LoadExtra`

```

876 \def\HyPsd@LoadExtra{%
877   \ifHy@psdextra
878     \ltx@iffileloaded{puenc.def}{%
879       \Hy@SaveCatcodeSettings{psdextra}%
880       \input{psdextra.def}%
881       \Hy@RestoreCatcodeSettings{psdextra}%
882       \let\HyPsd@LoadExtra\relax
883     }{}%
884   \fi
885 }

```

6.4 Additional user commands

6.4.1 \texorpdfstring

`\texorpdfstring` While expanding the string in `\pdfstringdef` the switch `\ifHy@pdfstring` is set. This is used by the full expandable macro `\texorpdfstring`. It expects two arguments, the first contains the string that will be set and processed by T_EX's stomach, the second contains the replacement for PDF strings.

```

886 \def\texorpdfstring{%
887   \ifHy@pdfstring

```

```

888     \expandafter\@secondoftwo
889     \else
890     \expandafter\@firstoftwo
891     \fi
892 }

```

6.4.2 Hooks for \pdfstringdef

\pdfstringdefPreHook Default definition of the hooks for \pdfstringdef. The construct \c@ifundefined \pdfstringdefPostHook with \let is a little bit faster than \providecommand.

```

893 \c@ifundefined{\pdfstringdefPreHook}{%
894   \let\pdfstringdefPreHook\empty
895 }{%
896 \c@ifundefined{\pdfstringdefPostHook}{%
897   \let\pdfstringdefPostHook@gobble
898 }{%

```

\pdfstringdefDisableCommands In \pdfstringdefPreHook the user can add code that is executed before the string, that have to be converted by \pdfstringdef, is expanded. So replacements for problematic macros can be given. The code in \pdfstringdefPreHook should not be replaced perhaps by an \renewcommand, because a previous meaning gets lost.

Macro \pdfstringdefDisableCommands avoids this, because it reuses the old meaning of the hook and appends the new code to \pdfstringdefPreHook, e.g.:

```

\pdfstringdefDisableCommands{%
\let~\textasciitilde
\def\Url{\pdfstringdefWarn\url}%
\let\textcolor@gobble
}%

```

In the argument of \pdfstringdefDisableCommands the character @ can be used in command names. So it is easy to use useful L^AT_EX commands like \gobble or \@firstofone.

```

899 \def\pdfstringdefDisableCommands{%
900   \begingroup
901   \makeatletter
902   \HyPsd@DisableCommands
903 }

```

\HyPsd@DisableCommands

```

904 \long\def\HyPsd@DisableCommands#1{%
905   \ltx@GlobalAppendToMacro\pdfstringdefPreHook{#1}%
906   \endgroup
907 }

```

\pdfstringdefWarn The purpose of \pdfstringdefWarn is to produce a warning message, so the user can see, that something can go wrong with the conversion to PDF strings.

The prefix \<- is added to the token. \noexpand protects the probably undefined one during the first expansion step. Then \HyPsd@CheckCatcodes can detect the not allowed token, \HyPsd@CatcodeWarning prints a warning message, after \HyPsd@RemovePrefix has removed the prefix.

\pdfstringdefWarn is intended for document authors or package writers, examples for use can be seen in the definition of \HyPsd@ifnextchar or \HyPsd@protected@testopt.

```
908 \def\pdfstringdefWarn#1{%
909   \expandafter\noexpand\csname->-\string#1\endcsname
910 }
```

6.5 Help macros for expansion

6.5.1 \ignorespaces

\HyPsd@ignorespaces With the help of a trick using \romannumeral the effect of \ignorespaces can be simulated a little. In a special case using an alphabetic constant \romannumeral eats an optional space. If the constant is zero, then the \romannumeral expression vanishes. The following macro uses this trick twice, thus \HyPsd@ignorespaces eats up to two following spaces.

```
911 \begingroup
912   \catcode0=12 %
913   \def\x{\endgroup
914   \def\HyPsd@ignorespaces{%
915     \romannumeral\expandafter`\expandafter^^@\%
916     \romannumeral`^^@\%
917   }%
918 }%
919 \x
```

6.5.2 Babel languages

change 2020-10-10: moved language patches to its own file as a first step toward removing them completely.

```
920 \newif\ifHy@next
921 </package>
```

Since version 2008/03/16 v3.8j babel used inside \AtBeginDocument:

```
\pdfstringdefDisableCommands{%
  \languageshorthands{system}%
}
```

As consequence the shorthands were shown in the bookmarks, and required a hyperref patch. In version 3.48 babel removed this unneeded code and so the patch could be removed.

Nothing to do for english. change 2020/07/16: removed patch for french. No longer needed. change 2020/07/21: removed patches for german, ngerman. Will be done by the language package. <https://github.com/jspitz/babel-german/issues/4> change 2020/10/10: removed patches for danish, dutch, finnish, portugues, swedish, usorbian, slovene see <https://github.com/latex3/babel/issues/84> change 2020/10/10: removed patch for macedonian, ukrainian; maintainers notified. change 2020/10/11: removed patch for russian, has been merged into babel-russian see <https://github.com/kia999/babel-russian/pull/3> change 2021/02/04: removed patches for greek numerals, code is now in babel-greek. spanish: Nested quoting environments are not supported (<<, >>). change 2021/07/19: removed patches for spanish, code is now in babel-spanish.

```
922 <*package>
```

6.5.3 CJK patch

```
923 \RequirePackage{intcalc}[2007/09/27]
```

```
\HyPsd@CJKhook
```

```
924 \def\HyPsd@CJKhook{%
925   \ltx@ifpackageloaded{CJK}{%
926     \let\CJK@kern\relax
927     \let\CJKkern\relax
928     \let\CJK@CJK\relax
929     \ifHy@CJKbookmarks
930       \HyPsd@CJKhook@bookmarks
931     \fi
932     \HyPsd@CJKhook@unicode
933   }{}%
934 }
```

6.5.4 CJK bookmarks

\HyPsd@CJKhook Some internal commands of package cjk are redefined to avoid error messages. For a rudimental support of CJK bookmarks the active characters are redefined so that they print themselves.

After preprocessing of Big5 encoded data the following string for a double-byte character is emitted:

```
^^7f<arg1>^^7f<arg2>^^7f
```

<arg1> is the first byte in the range (always > 0x80); <arg2> is the second byte in decimal notation ($\geq 0x40$).

```
935 \begingroup
936   \catcode"7F=\active
937   \toks@{%
938     \let\CJK@ignorespaces\empty
939     \def\CJK@char#1{\gobbletwo}%
940     \let\CJK@charx\gobblefour
941     \let\CJK@punctchar\gobblefour
942     \def\CJK@punctcharx#1{\gobblefour}%
943     \catcode"7F=\active
944     \def^^7f#1^^7f#2^^7f{%
945       \string #1\HyPsd@DecimalToOctal{#2}%
946     }%
947     % ...
948     \ifHy@unicode
949       \def\Hy@cjkpu{\80}%
950     \else
951       \let\Hy@cjkpu\empty
952     \fi
953     \HyPsd@CJKActiveChars
954   }%
955   \count@=127 %
956   \whilenum\count@<255 \do{%
957     \advance\count@ by 1 %
958     \lccode`\~=\count@
959     \lowercase{%
960       \toks@\expandafter{\the\toks@ ~}%
961     }%
```

```

961    }%
962  }%
963 \toks@\expandafter{\the\toks@ !}%
964 \xdef\HyPsd@CJKhook@bookmarks{%
965   \the\toks@
966 }%
967 \endgroup

```

\HyPsd@CJKActiveChars The macro \HyPsd@CJKActiveChars is only defined to limit the memory consumption of \HyPsd@CJKhook.

```

968 \def\HyPsd@CJKActiveChars#1{%
969   \ifx#1!%
970     \let\HyPsd@CJKActiveChars\relax
971   \else
972     \edef#1{\noexpand\Hy@cjkpu\string#1}%
973   \fi
974 \HyPsd@CJKActiveChars
975 }

```

\HyPsd@DecimalToOctal A character, given by the decimal number is converted to a PDF character.

```

976 \def\HyPsd@DecimalToOctal#1{%
977   \ifcase #1 %
978     \000\or \001\or \002\or \003\or \004\or \005\or \006\or \007%
979     \or \010\or \011\or \012\or \013\or \014\or \015\or \016\or \017%
980     \or \020\or \021\or \022\or \023\or \024\or \025\or \026\or \027%
981     \or \030\or \031\or \032\or \033\or \034\or \035\or \036\or \037%
982     \or \040\or \041\or \042\or \043\or \044\or \045\or \046\or \047%
983     \or \050\or \051\or \052\or \053\or \054\or \055\or \056\or \057%
984     \or \0\or \1\or \2\or \3\or \4\or \5\or \6\or \7%
985     \or \8\or \9\or \072\or \073\or \074\or \075\or \076\or \077%
986     \or \C\or \A\or \B\or \C\or \D\or \E\or \F\or \G%
987     \or \H\or \I\or \J\or \K\or \L\or \M\or \N\or \O%
988     \or \P\or \Q\or \R\or \S\or \T\or \U\or \V\or \W%
989     \or \X\or \Y\or \Z\or \133\or \134\or \135\or \136\or \137%
990     \or \140\or \a\or \b\or \c\or \d\or \e\or \f\or \g%
991     \or \h\or \i\or \j\or \k\or \l\or \m\or \n\or \o%
992     \or \p\or \q\or \r\or \s\or \t\or \u\or \v\or \w%
993     \or \x\or \y\or \z\or \173\or \174\or \175\or \176\or \177%
994     \or \200\or \201\or \202\or \203\or \204\or \205\or \206\or \207%
995     \or \210\or \211\or \212\or \213\or \214\or \215\or \216\or \217%
996     \or \220\or \221\or \222\or \223\or \224\or \225\or \226\or \227%
997     \or \230\or \231\or \232\or \233\or \234\or \235\or \236\or \237%
998     \or \240\or \241\or \242\or \243\or \244\or \245\or \246\or \247%
999     \or \250\or \251\or \252\or \253\or \254\or \255\or \256\or \257%
1000    \or \260\or \261\or \262\or \263\or \264\or \265\or \266\or \267%
1001    \or \270\or \271\or \272\or \273\or \274\or \275\or \276\or \277%
1002    \or \300\or \301\or \302\or \303\or \304\or \305\or \306\or \307%
1003    \or \310\or \311\or \312\or \313\or \314\or \315\or \316\or \317%
1004    \or \320\or \321\or \322\or \323\or \324\or \325\or \326\or \327%
1005    \or \330\or \331\or \332\or \333\or \334\or \335\or \336\or \337%
1006    \or \340\or \341\or \342\or \343\or \344\or \345\or \346\or \347%
1007    \or \350\or \351\or \352\or \353\or \354\or \355\or \356\or \357%
1008    \or \360\or \361\or \362\or \363\or \364\or \365\or \366\or \367%
1009    \or \370\or \371\or \372\or \373\or \374\or \375\or \376\or \377%

```

```
1010 \fi  
1011 }
```

6.5.5 CJK unicode

```
\HyPsd@CJKhook@unicode  
1012 \def\HyPsd@CJKhook@unicode{  
1013   \let\Unicode\HyPsd@CJK@Unicode  
1014   \let\CJKnumber\HyPsd@CJKnumber  
1015   \let\CJKdigits\HyPsd@CJKdigits  
1016 }  
  
\HyPsd@CJK@Unicode  
1017 \def\HyPsd@CJK@Unicode#1#2{  
1018   \ifnum#1<256 %  
1019     \HyPsd@DecimalToOctalFirst{#1}%  
1020     \HyPsd@DecimalToOctalSecond{#2}%  
1021   \else  
1022     \933%  
1023     \expandafter\expandafter\expandafter\HyPsd@HighA  
1024     \intcalcDiv{#1}{4}!  
1025     \933%  
1026     \ifcase\intcalcMod{#1}{4} %  
1027       4\or 5\or 6\or 7%  
1028     \fi  
1029     \HyPsd@DecimalToOctalSecond{#2}%  
1030   \fi  
1031 }  
  
1032 \def\HyPsd@HighA#1!{  
1033   \expandafter\expandafter\expandafter\HyPsd@HighB  
1034   \IntCalcDiv#1!64!%  
1035   \expandafter\expandafter\expandafter\HyPsd@HighD  
1036   \IntCalcMod#1!64!!%  
1037 }  
1038 \def\HyPsd@HighB#1!{  
1039   \expandafter\expandafter\expandafter\HyPsd@HighC  
1040   \IntCalcDec#1!!%  
1041 }  
1042 \def\HyPsd@HighC#1!{  
1043   \IntCalcDiv#1!4!%  
1044   \@backslashchar  
1045   \IntCalcMod#1!4!%  
1046 }  
1047 \def\HyPsd@HighD#1!{  
1048   \ifcase\IntCalcDiv#1!8! %  
1049     0\or 1\or 2\or 3\or 4\or 5\or 6\or 7%  
1050   \fi  
1051   \ifcase\IntCalcMod#1!8! %  
1052     0\or 1\or 2\or 3\or 4\or 5\or 6\or 7%  
1053   \fi  
1054 }  
1055 \def\HyPsd@DecimalToOctalFirst#1{  
1056   \9%
```

```

1057 \ifcase#1 %
1058   000\or 001\or 002\or 003\or 004\or 005\or 006\or 007%
1059   \or 010\or 011\or 012\or 013\or 014\or 015\or 016\or 017%
1060   \or 020\or 021\or 022\or 023\or 024\or 025\or 026\or 027%
1061   \or 030\or 031\or 032\or 033\or 034\or 035\or 036\or 037%
1062   \or 040\or 041\or 042\or 043\or 044\or 045\or 046\or 047%
1063   \or 050\or 051\or 052\or 053\or 054\or 055\or 056\or 057%
1064   \or 060\or 061\or 062\or 063\or 064\or 065\or 066\or 067%
1065   \or 070\or 071\or 072\or 073\or 074\or 075\or 076\or 077%
1066   \or 100\or 101\or 102\or 103\or 104\or 105\or 106\or 107%
1067   \or 120\or 111\or 112\or 113\or 114\or 115\or 116\or 117%
1068   \or 120\or 121\or 122\or 123\or 124\or 125\or 126\or 127%
1069   \or 130\or 131\or 132\or 133\or 134\or 135\or 136\or 137%
1070   \or 140\or 141\or 142\or 143\or 144\or 145\or 146\or 147%
1071   \or 150\or 151\or 152\or 153\or 154\or 155\or 156\or 157%
1072   \or 160\or 161\or 162\or 163\or 164\or 165\or 166\or 167%
1073   \or 170\or 171\or 172\or 173\or 174\or 175\or 176\or 177%
1074   \or 200\or 201\or 202\or 203\or 204\or 205\or 206\or 207%
1075   \or 210\or 211\or 212\or 213\or 214\or 215\or 216\or 217%
1076   \or 220\or 221\or 222\or 223\or 224\or 225\or 226\or 227%
1077   \or 230\or 231\or 232\or 233\or 234\or 235\or 236\or 237%
1078   \or 240\or 241\or 242\or 243\or 244\or 245\or 246\or 247%
1079   \or 250\or 251\or 252\or 253\or 254\or 255\or 256\or 257%
1080   \or 260\or 261\or 262\or 263\or 264\or 265\or 266\or 267%
1081   \or 270\or 271\or 272\or 273\or 274\or 275\or 276\or 277%
1082   \or 300\or 301\or 302\or 303\or 304\or 305\or 306\or 307%
1083   \or 310\or 311\or 312\or 313\or 314\or 315\or 316\or 317%
1084   \or 320\or 321\or 322\or 323\or 324\or 325\or 326\or 327%
1085   \or 330\or 331\or 332\or 333\or 334\or 335\or 336\or 337%
1086   \or 340\or 341\or 342\or 343\or 344\or 345\or 346\or 347%
1087   \or 350\or 351\or 352\or 353\or 354\or 355\or 356\or 357%
1088   \or 360\or 361\or 362\or 363\or 364\or 365\or 366\or 367%
1089   \or 370\or 371\or 372\or 373\or 374\or 375\or 376\or 377%
1090 \fi
1091 }
1092 \def\HyPsd@DecimalToOctalSecond#1{%
1093 \ifcase #1 %
1094   \000\or \001\or \002\or \003\or \004\or \005\or \006\or \007%
1095   \or \010\or \011\or \012\or \013\or \014\or \015\or \016\or \017%
1096   \or \020\or \021\or \022\or \023\or \024\or \025\or \026\or \027%
1097   \or \030\or \031\or \032\or \033\or \034\or \035\or \036\or \037%
1098   \or \040\or \041\or \042\or \043\or \044\or \045\or \046\or \047%
1099   \or \050\or \051\or \052\or \053\or \054\or \055\or \056\or \057%
1100   \or \060\or \061\or \062\or \063\or \064\or \065\or \066\or \067%
1101   \or \070\or \071\or \072\or \073\or \074\or \075\or \076\or \077%
1102   \or \100\or \101\or \102\or \103\or \104\or \105\or \106\or \107%
1103   \or \110\or \111\or \112\or \113\or \114\or \115\or \116\or \117%
1104   \or \120\or \121\or \122\or \123\or \124\or \125\or \126\or \127%
1105   \or \130\or \131\or \132\or \133\or \134\or \135\or \136\or \137%
1106   \or \140\or \141\or \142\or \143\or \144\or \145\or \146\or \147%
1107   \or \150\or \151\or \152\or \153\or \154\or \155\or \156\or \157%
1108   \or \160\or \161\or \162\or \163\or \164\or \165\or \166\or \167%
1109   \or \170\or \171\or \172\or \173\or \174\or \175\or \176\or \177%
1110   \or \200\or \201\or \202\or \203\or \204\or \205\or \206\or \207%

```

```

1111   \or \210\or \211\or \212\or \213\or \214\or \215\or \216\or \217%
1112   \or \220\or \221\or \222\or \223\or \224\or \225\or \226\or \227%
1113   \or \230\or \231\or \232\or \233\or \234\or \235\or \236\or \237%
1114   \or \240\or \241\or \242\or \243\or \244\or \245\or \246\or \247%
1115   \or \250\or \251\or \252\or \253\or \254\or \255\or \256\or \257%
1116   \or \260\or \261\or \262\or \263\or \264\or \265\or \266\or \267%
1117   \or \270\or \271\or \272\or \273\or \274\or \275\or \276\or \277%
1118   \or \300\or \301\or \302\or \303\or \304\or \305\or \306\or \307%
1119   \or \310\or \311\or \312\or \313\or \314\or \315\or \316\or \317%
1120   \or \320\or \321\or \322\or \323\or \324\or \325\or \326\or \327%
1121   \or \330\or \331\or \332\or \333\or \334\or \335\or \336\or \337%
1122   \or \340\or \341\or \342\or \343\or \344\or \345\or \346\or \347%
1123   \or \350\or \351\or \352\or \353\or \354\or \355\or \356\or \357%
1124   \or \360\or \361\or \362\or \363\or \364\or \365\or \366\or \367%
1125   \or \370\or \371\or \372\or \373\or \374\or \375\or \376\or \377%
1126   \fi
1127 }
1128 \def\HyPsd@CJKnumber#1{%
1129   \ifnum#1<\z@%
1130     \CJK@minus%
1131     \expandafter\HyPsd@@CJKnumber\expandafter{\number-\number#1}%
1132   \else%
1133     \expandafter\HyPsd@@CJKnumber\expandafter{\number#1}%
1134   \fi%
1135 }
1136 \def\HyPsd@@CJKnumber#1{%
1137   \ifcase#1 %
1138     \CJK@zero\or \CJK@one\or \CJK@two\or \CJK@three\or \CJK@four\or%
1139     \CJK@five\or \CJK@six\or \CJK@seven\or \CJK@eight\or \CJK@nine\or%
1140     \CJK@ten\or \CJK@ten\JK@one\or \CJK@ten\JK@two\or%
1141     \CJK@ten\JK@three\or \CJK@ten\JK@four\or \CJK@ten\JK@five\or%
1142     \CJK@ten\JK@six\or \CJK@ten\JK@seven\or \CJK@ten\JK@eight\or%
1143     \CJK@ten\JK@nine%
1144   \else%
1145     \ifnum#1<10000 %
1146       \HyPsd@CJKnumberFour#1!\empty{20}%
1147       \empty%
1148     \else%
1149       \ifnum#1<100000000 %
1150         \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour%
1151         \IntCalcDiv#1!10000!%
1152         !{}{20}%
1153         \CJK@tenthousand%
1154         \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour%
1155         \IntCalcMod#1!10000!%
1156         !\CJK@zero{10}%
1157         \empty%
1158     \else%
1159       \expandafter\HyPsd@CJKnumberLarge%
1160       \number\IntCalcDiv#1!100000000!\expandafter!%
1161       \number\IntCalcMod#1!100000000!!%
1162     \fi%
1163   \fi%
1164 }

```

```

1165 }
1166 \def\HyPsd@CJKnumberLarge#1!#2!{%
1167   \HyPsd@CJKnumberFour#1!{}{20}%
1168   \CJK@hundredmillion
1169   \ifnum#2=\z@
1170   \else
1171     \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1172     \IntCalcDiv#2!10000!%
1173     !\CJK@zero{10}%
1174     \CJK@tenthsousand
1175     \expandafter\expandafter\expandafter\HyPsd@CJKnumberFour
1176     \IntCalcMod#2!10000!%
1177     !\CJK@zero{10}%
1178     \@empty
1179   \fi
1180 }
1181 \def\HyPsd@CJKnumberFour#1!#2#3{%
1182   \ifnum#1=\z@
1183   \expandafter\@gobble
1184   \else
1185     \ifnum#1<1000 %
1186     #2%
1187     \HyPsd@CJKnumberThree#1!{}{#3}%
1188   \else
1189     \HyPsd@@CJKnumber{\IntCalcDiv#1!1000!}%
1190     \CJK@thousand
1191     \expandafter\expandafter\expandafter\HyPsd@CJKnumberThree
1192     \IntCalcMod#1!1000!%
1193     !\CJK@zero{10}%
1194   \fi
1195 \fi
1196 }
1197 \def\HyPsd@CJKnumberThree#1!#2#3{%
1198   \ifnum#1=\z@
1199   \else
1200     \ifnum#1<100 %
1201     #2%
1202     \HyPsd@CJKnumberTwo#1!{}{#3}%
1203   \else
1204     \HyPsd@@CJKnumber{\IntCalcDiv#1!100!}%
1205     \CJK@hundred
1206     \expandafter\expandafter\expandafter\HyPsd@CJKnumberTwo
1207     \IntCalcMod#1!100!%
1208     !\CJK@zero{10}%
1209   \fi
1210 \fi
1211 }
1212 \def\HyPsd@CJKnumberTwo#1!#2#3{%
1213   \ifnum#1=\z@
1214   \else
1215     \ifnum#1<#3 %
1216     #2%
1217     \HyPsd@@CJKnumber{#1}%
1218   \else

```

```

1219   \HyPsd@@CJKnumber{\IntCalcDiv#1!10!}{%
1220     \CJK@ten
1221     \ifnum\IntCalcMod#1!10!=\z@
1222     \else
1223       \HyPsd@@CJKnumber{\IntCalcMod#1!10!}{%
1224     \fi
1225   \fi
1226 }%
1227 }

1228 \def\HyPsd@CJKdigits#1{%
1229   \ifx*#1\relax
1230     \expandafter\HyPsd@@CJKdigits\expandafter\JK@zero
1231   \else
1232     \HyPsd@@CJKdigits\JK@null{#1}{%
1233   \fi
1234 }
1235 \def\HyPsd@@CJKdigits#1#2{%
1236   \ifx\#2\%
1237   \else
1238     \HyPsd@@@CJKdigits#1#2@nil
1239   \fi
1240 }%
1241 \def\HyPsd@@@CJKdigits#1#2#3@nil{%
1242   \HyPsd@CJKdigit#1{#2}{%
1243   \ifx\#3\%
1244     \expandafter\@gobble
1245   \else
1246     \expandafter\@firstofone
1247   \fi
1248 }%
1249   \HyPsd@@@CJKdigits#1#3@nil
1250 }%
1251 }
1252 \def\HyPsd@CJKdigit#1#2{%
1253   \ifcase#2 %
1254     #1\or
1255     \JK@one\or\JK@two\or\JK@three\or\JK@four\or
1256     \JK@five\or\JK@six\or\JK@seven\or\JK@eight\or\JK@nine
1257   \fi
1258 }

```

6.5.6 \inmathwarn-Patch

\HyPsd@inmathwarn The patch of \inmathwarn is needed to get rid of the infinite error loop with glyphs of other encodings (see the explanation above). Potentially the patch is dangerous, if the code in `ltoutenc.dtx` changes. Checked with L^AT_EX 2 _{ε} versions [1998/06/01] and [1998/12/01]. I expect that versions below [1995/12/01] don't work.

To understand the patch easier, the original code of \current@cmd and @changed@cmd follows (L^AT_EX 2 _{ε} release [1998/12/01]). In the normal case \pdfstringdef is executed in a context where \protect has the meaning of \typeset-protect (= \relax).

```

\def\@current@cmd#1{%
  \ifx\protect\@typeset@protect
    \inmathwarn#1%
  \else
    \noexpand#1\expandafter\@gobble
  \fi}
\def\@changed@cmd#1#2{%
  \ifx\protect\@typeset@protect
    \inmathwarn#1%
    \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
      \expandafter\ifx\csname ?\string#1\endcsname\relax
        \expandafter\def\csname ?\string#1\endcsname{%
          \TextSymbolUnavailable#1%
        }%
      \fi
    \global\expandafter\let
      \csname\cf@encoding\string#1\expandafter\endcsname
      \csname ?\string#1\endcsname
    \fi
    \csname\cf@encoding\string#1%
    \expandafter\endcsname
  \else
    \noexpand#1%
  \fi}
\gdef\TextSymbolUnavailable#1{%
  \@latex@error{%
    Command \protect#1 unavailable in encoding \cf@encoding%
  }{\@eha}}
\def\@inmathwarn#1{%
  \ifmmode
    \@latex@warning{Command \protect#1 invalid in math mode}%
  \fi}
1259 \def\HyPsd@inmathwarn#1#2{%
1260   \ifx#2\expandafter
1261     \expandafter\ifx\csname\cf@encoding\string#1\endcsname\relax
1262       \HyPsd@GLYPHERR
1263       \expandafter\@gobble\string#1%
1264     >%
1265     \expandafter\expandafter\expandafter\HyPsd@EndWithElse
1266   \else
1267     \expandafter\expandafter\expandafter\HyPsd@GobbleFiFi
1268   \fi
1269   \else
1270     \expandafter#2%
1271   \fi
1272 }
1273 \def\HyPsd@GobbleFiFi#1\fi#2\fi{}%
1274 \def\HyPsd@EndWithElse#1\else{\else}%

\HyPsd@add@accent
1275 \def\HyPsd@add@accent#1#2{%
1276   \HyPsd@GLYPHERR\expandafter\@gobble\string#1+\string#2>%
1277   #2%
1278 }%

```

6.5.7 Unexpandable spaces

\HyPsd@LetUnexpandableSpace In \HyPsd@@ProtectSpaces the space tokens are replaced by not expandable commands, that work like spaces:

- So they can caught by undelimited arguments.
- And they work in number, dimen, and skip assignments.

These properties are used in \HyPsd@CheckCatcodes.

```
1279 \def\HyPsd@LetUnexpandableSpace#1{%
1280   \expandafter\futurelet\expandafter#1\expandafter\@gobble\space\relax
1281 }
```

\HyPsd@UnexpandableSpace \HyPsd@UnexpandableSpace is used in \HyPsd@@ProtectSpaces. In \yPsd@@ProtectSpaces the space tokens are replaced by unexpandable commands \HyPsd@UnexpandableSpace, but that have the effect of spaces.

```
1282 \HyPsd@LetUnexpandableSpace\HyPsd@UnexpandableSpace
```

6.5.8 Marker for commands

\HyPsd@XSPACE Some commands and informations cannot be utilized before the string expansion \HyPsd@ITALCORR and the checking process. Command names are filtered out, so we need another \HyPsd@GLYPHERR way to transport the information: An unusual # with catcode 12 marks the beginning of the extra information.

```
1283 \edef\HyPsd@XSPACE{\string#\string X}
1284 \edef\HyPsd@ITALCORR{\string#\string I}
1285 \edef\HyPsd@GLYPHERR{\string#\string G}
```

6.5.9 \hskip fix

\HyPsd@hskip
1286 \def\HyPsd@hskip#1{\HyPsd@@hskip#1*\END}

\HyPsd@@hskip \HyPsd@hskip checks whether \hskip is called in its star form.
1287 \def\HyPsd@@hskip#1#2\END{%
1288 \ifx\\#2\\%
1289 \HyPsd@hspacetest{#1}%
1290 \else
1291 \expandafter\HyPsd@hspacetest
1292 \fi
1293 }

\HyPsd@hspacetest \HyPsd@hspacetest replaces the \hskip by a space, if the length is greater than zero.

```
1294 \def\HyPsd@hspacetest#1{\ifdim\dimexpr#1\relax>\z@\space\fi}
```

6.5.10 Fix for AMS classes

```
1295 \ltx@IfUndefined{tocsection}{%
1296   \let\HyPsd@AMSclassfix\relax
1297 }{%
1298   \def\HyPsd@AMSclassfix{%
```

```

1299   \let\toctpart\HyPsd@tocsection
1300   \let\toctchapter\HyPsd@tocsection
1301   \let\toappendix\HyPsd@tocsection
1302   \let\toctsection\HyPsd@tocsection
1303   \let\toctsubsection\HyPsd@tocsection
1304   \let\toctsubsubsection\HyPsd@tocsection
1305   \let\toctparagraph\HyPsd@tocsection
1306 }%
1307 \def\HyPsd@tocsection#1#2#3{%
1308   \if @#2@\else\if @#1@\else#1 \fi#2. \fi
1309   #3%
1310 }%
1311 }

```

6.5.11 Reference commands

\HyPsd@href
1312 \def\HyPsd@href#1{\@secondoftwo}

\HyPsd@ref Macro \HyPsd@ref calls the macro \HyPsd@@ref for star checking. The same methods like in \HyPsd@hskip is used.
1313 \def\HyPsd@ref#1{\HyPsd@@ref#1*\END}%

\HyPsd@@ref Macro \HyPsd@@ref checks if a star is present.
1314 \def\HyPsd@@ref#1*#2\END{%
1315 \ifx\\#2\\%
1316 \HyPsd@@ref{#1}%
1317 \else
1318 \expandafter\HyPsd@@ref
1319 \fi
1320 }%

\HyPsd@@@ref \HyPsd@@@ref does the work and extracts the first argument.
1321 \def\HyPsd@@@ref#1{%
1322 \expandafter\ifx\csname r@#1\endcsname\relax
1323 ??%
1324 \else
1325 \expandafter\expandafter\expandafter
1326 \car\csname r@#1\endcsname\@nil
1327 \fi
1328 }

\HyPsd@pageref Macro \HyPsd@pageref calls the macro \HyPsd@@pageref for star checking. The same methods like in \HyPsd@hskip is used.
1329 \def\HyPsd@pageref#1{\HyPsd@@pageref#1*\END}

\HyPsd@@pageref Macro \HyPsd@@pageref checks if a star is present.
1330 \def\HyPsd@@pageref#1*#2\END{%
1331 \ifx\\#2\\%
1332 \HyPsd@@@pageref{#1}%
1333 \else
1334 \expandafter\HyPsd@@@pageref
1335 \fi
1336 }

\HyPsd@@@pageref \HyPsd@@@pageref does the work and extracts the second argument.

```
1337 \def\HyPsd@@@pageref#1{%
1338   \expandafter\ifx\csname r@#1\endcsname\relax
1339   ??%
1340   \else
1341     \expandafter\expandafter\expandafter\expandafter
1342     \expandafter\expandafter\expandafter\@car
1343     \expandafter\expandafter\expandafter\@gobble
1344     \csname r@#1\endcsname{}@\nil
1345   \fi
1346 }
```

\HyPsd@nameref Macro \HyPsd@nameref calls the macro \HyPsd@nameref for star checking.
The same methods like in \HyPsd@hspace is used.

```
1347 \def\HyPsd@nameref#1{\HyPsd@nameref#1*\END}
```

\HyPsd@nameref Macro \HyPsd@nameref checks if a star is present.

```
1348 \def\HyPsd@nameref#1*#2\END{%
1349   \ifx\\#2\\%
1350   \HyPsd@@@nameref{#1}%
1351   \else
1352     \expandafter\HyPsd@@@nameref
1353   \fi
1354 }
```

\HyPsd@@@nameref \HyPsd@@@nameref does the work and extracts the third argument.

```
1355 \def\HyPsd@@@nameref#1{%
1356   \expandafter\ifx\csname r@#1\endcsname\relax
1357   ??%
1358   \else
1359     \expandafter\expandafter\expandafter\expandafter
1360     \expandafter\expandafter\expandafter\@car
1361     \expandafter\expandafter\expandafter\@gobbletwo
1362     \csname r@#1\endcsname{}{}@\nil
1363   \fi
1364 }
```

\HyPsd@autoref Macro \HyPsd@autoref calls the macro \HyPsd@autoref for star checking. The
same methods like in \HyPsd@hspace is used.

```
1365 \def\HyPsd@autoref#1{\HyPsd@@@autoref#1*\END}
```

\HyPsd@autoref Macro \HyPsd@autoref checks if a star is present.

```
1366 \def\HyPsd@@@autoref#1*#2\END{%
1367   \ifx\\#2\\%
1368   \HyPsd@@@autoref{#1}%
1369   \else
1370     \expandafter\HyPsd@@@autoref
1371   \fi
1372 }
```

\HyPsd@@@autoref \HyPsd@@@autoref does the work and extracts the second argument.

```
1373 \def\HyPsd@@@autoref#1{%
1374   \expandafter\ifx\csname r@#1\endcsname\relax
```

```

1375    ??%
1376    \else
1377    \expandafter\expandafter\expandafter\HyPsd@autorefname
1378    \csname r@#1\endcsname{}{}{}{@nil
1379    \expandafter\expandafter\expandafter
1380    \car\csname r@#1\endcsname{@nil
1381    \fi
1382 }

```

\HyPsd@autorefname At least a basic definition for getting the \autoref name.

```

1383 \def\HyPsd@autorefname#1#2#3#4#5{@nil{%
1384   \ifx\\#4\\%
1385   \else
1386   \HyPsd@@autorefname#4.\@nil
1387   \fi
1388 }

```

\HyPsd@@autorefname

```

1389 \def\HyPsd@@autorefname#1.#2@nil{%
1390   \ltx@ifundefined{#1autorefname}{%
1391     \ltx@ifundefined{#1name}{%
1392       }{%
1393         \csname#1name\endcsname\space
1394       }{%
1395     }{%
1396       \csname#1autorefname\endcsname\space
1397     }{%
1398 }

```

6.5.12 Redefining the defining commands

Definitions aren't allowed, because they aren't executed in an only expanding context. So the command to be defined isn't defined and can perhaps be undefined. This would cause TeX to stop with an error message. With a deep trick it is possible to define commands in such a context: \csname does the job, it defines the command to be \relax, if it has no meaning.

Active characters cannot be defined with this trick. It is possible to define all undefined active characters (perhaps that they have the meaning of \relax). To avoid side effects this should be done in \pdfstringdef shortly before the \xdef job. But checking and defining all possible active characters of the full range (0 until 255) would take a while. \pdfstringdef is slow enough, so this isn't done.

\HyPsd@DefCommand and \HyPsd@LetCommand expands to the commands \<def>-command and \<let>-command with the meaning of \def and \let. So it is detected by \HyPsd@CheckCatcodes and the command name \<def>-command or \<let>-command should indicate a forbidden definition command.

The command to be defined is converted to a string and back to a command name with the help of \csname. If the command is already defined, \noexpand prevents a further expansion, even though the command would expand to legal stuff. If the command don't have the meaning of \relax, \HyPsd@CheckCatcodes will produce a warning. (The command itself can be legal, but the warning is legitimate because of the position after a defining command.)

The difference between `\HyPsd@DefCommand` and `\HyPsd@LetCommand` is that the first one also cancels this arguments, the parameter and definition text. The right side of the `\let` commands cannot be canceled with an undelimited parameter because of a possible space token after `\futurelet`.

To avoid unmachted `\if...` tokens, the cases `\let\if...\iftrue` and `\let\if...\iffalse` are checked and ignored.

```
\HyPsd@DefCommand
\HyPsd@LetCommand 1399 \begingroup
1400   \def\x#1#2{%
1401     \endgroup
1402     \let#1\def
1403     \def\HyPsd@DefCommand##1##2##3{%
1404       #1%
1405       \expandafter\noexpand
1406         \csname\expandafter\@gobble\string##1\empty\endcsname
1407         \@gobble
1408     }%
1409     \let#2\let
1410     \def\HyPsd@@LetCommand##1{%
1411       \expandafter\ifx\csname##1\expandafter\endcsname
1412         \csname iftrue\endcsname
1413         \pdfstringdefWarn\let
1414         \expandafter\@gobble
1415     \else
1416       \expandafter\ifx\csname##1\expandafter\endcsname
1417         \csname ifffalse\endcsname
1418         \pdfstringdefWarn\let
1419         \expandafter\expandafter\expandafter\@gobble
1420     \else
1421       #2%
1422       \expandafter\noexpand
1423         \csname##1\expandafter\expandafter\expandafter\endcsname
1424     \fi
1425   \fi
1426 }%
1427 }%
1428 \expandafter\x\csname <def>-command\expandafter\endcsname
1429   \csname <let>-command\endcsname
1430 \def\HyPsd@LetCommand#1{%
1431   \expandafter\expandafter\expandafter\HyPsd@@LetCommand
1432   \expandafter\expandafter\expandafter\%%
1433   \expandafter\@gobble\string#1\empty
1434 }%
1435 }
```

6.5.13 `\ifnextchar`

`\HyPsd@ifnextchar` In `\pdfstringdef\@ifnextchar` is disabled via a `\let` command to save time. First a warning message is given, then the three arguments are canceled. `\@ifnextchar` cannot work in a correct manner, because it uses `\futurelet`, but this is a stomach feature, that doesn't work in an expanding context. There are several variants of `\@ifnextchar`:

- `\@ifnextchar`
- `\kernel@ifnextchar`
- `\new@ifnextchar` from package `amsgen.sty` (bug report `latex/3662`).

```
1436 \def\HyPsd@ifnextchar#1{%
1437   \pdfstringdefWarn#1%
1438   \expandafter\@gobbletwo\@gobble
1439 }
```

6.5.14 `\@protected@testopt@ifnextchar`

`\HyPsd@protected@testopt` Macros with optional arguments doesn't work properly, because they call `\@ifnextchar` to detect the optional argument (see the explanation of `\HyPsd@ifnextchar`). But a warning, that `\@ifnextchar` doesn't work, doesn't help the user very much. Therefore `\@protected@testopt` is also disabled, because its first argument is the problematic macro with the optional argument and it is called before `\@ifnextchar`.

```
1440 \def\HyPsd@protected@testopt#1{%
1441   \pdfstringdefWarn#1%
1442   \@gobbletwo
1443 }
```

6.6 Help macros for postprocessing

6.6.1 Generic warning.

`\HyPsd@Warning` For several reasons `\space` is masked and does not have its normal meaning. But it is used in warning messages, so it is redefined locally:

```
1444 \def\HyPsd@Warning#1{%
1445   \begingroup
1446   \let\space\ltx@space
1447   \Hy@Warning{#1}%
1448   \endgroup
1449 }
```

6.6.2 Protecting spaces

`\HyPsd@ProtectSpaces` `\HyPsd@ProtectSpaces` calls with the expanded string `\HyPsd@@ProtectSpacesFi`. The expanded string is protected by `|` at the beginning and end of the expanded string. Because of this there can be no group at the beginning or end of the string and grouping characters are not removed by the call of `\HyPsd@@ProtectSpacesFi`.

```
1450 \let\HyPsd@fi\fi
1451 \def\HyPsd@ProtectSpaces#1{%
1452   \xdef#1{%
1453     \iftrue
1454       \expandafter\HyPsd@@ProtectSpacesFi
1455       \expandafter|\expandafter\@empty#1| %
1456     \HyPsd@fi
1457   }%
1458   \expandafter\HyPsd@RemoveMask#1\HyPsd@End#1%
1459 }%
```

\HyPsd@@ProtectSpacesFi The string can contain command tokens, so it is better to use an \def instead of an \edef.

```
1460 \def\HyPsd@@ProtectSpacesFi#1 #2\HyPsd@fi{%
1461   \fi
1462   \unexpanded{#1}%
1463   \ifx\scrollmode#2\scrollmode
1464   \else
1465     \HyPsd@@ProtectSpacesFi\HyPsd@UnexpandableSpace#2%
1466   \HyPsd@fi
1467 }%
```

Remove mask.

\HyPsd@RemoveMask \HyPsd@RemoveMask removes the protecting |. It is used by \HyPsd@@ProtectSpacesFi and by the code in \pdfstringdef that removes the grouping characters.

```
1468 \def\HyPsd@RemoveMask|#1|\HyPsd@End#2{%
1469   \xdef#2{\unexpanded\expandafter{#1}}%
1470 }%
```

6.6.3 Remove grouping braces

\HyPsd@RemoveBraces #1 contains the expanded string, the result will be locally written in command \HyPsd@String.

```
1471 \def\HyPsd@RemoveBraces#1{%
1472   \ifx\scrollmode#1\scrollmode
1473   \else
1474     \HyPsd@@RemoveBracesFi#1\HyPsd@End{#1}%
1475   \fi
1476 }
```

\HyPsd@@RemoveBraces \HyPsd@@RemoveBraces is called with the expanded string, the end marked by \HyPsd@End, the expanded string again, but enclosed in braces and the string command. The first expanded string is scanned by the parameter text #1#2. By a comparison with the original form in #3 we can decide whether #1 is a single token or a group. To avoid the case that #2 is a group, the string is extended by a | before.

While removing the grouping braces an italic correction marker is inserted for supporting package `xspace` and letting ligatures broken.

Because the string is already expanded, the \if commands should disappeared. So we can move some parts out of the argument of \ltx@ReturnAfterFi.

```
1477 \def\HyPsd@@RemoveBracesFi#1#2\HyPsd@End#3\fi{%
1478   \fi
1479   \def\Hy@temp@A{#1#2}%
1480   \def\Hy@temp@B{#3}%
1481   \ifx\Hy@temp@A\Hy@temp@B
1482     \expandafter\def\expandafter\HyPsd@String\expandafter{%
1483       \HyPsd@String#1%
1484     }%
1485   \ifx\scrollmode#2\scrollmode
1486   \else
1487     \Hy@ReturnAfterFiFiEnd%
```

```

1488     \HyPsd@RemoveBraces{#2}%
1489   }%
1490   \fi
1491 \else
1492   \def\Hy@temp@A{#1}%
1493   \HyPsd@AppendItalcorr\HyPsd@String
1494   \ifx\Hy@temp@A\@empty
1495     \Hy@ReturnAfterElseFiFiEnd{%
1496       \HyPsd@RemoveBraces{#2}%
1497     }%
1498 \else
1499   \HyPsd@ProtectSpaces\Hy@temp@A
1500   \HyPsd@AppendItalcorr\Hy@temp@A
1501   \Hy@ReturnAfterFiFiEnd{%
1502     \expandafter\HyPsd@RemoveBraces\expandafter
1503     {\Hy@temp@A#2}%
1504   }%
1505   \fi
1506 \fi
1507 \Hy@ReturnEnd
1508 }

```

\HyPsd@AppendItalcorr The string can contain commands yet, so it is better to use \def instead of a \HyPsd@AppendItalcorr shorter \edef. The two help macros limit the count of \expandafter.

```

1509 \def\HyPsd@AppendItalcorr#1{%
1510   \expandafter\HyPsd@AppendItalcorr\expandafter{/}#1%
1511 }
1512 \def\HyPsd@AppendItalcorr#1#2{%
1513   \expandafter\def\expandafter#2\expandafter{#2#1}%
1514 }

```

6.6.4 Catcode check

Workaround for LuaTeX. \HyPsd@CheckCatcodes might trigger a bug of LuaTeX (0.60.2, 0.70.1, 0.70.2, ...) in the comparison with \ifcat, see <http://tracker.luatex.org/view.php?id=773>.

```

1515 \ltx@ifundefined{directlua}{%
1516 }{%
1517   \expandafter\ifx\csname\endcsname\relax\fi
1518 }

```

Check catcodes.

\HyPsd@CheckCatcodes Because \ifcat expands its arguments, this is prevented by \noexpand. In case of command tokens and active characters \ifcat now sees a \relax. After protecting spaces and removing braces #1 should be a single token, no group of several tokens, nor an empty group. (So the \expandafter\relax between \ifcat and \noexpand is only for safety and it should be possible to remove it.)

\protect and \relax should be removed silently. But it is too dangerous and breaks some code giving them the meaning of \empty. So commands with the meaning of \protect are removed here. (\protect should have the meaning of \typeset@protect that is equal to \relax).

For the comparison with active characters, ~ cannot be used because it has the meaning of a blank space here. And active characters need to be checked, if they have been defined using \protected.

```

1519 \begingroup
1520   \catcode`\Q=\active
1521   \let Q\ltx@empty
1522   \gdef\HyPsd@CheckCatcodes#1#2\HyPsd@End{%
1523     \global\let\HyPsd@Rest\relax
1524     \ifcat\relax\noexpand#1\relax
1525       \ifx#1\protect
1526       \else
1527         \ifx#1\penalty
1528           \setbox\z@=\hbox{%
1529             \afterassignment\HyPsd@AfterCountRemove
1530             \count@=#2\HyPsd@End
1531           }%
1532         \else
1533           \ifx#1\kern
1534             \setbox\z@=\hbox{%
1535               \afterassignment\HyPsd@AfterDimenRemove
1536               \dimen@=#2\HyPsd@End
1537             }%
1538           \else
1539             \ifx#1\hskip
1540               \setbox\z@=\hbox{%
1541                 \afterassignment\HyPsd@AfterSkipRemove
1542                 \skip@=#2\HyPsd@End
1543               }%
1544             \else
1545               \HyPsd@CatcodeWarning{#1}%
1546             \fi
1547           \fi
1548         \fi
1549       \fi
1550     \else
1551       \ifcat\noexpand#1\noexpandQ% active character
1552         \expandafter\expandafter\expandafter\def
1553         \expandafter\expandafter\expandafter\HyPsd@String
1554         \expandafter\expandafter\expandafter{%
1555           \expandafter\HyPsd@String\string#1%
1556         }%
1557       \else
1558         \ifcat#1A% letter
1559           \expandafter\def\expandafter\HyPsd@String\expandafter{%
1560             \HyPsd@String#1%
1561           }%
1562         \else
1563           \ifcat#1 % SPACE
1564             \expandafter\def\expandafter\HyPsd@String\expandafter{%
1565               \HyPsd@String\HyPsd@SPACEOPTI
1566             }%
1567           \else
1568             \ifcat$#1%
1569               \HyPsd@CatcodeWarning{math shift}%

```

```

1570     \else
1571         \ifcat<#1%
1572             \HyPsd@CatcodeWarning{alignment tab}%
1573         \else
1574             \ifcat^#1%
1575                 \HyPsd@CatcodeWarning{superscript}%
1576             \else
1577                 \ifcat_#1%
1578                     \HyPsd@CatcodeWarning{subscript}%
1579                 \else
1580                     \expandafter\def\expandafter\HyPsd@String\expandafter{%
1581                         \HyPsd@String#1%
1582                     }%
1583                     \fi
1584                     \fi
1585                     \fi
1586                     \fi
1587                     \fi
1588                     \fi
1589                     \fi
1590                     \fi
1591 \ifx\HyPsd@Rest\relax
1592     \ifx\scrollmode#2\scrollmode
1593     \else
1594         \Hy@ReturnAfterFiFiEnd{%
1595             \HyPsd@CheckCatcodes#2\HyPsd@End
1596         }%
1597         \fi
1598     \else
1599         \ifx\HyPsd@Rest\@empty
1600         \else
1601             \Hy@ReturnAfterFiFiEnd{%
1602                 \expandafter\HyPsd@CheckCatcodes\HyPsd@Rest\HyPsd@End
1603             }%
1604             \fi
1605             \fi
1606             \Hy@ReturnEnd
1607         }%
1608 \endgroup

```

Remove counts, dimens, skips.

\HyPsd@AfterCountRemove Counts like \penalty are removed silently.

```

1609 \def\HyPsd@AfterCountRemove#1\HyPsd@End{%
1610   \gdef\HyPsd@Rest{#1}%
1611 }

```

\HyPsd@AfterDimenRemove If the value of the dimen (\kern) is zero, it can be removed silently. All other values are difficult to interpret. Negative values do not work in bookmarks. Should positive values be removed or should they be replaced by space(s)? The following code replaces positive values greater than 1ex with a space and removes them else.

```

1612 \def\HyPsd@AfterDimenRemove#1\HyPsd@End{%
1613   \ifdim\ifx\HyPsd@String\@empty\z@\else\dimen@>1ex %

```

```

1614   \HyPsd@ReplaceSpaceWarning{\string\kern\space\the\dimen@}%
1615   \gdef\HyPsd@Rest{\HyPsd@UnexpandableSpace #1}%
1616 \else
1617   \ifdim\dimen@=\z@
1618   \else
1619     \HyPsd@RemoveSpaceWarning{\string\kern\space\the\dimen@}%
1620   \fi
1621   \gdef\HyPsd@Rest{#1}%
1622 \fi
1623 }

```

\HyPsd@AfterSkipRemove The glue part of skips do not work in PDF strings and are ignored. Skips (\hspace), that are not zero, have the same interpreting problems like dimens (see above).

```

1624 \def\HyPsd@AfterSkipRemove#1\HyPsd@End{%
1625   \ifdim\ifx\HyPsd@String\empty\z@\else\skip@>1ex %
1626     \HyPsd@ReplaceSpaceWarning{\string\hspace\space\the\skip@}%
1627     \gdef\HyPsd@Rest{\HyPsd@UnexpandableSpace #1}%
1628   \else
1629     \ifdim\skip@=\z@
1630   \else
1631     \HyPsd@RemoveSpaceWarning{\string\kern\space\the\skip@}%
1632   \fi
1633   \gdef\HyPsd@Rest{#1}%
1634 \fi
1635 }

```

Catcode warnings.

\HyPsd@CatcodeWarning \HyPsd@CatcodeWarning produces a warning for the user.

```

1636 \def\HyPsd@CatcodeWarning#1{%
1637   \HyPsd@Warning{%
1638     Token not allowed in a PDF string (%
1639     \ifHy@unicode
1640       Unicode%
1641     \else
1642       PDFDocEncoding%
1643     \fi
1644   ):%
1645   \MessageBreak removing `\\HyPsd@RemoveCmdPrefix#1'%
1646 }%
1647 }
1648 \begingroup
1649 \catcode`\|=0 %
1650 \catcode`\\=12 %
1651 \gdef\HyPsd@RemoveCmdPrefix#1{%
1652   \expandafter\HyPsd@@RemoveCmdPrefix
1653   \string#1\empty\empty\empty\empty\empty\empty
1654 }%
1655 \gdef\HyPsd@@RemoveCmdPrefix#1\empty\empty\empty\empty\empty\empty{%
1656 \endgroup

```

\HyPsd@RemoveSpaceWarning

```

1657 \def\HyPsd@RemoveSpaceWarning#1{%
1658   \HyPsd@Warning{%

```

```

1659   Token not allowed in a PDF string (%
1660   \ifHy@unicode
1661     Unicode%
1662   \else
1663     PDFDocEncoding%
1664   \fi
1665   ):%
1666   \MessageBreak #1\MessageBreak
1667   removed%
1668 }
1669 }

\HyPsd@ReplaceSpaceWarning
1670 \def\HyPsd@ReplaceSpaceWarning#1{%
1671   \HyPsd@Warning{%
1672     Token not allowed in a PDF string (%
1673     \ifHy@unicode
1674       Unicode%
1675     \else
1676       PDFDocEncoding%
1677     \fi
1678   ):%
1679   \MessageBreak #1\MessageBreak
1680   replaced by space%
1681 }
1682 }

```

6.6.5 Check for wrong glyphs

A wrong glyph is marked with `\relax`, the glyph name follows, delimited by `>`. `\@empty` ends the string.

```

1683 \def\HyPsd@GlyphProcess#1\relax#2\@empty{%
1684   \expandafter\def\expandafter\HyPsd@String\expandafter{%
1685     \HyPsd@String#1%
1686   }%
1687   \ifx\\#2\\%
1688   \else
1689     \ltx@ReturnAfterFi{%
1690       \HyPsd@GlyphProcessWarning#2\@empty
1691     }%
1692   \fi
1693 }
1694 \def\HyPsd@GlyphProcessWarning#1>#2\@empty{%
1695   \HyPsd@@GlyphProcessWarning#1++>%
1696   \HyPsd@GlyphProcess#2\@empty
1697 }
1698 \def\HyPsd@@GlyphProcessWarning#1+#+#3>{%
1699   \ifx\\#2\\%
1700   \HyPsd@Warning{%
1701     Glyph not defined in %
1702     P\ifHy@unicode U\else D1\fi\space encoding,\MessageBreak
1703     removing `\\backslashchar#1'%
1704   }%
1705   \else

```

```

1706   \HyPsd@Warning{%
1707     Composite letter `\'@backslashchar#1+\#2'\MessageBreak
1708     not defined in P\ifHy@unicode U\else D1\f\space encoding,%
1709     \MessageBreak
1710     removing `\'@backslashchar#1'%
1711   }%
1712   \fi
1713 }

```

Spaces.

\HyPsd@spaceopti In the string the spaces are represented by \HyPsd@spaceopti tokens. Within an \edef it prints itself as a simple space and looks for its next argument. If another space follows, so it replaces the next \HyPsd@spaceopti by an protected space \040.

```

1714 \def\HyPsd@spaceopti#1{ % first space
1715   \ifx\HyPsd@spaceopti#1%
1716     \040%
1717   \else
1718     #1%
1719   \fi
1720 }%

```

6.6.6 Replacing tokens

\HyPsd@Subst To save tokens \HyPsd@StringSubst is an wrapper for the command \HyPsd@Subst that does all the work: In string stored in command #3 it replaces the tokens #1 with #2.

- #1 Exact the tokens that should be replaced.
- #2 The replacement (don't need to be expanded).
- #3 Command with the string.

```

1721 \def\HyPsd@Subst#1#2#3{%
1722   \def\HyPsd@@ReplaceFi##1##2\END\fi{%
1723     \fi
1724     ##1%
1725     \ifx\scrollmode##2\scrollmode
1726     \else
1727       ##2%
1728     \HyPsd@@ReplaceFi##2\END
1729     \fi
1730   }%
1731   \xdef#3{%
1732     \iftrue
1733       \expandafter\HyPsd@@ReplaceFi#3#1\END
1734     \fi
1735   }%
1736 }

```

\HyPsd@StringSubst To save tokens in \pdfstringdef \HyPsd@StringSubst is a wrapper, that expands argument #1 before calling \HyPsd@Subst.

```

1737 \def\HyPsd@StringSubst#1{%
1738   \expandafter\HyPsd@Subst\expandafter{\string#1}%
1739 }

```

```
\HyPsd@EscapeTeX
```

```
1740 \begingroup
1741   \lccode`!=`\%
1742   \lccode`\|=`\%
1743   \lccode`\{`\%
1744   \lccode`\}`\%
1745   \lccode`0=\ltx@zero
1746   \lccode`1=\ltx@zero
1747   \lccode`3=\ltx@zero
1748   \lccode`4=\ltx@zero
1749   \lccode`5=\ltx@zero
1750   \lccode`7=\ltx@zero
1751 \lowercase{\endgroup
1752 \def\HyPsd@EscapeTeX#1{%
1753   \HyPsd@Subst{|045}#1%
1754   \HyPsd@Subst{|173}#1%
1755   \HyPsd@Subst{|175}#1%
1756 }%
1757 }
```

6.6.7 Support for package `xspace`

\HyPsd@doxspace \xspace does not work, because it uses a \futurelet that cannot be executed in TeX's mouth. So this implementation uses an argument to examine the next token. In a previous version I reused \xspace, but this version is shorter and easier to understand.

```
1758 \def\HyPsd@doxspace#1{%
1759   \ifx#1\relax\else
1760     \ifx#1.\else
1761       \ifx#1:\else
1762         \ifx#1,\else
1763           \ifx#1;\else
1764             \ifx#1!\else
1765               \ifx#1?\else
1766                 \ifx#1/\else
1767                   \ifx#1-\else
1768                     \ifx#1'\else
1769                       \HyPsd@SPACEOPTI
1770                     \fi
1771                   \fi
1772                 \fi
1773               \fi
1774             \fi
1775           \fi
1776         \fi
1777       \fi
1778     \fi
1779   \fi
1780 }#1%
1781 }%
```

6.6.8 Converting to Unicode

Eight bit characters are converted to the sixteen bit ones, \8 is replaced by \00, and \9 is removed. The result should be a valid Unicode PDF string without the Unicode marker at the beginning.

```
1782 \begingroup
1783   \catcode`\\=0 %
1784   \catcode`\\=12 %

\HyPsd@ConvertToUnicode
1785   |gdef|HyPsd@ConvertToUnicode#1{%
1786     |xdef#1{%
1787       |expandafter|HyPsd@DoConvert#1|\empty|\empty|\empty
1788     }%
1789     |ifx#1|\empty
1790     |else
1791       |xdef#1{%
1792         \376\377%
1793         #1%
1794       }%
1795     |fi
1796   }%

\HyPsd@DoConvert
1797   |gdef|HyPsd@DoConvert#1{%
1798     |ifx#1|\empty
1799     |else
1800       |ltx@ReturnAfterFi{%
1801         |ifx#1\%
1802         \%
1803         |expandafter|HyPsd@DoEscape
1804       |else
1805         |HyPsd@Char{#1}%
1806         |expandafter|HyPsd@DoConvert
1807       |fi
1808     }%
1809   |fi
1810 }%

\HyPsd@DoEscape
1811   |gdef|HyPsd@DoEscape#1{%
1812     |ifx#19%
1813       |expandafter|HyPsd@GetTwoBytes
1814     |else
1815       |ltx@ReturnAfterFi{%
1816         |ifx#18%
1817         00%
1818         |expandafter|HyPsd@GetTwoBytes
1819       |else
1820         #1%
1821         |expandafter|HyPsd@GetOneByte
1822       |fi
1823     }%
1824   |fi
```

```

1825  }%
1826 \HyPsd@GetTwoBytes
1827   |gdef| HyPsd@GetTwoBytes#1\#2#3#4{%
1828     #1\#2#3#4%
1829   |HyPsd@DoConvert
1829 }%
1830 \HyPsd@GetOneByte
1831   |gdef| HyPsd@GetOneByte#1#2{%
1832     #1#2%
1833   |HyPsd@DoConvert
1833 }%
1834 |endgroup
1835 \def\HyPsd@GetNextTwoTokens#1#2#3\END#4{%
1836   \xdef#4{\#4#1#2}%
1837   \HyPsd@@ConvertToUnicode#3\END#4%
1838 }
1839 \HyPsd@Char
1840   \begingroup
1841   \catcode0=9 %
1842   \catcode`^=7 %
1843   \catcode`^^^=12 %
1844   \def\x{^^^0000}%
1845   \expandafter\endgroup
1846   \ifx\x\empty
1847   \def\HyPsd@Char#1{%
1848     \ifnum`#1<128 %
1849       \@backslashchar 000#1%
1850     \else
1851       \ifnum`#1<65536 %
1852         \expandafter\HyPsd@CharTwoByte\number`#1!%
1853       \else
1854         \expandafter\expandafter\expandafter\HyPsd@CharSurrogate
1855         \intcalcSub`#1}{65536}!%
1856       \fi
1857     }%
1858   \def\HyPsd@CharTwoByte#1!{%
1859     \expandafter\expandafter\expandafter\HyPsd@CharOctByte
1860     \IntCalcDiv#1!256!!%
1861     \expandafter\expandafter\expandafter\HyPsd@CharOctByte
1862     \IntCalcMod#1!256!!%
1863   }%
1864   \def\HyPsd@CharOctByte#1!{%
1865     \@backslashchar
1866     \IntCalcDiv#1!64!%
1867     \intcalcDiv{\IntCalcMod#1!64!}{8}%
1868     \IntCalcMod#1!8!%
1869   }%

```

```

1870 \def\HyPsd@CharSurrogate#1{%
1871   \@backslashchar 33%
1872   \IntCalcDiv#1!262144!%
1873   \expandafter\expandafter\expandafter\HyPsd@CharOctByte
1874   \intcalcDiv{\IntCalcMod#1!262144!}{1024}!%
1875   \@backslashchar 33%
1876   \expandafter\expandafter\expandafter\IntCalcAdd
1877   \intcalcDiv{\IntCalcMod#1!1024!}{256}!4!%
1878   \expandafter\expandafter\expandafter\HyPsd@CharOctByte
1879   \IntCalcMod#1!256!%}
1880 }%
1881 \else
1882   \def\HyPsd@Char#1{%
1883     \@backslashchar 000#1%
1884   }%
1885 \fi

```

change 2022-02-21 For the case that utf8 chars are protected we need to expand them. This works only if \UTFviii@loop is not defined in a group, which will be the case in the new latex code, so we test for it.

```

1886 \ifcsname UTFviii@loop\endcsname
1887 \def\HyPsd@expand@utfvii{%
1888   \count@"C2
1889   \@tempcnta"F5
1890   \def\UTFviii@tmp{\expandafter\def\expandafter-\expandafter{~}}%
1891   \UTFviii@loop
1892 }
1893 \else
1894 \def\HyPsd@expand@utfvii{%
1895 \fi

```

6.6.9 Support for UTF-8 input encoding

After \usepackage[utf8]{inputenc} there are macros that expect the UTF-8 octets as arguments. Therefore we can calculate the PDF octal sequences directly. Because the PDF format is limited to UCS-2, conversion macros are needed for UTF-8 sequences with two and three octets only.

This calculation must be done in an expandable context, so we use eTeXhere for performance reasons. Unhappily the results of divisions are rounded. Thus a circumvention via \dimexpr is used, e.g.:

```
\numexpr 123/4\relax is replaced by
\number\dimexpr.25\dimexpr 123sp\relax\relax
```

```

1896 \begingroup
1897   \lccode`~=\`^f4\relax
1898 \lowercase{\endgroup
1899 \def\HyPsd@UTFviii{%
1900   \HyPsd@expand@utfvii
1901   \let\UTFviii@two@octets\HyPsd@UTFviii@two
1902   \let\UTFviii@three@octets\HyPsd@UTFviii@three
1903   \let\UTFviii@four@octets\HyPsd@UTFviii@four
1904   \ifx-\HyPsd@UTFviii@ccxliv@undef
1905   \let~\HyPsd@UTFviii@ccxliv@def

```

```

1906      \fi
1907      \let\unichar\HyPsd@unichar
1908  }%
1909 }%
1910 \def\HyPsd@UTFviii@ccxliv@undef{\@inpenC@undefined@{utf8}}%
1911 \edef\HyPsd@UTFviii@ccxliv@def{%
1912   \noexpand\UTFviii@four@octets$string ^~f4}%
1913 }%

```

The two octet form of UTF-8 110aaabb (A) and 10cccddd (B) must be converted into octal numbers 00a and bcd. The result is \8a\bcd (with a, b, c, d as octal numbers). The conversion equations.

$$a := A/4 - 48 \quad (1)$$

$$b := A - 4 * (A/4) \quad (2)$$

$$c := B/8 - 8 * ((8 * (B/8))/8) \quad (3)$$

$$d := B - 8 * (B/8) \quad (4)$$

$$\quad (5)$$

```

1914 \def\HyPsd@UTFviii@two#1#2{%
1915   \expandafter\HyPsd@UTFviii@@two
1916   \number\dimexpr.25\dimexpr`#1sp\expandafter\relax\expandafter|%
1917   \number`#1\expandafter|%
1918   \number\dimexpr.125\dimexpr`#2sp\expandafter\relax\expandafter|%
1919   \number`#2 \@nil
1920 }%
1921 \def\HyPsd@UTFviii@two#1|#2|#3|#4@\nil{%
1922   \expandafter\8%
1923   \number\numexpr #1-48\expandafter\relax
1924   \csname\number\numexpr #2-4*\#1\relax\expandafter\endcsname
1925   \number\numexpr #3-8*%
1926   \number\dimexpr.125\dimexpr#3sp\relax\relax\expandafter\relax
1927   \number\numexpr #4-8*\#3\relax
1928 }%

```

Three octet form: 1110aabb (A), 10bcccd (B), and 10eeeeff (C). The result is \9abc\def (with a, ..., f as octal numbers). The conversion equations:

$$a := A/4 - 56 \quad (6)$$

$$b := 2 * (A - 4 * (A/4)) + ((B - 128 < 32)?0 : 1) \quad (7)$$

$$c := B/4 - 32 - ((B - 128 < 32)?0 : 8) \quad (8)$$

$$d := B - 4 * (B/4) \quad (9)$$

$$e := C/8 - 16 \quad (10)$$

$$f := C - 8 * (C/8) \quad (11)$$

$$\quad (12)$$

```

1929 \def\HyPsd@UTFviii@three#1#2#3{%
1930   \expandafter\HyPsd@UTFviii@@three
1931   \number\dimexpr.25\dimexpr`#1sp\expandafter\relax\expandafter|%
1932   \number`#1\expandafter|%
1933   \number\ifnum\numexpr`#2-128\relax <32 0\else 1\fi\expandafter|%
1934   \number\dimexpr.25\dimexpr`#2sp\expandafter\relax\expandafter|%

```

```

1935   \number`#2\expandafter|%
1936   \number`\dimexpr.125\dimexpr`#3sp\expandafter\relax\expandafter|%
1937   \number`#3 \@nil
1938 }%
1939 \def\HyPsd@UTFviii@@three#1|#2|#3|#4|#5|#6|#7@\nil{%
1940   \expandafter\%
1941   \number\numexpr #1-56\expandafter\relax
1942   \number\numexpr 2*(#2-4*#1)+#3\expandafter\relax
1943   \number\numexpr #4 - 32 -\ifcase#3 0\else 8\fi\expandafter\relax
1944   \csname\number\numexpr #5-4*#4\relax\expandafter\endcsname
1945   \number\numexpr #6-16\expandafter\relax
1946   \number\numexpr #7-8*#6\relax
1947 }%

```

Surrogates: 4 octets in UTF-8, a surrogate pair in UTF-16. High surrogate range: U+D800–U+DBFF, low surrogate range: U+DC00–U+DFFF.

```

UTF-8: 11110uuu 10uuzzzz 10yyyyyy 10xxxxxx
wwww = uuuuu - 1
UTF-16: 110110ww wwzzzzyy 110111yy yyxxxxxxxx
octal: 011 011 0ww 0ww zzz zyy 011 011 1yy 0yy xxx xxx

```

```

1948 \def\HyPsd@UTFviii@four#1#2{%
1949   \expandafter\HyPsd@UTFviii@four\number
1950   \numexpr-1+(`#1-240)*4+\dimexpr.0625\dimexpr`#2sp-128sp%
1951   \expandafter|\number
1952   \numexpr`#2-16*\dimexpr.0625\dimexpr`#2sp|%
1953 }%
1954 \def\HyPsd@UTFviii@four#1|#2|#3{%
1955   \933\number\dimexpr.25\dimexpr`#1sp\relax\relax
1956   \csname\number\numexpr#1-4*\dimexpr.25\dimexpr`#1sp\endcsname
1957   \ifodd#2 %
1958     \number\numexpr(#2-1)/2\relax
1959   \else
1960     \number\numexpr#2/2\relax
1961   \fi
1962   \number\numexpr\ifodd#2 4+\fi
1963   \dimexpr.0625\dimexpr`#3sp-128sp\relax\relax\relax
1964   \933%
1965   \expandafter\HyPsd@UTFviii@four\number
1966   \numexpr`#3-16*\dimexpr.0625\dimexpr`#3sp|%
1967 }%
1968 \def\HyPsd@@UTFviii@four#1|#2{%
1969   \number\numexpr4+\dimexpr.25\dimexpr`#1sp\relax\relax\relax
1970   \csname\number\numexpr#1-4*\dimexpr.25\dimexpr`#1sp\endcsname
1971   \number\dimexpr.125\dimexpr`#2sp-128sp\relax\relax
1972   \number\numexpr`#2-8*\dimexpr.125\dimexpr`#2sp\relax\relax\relax
1973 }%

```

Input encoding utf8x of package ucs uses macro \unichar. Values greater than "FFFF" are not supported.

```

1974 \def\HyPsd@unichar#1{%
1975   \ifHy@unicode
1976     \ifnum#1>"10FFFF %
1977     \HyPsd@UnicodeReplacementCharacter % illegal

```

```

1978      \else
1979      \ifnum#1>"FFFF %
High-surrogate code point. ("D800 = 55296, \p@ = 1pt = 65536sp)
1980          \expandafter\HyPsd@unichar\expandafter{%
1981              \number\numexpr 55296+%
1982                  \dimexpr.0009765625\dimexpr\number#1sp-\p@
1983                      \relax\relax\relax
1984      }%
Low-surrogate code point. ("DC00 = 56320, "DC00 - 65536 = -9216)
1985          \expandafter\HyPsd@unichar\expandafter{%
1986              \number\numexpr#1-9216%
1987                  -1024*\dimexpr.0009765625\dimexpr\number#1sp-\p@
1988                      \relax\relax\relax
1989      }%
1990      \else
1991          \ifnum#1>"7FF %
1992              \%
1993                  \expandafter\HyPsd@unichar@first@byte\expandafter{%
1994                      \number
1995                          \dimexpr.00390625\dimexpr\number#1sp\relax\relax
1996                      }%
1997                  \else
1998                      \%
1999                          \number\dimexpr.00390625\dimexpr\number#1sp\relax\relax
2000                      \fi
2001                  \expandafter\HyPsd@unichar@second@byte\expandafter{%
2002                      \number
2003                          \numexpr#1-256*\number
2004                              \dimexpr.00390625\dimexpr\number#1sp\relax\relax\relax
2005                      }%
2006                      \fi
2007                  \fi
2008      \else
2009          .% unsupported (Unicode -> PDF Doc Encoding)
2010      \fi
2011  }%
2012 \def\HyPsd@UnicodeReplacementCharacter{\9377\375}%
2013 \def\HyPsd@unichar@first@byte#1{%
2014     \number\dimexpr.015625\dimexpr#1sp\relax\relax
2015     \expandafter\HyPsd@unichar@octtwo\expandafter{%
2016         \number
2017             \numexpr#1-64*\number\dimexpr.015625\dimexpr#1sp%
2018             \relax\relax\relax
2019     }%
2020 }%
2021 \def\HyPsd@unichar@second@byte#1{%
2022     \csname\number\dimexpr.015625\dimexpr#1sp\relax\relax\endcsname
2023     \expandafter\HyPsd@unichar@octtwo\expandafter{%
2024         \number
2025             \numexpr#1-64*\number\dimexpr.015625\dimexpr#1sp%
2026             \relax\relax\relax
2027     }%
2028 }%

```

```

2029 \def\HyPsd@unichar{octtwo#1{%
2030   \number\dimexpr.125\dimexpr#1sp\relax\relax
2031   \number\numexpr#1-8*\number\dimexpr.125\dimexpr#1sp%
2032   \relax\relax\relax
2033 }%

```

\HyPsd@utf@viii@undeferr \utf@viii@undeferr comes from file utf8x.def from package ucs.

```

2034 \def\HyPsd@utf@viii@undeferr#1#2#3#4#5#6{%
2035   \ifx\@gobble#1%
2036   \else
2037     [Please insert \textbackslash PrerenderUnicode%
2038     \textbraceleft#1\textbraceright\space
2039     into preamble]%
2040   \fi
2041 }%

```

6.6.10 Support for die faces (ifsym et. al.)

\HyPsd@DieFace Die faces are provided by

Package	Macro
ifsym	\Cube
epsdice	\epsdice
hhcount	\fcdice

\Cube and \epsdice restrict the range to the numbers one to six. \fcdice generates for larger numbers several dice faces with the sum matching the number. The implementation for the PDF strings follows \fcdice.

```

2042 \def\HyPsd@DieFace#1{%
2043   \ifHy@unicode
2044     \ifnum#1<1 %
2045       \HyPsd@UnicodeReplacementCharacter
2046     \else
2047       \ifnum#1>6 %
2048         \9046\205%
2049         \expandafter\expandafter\expandafter
2050         \HyPsd@DieFaceLarge\intcalcSub{#1}{6}!%
2051     \else
2052       \9046\20\intcalcDec{#1}%
2053     \fi
2054   \fi
2055 \else
2056   .% Die faces are not part of PDFDocEncoding
2057 \fi
2058 }

```

\HyPsd@DieFaceLarge

```

2059 \def\HyPsd@DieFaceLarge#1!{%
2060   \ifnum#1>6 %
2061     \expandafter\ltx@firstoftwo
2062   \else
2063     \expandafter\ltx@secondoftwo
2064   \fi
2065 }%

```

```

2066   \9046\205%
2067   \expandafter\expandafter\expandafter
2068   \HyPsd@DieFaceLarge\IntCalcSub#1!6!!%
2069 }%
2070   \9046\20\IntCalcDec#1!%
2071 }%
2072 }

```

6.6.11 Support for moon phases of package china2e

```

2073 \def\HyPsd@MoonPha#1{%
2074   \ifcase\intcalcNum{#1} %
2075     \HyPsd@UnicodeReplacementCharacter
2076   \or % 1
2077   % U+1F31A NEW MOON WITH FACE; \MoonPha{1} (china2e)
2078   \9330\074\9337\032%
2079   \or % 2
2080   \HyPsd@UnicodeReplacementCharacter
2081   \or % 3
2082   % U+1F31D FULL MOON WITH FACE; \MoonPha{3} (china2e)
2083   \9330\074\9337\035%
2084   \or % 4
2085   % U+1F31C LAST QUARTER MOON WITH FACE; \MoonPha{4} (china2e)
2086   \9330\074\9337\034%
2087   \else
2088   \HyPsd@UnicodeReplacementCharacter
2089   \fi
2090 }
2091 %* \HyPsd@MoonPha -> \MoonPha

```

6.6.12 Support for package pifont

```

\HyPsd@ding
2092 \def\HyPsd@ding#1{%
2093   \ifHy@unicode
2094     \ifnum#1<32 %
2095       \HyPsd@UnicodeReplacementCharacter
2096     \else
2097       \ifnum#1>254 %
2098         \HyPsd@UnicodeReplacementCharacter
2099     \else
2100       \ifnum#1<127 %
2101         \expandafter\expandafter\expandafter
2102         \HyPsd@ding\intcalcNum{#1}!%
2103       \else
2104         \ifnum#1>160 %
2105           \expandafter\expandafter\expandafter
2106           \HyPsd@ding\intcalcNum{#1}!%
2107         \else
2108           \HyPsd@UnicodeReplacementCharacter
2109         \fi
2110       \fi
2111     \fi
2112   \fi
2113 \else

```

```

2114      .% Dingbats are not part of PDFDocEncoding
2115      \fi
2116  }

\HyPsd@@ding
2117 \def\HyPsd@@ding#1!{%
2118   \ltx@ifundefined{\HyPsd@ding@#1}{%
2119     \ifnum#1<127 %
2120       \9047%
2121       \HyPsd@DecimalToOctalSecond{\IntCalcSub#1!32!}%
2122     \else
2123       \ifnum#1<168 %
2124         \9047\14\IntCalcSub#1!160!%
2125       \else
2126         \ifnum#1>181 %
2127           \9047\HyPsd@DecimalToOctalSecond{\IntCalcSub#1!64!}%
2128         \else
2129           % 172..181 -> U+2460..U+2469
2130           \9044\HyPsd@DecimalToOctalSecond{\IntCalcSub#1!76!}%
2131         \fi
2132       \fi
2133     \fi
2134   }%
2135   \csname HyPsd@ding@#1\endcsname
2136 }%
2137 }

2138 \@namedef{HyPsd@ding@32}{\space}
2139 % U+260E BLACK TELEPHONE
2140 \@namedef{HyPsd@ding@37}{\9046\016}% U+260E
2141 % U+261B BLACK RIGHT POINTING INDEX
2142 \@namedef{HyPsd@ding@42}{\9046\033}% U+261B
2143 % U+261E WHITE RIGHT POINTING INDEX
2144 \@namedef{HyPsd@ding@43}{\9046\036}% U+261E
2145 % U+2605 BLACK STAR
2146 \@namedef{HyPsd@ding@72}{\9046\005}% U+2605
2147 % U+25CF BLACK CIRCLE
2148 \@namedef{HyPsd@ding@108}{\9045\317}% U+25CF
2149 % U+25A0 BLACK SQUARE
2150 \@namedef{HyPsd@ding@110}{\9045\240}% U+25A0
2151 % U+25B2 BLACK UP-POINTING TRIANGLE
2152 \@namedef{HyPsd@ding@115}{\9045\262}% U+25B2
2153 % U+25BC BLACK DOWN-POINTING TRIANGLE
2154 \@namedef{HyPsd@ding@116}{\9045\274}% U+25BC
2155 % U+25C6 BLACK DIAMOND
2156 \@namedef{HyPsd@ding@117}{\9045\306}% U+25C6
2157 % U+25D7 RIGHT HALF BLACK CIRCLE
2158 \@namedef{HyPsd@ding@119}{\9045\327}% U+25D7
2159 \@namedef{HyPsd@ding@168}{\textclubsuitblack}%
2160 \@namedef{HyPsd@ding@169}{\textdiamondsuitblack}%
2161 \@namedef{HyPsd@ding@170}{\textheartsuitblack}%
2162 \@namedef{HyPsd@ding@171}{\textspadesuitblack}%
2163 \@namedef{HyPsd@ding@213}{\textrightarrow}%
2164 \@namedef{HyPsd@ding@214}{\textleftarrow}%

```

```

2165 \@namedef{HyPsd@ding@215}{\textupdownarrow}%
2166 \@namedef{HyPsd@ding@240}{\HyPsd@UnicodeReplacementCharacter}

```

7 Support of other packages

7.1 Package subfigure

Added fix for version 2.1. Here \sub@label is defined.

```

2167 \@ifpackageloaded{subfigure}{%
2168   \ltx@IfUndefined{\sub@label}{%
2169     \Hy@hypertexnamesfalse
2170   }{%
2171     \renewcommand*\{\sub@label}{1}{%
2172       \bsphack
2173       \subfig@oldlabel{\#1}%
2174     \if@filesw
2175       \begingroup
2176         \edef\@currentlabstr{%
2177           \expandafter\strip@prefix\meaning\@currentlabelname
2178         }%
2179         \protected@write\auxout{}{%
2180           \string\newlabel{\sub@#1}{%
2181             \nameuse{\@thesub\@capttype}%
2182             \thepage}%
2183             \%
2184             \expandafter\strip@period\@currentlabstr
2185             \relax.\relax\@@%
2186           }%
2187           \currentHref}%
2188         \%
2189       }%
2190     }%
2191   \endgroup
2192   \fi
2193   \esphack
2194 }%
2195 }%
2196 }{%

```

7.2 Package xr and xr-hyper

The beta version of xr that supports \XR@addURL is called **xr-hyper**. If reading external aux files check whether they have a non zero fourth field in \newlabel and if so, add the URL as the fifth field. Change 2023-05-14: xr-hyper adds the field.

```

2197 \def\Hy@true{true}
2198 \def\Hy@false{false}

```

Providing dummy definitions.

```

2199 \let\literalps@out\gobble
2200 \newcommand\pdfbookmark[3][]{}
2201 \def\Acrobatmenu#1#2{\leavevmode#2}
2202 \def\Hy@writebookmark#1#2#3#4#5{}%

```

8 Help macros for links

Anchors get created on the baseline of where they occur. If an XYZ PDF view is set, this means that the link places the top of the screen *on the baseline* of the target. If this is an equation, for instance, it means that you cannot see anything. Some links, of course, are created at the start of environments, and so it works. To allow for this, anchors are raised, where possible, by some small amount. This defaults to \baselineskip, but users can set it to something else in two ways (thanks to Heiko Oberdiek for suggesting this):

1. Redefine \HyperRaiseLinkDefault to be eg the height of a \strut
2. Redefine \HyperRaiseLinkHook to do something complicated; it must give a value to \HyperRaiseLinkLength, which is what actually gets used

```
2203 \let\HyperRaiseLinkHook\empty
2204 \def\HyperRaiseLinkDefault{\baselineskip}

\HyperRaiseLinkHook allows the user to reassign \HyperRaiseLinkLength.
2205 \newcount\Hy@SavedSpaceFactor
2206 \def\Hy@SaveSpaceFactor{%
2207   \global\Hy@SavedSpaceFactor=\ifhmode\spacefactor\else\z@\fi
2208 }
2209 \def\Hy@RestoreSpaceFactor{%
2210   \relax
2211   \ifhmode
2212     \ifnum\Hy@SavedSpaceFactor>\z@
2213       \spacefactor=\Hy@SavedSpaceFactor
2214     \fi
2215   \fi
2216 }
2217 \def\Hy@SaveSavedSpaceFactor{%
2218   \edef\Hy@RestoreSavedSpaceFactor{%
2219     \global\Hy@SavedSpaceFactor=\the\Hy@SavedSpaceFactor\relax
2220   }%
2221 }
2222 \def\Hy@raisedlink#1{%
2223   \ifvmode
2224     #1%
2225   \else
2226     \Hy@SaveSpaceFactor
2227     \penalty\@M
2228     \smash{%
2229       \begingroup
2230         \let\HyperRaiseLinkLength\@tempdima
2231         \setlength\HyperRaiseLinkLength\HyperRaiseLinkDefault
2232         \HyperRaiseLinkHook
2233       \expandafter\endgroup
2234       \expandafter\raise\the\HyperRaiseLinkLength\hbox{%
2235         \Hy@RestoreSpaceFactor
2236         #1%
2237         \Hy@SaveSpaceFactor
2238       }%
2239     }%
2240   \Hy@RestoreSpaceFactor
```

```

2241 \fi
2242 }

\Hy@SaveLastskip Inserting a \special command to set a destination destroys the \lastskip value.
\Hy@RestoreLastskip 2243 \def\Hy@SaveLastskip{%
2244 \let\Hy@RestoreLastskip\relax
2245 \ifvmode
2246 \ifdim\lastskip=\z@
2247 \ifnum\lastnodetype=1 %
2248 \let\Hy@RestoreLastskip\relax
2249 \else
2250 \let\Hy@RestoreLastskip\nobreak
2251 \fi
2252 \else
2253 \begingroup
2254 \skip@=\lastskip
2255 \edef\x{%
2256 \endgroup
2257 \def\noexpand\Hy@RestoreLastskip{%
2258 \noexpand\ifvmode
2259 \noexpand\nobreak
2260 \vskip\the\skip@
2261 \vskip\the\lastskip\relax
2262 \noexpand\fi
2263 }%
2264 }%
2265 \x
2266 \fi
2267 \else
2268 \ifhmode
2269 \ifdim\lastskip=\z@
2270 \let\Hy@RestoreLastskip\nobreak
2271 \else
2272 \begingroup
2273 \skip@=\lastskip
2274 \edef\x{%
2275 \endgroup
2276 \def\noexpand\Hy@RestoreLastskip{%
2277 \noexpand\ifhmode
2278 \noexpand\nobreak
2279 \hskip\the\skip@
2280 \hskip\the\lastskip\relax
2281 \noexpand\fi
2282 }%
2283 }%
2284 \x
2285 \fi
2286 \fi
2287 \fi
2288 }%

```

9 Options

```

2289 \SetupKeyvalOptions{%
2290   family=Hyp,%
2291   prefix=HyOpt%
2292 }

```

9.1 Help macros

Package like hyperxmp want to retrieve the value of keys like pdfauthor. To avoid that we have two parallel interfaces we provide the interface from the pdfmanagement/ltdocinit if it doesn't exist.

```

\AddToDocumentProperties
\GetDocumentProperties 2293 \ExplSyntaxOn
2294 \@ifundefined{AddToDocumentProperties}
2295 {
2296   \prop_new:N \g__hyp_documentproperties_prop
2297   \NewDocumentCommand\AddToDocumentProperties{O{\@currname}mm}{%
2298     %
2299     \exp_args:NNx
2300     \prop_gput:Nnn \g__hyp_documentproperties_prop
2301     %
2302     \tl_if_blank:eTF {#1}{top-level/}{#1/} #2
2303     %
2304     { #3}
2305   }
2306   \NewExpandableDocumentCommand\GetDocumentProperties{m}{%
2307     %
2308     \prop_item:Nn \g__hyp_documentproperties_prop {#1}
2309   }
2310 }{}%
2311 \ExplSyntaxOff

\IfHyperBooleanExists
2312 \def\IfHyperBooleanExists#1{%
2313   \ltx@ifundefined{Hy@#1false}\ltx@secondoftwo{%
2314     \ltx@ifundefined{KV@Hyp@#1@default}\ltx@secondoftwo\ltx@firstoftwo
2315   }%
2316 }
2317 \@namedef{KV@Hyp@stopdearly@default}{}

\IfHyperBoolean
2318 \def\IfHyperBoolean#1{%
2319   \IfHyperBooleanExists{#1}{%
2320     \csname ifHy@#1\endcsname
2321     \expandafter\ltx@firstoftwo
2322   \else
2323     \expandafter\ltx@secondoftwo
2324   \fi
2325 } \ltx@secondoftwo
2326 }

\Hy@boolkey
2327 \def\Hy@boolkey#1#2{%

```

```

2328 \edef\Hy@tempa{\#2}%
2329 \lowercase\expandafter{%
2330   \expandafter\def\expandafter\Hy@tempa\expandafter{\Hy@tempa}%
2331 }%
2332 \ifx\Hy@tempa\empty
2333   \let\Hy@tempa\Hy@true
2334 \fi
2335 \ifx\Hy@tempa\Hy@true
2336 \else
2337   \ifx\Hy@tempa\Hy@false
2338   \else
2339     \let\Hy@tempa\relax
2340   \fi
2341 \fi
2342 \ifx\Hy@tempa\relax
2343   \Hy@WarnOptionValue{\#2}{\#1}{`true' or `false'}%
2344 \else
2345   \Hy@Info{Option `#1' set `\\Hy@tempa'}%
2346   \csname Hy@#1\Hy@tempa\endcsname
2347 \fi
2348 }

\Hy@WarnOptionValue
2349 \def\Hy@WarnOptionValue#1#2#3{%
2350   \Hy@Warning{%
2351     Unexpected value `#1'\MessageBreak
2352     of option `#2' instead of\MessageBreak
2353     #3%
2354   }%
2355 }

\Hy@DisableOption
2356 \def\Hy@DisableOption#1{%
2357   \ltx@ifundefined{KV@Hyp@#1@default}{%
2358     \define@key{Hyp}{#1}%
2359   }{%
2360     \define@key{Hyp}{#1}[]%
2361   }%
2362   {\Hy@WarnOptionDisabled{#1}}%
2363 }
2364

\Hy@WarnOptionDisabled
2365 \def\Hy@WarnOptionDisabled#1{%
2366   \Hy@Warning{%
2367     Option `#1' has already been used,\MessageBreak
2368     setting the option has no effect%
2369   }%
2370 }

```

\Hy@CheckOptionValue Some options take a string value out of a limited set of values. Macro \Hy@Check-OptionValue checks whether the given value #1 for option #2 is a member of the value list #3.

```

2371 \def\Hy@CheckOptionValue#1#2#3{%
2372   \begingroup
2373   \edef\x{\#1}%
2374   \@onelvel@sanitize\x
2375   \let\y=\x
2376   \def\do##1##2{%
2377     \def\z{##1}%
2378     \@onelvel@sanitize\z
2379     \ifx\x\z
2380       \let\y=n%
2381       \let\do\@gobbletwo
2382     \fi
2383   }%
2384   #3%
2385   \ifx\y y%
2386     \def\do##1##2{%
2387       * `##1'%
2388       \ifx\##2\\ \else\space(\##2)\fi
2389       \MessageBreak
2390   }%
2391   \Hy@Warning{%
2392     Values of option `##2':\MessageBreak
2393   }%
2394   * An empty value disables the option.\MessageBreak
2395   Unknown value `x'%
2396 }%
2397 \fi
2398 \endgroup
2399 }

```

\Hy@DefNameKey #1: option name

#2: \do list with known values, first argument of \do is value, second argument is a comment.

```

2400 \def\Hy@DefNameKey#1{%
2401   \expandafter\Hy@DefNameKey\csname @#1\endcsname{#1}%
2402 }

```

\Hy@DefNameKey #1: macro for value storage

#2: option name

#3: \do list with known values.

```

2403 \def\Hy@DefNameKey#1#2#3{%
2404   \define@key{Hyp}{#2}{%
2405     \edef#1{\#1}%
2406     \ifx#1\empty
2407     \else
2408       \Hy@CheckOptionValue{\#1}{\#2}{\#3}%
2409     \fi
2410   }%
2411   \let#1\empty
2412 }

```

\Hy@UseNameKey

```

2413 \def\Hy@UseNameKey#1#2{%

```

```

2414 \ifx#2\empty
2415 \else
2416 /#1/#2%
2417 \fi
2418 }

9.2 Defining the options

2419 \define@key{Hyp}{implicit}[true]{%
2420   \Hy@boolkey{implicit}{#1}%
2421 }
2422 \define@key{Hyp}{draft}[true]{%
2423   \Hy@boolkey{draft}{#1}%
2424 }
2425 \define@key{Hyp}{final}[true]{%
2426   \Hy@boolkey{final}{#1}%
2427 }
2428 \let\KV@Hyp@nolinks\KV@Hyp@draft

2429 \def\Hy@ObsoletePaperOption#1{%
2430   \Hy@WarningNoLine{%
2431     Option `#1' is no longer used%
2432   }%
2433   \define@key{Hyp}{#1}[true]{%
2434 }
2435 \def\Hy@temp#1{%
2436   \define@key{Hyp}{#1}[true]{%
2437     \Hy@ObsoletePaperOption{#1}%
2438   }%
2439 }
2440 \Hy@temp{a4paper}
2441 \Hy@temp{a5paper}
2442 \Hy@temp{b5paper}
2443 \Hy@temp{letterpaper}
2444 \Hy@temp{legalpaper}
2445 \Hy@temp{executivepaper}

2446 \define@key{Hyp}{setpagesize}[true]{%
2447   \Hy@boolkey{setpagesize}{#1}%
2448 }
2449 \define@key{Hyp}{debug}[true]{%
2450   \Hy@boolkey{debug}{#1}%
2451 }
2452 \define@key{Hyp}{linktocpage}[true]{%
2453   \Hy@boolkey{linktocpage}{#1}%
2454   \ifHy@linktocpage
2455     \let\Hy@linktoc\Hy@linktoc@page
2456   \else
2457     \let\Hy@linktoc\Hy@linktoc@section
2458   \fi
2459 }
2460 \chardef\Hy@linktoc@none=0 %
2461 \chardef\Hy@linktoc@section=1 %
2462 \chardef\Hy@linktoc@page=2 %
2463 \chardef\Hy@linktoc@all=3 %

```

```

2464 \ifHy@linktocpage
2465   \let\Hy@linktoc\Hy@linktoc@page
2466 \else
2467   \let\Hy@linktoc\Hy@linktoc@section
2468 \fi
2469 \define@key{Hyp}{linktoc}{%
2470   \@ifundefined{Hy@linktoc@\#1}{%
2471     \Hy@Warning{%
2472       Unexpected value `#\#1' of\MessageBreak
2473       option `linktoc' instead of `none',\MessageBreak
2474       `section', `page' or `all'%
2475     }%
2476   }{%
2477     \expandafter\let\expandafter\Hy@linktoc
2478     \csname Hy@linktoc@\#1\endcsname
2479   }%
2480 }
2481 \define@key{Hyp}{extension}{\def\XR@ext{\#1}}
2482 \let\XR@ext\relax
2483 \define@key{Hyp}{verbose}[true]{%
2484   \Hy@boolkey{verbose}{\#1}%
2485 }

```

If we are going to PDF via HyperTeX \special commands, the dvips (-z option) processor does not know the *height* of a link, as it works solely on the position of the closing \special. If we use this option, the \special is raised up by the right amount, to fool the dvi processor.

```

2486 \define@key{Hyp}{raiselinks}[true]{%
2487   \Hy@boolkey{raiselinks}{\#1}%
2488 }

```

Most PDF-creating drivers do not allow links to be broken

```

2489 \def\Hy@setbreaklinks#1{%
2490   \csname breaklinks#1\endcsname
2491 }
2492 \def\Hy@breaklinks@unsupported{%
2493   \ifx\Hy@setbreaklinks\@gobble
2494     \ifHy@breaklinks
2495       \Hy@WarningNoLine{%
2496         You have enabled option `breaklinks'.\MessageBreak
2497         But driver `\'\Hy@driver.def' does not support this.\MessageBreak
2498         Expect trouble with the link areas of broken links%
2499       }%
2500     \fi
2501   \fi
2502 }
2503 \define@key{Hyp}{breaklinks}[true]{%
2504   \Hy@boolkey{breaklinks}{\#1}%
2505   \let\Hy@setbreaklinks\@gobble
2506 }
2507 \define@key{Hyp}{localanchorname}[true]{%
2508   \Hy@WarningNoLine{%
2509     Option `localanchorname' is deprecated%
2510   }%

```

```

2511 \Hy@boolkey{localanchorname}{#1}%
2512 }

Determines whether an automatic anchor is put on each page
2513 \define@key{Hyp}{pageanchor}[true]{%
2514 \Hy@boolkey{pageanchor}{#1}%
2515 }

Are the page links done as plain arabic numbers, or do they follow the formatting
of the package? The latter loses if you put in typesetting like \textbf or the like.
2516 \define@key{Hyp}{plainpages}[true]{%
2517 \Hy@boolkey{plainpages}{#1}%
2518 }

Are the names for anchors made as per the HyperTeX system, or do they simply
use what LATEX provides?
2519 \define@key{Hyp}{naturalnames}[true]{%
2520 \Hy@boolkey{naturalnames}{#1}%
2521 }

Completely ignore the names as per the HyperTeX system, and use unique coun-
ters.
2522 \define@key{Hyp}{hypertexnames}[true]{%
2523 \Hy@boolkey{hypertexnames}{#1}%
2524 }

Currently, dvips doesn't allow anchors nested within targets, so this option tries
to stop that happening. Other processors may be able to cope.
2525 \define@key{Hyp}{nesting}[true]{%
2526 \Hy@boolkey{nesting}{#1}%
2527 }

2528 \define@key{Hyp}{destlabel}[true]{%
2529 \Hy@boolkey{destlabel}{#1}%
2530 }

2531 \define@key{Hyp}{unicode}[true]{%
2532 \Hy@boolkey{unicode}{#1}%
2533 \ifHy@unicode
2534 \def\HyPsd@pdfencoding{unicode}%
2535 \HyPsd@LoadUnicode
2536 \else
2537 \def\HyPsd@pdfencoding{pdfdoc}%
2538 \fi
2539 }

2540 \Hy@AtBeginDocument{%
2541 \ifx\HyPsd@LoadUnicode\relax
2542 \else
2543 \def\HyPsd@LoadUnicode{%
2544 \Hy@Error{%
2545 Unicode support for bookmarks is not available.\MessageBreak
2546 Activate unicode support by using one of the options\MessageBreak
2547 `unicode', `pdfencoding=unicode', `pdfencoding=auto'\MessageBreak
2548 in the preamble%
2549 }@\ehc
2550 \global\let\HyPsd@LoadUnicode\relax
2551 \global\Hy@unicodedefalse
2552 \global\let\Hy@unicodetrue\Hy@unicodedefalse

```

```

2553      }%
2554  \fi
2555 }

2556 \define@key{Hyp}{pdfencoding}{%
2557   \edef\HyPsd@temp{\#1}%
2558   \ifx\HyPsd@temp\HyPsd@pdfencoding@pdfdoc
2559     \let\HyPsd@pdfencoding\HyPsd@temp
2560     \Hy@unicodefalse
2561   \else
2562     \ifcase\ifx\HyPsd@temp\HyPsd@pdfencoding@unicode
2563       \z@
2564     \else
2565       \ifx\HyPsd@temp\HyPsd@pdfencoding@auto
2566         \z@
2567       \else
2568         \cne
2569       \fi
2570     \fi
2571   \let\HyPsd@pdfencoding\HyPsd@temp
2572   \hypersetup{unicode}%
2573   \ifHy@unicode
2574     \def\HyPsd@pdfencoding{\#1}%
2575     \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
2576       \HyPsd@LoadStringEnc
2577     \fi
2578   \else
2579     \Hy@Warning{Cannot switch to unicode bookmarks}%
2580     \let\HyPsd@pdfencoding\HyPsd@pdfencoding@pdfdoc
2581   \fi
2582   \else
2583     \cnelevel@sanitize\HyPsd@temp
2584     \Hy@Warning{%
2585       Values of option `pdfencoding': `MessageBreak'
2586       `pdfdoc', `unicode', `auto'. `MessageBreak'
2587       Ignoring unknown value `\\HyPsd@temp'%
2588     }%
2589   \fi
2590 \fi
2591 }

2592 \def\HyPsd@pdfencoding@auto{auto}
2593 \def\HyPsd@pdfencoding@pdfdoc{pdfdoc}
2594 \def\HyPsd@pdfencoding@unicode{unicode}

```

change 2020-08-14, use unicode by default:

```

2595 \let\HyPsd@pdfencoding\HyPsd@pdfencoding@unicode
2596 \HyPsd@LoadUnicode
2597 \def\HyPsd@LoadStringEnc{%
2598   \RequirePackage{stringenc}[2009/12/15]%
2599   \let\HyPsd@LoadStringEnc\relax
2600 }
2601 \Hy@AtBeginDocument{%
2602   \@ifpackageloaded{stringenc}{%
2603     \let\HyPsd@LoadStringEnc\relax
2604   }{%

```

```

2605   \def\HyPsd@LoadStringEnc{%
2606     \Hy@WarningNoLine{%
2607       Missing package `stringenc'. Use `pdfencoding=auto'\MessageBreak
2608       in the preamble or load the package there%
2609     }%
2610   }%
2611 }%
2612 }

2613 \define@key{Hyp}{psdextra}[true]{%
2614   \Hy@boolkey{psdextra}{#1}%
2615   \HyPsd@LoadExtra
2616 }

2617 \def\hypersetup{\kvsetkeys{Hyp}{}

2618 \newif\ifHy@setpdfversion
2619 \define@key{Hyp}{pdfversion}{%
2620   \@ifundefined{Hy@pdfversion@#1}{%
2621     \PackageWarning{hyperref}{%
2622       Unsupported PDF version `#1'.\MessageBreak
2623       Valid values: 1.2-1.7, 2.0%
2624     }%
2625   }{%
2626     \Hy@setpdfversiontrue
2627     \c@nameuse{Hy@pdfversion@#1}%
2628   }%
2629 }

\Hy@pdfminorversion already used elsewhere to denote \pdfminorversion or
\pdfvariable majorversion} so introduce new names here.
2630 \c@namedef{Hy@pdfversion@1.2}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{2}}%
2631 \c@namedef{Hy@pdfversion@1.3}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{3}}%
2632 \c@namedef{Hy@pdfversion@1.4}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{4}}%
2633 \c@namedef{Hy@pdfversion@1.5}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{5}}%
2634 \c@namedef{Hy@pdfversion@1.6}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{6}}%
2635 \c@namedef{Hy@pdfversion@1.7}{\def\Hy@pdf@majorversion{1}\def\Hy@pdf@mi-
norversion{7}}%
2636 \c@namedef{Hy@pdfversion@2.0}{\def\Hy@pdf@majorversion{2}\def\Hy@pdf@mi-
norversion{0}}%
2637 \def\Hy@pdf@majorversion{1}\def\Hy@pdf@minorversion{5}

Legacy name, earlier releases assumed 1.x
2638 \let\Hy@pdfversion\Hy@pdf@minorversion
2639 \def\Hy@pdf@majorminor@version{\numexpr100*\Hy@pdf@majorversion+\Hy@pdf@mi-
norversion\relax}
2640 \def\Hy@pdfmajorminor@version{\numexpr100*\Hy@pdfmajorversion+\Hy@pdfmi-
norversion\relax}

if pdfminorversion is defined, make sure pdfmajorversion is too.
2641 \@ifundefined{pdfminorversion}{}{%
2642 \@ifundefined{pdfmajorversion}{}{%
2643 \newcount\pdfmajorversion

```

```

2644 \pdfmajorversion=1
2645 }{}%
2646 }
2647 \ifx\pdfmajorversion\@undefined\else
2648 \def\Hy@pdfmajorversion{\pdfmajorversion}
2649 \fi

```

10 Options for different drivers

```

2650 \newif\ifHy@DviMode
2651 \let\Hy@DviErrMsg\ltx@empty
2652 \ifpdf
2653   \def\Hy@DviErrMsg{pdfTeX or LuaTeX is running in PDF mode}%
2654 \else
2655   \ifxetex
2656     \def\Hy@DviErrMsg{XeTeX is running}%
2657   \else
2658     \ifvtex
2659       \ifnum\OpMode=\z@
2660         \Hy@DviModetrue
2661       \else
2662         \def\Hy@DviErrMsg{VTeX is running, but not in DVI mode}%
2663       \fi
2664     \else
2665       \Hy@DviModetrue
2666     \fi
2667   \fi
2668 \fi
2669 \def\HyOpt@CheckDvi#1{%
2670   \ifHy@DviMode
2671     \expandafter\ltx@firstofone
2672   \else
2673     \Hy@Error{%
2674       Wrong DVI mode driver option `#1',\MessageBreak
2675       because \Hy@DviErrMsg
2676     }\@ehc
2677     \expandafter\ltx@gobble
2678   \fi
2679 }
2680 \DeclareVoidOption{tex4ht}{%
2681   \Hy@texhttrue
2682   \kvsetkeys{Hyp}{colorlinks=true}%
2683   \def\BeforeTeXIVht{\RequirePackage{color}}%
2684   \def\Hy@driver{htex4ht}%
2685   \def\MaybeStopEarly{%
2686     \Hy@Message{Stopped early}%
2687     \Hy@AtBeginDocument{%
2688       \PDF@FinishDoc
2689       \gdef\PDF@FinishDoc{}%
2690     }%
2691     \endinput
2692   }%
2693 }
2694 \DeclareVoidOption{pdftex}{%

```

```

2695 \ifpdf
2696   \def\Hy@driver{hpdftex}%
2697   \PassOptionsToPackage{pdftex}{color}%
2698 \else
2699   \Hy@Error{%
2700     Wrong driver option `pdftex',\MessageBreak
2701     because pdfTeX in PDF mode is not detected%
2702   }\@ehc
2703 \fi
2704 }
2705 \DeclareVoidOption{luatex}{%
2706   \ifpdf
2707     \ifx\pdfextension@\undefined
2708       \def\Hy@driver{hpdftex}%
2709       \PassOptionsToPackage{pdftex}{color}%
2710     \else
2711       \def\Hy@driver{hluatex}%
2712       \PassOptionsToPackage{luatex}{color}%
2713     \fi
2714   \else
2715     \Hy@Error{%
2716       Wrong driver option `luatex',\MessageBreak
2717       because LuaTeX in PDF mode is not detected%
2718     }\@ehc
2719   \fi
2720 }
2721 \DeclareVoidOption{nativepdf}{%
2722   \HyOpt@CheckDvi{nativepdf}{%
2723     \def\Hy@driver{hdvips}%
2724     \PassOptionsToPackage{dvips}{color}%
2725   }%
2726 }
2727 \DeclareVoidOption{dvipdfm}{%
2728   \HyOpt@CheckDvi{dvipdfm}{%
2729     \def\Hy@driver{hdvipdfm}%
2730   }%
2731 }
2732 \DeclareVoidOption{dvipdfmx}{%
2733   \HyOpt@CheckDvi{dvipdfmx}{%
2734     \def\Hy@driver{hdvipdfm}%
2735     \PassOptionsToPackage{dvipdfmx}{color}%
2736   }%
2737 }
2738 \define@key{Hyp}{dvipdfmx-outline-open}[true]{%
2739   \expandafter\ifx\csname if#1\expandafter\endcsname
2740     \csname iftrue\endcsname
2741     \chardef\SpecialDvipdfmxOutlineOpen\@ne
2742   \else
2743     \chardef\SpecialDvipdfmxOutlineOpen\z@
2744   \fi
2745 }
2746 \DeclareVoidOption{xetex}{%
2747   \ifxetex
2748     \def\Hy@driver{hxetex}%

```

```

2749 \else
2750   \Hy@Error{%
2751     Wrong driver option `xetex',\MessageBreak
2752     because XeTeX is not detected%
2753   }\@ehc
2754 \fi
2755 }
2756 \DeclareVoidOption{pdfmark}{%
2757   \HyOpt@CheckDvi{pdfmark}{%
2758     \def\Hy@driver{hdvips}%
2759   }%
2760 }
2761 \DeclareVoidOption{dvips}{%
2762   \HyOpt@CheckDvi{dvips}{%
2763     \def\Hy@driver{hdvips}%
2764     \PassOptionsToPackage{dvips}{color}%
2765   }%
2766 }
2767 \DeclareVoidOption{hypertex}{%
2768   \HyOpt@CheckDvi{hypertex}{%
2769     \def\Hy@driver{hypertex}%
2770   }%
2771 }
2772 \let\Hy@MaybeStopNow\relax
2773 \DeclareVoidOption{vtex}{%
2774   \ifvtex
2775     \ifnum 0\ifnum\OpMode<1 1\fi \ifnum\OpMode>3 1\fi =0 %
2776       \def\Hy@driver{hvtx}%
2777     \else
2778       \ifnum\OpMode=10\relax
2779         \def\Hy@driver{hvtxhtm}%
2780         \def\MaybeStopEarly{%
2781           \Hy@Message{Stopped early}%
2782           \Hy@AtBeginDocument{%
2783             \PDF@FinishDoc
2784             \gdef\PDF@FinishDoc{}%
2785           }%
2786           \endinput
2787         }%
2788       \else
2789         \Hy@Error{%
2790           Wrong driver option `vtex',\MessageBreak
2791           because of wrong OpMode (\the\OpMode)%
2792         }\@ehc
2793       \fi
2794     \fi
2795   \else
2796     \Hy@Error{%
2797       Wrong driver option `vtex',\MessageBreak
2798       because VTeX is not running%
2799     }\@ehc
2800   \fi
2801 }
2802 \DeclareVoidOption{vtxpdfmark}{%

```

```

2803 \ifvtex
2804   \ifnum 0\ifnum\OpMode<1 1\fi \ifnum\OpMode>3 1\fi =0 %
2805     \def\Hy@driver{hvtxmrk}%
2806   \else
2807     \Hy@Error{%
2808       Wrong driver option `vtexpdfmark',\MessageBreak
2809       because of wrong OpMode (\the\OpMode)%
2810     }@\ehc
2811   \fi
2812 \else
2813   \Hy@Error{%
2814     Wrong driver option `vtexpdfmark',\MessageBreak
2815     because VTeX is not running%
2816   }@\ehc
2817 \fi
2818 }
2819 \DeclareVoidOption{dviwindo}{%
2820   \HyOpt@CheckDvi{dviwindo}{%
2821     \def\Hy@driver{hdviwind}%
2822     \kvsetkeys{Hyp}{colorlinks}%
2823     \PassOptionsToPackage{dviwindo}{color}%
2824   }%
2825 }
2826 \DeclareVoidOption{dvipsone}{%
2827   \HyOpt@CheckDvi{dvipsone}{%
2828     \def\Hy@driver{hdvipson}%
2829     \PassOptionsToPackage{dvipsone}{color}%
2830   }%
2831 }
2832 \DeclareVoidOption{textures}{%
2833   \HyOpt@CheckDvi{textures}{%
2834     \def\Hy@driver{htexture}%
2835   }%
2836 }
2837 \DeclareVoidOption{latex2html}{%
2838   \Hy@Warning{Option `latex2html' is obsolete. \MessageBreak
2839   A current html.sty will do all necessary (re)definitions%
2840 }%
2841 }
2842 \DeclareVoidOption{hitex}{%
2843   \ifhint
2844     \IfFileExists{hhitex.def}%
2845       {\def\Hy@driver{hhitex}}%
2846       {\Hy@Warning{%
2847         Missing driver file `hhitex.def',\MessageBreak
2848         ignoring hitex driver%
2849       }}%
2850   \else
2851     \Hy@Error{%
2852       Wrong driver option `hitex',\MessageBreak
2853       because HiTeX is not detected%
2854     }@\ehc
2855   \fi
2856 }

```

No more special treatment for ps2pdf. Let it sink or swim.

```

2857 \DeclareVoidOption{ps2pdf}{%
2858   \HyOpt@CheckDvi{ps2pdf}{%
2859     \def\Hy@driver{dvips}%
2860     \PassOptionsToPackage{dvips}{color}%
2861   }%
2862 }
2863 \let\HyOpt@DriverFallback\ltx@empty
2864 \define@key{Hyp}{driverfallback}{%
2865   \ifHy@DviMode
2866     \def\HyOpt@DriverFallback{\#1}%
2867     \Hy@Match\HyOpt@DriverFallback{}{%
2868       ^(|dvipdfm|dvipdfmx|dvips|dvipsone|dviwindo|hypertex|ps2pdf|%
2869       latex2html|tex4ht)$}%
2870   }{}{%
2871     \Hy@Warning{%
2872       Invalid driver `#\#1' for option\MessageBreak
2873       `driverfallback'%
2874     }%
2875     \let\HyOpt@DriverFallback\ltx@empty
2876   }%
2877 \fi
2878 }
2879 \let\HyOpt@CustomDriver\ltx@empty
2880 \define@key{Hyp}{customdriver}{%
2881   \IfFileExists{\#1.def}{%
2882     \def\HyOpt@CustomDriver{\#1}%
2883   }{%
2884     \Hy@Warning{%
2885       Missing driver file `#\#1.def',\MessageBreak
2886       ignoring custom driver%
2887     }%
2888   }%
2889 }
```

11 Options to add extra features

Make included figures (assuming they use the standard graphics package) be hyperlinks. Off by default. Needs more work.

```

2890 \define@key{Hyp}{hyperfigures}[true]{%
2891   \Hy@boolkey{hyperfigures}{\#1}%
2892 }
```

The automatic footnote linking can be disabled by option hyperfootnotes.

```

2893 \define@key{Hyp}{hyperfootnotes}[true]{%
2894   \Hy@boolkey{hyperfootnotes}{\#1}%
2895 }
```

Set up back-referencing to be hyper links, by page, slide or section number,

```

2896 \def\back@none{none}
2897 \def\back@section{section}
2898 \def\back@page{page}
2899 \def\back@slide{slide}
2900 \define@key{Hyp}{backref}[section]{%
```

```

2901 \lowercase{\def\Hy@tempa{#1}}%
2902 \ifx\Hy@tempa\empty
2903   \let\Hy@tempa\back@section
2904 \fi
2905 \ifx\Hy@tempa\Hy@false
2906   \let\Hy@tempa\back@none
2907 \fi
2908 \ifx\Hy@tempa\back@slide
2909   \let\Hy@tempa\back@section
2910 \fi
2911 \ifx\Hy@tempa\back@page
2912   \PassOptionsToPackage{hyperpageref}{backref}%
2913   \Hy@backreftrue
2914 \else
2915   \ifx\Hy@tempa\back@section
2916     \PassOptionsToPackage{hyperref}{backref}%
2917     \Hy@backreftrue
2918 \else
2919   \ifx\Hy@tempa\back@none
2920     \Hy@backreffalse
2921 \else
2922   \Hy@WarnOptionValue{#1}{backref}{%
2923     `section', `slide', `page', `none', \MessageBreak
2924     or `false'}%
2925 \fi
2926 \fi
2927 \fi
2928 }
2929 \define@key{Hyp}{pagebackref}[true]{%
2930   \edef\Hy@tempa{#1}%
2931   \lowercase{\expandafter{%
2932     \expandafter\def\expandafter\Hy@tempa\expandafter{\Hy@tempa}%
2933   }}%
2934 \ifx\Hy@tempa\empty
2935   \let\Hy@tempa\Hy@true
2936 \fi
2937 \ifx\Hy@tempa\Hy@true
2938   \PassOptionsToPackage{hyperpageref}{backref}%
2939   \Hy@backreftrue
2940 \else
2941   \ifx\Hy@tempa\Hy@false
2942     \Hy@backreffalse
2943 \else
2944   \Hy@WarnOptionValue{#1}{pagebackref}{`true' or `false'}%
2945 \fi
2946 \fi
2947 }

```

Make index entries be links back to the relevant pages. By default this is turned on, but may be stopped.

```

2948 \define@key{Hyp}{hyperindex}[true]{%
2949   \Hy@boolkey{hyperindex}{#1}%
2950 }

```

Configuration of encap char.

```

2951 \define@key{Hyp}{encap}{\|}{%
2952   \def\HyInd@EncapChar{\#1}%
2953 }

```

12 Language options

The `\autoref` feature depends on the language.

```

2954 \def\HyLang@afrikaans{%
2955   \def\equationautorefname{Vergelyking}%
2956   \def\footnoteautorefname{Voetnota}%
2957   \def\itemautorefname{Item}%
2958   \def\figureautorefname{Figuur}%
2959   \def\tableautorefname{Tabel}%
2960   \def\partautorefname{Deel}%
2961   \def\appendixautorefname{Bylae}%
2962   \def\chapterautorefname{Hoofstuk}%
2963   \def\sectionautorefname{Afdeling}%
2964   \def\subsectionautorefname{Subafdeling}%
2965   \def\subsubsectionautorefname{Subsubafdeling}%
2966   \def\paragraphautorefname{Paragraaf}%
2967   \def\ subparagraphautorefname{Subparagraaf}%
2968   \def\FancyVerbLineautorefname{Lyn}%
2969   \def\theoremautorefname{Teorema}%
2970   \def\pageautorefname{Bladsy}%
2971 }
2972 \def\HyLang@english{%
2973   \def\equationautorefname{Equation}%
2974   \def\footnoteautorefname{footnote}%
2975   \def\itemautorefname{item}%
2976   \def\figureautorefname{Figure}%
2977   \def\tableautorefname{Table}%
2978   \def\partautorefname{Part}%
2979   \def\appendixautorefname{Appendix}%
2980   \def\chapterautorefname{chapter}%
2981   \def\sectionautorefname{section}%
2982   \def\subsectionautorefname{subsection}%
2983   \def\subsubsectionautorefname{subsubsection}%
2984   \def\paragraphautorefname{paragraph}%
2985   \def\ subparagraphautorefname{subparagraph}%
2986   \def\FancyVerbLineautorefname{line}%
2987   \def\theoremautorefname{Theorem}%
2988   \def\pageautorefname{page}%
2989 }
2990 \def\HyLang@french{%
2991   \def\equationautorefname{'equation}%
2992   \def\footnoteautorefname{note}%
2993   \def\itemautorefname{item}%
2994   \def\figureautorefname{figure}%
2995   \def\tableautorefname{tableau}%
2996   \def\partautorefname{partie}%
2997   \def\appendixautorefname{annexe}%
2998   \def\chapterautorefname{chapitre}%
2999   \def\sectionautorefname{section}%

```

```

3000 \def\subsectionautorefname{sous-section}%
3001 \def\subsubsectionautorefname{sous-sous-section}%
3002 \def\paragraphautorefname{paragraphe}%
3003 \def\ subparagraphautorefname{sous-paragraphe}%
3004 \def\FancyVerbLineautorefname{ligne}%
3005 \def\theoremautorefname{th\'eor\`eme}%
3006 \def\pageautorefname{page}%
3007 }
3008 \def\HyLang@german{%
3009 \def\equationautorefname{Gleichung}%
3010 \def\footnoteautorefname{Fu\ss note}%
3011 \def\itemautorefname{Punkt}%
3012 \def\figureautorefname{Abbildung}%
3013 \def\tableautorefname{Tabelle}%
3014 \def\partautorefname{Teil}%
3015 \def\appendixautorefname{Anhang}%
3016 \def\chapterautorefname{Kapitel}%
3017 \def\sectionautorefname{Abschnitt}%
3018 \def\subsectionautorefname{Unterabschnitt}%
3019 \def\subsubsectionautorefname{Unterunterabschnitt}%
3020 \def\paragraphautorefname{Absatz}%
3021 \def\ subparagraphautorefname{Unterabsatz}%
3022 \def\FancyVerbLineautorefname{Zeile}%
3023 \def\theoremautorefname{Theorem}%
3024 \def\pageautorefname{Seite}%
3025 }
3026 \def\HyLang@italian{%
3027 \def\equationautorefname{Equazione}%
3028 \def\footnoteautorefname{nota}%
3029 \def\itemautorefname{punto}%
3030 \def\figureautorefname{Figura}%
3031 \def\tableautorefname{Tabella}%
3032 \def\partautorefname{Parte}%
3033 \def\appendixautorefname{Appendice}%
3034 \def\chapterautorefname{Capitolo}%
3035 \def\sectionautorefname{sezione}%
3036 \def\subsectionautorefname{sottosezione}%
3037 \def\subsubsectionautorefname{sottosottosezione}%
3038 \def\paragraphautorefname{paragrafo}%
3039 \def\ subparagraphautorefname{sottoparagrafo}%
3040 \def\FancyVerbLineautorefname{linea}%
3041 \def\theoremautorefname{Teorema}%
3042 \def\pageautorefname{Pag.\C}%
3043 }
3044 \def\HyLang@magyarl{%
3045 \def\equationautorefname{Egyenlet}%
3046 \def\footnoteautorefname{l\'abjegyzet}%
3047 \def\itemautorefname{Elem}%
3048 \def\figureautorefname{\'Abra}%
3049 \def\tableautorefname{T\'abl\'azat}%
3050 \def\partautorefname{R\'esz}%
3051 \def\appendixautorefname{F\"uggel\'ek}%
3052 \def\chapterautorefname{fejezet}%
3053 \def\sectionautorefname{szakasz}%

```

```

3054 \def\subsectionautorefname{alszakasz}%
3055 \def\subsubsectionautorefname{alalszakasz}%
3056 \def\paragraphautorefname{bekezd\'es}%
3057 \def\ subparagraphautorefname{albekezd\'es}%
3058 \def\FancyVerbLineautorefname{sor}%
3059 \def\theoremautorefname{T\'etel}%
3060 \def\pageautorefname{oldal}%
3061 }
3062 \def\HyLang@portuges{%
3063 \def\equationautorefname{Equa\c c c\~ao}%
3064 \def\footnoteautorefname{Nota de rodap\'e}%
3065 \def\itemautorefname{Item}%
3066 \def\figureautorefname{Figura}%
3067 \def\tableautorefname{Tabela}%
3068 \def\partautorefname{Parte}%
3069 \def\appendixautorefname{Ap\^endice}%
3070 \def\chapterautorefname{Cap\'itulo}%
3071 \def\sectionautorefname{Se\c c c\~ao}%
3072 \def\subsectionautorefname{Subse\c c c\~ao}%
3073 \def\subsubsectionautorefname{Subsubse\c c c\~ao}%
3074 \def\paragraphautorefname{par\'agrafo}%
3075 \def\ subparagraphautorefname{subpar\'agrafo}%
3076 \def\FancyVerbLineautorefname{linha}%
3077 \def\theoremautorefname{Teorema}%
3078 \def\pageautorefname{P\'agina}%
3079 }

```

Next commented section for Russian is provided by Olga Lapko.

Next follow the checked reference names with commented variants and explanations. All they are abbreviated and they won't create a grammatical problems in the *middle* of sentences.

The most weak points in these abbreviations are the `\equationautorefname`, `\theoremautorefname` and the `\FancyVerbLineautorefname`. But those three, and also the `\footnoteautorefname` are not *too* often referenced. Another rather weak point is the `\appendixautorefname`.

```
3080 \def\HyLang@russian{%
```

The abbreviated reference to the equation: it is not for “the good face of the book”, but maybe it will be better to get the company for the `\theoremautorefname`?

```
3081 \def\equationautorefname{\cyr\cyrv\cyry\cyrr.}%
```

The name of the equation reference has common form for both nominative and accusative but changes in other forms, like “of `\autoref{auto}`” etc. The full name must follow full name of the `\theoremautorefname`.

```
3082 % \def\equationautorefname{%
3083 %   \cyr\cyrv\cyry\cyrr\cyla\cyrh\cyre\cyrn\cyri\cyre
3084 % }%
```

The variant of footnote has abbreviation form of the synonym of the word “footnote”. This variant of abbreviated synonym has alternative status (maybe obsolete?).

```
3085 \def\footnoteautorefname{%
3086   \cyr\cyrp\cyro\cyrd\crys\cyrt\cyrr.\ \cyrp\cyrr\cyri\cyrm.%}
3087 }%
```

Commented form of the full synonym for “footnote”. It has common form for both nominative and accusative but changes in other forms, like “of \autoref{auto}”

```
3088 % \def\footnoteautorefname{%
3089 %   \cyr\cyrp\cyro\cyrd\crys\cyrt\cyrr\cyro\cyrch\cyrn\cyro\cyre\ %
3090 %   \cyp\cyrr\cyri\cyrm\cyre\cyrch\cyla\cyrn\cyri\cyre
3091 % }%
```

Commented forms of the “footnote”: have different forms, the same is for the nominative and accusative. (The others needed?)

```
3092 % \def\Nomfootnoteautorefname{\cyr\crys\cyrn\cyro\crys\cyrk\cyra}%
3093 % \def\Accfootnoteautorefname{\cyr\crys\cyrn\cyro\crys\cyrk\cyrn}%
```

Name of the list item, can be confused with the paragraph reference name, but reader could understand meaning from context(?). Commented variant has common form for both nominative and accusative but changes in other forms, like “of \autoref{auto}” etc.

```
3094 \def\itemautorefname{\cyr\cyrp.}%
3095 % \def\itemautorefname{\cyr\cyrp\cyrn\cyrk\cyrn\cyrk\cyrt}%
```

Names of the figure and table have stable (standard) abbreviation forms. No problem in the middle of sentence.

```
3096 \def\figureautorefname{\cyr\cyrr\cyri\crys.}%
3097 \def\tableautorefname{\cyr\cyrt\cyra\cyrb\cyrn.}%
```

Names of the part, chapter, section(s) have stable (standard) abbreviation forms. No problem in the middle of sentence.

```
3098 \def\partautorefname{\cyr\cyrch.}%
3099 \def\chapterautorefname{\cyr\cyrg\cyrn.}%
3100 \def\sectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%
```

Name of the appendix can use this abbreviation, but it is not standard for books, i.e, not for “the good face of the book”. Commented variant has common form for both nominative and accusative but changes in other forms, like “of \autoref{auto}” etc.

```
3101 \def\appendixautorefname{\cyr\cyrp\cyrr\cyri\cyrn.}%
3102 % \def\appendixautorefname{%
3103 %   \cyr\cyrp\cyrr\cyri\cyrn\cyro\cyrzh\cyre\cyrn\cyri\cyre
3104 % }%
```

The sectioning command have stable (almost standard) and common abbreviation form for all levels (the meaning of these references visible from the section number). No problem.

```
3105 \def\subsectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%
3106 \def\subsubsectionautorefname{\cyr\cyrr\cyra\cyrz\cyrd.}%
```

The names of references to paragraphs also have stable (almost standard) and common abbreviation form for all levels (the meaning of these references is visible from the section number). No problem in the middle of sentence.

```
3107 \def\paragraphautorefname{\cyr\cyrp.}%
3108 \def\subparagraphautorefname{\cyr\cyrp.}%
```

Commented variant can be used in books but since it has common form for both nominative and accusative but it changes in other forms, like “of \autoref{auto}” etc.

```
3109 % \def\paragraphautorefname{\cyr\cyrp\cyrn\cyrk\cyrt}%
3110 % \def\subparagraphautorefname{\cyr\cyrp\cyrn\cyrk\cyrt}%
```

The name of verbatim line. Here could be a standard of the abbreviation (used very rare). But the author preprint publications (which have not any editor or corrector) can use this abbreviation for the page reference. So the meaning of the line reference can be read as reference to the page.

```
3111 \def\fancyverblineautorefname{\cyr\cyrs\cyrt\cyrr.}%
```

Commented names of the “verbatim line”: have different forms, also the nominative and accusative.

```
3112 % \def\nomfancyverblineautorefname{\cyr\cyrs\cyrt\cyrr\cyro\cyrk\cyra}%
3113 % \def\accfancyverblineautorefname{\cyr\cyrs\cyrt\cyrr\cyro\cyrk\cyru}%
```

The alternative, ve-e-e-ery professional abbreviation, was used in typography markup for typesetters.

```
3114 % \def\fancyverblineautorefname{\cyr\cyrs\cyrt\cyrr\cyrk.}%
```

The names of theorem: if we want have “the good face of the book”, so the theorem reference must have the full name (like equation reference). But ...

```
3115 \def\theoremautorefname{\cyr\cyrt\cyre\cyro\cyrr.}%
```

Commented forms of the “theorem”: have different forms, also the nominative and accusative.

```
3116 % \def\nomtheoremautorefname{\cyr\cyrt\cyre\cyro\cyrr\cyre\cyrm\cyra}%
3117 % \def\acctheoremautorefname{\cyr\cyrt\cyre\cyro\cyrr\cyre\cyrm\cyru}%
```

Name of the page stable (standard) abbreviation form. No problem.

```
3118 \def\pageautorefname{\cyr\cyrs.}%
3119 }
```

```
3120 \def\hylang@spanish{%
3121   \def\equationautorefname{Ecuaci\'on}%
3122   \def\footnoteautorefname{Nota a pie de p\'agina}%
3123   \def\itemautorefname{Elemento}%
3124   \def\figureautorefname{Figura}%
3125   \def\tableautorefname{Tabla}%
3126   \def\partautorefname{Parte}%
3127   \def\appendixautorefname{Ap\'endice}%
3128   \def\chapterautorefname{Cap\'itulo}%
3129   \def\sectionautorefname{Secci\'on}%
3130   \def\subsectionautorefname{Subsecci\'on}%
3131   \def\subsubsectionautorefname{Subsubsecci\'on}%
3132   \def\paragraphautorefname{P\'arrafo}%
3133   \def\ subparagraphautorefname{Subp\'arrafo}%
3134   \def\fancyverblineautorefname{L\'inea}%
3135   \def\theoremautorefname{Teorema}%
3136   \def\pageautorefname{P\'agina}%
3137 }
```

```
3138 \def\hylang@catalan{%
3139   \def\equationautorefname{Equaci\'o}%
3140   \def\footnoteautorefname{Nota al peu de p\'agina}%
3141   \def\itemautorefname{Element}%
3142   \def\figureautorefname{Figura}%
3143   \def\tableautorefname{Taula}%
3144   \def\partautorefname{Part}%
3145   \def\appendixautorefname{Ap\'endix}%
3146   \def\chapterautorefname{Cap\'itol}%
}
```

```

3147 \def\sectionautorefname{Secci\'o}%
3148 \def\subsectionautorefname{Subsecci\'o}%
3149 \def\subsubsectionautorefname{Subsubsecci\'o}%
3150 \def\paragraphautorefname{Par\`agraf}%
3151 \def\subparagraphautorefname{Subpar\`agraf}%
3152 \def\FancyVerbLineautorefname{L\'inia}%
3153 \def\theoremautorefname{Teorema}%
3154 \def\pageautorefname{P\'agina}%
3155 }

3156 \def\HyLang@vietnamese{%
3157   \def\equationautorefname{Ph\uuhorn{} \ohorn{} ng tr\`inh}%
3158   \def\footnoteautorefname{Ch\u th\ich}%
3159   \def\itemautorefname{m\du{c}}%
3160   \def\figureautorefname{H\`inh}%
3161   \def\tableautorefname{B\h{a}ng}%
3162   \def\partautorefname{Ph\`acircumflex{n}}%
3163   \def\appendixautorefname{Ph\d{u} l\d{u}c}%
3164   \def\chapterautorefname{ch\uhorn{} \ohorn{} ng}%
3165   \def\sectionautorefname{m\du{c}}%
3166   \def\subsectionautorefname{m\du{c}}%
3167   \def\subsubsectionautorefname{m\du{c}}%
3168   \def\paragraphautorefname{\dj{o}\d{a}n}%
3169   \def\subparagraphautorefname{\dj{o}\d{a}n}%
3170   \def\FancyVerbLineautorefname{d\`ong}%
3171   \def\theoremautorefname{\DJ{} \d{i}nh l'y}%
3172   \def\pageautorefname{Trang}%
3173 }

```

Greek, see github issue 52

```

3174 \def\HyLang@greek{%
3175   \def\equationautorefname{\textEpsilon\textxi\acctonus\textiota\textsigma\tex-
tomega\textsigma\texteta}%
3176   \def\footnoteautorefname{\textupsilon\textpi\textomicron\textsigma\tex-
teta\textmu\textepsilon\acctonus\textiota\textomega\textsigma\texteta}%
3177   \def\itemautorefname{\textalpha\textnu\texttau\textiota\textkappa\textep-
sil\acctonus\textiota\textmu\textepsilon\textnu\textomicron}%
3178   \def\figureautorefname{\textSigma\textchi\acctonus\texteta\textmu\textal-
pha}%
3179   \def\tableautorefname{\textPi\acctonus\textiota\textnu\textalpha\textkappa\text-
alpha}%
3180   \def\partautorefname{\textMu\acctonus\textepsilon\textrho\textomicron\textvar-
sigma}%
3181   \def\appendixautorefname{\textPi\textalpha\textrho\acctonus\textalpha\text-
trho\texttau\texteta\textmu\textalpha}%
3182   \def\chapterautorefname{\textkappa\textepsilon\textphi\acctonus\textal-
pha\textlambda\textalpha\textiota\textomicron}%
3183   \def\sectionautorefname{\textepsilon\texttau\textnu\acctonus\textomicron\text-
tau\textalpha}%
3184   \def\subsectionautorefname{\textupsilon\textpi\textomicron\textepsilon\textnu\ac-
tonos\textomicron\texttau\textalpha}%
3185   \def\subsubsectionautorefname{\textupsilon\textpi\textomicron-\textupsilon\textpi\textomicron\text-
tau\textalpha}%
3186   \def\paragraphautorefname{\textpi\textalpha\textrho\acctonus\textalpha\textgamma\text-
rho\textalpha\textphi\textomicron\textvarsigma}%
3187   \def\subparagraphautorefname{\textupsilon\textpi\textomicron\textpi\text-
}
```

```

3188 \def\fancyverblineautorefname{\textgamma\textrho\textalpha\textmu\textmu\textmu\ac-
3189 ctonos\texteta}%
3190 \def\theoremautorefname{\textTheta\textepsilon\textmu\textalpha\textmu\textmu\textmu\ac-
3191 ttonos\texteta}%
3192 \def\HyLang@dutch{%
3193   \def\equationautorefname{Vergelijking}%
3194   \def\footnoteautorefname{voetnoot}%
3195   \def\itemautorefname{punt}%
3196   \def\figureautorefname{Figuur}%
3197   \def\tableautorefname{Tabel}%
3198   \def\partautorefname{Deel}%
3199   \def\appendixautorefname{Bijlage}%
3200   \def\chapterautorefname{hoofdstuk}%
3201   \def\sectionautorefname{paragraaf}%
3202   \def\subsectionautorefname{deelparagraaf}%
3203   \def\subsubsectionautorefname{deel-deelparagraaf}%
3204   \def\paragraphautorefname{alinea}%
3205   \def\ subparagraphautorefname{deelalinea}%
3206   \def\fancyverblineautorefname{regel}%
3207   \def\theoremautorefname{Stelling}%
3208   \def\pageautorefname{pagina}%
3209 }
3210 \def\HyLang@norsk{%
3211   \def\equationautorefname{Ligning}%
3212   \def\footnoteautorefname{fotnote}%
3213   \def\itemautorefname{element}%
3214   \def\figureautorefname{Figur}%
3215   \def\tableautorefname{Tabell}%
3216   \def\partautorefname{Del}%
3217   \def\appendixautorefname{Tillegg}%
3218   \def\chapterautorefname{kapittel}%
3219   \def\sectionautorefname{seksjon}%
3220   \def\subsectionautorefname{underseksjon}%
3221   \def\subsubsectionautorefname{under-underseksjon}%
3222   \def\paragraphautorefname{avsnitt}%
3223   \def\ subparagraphautorefname{underavsnitt}%
3224   \def\fancyverblineautorefname{Linje}%
3225   \def\theoremautorefname{Teorem}%
3226   \def\pageautorefname{side}%
3227 }
3228 \def\HyLang@danish{%
3229   \def\equationautorefname{Ligning}%
3230   \def\footnoteautorefname{fodnote}%
3231   \def\itemautorefname{element}%
3232   \def\figureautorefname{Figur}%
3233   \def\tableautorefname{Tabel}%
3234   \def\partautorefname{Del}%
3235   \def\appendixautorefname{Bilag}%
3236   \def\chapterautorefname{kapitel}%

```

```

3237 \def\sectionautorefname{sektion}%
3238 \def\subsectionautorefname{under-sektion}%
3239 \def\subsubsectionautorefname{under-under-sektion}%
3240 \def\paragraphautorefname{afsnit}%
3241 \def\ subparagraphautorefname{underafsnit}%
3242 \def\FancyVerbLineautorefname{linje}%
3243 \def\theoremautorefname{Teorem}%
3244 \def\pageautorefname{side}%
3245 }
3246 \def\HyLang@swedish{%
3247 \def\equationautorefname{Ekvation}%
3248 \def\footnoteautorefname{fotnot}%
3249 \def\itemautorefname{punkt}%
3250 \def\figureautorefname{Figur}%
3251 \def\tableautorefname{Tabell}%
3252 \def\partautorefname{Del}%
3253 \def\appendixautorefname{Bilaga}%
3254 \def\chapterautorefname{kapitel}%
3255 \def\sectionautorefname{avsnitt}%
3256 \def\subsectionautorefname{underavsnitt}%
3257 \def\subsubsectionautorefname{under-underavsnitt}%
3258 \def\paragraphautorefname{paragraf}%
3259 \def\ subparagraphautorefname{underparagraf}%
3260 \def\FancyVerbLineautorefname{linje}%
3261 \def\theoremautorefname{Teorem}%
3262 \def\pageautorefname{sida}%
3263 }

```

Instead of package babel's definition of `\addto` the implementation of package varioref is used. Additionally argument `#1` is checked for `\relax`.

```

3264 \def\HyLang@addto#1#2{%
3265 #2%
3266 \@temptokena{#2}%
3267 \ifx#1\relax
3268 \let#1\empty
3269 \fi
3270 \ifx#1\@undefined
3271 \edef#1{\the\@temptokena}%
3272 \else
3273 \toks@\expandafter{#1}%
3274 \edef#1{\the\toks@\the\@temptokena}%
3275 \fi
3276 \@temptokena{} \toks@\@temptokena
3277 }

3278 \def\HyLang@DeclareLang#1#2#3{%
3279 \@ifpackagewith{babel}{#1}{%
3280 \expandafter\HyLang@addto
3281 \csname extras#1\expandafter\endcsname
3282 \csname HyLang@#2\endcsname
3283 \begingroup
3284 \edef\x{\endgroup
3285 #3%
3286 }%
3287 \x

```

```

3288  \@namedef{HyLang@#1@done}{}%
3289 }{}%
3290 \begingroup
3291 \edef\x{\#1\#2}%
3292 \noexpand\ifx\#2\relax
3293 \errmessage{No definitions for language \#2' found!}%
3294 \noexpand\fi
3295 \endgroup
3296 \noexpand\define@key{Hyp}{#1}[]{%
3297 \noexpand\@ifundefined{HyLang@#1@done}{}{%
3298 \noexpand\HyLang@addto{\noexpand##1}{\noexpand##2}%
3299 ##3}%
3300 \noexpand\@namedef{HyLang@#1@done}{}%
3301 }{}%
3302 }%
3303 }%
3304 \expandafter\x\csname extras#1\expandafter\endcsname
3305 \csname HyLang@#2\endcsname
3306 }
3307 \HyLang@DeclareLang{english}{english}{}%
3308 \HyLang@DeclareLang{UKenglish}{english}{}%
3309 \HyLang@DeclareLang{british}{english}{}%
3310 \HyLang@DeclareLang{USenglish}{english}{}%
3311 \HyLang@DeclareLang{american}{english}{}%
3312 \HyLang@DeclareLang{german}{german}{}%
3313 \HyLang@DeclareLang{austrian}{german}{}%
3314 \HyLang@DeclareLang{ngerman}{german}{}%
3315 \HyLang@DeclareLang{naustrian}{german}{}%
3316 \HyLang@DeclareLang{nswissgerman}{german}{}%
3317 \HyLang@DeclareLang{swissgerman}{german}{}%
3318 \HyLang@DeclareLang{russian}{russian}{\noexpand\hypersetup{unicode}}%
3319 \HyLang@DeclareLang{brazil}{portuges}{}%
3320 \HyLang@DeclareLang{brazilian}{portuges}{}%
3321 \HyLang@DeclareLang{portuguese}{portuges}{}%
3322 \HyLang@DeclareLang{spanish}{spanish}{}%
3323 \HyLang@DeclareLang{catalan}{catalan}{}%
3324 \HyLang@DeclareLang{afrikaans}{afrikaans}{}%
3325 \HyLang@DeclareLang{french}{french}{}%
3326 \HyLang@DeclareLang{frenchb}{french}{}%
3327 \HyLang@DeclareLang{francais}{french}{}%
3328 \HyLang@DeclareLang{acadian}{french}{}%
3329 \HyLang@DeclareLang{canadien}{french}{}%
3330 \HyLang@DeclareLang{italian}{italian}{}%
3331 \HyLang@DeclareLang{magyar}{magyar}{}%
3332 \HyLang@DeclareLang{hungarian}{magyar}{}%
3333 \HyLang@DeclareLang{greek}{greek}{}%
3334 \HyLang@DeclareLang{dutch}{dutch}{}%
3335 \HyLang@DeclareLang{norsk}{norsk}{}%
3336 \HyLang@DeclareLang{norwegian}{norsk}{}%
3337 \HyLang@DeclareLang{danish}{danish}{}%
3338 \HyLang@DeclareLang{swedish}{swedish}{}%

```

More work is needed in case of options vietnamese and vietnam.

```
3339 \DeclareVoidOption{vietnamese}{%
```

```

3340 \HyLang@addto\extrasvietnamese\HyLang@vietnamese
3341 \Hy@AtEndOfPackage{%
3342   \@ifundefined{T@PU}{}{%
3343     \input{puvnenc.def}%
3344   }%
3345 }%
3346 }
3347 \DeclareVoidOption{vietnam}{%
3348   \HyLang@addto\extrasvietnam\HyLang@vietnamese
3349   \Hy@AtEndOfPackage{%
3350     \@ifundefined{T@PU}{}{%
3351       \input{puvnenc.def}%
3352     }%
3353   }%
3354 }

```

Similar for option arabic that just loads the additions to PU encoding for Arabi.

```

3355 \DeclareVoidOption{arabic}{%
3356   \Hy@AtEndOfPackage{%
3357     \@ifundefined{T@PU}{}{%
3358       \input{puarenc.def}%
3359     }%
3360   }%
3361 }

```

13 Options to change appearance of links

Colouring links at the L^AT_EX level is useful for debugging, perhaps.

```

3362 \define@key{Hyp}{colorlinks}[true]{%
3363   \Hy@boolkey{colorlinks}{#1}%
3364 }
3365 \DeclareVoidOption{hidelinks}{%
3366   \Hy@colorlinksfalse
3367   \Hy@ocgcolorlinksfalse
3368   \Hy@frenchlinksfalse
3369   \def\Hy@colorlink##1{\begingroup}%
3370   \def\Hy@endcolorlink{\endgroup}%
3371   \def\@pdfborder{0 0 0}%
3372   \let\@pdfborderstyle\ltx@empty
3373 }
3374 \define@key{Hyp}{ocgcolorlinks}[true]{%
3375   \Hy@boolkey{ocgcolorlinks}{#1}%
3376 }
3377 \Hy@AtBeginDocument{%
3378   \begingroup
3379   \@ifundefined{OBJ@OCG@view}{%
3380     \ifHy@ocgcolorlinks
3381       \Hy@Warning{%
3382         Driver does not support `ocgcolorlinks', \MessageBreak
3383         using `colorlinks' instead%
3384       }%
3385     \fi
3386   }%

```

```

3387 \endgroup
3388 }
3389 \define@key{Hyp}{frenchlinks}[true]{%
3390 \Hy@boolkey{frenchlinks}{#1}%
3391 }

```

14 Bookmarking

```

3392 \begingroup\expandafter\expandafter\expandafter\endgroup
3393 \expandafter\ifx\csname chapter\endcsname\relax
3394 \def\toclevel@part{0}%
3395 \else
3396 \def\toclevel@part{-1}%
3397 \fi
3398 \def\toclevel@chapter{0}
3399 \def\toclevel@section{1}
3400 \def\toclevel@subsection{2}
3401 \def\toclevel@subsubsection{3}
3402 \def\toclevel@paragraph{4}
3403 \def\toclevel@subparagraph{5}
3404 \def\toclevel@figure{0}
3405 \def\toclevel@table{0}

3406 \define@key{Hyp}{bookmarks}[true]{%
3407 \Hy@boolkey{bookmarks}{#1}%
3408 }

3409 \define@key{Hyp}{bookmarksopen}[true]{%
3410 \Hy@boolkey{bookmarksopen}{#1}%
3411 }

```

The depth of the outlines is controlled by option `bookmarksdepth`. The option acts globally and distinguishes three cases:

- `bookmarksdepth`: Without value hyperref uses counter `tocdepth` (compatible behaviour and default).
- `bookmarksdepth=<number>`: the depth is set to `<number>`.
- `bookmarksdepth=<name>`: The `<name>` must not start with a number or minus sign. It is a document division name (part, chapter, section, ...). Internally the value of macro `\toclevel@<name>` is used.

```

3412 \let\Hy@bookmarksdepth\c@tocdepth
3413 \define@key{Hyp}{bookmarksdepth}[]{%
3414 \begingroup
3415 \edef\x{\#1}%
3416 \ifx\x\empty
3417 \global\let\Hy@bookmarksdepth\c@tocdepth
3418 \else
3419 \c@ifundefined{toclevel@\x}{%
3420 \c@onelevel@sanitize\x
3421 \edef\y{\expandafter\c@car\x\c@nil}%
3422 \ifcase 0\expandafter\ifx\y-1\fi
3423 \expandafter\ifnum\expandafter`y>47 %
3424 \expandafter\ifnum\expandafter`y<58 1\fi\fi\relax

```

```

3425      \Hy@Warning{Unknown document division name (\x)}%
3426      \else
3427          \setbox\z@\=\hbox{%
3428              \count@\=\\x
3429              \xdef\Hy@bookmarksdepth{\the\count@}%
3430          }%
3431      \fi
3432  }%}
3433      \setbox\z@\=\hbox{%
3434          \count@\=\csname toclevel@\x\endcsname
3435          \xdef\Hy@bookmarksdepth{\the\count@}%
3436      }%
3437  }%
3438      \fi
3439  \endgroup
3440 }

```

‘bookmarksopenlevel’ to specify the open level. From Heiko Oberdiek.

```

3441 \define@key{Hyp}{bookmarksopenlevel}{%
3442   \def\@bookmarksopenlevel{\#1}%
3443 }
3444 \def\@bookmarksopenlevel{\maxdimen}
3445 % `bookmarkstype' to specify which `toc' file to mimic
3446 \define@key{Hyp}{bookmarkstype}{%
3447   \def\Hy@bookmarkstype{\#1}%
3448 }
3449 \def\Hy@bookmarkstype{toc}

```

Richard Curnow <richard@curnow.demon.co.uk> suggested this functionality. It adds section numbers etc to bookmarks.

```

3450 \define@key{Hyp}{bookmarksnumbered}{[true]}{%
3451   \Hy@boolkey{bookmarksnumbered}{\#1}%
3452 }

```

Option CJKbookmarks enables the patch for CJK bookmarks.

```

3453 \define@key{Hyp}{CJKbookmarks}{[true]}{%
3454   \Hy@boolkey{CJKbookmarks}{\#1}%
3455 }
3456 \def\Hy@temp{\#1{%
3457   \expandafter\Hy@@temp\csname \#1color\endcsname{\#1}%
3458 }
3459 \def\Hy@@temp{\#1\#2\#3{%
3460   \define@key{Hyp}{\#2color}{%
3461     \HyColor@HyperrefColor{\#1}\#1%
3462   }%
3463   \def{\#1}{\#3}%
3464 }
3465 \Hy@temp{link}{red}
3466 \Hy@temp{anchor}{black}
3467 \Hy@temp{cite}{green}
3468 \Hy@temp{file}{cyan}
3469 \Hy@temp{url}{magenta}
3470 \Hy@temp{menu}{red}
3471 \Hy@temp{run}{\@filecolor}
3472 \define@key{Hyp}{pagecolor}{%

```

```

3473 \Hy@WarningPageColor
3474 }
3475 \def\Hy@WarningPageColor{%
3476 \Hy@WarningNoLine{Option `pagecolor' is not available anymore}%
3477 \global\let\Hy@WarningPageColor\relax
3478 }
3479 \define@key{Hyp}{allcolors}{%
3480 \HyColor@HyperrefColor{\#1}\@linkcolor
3481 \HyColor@HyperrefColor{\#1}\@anchorcolor
3482 \HyColor@HyperrefColor{\#1}\@citecolor
3483 \HyColor@HyperrefColor{\#1}\@filecolor
3484 \HyColor@HyperrefColor{\#1}\@urlcolor
3485 \HyColor@HyperrefColor{\#1}\@menucolor
3486 \HyColor@HyperrefColor{\#1}\@runcolor
3487 }
3488 \def\hyperbaseurl#1{\def\@baseurl{#1}}
3489 \define@key{Hyp}{baseurl}{\hyperbaseurl{#1}}
3490 \let\@baseurl\empty
3491 \def\hyperlinkfileprefix#1{\def\Hy@linkfileprefix{#1}}
3492 \define@key{Hyp}{linkfileprefix}{\hyperlinkfileprefix{#1}}
3493 \hyperlinkfileprefix{file:}

```

15 PDF-specific options

\@pdfpagetransition The value of option pdfpagetransition is stored in \@pdfpagetransition. Its initial value is set to \relax in order to be able to differentiate between a not used option and an option with an empty value.

```

3494 \let\@pdfpagetransition\relax
3495 \define@key{Hyp}{pdfpagetransition}{%
3496 \def\@pdfpagetransition{\#1}%
3497 }

```

\@pdfpageduration The value of option pdfpageduration is stored in \@pdfpageduration. Its initial value is set to \relax in order to be able to differentiate between a not used option and an option with an empty value.

```

3498 \let\@pdfpageduration\relax
3499 \define@key{Hyp}{pdfpageduration}{%
3500 \def\@pdfpageduration{\#1}%
3501 \Hy@Match\@pdfpageduration{}{%
3502 ^([0-9]+\.[0-9]*|[0-9]*\.[0-9]+)$%
3503 }{%
3504 \Hy@Warning{%
3505 Invalid value `@\pdfpageduration'\MessageBreak
3506 of option `pdfpageduration'\MessageBreak
3507 is replaced by an empty value}%
3508 }%
3509 \let\@pdfpageduration\ltx\empty
3510 }%
3511 }

```

The value of the bordercolor options are not processed by the color package. Therefore the value consists of space separated rgb numbers in the range 0 until 1.

Package `xcolor` provides `\XC@bordercolor` since version 1.1. If the two spaces in the color specification are missing, then the value is processed as color specification from package `xcolor` by using `\XC@bordercolor` (since `xcolor` 2004/05/09 v1.11, versions 2005/03/24 v2.02 until 2006/11/28 v2.10 do not work because of a bug that is fixed in 2007/01/21 v2.11).

```

3512 \def\Hy@ColorList{cite,file,link,menu,run,url}
3513 \@for\Hy@temp:=\Hy@ColorList\do{%
3514   \edef\Hy@temp{%
3515     \noexpand\define@key{Hyp}{\Hy@temp bordercolor}{%
3516       \noexpand\HyColor@HyperrefBorderColor
3517       {##1}%
3518       \expandafter\noexpand\csname @\Hy@temp bordercolor\endcsname
3519       {hyperref}%
3520       {\Hy@temp bordercolor}%
3521     }%
3522   }%
3523   \Hy@temp
3524 }
3525 \define@key{Hyp}{pagebordercolor}{%
3526   \Hy@WarningPageBorderColor
3527 }
3528 \def\Hy@WarningPageBorderColor{%
3529   \Hy@WarningNoLine{Option `pagebordercolor' is not available anymore}%
3530   \global\let\Hy@WarningPageBorderColor\relax
3531 }
3532 \define@key{Hyp}{allbordercolors}{%
3533   \def\Hy@temp##1##2{%
3534     \HyColor@HyperrefBorderColor{##1}##1{hyperref}{##2bordercolor}%
3535   }%
3536   \Hy@temp{@citebordercolor{cite}}%
3537   \Hy@temp{@filebordercolor{file}}%
3538   \Hy@temp{@linkbordercolor{link}}%
3539   \Hy@temp{@menubordercolor{menu}}%
3540   \Hy@temp{@runbordercolor{run}}%
3541   \Hy@temp{@urlbordercolor{url}}%
3542 }
3543 \define@key{Hyp}{pdfhighlight}{\def\@pdfhighlight{##1}}
3544 \Hy@DefNameKey{pdfhighlight}{%
3545   \do{/I}{Invert}%
3546   \do{/N}{None}%
3547   \do{/O}{Outline}%
3548   \do{/P}{Push}%
3549 }
3550 \def\Hy@setpdfhighlight{%
3551   \ifx\@pdfhighlight\empty
3552   \else
3553     /H\@pdfhighlight
3554   \fi
3555 }
3556 \define@key{Hyp}{pdfborder}{%
3557   \let\Hy@temp\@pdfborder
3558   \def\@pdfborder{##1}%
3559   \Hy@Match\@pdfborder{}{%

```

```

3560  ^\HyPat@NonNegativeReal/ %
3561  \HyPat@NonNegativeReal/ %
3562  \HyPat@NonNegativeReal/%
3563  ( ?\| \HyPat@NonNegativeReal/( \HyPat@NonNegativeReal/*])?$$%
3564 }{}{%
3565 \Hy@Warning{%
3566 Invalid value `@\pdfborder'\MessageBreak
3567 for option `pdfborder'.\MessageBreak
3568 Option setting is ignored%
3569 }%
3570 \let\@pdfborder\Hy@temp
3571 }%
3572 }
3573 \define@key{Hyp}{pdfborderstyle}{%
3574 \let\Hy@temp\@pdfborderstyle
3575 \def\@pdfborderstyle{\#1}%
3576 \Hy@Match\@pdfborderstyle{}{%
3577 ^%
3578 (* /Type */Border%
3579 | */W +\HyPat@NonNegativeReal/%
3580 | */S *[SDBIU]%
3581 | */D *[(*(\HyPat@NonNegativeReal/( \HyPat@NonNegativeReal/)?)?)?]%
3582 )* *$%
3583 }{}{%
3584 \Hy@Warning{%
3585 Invalid value `@\pdfborderstyle'\MessageBreak
3586 for option `pdfborderstyle'.\MessageBreak
3587 Option setting is ignored%
3588 }%
3589 \let\@pdfborderstyle\Hy@temp
3590 }%
3591 }
3592 \def\Hy@setpdfborder{%
3593 \ifx\@pdfborder\@empty
3594 \else
3595 /Border[\@pdfborder]%
3596 \fi
3597 \ifx\@pdfborderstyle\@empty
3598 \else
3599 /BS<<@\pdfborderstyle>>%
3600 \fi
3601 }
3602 \Hy@DefNameKey{pdffagemode}{%
3603 \do{UseNone}{}%
3604 \do{UseOutlines}{}%
3605 \do{UseThumbs}{}%
3606 \do{FullScreen}{}%
3607 \do{UseOC}{PDF 1.5}%
3608 \do{UseAttachments}{PDF 1.6}%
3609 }
3610 \Hy@DefNameKey{pdfnonfullscreenpagemode}{%
3611 \do{UseNone}{}%
3612 \do{UseOutlines}{}%
3613 \do{UseThumbs}{}%

```

```

3614 \do{FullScreen}{}
3615 \do{UseOC}{PDF 1.5}{}
3616 \do{UseAttachments}{PDF 1.6}{}
3617 }
3618 \Hy@DefNameKey{pdfdirection}{%
3619 \do{L2R}{Left to right}{}
3620 \do{R2L}{Right to left}{}
3621 }
3622 \Hy@DefNameKey{pdfviewarea}{%
3623 \do{MediaBox}{}
3624 \do{CropBox}{}
3625 \do{BleedBox}{}
3626 \do{TrimBox}{}
3627 \do{ArtBox}{}
3628 }
3629 \Hy@DefNameKey{pdfviewclip}{%
3630 \do{MediaBox}{}
3631 \do{CropBox}{}
3632 \do{BleedBox}{}
3633 \do{TrimBox}{}
3634 \do{ArtBox}{}
3635 }
3636 \Hy@DefNameKey{pdfprintarea}{%
3637 \do{MediaBox}{}
3638 \do{CropBox}{}
3639 \do{BleedBox}{}
3640 \do{TrimBox}{}
3641 \do{ArtBox}{}
3642 }
3643 \Hy@DefNameKey{pdfprintclip}{%
3644 \do{MediaBox}{}
3645 \do{CropBox}{}
3646 \do{BleedBox}{}
3647 \do{TrimBox}{}
3648 \do{ArtBox}{}
3649 }
3650 \Hy@DefNameKey{pdfprintscaling}{%
3651 \do{AppDefault}{}
3652 \do{None}{}
3653 }
3654 \Hy@DefNameKey{pdfduplex}{%
3655 \do{Simplex}{}
3656 \do{DuplexFlipShortEdge}{}
3657 \do{DuplexFlipLongEdge}{}
3658 }
3659 \Hy@DefNameKey{pdffpicktraybypdfsize}{%
3660 \do{true}{}
3661 \do{false}{}
3662 }
3663 \define@key{Hyp}{pdfprintpagerange}{%
3664 \def\@pdfprintpagerange{\#1}%
3665 }
3666 \Hy@DefNameKey{pdfnumcopies}{%
3667 \do{2}{two copies}%

```

```

3668 \do{3}{three copies}%
3669 \do{4}{four copies}%
3670 \do{5}{five copies}%
3671 }

3672 \define@key{Hyp}{pdfusetitle}[true]{%
3673   \Hy@boolkey{pdfusetitle}{#1}%
3674 }
3675 \def\HyXeTeX@CheckUnicode{%
3676   \ifxetex
3677     \ifHy@unicode
3678     \else
3679       \Hy@WarningNoLine{%
3680         XeTeX driver only supports unicode.\MessageBreak
3681         Enabling option `unicode'%
3682       }%
3683       \kvsetkeys{Hyp}{unicode}%
3684     \fi
3685   \else
3686     \let\HyXeTeX@CheckUnicode\relax
3687   \fi
3688 }
3689 \def\HyPsd@PrerenderUnicode#1{%
3690   \begingroup
3691   \expandafter\ifx\csname PrerenderUnicode\endcsname\relax
3692   \else
3693     \sbox0{%
3694       \let\GenericInfo\gobbletwo
3695       \let\GenericWarning\gobbletwo
3696       \let\GenericError\gobblefour
3697       \PrerenderUnicode{#1}%
3698     }%
3699   \fi
3700   \endgroup
3701 }
3702 \define@key{Hyp}{pdftitle}{%
3703   \AddToDocumentProperties[hyperref]{pdftitle}{#1}%
3704   \HyXeTeX@CheckUnicode
3705   \HyPsd@PrerenderUnicode{#1}%
3706   \pdfstringdef\@pdftitle{#1}%
3707 }
3708 \define@key{Hyp}{pdfauthor}{%
3709   \AddToDocumentProperties[hyperref]{pdfauthor}{#1}%
3710   \HyXeTeX@CheckUnicode
3711   \HyPsd@PrerenderUnicode{#1}%
3712   \pdfstringdef\@pdfauthor{#1}%
3713 }
3714 \define@key{Hyp}{pdfproducer}{%
3715   \AddToDocumentProperties[hyperref]{pdfproducer}{#1}%
3716   \HyXeTeX@CheckUnicode
3717   \HyPsd@PrerenderUnicode{#1}%
3718   \pdfstringdef\@pdfproducer{#1}%
3719 }
3720 \define@key{Hyp}{pdfcreator}{%
3721   \AddToDocumentProperties[hyperref]{pdfcreator}{#1}%

```

```

3722 \HyXeTeX@CheckUnicode
3723 \HyPsd@PrerenderUnicode{#1}%
3724 \pdfstringdef\@pdfcreator{#1}%
3725 }
3726 \define@key{Hyp}{addtopdfcreator}{%
3727 \HyXeTeX@CheckUnicode
3728 \HyPsd@PrerenderUnicode{#1}%
3729 \pdfstringdef\@pdfcreator{\@pdfcreator, #1}%
3730 }
3731 \define@key{Hyp}{pdfcreationdate}{%
3732 \begingroup
3733 \Hy@unicodedeffalse
3734 \pdfstringdef\@pdfcreationdate{#1}%
3735 \endgroup
3736 }
3737 \define@key{Hyp}{pdfmoddate}{%
3738 \begingroup
3739 \Hy@unicodedeffalse
3740 \pdfstringdef\@pdfmoddate{#1}%
3741 \endgroup
3742 }
3743 \define@key{Hyp}{pdfsubject}{%
3744 \AddToDocumentProperties[hyperref]{pdfsubject}{#1}%
3745 \HyXeTeX@CheckUnicode
3746 \HyPsd@PrerenderUnicode{#1}%
3747 \pdfstringdef\@pdfsubject{#1}%
3748 }
3749 \define@key{Hyp}{pdfkeywords}{%
3750 \AddToDocumentProperties[hyperref]{pdfkeywords}{#1}%
3751 \HyXeTeX@CheckUnicode
3752 \HyPsd@PrerenderUnicode{#1}%
3753 \pdfstringdef\@pdfkeywords{#1}%
3754 }
3755 \define@key{Hyp}{pdftrapped}{%
3756 \lowercase{\edef\Hy@temp{#1}}%
3757 \ifx\Hy@temp\HyInfo@trapped@true
3758 \def\@pdftrapped{True}%
3759 \else
3760 \ifx\Hy@temp\HyInfo@trapped@false
3761 \def\@pdftrapped{False}%
3762 \else
3763 \ifx\Hy@temp\HyInfo@trapped@unknown
3764 \def\@pdftrapped{Unknown}%
3765 \else
3766 \ifx\Hy@temp\empty
3767 \else
3768 \Hy@Warning{%
3769 Unsupported value `#1'\MessageBreak
3770 for option `pdftrapped'%
3771 }%
3772 \fi
3773 \def\@pdftrapped{}%
3774 \fi
3775 \fi

```

```

3776 \fi
3777 }
3778 \def\HyInfo@trapped@true{true}
3779 \def\HyInfo@trapped@false{false}
3780 \def\HyInfo@trapped@unknown{unknown}
3781 \def\HyInfo@TrappedUnsupported{%
3782 \ifx\@pdftrapped\@empty
3783 \else
3784 \Hy@Warning{`pdftrapped' is not supported by this driver}%
3785 \gdef\HyInfo@TrappedUnsupported{}%
3786 \fi
3787 }
3788 \define@key{Hyp}{pdfinfo}{%
3789 \kvsetkeys{pdfinfo}{#1}%
3790 }
3791 \def\Hy@temp#1{%
3792 \lowercase{\Hy@temp@A{#1}{#1}}%
3793 }
3794 \def\Hy@temp@A#1#2{%
3795 \define@key{pdfinfo}{#2}{%
3796 \hypersetup{pdf#1={##1}}%
3797 }%
3798 }
3799 \Hy@temp{Title}
3800 \Hy@temp{Author}
3801 \Hy@temp{Keywords}
3802 \Hy@temp{Subject}
3803 \Hy@temp{Creator}
3804 \Hy@temp{Producer}
3805 \Hy@temp{CreationDate}
3806 \Hy@temp{ModDate}
3807 \Hy@temp{Trapped}
3808 \newif\ifHyInfo@AddonUnsupported
3809 \kv@set@family@handler{pdfinfo}{%
3810 \HyInfo@AddonHandler{#1}{#2}%
3811 }
3812 \let\HyInfo@do\relax
3813 \def\HyInfo@AddonHandler#1#2{%
3814 \ifx\kv@value\relax
3815 \Hy@Warning{%
3816 Option `pdfinfo': ignoring key `\\kv@key' without value}%
3817 }%
3818 \else
3819 \EdefEscapeName\HyInfo@KeyEscaped{\kv@key}%
3820 \EdefUnescapeName\HyInfo@Key{\HyInfo@KeyEscaped}%
3821 \expandafter\ifx\csname KV@pdfinfo@\HyInfo@Key\endcsname\relax
3822 \ifHyInfo@AddonUnsupported
3823 \Hy@Warning{%
3824 This driver does not support additional\MessageBreak
3825 information entries, therefore\MessageBreak
3826 `\\kv@key' is ignored}%
3827 }%
3828 \else
3829 \def\HyInfo@tmp##1{%

```

```

3830   \kv@define@key{pdfinfo}{##1}{%
3831     \HyXeTeX@CheckUnicode
3832     \HyPsd@PrerenderUnicode{####1}%
3833     \pdfstringdef\HyInfo@Value{####1}%
3834     \global\expandafter
3835     \let\csname HyInfo@Value\endcsname
3836       \HyInfo@Value
3837   }%
3838 }%
3839 \expandafter\HyInfo@tmp\expandafter{\HyInfo@Key}%
3840 \global\expandafter
3841 \let\csname KV@pdfinfo@\HyInfo@Key\expandafter\endcsname
3842   \csname KV@pdfinfo@\HyInfo@Key\endcsname
3843 \xdef\HyInfo@AddonList{%
3844   \HyInfo@AddonList
3845   \HyInfo@do{\HyInfo@Key}%
3846 }%
3847 \expandafter\kv@parse@normalized\expandafter{%
3848   \HyInfo@Key={#2}%
3849 }{%
3850   \kv@processor@default{pdfinfo}%
3851 }%
3852 \fi
3853 \else
3854   \expandafter\kv@parse@normalized\expandafter{%
3855   \HyInfo@Key={#2}%
3856 }{%
3857   \kv@processor@default{pdfinfo}%
3858 }%
3859 \fi
3860 \fi
3861 }
3862 \def\HyInfo@GenerateAddons{%
3863   \ifHyInfo@AddonUnsupported
3864     \def\HyInfo@Addons{}%
3865   \else
3866     \begingroup
3867       \toks@{}%
3868       \def\HyInfo@do##1{%
3869         \edef\EscapeName\HyInfo@Key{##1}%
3870         \edef\x{%
3871           \toks@{%
3872             \the\toks@
3873             \HyInfo@Key(\csname HyInfo@Value@##1\endcsname)%
3874           }%
3875         }%
3876         \x
3877       }%
3878       \HyInfo@AddonList
3879       \edef\x{\endgroup
3880         \def\noexpand\HyInfo@Addons{\the\toks@}%
3881       }%
3882       \x
3883     \fi

```

```

3884 }
3885 \global\let\HyInfo@AddonList\ltx@empty
3886 \define@key{Hyp}{pdfview}{\calculate@pdfview#1 \\}
3887 \define@key{Hyp}{pdflinkmargin}{\setpdflinkmargin{\#1}}
3888 \let\setpdflinkmargin\@gobble
3889 \def\calculate@pdfview#1 #2\\{%
3890   \def\@pdfview{\#1}%
3891   \ifx\\#2\\%
3892     \def\@pdfviewparams{-32768}%
3893   \else
3894     \def\@pdfviewparams{\#2}%
3895   \fi
3896 }
3897 \def\Hy@number{\#1}%
3898 \the\numexpr\#1\relax
3899 }%
3900 \define@key{Hyp}{pdfstartpage}{%
3901   \ifx\\#1\\%
3902     \let\@pdfstartpage\ltx@empty
3903   \else
3904     \edef\@pdfstartpage{\Hy@number{\#1}}%
3905   \fi
3906 }%
3907 \define@key{Hyp}{pdfstartview}{%
3908   \ifx\\#1\\%
3909     \let\@pdfstartview\ltx@empty
3910   \else
3911     \def\@pdfstartview{/#1}%
3912   \fi
3913 }
3914 \def\HyPat@NonNegativeReal/{%
3915   \*[([0-9]+\.?[0-9]*|[0-9]*\.[0-9]+)]*%
3916 }
3917 \define@key{Hyp}{pd fremotestartview}{%
3918   \ifx\\#1\\%
3919     \def\@pd fremotestartview{/Fit}%
3920   \else
3921     \edef\@pd fremotestartview{\#1}%
3922     \Hy@Match\@pd fremotestartview{}{%
3923       ^XYZ(%
3924         ()| %
3925         (null|-?\HyPat@NonNegativeReal/) %
3926         (null|-?\HyPat@NonNegativeReal/) %
3927         (null|\HyPat@NonNegativeReal/)%
3928       )| % end of "XYZ"
3929       Fit(%
3930         ()| %
3931         B| %
3932         (H|V|BH|BV)(%
3933           ()| %
3934             (null|\HyPat@NonNegativeReal/)%
3935           )| %
3936         R %
3937       \HyPat@NonNegativeReal/ %

```

```

3938          \HyPat@NonNegativeReal/ %
3939          \HyPat@NonNegativeReal/ %
3940          \HyPat@NonNegativeReal/%
3941      )% end of "Fit"
3942  )$%
3943 }{%
3944 \Hy@Warning{%
3945   Invalid value `@\pdfremotestartview\MessageBreak
3946   of `pdfremotestartview\MessageBreak
3947   is replaced by `Fit'%}
3948 }%
3949 \let@\pdfremotestartview\@empty
3950 }%
3951 \ifx@\pdfremotestartview\@empty
3952   \def@\pdfremotestartview{/Fit}%
3953 \else
3954   \edef@\pdfremotestartview{/\@pdfremotestartview}%
3955 \fi
3956 \fi
3957 }
3958 \define@key{Hyp}{pdffpagescrop}{\edef@\pdffpagescrop{\#1}}
3959 \define@key{Hyp}{pdftoolbar}[true]{%
3960   \Hy@boolkey{pdftoolbar}{\#1}%
3961 }
3962 \define@key{Hyp}{pdfmenubar}[true]{%
3963   \Hy@boolkey{pdfmenubar}{\#1}%
3964 }
3965 \define@key{Hyp}{pdfwindowui}[true]{%
3966   \Hy@boolkey{pdfwindowui}{\#1}%
3967 }
3968 \define@key{Hyp}{pdffitwindow}[true]{%
3969   \Hy@boolkey{pdffitwindow}{\#1}%
3970 }
3971 \define@key{Hyp}{pdfcenterwindow}[true]{%
3972   \Hy@boolkey{pdfcenterwindow}{\#1}%
3973 }
3974 \define@key{Hyp}{pdfdisplaydoctitle}[true]{%
3975   \Hy@boolkey{pdfdisplaydoctitle}{\#1}%
3976 }
3977 \define@key{Hyp}{pdfa}[true]{%
3978   \Hy@boolkey{pdfa}{\#1}%
3979 }
3980 \define@key{Hyp}{pdfnewwindow}[true]{%
3981   \def\Hy@temp{\#1}%
3982   \ifx\Hy@temp\@empty
3983     \Hy@pdfnewwindowsetfalse
3984   \else
3985     \Hy@pdfnewwindowsettrue
3986   \Hy@boolkey{pdfnewwindow}{\#1}%
3987 \fi
3988 }
3989 \def\Hy@SetNewWindow{%
3990   \ifHy@pdfnewwindowset
3991     /NewWindow %

```

```

3992   \ifHy@pdfnewwindow true\else false\fi
3993   \fi
3994 }
3995 \Hy@DefNameKey{pdfpagelayout}{%
3996   \do{SinglePage}{}%
3997   \do{OneColumn}{}%
3998   \do{TwoColumnLeft}{}%
3999   \do{TwoColumnRight}{}%
4000   \do{TwoPageLeft}{PDF 1.5}%
4001   \do{TwoPageRight}{PDF 1.5}%
4002 }
4003 \define@key{Hyp}{pdflang}{%
4004   \edef@\pdflang{\#1}%
4005   \def\Hy@temp{\relax}%
4006   \ifx@\pdflang\Hy@temp
4007     \let@\pdflang\relax
4008   \fi
4009   \ifx@\pdflang\relax
4010   \else
4011     \ifx@\pdflang\ltx@empty
4012   \else

```

Test according to ABNF of RFC 3066.

```

4013   \Hy@Match@\pdflang{icase}{%
4014     ^%
4015     [a-z]{1,8}%
4016     (-[a-z0-9]{1,8})*%
4017     $%
4018   }{%

```

Test according to ABNF of RFC 5646.

```

4019   \Hy@Match@\pdflang{icase}{%
4020     ^%
4021     (%
4022       % langtag
4023         (% language
4024           [a-z]{2,3}%
4025           ([a-z]{3}(-[a-z]{3}){0,2})?% extlang
4026           |[a-z]{4}% reserved for future use
4027           |[a-z]{5,8}% registered language subtag
4028         )%
4029         (-[a-z]{4})?% script
4030         (-([a-z]{2}|[0-9]{3}))?% region
4031         (-([a-z]{5,8}|[0-9][a-z0-9]{3}))?% variant
4032         (-[0-9a-wyz](-[a-z0-9]{2,8})+)*% extension
4033         (-x(-[a-z0-9]{1,8})+)?% privateuse
4034       % privateuse
4035       |x-(a-z0-9){1,8})+%
4036       % grandfathered/irregular
4037       |en-GB-oed%
4038       |i-(amil|bnn|default|enochian|hak|klingon|lux|%
4039         mingo|navajo|pwn|tao|tay|tsu)%
4040       |sgn-(BE-FR|BE-NL|CH-DE)%
4041       % grandfathered/regular
4042       |art-lojban%

```

```

4043     |cel-gaulish%
4044     |no-(bok|nyn)%
4045     |zh-(guoyu|hakka|min|min-nan|xiang)%
4046     )%
4047     $%
4048     }{%

```

Test for unique extensions.

```

4049     \Hy@Match{-\@pdflang}{icase}{-[a-wyz0-9]}{%
4050         \Hy@Match{\@pdflang}{icase}{^x-}{}{%
4051             % remove privateuse
4052             \edef\Hy@temp{-\@pdflang}%
4053             \Hy@Match\Hy@temp{icase}{%
4054                 ^
4055                 (%
4056                 (-[a-wyz0-9]|-[a-z0-9]{2,8})*%
4057                 )%
4058                 -x-%
4059             }{%
4060                 \edef\Hy@temp{%
4061                     \expandafter\strip@prefix\pdflastmatch1%
4062                 }%
4063             }{%
4064             \Hy@Match\Hy@temp{icase}{%
4065                 (-[a-wyz0-9]-).*\ltx@backslashchar1%
4066             }{%
4067                 \Hy@Warning{%
4068                     Invalid language identifier `#1'\MessageBreak
4069                     for option `pdflang', because it violates\MessageBreak
4070                     well-formedness defined in RFC 4646\MessageBreak
4071                     by duplicate singleton subtags%
4072                 }%
4073                 \let\@pdflang\relax
4074             }{%
4075             }%
4076         }{%

```

User-assigned country codes are forbidden in language tags (RFC 3066).

```

4077     \ifx\@pdflang\relax
4078     \else
4079         \Hy@Match{\@pdflang}{icase}{%
4080             ^
4081             [a-zA-Z]{2}-%
4082             (%
4083                 aa|AA|%
4084                 [qQ][m-zA-Z]|%
4085                 [xX][a-zA-Z]|%
4086                 zz|ZZ%
4087             )%
4088             (-|$)%
4089         }{%
4090             \Hy@Warning{%
4091                 Invalid language identifier `#1'\MessageBreak
4092                 for option `pdflang' because of invalid country code%
4093                 \MessageBreak

```

```

4094           in second subtag (RFC 3066)%
4095       }%
4096       \let\@pdflang\relax
4097   }{ }%
4098   \fi
4099 }{ %
4100   \Hy@Warning{%
4101     Invalid language identifier `#1'\MessageBreak
4102     for option `pdflang', because it violates\MessageBreak
4103     well-formedness defined in RFC 5646%
4104   }%
4105   \let\@pdflang\relax
4106 }{ %
4107 }{ %
4108   \Hy@Warning{%
4109     Invalid language identifier `#1'\MessageBreak
4110     for option `pdflang' (RFC 3066)%
4111   }%
4112   \let\@pdflang\relax
4113 }{ %
4114   \fi
4115 }{ %
4116 }
4117 \define@key{Hyp}{pdffpagelabels}[true]{%
4118   \Hy@boolkey{pdffpagelabels}{#1}%
4119 }
4120 \define@key{Hyp}{pdfescapeform}[true]{%
4121   \Hy@boolkey{pdfescapeform}{#1}%
4122 }

```

Default values:

```

4123 \def\@linkbordercolor{1 0 0}
4124 \def\@urlbordercolor{0 1 1}
4125 \def\@menubordercolor{1 0 0}
4126 \def\@filebordercolor{0 .5 .5}
4127 \def\@runbordercolor{0 .7 .7}
4128 \def\@citebordercolor{0 1 0}
4129 \def\@pdfhighlight{/I}
4130 \let\@pdftitle\ltx@empty
4131 \let\@pdfauthor\ltx@empty
4132 \let\@pdfproducer\relax
4133 \def\@pdfcreator{LaTeX with hyperref}
4134 \let\@pdfcreationdate\ltx@empty
4135 \let\@pdfmoddate\ltx@empty
4136 \let\@pdfsubject\ltx@empty
4137 \let\@pdfkeywords\ltx@empty
4138 \let\@pdftrapped\ltx@empty
4139 \let\@pdfpagescrop\ltx@empty
4140 \def\@pdfstartview{/Fit}
4141 \def\@pdfremotestartview{/Fit}
4142 \def\@pdfstartpage{1}
4143 \let\@pdfprintpagerange\ltx@empty
4144 \let\@pdflang\relax
4145 \let\PDF@SetupDoc\@empty
4146 \let\PDF@FinishDoc\@empty

```

```

4147 \let\phantomsection\@empty
4148 \let\special@paper\@empty
4149 \def\HyperDestNameFilter#1{\#1}
4150 \Hy@AtBeginDocument{%
4151   \begingroup
4152     \edef\x{\ifdim\stockheight>\z@\stockheight\else\paperheight\fi}%
4153     \dimen@=\x\relax
4154     \ifdim\dimen@>\z@
4155     \else
4156       \dimen@=11in\relax
4157       \Hy@WarningNoLine{%
4158         Height of page (\expandafter\string\x) %
4159         is invalid (\the\x),\MessageBreak
4160         using 11in%
4161       }%
4162     \fi
4163     \dimen@=0.99626401\dimen@
4164     \xdef\Hy@pageheight{\strip@pt\dimen@}%
4165   \endgroup
4166 }
4167 \def\HyInd@EncapChar{\|}
```

Allow the user to use `\ExecuteOptions` in the cfg file even though this package does not use the normal option mechanism. Use `\hyper@normalise` as a scratch macro, since it is going to be defined in a couple of lines anyway.

```

4168 \let\hyper@normalise\ExecuteOptions
4169 \let\ExecuteOptions\hypersetup
4170 \Hy@RestoreCatcodes
4171 \InputIfFileExists{hyperref.cfg}{}{%
4172 \Hy@SetCatcodes
4173 \let\ExecuteOptions\hyper@normalise
4174 \ifx\Hy@MaybeStopNow\relax
4175 \else
4176   \Hy@stoppedearlytrue
4177   \expandafter\Hy@MaybeStopNow
4178 \fi
4179 \Hy@stoppedearlyfalse
```

To add flexibility, we will not use the ordinary processing of package options, but put them through the `keyval` package. This section was written by David Carlisle.

```

4180 \SetupKeyvalOptions{family=Hyp}
4181 \DeclareLocalOptions{%
4182   a4paper,a5paper,b5paper,letterpaper,legalpaper,executivepaper%
4183 }
```

Add option `tex4ht` if package `tex4ht` is loaded.

```

4184 \@ifpackagewith{hyperref}{tex4ht}{%
4185 }{%
4186   \@ifpackageloaded{tex4ht}{%
4187     \PassOptionsToPackage{tex4ht}{hyperref}%
4188   }{%
4189     \ltx@ifundefined{HCode}{%
4190       }{%
4191         \begingroup
4192           \def\Hy@pkg{tex4ht}%
4193         }
```

```

4193 \def\Hy@temp@a#1\RequirePackage[#2]#3#4\Hy@NIL{%
4194   \def\Hy@param{#2#3}%
4195   \ifx\Hy@param\ltx@empty
4196     \expandafter\ltx@gobble
4197   \else
4198     \def\Hy@param{#3}%
4199     \ifx\Hy@param\Hy@pkg
4200       \PassOptionsToPackage{#2}{tex4ht}%
4201       \expandafter\expandafter\expandafter\@gobble
4202     \else
4203       \expandafter\expandafter\expandafter\ltx@firstofone
4204     \fi
4205   \fi
4206   {\Hy@temp@a#4\Hy@NIL}%
4207 }%
4208 \expandafter
4209 \Hy@temp@a\@documentclasshook\RequirePackage[]{}{\Hy@NIL}
4210 \endgroup
4211 \PassOptionsToPackage{tex4ht}{hyperref}%
4212 }%
4213 }%
4214 }

4215 \let\ReadBookmarks\relax
4216 \ProcessKeyvalOptions{Hyp}

```

After processing options.

15.1 Package xspace support

```

4217 \def\Hy@xspace@end{%
4218   \ltx@ifundefined{xspaceaddexceptions}{%
4219     \Hy@AtBeginDocument{%
4220       \ltx@ifundefined{xspaceaddexceptions}{%
4221         }{%
4222           \def\Hy@xspace@end{%
4223             \ltx@gobble{end for xspace}%
4224           }%
4225         \xspaceaddexceptions{%
4226           \Hy@xspace@end,\hyper@linkend,\hyper@anchorend
4227         }%
4228       }%
4229     }%
4230   }{%
4231   \def\Hy@xspace@end{%
4232     \ltx@gobble{end for xspace}%
4233   }%
4234   \xspaceaddexceptions{\Hy@xspace@end,\hyper@linkend,\hyper@anchorend}%
4235 }

```

15.2 Option draft

```

4236 \Hy@AtBeginDocument{%
4237   \ifHy@draft
4238     \let\hyper@anchor\@gobble
4239     \gdef\hyper@link#1#2#3{#3\Hy@xspace@end}%

```

```

4240 \def\hyper@anchorstart{\#1\#2{#2\Hy@xspace@end}%
4241 \def\hyper@anchorend{\Hy@xspace@end}%
4242 \let\hyper@linkstart\gobbletwo
4243 \def\hyper@linkend{\Hy@xspace@end}%
4244 \def\hyper@linkurl{\#1\#2{#1\Hy@xspace@end}%
4245 \def\hyper@linkfile{\#1\#2\#3{#1\Hy@xspace@end}%
4246 \def\hyper@link{\#1\#2\#3\#4{#4\Hy@xspace@end}%
4247 \def\Acrobatmenu{\#1\#2{\leavevmode\#2\Hy@xspace@end}%
4248 \let\PDF@SetupDoc\empty
4249 \let\PDF@FinishDoc\empty
4250 \let\ReadBookmarks\relax
4251 \let\WriteBookmarks\relax
4252 \Hy@Warning{Draft mode on}%
4253 \fi
4254 \Hy@DisableOption{draft}%
4255 \Hy@DisableOption{nolinks}%
4256 \Hy@DisableOption{final}%
4257 }

```

15.3 PDF/A

```

4258 \Hy@DisableOption{pdfa}
4259 \ifHy@pdfa
4260 \ifnum \Hy@pdf@majorminor@version< 104
4261 \kvsetkeys{Hyp}{pdfversion=1.4}%
4262 \fi
4263 \Hy@DisableOption{pdfversion}%
4264 \def\Hy@Acrobatmenu{\#1\#2{%
4265 \leavevmode
4266 \begingroup
4267 \edef\x{\#1}%
4268 \onelevel@sanitize\x
4269 \ifx\x\Hy@NextPage
4270 \let\y=Y%
4271 \else
4272 \ifx\x\Hy@PrevPage
4273 \let\y=Y%
4274 \else
4275 \ifx\x\Hy@FirstPage
4276 \let\y=Y%
4277 \else
4278 \ifx\x\Hy@LastPage
4279 \let\y=Y%
4280 \else
4281 \let\y=N%
4282 \fi
4283 \fi
4284 \fi
4285 \fi
4286 \expandafter\endgroup
4287 \ifx\y Y%
4288 \else
4289 \Hy@Error{%
4290 PDF/A: Named action `#1' is not permitted}%
4291 }@\ehc

```

```

4292      {#2}%
4293      \expandafter\@gobble
4294      \fi
4295  }%
4296 \def\Hy@temp#1{%
4297   \expandafter\def\csname Hy@#1\endcsname{#1}%
4298   \expandafter\@onelvelsanitize\csname Hy@#1\endcsname
4299 }%
4300 \Hy@temp{NextPage}%
4301 \Hy@temp{PrevPage}%
4302 \Hy@temp{FirstPage}%
4303 \Hy@temp{LastPage}%
4304 \else
4305 \def\Hy@Acrobatmenu#1#2{\leavevmode}%
4306 \fi

```

15.4 Patch for babel's \texttilde

Babel does not define \texttilde in NFSS2 manner, so the NFSS2 definitions of PD1 or PU encoding is not compatible. To fix this, \texttilde is defined in babel manner.

change 2020-10-10: no trace of \texttilde can be found in the three languages spanish, galician and estonian so the patch has been removed as outdated.

```

4307 \def\Hy@wrapper@babel#1#2{%
4308   \begingroup
4309   \Hy@safe@activestruue
4310   \set@display@protect
4311   \edef\x{#2}%
4312   \onelevelsanitize\x
4313   \toks@{#1}%
4314   \edef\x{\endgroup\the\toks@\{x\}}%
4315   \x
4316 }
4317 \def\Hy@WrapperDef#1{%
4318   \begingroup
4319   \escapechar=\m@ne
4320   \xdef\Hy@gtemp{%
4321     \expandafter\noexpand\csname HyWrap@\string#1\endcsname
4322   }%
4323   \endgroup
4324   \edef#1{%
4325     \noexpand\Hy@wrapper@babel
4326     \expandafter\noexpand\Hy@gtemp
4327   }%
4328   \expandafter\def\Hy@gtemp
4329 }

4330 \ifHy@hyperfigures
4331   \Hy@Info{Hyper figures ON}%
4332 \else
4333   \Hy@Info{Hyper figures OFF}%
4334 \fi
4335 \ifHy@nesting
4336   \Hy@Info{Link nesting ON}%
4337 \else

```

```

4338 \Hy@Info{Link nesting OFF}%
4339 \fi
4340 \ifHy@hyperindex
4341 \Hy@Info{Hyper index ON}%
4342 \else
4343 \Hy@Info{Hyper index OFF}%
4344 \fi
4345 \ifHy@plainpages
4346 \Hy@Info{Plain pages ON}%
4347 \else
4348 \Hy@Info{Plain pages OFF}%
4349 \fi
4350 \ifHy@backref
4351 \Hy@Info{Backreferencing ON}%
4352 \else
4353 \Hy@Info{Backreferencing OFF}%
4354 \fi
4355 \ifHy@implicit
4356 \Hy@Info{Implicit mode ON; LaTeX internals redefined}%
4357 \else
4358 \Hy@Info{Implicit mode OFF; no redefinition of LaTeX internals}%
4359 \def\MaybeStopEarly{%
4360   \Hy@Message{Stopped early}%
4361   \Hy@AtBeginDocument{%
4362     \PDF@FinishDoc
4363     \gdef\PDF@FinishDoc{}%
4364   }%
4365   \endinput
4366 }%
4367 \Hy@AtBeginDocument{%
4368   \let\autoref\ref
4369   \let\autopageref\pageref
4370   \ifx\@pdfpagemode\@empty
4371     \gdef\@pdfpagemode{UseNone}%
4372   \fi
4373   \global\Hy@backreffalse
4374 }%
4375 \Hy@AtEndOfPackage{%
4376   \global\let\ReadBookmarks\relax
4377   \global\let\WriteBookmarks\relax
4378 }%
4379 \fi
4380 \Hy@DisableOption{implicit}

```

15.4.1 Driver loading

Ensure that `\stockwidth` and `\stockheight` are defined

```

4381 \@ifundefined{stockwidth}{\newdimen\stockwidth}{}%
4382 \@ifundefined{stockheight}{\newdimen\stockheight}{}%
4383 \Hy@AtEndOfPackage{%
4384   \@ifpackageloaded{tex4ht}{%
4385     \def\Hy@driver{htex4ht}%
4386     \Hy@texhttrue

```

```
4387 }{)%
```

Some drivers can be detected. Check for these drivers, whether the given driver option is ok. Otherwise force the right driver or use the default driver.

```
4388 \ifx\Hy@driver\@empty
4389 \else
4390   \ifx\pdfextension\@undefined
4391     \def\Hy@temp{hpdftex}%
4392   \else
4393     \def\Hy@temp{hluatex}%
4394   \fi
4395 \ifpdf
4396   \ifx\Hy@driver\Hy@temp
4397   \else
4398     \Hy@WarningNoLine{%
4399       Wrong driver `\'\Hy@driver.def';\MessageBreak
4400       pdfTeX is running in PDF mode.\MessageBreak
4401       Forcing driver `\'\Hy@temp.def'%
4402     }%
4403     \let\Hy@driver\Hy@temp
4404   \fi
4405 \else
4406   \ifx\Hy@driver\Hy@temp
4407     \Hy@WarningNoLine{%
4408       Wrong driver `\'\Hy@driver.def';\MessageBreak
4409       pdfTeX is not running in PDF mode.\MessageBreak
4410       Using default driver%
4411     }%
4412     \let\Hy@driver\@empty
4413   \fi
4414 \fi
4415 \fi
4416 \ifHy@texht
4417 \else
4418   \ifx\Hy@driver\@empty
4419   \else
4420     \def\Hy@temp{hxetex}%
4421     \ifxetex
4422       \ifx\Hy@driver\Hy@temp
4423     \else
4424       \Hy@WarningNoLine{%
4425         Wrong driver `\'\Hy@driver.def';\MessageBreak
4426         XeTeX is running.\MessageBreak
4427         Forcing driver `\'\Hy@temp.def' for XeTeX%
4428       }%
4429     \let\Hy@driver\Hy@temp
4430   \fi
4431 \fi
4432 \fi
4433 \fi
4434 \ifx\Hy@driver\@empty
4435 \else
4436   \def\Hy@temp{hhitex}%
4437   \ifhint
```

```

4438   \ifx\Hy@driver\Hy@temp
4439   \else
4440     \Hy@WarningNoLine{%
4441       Wrong driver `'\Hy@driver.def';\MessageBreak
4442       htex is running.\MessageBreak
4443       Forcing driver `'\Hy@temp.def'%
4444     }%
4445     \let\Hy@driver\Hy@temp
4446   \fi
4447   \fi
4448   \fi
4449   \ifx\Hy@driver\@empty
4450   \else
4451     \def\Hy@temp{hvtexhtm}%
4452     \ifnum\ifvtex\OpMode\else\m@ne\fi=10 %
4453       \ifx\Hy@driver\Hy@temp
4454     \else
4455       \Hy@WarningNoLine{%
4456         Wrong driver `'\Hy@driver.def';\MessageBreak
4457         VTeX is running in HTML mode.\MessageBreak
4458         Forcing driver `'\Hy@temp.def'%
4459       }%
4460       \let\Hy@driver\Hy@temp
4461     \fi
4462   \else
4463     \ifx\Hy@driver\Hy@temp
4464       \Hy@WarningNoLine{%
4465         Wrong driver `'\Hy@driver.def';\MessageBreak
4466         VTeX is not running in HTML mode.\MessageBreak
4467         Using default driver%
4468       }%
4469       \let\Hy@driver\@empty
4470     \fi
4471   \fi
4472 \fi

```

If the driver is not given, find the right driver or use the default driver.

```

4473 \let\HyOpt@DriverType\ltx@empty
4474 \ifx\HyOpt@CustomDriver\ltx@empty
4475   \ifx\Hy@driver\@empty
4476     \def\HyOpt@DriverType{ (autodetected)}%
4477     \providecommand*\{\Hy@defaultdriver}{hvtex}%
4478   \ifpdf
4479     \ifx\pdfextension\@undefined
4480       \def\Hy@driver{hpdftex}%
4481     \else
4482       \def\Hy@driver{hluatex}%
4483     \fi
4484   \else
4485     \ifxetex
4486       \def\Hy@driver{hxetex}%
4487     \else
4488       \ifnum\ifvtex\OpMode\else\m@ne\fi=10 %
4489         \def\Hy@driver{hvtexhtm}%
4490         \def\MaybeStopEarly{%

```

```

4491      \Hy@Message{Stopped early}%
4492      \Hy@AtBeginDocument{%
4493          \PDF@FinishDoc
4494          \gdef\PDF@FinishDoc{}%
4495      }%
4496      \endinput
4497  }%
4498 \else
4499     \ifhint
4500         \def\Hy@driver{hhitex}
4501     \else
4502         \ifnum\ifvtex\OpMode\else\m@ne\f@=\@ne
4503             \def\Hy@driver{hvtex}%
4504         \else
4505             \ifnum\ifvtex\OpMode\else\m@ne\f@=\tw@
4506                 \def\Hy@driver{hvtex}%
4507             \else
4508                 \ifx\HyOpt@DriverFallback\ltx@empty
4509                     \let\Hy@driver\Hy@defaultdriver
4510                     \def\HyOpt@DriverType{\(default)}%
4511                 \else
4512                     \begingroup
4513                         \toks@\expandafter{\HyOpt@DriverFallback}%
4514                         \edef\x{\endgroup
4515                             \noexpand\kvsetkeys{Hyp}{\the\toks@}%
4516                         }%
4517                     \x
4518                     \ifx\Hy@driver\ltx@empty
4519                         \let\Hy@driver\Hy@defaultdriver
4520                         \def\HyOpt@DriverType{\(default)}%
4521                     \else
4522                         \def\HyOpt@DriverType{\(fallback)}%
4523                     \fi
4524                 \fi
4525                 \fi
4526                 \fi
4527                 \fi
4528                 \fi
4529                 \fi
4530             \fi
4531             \ifx\Hy@driver\Hy@defaultdriver
4532                 \def\Hy@temp{hdviwind}%
4533                 \ifx\Hy@temp\Hy@driver
4534                     \kvsetkeys{Hyp}{colorlinks}%
4535                     \PassOptionsToPackage{dviwindo}{color}%
4536                 \fi
4537                 \fi
4538             \fi
4539         \else
4540             \def\HyOpt@DriverType{\(custom)}%
4541             \let\Hy@driver\HyOpt@CustomDriver
4542         \fi
4543 \Hy@InfoNoLine{Driver\HyOpt@DriverType: \Hy@driver}%
4544 \chardef\Hy@VersionChecked=0 %

```

```

4545 \input{\Hy@driver.def}%
4546 \ifcase\Hy@VersionChecked
4547   \Hy@VersionCheck{\Hy@driver.def}%
4548 \fi
4549 \let\@unprocessedoptions\relax
4550 \Hy@RestoreCatcodes
4551 \Hy@DisableOption{tex4ht}%
4552 \Hy@DisableOption{pdftex}%
4553 \Hy@DisableOption{nativepdf}%
4554 \Hy@DisableOption{dvipdfm}%
4555 \Hy@DisableOption{dvipdfmx}%
4556 \Hy@DisableOption{dvipdfmx-outline-open}%
4557 \Hy@DisableOption{pdfmark}%
4558 \Hy@DisableOption{dvips}%
4559 \Hy@DisableOption{hypertex}%
4560 \Hy@DisableOption{vtx}%
4561 \Hy@DisableOption{vtxexpdfmark}%
4562 \Hy@DisableOption{dviwindo}%
4563 \Hy@DisableOption{dvipsone}%
4564 \Hy@DisableOption{textures}%
4565 \Hy@DisableOption{latex2html}%
4566 \Hy@DisableOption{ps2pdf}%
4567 \Hy@DisableOption{xetex}%
4568 \Hy@DisableOption{driverfallback}%
4569 \Hy@DisableOption{customdriver}%
4570 \Hy@DisableOption{pdfversion}%
4571 }

```

Support for open outlines is enabled for Xe_TE_X >= 0.9995. I don't know, if older versions also support this. AFAIK older dvipdfmx versions will break, thus the switch cannot be turned on by default.

```

4572 \newif\ifHy@DvipdfmxOutlineOpen
4573 \ifxetex
4574 \ifdim\number\XeTeXversion\XeTeXrevision in<0.9995in %
4575 \else
4576   \chardef\SpecialDvipdfmxOutlineOpen\@ne
4577   \Hy@DvipdfmxOutlineOpenture
4578 \fi
4579 \fi
4580 \begingroup\expandafter\expandafter\expandafter\endgroup
4581 \expandafter\ifx\csname SpecialDvipdfmxOutlineOpen\endcsname\relax
4582 \else
4583 \ifnum\SpecialDvipdfmxOutlineOpen>\z@%
4584   \Hy@DvipdfmxOutlineOpenture
4585 \fi
4586 \fi

```

15.4.2 Bookmarks

```

4587 \def\WriteBookmarks{0}
4588 \def\@bookmarkopenstatus#1{%
4589   \ifHy@bookmarksopen

```

The purpose of the \@firstofone-number-space-construct is that no \relax will be inserted by T_EX before the \else:

```

4590 \ifnum#1<\expandafter\@firstofone\expandafter
4591     {\number\@bookmarksopenlevel} % explicit space
4592 \else
4593     -%
4594 \fi
4595 \else
4596     -%
4597 \fi
4598 }
4599 \ifHy@bookmarks
4600 \Hy@Info{Bookmarks ON}%
4601 \ifx\@pdfpagemode\@empty
4602     \def\@pdfpagemode{UseOutlines}%
4603 \fi
4604 \else
4605     \let\@bookmarkopenstatus\ltx@gobble
4606 \Hy@Info{Bookmarks OFF}%
4607 \Hy@AtEndOfPackage{%
4608     \global\let\ReadBookmarks\relax
4609     \global\let\WriteBookmarks\relax
4610 }%
4611 \ifx\@pdfpagemode\@empty
4612     \def\@pdfpagemode{UseNone}%
4613 \fi
4614 \fi
4615 \Hy@DisableOption{bookmarks}

```

Add wrapper for setting standard catcodes (babel's shorthands).

```

4616 \def\Hy@CatcodeWrapper#1{%
4617     \let\Hy@EndWrap\ltx@empty
4618     \def\TMP@EnsureCode##1##2{%
4619         \edef\Hy@EndWrap{%
4620             \Hy@EndWrap
4621             \catcode##1 \the\catcode##1\relax
4622         }%
4623         \catcode##1 ##2\relax
4624     }%
4625     \TMP@EnsureCode{10}{12}% ^^J
4626     \TMP@EnsureCode{33}{12}% !
4627     \TMP@EnsureCode{34}{12}% "
4628     \TMP@EnsureCode{36}{3}% $ (math)
4629     \TMP@EnsureCode{38}{4}% & (alignment)
4630     \TMP@EnsureCode{39}{12}% '
4631     \TMP@EnsureCode{40}{12}% (
4632     \TMP@EnsureCode{41}{12}% )
4633     \TMP@EnsureCode{42}{12}% *
4634     \TMP@EnsureCode{43}{12}% +
4635     \TMP@EnsureCode{44}{12}% ,
4636     \TMP@EnsureCode{45}{12}% -
4637     \TMP@EnsureCode{46}{12}% .
4638     \TMP@EnsureCode{47}{12}% /
4639     \TMP@EnsureCode{58}{12}% :
4640     \TMP@EnsureCode{59}{12}% ;
4641     \TMP@EnsureCode{60}{12}% <
4642     \TMP@EnsureCode{61}{12}% =

```

```

4643 \TMP@EnsureCode{62}{12}%
4644 \TMP@EnsureCode{63}{12}%
4645 \TMP@EnsureCode{91}{12}%
4646 \TMP@EnsureCode{93}{12}%
4647 \TMP@EnsureCode{94}{7}%
4648 \TMP@EnsureCode{95}{8}%
4649 \TMP@EnsureCode{96}{12}%
4650 \TMP@EnsureCode{124}{12}%
4651 \TMP@EnsureCode{126}{13}%
4652 #1\relax
4653 \Hy@EndWrap
4654 }

\HyColor@UseColor expects a macro as argument. It contains the color specification.

4655 \Hy@AtBeginDocument{%
4656   \ifHy@ocgcolorlinks
4657     \kvsetkeys{Hyp}{colorlinks}%
4658   \ifHy@pdfa
4659     \Hy@Warning{%
4660       PDF/A: Optional Content Groups are prohibited,\MessageBreak
4661       using `colorlinks' instead of `ocgcolorlinks'%
4662     }%
4663     \Hy@ocgcolorlinksfalse
4664   \fi
4665 \fi
4666 \ifHy@ocgcolorlinks
4667 \else
4668   \Hy@DisableOption{ocgcolorlinks}%
4669 \fi
4670 \ifHy@colorlinks
4671   \def\@pdfborder{0 0 0}%
4672   \let\@pdfborderstyle\@empty
4673   \Hy@CatcodeWrapper{%
4674     \RequirePackage{color}%
4675   }%
4676   \def\Hy@colorlink#1{%
4677     \begingroup
4678     \HyColor@UseColor#1%
4679   }%
4680   \def\Hy@endcolorlink{\endgroup}%
4681   \Hy@Info{Link coloring ON}%
4682 \else
4683   \ifHy@frenchlinks
4684     \def\Hy@colorlink#1{\begingroup\fontshape{\scdefault}\selectfont}%
4685     \def\Hy@endcolorlink{\endgroup}%
4686     \Hy@Info{French linking ON}%
4687 \else

```

for grouping consistency:

```

4688   \def\Hy@colorlink#1{\begingroup}%
4689   \def\Hy@endcolorlink{\endgroup}%
4690   \Hy@Info{Link coloring OFF}%
4691 \fi
4692 \fi

```

```

4693 \Hy@DisableOption{colorlinks}%
4694 \Hy@DisableOption{frenchlinks}%
4695 \ifHy@texht
4696 \else
4697   \ifHy@implicit
4698     \let \T@Ref\HyRef@Ref
4699     \def\@refstar#1{%
4700       \NR@ref@showkeys{#1}%
4701       \HyRef@StarSetRef{#1}\@firstoffive
4702     }
4703     \def\@pagerefstar#1{%
4704       \NR@ref@showkeys{#1}%
4705       \HyRef@StarSetRef{#1}\@secondoffive
4706     }
4707     \def\@namerefstar#1{%
4708       \NR@ref@showkeys{#1}%
4709       \HyRef@StarSetRef{#1}\@thirdoffive
4710     }
4711     \def\@Refstar#1{%
4712       \NR@ref@showkeys{#1}%
4713       \HyRef@StarSetRef{#1}\HyRef@MakeUppercaseFirstOfFive
4714     }%
4715   \else
4716     \fi
4717   \fi
4718 }
4719 \Hy@AtBeginDocument{%
4720   \ifx\ReadBookmarks\relax
4721   \else
4722     \Hy@CatcodeWrapper\ReadBookmarks
4723   \fi
4724 }

4725 \ifHy@backref
4726   \RequirePackage{backref}%
4727 \else
4728   \let\Hy@backout\@gobble
4729 \fi
4730 \Hy@DisableOption{backref}
4731 \Hy@DisableOption{pagebackref}

4732 \Hy@activeanchorfalse

```

16 User hypertext macros

We need to normalise all user commands taking a URL argument; Within the argument the following special definitions apply: `\#`, `\%`, `~` produce `#`, `%`, `~` respectively. for consistency `\~` produces `~` as well. At the *top level only* ie not within the argument of another command, you can use `#` and `%` unescaped, to produce themselves. even if, say, `#` is entered as `#` it will be converted to `\#` so it does not die if written to an aux file etc. `\#` will write as `#` locally while making `\specials`.

```

4733 \begingroup
4734 \endlinechar=-1 %
4735 \catcode`^^A=14 %
4736 \catcode`^^M\active
4737 \catcode`\%\active
4738 \catcode`\#\active
4739 \catcode`\_\active
4740 \catcode`\$\active
4741 \catcode`\&\active
4742 \gdef\hyper@normalise{^^A
4743   \begingroup
4744   \catcode`^^M\active
4745   \def^^M{ }^^A
4746   \catcode`\%\active
4747   \let%\@percentchar
4748   \let%\@percentchar
4749   \catcode`\#\active
4750   \def#{\hyper@hash}^^A
4751   \def#{\hyper@hash}^^A
4752   \@makeother\&^^A
4753   \edef&{\string&}^^A
4754   \edef\&{\string&}^^A
4755   \edef\textunderscore{\string_}^^A
4756   \let\_textunderscore
4757   \catcode`\_\active
4758   \let\_textunderscore
4759   \let~\hyper@tilde
4760   \let~\hyper@tilde
4761   \let\textasciitilde\hyper@tilde
4762   \let\\@\backslashchar
4763   \edef${\string$}^^A
4764   \Hy@safe@activestru
4765   \hyper@n@rmalise
4766 }^^A
4767 \catcode`\#=6 ^^A
4768 \gdef\Hy@ActiveCarriageReturn{^^M}^^A
4769 \gdef\hyper@n@rmalise#1#2{^^A
4770   \def\Hy@tempa{#2}^^A
4771   \ifx\Hy@tempa\Hy@ActiveCarriageReturn
4772     \ltx@ReturnAfterElseFi{^^A
4773       \hyper@normalise{#1}^^A
4774     }^^A
4775   \else
4776     \ltx@ReturnAfterFi{^^A
4777       \hyper@normalise{#1}{#2}^^A
4778     }^^A
4779   \fi
4780 }^^A
4781 \gdef\hyper@normalise#1#2{^^A
4782   \edef\Hy@tempa{^^A
4783   \endgroup
4784   \noexpand#1{\Hy@RemovePercentCr#2%^^M\@nil}^^A
4785 }^^A
4786 \Hy@tempa

```

```

4787 }^^A
4788 \gdef\Hy@RemovePercentCr#1%^^M#2\@nil{^^A
4789 #1^^A
4790 \ifx\limits#2\limits
4791 \else
4792 \ltx@ReturnAfterFi{^^A
4793 \Hy@RemovePercentCr #2\@nil
4794 }^^A
4795 \fi
4796 }^^A
4797 \endgroup
4798 \providecommand*\hyper@chars{%
4799 \let\#\hyper@hash
4800 \let\%\hyper@percentchar
4801 \Hy@safe@activestru
4802 }
4803 \def\hyperlink#1#2{%
4804 \hyper@link{}{\#1}{\#2}%
4805 }
4806 \def\Hy@VerboseLinkStart#1#2{%
4807 \ifHy@verbose
4808 \begingroup
4809 \Hy@safe@activestru
4810 \xdef\Hy@VerboseGlobalTemp{(#1)`#2'}%
4811 \Hy@Info{Reference \Hy@VerboseGlobalTemp}%
4812 \xdef\Hy@VerboseGlobalTemp{%
4813 \Hy@VerboseGlobalTemp, %
4814 line \the\inputlineno
4815 }%
4816 \endgroup
4817 \let\Hy@VerboseLinkInfo\Hy@VerboseGlobalTemp
4818 \conelevel@sanitize\Hy@VerboseLinkInfo
4819 \fi
4820 }
4821 \def\Hy@VerboseLinkInfo{<VerboseLinkInfo>}
4822 \def\Hy@VerboseLinkStop{%
4823 \ifHy@verbose
4824 \begingroup
4825 \edef\x{\endgroup
4826 \write\m@ne{%
4827 Package `hyperref' Info: %
4828 End of reference \Hy@VerboseLinkInfo.%}
4829 }%
4830 }%
4831 \x
4832 \fi
4833 }
4834 \def\Hy@VerboseAnchor#1{%
4835 \ifHy@verbose
4836 \begingroup
4837 \Hy@safe@activestru
4838 \Hy@Info{Anchor `\\HyperDestNameFilter{\#1}'%}
4839 \endgroup

```

```

4840 \fi
4841 }
4842 \def\Hy@AllowHyphens{%
4843 \relax
4844 \ifhmode
4845 \penalty\@M
4846 \hskip\z@skip
4847 \fi
4848 }
4849 \DeclareRobustCommand*\{\! href\}[1][]{%
4850 \begingroup
4851 \setkeys[href]{#1}%
4852 \@ifnextchar\bgroup\Hy@href{\hyper@normalise\! href@}%
4853 }
4854 \def\Hy@href#1{%
4855 \hyper@normalise\! href@%
4856 }
4857 \begingroup
4858 \catcode`\$=6 %
4859 \catcode`\#=12 %
4860 \gdef\! href@$1{\expandafter\! href@\! split$1##\#\$\}%
4861 \gdef\! href@\! split$1##$2##$3\$\$4{%
4862 \hyper@link{$1}{$2}{$4}}%
4863 \endgroup
4864 }%
4865 \endgroup

```

Option ‘page’.

```

4866 \define@key[href]{page}{%
4867 \def\Hy@href@page{#1}%
4868 }
4869 \let\Hy@href@page\empty
4870 \newcount\c@Hy@tempcnt
4871 \def\theHy@tempcnt{\the\c@Hy@tempcnt}
4872 \def\Hy@MakeRemoteAction{%
4873 \ifx\Hy@href@page\empty
4874 \def\Hy@href@page{0}%
4875 \else
4876 \setcounter{Hy@tempcnt}{\Hy@href@page}%
4877 \ifnum\c@Hy@tempcnt<\@ne
4878 \Hy@Warning{%
4879 Invalid page number (\theHy@tempcnt)\MessageBreak
4880 for remote PDF file.\MessageBreak
4881 Using page 1}%
4882 }%
4883 \def\Hy@href@page{0}%
4884 \else
4885 \global\advance\c@Hy@tempcnt\m@ne
4886 \edef\Hy@href@page{\theHy@tempcnt}%
4887 \fi
4888 \fi

```

If a next action is set, then also a new window should be opened. Otherwise AR reclaims that it closes the current file with discarding the next actions.

```

4889 \ifx\Hy@href@nextactionraw\@empty
4890 \else
4891 \Hy@pdfnewwindowsettrue
4892 \Hy@pdfnewwindowtrue
4893 \fi
4894 }

Option ‘pd fremotestartview’.
4895 \define@key{href}{pd fremotestartview}{%
4896 \setkeys{Hyp}{pd fremotestartview={#1}}%
4897 }

Option ‘pdfnewwindow’.
4898 \let\KV@href@pdfnewwindow\KV@Hyp@pdfnewwindow
4899 \let\KV@href@pdfnewwindow@default\KV@Hyp@pdfnewwindow@default

Option ‘ismap’.
4900 \newif\ifHy@href@ismap
4901 \define@key{href}{ismap}[true]{%
4902 \ltx@ifundefined{Hy@href@ismap#1}{%
4903 \Hy@Error{%
4904 Invalid value (#1) for key `ismap'.\MessageBreak
4905 Permitted values are `true' or `false'.\MessageBreak
4906 Ignoring `ismap'%}
4907 }\@ehc
4908 }{%
4909 \csname Hy@href@ismap#1\endcsname
4910 }%
4911 }

Option ‘nextactionraw’.
4912 \let\Hy@href@nextactionraw\@empty
4913 \define@key{href}{nextactionraw}{%
4914 \edef\Hy@href@nextactionraw{#1}%
4915 \ifx\Hy@href@nextactionraw\@empty
4916 \else
4917 \Hy@Match\Hy@href@nextactionraw{}{%
4918 ^(\HyPat@ObjRef/|<<.* /S[ /].+>>|%
4919 |[( ?\HyPat@ObjRef/|<<.* /S[ /].+>>)+ ?])$%
4920 }{}{%
4921 \Hy@Warning{Invalid value for `nextactionraw':\MessageBreak
4922 \Hy@href@nextactionraw\MessageBreak
4923 The action is discarded%}
4924 }%
4925 }{%
4926 \ifx\Hy@href@nextactionraw\@empty
4927 \else
4928 \edef\Hy@href@nextactionraw{/Next \Hy@href@nextactionraw}%
4929 \fi
4930 \fi
4931 }
4932 \def\HyPat@ObjRef/{.+}

Load package url.sty and save the meaning of the original \url in \nolinkurl.
4933 \RequirePackage{url}
4934 \let\HyOrg@url\url

```

```

4935 \def\Hurl{\begingroup\Url}
4936 \DeclareRobustCommand*\nolinkurl{\hyper@normalise\nolinkurl@}
4937 \def\nolinkurl@#1{\Hurl{#1}}
4938 \DeclareRobustCommand*\url{\hyper@normalise\url@}
4939 \def\url@#1{\hyper@linkurl{\Hurl{#1}}{#1}}
4940 \DeclareRobustCommand*\hyperimage{\hyper@normalise\hyper@image}
4941 \providecommand\hyper@image[2]{#2}
4942 \def\hypertarget#1#2{%
4943   \ifHy@nesting
4944     \hyper@anchor{#1}{#2}%
4945   \else
4946     \hyper@anchor{#1}{\relax}{#2}%
4947   \fi
4948 }

```

\hyperref is more complicated, as it includes the concept of a category of link, used to make the name. This is not really used in this package. \hyperdef sets up an anchor in the same way. They each have three parameters of category, linkname, and marked text, and \hyperref also has a first parameter of URL. If there is an optional first parameter to \hyperdef, it is the name of a L^AT_EX label which can be used in a short form of \hyperref later, to avoid remembering the name and category.

```

4949 \DeclareRobustCommand*\hyperref{%
4950   \ifnnextchar{\Hy@babelnormalise\label@hyperref}{\hyperref
4951 }
4952 \def\Hy@babelnormalise#1[#2]{%
4953   \begingroup
4954     \Hy@safe@activestruce
4955     \let\protect\@unexpandable@protect
4956     \edef\Hy@tempa{%
4957       \endgroup
4958       \noexpand#1[#2]}%
4959   }%
4960   \Hy@tempa
4961 }
4962 \def\@hyperref{\hyper@normalise\@hyperref}
4963 \def\@hyperref#1#2#3{%
4964   \edef\ref@one{\ifx\\#2\\else#2.\fi#3}%
4965   \expandafter\tryhyper@link\ref@one\\#1}%
4966 }
4967 \def\tryhyper@link#1\\#2{%
4968   \hyper@link{#2}{#1}%
4969 }

```

```

4970 \def\hyperdef{\ifnnextchar{\label@hyperdef}{\@hyperdef}}
4971 \def\@hyperdef#1#2#3{%, category, name, text
4972   \ifx\\#1\\%
4973     \def\Hy@AnchorName{#2}%
4974   \else
4975     \def\Hy@AnchorName{#1.#2}%
4976   \fi
4977   \ifHy@nesting
4978     \expandafter\hyper@anchor\expandafter{\Hy@AnchorName}{#3}%
4979   \else

```

```

4980   \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{\relax}#3%
4981   \fi
4982 }

```

We also have a need to give a *LATeX label* to a hyper reference, to ease the pain of referring to it later. `\hyperrefundefinedlink` may be redefined by a user to add colour or other formatting.

```

4983 \let\hyperrefundefinedlink\@firstofone
4984 \def\label@hyperref[#1]{%
4985   \expandafter\label@hyperref\csname r@#1\endcsname{#1}%
4986 }%
4987 \def\label@hyperref#1#2#3{%
4988   \ifx#1\relax
4989     \protect\G@refundefinedtrue
4990     \CL@tex@warning{%
4991       Hyper reference `#2' on page \thepage \space undefined%
4992     }%
4993     \begingroup
4994       \hyperrefundefinedlink{#3}%
4995     \endgroup
4996   \else
4997     \hyper@link{\expandafter\@fifthoffive#1}%
4998     {\expandafter\@fourthoffive#1\@empty\@empty}{#3}%
4999   \fi
5000 }
5001 \def\label@hyperdef[#1]#2#3#4{%
5002   % label name, category, name,
5003   % anchor text
5004   @bsphack
5005   \ifx\\#2\\%
5006     \def\Hy@AnchorName{#3}%
5007   \else
5008     \def\Hy@AnchorName{#2.#3}%
5009   \fi
5010   \if@filesw
5011     \protected@write\@auxout{}{%
5012       \string\newlabel{#1}{{}\{}{}\{\}\{}{}\{\Hy@AnchorName}\{\}}%
5013     }%
5014   \fi
5015   @esphack
5016   \ifHy@nesting
5017     \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{#4}%
5018   \else
5019     \expandafter\hyper@@anchor\expandafter{\Hy@AnchorName}{\relax}#4%
5020   \fi
}

```

`\hyperget` To create manually bookmarks one need the destination name. If there is a label, the name can be retrieved with commands from refcount. Such a destination name must take `\HyperDestNameFilter` into account

```
\HyperDestNameFilter{\getrefbykeydefault{label}{anchor}{Doc-Start}}
```

To make this easier, we define `\hyperget`

```
5021 \ExplSyntaxOn
```

```

5022 \cs_new:Npn \hyperget #1 #2
5023 {
5024   \use:c { __hyp_get_#1:n } { #2}
5025 }
5026
5027 \cs_new:Npn \__hyp_get_anchor:n #1
5028 {
5029   \HyperDestNameFilter
5030   {
5031     \cs_if_exist:cTF {r@#1}
5032     {
5033       \tl_item:cn {r@#1}{4}
5034     }
5035     {
5036       Doc-Start
5037     }
5038   }
5039 }
5040 \cs_new:Npn \__hyp_get_pageanchor:n #1
5041 {
5042   \HyperDestNameFilter
5043   {
5044     \cs_if_exist:cTF {r@#1}
5045     {
5046       page. \tl_item:cn {r@#1}{2}
5047     }
5048     {
5049       Doc-Start
5050     }
5051   }
5052 }
5053 \cs_new:Npn \__hyp_get_currentanchor:n #1
5054 {
5055   \HyperDestNameFilter { \currentHref }
5056 }
5057 \ExplSyntaxOff

```

16.1 Link box support for XeTeX

```

5058 \newdimen\XeTeXLinkMargin
5059 \setlength{\XeTeXLinkMargin}{2pt}
5060 \ifxetex
5061   \font\XeTeXLink@font=pzdr at 1sp\relax
5062 \newcommand*\{\XeTeXLink@space}{%
5063   \begingroup
5064     \XeTeXLink@font
5065     \@xxii
5066   \endgroup
5067 }%
5068 \newcommand{\XeTeXLinkBox}[1]{%
5069   \begingroup
5070     \leavevmode
5071     \sbox{z@{#1}}%
5072   \begin{group}

```

```

5073   \dimen@=\dp\z@
5074   \advance\dimen@\XeTeXLinkMargin
5075   \setbox\tw@=\llap{%
5076     \hbox@\XeTeXLinkMargin{%
5077       \lower\dimen@\hbox{\XeTeXLink@space}%
5078       \hss
5079     }%
5080   }%
5081   \dp\tw@=\dp\z@
5082   \ht\tw@=\ht\z@
5083   \copy\tw@
5084 \endgroup
5085 \copy\z@
5086 \dimen@=\ht\z@
5087 \advance\dimen@\XeTeXLinkMargin
5088 \setbox\tw@=\rlap{%
5089   \hbox@\XeTeXLinkMargin{%
5090     \hss
5091     \raise\dimen@\hbox{\XeTeXLink@space}%
5092   }%
5093 }%
5094 \dp\tw@=\dp\z@
5095 \ht\tw@=\ht\z@
5096 \copy\tw@
5097 \endgroup
5098 }%
5099 \else
5100 \newcommand*{\XeTeXLinkBox}[1]{%
5101   \begingroup
5102   \leavevmode
5103   \sbox\z@{\#1}%
5104   \copy\z@
5105 \endgroup
5106 }%
5107 \fi

```

17 Underlying basic hypertext macros

Links have an optional type, a filename (possibly a URL), an internal name, and some marked text. (Caution: the internal name may contain babel shorthand characters.) If the second parameter is empty, its an internal link, otherwise we need to open another file or a URL. A link start has a type, and a URL.

```

5108 \def\hyper@link{\let\Hy@reserved@a\relax
5109  \@ifnextchar[{\hyper@link@}{\hyper@link@[link]}%
5110 }
5111 % #1: type
5112 % #2: URL
5113 % #3: destination name
5114 % #4: text
5115 \def\hyper@link@[#1]#2#3#4{%
5116   \ltx@ifempty{#4}{% link text
5117     \Hy@Warning{Suppressing empty link}%
5118   }{%
5119     \begingroup

```

```

5120   \protected@edef\Hy@tempa{\#2}%
5121   \edef\Hy@tempb{\#3}%
5122   \ifx\Hy@tempa\ltx@empty
5123     \ifx\Hy@tempb\ltx@empty
5124       \Hy@Warning{Suppressing link with empty target}%
5125       \toks@{%
5126         \endgroup
5127         \ltx@secondoftwo
5128       }%
5129     \else
5130       \toks@{%
5131         \endgroup
5132         \hyper@link{\#1}%
5133       }%
5134     \fi
5135   \else
5136     \toks@{%
5137       \endgroup
5138       \expandafter\hyper@readexternallink{\#2}\{\#1}%
5139     }%
5140   \fi
5141   \Hy@safe@activesfalse
5142   \toks@\expandafter{%
5143     \the\expandafter\toks@
5144     \expandafter{\Hy@tempb}{\#4}%
5145   }%
5146   \the\toks@
5147 }%
5148 }

```

The problem here is that the first (URL) parameter may be a local file: reference (in which case some browsers treat it differently) or a genuine URL, in which case we'll have to activate a real Web browser. Note that a simple name is also a URL, as that is interpreted as a relative file name. We have to worry about # signs in a local file as well.

```

5149 \def\hyper@readexternallink#1\#2#3#4{%
5150   \begingroup
5151   \let\\\relax
5152   \expandafter\endgroup
5153   \expandafter\@hyper@@readexternallink#1\{\#2\}{\#3}{\#4}%
5154 }
5155 \def\@hyper@@readexternallink#1\#2#3#4{%

```

Parameters are:

1. The URL or file name
2. The type
3. The internal name
4. The link string

We need to get the 1st parameter properly expanded, so we delimit the arguments rather than passing it inside a group.

```

5156  \@hyper@readexternallink{\#2}{\#3}{\#4}{\#1}:\\\{\#1}%
5157 }

```

Now (potentially), we are passed: 1) The link type 2) The internal name, 3) the link string, 4) the URL type (http, mailto, file etc), 5) the URL details 6) anything after a real : in the URL 7) the whole URL again

```

5158 \def\@pdftempwordfile{file}%
5159 \def\@pdftempwordrun{run}%
5160 \def\@hyper@readexternallink#1#2#3#4:#5:#6\\#7{%

```

If there are no colons at all (#6 is blank), its a local file; if the URL type (#4) is blank, its probably a Mac filename, so treat it like a file: URL. The only flaw is if its a relative Mac path, with several colon-separated elements — then we lose. Such names must be prefixed with an explicit dvi:

```

5161  \ifx\\#6\\%
5162    \@hyper@linkfile file:#7\\{\#3}{\#2}{\#7}%
5163  \else
5164    \ifx\\#4\\%
5165      \@hyper@linkfile file:#7\\{\#3}{\#2}{\#7}%
5166    \else

```

If the URL type is ‘file’, pass it for local opening

```

5167  \def\@pdftempa{\#4}%
5168  \ifx\@pdftempa\@pdftempwordfile
5169    \@hyper@linkfile#7\\{\#3}{\#2}{\#7}%
5170  \else

```

if it starts ‘run:’, its to launch an application.

```

5171  \ifx\@pdftempa\@pdftempwordrun
5172    \ifHy@pdfa
5173      \Hy@Error{%
5174        PDF/A: Launch action is prohibited%
5175      }@\ehc
5176      \begingroup
5177        \leavevmode
5178        #2%
5179      \endgroup
5180    \else
5181      \@hyper@launch#7\\{\#3}{\#2}%
5182    \fi
5183  \else

```

otherwise its a URL

```

5184    \hyper@linkurl{\#3}{\#7\ifx\\#2\\else\hyper@hash#2\fi}%
5185    \fi
5186    \fi
5187    \fi
5188  \fi
5189 }

```

By default, turn run: into file:

```

5190 \def\@hyper@launch run:#1\\#2#3{%
5191   \hyper@linkurl{\#2}{%
5192     \Hy@linkfileprefix
5193     #1%
5194     \ifx\\#3\\%

```

```
5195     \else
5196         \hyper@hash
5197         #3%
5198     \fi
5199 }
5200 }
```

D P Story <story@uakron.edu> pointed out that relative paths starting .. fell over. Switched to using \filename@parse to solve this.

```

5201 \def\@hyper@linkfile file:#1\\#2#3#4{%
5202   %file url,link string, name, original uri
5203   \filename@parse{\#1}%
5204   \ifx\filename@ext\relax
5205     \edef\filename@ext{\XR@ext}%
5206   \fi
5207   \def\use@file{\filename@area\filename@base.\filename@ext}%
5208   \Hy@IfStringEndsWith\filename@ext\XR@ext{%
5209     \hyper@linkfile{\#2}{\use@file}{\#3}%
5210   }{%
5211     \ifx\@baseurl\empty
5212       \hyper@linkurl{\#2}{%
5213         \#4\ifx\\#3\\ \else\hyper@hash#3\fi
5214       }%
5215     \else
5216       \hyper@linkurl{\#2}{\use@file\ifx\\#3\\ \else\hyper@hash#3\fi}%
5217     \fi
5218   }%
5219 }
5220 \def\Hy@IfStringEndsWith#1#2{%
5221   \begingroup
5222   \edef\x{\#1}%
5223   \onelevel@sanitize\x
5224   \edef\x{.\x$}%
5225   \edef\y{\#2}%
5226   \onelevel@sanitize\y
5227   \edef\y{.\y$}%
5228   \expandafter\def\expandafter\z\expandafter##\expandafter1\y##2\@nil{%
5229     \endgroup
5230     \ifx\relax##2\relax
5231       \expandafter\ltx@secondoftwo
5232     \else
5233       \expandafter\ltx@firstoftwo
5234     \fi
5235   }%
5236   \expandafter\expandafter\expandafter\z\expandafter\x\y\@nil
5237 }
5238 \def\Hy@StringLocalhost{localhost}
5239 \onelevel@sanitize\Hy@StringLocalhost
5240 \def\Hy@CleanupFile#1{%
5241   \edef#1{\#1}%
5242   \expandafter\Hy@@CleanupFile#1\hbox///\hbox\@nil{\#1}%
5243 }
5244 \def\Hy@@CleanupFile#1//#2/#3\hbox#4\@nil#5{%
5245   \begingroup

```

```

5246 \toks@{\endgroup}%
5247 \def\x{\#1}%
5248 \ifx\x\empty
5249   \def\x{\#2}%
5250   \ifx\x\empty
5251     \toks@{\endgroup\def#5{/#3}}%
5252   \else
5253     \onelevel@sanitize\x
5254     \ifx\x\Hy@StringLocalhost
5255       \toks@{\endgroup\def#5{/#3}}%
5256     \fi
5257   \fi
5258 \fi
5259 \the\toks@
5260 }

```

Anchors have a name, and marked text. We have to be careful with the marked text, as if we break off part of something to put a `\special` around it, all hell breaks loose. Therefore, we check the category code of the first token, and only proceed if its safe. Tanmoy sorted this out.

A curious case arises if the original parameter was in braces. That means that #2 comes here a multiple letters, and the `noexpand` just looks at the first one, putting the rest in the output. Yuck.

```

5261 \long\def\hyper@@anchor#1#2{\hyper@@anchor#1\relax#2\relax}
5262 \long\def\@hyper@@anchor#1\relax#2#3\relax{%
5263   \ifx\\#1\\%
5264     #2\Hy@Warning{Ignoring empty anchor}%
5265   \else
5266     \def\anchor@spot{#2#3}%
5267     \let\put@me@back\empty
5268     \ifx\relax#2\relax
5269     \else
5270       \ifHy@nesting
5271     \else
5272       \ifcat a\noexpand#2\relax
5273     \else
5274       \ifcat 0\noexpand#2 \relax
5275     \else
5276       \typeout{Anchor start is not alphanumeric %
5277       on input line\the\inputlineno%
5278     }%
5279     \let\anchor@spot\empty
5280     \def\put@me@back{#2#3}%
5281   \fi
5282   \fi
5283   \fi
5284   \fi
5285 \ifHy@activeanchor
5286   \anchor@spot
5287 \else
5288   \hyper@anchor{#1}%
5289 \fi
5290 \expandafter\put@me@back
5291 \fi

```

```

5292 \let\anchor@spot\empty
5293 }
5294 \let\anchor@spot\ltx@empty

18 Option ‘destlabel’

5295 \ifHy@destlabel

\hyper@newdestlabel
5296 \def\hyper@newdestlabel#1#2{%
5297 \begingroup
5298 \Hy@safe@activestore
5299 \edef\x{\endgroup
5300 \noexpand\@newlabel{HyDL}{#1}{#2}%
5301 }%
5302 \x
5303 }%

\hyper@destlabel@hook
5304 \providecommand*\hyper@destlabel@hook{}%

\Hy@DestRename
5305 \newcommand*{\Hy@DestRename}[2]{%
5306 \ltx@ifundefined{HyDL!#1}{%
5307 \begingroup
5308 \Hy@safe@activestore
5309 \edef\dest@name{#1}%
5310 \edef\label@name{#2}%
5311 \hyper@destlabel@hook
5312 \Hy@IsEmpty{dest@name}{%
5313 \Hy@IsEmpty{label@name}{%
5314 \global\expandafter
5315 \let\csname HyDL!#1\endcsname\ltx@empty
5316 \if@filesw
5317 \protected@write\auxout{}{%
5318 \string\hyper@newdestlabel
5319 {#1}%
5320 {\label@name}%
5321 }%
5322 \fi
5323 }%
5324 }%
5325 \endgroup
5326 }{}%
5327 }%}

\HyperDestRename
5328 \newcommand*{\HyperDestRename}[2]{%
5329 \AtBeginDocument{%
5330 \Hy@DestRename{#1}{#2}%
5331 }%
5332 }%
5333 \AtBeginDocument{%

```

```

5334   \let\HyperDestRename\Hy@DestRename
5335 }%
\\Hy@IsNotEmpty
5336 \def\Hy@IsNotEmpty#1{%
5337   \ltx@ifundefined{#1}\ltx@gobble{%
5338     \expandafter\ifx\csname#1\endcsname\ltx@empty
5339       \expandafter\ltx@gobble
5340     \else
5341       \expandafter\ltx@firstofone
5342     \fi
5343   }%
5344 }%
5345 \ltx@GlobalAppendToMacro\label@hook{%
5346   \HyperDestRename\@currentHref\label@name
5347 }%
\\HyperDestLabelReplace
5348 \def\HyperDestLabelReplace#1{%
5349   \ltx@ifundefined{HyDL@#1}{%
5350     #1%
5351   }{%
5352     \csname HyDL@#1\endcsname
5353   }%
5354 }%
\\HyperDestNameFilter
5355 \let\HyperDestNameFilter\HyperDestLabelReplace
5356 \else
\\hyper@newdestlabel
5357 \let\hyper@newdestlabel\ltx@gobbletwo
\\HyperDestLabelReplace
5358 \let\HyperDestLabelReplace\ltx@firstofone
\\HyperDestRename
5359 \let\HyperDestRename\ltx@gobbletwo
5360 \fi
5361 \Hy@DisableOption{destlabel}
    Provide a dummy default definition of \hyper@newdestlabel inside the .aux
files.
5362 \AddToHook{include/before}
5363 {\immediate\write\@partaux{\string\providecommand\string\hyper@newdest-
label[2]{}}}
5364 \AddToHook{begindocument}
5365 {\immediate\write\@mainaux{\string\providecommand\string\hyper@newdest-
label[2]{}}}

```

19 Forms creation

Allow for creation of PDF or HTML forms. The effects here are limited somewhat by the need to support both output formats, so it may not be as clever as something which only wants to make PDF forms.

I (Sebastian) could not have started this without the encouragement of T V Raman.

19.1 Field flags

The field flags are organized in a bit set.

```
5366 \RequirePackage{bitset}
```

Each flag has a option name, an `\if` switch, and a bit position. The default is always ‘false’, the flag is clear. This is also the default of the switch created by `\newif`.

The names of the flags in the PDF specification (1.7) are used as lowercase option names.

```
\HyField@NewFlag #1: type: F annot flags, Ff field flags
#2: PDF name
#3: PDF position
5367 \def\HyField@NewFlag#1#2{%
5368   \lowercase{\HyField@NewOption{#2}}%
5369   \lowercase{\HyField@NewBitsetFlag{#2}{#2}{#1}}%
5370 }
```

```
\HyField@NewFlagOnly
5371 \def\HyField@NewFlagOnly#1#2{%
5372   \lowercase{\HyField@NewBitsetFlag{#2}{#2}{#1}}%
5373 }
```

```
\HyField@NewOption #1: option name
5374 \def\HyField@NewOption#1{%
5375   \expandafter\newif\csname ifFld@#1\endcsname
5376   \define@key{Field}{#1}[true]{%
5377     \lowercase{\Field@boolkey{##1}{#1}}%
5378   }%
5379 }
```

```
\HyField@NewBitsetFlag Package ‘bitset’ uses zero based positions, the PDF specification starts with one.
#1: option
#2: PDF name
#3: type: F annot flags, Ff field flags
#4: PDF position
5380 \def\HyField@NewBitsetFlag#1#2#3#4{%
5381   \begingroup
5382   \count@=#4\relax
5383   \advance\count@\m@ne
5384   \def\x##1{%
5385     \endgroup
5386     \expandafter\def\csname HyField@#3@#1\endcsname{##1}%
5387     \expandafter\ifx\csname HyField@#3@##1\endcsname\relax
```

```

5388      \expandafter\edef\csname HyField@##3@##1\endcsname{%
5389          (\number#4) #2%
5390      }%
5391  \else
5392      \expandafter\edef\csname HyField@##3@##1\endcsname{%
5393          \csname HyField@##3@##1\endcsname
5394          /#2%
5395      }%
5396      \fi
5397  }%
5398  \expandafter\x\expandafter{\the\count@}%
5399 }

\HyField@UseFlag The bit set is HyField@##1
5400 \def\HyField@UseFlag##1##2{%
5401   \lowercase{\HyField@@UseFlag{##2}{##1}}%
5402 }

\HyField@@UseFlag
5403 \def\HyField@@UseFlag##1##2{%
5404   \bitsetSetValue{HyField@##2}{%
5405     \csname HyField@##2@##1\endcsname
5406   }{%
5407     \csname ifFld@##1\endcsname 1\else 0\fi
5408   }%
5409 }

\HyField@SetFlag The bit set is HyField@##1
5410 \def\HyField@SetFlag##1##2{%
5411   \lowercase{\HyField@@SetFlag{##2}{##1}}%
5412 }

\HyField@@SetFlag
5413 \def\HyField@@SetFlag##1##2{%
5414   \bitsetSetValue{HyField@##2}{%
5415     \csname HyField@##2@##1\endcsname
5416   }{1}%
5417 }

\HyField@PrintFlags
5418 \def\HyField@PrintFlags##1##2{%
5419   \ifHy@verbose
5420     \begingroup
5421       \let\Hy@temp\empty
5422       \let\MessageBreak\relax
5423       \expandafter\@for\expandafter\x\expandafter:\expandafter=%
5424       \bitsetGetSetBitList{HyField@##1}\do{%
5425         \edef\Hy@temp{%
5426           \Hy@temp
5427             \csname HyField@##1@x\endcsname\MessageBreak
5428         }%
5429       }%
5430     \edef\x{\endgroup

```

```

5431 \noexpand\Hy@Info{%
5432   Field flags: %
5433   \expandafter\ifx\@car\#1\@nil S\else/\fi
5434   #1 %
5435   \bitsetGetDec{\HyField@#1} %
5436   (0x\bitsetGetHex{\HyField@#1}{32})\MessageBreak
5437   \Hy@temp
5438   for #2%
5439 }%
5440 }\x
5441 \fi
5442 }

```

19.1.1 Declarations of field flags

“Table 8.70 Field flags common to all field types”

```

5443 \HyField@NewFlag{Ff}{ReadOnly}{1}
5444 \HyField@NewFlag{Ff}{Required}{2}
5445 \HyField@NewFlag{Ff}{NoExport}{3}

```

“Table 8.75 Field flags specific to button fields”

```

5446 \HyField@NewFlag{Ff}{NoToggleToOff}{15}
5447 \HyField@NewFlag{Ff}{Radio}{16}
5448 \HyField@NewFlag{Ff}{PushButton}{17}
5449 \HyField@NewFlag{Ff}{RadiosInUnison}{26}

```

“Table 8.77 Field flags specific to text fields”

```

5450 \HyField@NewFlag{Ff}{Multiline}{13}
5451 \HyField@NewFlag{Ff}{Password}{14}
5452 \HyField@NewFlag{Ff}{FileSelect}{21}%
5453 \HyField@NewFlag{Ff}{DoNotSpellCheck}{23}%
5454 \HyField@NewFlag{Ff}{DoNotScroll}{24}%
5455 \HyField@NewFlag{Ff}{Comb}{25}%
5456 \HyField@NewFlag{Ff}{RichText}{26}%

```

“Table 8.79 field flags specific to choice fields”

```

5457 \HyField@NewFlag{Ff}{Combo}{18}
5458 \HyField@NewFlag{Ff}{Edit}{19}
5459 \HyField@NewFlag{Ff}{Sort}{20}
5460 \HyField@NewFlag{Ff}{MultiSelect}{22}%
5461 % \HyField@NewFlag{Ff}{DoNotSpellCheck}{23}%
5462 \HyField@NewFlag{Ff}{CommitOnSelChange}{27}%

```

Signature fields are not supported.

Until 6.76i hyperref uses field option ‘combo’ to set three flags ‘Combo’, ‘Edit’, and ‘Sort’. Option ‘popdown’ sets flag ‘Combo’ only.

```

5463 \newif\ifFld@popdown
5464 \define@key{Field}{popdown}[true]{%
5465   \lowercase{\Field@boolkey{\#1}}{popdown}%
5466 }

```

Annotation flags. The form objects are widget annotations. There are two flags for readonly settings, the one in the annotation flags is ignored, instead the other in the field flags is used.

Flag Print is not much useful, because hyperref do not use the appearance entry of the annotations for most fields.

```

5467 \HyField@NewFlag{F}{Invisible}{1}
5468 \HyField@NewFlag{F}{Hidden}{2}%
5469 \HyField@NewFlag{F}{Print}{3}%
5470 \HyField@NewFlag{F}{NoZoom}{4}%
5471 \HyField@NewFlag{F}{NoRotate}{5}%
5472 \HyField@NewFlag{F}{NoView}{6}%
5473 \HyField@NewFlag{F}{Locked}{8}%
5474 \HyField@NewFlag{F}{ToggleNoView}{9}%
5475 \HyField@NewFlag{F}{LockedContents}{10}%
5476 \ifHy@pdflatex
5477   \def\HyField@PDFAFlagWarning{\#1\#2}%
5478   \Hy@Warning{%
5479     PDF/A: Annotation flag `#1' must\MessageBreak
5480     be set to `#2'%
5481   }%
5482 }%
5483 \Fld@invisibl>false
5484 \def\Fld@invisibl>true{%
5485   \HyField@PDFAFlagWarning{invisibl}{false}%
5486 }%
5487 \Fld@hiddenfalse
5488 \def\Fld@hiddentrue{%
5489   \HyField@PDFAFlagWarning{hidden}{false}%
5490 }%
5491 \Fld@printtrue
5492 \def\Fld@printfalse{%
5493   \HyField@PDFAFlagWarning{print}{true}%
5494 }%
5495 \Fld@nozoomtrue
5496 \def\Fld@nozoomfalse{%
5497   \HyField@PDFAFlagWarning{nozoom}{true}%
5498 }%
5499 \Fld@norotatefalse
5500 \def\Fld@norotatetrue{%
5501   \HyField@PDFAFlagWarning{norotate}{true}%
5502 }%
5503 \Fld@noviewfalse
5504 \def\Fld@noviewtrue{%
5505   \HyField@PDFAFlagWarning{noview}{false}%
5506 }%
5507 \fi

```

Submit flags. Flag 1 Include/Exclude is not supported, use option noexport instead.

```

5508 \HyField@NewFlag{Submit}{IncludeNoValueFields}{2}
5509 \HyField@NewFlagOnly{Submit}{ExportFormat}{3}
5510 \HyField@NewFlag{Submit}{GetMethod}{4}
5511 \HyField@NewFlag{Submit}{SubmitCoordinates}{5}
5512 \HyField@NewFlagOnly{Submit}{XFDF}{6}
5513 \HyField@NewFlag{Submit}{IncludeAppendSaves}{7}
5514 \HyField@NewFlag{Submit}{IncludeAnnotations}{8}
5515 \HyField@NewFlagOnly{Submit}{SubmitPDF}{9}

```

```

5516 \HyField@NewFlag{Submit}{CanonicalFormat}{10}
5517 \HyField@NewFlag{Submit}{ExclNonUserAnnots}{11}
5518 \HyField@NewFlag{Submit}{ExclFKey}{12}
5519 \HyField@NewFlag{Submit}{EmbedForm}{14}

5520 \define@key{Field}{export}{%
5521   \lowercase{\def\Hy@temp{\#1}}%
5522   \@ifundefined{Fld@export@\Hy@temp}{%
5523     \@onellevel@sanitize\Hy@temp
5524     \Hy@Error{%
5525       Unknown export format `\'\Hy@temp'.\MessageBreak
5526       Known formats are `FDF', `HTML', `XFDF', and `PDF'%
5527     }@\ehc
5528   }{%
5529     \let\Fld@export\Hy@temp
5530   }%
5531 }
5532 \def\Fld@export{fdf}
5533 \@namedef{Fld@export@fdf}{0}%
5534 \@namedef{Fld@export@html}{1}%
5535 \@namedef{Fld@export@xfdf}{2}%
5536 \@namedef{Fld@export@pdf}{3}%

```

19.1.2 Set submit flags

```
\HyField@FlagsSubmit
5537 \def\HyField@FlagsSubmit{%
5538   \bitsetReset{HyField@Submit}%
5539   \ifcase\@nameuse{Fld@export@\Fld@export} %
5540     % FDF
5541     \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5542     \HyField@UseFlag{Submit}{SubmitCoordinates}%
5543     \HyField@UseFlag{Submit}{IncludeAppendSaves}%
5544     \HyField@UseFlag{Submit}{IncludeAnnotations}%
5545     \HyField@UseFlag{Submit}{CanonicalFormat}%
5546     \HyField@UseFlag{Submit}{ExclNonUserAnnots}%
5547     \HyField@UseFlag{Submit}{ExclFKey}%
5548     \HyField@UseFlag{Submit}{EmbedForm}%
5549   \or % HTML
5550     \HyField@SetFlag{Submit}{ExportFormat}%
5551     \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5552     \HyField@UseFlag{Submit}{GetMethod}%
5553     \HyField@UseFlag{Submit}{SubmitCoordinates}%
5554     \HyField@UseFlag{Submit}{CanonicalFormat}%
5555   \or % XFDF
5556     \HyField@SetFlag{Submit}{XFDF}%
5557     \HyField@UseFlag{Submit}{IncludeNoValueFields}%
5558     \HyField@UseFlag{Submit}{SubmitCoordinates}%
5559     \HyField@UseFlag{Submit}{CanonicalFormat}%
5560   \or % PDF
5561     \HyField@SetFlag{Submit}{SubmitPDF}%
5562     \HyField@UseFlag{Submit}{GetMethod}%
5563   \fi
5564 \HyField@PrintFlags{Submit}{submit button field}%

```

```

5565 \bitsetIsEmpty{HyField@Submit}{%
5566   \let\Fld@submitflags\ltx@empty
5567 }{%
5568   \edef\Fld@submitflags{/Flags \bitsetGetDec{HyField@Submit}}{%
5569 }%
5570 }

```

19.1.3 Set annot flags in fields

\HyField@FlagsAnnot

```

5571 \def\HyField@FlagsAnnot#1{%
5572   \bitsetReset{HyField@F}{%
5573     \HyField@UseFlag{F}{Invisible}{%
5574     \HyField@UseFlag{F}{Hidden}{%
5575       \HyField@UseFlag{F}{Print}{%
5576         \HyField@UseFlag{F}{NoZoom}{%
5577           \HyField@UseFlag{F}{NoRotate}{%
5578             \HyField@UseFlag{F}{NoView}{%
5579               \HyField@UseFlag{F}{Locked}{%
5580                 \HyField@UseFlag{F}{ToggleNoView}{%
5581                   \HyField@UseFlag{F}{LockedContents}{%
5582                     \HyField@PrintFlags{F}{#1}{%
5583                       \bitsetIsEmpty{HyField@F}{%
5584                         \let\Fld@annotflags\ltx@empty
5585 }{%
5586   \edef\Fld@annotflags{/F \bitsetGetDec{HyField@F}}{%
5587 }%
5588 }

```

19.1.4 Pushbutton field

\HyField@FlagsPushButton

```

5589 \def\HyField@FlagsPushButton{%
5590   \HyField@FlagsAnnot{push button field}{%
5591   \bitsetReset{HyField@Ff}{%
5592     \HyField@UseFlag{Ff}{ReadOnly}{%
5593     \HyField@UseFlag{Ff}{Required}{%
5594     \HyField@UseFlag{Ff}{NoExport}{%
5595     \HyField@SetFlag{Ff}{Pushbutton}{%
5596     \HyField@PrintFlags{Ff}{push button field}{%
5597     \bitsetIsEmpty{HyField@Ff}{%
5598       \let\Fld@flags\ltx@empty
5599 }{%
5600   \edef\Fld@flags{/Ff \bitsetGetDec{HyField@Ff}}{%
5601 }%
5602 }

```

19.1.5 Check box field

\HyField@FlagsCheckBox

```

5603 \def\HyField@FlagsCheckBox{%
5604   \HyField@FlagsAnnot{check box field}{%
5605   \bitsetReset{HyField@Ff}{%

```

```

5606 \HyField@UseFlag{Ff}{ReadOnly}%
5607 \HyField@UseFlag{Ff}{Required}%
5608 \HyField@UseFlag{Ff}{NoExport}%
5609 \HyField@PrintFlags{Ff}{checkbox field}%
5610 \bitsetIsEmpty{\HyField@Ff}{%
5611   \let\Fld@flags\ltx@empty
5612 }{%
5613   \edef\Fld@flags{/Ff \bitsetGetDec{\HyField@Ff}}%
5614 }%
5615 }

```

19.1.6 Radio button field

\HyField@FlagsRadioButton

```

5616 \def\HyField@FlagsRadioButton{%
5617   \HyField@FlagsAnnot{radio button field}%
5618   \bitsetReset{\HyField@Ff}%
5619   \HyField@UseFlag{Ff}{ReadOnly}%
5620   \HyField@UseFlag{Ff}{Required}%
5621   \HyField@UseFlag{Ff}{NoExport}%
5622   \HyField@UseFlag{Ff}{NoToggleToOff}%
5623   \HyField@SetFlag{Ff}{Radio}%
5624   \HyField@UseFlag{Ff}{RadiosInUnison}%
5625   \HyField@PrintFlags{Ff}{radio button field}%
5626   \bitsetIsEmpty{\HyField@Ff}{%
5627     \let\Fld@flags\ltx@empty
5628   }{%
5629     \edef\Fld@flags{/Ff \bitsetGetDec{\HyField@Ff}}%
5630   }%
5631 }

```

19.1.7 Text fields

\HyField@FlagsText

```

5632 \def\HyField@FlagsText{%
5633   \HyField@FlagsAnnot{text field}%
5634   \bitsetReset{\HyField@Ff}%
5635   \HyField@UseFlag{Ff}{ReadOnly}%
5636   \HyField@UseFlag{Ff}{Required}%
5637   \HyField@UseFlag{Ff}{NoExport}%
5638   \HyField@UseFlag{Ff}{Multiline}%
5639   \HyField@UseFlag{Ff}{Password}%
5640   \HyField@UseFlag{Ff}{FileSelect}%
5641   \HyField@UseFlag{Ff}{DoNotSpellCheck}%
5642   \HyField@UseFlag{Ff}{DoNotScroll}%
5643 \ifFld@comb
5644   \ifcase0\ifFld@multiline
5645     \else\ifFld@password
5646     \else\ifFld@fileselect
5647     \else 1\f1\f1\f1\relax
5648   \Hy@Error{%
5649     Field option `comb' cannot used together with\MessageBreak
5650     `multiline', `password', or `fileselect'%

```

```

5651     } \c@ehc
5652 \else
5653   \HyField@UseFlag{Ff}{Comb}%
5654 \fi
5655 \fi
5656 \HyField@UseFlag{Ff}{RichText}%
5657 \HyField@PrintFlags{Ff}{text field}%
5658 \bitsetIsEmpty{\HyField@Ff}{%
5659   \let\Fl@flags\ltx@empty
5660 }{%
5661   \edef\Fl@flags{/Ff \bitsetGetDec{\HyField@Ff}}%
5662 }%
5663 }

```

19.1.8 Choice fields

\HyField@FlagsChoice

```

5664 \def\HyField@FlagsChoice{%
5665   \HyField@FlagsAnnot{choice field}%
5666   \bitsetReset{\HyField@Ff}%
5667   \HyField@UseFlag{Ff}{ReadOnly}%
5668   \HyField@UseFlag{Ff}{Required}%
5669   \HyField@UseFlag{Ff}{NoExport}%
5670   \HyField@UseFlag{Ff}{Combo}%
5671   \ifFl@combo
5672     \HyField@UseFlag{Ff}{Edit}%
5673   \fi
5674   \HyField@UseFlag{Ff}{Sort}%
5675   \HyField@UseFlag{Ff}{MultiSelect}%
5676   \ifFl@combo
5677     \ifFl@edit
5678       \HyField@UseFlag{Ff}{DoNotSpellCheck}%
5679     \fi
5680   \fi
5681   \HyField@UseFlag{Ff}{CommitOnSelChange}%
5682   \HyField@PrintFlags{Ff}{choice field}%
5683   \bitsetIsEmpty{\HyField@Ff}{%
5684     \let\Fl@flags\ltx@empty
5685   }{%
5686   \edef\Fl@flags{/Ff \bitsetGetDec{\HyField@Ff}}%
5687 }%
5688 }

```

19.2 Choice field

\HyField@PDFChoices #1: list of choices in key value syntax, key = exported name, value = displayed text.

Input: \Fl@default, \Fl@value, \ifFl@multiselect

Result: \Fl@choices with entries: /Opt, /DV, /V, /I.

```

5689 \def\HyField@PDFChoices#1{%
5690   \begingroup
5691   \global\let\Fl@choices\ltx@empty
5692   \let\HyTmp@optlist\ltx@empty

```

```

5693 \let\HyTmp@optitem\relax
5694 \count@=0 %
5695 \kv@parse{#1}{%
5696   \Hy@pdfstringdef\kv@key\kv@key
5697   \ifx\kv@value\relax
5698     \ifnum\Hy@pdf@major@minor@version<103 % implementation note 122, PDF spec 1.7
5699       \xdef\Fld@choices{\Fld@choices[(\kv@key)(\kv@key)]}%
5700     \else
5701       \xdef\Fld@choices{\Fld@choices(\kv@key)}%
5702     \fi
5703   \else
5704     \Hy@pdfstringdef\kv@value\kv@value
5705     \xdef\Fld@choices{\Fld@choices[(\kv@value)(\kv@key)]}%
5706   \fi
5707   \edef\HyTmp@optlist{%
5708     \HyTmp@optlist
5709     \HyTmp@optitem{\the\count@}{\kv@key}0%
5710   }%
5711   \advance\count@ by 1 %
5712   \gobbletwo
5713 }%
5714 \xdef\Fld@choices{/Opt[\Fld@choices]}%
5715 \ifFld@multiselect
5716   \HyField@@PDFChoices{DV}\Fld@default
5717   \HyField@@PDFChoices{V}\Fld@value
5718 \else
5719   \ifx\Fld@default\relax
5720   \else
5721     \pdfstringdef\Hy@gtemp\Fld@default
5722     \xdef\Fld@choices{\Fld@choices/DV(\Hy@gtemp)}%
5723   \fi
5724   \ifx\Fld@value\relax
5725   \else
5726     \pdfstringdef\Hy@gtemp\Fld@value
5727     \xdef\Fld@choices{\Fld@choices/V(\Hy@gtemp)}%
5728   \fi
5729 \fi
5730 \endgroup
5731 }

\HyField@@PDFChoices
5732 \def\HyField@@PDFChoices#1#2{%
5733   \ifx#2\relax
5734   \else
5735     \count@=0 %
5736     \def\HyTmp@optitem##1##2##3{%
5737       \def\HyTmp@key{##2}%
5738       \ifx\HyTmp@key\Hy@gtemp
5739         \expandafter\def\expandafter\HyTmp@optlist\expandafter{%
5740           \HyTmp@optlist
5741           \HyTmp@optitem##1##21%
5742         }%
5743         \let\HyTmp@found=Y%
5744       \else

```

```

5745      \expandafter\def\expandafter\HyTmp@optlist\expandafter{%
5746          \HyTmp@optlist
5747          \HyTmp@optitem{##1}{##2}##3%
5748      }%
5749      \fi
5750  }%
5751 \expandafter\comma@parse\expandafter{#2}{%
5752     \pdfstringdef\Hy@gtemp\comma@entry
5753     \let\HyTmp@found=N %
5754     \expandafter\let\expandafter\HyTmp@optlist\expandafter\@empty
5755     \HyTmp@optlist
5756     \ifx\HyTmp@found Y%
5757         \advance\count@ by 1 %
5758     \else
5759         \onelevel@sanitize\comma@entry
5760         \PackageWarning{hyperref}{%
5761             \string\ChoiceBox: Ignoring value `\\comma@entry',%
5762             \MessageBreak
5763             it cannot be found in the choices%
5764         }%
5765         \fi
5766         \gobble
5767     }%
5768 \def\HyTmp@optitem##1##2##3{%
5769     \ifnum##3=1 %
5770         (##2)%
5771     \fi
5772 }%
5773 \ifcase\count@
5774 \or
5775     \xdef\Fld@choices{\Fld@choices/#1\HyTmp@optlist}%
5776 \else
5777     \xdef\Fld@choices{\Fld@choices/#1[\HyTmp@optlist]}%
5778     \ifx#1V%
5779         \def\HyTmp@optitem##1##2##3{%
5780             \ifnum##3=1 %
5781                 \firstofone{ ##1}%
5782             \fi
5783         }%
5784         \edef\HyTmp@optlist{\HyTmp@optlist}%
5785         \xdef\Fld@choices{%
5786             \Fld@choices
5787             /I[\expandafter\firstofone\HyTmp@optlist]%
5788         }%
5789         \fi
5790     \fi
5791 \fi
5792 }

```

19.3 Forms

\HyField@SetKeys

```

5793 \def\HyField@SetKeys{%
5794     \kvsetkeys{Field}%

```

```

5795 }

5796 \newif\ifFld@checked
5797 \newif\ifFld@disabled
5798 \Fld@checkedfalse
5799 \Fld@disabledfalse
5800 \newcount\Fld@menulength
5801 \newdimen\Field@Width
5802 \newdimen\Fld@charsize
5803 \Fld@charsize=10\p@
5804 \def\Fld@maxlen{0}
5805 \def\Fld@align{0}
5806 \def\Fld@color{0 0 0 rg}
5807 \def\Fld@bcolor{1 1 1}
5808 \def\Fld@bordercolor{1 0 0}
5809 \def\Fld@bordersep{1\p@}
5810 \def\Fld@borderwidth{1}
5811 \def\Fld@borderstyle{S}
5812 \def\Fld@cbsymbol{4}
5813 \def\Fld@radiosymbol{H}
5814 \def\Fld@rotation{0}
5815 \def\Form{\@ifnextchar[{\@Form}{\@Form[]}}
5816 \def\endForm{\@endForm}
5817 \newif\ifForm@html
5818 \Form@htmlfalse
5819 \def\Form@boolkey#1#2{%
5820   \csname Form@#2\ifx\relax#1\relax true\else#1\f\endcsname
5821 }
5822 \define@key{Form}{action}{%
5823   \hyper@normalise\Hy@DefFormAction{#1}%
5824 }
5825 \def\Hy@DefFormAction{\def\Form@action}
5826 \def\enc@@html{html}
5827 \define@key{Form}{encoding}{%
5828   \def\Hy@tempa{#1}%
5829   \ifx\Hy@tempa\enc@@html
5830     \Form@htmltrue
5831     \def\Fld@export{html}%
5832   \else
5833     \Hy@Warning{%
5834       Form `encoding' key with \MessageBreak
5835       unknown value `#1'%
5836     }%
5837     \Form@htmlfalse
5838   \fi
5839 }
5840 \define@key{Form}{method}{%
5841   \lowercase{\def\Hy@temp{#1}}%
5842   \@ifundefined{Form@method@\Hy@temp}{%
5843     \@onelvel@sanitize\Hy@temp
5844     \Hy@Error{%
5845       Unknown method `\'\Hy@temp'.\MessageBreak
5846       Known values are `post' and `get'%
5847   }@\ehc

```

```

5848  }{%
5849   \let\Form@method\Hy@temp
5850   \ifcase\@nameuse{Form@method@\Hy@temp} %
5851     \Fld@getmethodfalse
5852   \else
5853     \Fld@getmethodtrue
5854   \fi
5855 }%
5856 }
5857 \def\Form@method{}
5858 \namedef{Form@method@post}{0}
5859 \namedef{Form@method@get}{1}
5860 \newif\ifHyField@NeedAppearances
5861 \def\HyField@NeedAppearancesfalse{%
5862   \global\let\ifHyField@NeedAppearances\iffalse
5863 }
5864 \def\HyField@NeedAppearancestrue{%
5865   \global\let\ifHyField@NeedAppearances\iftrue
5866 }
5867 \HyField@NeedAppearancestrue
5868 \define@key{Form}{NeedAppearances}[true]{%
5869   \edef\Hy@tempa{\#1}%
5870   \ifx\Hy@tempa\Hy@true
5871     \HyField@NeedAppearancestrue
5872   \else
5873     \ifx\Hy@tempa\Hy@false
5874       \HyField@NeedAppearancesfalse
5875     \else
5876       \Hy@Error{%
5877         Unexpected value `~\Hy@tempa'`MessageBreak
5878         of option `NeedAppearances' instead of`MessageBreak
5879         `true' or `false'%
5880       }@\ehc
5881     \fi
5882   \fi
5883 }
5884 \def\Field@boolkey#1#2{%
5885   \csname Fld@#2\ifx\relax#1\relax true\else#1\fi\endcsname
5886 }
5887 \ifHy@texht
5888   \newtoks\Field@toks
5889   \Field@toks={ }%
5890 \def\Field@addtoks#1#2{%
5891   \edef\@processme{\Field@toks{\the\Field@toks\space #1="#"2}}%
5892   \@processme
5893 }%
5894 \else
5895   \def\Hy@WarnHTMLFieldOption#1{%
5896     \Hy@Warning{%
5897       HTML field option `~#1`MessageBreak
5898       is ignored%
5899     }%
5900   }%
5901 \fi

```

```

5902 \def\Fld@checkequals#1==#2==#3\\{%
5903   \def@\currDisplay{#1}%
5904   \ifx\\#2\\%
5905     \def@\currValue{#1}%
5906   \else
5907     \def@\currValue{#2}%
5908   \fi
5909   \expandafter\Hy@pdfstringdef\expandafter\currValue\expandafter{\currValue}%
5910 }
5911 \define@key{Field}{loc}{%
5912   \def\Fld@loc{#1}%
5913 }
5914 \define@key{Field}{checked}[true]{%
5915   \lowercase{\Field@boolkey{#1}}{checked}%
5916 }
5917 \define@key{Field}{disabled}[true]{%
5918   \lowercase{\Field@boolkey{#1}}{disabled}%
5919 }
5920 \ifHy@texht
5921   \define@key{Field}{accesskey}{%
5922     \Field@addtoks{accesskey}{#1}%
5923   }%
5924   \define@key{Field}{tabkey}{%
5925     \Field@addtoks{tabkey}{#1}%
5926   }%
5927 \else
5928   \define@key{Field}{accesskey}{%
5929     \Hy@WarnHTMLFieldOption{accesskey}%
5930   }%
5931   \define@key{Field}{tabkey}{%
5932     \Hy@WarnHTMLFieldOption{tabkey}%
5933   }%
5934 \fi
5935 \define@key{Field}{name}{%
5936   \def\Fld@name{#1}%
5937 }
5938 \let\Fld@altname\relax
5939 \define@key{Field}{altname}{%
5940   \def\Fld@altname{#1}%
5941 }
5942 \let\Fld@mappingname\relax
5943 \define@key{Field}{mappingname}{%
5944   \def\Fld@mappingname{#1}%
5945 }
5946 \define@key{Field}{width}{%
5947   \def\Fld@width{#1}%
5948   \Field@Width#1\setbox0=\hbox{m}%
5949 }
5950 \define@key{Field}{maxlen}{%
5951   \def\Fld@maxlen{#1}%
5952 }
5953 \define@key{Field}{menulength}{%
5954   \Fld@menulength=#1\relax
5955 }

```

```

5956 \define@key{Field}{height}{%
5957   \def\Fld@height{\#1}%
5958 }
5959 \define@key{Field}{charsize}{%
5960   \setlength{\Fld@charsize}{\#1}%
5961 }
5962 \define@key{Field}{borderwidth}{%
5963   \Hy@defaultbp\Fld@borderwidth{\#1}%
5964 }
5965 \def\Hy@defaultbp{\#1\#2}{%
5966   \begingroup
5967   \afterassignment\Hy@defaultbpAux
5968   \dimen@=\#2bp\relax{\#1}{\#2}%
5969 }
5970 \def\Hy@defaultbpAux{\#1\relax\#2\#3}{%
5971   \ifx!\#1!
5972   \endgroup
5973   \def\#2{\#3}%
5974 } \else
5975   \edef\x{\endgroup
5976   \def\noexpand{\#2}{%
5977     \strip@pt\dimexpr\dimen@*800/803\relax
5978   }}\x
5979 } \fi
5980 } \%
5981 }
5982 \define@key{Field}{borderstyle}{%
5983   \let\Hy@temp\Fld@borderstyle
5984   \def\Fld@borderstyle{\#1}%
5985   \Hy@Match\Fld@borderstyle{}{%
5986     ^[SDBIU]$%
5987   }{}{%
5988     \Hy@Warning{%
5989       Invalid value `@\pdfborderstyle'\MessageBreak
5990       for option `pdfborderstyle'. Valid values:\MessageBreak
5991       \space\space S (Solid), D (Dashed), B (Beveled),\MessageBreak
5992       \space\space I (Inset), U (Underline)\MessageBreak
5993       Option setting is ignored%
5994     }%
5995     \let\Fld@borderstyle\Hy@temp
5996   }%
5997 }
5998 \define@key{Field}{bordersep}{%
5999   \def\Fld@bordersep{\#1}%
6000 }
6001 \define@key{Field}{default}{%
6002   \Hy@pdfstringdef\Fld@default{\#1}%
6003 }
6004 \define@key{Field}{align}{%
6005   \def\Fld@align{\#1}%
6006 }
6007 \define@key{Field}{value}{%
6008   \Hy@pdfstringdef\Fld@value{\#1}%
6009 }

```

```

6010 \define@key{Field}{checkboxsymbol}{%
6011   \Fld@DingDef\Fld@cbsymbol{\#1}%
6012 }
6013 \define@key{Field}{radiosymbol}{%
6014   \Fld@DingDef\Fld@radiosymbol{\#1}%
6015 }
6016 \def\Fld@DingDef#1#2{%
6017   \let\Fld@temp\ltx@empty
6018   \Fld@@DingDef#2\ding{}@\nil
6019   \let#1\Fld@temp
6020 }
6021 \def\Fld@@DingDef#1\ding#2#3@\nil{%
6022   \expandafter\def\expandafter\ltx@empty\expandafter{%
6023     \Fld@temp
6024     #1%
6025   }%
6026   \ifx\\#3\\%
6027     \expandafter\gobble
6028   \else
6029     \begingroup
6030       \lccode`0=#2\relax
6031     \lowercase{\endgroup
6032       \expandafter\def\expandafter\ltx@empty\expandafter{%
6033         \Fld@temp
6034         0%
6035       }%
6036     }%
6037     \expandafter\@firstofone
6038   \fi
6039 }
6040 \Fld@@DingDef#3@\nil
6041 }%
6042 }

6043 \define@key{Field}{rotation}{%
6044   \def\Fld@rotation{\#1}%
6045 }

6046 \define@key{Field}{backgroundcolor}{%
6047   \HyColor@FieldBColor{\#1}\Fld@bcolor{hyperref}{backgroundcolor}%
6048 }
6049 \define@key{Field}{bordercolor}{%
6050   \HyColor@FieldBColor{\#1}\Fld@bordercolor{hyperref}{bordercolor}%
6051 }
6052 \define@key{Field}{color}{%
6053   \HyColor@FieldColor{\#1}\Fld@color{hyperref}{color}%
6054 }

6055 \let\Fld@onclick@code\ltx@empty
6056 \let\Fld@format@code\ltx@empty
6057 \let\Fld@validate@code\ltx@empty
6058 \let\Fld@calculate@code\ltx@empty
6059 \let\Fld@keystroke@code\ltx@empty
6060 \let\Fld@confocus@code\ltx@empty
6061 \let\Fld@onblur@code\ltx@empty
6062 \let\Fld@onmousedown@code\ltx@empty

```

```

6063 \let\Fld@onmouseup@code\ltx@empty
6064 \let\Fld@onenter@code\ltx@empty
6065 \let\Fld@onexit@code\ltx@empty
6066 \def\Hy@temp#1{%
6067   \expandafter\Hy@@temp\csname Fld@#1@code\endcsname{#1}%
6068 }
6069 \def\Hy@@temp#1#2{%
6070   \ifHy@pdfa
6071     \define@key{Field}{#2}{%
6072       \Hy@Error{%
6073         PDF/A: Additional action `#2' is prohibited%
6074       }@\ehc
6075     }%
6076   \else
6077     \define@key{Field}{#2}{%
6078       \def#1{\##1}%
6079     }%
6080   \fi
6081 }
6082 \Hy@temp{keystroke}
6083 \Hy@temp{format}
6084 \Hy@temp{validate}
6085 \Hy@temp{calculate}
6086 \Hy@temp{onfocus}
6087 \Hy@temp{onblur}
6088 \Hy@temp{onenter}
6089 \Hy@temp{onexit}

6090 \let\Fld@calculate@sortkey\ltx@empty
6091 \define@key{Field}{calculatesortkey}[1]{%
6092   \def\Fld@calculate@sortkey{#1}%
6093 }

6094 \ifHy@texht
6095   \def\Hy@temp#1{%
6096     \define@key{Field}{#1}{%
6097       \Field@addtoks{#1}{\##1}%
6098     }%
6099   }%
6100 \else
6101   \def\Hy@temp#1{%
6102     \define@key{Field}{#1}{%
6103       \Hy@WarnHTMLFieldOption{#1}%
6104     }%
6105   }%
6106 \fi
6107 \Hy@temp{ondblclick}
6108 \Hy@temp{onmousedown}
6109 \Hy@temp{onmouseup}
6110 \Hy@temp{onmouseover}
6111 \Hy@temp{onmousemove}
6112 \Hy@temp{onmouseout}
6113 \Hy@temp{onkeydown}
6114 \Hy@temp{onkeyup}
6115 \Hy@temp{onselect}

```

```

6116 \Hy@temp{onchange}
6117 \Hy@temp{onkeypress}
6118 \ifHy@texht
6119   \define@key{Field}{onclick}{%
6120     \Field@addtoks{onclick}{\#1}%
6121   }%
6122 \else
6123   \ifHy@pdfa
6124     \define@key{Field}{onclick}{%
6125       \Hy@Error{%
6126         PDF/A: Action `onclick' is prohibited%
6127       }@\ehc
6128     }%
6129 \else
6130   \define@key{Field}{onclick}{%
6131     \def\Fld@onclick@code{\#1}%
6132   }%
6133 \fi
6134 \fi

6135 \DeclareRobustCommand\TextField{%
6136   \@ifnextchar[{\@\TextField}{\@\TextField[]}%
6137 }
6138 \DeclareRobustCommand\ChoiceMenu{%
6139   \@ifnextchar[{\@\ChoiceMenu}{\@\ChoiceMenu[]}%
6140 }
6141 \DeclareRobustCommand\CheckBox{%
6142   \@ifnextchar[{\@\CheckBox}{\@\CheckBox[]}%
6143 }
6144 \DeclareRobustCommand\PushButton{%
6145   \@ifnextchar[{\@\PushButton}{\@\PushButton[]}%
6146 }
6147 \DeclareRobustCommand\Gauge{%
6148   \@ifnextchar[{\@\Gauge}{\@\Gauge[]}%
6149 }
6150 \DeclareRobustCommand\Submit{%
6151   \@ifnextchar[{\@\Submit}{\@\Submit[]}%
6152 }
6153 \DeclareRobustCommand\Reset{%
6154   \@ifnextchar[{\@\Reset}{\@\Reset[]}%
6155 }
6156 \def\LayoutTextField#1#2{%
6157   \def\Hy@temp{\#1}%
6158   \ifx\Hy@temp\empty
6159     #2%
6160   \else
6161     #1 #2%
6162   \fi
6163 }
6164 \def\LayoutChoiceField#1#2{%
6165   \def\Hy@temp{\#1}%
6166   \ifx\Hy@temp\empty
6167     #2%
6168   \else
6169     #1 #2%

```

```

6170 \fi
6171 }
6172 \def\LayoutCheckField#1#2{%
6173   \def\Hy@temp{#1}%
6174   \ifx\Hy@temp\empty
6175     #2%
6176   \else
6177     #1 #2%
6178   \fi
6179 }
6180 \def\LayoutPushButtonField#1{%
6181   #1%
6182 }
6183 \def\MakeRadioField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6184 \def\MakeCheckField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6185 \def\MakeTextField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6186 \def\MakeChoiceField#1#2{\vbox to #2{\hbox to #1{\hfill}\vfill}}
6187 \def\MakeButtonField#1{%
6188   \sbox0{%
6189     \hspace{\Fld@borderwidth bp}\hspace{\Fld@borderwidth bp}%
6190   }%
6191   \tempdima\ht0 %
6192   \advance\tempdima by \Fld@borderwidth bp %
6193   \advance\tempdima by \Fld@borderwidth bp %
6194   \ht0\tempdima
6195   \tempdima\dp0 %
6196   \advance\tempdima by \Fld@borderwidth bp %
6197   \advance\tempdima by \Fld@borderwidth bp %
6198   \dp0\tempdima
6199   \box0\relax
6200 }
6201 \def\DefaultHeightofSubmit{14pt}
6202 \def\DefaultWidthofSubmit{2cm}
6203 \def\DefaultHeightofReset{14pt}
6204 \def\DefaultWidthofReset{2cm}
6205 \def\DefaultHeightofCheckBox{\normalbaselineskip}
6206 \def\DefaultWidthofCheckBox{\normalbaselineskip}
6207 \def\DefaultHeightofChoiceMenu{\normalbaselineskip}
6208 \def\DefaultWidthofChoiceMenu{\normalbaselineskip}
6209 \def\DefaultHeightofText{\normalbaselineskip}
6210 \def\DefaultHeightofTextMultiline{4\normalbaselineskip}
6211 \def\DefaultWidthofText{3cm}
6212 \def\DefaultOptionsofSubmit{print,name=Submit,noexport}
6213 \def\DefaultOptionsofReset{print,name=Reset,noexport}
6214 \def\DefaultOptionsofPushButton{print}
6215 \def\DefaultOptionsofCheckBox{print}
6216 \def\DefaultOptionsofText{print}

```

Default options for the types of \ChoiceMenu.

```

6217 \def\DefaultOptionsofListBox{print}
6218 \def\DefaultOptionsofComboBox{print,edit,sort}
6219 \def\DefaultOptionsofPopdownBox{print}
6220 \def\DefaultOptionsofRadio{print,notoggleoff}

```

20 Setup

```
6221 \ifHy@hyperfigures
6222   \Hy@Info{Hyper figures ON}%
6223 \else
6224   \Hy@Info{Hyper figures OFF}%
6225 \fi
6226 \ifHy@nesting
6227   \Hy@Info{Link nesting ON}%
6228 \else
6229   \Hy@Info{Link nesting OFF}%
6230 \fi
6231 \ifHy@hyperindex
6232   \Hy@Info{Hyper index ON}%
6233 \else
6234   \Hy@Info{Hyper index OFF}%
6235 \fi
6236 \ifHy@backref
6237   \Hy@Info{backreferencing ON}%
6238 \else
6239   \Hy@Info{backreferencing OFF}%
6240 \fi
6241 \ifHy@colorlinks
6242   \Hy@Info{Link coloring ON}%
6243 \else
6244   \Hy@Info{Link coloring OFF}%
6245 \fi
6246 \ifHy@ocgcolorlinks
6247   \Hy@Info{Link coloring with OCG ON}%
6248 \else
6249   \Hy@Info{Link coloring with OCG OFF}%
6250 \fi
6251 \ifHy@pdfa
6252   \Hy@Info{PDF/A mode ON}%
6253 \else
6254   \Hy@Info{PDF/A mode OFF}%
6255 \fi
```

21 Low-level utility macros

We need unrestricted access to the #, ~ and " characters, so make them nice macros.

```
6256 \edef\hyper@hash{\string#}
6257 \edef\hyper@tilde{\string~}
6258 \edef\hyper@quote{\string"}
```

Support \label before \begin{document}.

```
6259 \def\@currentHref{Doc-Start}
6260 \let\Hy@footnote@\currentHref\@empty
```

We give the start of document a special label; this is used in backreferencing-by-section, to allow for cites before any sectioning commands. Set up PDF info.

```
6261 \Hy@AtBeginDocument{%
6262   \Hy@pdfstringtrue
6263   \PDF@SetupDoc
```

```

6264 \let\PDF@SetupDoc\@empty
6265 \Hy@DisableOption{pdfpagescrop}%
6266 \Hy@DisableOption{pdfpagemode}%
6267 \Hy@DisableOption{pdfnonfullscreenpagemode}%
6268 \Hy@DisableOption{pdfdirection}%
6269 \Hy@DisableOption{pdfviewarea}%
6270 \Hy@DisableOption{pdfviewclip}%
6271 \Hy@DisableOption{pdfprintarea}%
6272 \Hy@DisableOption{pdfprintclip}%
6273 \Hy@DisableOption{pdfprintscaling}%
6274 \Hy@DisableOption{pdfduplex}%
6275 \Hy@DisableOption{pdfpicktraybypdfsize}%
6276 \Hy@DisableOption{pdfprintpagerange}%
6277 \Hy@DisableOption{pdfnumcopies}%
6278 \Hy@DisableOption{pdfstartview}%
6279 \Hy@DisableOption{pdfstartpage}%
6280 \Hy@DisableOption{pdftoolbar}%
6281 \Hy@DisableOption{pdfmenubar}%
6282 \Hy@DisableOption{pdfwindowui}%
6283 \Hy@DisableOption{pdffitwindow}%
6284 \Hy@DisableOption{pdfcenterwindow}%
6285 \Hy@DisableOption{pdfdisplaydoctitle}%
6286 \Hy@DisableOption{pdfpagelayout}%
6287 \Hy@DisableOption{pdflang}%
6288 \Hy@DisableOption{baseurl}%
6289 \ifHy@texht\else\hyper@anchorstart{Doc-Start}\hyper@anchorend\fi
6290 \Hy@pdfstringfalse
6291 }

```

Ignore star from referencing macros: This is only needed if LaTeX doesn't define the starred variants itself.

```

6292 \@ifundefined{@kernel@ref}
6293 { \LetLtxMacro\NoHy@OrgRef\ref
6294 \DeclareRobustCommand*\{\ref\}{%
6295 \@ifstar\NoHy@OrgRef\NoHy@OrgRef
6296 }
6297 \LetLtxMacro\NoHy@OrgPageRef\pageref
6298 \DeclareRobustCommand*\{\pageref\}{%
6299 \@ifstar\NoHy@OrgPageRef\NoHy@OrgPageRef
6300 }{}}

```

22 Localized nullifying of package

Sometimes we just don't want the wretched package interfering with us. Define an environment we can put in manually, or include in a style file, which stops the hypertext functions doing anything. This is used, for instance, in the Elsevier classes, to stop `hyperref` playing havoc in the front matter.

```

6301 \def\NoHyper{%
6302 \def\hyper@link@{##1}##2##3##4{##4\Hy@xspace@end}%
6303 \def\hyper@anchor##1##2{##2\Hy@xspace@end}%
6304 \global\let\hyper@livelink\hyper@link
6305 \gdef\hyper@link##1##2##3{##3\Hy@xspace@end}%
6306 \let\hyper@anchor\ltx@gobble

```

```

6307 \let\hyper@anchorstart\ltx@gobble
6308 \def\hyper@anchorend{\Hy@xspace@end}%
6309 \let\hyper@linkstart\ltx@gobbletwo
6310 \def\hyper@linkend{\Hy@xspace@end}%
6311 \def\hyper@linkurl##1##2{##1\Hy@xspace@end}%
6312 \def\hyper@linkfile##1##2##3{##1\Hy@xspace@end}%
6313 \let\Hy@backout\@gobble
6314 }
6315 \def\stop@hyper{%
6316 \def\hyper@link@[##1]##2##3##4{##4\Hy@xspace@end}%
6317 \let\Hy@backout\@gobble
6318 \let\hyper@@anchor\ltx@gobble
6319 \def\hyper@link##1##2##3##3\Hy@xspace@end}%
6320 \let\hyper@anchor\ltx@gobble
6321 \let\hyper@anchorstart\ltx@gobble
6322 \def\hyper@anchorend{\Hy@xspace@end}%
6323 \let\hyper@linkstart\ltx@gobbletwo
6324 \def\hyper@linkend{\Hy@xspace@end}%
6325 \def\hyper@linkurl##1##2{##1\Hy@xspace@end}%
6326 \def\hyper@linkfile##1##2##3{##1\Hy@xspace@end}%
6327 }
6328 \def\endNoHyper{%
6329 \global\let\hyper@link\hyper@livelink
6330 }
6331 </package>

```

23 Package nohyperref

This package is introduced by Sebastian Rahtz.

Package nohyperref is a dummy package that defines some low level and some top-level commands. It is done for jadetex, which calls hyperref low-level commands, but it would also be useful with people using normal hyperref, who really do not want the package loaded at all.

Some low-level commands:

```

6332 <*nohyperref>
6333 \RequirePackage{letltxmacro}[2008/06/13]
6334 \let\hyper@@anchor\@gobble
6335 \def\hyper@link##1##2##3{##3}%
6336 \let\hyper@anchorstart\@gobble
6337 \let\hyper@anchorend\@empty
6338 \let\hyper@linkstart\@gobbletwo
6339 \let\hyper@linkend\@empty
6340 \def\hyper@linkurl##1##2{##1}%
6341 \def\hyper@linkfile##1##2##3{##1}%
6342 \def\hyper@link@[##1]##2##3{##3}%
6343 \let\PDF@SetupDoc\@empty
6344 \let\PDF@FinishDoc\@empty
6345 \def\nohyperpage##1{##1}

```

Some top-level commands:

```

6346 \def\Acrobatmenu##1##2{\leavevmode##2}
6347 \let\pdfstringdefDisableCommands\@gobbletwo
6348 \let\texorpdfstring\@firstoftwo

```

```

6349 \let\pdfbookmark@undefined
6350 \newcommand\pdfbookmark[3][]{}
6351 \let\phantomsection\@empty
6352 \let\hypersetup@gobble
6353 \let\hyperbaseurl@gobble
6354 \newcommand*\href[3][]{\#3}
6355 \let\hyperdef@gobbletwo
6356 \let\hyperlink@gobble
6357 \let\hypertarget@gobble
6358 \def\hyperref{%
6359   \@ifnextchar{@gobbleopt{\expandafter@gobbletwo@gobble}}%
6360 }
6361 \long\def@gobbleopt[#1]{}
6362 \let\hyperpage\@empty

```

Ignore star from referencing macros. This is only needed in older formats.

```

6363 \@if@t@r\fmtversion{2022-06-01}
6364 {}%
6365 {}%
6366   \LetLtxMacro\NoHy@OrgRef\ref
6367   \DeclareRobustCommand*\ref{%
6368     \@ifstar\NoHy@OrgRef\NoHy@OrgRef
6369   }%
6370   \LetLtxMacro\NoHy@OrgPageRef\pageref
6371   \DeclareRobustCommand*\pageref{%
6372     \@ifstar\NoHy@OrgPageRef\NoHy@OrgPageRef
6373   }%
6374 }
6375 </nohyperref>

```

24 The Mangling Of Aux and Toc Files

Some extra tests so that the hyperref package may be removed or added to a document without having to remove .aux and .toc files (this section is by David Carlisle) All the code is delayed to `\begin{document}`

```

6376 <*package>
6377 \Hy@AtBeginDocument{%

```

First the code to deal with removing the hyperref package from a document.

Write some stuff into the aux file so if the next run is done without hyperref, then `\newlabel` is defined to cope with the extra arguments. change 2022-03-28: removed the code for `\contentsline`, it is no longer needed as `\contentsline` has now always four arguments.

```

6378 \if@filesw
6379   \immediate\write\@auxout{%
6380     \string\providecommand\string\HyperFirstAtBeginDocument{%
6381       \string\AtBeginDocument}^^J%
6382     \string\HyperFirstAtBeginDocument{%
6383       \string\ifx\string\hyper@anchor\string\@undefined^^J%
6384         \string\global\string\let\string\oldnewlabel\string\newlabel^^J%
6385         \string\gdef\string\newlabel\string#\string#1\string#\string#2{%
6386           \string\newlabelxx{\string#\string#1\string#\string#2}^^J%
6387         \string\gdef\string\newlabelxx{%

```

```

6388      \string#1\string#2\string#3\string#4\string#5\string#6{%
6389      \string\oldnewlabel{\string#1}{{\string#2}{\string#3}}}}^J%

```

But the new aux file will be read again at the end, with the normal definitions expected, so better put things back as they were.

```

6390      \string\AtEndDocument{%
6391          \string\ifx\string\hyper@anchor\string\@undefined^^J%
6392              \string\let\string\newlabel\string\oldnewlabel^^J%
6393          \string\fi%
6394      }^^J%

```

If the document is being run with hyperref put this definition into the aux file, so we can spot it on the next run.

```

6395      \string\fi%
6396  }^^J%
6397      \string\global\string\let\string\hyper@last\relax^^J%
6398      \string\gdef\string\HyperFirstAtBeginDocument\string#1{\string#1}%
6399  }%
6400 \fi
6401 \let\HyperFirstAtBeginDocument\ltx@firstofone

```

Now the code to deal with adding the hyperref package to a document with aux and toc written the standard way.

If hyperref was used last time, do nothing. change 2022-03-28: removed the test for an old toc. \contentsline has now always four arguments.

```

6402 \ifx\hyper@last\@undefined
6403 \def\newlabel#1#2{\@newlabel{#1}{#2}{}}{}}%
6404 \fi
6405 }

```

25 Title strings

If options `pdftitle` and `pdfauthor` are not used, these informations for the pdf information dictionary can be extracted by the `\title` and `\author`.

```

6406 \ifHy@pdfusetitle
6407 \let\HyOrg@title\title
6408 \let\HyOrg@author\author
6409 \def\title{\@ifnextchar[\{\Hy@scantitle\}{\Hy@scantitle}}%
6410 \def\Hy@scantitle[#1]{%
6411   \gdef\Hy@title{#1}%
6412   \HyOrg@title{#1}%
6413 }%
6414 \def\Hy@scantitle#1{%
6415   \gdef\Hy@title{#1}%
6416   \HyOrg@title{#1}%
6417 }%
6418 \def\author{\@ifnextchar[\{\Hy@scantauthor\}{\Hy@scantauthor}}%
6419 \def\Hy@scantauthor[#1]{%
6420   \gdef\Hy@author{#1}%
6421   \HyOrg@author{#1}%
6422 }%
6423 \def\Hy@scantauthor#1{%
6424   \gdef\Hy@author{#1}%

```

```

6425   \HyOrg@author{\#1}%
6426 }%

```

The case, that `\title`, or `\author` are given before hyperref is loaded, is much more complicate, because LaTeX initializes the macros `\@title` and `\@author` with LaTeX error and warning messages.

```

6427 \begingroup
6428 \def\process@me{\@nil#2{%
6429   \expandafter\let\expandafter\x\csname \#2\endcsname
6430   \edef\y{\expandafter\strip@prefix\meaning\x}%
6431   \def\c{\#1#1##2\@nil{%
6432     \ifx\#\#\#1\%
6433     \else
6434       \expandafter\gdef\csname Hy\#2\expandafter\endcsname
6435         \expandafter{\x}%
6436     \fi
6437   }%
6438   \expandafter\c\y\relax#1\@nil
6439 }%
6440 \expandafter\process@me\string@\@latex@{\@nil{title}}%
6441 \expandafter\process@me\string@\@latex@{\@nil{author}}%
6442 \endgroup
6443 \fi
6444 \Hy@DisableOption{pdfusetitle}

```

Macro `\Hy@UseMaketitleInfos` is used in the driver files, before the information entries are used.

The newline macro `\newline` or `\%` is much more complicate. In the title a good replacement can be a space, but can be already a space after `\%` in the title string. So this space is removed by scanning for the next non-empty argument.

In the macro `\author` the newline can perhaps separate the different authors, so the newline expands here to a comma with space.

The possible arguments such as space or the optional argument after the newline macros are not detected.

A possible ¹removes its argument.

```

6445 \def\Hy@UseMaketitleString#1{%
6446   \ltx@IfUndefined{\Hy@#1}{}{%
6447   \begingroup
6448   \let\Hy@saved@hook\pdfstringdefPreHook
6449   \pdfstringdefDisableCommands{%
6450     \expandafter\let\expandafter\\csname Hy@newline\#1\endcsname
6451     \let\newline\%
6452     \def\and{; }%
6453     \let\thanks\@gobble%
6454   }%
6455   \expandafter\ifx\csname @pdf\#1\endcsname\@empty
6456     \expandafter\pdfstringdef\csname @pdf\#1\endcsname{%
6457       \csname Hy\#1\endcsname\@empty
6458     }%
6459   \fi
6460   \global\let\pdfstringdefPreHook\Hy@saved@hook
6461   \endgroup
6462 }%
6463 }

```

```

6464 \def\Hy@newline@title#1{ #1}
6465 \def\Hy@newline@author#1{, #1}
6466 \def\Hy@UseMaketitleInfos{%
6467   \Hy@UseMaketitleString{title}%
6468   \Hy@UseMaketitleString{author}%
6469 }

```

26 Page numbers

This stuff is done by Heiko Oberdiek.

27 Every page

```

6470 \RequirePackage{atbegshi}[2007/09/09]
6471 \let\Hy@EveryPageHook\ltx@empty
6472 \let\Hy@EveryPageBoxHook\ltx@empty
6473 \let\Hy@FirstPageHook\ltx@empty
6474 \AtBeginShipout{%
6475   \Hy@EveryPageHook
6476   \ifx\Hy@EveryPageBoxHook\ltx@empty
6477   \else
6478     \setbox\AtBeginShipoutBox=\vbox{%
6479       \offinterlineskip
6480       \Hy@EveryPageBoxHook
6481       \box\AtBeginShipoutBox
6482     }%
6483   \fi
6484 }
6485 \ltx@iffileloaded{hpdf.tex.def}{%
6486   \AtBeginShipout{%
6487     \Hy@FirstPageHook
6488     \global\let\Hy@FirstPageHook\ltx@empty
6489   }%
6490 }{%
6491   \AtBeginShipoutFirst{%
6492     \Hy@FirstPageHook
6493   }%
6494 }
6495 \g@addto@macro\Hy@FirstPageHook{%
6496   \PDF@FinishDoc
6497   \global\let\PDF@FinishDoc\ltx@empty
6498 }

```

27.1 PDF /PageLabels

Internal macros of this module are marked with \HyPL@.

```

6499 \ifHy@pdfpagelabels
6500   \begingroup\expandafter\expandafter\expandafter\endgroup
6501   \expandafter\ifx\csname thepage\endcsname\relax
6502   \Hy@pdfpagelabelsfalse
6503   \Hy@WarningNoLine{%
6504     Option `pdfpagelabels' is turned off\MessageBreak

```

```

6505     because \string\thepage\space is undefined%
6506   }%
6507   \csname fi\endcsname
6508   \csname iffalse\expandafter\endcsname
6509   \fi

```

\thispdfpagelabel The command \thispdfpagelabel allows to label a special page without the redefinition of \thepage for the page.

```

6510   \def\thispdfpagelabel#1{%
6511     \gdef\HyPL@thisLabel{#1}%
6512   }%
6513   \global\let\HyPL@thisLabel\relax

```

\HyPL@Labels The page labels are collected in \HyPL@Labels and set at the end of the document.

```
6514   \let\HyPL@Labels\ltx@empty
```

\Hy@abspage We have to know the absolute page number and introduce a new counter for that.

```

6515   \newcount\Hy@abspage
6516   \Hy@abspage=0 %

```

For comparisons with the values of the previous page, some variables are needed:

```

6517   \def\HyPL@LastType{init}%
6518   \def\HyPL@LastNumber{0}%
6519   \let\HyPL@LastPrefix\ltx@empty

```

Definitions for the PDF names of the L^AT_EX pendants.

```

6520   \def\HyPL@arabic{D}%
6521   \def\HyPL@Roman{R}%
6522   \def\HyPL@roman{r}%
6523   \def\HyPL@Alph{A}%
6524   \def\HyPL@alph{a}%

6525   \let\HyPL@SlidesSetPage\ltx@empty
6526   \ltx@ifclassloaded{slides}{%
6527     \def\HyPL@SlidesSetPage{%
6528       \advance\c@page\ltx@one
6529       \ifnum\value{page}>\ltx@one
6530         \protected@edef\HyPL@SlidesOptionalPage{%
6531           \Hy@SlidesFormatOptionalPage{\thepage}%
6532         }%
6533       \else
6534         \let\HyPL@SlidesOptionalPage\ltx@empty
6535       \fi
6536       \advance\c@page-\ltx@one
6537       \def\HyPL@page{%
6538         \csname the\Hy@SlidesPage\endcsname
6539         \HyPL@SlidesOptionalPage
6540       }%
6541     }%
6542   }{}%

```

\HyPL@EveryPage If a page is shipout and the page number is known, \HyPL@EveryPage has to be called. It stores the current page label.

```

6543 \def\HyPL@EveryPage{%
6544   \begingroup
6545     \ifx\HyPL@thisLabel\relax
6546       \let\HyPL@page\thepage
6547       \HyPL@SlidesSetPage
6548     \else
6549       \let\HyPL@page\HyPL@thisLabel
6550       \global\let\HyPL@thisLabel\relax
6551     \fi
6552     \let\HyPL@Type\relax
6553     \ifnum\c@page>0 %
6554       \ifx\HyPL@SlidesSetPage\ltx@empty
6555         \expandafter\HyPL@CheckThePage\HyPL@page\@nil
6556       \fi
6557     \fi
6558     \let\Hy@temp Y%
6559     \ifx\HyPL@Type\HyPL@LastType
6560     \else
6561       \let\Hy@temp N%
6562     \fi
6563     \ifx\HyPL@Type\relax
6564       \pdfstringdef\HyPL@Prefix{\HyPL@page}%
6565     \else
6566       \pdfstringdef\HyPL@Prefix\HyPL@Prefix
6567     \fi
6568     \ifx\HyPL@Prefix\HyPL@LastPrefix
6569     \else
6570       \let\Hy@temp N%
6571     \fi
6572     \if Y\Hy@temp
6573       \advance\c@page by -1 %
6574       \ifnum\HyPL@LastNumber=\the\c@page\relax
6575       \else
6576         \let\Hy@temp N%
6577       \fi
6578       \Hy@StepCount\c@page
6579     \fi
6580     \if N\Hy@temp
6581       \ifx\HyPL@Type\relax
6582         \HyPL@StorePageLabel{/P(\HyPL@Prefix)}%
6583       \else
6584         \HyPL@StorePageLabel{%
6585           \ifx\HyPL@Prefix\@empty
6586             \else
6587               /P(\HyPL@Prefix)%
6588             \fi
6589             /S/\csname HyPL\HyPL@Type\endcsname
6590             \ifnum\the\c@page=1 %
6591             \else
6592               \space/St \the\c@page
6593             \fi
6594           }%
6595         \fi
6596       \fi

```

```

6597 \xdef\HyPL@LastNumber{\the\c@page}%
6598 \global\let\HyPL@LastType\HyPL@Type
6599 \global\let\HyPL@LastPrefix\HyPL@Prefix
6600 \endgroup
6601 \Hy@GlobalStepCount\Hy@abspage
6602 }%

```

\HyPL@CheckThePage Macro \HyPL@CheckThePage calls \HyPL@@CheckThePage that does the job.

```

6603 \def\HyPL@CheckThePage#1@nil{%
6604   \HyPL@@CheckThePage{#1}#1\csname\endcsname\c@page\@nil
6605 }%

```

\HyPL@@CheckThePage The first check is, is \thepage is defined such as in L^AT_EX, e.g.: \csname @arabic\endcsname\c@page. In the current implementation the check fails, if there is another \csname before.

The second check tries to detect \arabic{page} at the end of the definition text of \thepage.

```

6606 \def\HyPL@@CheckThePage#1#2\csname#3\endcsname\c@page#4\@nil{%
6607   \def\Hy@tempa{#4}%
6608   \def\Hy@tempb{\csname\endcsname\c@page}%
6609   \ifx\Hy@tempa\Hy@tempb
6610     \expandafter\ifx\csname HyPL#3\endcsname\relax
6611     \else
6612       \def\HyPL@Type{#3}%
6613       \def\HyPL@Prefix{#2}%
6614     \fi
6615   \else
6616     \begingroup
6617       \let\Hy@next\endgroup
6618       \let\HyPL@found\@undefined
6619       \def\arabic{\HyPL@Format{arabic}}%
6620       \def\Roman{\HyPL@Format{Roman}}%
6621       \def\roman{\HyPL@Format{roman}}%
6622       \def\Alph{\HyPL@Format{Alph}}%
6623       \def\alph{\HyPL@Format{alph}}%
6624       \protected@edef\Hy@temp{#1}%
6625       \ifx\HyPL@found\relax
6626         \toks@\expandafter{\Hy@temp}%
6627         \edef\Hy@next{\endgroup
6628           \noexpand\HyPL@@CheckThePage\the\toks@
6629             \noexpand\HyPL@found\relax\noexpand\@nil
6630           }%
6631         \fi
6632       \Hy@next
6633     \fi
6634 }%

```

\HyPL@Format The help macro \HyPL@Format is executed while a \protected@edef in the second check method of \HyPL@@CheckPage. The first occurrences of, for example, \arabic{page} is marked by \HyPL@found that is also defined by \csname.

```

6635 \def\HyPL@Format#1#2{%
6636   \ifx\HyPL@found\@undefined
6637     \expandafter\ifx\csname c@#2\endcsname\c@page

```

```

6638     \expandafter\noexpand\csname HyPL@found\endcsname{#1}%
6639     \else
6640     \expandafter\noexpand\csname#1\endcsname{#2}%
6641     \fi
6642 \else
6643     \expandafter\noexpand\csname#1\endcsname{#2}%
6644     \fi
6645 }%

```

\HyPL@@@CheckThePage If the second check method is successful, \HyPL@@@CheckThePage scans the result of \HyPL@Format and stores the found values.

```

6646 \def\HyPL@@@CheckThePage#1\HyPL@found#2#3\@nil{%
6647   \def\Hy@tempa{#3}%
6648   \def\Hy@tempb{\HyPL@found\relax}%
6649   \ifx\Hy@tempa\Hy@tempb
6650     \def\HyPL@Type{@#2}%
6651     \def\HyPL@Prefix{#1}%
6652   \fi
6653 }%

```

\HyPL@StorePageLabel Dummy for drivers that does not support /PageLabel.

```
6654 \providecommand*\HyPL@StorePageLabel}[1]{}
```

\HyPL@Useless The /PageLabels entry does not make sense, if the absolute page numbers and the page labels are the same. Then \HyPL@Labels has the meaning of \HyPL@Useless.

```

6655 \def\HyPL@Useless{0<</S/D>>}%
6656 \Onelevel@sanitize\HyPL@Useless

```

\HyPL@SetPageLabels The page labels are written to the PDF catalogue. The command \Hy@PutCatalog is defined in the driver files.

```

6657 \def\HyPL@SetPageLabels{%
6658   \Onelevel@sanitize\HyPL@Labels
6659   \ifx\HyPL@Labels\empty
6660   \else
6661     \ifx\HyPL@Labels\HyPL@Useless
6662     \else
6663       \Hy@PutCatalog{/PageLabels<</Nums[\HyPL@Labels]>>}%
6664     \fi
6665   \fi
6666 }%

```

```

6667 \g@addto@macro\Hy@EveryPageHook{\HyPL@EveryPage}%
6668 \fi

```

Option ‘pdfpagelabels’ has been used and is now disabled.

```

6669 \Hy@DisableOption{pdfpagelabels}
6670 </package>

```

27.1.1 pdfTeX and VTeX

Because of pdfTeX’s \pdfcatalog command the /PageLabels entry can set at end of document in the first run.

```

\Hy@PutCatalog
6671 <*pdftex>
6672 \pdf@ifdraftmode{%
6673   \let\Hy@PutCatalog\ltx@gobble
6674 }{%
6675   \let\Hy@PutCatalog\pdfcatalog
6676 }
6677 </pdftex>

```

The code for VTeX is more complicate, because it does not allow the direct access to the /Catalog object. The command scans its argument and looks for a /PageLabels entry.

VTeX 6.59g is the first version, that implements \special{!pdfpagelabels...}. For this version \VTeXversion reports 660.

```

6678 <*vtex>
6679 \providecommand*\XR@ext}{pdf}
6680 \edef\Hy@VTeXversion{%
6681   \ifx\VTeXversion\undefined
6682     \z@
6683   \else
6684     \ifx\VTeXversion\relax
6685       \z@
6686     \else
6687       \VTeXversion
6688     \fi
6689   \fi
6690 }
6691 \begingroup
6692 \ifnum\Hy@VTeXversion<660 %
6693   \gdef\Hy@PutCatalog#1{%
6694     \Hy@WarningNoLine{%
6695       VTeX 6.59g or above required for pdfpagelabels%
6696     }%
6697   }%
6698 \else
6699   \gdef\Hy@PutCatalog#1{%
6700     \Hy@vt@PutCatalog#1/PageLabels<>>\@nil
6701   }%
6702 \gdef\Hy@vt@PutCatalog#1/PageLabels<>#3\@nil{%
6703   \ifx\\#2\\%
6704   \else
6705     \immediate\special{!pdfpagelabels #2}%
6706   \fi
6707 }%
6708 \fi
6709 \endgroup
6710 </vtex>
6711 <*pdftex | vtex>

```

\HyPL@StorePageLabel This macro adds the entry #1 to \HyPL@Labels.

```

6712 \ifHy@pdfpagelabels
6713 \def\HyPL@StorePageLabel#1{%
6714   \toks@\expandafter{\HyPL@Labels}%

```

```

6715 \xdef\HyPL@Labels{%
6716   \the\toks@
6717   \the\Hy@abspage<<#1>>%
6718 }%
6719 }%

```

Package `atveryend` is used to get behind the final `\clearpage` and to avoid a `\clearpage` in `\AtEndDocument`. Then the PDF catalog entry for `\PageLabels` is set.

```

6720 \RequirePackage{atveryend}[2009/12/07]%
6721 \AtVeryEndDocument{%
6722   \HyPL@SetPageLabels
6723 }%
6724 \fi
6725 </pdftex | vtex>

```

27.1.2 xetex

```

6726 <*xetex>
6727 \HyPsd@LoadUnicode
6728 \Hy@unicodetrue
6729 \ifx\HyPsd@pdfencoding\HyPsd@pdfencoding@unicode
6730 \else
6731 \let\HyPsd@pdfencoding\HyPsd@pdfencoding@auto
6732 \fi
6733 \HyPsd@LoadStringEnc
6734 \define@key{Hyp}{unicode}[true]{%
6735 \Hy@boolkey{unicode}{#1}%
6736 \ifHy@unicode
6737 \else
6738 \Hy@Warning{%
6739 XeTeX driver only supports `unicode=true'. Ignoring\MessageBreak
6740 option setting `unicode=false'%
6741 }%
6742 \Hy@unicodetrue
6743 \fi
6744 }
6745 \define@key{Hyp}{pdfencoding}{%
6746 \edef\HyPsd@temp{#1}%
6747 \ifx\HyPsd@temp\HyPsd@pdfencoding@unicode
6748 \let\HyPsd@pdfencoding\HyPsd@temp
6749 \else
6750 \ifx\HyPsd@temp\HyPsd@pdfencoding@auto
6751 \let\HyPsd@pdfencoding\HyPsd@temp
6752 \else
6753 \Hy@Warning{%
6754 XeTeX driver only supports\MessageBreak
6755 `pdfencoding=unicode|auto'. Ignoring option\MessageBreak
6756 setting `pdfencoding=\HyPsd@temp'%
6757 }%
6758 \fi
6759 \fi
6760 }

```

```
6761 \let\HyTeX@CheckUnicode\relax
```

Since 2016 (x)dvipdfmx has a special to control the spacing of annotation borders.
So let's make use of it:

```
6762 \def\setpdfinkmargin#1{%
6763   \begingroup
6764     \setlength{\dimen@}{#1}%
6765     \special{dvipdfmx:config g \strip@pt\dimen@}%
6766   \endgroup
6767 }</xetex>
```

set the pdf version

```
6768 <*dvipdfm | xetex>
6769 \special{pdf:majorversion \Hy@pdf@majorversion}
6770 \special{pdf:minorversion \Hy@pdf@minorversion}
6771 </dvipdfm | xetex>
```

27.1.3 pdfmarkbase, dvipdfm, xetex

```
6772 <*pdfmarkbase>
6773 \begingroup
6774   \@ifundefined{headerps@out}{}{%
6775     \toks@\expandafter{\Hy@FirstPageHook}%
6776     \xdef\Hy@FirstPageHook{%
6777       \noexpand\headerps@out{%
6778         systemdict /pdfmark known%%
6779       }%
6780       userdict /?pdfmark systemdict /exec get put%%
6781     }%
6782       userdict /?pdfmark systemdict /pop get put %
6783       userdict /pdfmark systemdict /cleartomark get put%%
6784     }%
6785     \ifelse{%
6786   }%
6787     \the\toks@
6788   }%
6789 }%
6790 \endgroup
6791 </pdfmarkbase>
```

\Hy@PutCatalog

```
6792 <dvipdfm | xetex>\def\Hy@PutCatalog#1{\@pdfm@mark{docview <<#1>>}}
6793 <*pdfmarkbase>
6794 \def\Hy@PutCatalog#1{%
6795   \pdfmark{pdfmark=/PUT,Raw={\string{Catalog\string} <<#1>>}}%
6796 }
6797 </pdfmarkbase>

6798 <*pdfmarkbase | dvipdfm | xetex>
6799 \ifHy@pdfpagelabels
```

\HyPL@StorePageLabel This macro writes a string to the .aux file.

```
6800 \def\HyPL@StorePageLabel#1{%
6801   \if@filesw
6802     \begingroup
6803       \edef\Hy@tempa{\the\Hy@abspage<<#1>>}%
6804       \immediate\write\@mainaux{%
```

```

6805      \string\HyPL@Entry{\Hy@tempa}%
6806      }%
6807      \endgroup
6808      \fi
6809  }%

```

Write a dummy definition of `\HyPL@Entry` for the case, that the next run is done without hyperref. A marker for the rerun warning is set and the `/PageLabels` is written.

```

6810  \Hy@AtBeginDocument{%
6811    \if@filesw
6812      \immediate\write\@mainaux{%
6813        \string\providecommand\string*\string\HyPL@Entry[1]{}}%
6814      }%
6815    \fi
6816    \ifx\HyPL@Labels\@empty
6817      \Hy@WarningNoLine{Rerun to get /PageLabels entry}%
6818    \else
6819      \HyPL@SetPageLabels
6820    \fi
6821    \let\HyPL@Entry\@gobble
6822  }%

```

`\HyPL@Entry`

```

6823  \def\HyPL@Entry#1{%
6824    \expandafter\gdef\expandafter\HyPL@Labels\expandafter{%
6825      \HyPL@Labels
6826      #1%
6827    }%
6828  }%
6829 \fi
6830 </pdfmarkbase | dvipdfm | xetex>
6831 <*packageEnd>
6832 \ifx\MaybeStopEarly\relax
6833 \else
6834   \Hy@stopedearlytrue
6835   \expandafter\MaybeStopEarly
6836 \fi
6837 \Hy@stopedearlyfalse

```

28 Automated L^AT_EX hypertext cross-references

Anything which can be referenced advances some counter; we overload this to put in a hypertext starting point (with no visible anchor), and make a note of that for later use in `\label`. This will fail badly if `\theH<name>` does not expand to a sensible reference. This means that classes or package which introduce new elements need to define an equivalent `\theH<name>` for every `\the<name>`. We do make a trap to make `\theH<name>` be the same as `\arabic{<name>}`, if `\theH<name>` is not defined, but this is not necessarily a good idea. Alternatively, the ‘naturalnames’ option uses whatever L^AT_EX provides, which may be useable.

But then its up to you to make sure these are legal PDF and HTML names. The ‘hypertexnames=false’ option just makes up arbitrary names.

All the shenanigans is to make sure section numbers etc are always arabic, separated by dots. Who knows how people will set up \currentlabel? If they put spaces in, or brackets (quite legal) then the hypertext processors will get upset.

But this is flaky, and open to abuse. Styles like `subeqn` will mess it up, for starters. Appendices are an issue, too. We just hope to cover most situations. We can at least cope with the standard sectioning structure, allowing for `\part` and `\chapter`.

Start with a fallback for equations

```

6838 \def\Hy@CounterExists#1{%
6839   \begingroup\expandafter\expandafter\expandafter\endgroup
6840   \expandafter\ifx\csname c@#1\endcsname\relax
6841     \expandafter@gobble
6842   \else
6843     \begingroup\expandafter\expandafter\expandafter\endgroup
6844     \expandafter\ifx\csname the#1\endcsname\relax
6845       \expandafter\expandafter\expandafter@gobble
6846     \else
6847       \expandafter\expandafter\expandafter@firstofone
6848     \fi
6849   \fi
6850 }
6851 \Hy@CounterExists{section}{%
6852   \providecommand{\theHequation}{\theHsection.\arabic{equation}}%
6853 }
6854 \providecommand{\theHequation}{\arabic{equation}}%
6855 \Hy@CounterExists{part}{%
6856   \providecommand{\theHpart}{\arabic{part}}%
6857 }
6858 \ltx@ifundefined{thechapter}{%
6859   \providecommand{\theHsection}{\arabic{section}}%
6860   \providecommand{\theHfigure}{\arabic{figure}}%
6861   \providecommand{\theHtable}{\arabic{table}}%
6862 }{%
6863   \providecommand{\theHchapter}{\arabic{chapter}}%
6864   \providecommand{\theHfigure}{\theHchapter.\arabic{figure}}%
6865   \providecommand{\theHtable}{\theHchapter.\arabic{table}}%
6866   \providecommand{\theHsection}{\theHchapter.\arabic{section}}%
6867 }
6868 \providecommand{\theHsubsection}{\theHsection.\arabic{subsection}}%
6869 \providecommand{\theHsubsubsection}{\theHsubsection.\arabic{subsubsection}}%
6870 \providecommand{\theHparagraph}{\theHsubsubsection.\arabic{paragraph}}%
6871 \providecommand{\theH subparagraph}{\theHparagraph.\arabic{subparagraph}}%
6872 \providecommand{\theH theorem}{\theHsection.\arabic{theorem}}%
6873 \providecommand{\theHthm}{\theHsection.\arabic{thm}}%

```

Thanks to Greta Meyer (gbd@pop.cwru.edu) for making me realize that enumeration starts at 0 for every list! But `\item` occurs inside `\trivlist`, so check if its a real `\item` before incrementing counters.

```

6874 \let\H@item\item
6875 \newcounter{Item}
6876 \def\theHItem{\arabic{Item}}

```

```

6877 \def\item{%
6878   \@hyper@itemfalse
6879   \if@nmbrlist\@hyper@itemtrue\fi
6880   \H@item
6881 }
6882 \providecommand{\theHenumi}{\theHItem}
6883 \providecommand{\theHenumii}{\theHItem}
6884 \providecommand{\theHenumiii}{\theHItem}
6885 \providecommand{\theHenumiv}{\theHItem}
6886 \providecommand{\theHHfootnote}{\arabic{Hfootnote}}
6887 \providecommand{\theHmpfootnote}{\arabic{mpfootnote}}
6888 \@ifundefined{\theHmpfootnote}{%
6889   \let\theHmpfootnote\theHHfootnote
6890 }{%
6891 }

```

Tanmoy asked for this default handling of undefined `\theH<name>` situations. It really isn't clear what would be ideal, whether to turn off hyperizing of unknown elements, to pick up the textual definition of the counter, or to default it to something like `\arabic{name}`. We take the latter course, slightly worriedly.

```

6891 \let\H@refstepcounter\refstepcounter
6892 \edef\name@of@eq{%

```

We do not want the handler for `\refstepcounter` to cut in during the processing of `\item` (we handle that separately), so we provide a bypass conditional. change 2022-04-22: removed test for the slide counter and for the equation name. change 2022-05-02: added the new boolean set by `\LinkTargetOn/\LinkTargetOff`

```

6893 \newif\if@hyper@item
6894 \newif\if@skiphyperref
6895 \@hyper@itemfalse
6896 \@skiphyperreffalse
6897 \ExplSyntaxOn
6898 \def\refstepcounter#1{%
6899   \legacy_if:nF {Hy@pdfstring}
6900   {
6901     \H@refstepcounter{#1}%
6902     \bool_lazy_and:nnT
6903       { \l__hyp_target_create_bool }
6904       { ! \legacy_if_p:n{@skiphyperref} }
6905     {
6906       \legacy_if:nTF {\@hyper@item}
6907         {
6908           \stepcounter{Item}%
6909           \hyper@refstepcounter{Item}%
6910           \@hyper@itemfalse
6911         }
6912         {
6913           \hyper@refstepcounter{#1}%
6914         }
6915     }
6916   }
6917 }
6918 \ExplSyntaxOff
6919 \let\Hy@saved@refstepcounter\refstepcounter

```

AMSLATEX processes all equations twice; we want to make sure that the hyper stuff is not executed twice, so we use the AMS \ifmeasuring@, initialized if AMS math is not used.

```
6920 \@ifpackageloaded{amsmath}{}{\newif\ifmeasuring@\measuring@false}
```

```
\hyper@refstepcounter
```

```
6921 \def\hyper@refstepcounter#1{%
6922   \HyCnt@ProvideTheHCounter{#1}%
6923   \hyper@makecurrent{#1}%
6924   \ifmeasuring@
6925   \else
6926     \Hy@raisedlink{%
6927       \hyper@anchorstart{\@currentHref}\hyper@anchorend
6928     }%
6929   \fi
6930 }
```

\Hy@ProvideTheHCounter \theH<counter> is not set for counters that are defined before ‘hyperref’ is loaded. In \cl@ckpt, the clear counter list of the artificial counter @ckpt, LATEX remembers the defined counters (needed for \include). We check the clear counter lists, whether our counter is present. If we found it, then we add the parent counter value to \theH<counter>. The \@elt list is used in sanitized form for the comparison, because the list might contain other stuff than \@elts. Also it simplifies the implementation, because LATEX’, substring search \in@ can be used.

```
6931 \def\HyCnt@ProvideTheHCounter#1{%
6932   \@ifundefined{theH#1}{%
6933     \expandafter\def\csname theH#1\endcsname{}%
6934     \def\Hy@temp{\@elt{#1}}%
6935     \ltx@onelvel@sanitize\Hy@temp
6936     \let\HyOrg@elt\@elt
6937     \edef\@elt{%
6938       \noexpand\HyCnt@LookForParentCounter
6939       \expandafter\noexpand\csname theH#1\endcsname
6940     }%
6941     \cl@ckpt
6942     \let\@elt\HyOrg@elt
6943     \expandafter
6944     \ltx@LocalAppendToMacro\csname theH#1\expandafter\endcsname
6945     \expandafter{%
6946       \expandafter\@arabic\csname c@#1\endcsname
6947     }%
6948   }{}%
6949 }
```

```
\Hy@LookForParentCounter
```

```
6950 \def\HyCnt@LookForParentCounter#1#2{%
6951   \expandafter\let\expandafter\Hy@temp@A\csname cl@#2\endcsname
6952   \ltx@ifundefined{cl@#2}{%
6953   }{%
6954     \ltx@onelvel@sanitize\Hy@temp@A
6955     \edef\Hy@temp@A{%
6956       \noexpand\in@\{\Hy@temp\}{\Hy@temp@A}%
6957     }\Hy@temp@A
6958 }
```

```

6958   \ifin@
6959     \ltx@IfUndefined{theH#2}{%
6960       \expandafter\ltx@LocalAppendToMacro\expandafter#1%
6961       \expandafter{%
6962         \expandafter\@arabic\csname c@#2\endcsname.%}
6963       }%
6964     }{%
6965       \expandafter\ltx@LocalAppendToMacro\expandafter#1%
6966       \expandafter{%
6967         \csname theH#2\endcsname.%}
6968       }%
6969     }%
6970   \fi
6971 }%
6972 }

```

After `\appendix` “chapter” (or “section” for classes without chapter) should be replaced by “appendix” to get `\autoref` work. Macro `\Hy@chapapp` contains the current valid name like `\@chapapp`, which cannot be used, because this string depends on the current language.

The “french” package defines counter `\thechapter` by `\newcounterchapter`, if `\@ifundefined{chapter}`.

```

6973 \begingroup\expandafter\expandafter\expandafter\endgroup
6974 \expandafter\ifx\csname chapter\endcsname\relax
6975   \def\Hy@chapterstring{section}%
6976 \else
6977   \def\Hy@chapterstring{chapter}%
6978 \fi
6979 \def\Hy@appendixstring{appendix}
6980 \def\Hy@chapapp{\Hy@chapterstring}
6981 \ltx@IfUndefined{appendix}{%
6982 }{%
6983   \let\HyOrg@appendix\appendix
6984   \def\Hy@AlphNoErr#1{%
6985     \ifnum\value{#1}>26 %
6986       Alph\@number\value{#1}%
6987     \else
6988       \ifnum\value{#1}<1 %
6989         Alph\@number\value{#1}%
6990       \else
6991         \Alph{#1}%
6992       \fi
6993     \fi
6994   }%
6995 \def\appendix{%
6996   \ltx@IfUndefined{chapter}{%
6997     \gdef\theHsection{\Hy@AlphNoErr{section}}%
6998   }{%
6999     \gdef\theHchapter{\Hy@AlphNoErr{chapter}}%
7000   }%
7001   \xdef\Hy@chapapp{\Hy@appendixstring}%
7002   \HyOrg@appendix
7003 }%
7004 }

```

```

\Hy@Test@alph
7005 \def\Hy@Test@alph#1{%
7006   \ifcase#1\or
7007     a\or b\or c\or d\or e\or f\or g\or h\or i\or j\or
7008     k\or l\or m\or n\or o\or p\or q\or r\or s\or t\or
7009     u\or v\or w\or x\or y\or z%
7010   \else
7011     \ctrerr
7012   \fi
7013 }

\Hy@Test@Alph
7014 \def\Hy@Test@Alph#1{%
7015   \ifcase#1\or
7016     A\or B\or C\or D\or E\or F\or G\or H\or I\or J\or
7017     K\or L\or M\or N\or O\or P\or Q\or R\or S\or T\or
7018     U\or V\or W\or X\or Y\or Z%
7019   \else
7020     \ctrerr
7021   \fi
7022 }

```

We define a hook to allow to overwrite the next destination name.

```

7023 \NewHook{__hyp/target/setname}
7024 \define@key{Hyp}{next-anchor}{%
7025   \AddToHookNext{__hyp/target/setname}{%
7026     {\Hy@MakeCurrentHref{#1}}%
7027   }

```

\hyper@makecurrent Because of Babel mucking around, nullify \textlatin when making names. And @number because of babel's lrbabel.def. change 2021-08-15: For new formats we add a hook which allows to overwrite the name of the next destination.

```

7028 \def\hyper@makecurrent#1{%
7029   \begingroup
7030     \Hy@safe@activestru
7031     \edef\Hy@param{\#1}%
7032     \ifx\Hy@param\Hy@chapterstring
7033       \let\Hy@param\Hy@chapapp
7034     \fi
7035     \ifHy@hypertexnames
7036       \let\@number\@firstofone
7037       \def\fnsymbol##1{fnsymbol\number##1}%
7038       \def\arabic##1{\number##1}%
7039       \ifx\@alph\Hy@Test@alph
7040     \else
7041       \def\@alph{\alph\number}%
7042     \fi
7043     \ifx\@Alph\Hy@Test@Alph
7044     \else
7045       \def\@Alph{\Alph\number}%
7046     \fi
7047     \ifHy@naturalnames
7048       \let\textlatin\@firstofone

```

```

7049   \xdef\HyperGlobalCurrentHref{\csname the#1\endcsname}%
7050   \else
7051     \xdef\HyperGlobalCurrentHref{%
7052       \csname
7053         the%
7054         \expandafter\ifx\csname theH#1\endcsname\relax\else H\fi
7055         #1%
7056       \endcsname
7057     }%
7058   \fi
7059   \xdef\HyperGlobalCurrentHref{%
7060     \Hy@param.\expandafter\strip@prefix\meaning\HyperGlobalCurrentHref
7061   }%
7062 \else
7063   \Hy@GlobalStepCount\Hy@linkcounter
7064   \xdef\HyperGlobalCurrentHref{\Hy@param.\the\Hy@linkcounter}%
7065 \fi
7066 \endgroup
7067 \let\HyperLocalCurrentHref\HyperGlobalCurrentHref
7068 \ifHy@localanchorname
7069   \let\@currentHref\HyperLocalCurrentHref
7070 \else
7071   \global\let\@currentHref\HyperGlobalCurrentHref
7072 \fi
7073 \UseHook{__hyp/target/setname}%
7074 }

\Hy@MakeCurrentHref
7075 \def\Hy@MakeCurrentHref#1{%
7076   \edef\HyperLocalCurrentHref{#1}%
7077   \@onelvel@sanitize\HyperLocalCurrentHref
7078   \global\let\HyperGlobalCurrentHref\HyperLocalCurrentHref
7079   \let\HyperLocalCurrentHref\HyperGlobalCurrentHref
7080   \ifHy@localanchorname
7081     \let\@currentHref\HyperLocalCurrentHref
7082   \else
7083     \global\let\@currentHref\HyperGlobalCurrentHref
7084   \fi
7085 }

```

\Hy@MakeCurrentHrefAuto This command is e.g. used to create destinations for unnumbered sections and chapters. For new formats we add a hook which allows to overwrite the name of the next destination.

```

7086 \def\Hy@MakeCurrentHrefAuto#1{%
7087   \Hy@GlobalStepCount\Hy@linkcounter
7088   \Hy@MakeCurrentHref{#1.\the\Hy@linkcounter}%
7089   \UseHook{__hyp/target/setname}}

```

\@currentHlabel \@currrentHlabel is only defined for compatibility with package ‘hypdvips’.

```
7090 \def\@currentHlabel{\@currentHref}
```

29 Package ifthen support

Since version 6.75a this is done in package nameref.

For compatibility \hypergetref and \hypergetpageref are still provided. But they do not generate warnings, if the reference is undefined.

```
7091 \def\hypergetref#1{\getrefbykeydefault{#1}{}{??}}
7092 \def\hypergetpageref#1{\getrefbykeydefault{#1}{page}{0}}
```

30 Package titlesec and titleref support

This code is contributed by Javier Bezos (Email: jbez@arrakis.es).

Package titlesec support:

```
7093 \@ifpackageloaded{titlesec}{%
7094   \def\ttl@Hy@steplink#1{%
7095     \Hy@MakeCurrentHrefAuto{#1*}%
7096     \edef\ttl@Hy@saveanchor{%
7097       \noexpand\Hy@raisedlink{%
7098         \noexpand\hyper@anchorstart{\@currentHref}%
7099         \noexpand\hyper@anchorend
7100         \def\noexpand\ttl@Hy@SavedCurrentHref{\@currentHref}%
7101         \noexpand\ttl@Hy@PatchSaveWrite
7102       }%
7103     }%
7104   }%
7105   \def\ttl@Hy@PatchSaveWrite{%
7106     \begingroup
7107       \toks@\expandafter{\ttl@savewrite}%
7108       \edef\x{\endgroup
7109         \def\noexpand\ttl@savewrite{%
7110           \let\noexpand\ttl@currentHref
7111             \noexpand\ttl@Hy@SavedCurrentHref
7112           \the\toks@
7113         }%
7114       }%
7115     \x
7116   }%
7117   \def\ttl@Hy@refstepcounter#1{%
7118     \let\ttl@b\Hy@raisedlink
7119     \def\Hy@raisedlink##1{%
7120       \def\ttl@Hy@saveanchor{\Hy@raisedlink{##1}}%
7121     }%
7122     \refstepcounter{#1}%
7123     \let\Hy@raisedlink\ttl@b
7124   }%
7125 }
```

31 Package varioref support

Package nameref uses five arguments for the ref system. Fix provided by Felix Neubauer (felix.neubauer@gmx.net). This fix will no longer be needed with latex 2021-11-15.

```

7126 \c@if@t@r\fmtversion{2021-11-15}
7127 {}%
7128 {
7129   \AtBeginDocument{%
7130   \def\Hy@varioref@undefined{{?}{?}{?}{?}}{}{}{}}
7131   \c@ifpackageloaded{varioref}{%
7132     \def\vref@pagenum#1#2{%
7133       \c@ifundefined{r@#2}{%
7134         \expandafter\let\csname r@#2\endcsname\Hy@varioref@undefined
7135       }{}%
7136       \edef#1{\getpagerefnumber{#2}}%
7137     }%
7138   }{}}
7139 }
7140 }

```

32 Package longtable support

Sometimes the anchor of the longtable goes to the previous page. Thus the following patch separates the anchor setting and counter incrementation by hyperref's \refstepcounter and the anchor setting is moved after \vskip\LTpre.

Patch of \LT@array: replace \refstepcounter by the original \H@refstepcounter without anchor generation

```

7141 \c@ifpackageloaded{longtable}{%
7142 \c;ifundefined{hyper@nopatch@longtable}{%
7143   \begingroup
7144     \def\y{\LT@array}%
7145     \c;ifundefined{scr@LT@array}{%
7146       \c;ifundefined{adl@LT@array}{}{\def\y{\adl@LT@array}}%
7147     }{\def\y{\scr@LT@array}}%
7148     \long\def\x{\refstepcounter#1#2\sharp#3#4\@nil}%
7149     \expandafter\endgroup
7150     \expandafter\def\y[##1]##2{%
7151       \H@refstepcounter{##1}%
7152       \hyper@makecurrent{table}%
7153       \let\Hy@LT@currentHref\@currentHref
7154       #2\sharp##4%
7155     }%
7156   }%
7157   \expandafter\expandafter\expandafter\x\y[##1]##2\@nil

```

Patch of \LT@start: add anchor before first line after \vskip\LTpre

```

7158 \begingroup
7159   \def\x#1\ifvoid\LT@foot#2\fi#3\@nil{%
7160     \endgroup
7161     \def\LT@start{%
7162       #1%
7163       \ifvoid\LT@foot#2\fi
7164       \let\@currentHref\Hy@LT@currentHref
7165       \Hy@raisedlink{%
7166         \hyper@anchorstart{\@currentHref}\hyper@anchorend
7167       }%
7168       #3%

```

```

7169      }%
7170      }%
7171  \expandafter\x\LT@start@nil
7172 }{%
7173 }{%

```

33 Equations

We want to make the whole equation a target anchor. Overload equation, temporarily reverting to original `\refstepcounter`. If, however, it is in AMS math, we do not do anything, as the tag mechanism is used there (see section 40). The exception is that we move the equation incrementation inside the math environment to avoid specials outside and a wrong vertical spacing of equation environments. This and more math related patches can be suppressed with `\hyper@nopatch@math-env`

```

7174 \let\new@refstepcounter\refstepcounter
7175 \let\H@equation\equation
7176 \let\H@endequation\endequation
7177 \@ifundefined{hyper@nopatch@mathenv}{%
7178   \@ifpackageloaded{amsmath}{%
7179     \long\def\Hy@temp{%
7180       \incr@eqnum
7181       \mathdisplay@push
7182       \st@rredfalse \global\@eqnswtrue
7183       \mathdisplay{equation}}%
7184   }%
7185   \ifx\Hy@temp\equation
7186     \expandafter\ifx\csname if@fleqn\expandafter\endcsname
7187       \csname iftrue\endcsname
7188   \else
7189     \long\def\equation{%
7190       \mathdisplay@push
7191       \st@rredfalse \global\@eqnswtrue
7192       \mathdisplay{equation}}%
7193       \incr@eqnum
7194   }%
7195   \fi
7196 \fi
7197 }{%
7198 \def\equation{%
7199   \let\refstepcounter\H@refstepcounter
7200   \H@equation
7201   \hyper@makecurrent{equation}}%

```

`\mathopen` is needed in case the equation starts with an unary minus, for example.

```

7202   \mathopen{%
7203     \Hy@raisedlink{\hyper@anchorstart{\@currentHref}}{%
7204   }%
7205   \let\refstepcounter\new@refstepcounter
7206   }%
7207 \def\endequation{%
7208   \ifx\Hy@raisedlink\ltx@empty

```

```

7209     \hyper@anchorend
7210     \else
7211     \mathclose{\Hy@raisedlink{\hyper@anchorend}}%
7212     \fi
7213     \H@endequation
7214   }%
7215 }
7216 }{}
```

My goodness, why can't L^AT_EX be consistent? Why is \eqnarray set up differently from other objects?

People (you know who you are, Thomas Beuth) sometimes make an eqnarray where *all* the lines end with \notag, so there is no suitable anchor at all. In this case, pass by on the other side.

```

7217 \newif\if@eqnstar
7218 \c@eqnstarfalse
7219 \let\H@eqnarray\eqnarray
7220 \let\H@endeqnarray\endeqnarray
7221 \c@ifundefined{hyper@nopatch@mathenv}{%
7222   \def\eqnarray{%
7223     \let\Hy@reserved@a\relax
7224     \def\@currentHref{}%
7225     \H@eqnarray
7226     \if@eqnstar
7227     \else
7228       \ifx\\@\currentHref\\%
7229     \else
7230       \hyper@makecurrent{equation}%
7231       \mathopen{%
7232         \Hy@raisedlink{%
7233           \hyper@anchorstart{\@currentHref}\hyper@anchorend
7234         }%
7235       }%
7236     \fi
7237   \fi
7238 }
7239 \def\endeqnarray{%
7240   \H@endeqnarray
7241 }
7242 }{}}
```

This is quite heavy-handed, but it works for now. If its an eqnarray* we need to disable the hyperref actions. There may well be a cleaner way to trap this. Bill Moss found this.

```

7243 \c@namedef{eqnarray*}{%
7244   \protected\def\c@eqncr{\nonumber\c@seqncr}\c@eqnstartrue\eqnarray
7245 }
7246 \c@namedef{endeqnarray*}{%
7247   \nonumber\endeqnarray\c@eqnstarfalse
7248 }
```

Then again, we have the *subeqnarray* package. Tanmoy provided some code for this:

```

7249 \ltx@IfUndefined{subeqnarray}{}{%
7250   \let\H@subeqnarray\subeqnarray
```

```

7251 \let\H@endsubeqnarray\endsubeqnarray
7252 \def\subeqnarray{%
7253   \let\Hy@reserved@a\relax
7254   \H@subeqnarray
7255   \hyper@makecurrent{equation}%
7256   \hyper@anchorstart{\@currentHref}{}\hyper@anchorend
7257 }%
7258 \def\endsubeqnarray{%
7259   \H@endsubeqnarray
7260 }%
7261 \providecommand\theHsubequation{\theHequation\alph{subequation}}%
7262 }

```

The aim of this macro is to produce a sanitized version of its argument, to make it a safe label.

```

7263 \def\make@stripped@name#1{%
7264   \begingroup
7265     \escapechar\m@ne
7266     \global\let\newname\empty
7267     \protected@edef\Hy@tempa{#1}%
7268     \edef\@tempb{%
7269       \noexpand\@tfor\noexpand\Hy@tempa:=%
7270         \expandafter\strip@prefix\meaning\Hy@tempa
7271     }%
7272     \@tempb\do{%
7273       \if\Hy@tempa\else
7274         \if}\Hy@tempa\else
7275           \xdef\newname{\newname\Hy@tempa}%
7276         \fi
7277       \fi
7278     }%
7279   \endgroup
7280 }

```

Support for amsmath's subequations:

```

7281 \ifcsname subequations\endcsname
7282   \let\HyOrg@subequations\subequations
7283   \def\subequations{%
7284     \stepcounter{equation}%
7285     \protected@edef\theHparentequation{\theHequation}%
7286     \addtocounter{equation}{-1}%
7287     \HyOrg@subequations
7288     \def\theHequation{\theHparentequation\alph{equation}}%
7289     \ignorespaces
7290   }%
7291 \fi

```

Support for theorems. We move the target into the para hook to avoid spacing problem. The patch will not apply to `\cleveref` but hopefully it does the right thing anyway. `\@currentHref` is updated directly for labels set before the actual start of the paragraph. The target can be behind a target created from a following list, so we restore `\@currentHref` just in case

```

7292 \newcommand\Hy@theorem@refstepcounter[1]{%
7293   \H@refstepcounter{#1}%
7294 }

```

```

7295 \hyper@makecurrent{#1}%
7296 \global\let\Hy@dth@currentHref\@currentHref
7297 \AddToHookNext{para/begin}
7298 {\let\Hy@tempa\@currentHref
7299 \MakeLinkTarget*\{\Hy@dth@currentHref\}%
7300 \global\let\@currentHref\Hy@tempa
7301 }%
7302 }
7303 \@ifundefined{hyper@nopatch@thm}{%
7304 \AtBeginDocument{%
7305 \@ifpackageloaded{cleveref}{%
7306 {\AddToHook{cmd/@thm/before}{\ifhmode\unskip\f}}%
7307 }%
7308 \ifpatchable@thm{\refstepcounter}{%
7309 {\patchcmd{\@thm}{\refstepcounter}{\Hy@theorem@refstepcounter}{}{}}%
7310 }%
7311 }}}{}}

```

34 Footnotes

The footnote mark is a hypertext link, and the text is a target. We separately number the footnotes sequentially through the text, separately from whatever labels the text assigns. Too hard to keep track of markers otherwise. If the raw forms `\footnotemark` and `\footnotetext` are used, force them to use un-hyper original. If `\hyper@nopatch@footnote` is defined we don't patch but assume that addings links to footnotes is handled elsewhere.

```

7312 \@ifundefined{hyper@nopatch@footnote}{%
7313 \ifHy@hyperfootnotes
7314 \newcounter{Hfootnote}%
7315 \let\H@footnotetext\footnotetext
7316 \let\H@footnotemark\footnotemark
7317 \def\xfootnotenext[#1]{%
7318 \begingroup
7319 \csname c@\@mpfn\endcsname #1\relax
7320 \unrestored@protected\xdef\@thefnmark{\thempfn}%
7321 \endgroup
7322 \ifx\@footnotetext\@mpfootnotetext
7323 \expandafter\H@mpfootnotetext
7324 \else
7325 \expandafter\H@footnotetext
7326 \fi
7327 }%
7328 \def\xfootnotemark[#1]{%
7329 \begingroup
7330 \c@footnote #1\relax
7331 \unrestored@protected\xdef\@thefnmark{\thefootnote}%
7332 \endgroup
7333 \H@footnotemark
7334 }%
7335 \let\H@mpfootnotetext\mpfootnotetext
7336 \long\def\mpfootnotetext#1{%
7337 \H@mpfootnotetext{%

```

```

7338 \ifHy@nesting
7339   \expandafter\ltx@firstoftwo
7340 \else
7341   \expandafter\ltx@secondoftwo
7342 \fi
7343 }%
7344   \expandafter\hyper@@anchor\expandafter{%
7345     \Hy@footnote@currentHref
7346   }{\ignorespaces #1}%
7347 }{%
7348   \Hy@raisedlink{%
7349     \expandafter\hyper@@anchor\expandafter{%
7350       \Hy@footnote@currentHref
7351     }{\relax}%
7352   }{\ignorespaces #1}%
7353 }%
7354 }%
7355 }%
7356 \long\def\@footnotetext#1{%
7357   \H@@footnotetext{%
7358     \ifHy@nesting
7359       \expandafter\ltx@firstoftwo
7360     \else
7361       \expandafter\ltx@secondoftwo
7362     \fi
7363   }%
7364   \expandafter\hyper@@anchor\expandafter{%
7365     \Hy@footnote@currentHref
7366   }{\ignorespaces #1}%
7367 }{%
7368   \Hy@raisedlink{%
7369     \expandafter\hyper@@anchor\expandafter{%
7370       \Hy@footnote@currentHref
7371     }{\relax}%
7372   }%
7373   \let\@currentHref\Hy@footnote@currentHref
7374   \let\@currentlabelname\@empty
7375   \ignorespaces #1}%
7376 }%
7377 }%
7378 }%

```

Redefine `\@footnotemark`, borrowing its code (at the cost of getting out of sync with `latex.ltx`), to take advantage of its white space and hyphenation fudges. If we just overload it, we can get variant documents (the word before the footnote is treated differently). Thanks to David Carlisle and Brian Ripley for confusing and helping me on this.

```

7379 \def\@footnotemark{%
7380   \leavevmode
7381   \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
7382   \stepcounter{Hfootnote}%
7383   \global\let\Hy@saved@currentHref\@currentHref
7384   \hyper@makecurrent{Hfootnote}%
7385   \global\let\Hy@footnote@currentHref\@currentHref

```

```

7386 \global\let\@currentHref\Hy@saved@currentHref
7387 \hyper@linkstart{link}{\Hy@footnote@currentHref}%
7388 \makefnmark
7389 \hyper@linkend
7390 \ifhmode\spacefactor\@x@sf\fi
7391 \relax
7392 }%

```

Tabularx causes footnote problems, disable the linking if that is loaded. Since v6.82i footnotes are only disabled inside the environment ‘tabularx’.

```

7393 \@ifpackageloaded{tabularx}{%
7394   \let\HyOrg@TX@endtabularx\TX@endtabularx
7395   \def\Hy@tabularx@hook{%
7396     \let\@footnotetext\H@@footnotetext
7397     \let\@footnotemark\H@@footnotemark
7398     \let\@mpfootnotetext\H@@mpfootnotetext
7399   }%
7400   \begingroup
7401     \toks@\expandafter{\TX@endtabularx}%
7402     \xdef\Hy@gtemp{%
7403       \noexpand\Hy@tabularx@hook
7404       \the\toks
7405     }%
7406   \endgroup
7407   \let\TX@endtabularx\Hy@gtemp
7408 }{}%

```

Support for footnotes in p columns of longtable. Here \footnote commands are splitted into \footnotemark and a call of \footnotetext with the optional argument, that is not supported by hyperref. The result is a link by \footnotemark without valid anchor

```

7409 \@ifpackageloaded{longtable}{%
7410   \CheckCommand{\LT@p@ftntext}[1]{%
7411     \edef\@tempa{%
7412       \the\LT@p@ftn
7413       \noexpand\footnotetext[\the\c@footnote]%
7414     }%
7415     \global\LT@p@ftn\expandafter{\@tempa{\#1}}%
7416   }%
7417   \long\def\LT@p@ftntext{\%
7418     \edef\@tempa{%
7419       \the\LT@p@ftn
7420       \begingroup
7421         \noexpand\c@footnote=\the\c@footnote\relax
7422         \noexpand\protected\xdef\noexpand\@thefnmark{%
7423           \noexpand\thempfn
7424         }%
7425         \noexpand\Hy@LT@footnotetext{%
7426           \Hy@footnote@currentHref
7427         }%
7428       }%
7429     \global\LT@p@ftn\expandafter{%
7430       \@tempa{\#1}%
7431     }%
7432   }%

```

```

7433   }%
7434   \long\def\Hy@LT@footnotetext{\#1\#2{%
7435     \H@footnotetext{%
7436       \ifHy@nesting
7437         \hyper@@anchor{\#1}{\#2}%
7438       \else
7439         \Hy@raisedlink{%
7440           \hyper@@anchor{\#1}{\relax}%
7441         }%
7442       \def\@currentHref{\#1}%
7443       \let\@currentlabelname\@empty
7444       \#2%
7445     \fi
7446   }%
7447 }%
7448 }{}}%

```

Footnotes for fancyvrb (Fix by Manuel Pégourié-Gonnard).

```

7449  \@ifpackageloaded{fancyvrb}{%
7450    \def\V@footnotetext{%
7451      \insert\footins\bgroup
7452      \csname reset@font\endcsname
7453      \footnotesize
7454      \interlinepenalty\interfootnotelinepenalty
7455      \splittopskip\footnotesep
7456      \splitmaxdepth\dp\strutbox
7457      \floatingpenalty \MM
7458      \hsize\columnwidth
7459      \parboxrestore
7460      \def\@currentcounter{footnote}%
7461        \protected@edef\@currentlabel{\csname p@footnote\endcsname\@thefn-
mark}%
7462        \makefntext{}%
7463        \rule{\z@}{\footnotesep}%
7464      \bgroup
7465      \aftergroup\V@@footnotetext
7466      \Hy@raisedlink{%
7467        \expandafter\hyper@@anchor\expandafter{%
7468          \Hy@footnote\@currentHref
7469        }{\relax}%
7470      }%
7471      \let\@currentHref\Hy@footnote\@currentHref
7472      \let\@currentlabelname\@empty
7473      \ignorespaces
7474    }%
7475  }{}}%

```

KOMA-Script or newer LaTeX defines \footref that uses both \ref and \footnotemark resulting in two links, one of them wrong.

```

7476  \def\Hy@temp{\#1{%
7477    \begingroup
7478    \unrestored@protected\xdef\@thefnmark{\ref{\#1}}%
7479  \endgroup
7480  \footnotemark
7481 }%

```

```

7482 \ifx\Hy@temp\footref
7483   \def\footref#1{%
7484     \begingroup
7485       \unrestored@protected@xdef\@thefnmark{\ref{#1}}%
7486     \endgroup
7487     \H@@footnotemark
7488   }%
7489 \fi

```

But the special footnotes in `\maketitle` are much too hard to deal with properly. Let them revert to plain behaviour. The koma classes add an optional argument.

```

7490 \let\HyOrg@maketitle\maketitle
7491 \def\maketitle{%
7492   \let\Hy@saved@footnotemark\@footnotemark
7493   \let\Hy@saved@footnotetext\@footnotetext
7494   \let\@footnotemark\H@@footnotemark
7495   \let\@footnotetext\H@@footnotetext
7496   \@ifnextchar[\Hy@maketitle@optarg{%
7497     \HyOrg@maketitle
7498     \Hy@maketitle@end
7499   }%
7500 }%
7501 \def\Hy@maketitle@optarg[#1]{%
7502   \HyOrg@maketitle{[#1]}%
7503   \Hy@maketitle@end
7504 }%
7505 \def\Hy@maketitle@end{%
7506   \@ifx\@footnotemark\H@@footnotemark
7507     \let\@footnotemark\Hy@saved@footnotemark
7508   \fi
7509   \@ifx\@footnotetext\H@@footnotetext
7510     \let\@footnotetext\Hy@saved@footnotetext
7511   \fi
7512 }%

```

`\realfootnote` Does anyone remember the function and purpose of `\realfootnote`?

```

7513 \def\realfootnote{%
7514   \@ifnextchar[\@xfootnote{%
7515     \stepcounter{\@mpfn}%
7516     \protected@xdef\@thefnmark{\thempfn}%
7517     \H@@footnotemark\H@@footnotetext
7518   }%
7519 }%
7520 \fi
7521 }{}}
7522 \Hy@DisableOption{hyperfootnotes}

7523 </packageEnd>
7524 <*check>
7525 \checklateX
7526 \checkcommand\def\@xfootnotenext[#1]{%
7527   \begingroup
7528     \csname c@\@mpfn\endcsname #1\relax

```

```

7529   \unrestored@protected@xdef\@thefnmark{\thempfn}%
7530   \endgroup
7531   \@footnotetext
7532 }
7533 \checkcommand\def\@xfootnotemark[#1]{%
7534   \begingroup
7535     \c@footnote #1\relax
7536     \unrestored@protected@xdef\@thefnmark{\thefootnote}%
7537   \endgroup
7538   \@footnotemark
7539 }
7540 \checkcommand\def\@footnotemark{%
7541   \leavevemode
7542   \ifhmode\edef\@x@sf{\the\spacefactor}\nobreak\fi
7543   \@makefnmark
7544   \ifhmode\spacefactor\@x@sf\fi
7545   \relax
7546 }
7547 </check>
7548 <*packageEnd>

```

35 Float captions

Make the float caption the hypertext anchor; curiously enough, we can't just copy the definition of \caption. Its all to do with expansion. It screws up. Sigh.

```

7549 \@ifundefined{hyper@nopatch@caption}{%
7550   \def\caption{%
7551     \ifx\@captype\@undefined
7552       \@latex@error{\noexpand\caption outside float}\@ehd
7553       \expandafter\@gobble
7554     \else
7555       \H@refstepcounter\@captype
7556       \let\Hy@tempa\caption
7557       \@ifundefined{float@caption}{%
7558         }{%
7559           \expandafter\ifx\csname float@c@\@captype\endcsname
7560             \float@caption
7561             \let\Hy@tempa\Hy@float@caption
7562           \fi
7563         }%
7564       \expandafter\@firstofone
7565     \fi
7566   }{\@dblarg{\Hy@tempa\@captype}}%
7567 }
7568 \long\def\@caption#1[#2]{#3}{%
7569   \expandafter\ifx\csname if@capstart\expandafter\endcsname
7570     \csname iftrue\endcsname
7571     \global\let\@currentHref\hc@currentHref
7572   \else
7573     \hyper@makecurrent{\@captype}%
7574   \fi
7575   \@ifundefined{NR@getttitle}{%
7576     \def\@currentlabelname{#2}%

```

```

7577  }{%
7578    \NR@getttitle{\#2}%
7579  }%
7580  \par\addcontentsline{\csname ext@\#1\endcsname}{\#1}{%
7581    \protect\numberline{\csname the\#1\endcsname}\ignorespaces #2}%
7582 }%
7583 \begingroup
7584   \parboxrestore
7585   \if@minipage
7586     \setminipage
7587   \fi
7588   \normalsize
7589   \expandafter\ifx\csname if@capstart\expandafter\endcsname
7590     \csname iftrue\endcsname
7591     \global\@capstartfalse
7592     \makecaption{\csname fnum@\#1\endcsname}\ignorespaces#3}%
7593 \else
7594   \makecaption{\csname fnum@\#1\endcsname}\ignorespaces
7595   \ignorespaces

```

If we cannot have nesting, the anchor is empty.

```

7596  \ifHy@nesting
7597    \expandafter\hyper@@anchor\expandafter{\@currentHref}{\#3}%
7598  \else
7599    \Hy@raisedlink{%
7600      \expandafter\hyper@@anchor\expandafter{%
7601        \@currentHref
7602      }{\relax}}%
7603    }%
7604    \#3%
7605  \fi
7606  }%
7607  \fi
7608  \par
7609  \endgroup
7610 }{}%end no patch

```

Compatibility with float.sty: anchor setting at the top of the float, if the float is controlled by float.sty. Several \caption commands inside one float are not supported.

\HyNew@float@makebox is introduced as feature request of Axel Sommerfeldt to make the life easier for his package ‘caption’.

```

7611 \let\Hy@float@caption\@caption
7612 \newcommand{\HyNew@float@makebox}[1]{%
7613   \HyOrg@float@makebox{%
7614     #1\relax
7615     \ifx\Hy@float@currentHref\@undefined
7616     \else
7617       \expandafter\hyper@@anchor\expandafter{%
7618         \Hy@float@currentHref
7619       }{\relax}}%
7620     \global\let\Hy@float@currentHref\@undefined
7621   \fi
7622 }%
7623 }%

```

```

7624 \@ifpackageloaded{float}{%
7625   \def\Hy@float@caption{%
7626     \ifx\Hy@float@currentHref\@undefined
7627       \hyper@makecurrent{\@capttype}%
7628       \global\let\Hy@float@currentHref\@currentHref
7629     \else
7630       \let\@currentHref\Hy@float@currentHref
7631     \fi
7632   }%
7633 }%
7634 \let\HyOrg@float@makebox\float@makebox
7635 \let\float@makebox\HyNew@float@makebox
7636 }{}}

7637 
```

7638 (*check)

7639 \checklateX[1999/06/01 - 2000/06/01]

7640 \checkcommand\def\caption{%

7641 \ifx\@capttype\@undefined

7642 \@latex@error{\noexpand\caption outside float}\@ehd

7643 \expandafter\gobble

7644 \else

7645 \refstepcounter\@capttype

7646 \expandafter\@firstofone

7647 \fi

7648 {\@dblarg{\@caption\@capttype}}%

7649 }

7650 \checkcommand\long\def\@caption#1[#2]#3{%
7651 \par
7652 \addcontentsline{\csname ext@\#1\endcsname}{\#1}{%
7653 \protect\numberline{\csname the\#1\endcsname}{\ignorespaces #2}}%
7654 }%
7655 \begingroup
7656 \parboxrestore
7657 \if@minipage
7658 \setminipage
7659 \fi
7660 \normalsize
7661 \makecaption{\csname fnum@\#1\endcsname}{\ignorespaces #3}\par
7662 \endgroup
7663 }
7664

7665 (*packageEnd)

36 Bibliographic references

This is not very robust, since many styles redefine these things. The package used to redefine \citet and the like; then we tried adding the hyperref call explicitly into the .aux file. Now we redefine \bibtex; this still breaks some citation packages so we have to work around them. But this remains extremely dangerous. Any or all of *achemso* and *drftcite* may break.

However, lets make an attempt to get *natbib* right, because that's a powerful, important package. Patrick Daly (daly@linmpi.mpg.de) has provided hooks for

us, so all we need to do is activate them.

```

7666 \def\hyper@natlinkstart#1{%
7667   \Hy@backout{#1}%
7668   \hyper@linkstart{cite}{cite.\#1}%
7669   \def\hyper@nat@current{#1}%
7670 }
7671 \def\hyper@natlinkend{%
7672   \hyper@linkend
7673 }
7674 \def\hyper@natlinkbreak#1#2{%
7675   \hyper@linkend#1\hyper@linkstart{cite}{cite.\#2}%
7676 }
7677 \def\hyper@natanchorstart#1{%
7678   \Hy@raisedlink{\hyper@anchorstart{cite.\#1}}%
7679 }
7680 \def\hyper@natanchorend{\hyper@anchorend}

```

Do not play games if we have natbib support. Macro extra@binfo added for chapterbib support. Chapterbib also wants \extra@binfo in the hyper-link, but since the link tag is not expanded immediately, we use \extra@b@citeb, so cites in a chapter will link to the bibliography in that chapter.

```

7681 \ifundefined{hyper@nopatch@bib}
7682 {%
7683   \ltx@ifUndefined{NAT@parse}{%
7684     \providecommand*\@extra@binfo{}%
7685     \providecommand*\@extra@b@citeb{}%
7686     \def\bibcite#1#2{%
7687       \newl@bel{b}{\#1\@extra@binfo}{%
7688         \hyper@link[cite]{\#1\@extra@b@citeb}{\#2}}%
7689     }%
7690   }%
7691   \gdef\@extra@binfo{}%

```

Package `babel` redefines `\bibcite` with macro `\bb@cite@choice`. It needs to be overwritten to avoid the warning “Label(s) may have changed.”.

```

7692   \let\Hy@bibcite\bibcite
7693   \begingroup
7694     \ifundefined{bb@cite@choice}{}{%
7695       \g@addto@macro\bb@cite@choice{%
7696         \let\bibcite\Hy@bibcite
7697       }%
7698     }%
7699   \endgroup
\@BIBLABEL is working around a ‘feature’ of RevTeX.
7700   \providecommand*\@BIBLABEL{\@biblabel}%
7701   \def\@lbibitem[#1]#2{%
7702     \@skiphyperreftrue
7703     \H@item{%
7704       \ifx\Hy@raisedlink\empty
7705         \hyper@anchorstart{cite.\#2\@extra@b@citeb}%
7706         \@BIBLABEL{#1}%
7707         \hyper@anchorend
7708       \else
7709         \Hy@raisedlink{%

```

```

7710      \hyper@anchorstart{cite.\#2@\extra@b@citeb}\hyper@anchorend
7711      }%
7712      \OBIBLABEL{\#1}%
7713      \fi
7714      \hfill
7715      }%
7716      \@skiphyperreffalse
7717      \if@filesw
7718      \begingroup
7719      \let\protect\noexpand
7720      \immediate\write\auxout{%
7721      \string\bibcite{\#2}{\#1}%
7722      }%
7723      \endgroup
7724      \fi
7725      \ignorespaces
7726      }%

```

Since `\bibitem` is doing its own labelling, call the raw version of `\item`, to avoid extra spurious labels

```

7727      \def\@bibitem#1{%
7728      \@skiphyperreftrue\H@item\@skiphyperreffalse
7729      \Hy@raisedlink{%
7730      \hyper@anchorstart{cite.\#1@\extra@b@citeb}\relax\hyper@anchorend
7731      }%
7732      \if@filesw
7733      \begingroup
7734      \let\protect\noexpand
7735      \immediate\write\auxout{%
7736      \string\bibcite{\#1}{\the\value{\@listctr}}}%
7737      }%
7738      \endgroup
7739      \fi
7740      \ignorespaces
7741      }%
7742  }{}%
7743 }{}}

7744 </packageEnd>
7745 <*check>
7746 \checklateX
7747 \checkcommand\def\@lbibitem[#1]{%
7748  \item[\@biblabel{\#1}\hfill]%
7749  \if@filesw
7750  {%
7751  \let\protect\noexpand
7752  \immediate\write\auxout{%
7753  \string\bibcite{\#2}{\#1}%
7754  }%
7755  }%
7756  \fi
7757  \ignorespaces
7758 }
7759 \checkcommand\def\@bibitem#1{%
7760  \item

```

```
7761 \if@filesw
7762   \immediate\write\@auxout{%
7763     \string\bibcite{#1}{\the\value{\@listctr}}%
7764   }%
7765 \fi
7766 \ignorespaces
7767 }
7768 </check>
7769 <*packageEnd>
```

36.1 Package harvard

Override Peter Williams' Harvard package; we have to a) make each of the citation types into a link; b) make each citation write a backref entry, and c) kick off a backreference section for each bibliography entry.

The redefinitions have to be deferred to `\begin{document}`, because if `harvard.sty` is loaded and `html.sty` is present and detects `pdTeX`, then `hyperref` is already loaded at the begin of `harvard.sty`, and the `\newcommand` macros causes error messages.

```

7770 \@ifpackageloaded{harvard}{%
7771   \Hy@AtBeginDocument{%
7772     \Hy@Info{*** compatibility with harvard **** }%
7773     \Hy@raiselinksfalse
7774   \def\harvardcite{\#1\#2\#3\#4{%
7775     \global\cnamedef{HAR@fn\#1}{\hyper@link[cite]{}{\cite.\#1}{\#2}}%
7776     \global\cnamedef{HAR@an\#1}{\hyper@link[cite]{}{\cite.\#1}{\#3}}%
7777     \global\cnamedef{HAR@yr\#1}{\hyper@link[cite]{}{\cite.\#1}{\#4}}%
7778     \global\cnamedef{HAR@df\#1}{\csname HAR@fn\#1\endcsname}%
7779   }%
7780   \def\HAR@citetoaux{\#1{%
7781     \if@filesw\immediate\write\auxout{\string\citation{\#1}}\fi%
7782     \ifHy@backref
7783       \ifx\@empty\currentlabel
7784         \else
7785           \bsphack
7786           \if@filesw
7787             \protected\write\auxout{%
7788               \string\@writefile{brf}{%
7789                 \string\backcite{\#1}{%
7790                   {\thepage}{\@currentlabel}{\@currentHref}}%
7791                 }%
7792               }%
7793             }%
7794             \fi
7795             \esphead
7796           \fi
7797           \fi
7798   }%
7799   \def\harvarditem{%
7800     \@ifnextchar{`}{\harvarditem}{\harvarditem[\null]}%
7801   }%
7802   \def\@harvarditem[#1]{\par{%
7803     \item[]\#1}%

```

```

7804 \hyper@anchorstart{cite.\#4}\relax\hyper@anchorend
7805 \if@filesw
7806   \begingroup
7807     \def\protect##1{\string ##1\space}%
7808     \ifthenelse{\equal{#1}{\null}}%
7809       {\def\next{{#4}{#2}{#2}{#3}}}%
7810       {\def\next{{#4}{#2}{#1}{#3}}}%
7811     \immediate\write\auxout{\string\harvardcite\codeof\next}%
7812   \endgroup
7813 \fi
7814 \protect\hspace*{-\labelwidth}%
7815 \protect\hspace*{-\labelsep}%
7816 \ignorespaces
7817 #5%
7818 \ifHy@backref
7819   \newblock
7820   \backref{\csname br@\#4\endcsname}%
7821 \fi
7822 \par
7823 }%

```

\HAR@checkcitations Package hyperref has added \hyper@link, so the original test \HAR@checkcitations will fail every time and always will appear the “Changed labels” warning. So we have to redefine \Har@checkcitations:

```

7824 \long\def\HAR@checkcitations#1#2#3#4{%
7825   \def\HAR@tempa{\hyper@link[cite]{}{cite.\#1}{#2}}%
7826   \expandafter\ifx\csname HAR@fn@\#1\endcsname\HAR@tempa
7827     \def\HAR@tempa{\hyper@link[cite]{}{cite.\#1}{#3}}%
7828   \expandafter\ifx\csname HAR@an@\#1\endcsname\HAR@tempa
7829     \def\HAR@tempa{\hyper@link[cite]{}{cite.\#1}{#4}}%
7830   \expandafter\ifx\csname HAR@yr@\#1\endcsname\HAR@tempa
7831     \else
7832       \tempswattrue
7833     \fi
7834   \else
7835     \tempswattrue
7836   \fi
7837   \else
7838     \tempswattrue
7839   \fi
7840 }%
7841 }%
7842 }{}%

```

36.2 Package chicago

The links by \citeN and \shortciteN should include the closing parentheses.

```
7843 \@ifpackageloaded{chicago}{%
```

```
\citeN
7844 \def\citeN{%
7845   \def\@citesep{~-1000}%
```

```

7846  \def\@cite##1##2##1{%
7847  \def\citeauthoryear##1##2##3##1 {##3\@cite@opt}}%
7848  \@citedata@opt
7849 }%}

\shortciteN
7850 \def\shortciteN{%
7851  \def\@citeseppen{-1000}%
7852  \def\@cite##1##2##1{%
7853  \def\citeauthoryear##1##2##3##2 {##3\@cite@opt}}%
7854  \@citedata@opt
7855 }%}

\@citedata@opt
7856 \def\@citedata@opt{%
7857  \let\@cite@opt\@empty
7858  \@ifnextchar [{%
7859   \tempswatru
7860   \@citedatax@opt
7861 }{%
7862   \tempswafalse
7863   \@citedatax[]%
7864 }%
7865 }%}

\@citedatax@opt
7866 \def\@citedatax@opt[#1]{%
7867  \def\@cite@opt{, #1}%
7868  \@citedatax[{\#1}]%
7869 }%}

7870 }{}}

```

37 Page numbers

The last page should not contain a /Dur key, because there is no page after the last page. Therefore at the last page there should be a command \hypersetup{pdfpageduration={}}. This can be set with \AtEndDocument, but it can be too late, if the last page is already finished, or too early, if lots of float pages will follow. Therefore currently nothing is done by hyperref.

This where we supply a destination for each page.

```

7871 \ltx@ifclassloaded{slides}{%
7872  \def\Hy@SlidesFormatOptionalPage##1{(\#1)}%
7873  \def\Hy@PageAnchorSlidesPlain{%
7874    \advance\c@page\ltx@one
7875    \edef\Hy@TempPageAnchor{%
7876      \noexpand\hyper@@anchor{%
7877        page.\the\c@slide.\the\c@overlay.\the\c@note}%
7878      \ifnum\c@page=\ltx@one
7879      \else
7880        .\the\c@page
7881      \fi

```

```

7882      }%
7883  }%
7884  \advance\c@page-\ltx@one
7885 }%
7886 \def\Hy@PageAnchorSlide{%
7887   \advance\c@page\ltx@one
7888   \ifnum\c@page>\ltx@one
7889     \ltx@ifundefined{theHpage}{%
7890       \protected@edef\Hy@TheSlideOptionalPage{%
7891         \Hy@SlidesFormatOptionalPage{\thepage}}%
7892     }%
7893   }{%
7894     \protected@edef\Hy@TheSlideOptionalPage{%
7895       \Hy@SlidesFormatOptionalPage{\theHpage}}%
7896     }%
7897   }%
7898 \else
7899   \def\Hy@TheSlideOptionalPage{}%
7900 \fi
7901 \advance\c@page-\ltx@one
7902 \pdfstringdef\@the@H@page{%
7903   \csname
7904     the\%
7905   \ltx@ifundefined{theH\Hy@SlidesPage}{}{H}%
7906   \Hy@SlidesPage
7907   \endcsname
7908   \Hy@TheSlideOptionalPage
7909 }%
7910 \ltx@gobblethree
7911 }%
7912 \def\Hy@SlidesPage[slide]{%
7913 \g@addto@macro\slide{%
7914   \def\Hy@SlidesPage[slide]{%
7915 }%
7916 \g@addto@macro\overlay{%
7917   \def\Hy@SlidesPage[overlay]{%
7918 }%
7919 \g@addto@macro\note{%
7920   \def\Hy@SlidesPage[note]{%
7921 }%
7922 }{%
7923 \def\Hy@PageAnchorSlidesPlain{}%
7924 \def\Hy@PageAnchorSlide{}%
7925 }
7926 \def\Hy@EveryPageAnchor{%
7927 \Hy@DistillerDestFix
7928 \ifHy@pageanchor
7929   \ifHy@hypertexnames
7930     \ifHy@plainpages
7931       \def\Hy@TempPageAnchor{\hyper@anchor{page.\the\c@page}}%
7932       \Hy@PageAnchorSlidesPlain
7933     \else
7934       \begingroup
7935         \let\@number\@firstofone

```

```

7936      \Hy@unicodedefalse
7937      \Hy@PageAnchorSlide
7938      \pdfstringdef{\the@H@page}{\thepage}%
7939      \endgroup
7940      \Edef\UnescapeString{\the@H@page}{\the@H@page}%
7941      \def\Hy@TempPageAnchor{\hyper@anchor{page.\the@H@page}}%
7942      \fi
7943 \else
7944     \Hy@GlobalStepCount\Hy@pagecounter
7945     \def\Hy@TempPageAnchor{%
7946       \hyper@anchor{page.\the\Hy@pagecounter}}%
7947     }%
7948 \fi
7949 \vbox to 0pt{%
7950   \kern\voffset
7951   \kern\topmargin
7952   \kern-1bp\relax
7953   \hbox to 0pt{%
7954     \kern\hoffset
7955     \kern\ifodd\value{page}%
7956       \oddsidemargin
7957     \else
7958       \evensidemargin
7959     \fi
7960     \kern-1bp\relax
7961     \Hy@TempPageAnchor\relax
7962     \hss
7963   }%
7964   \vss
7965 }%
7966 \fi
7967 }
7968 \g@addto@macro\Hy@EveryPageBoxHook{%
7969   \Hy@EveryPageAnchor
7970 }

```

38 Table of contents

TV Raman noticed that people who add arbitrary material into the TOC generate a bad or null link. We avoid that by checking if the current destination is empty. But if ‘the most recent destination’ is not what you expect, you will be in trouble. In newer L^AT_EX releases this is defined to put a % at the end of the line in the tocfile.

```

7971 \providecommand\protected@file@percent{}%
7972 \@ifundefined{hyper@nopatch@toc}{%
7973   \def\addcontentsline#1#2#3{%
7974     \begingroup
7975     \let\label\@gobble
7976     \ifx\@currentHref\@empty
7977       \Hy@Warning{%
7978         No destination for bookmark of \string\addcontentsline,%
7979         \MessageBreak destination is added%}

```

```

7980      }%
7981      \phantomsection
7982  \fi
7983  \expandafter\ifx\csname toplevel@#2\endcsname\relax
7984      \begingroup
7985          \def\Hy@tempa{#1}%
7986          \ifx\Hy@tempa\Hy@bookmarkstype
7987              \Hy@WarningNoLine{%
7988                  bookmark level for unknown #2 defaults to 0%
7989              }%
7990          \else
7991              \Hy@Info{bookmark level for unknown #2 defaults to 0}%
7992          \fi
7993      \endgroup
7994      \expandafter\gdef\csname toplevel@#2\endcsname{0}%
7995  \fi
7996  \edef\Hy@toplevel{\csname toplevel@#2\endcsname}%
7997  \Hy@writebookmark{\csname the#2\endcsname}%
7998      {#3}%
7999      {\@currentHref}%
8000      {\Hy@toplevel}%
8001      {#1}%
8002  \ifHy@verbose
8003      \begingroup
8004          \def\Hy@tempa{#3}%
8005          \conelevel@sanitize\Hy@tempa
8006          \let\temp@online\on@line
8007          \let\on@line\@empty
8008          \Hy@Info{%
8009              bookmark\temp@online:\MessageBreak
8010              thecounter {\csname the#2\endcsname}\MessageBreak
8011              text {\Hy@tempa}\MessageBreak
8012              reference {\@currentHref}\MessageBreak
8013              toplevel {\Hy@toplevel}\MessageBreak
8014              type {#1}%
8015          }%
8016      \endgroup
8017  \fi
8018  \addtocontents{#1}{%
8019      \protect\contentsline{#2}{#3}{\thepage}{\@currentHref}\protected@file@per-
cent
8020  }%
8021  \endgroup
8022 }
8023 }{}}

```

\contentsline The page number might be empty. In this case the link for the page number is suppressed to avoid little link boxes.

change 2022-11-13: To avoid problems if MakeUppercase is used around the entry we use special protected commands:

```

8024 \protected\def\Hy@toclinkstart{\hyper@linkstart{link}{\Hy@tocdestname}}
8025 \protected\def\Hy@toclinkend{\hyper@linkend}
8026
8027 \@ifundefined{hyper@nopatch@toc}{%

```

```

8028 \def\contentsline#1#2#3#4{%
8029   \begingroup
8030     \Hy@safe@activestore
8031   \edef\x{\endgroup
8032     \def\noexpand\Hy@tocdestname{#4}%
8033   }\x
8034 \ifx\Hy@tocdestname\ltx@empty
8035   \csname l@#1\endcsname{#2}{#3}%
8036 \else
8037   \ifcase\Hy@linktoc % none
8038     \csname l@#1\endcsname{#2}{#3}%
8039   \or % section
8040     \csname l@#1\endcsname{%
8041       \Hy@toalinkstart{#2}\Hy@toalinkend
8042     }{#3}%
8043   \or % page
8044     \def\Hy@temp{#3}%
8045     \ifx\Hy@temp\ltx@empty
8046       \csname l@#1\endcsname{#2}{#3}%
8047     \else
8048       \csname l@#1\endcsname{#2}{%
8049         \Hy@toalinkstart{#3}\Hy@toalinkend
8050       }%
8051     \fi
8052   \else % all
8053     \def\Hy@temp{#3}%
8054     \ifx\Hy@temp\ltx@empty
8055       \csname l@#1\endcsname{%
8056         \Hy@toalinkstart{#2}\Hy@toalinkend
8057       }%
8058     \else
8059       \csname l@#1\endcsname{%
8060         \Hy@toalinkstart{#2}\Hy@toalinkend
8061       }%
8062       \Hy@toalinkstart{#3}\Hy@toalinkend
8063     }%
8064   \fi
8065 \fi
8066 \fi
8067 }
8068 }{}}

8069 
```

```

8070 <*check>
8071 \checklateX
8072 \checkcommand\def\addcontentsline#1#2#3{%
8073   \addtocontents{#1}{\protect\contentsline{#2}{#3}{\thepage}}%
8074 }
8075 \checkcommand\def\contentsline#1{\csname l@#1\endcsname}
8076 
```

```

8077 <*packageEnd>
```

39 New counters

The whole theorem business makes up new counters on the fly; we are going to intercept this. Sigh. Do it at the level where new counters are defined.

```
8078 \@ifundefined{hyper@nopatch@counter}
8079   {
8080     \let\H@definecounter\@definecounter
8081     \def\@definecounter#1{%
8082       \H@definecounter{#1}%
8083       \expandafter\gdef\csname theH#1\endcsname{\arabic{#1}}%
8084     }
8085   }{}
```

But what if they have used the optional argument to e.g. `\newtheorem` to determine when the numbering is reset? OK, we'll trap that too.

```
8086 \@ifundefined{hyper@nopatch@counter}
8087   {
8088     \let\H@newctr\@newctr
8089     \def\@newctr#1[#2]{%
8090       \H@newctr#1[#2]%
8091       \expandafter\gdef\csname theH#1\endcsname{%
8092         \csname the\@ifundefined{theH#2}{\{}{H}\#2\endcsname.\arabic{#1}}%
8093       }%
8094     }
8095   }{}
```

40 AMS^LA_TE_X compatibility

Oh, no, they don't use anything as simple as `\refstepcounter` in the AMS! We need to intercept some low-level operations of theirs. Damned if we are going to try and work out what they get up to. Just stick a label of 'AMS' on the front, and use the label *they* worked out. If that produces something invalid, I give up. They'll change all the code again anyway, I expect (SR).

Version 6.77p uses a patch by Ross Moore.

If `\hyper@nopatch@amsmath@tag` is defined we don't patch but assume that kernel code adds anchors to equations.

```
8096 \@ifundefined{hyper@nopatch@amsmath@tag}
8097   {%
8098     \@ifpackageloaded{amsmath}{%
8099       \def\Hy@make@anchor{%
8100         \Hy@MakeCurrentHrefAuto{AMS}%
8101         \Hy@raisedlink{\hyper@anchorstart{\@currentHref}\hyper@anchorend}%
8102       }%
8103       \def\Hy@make@df@tag@@#1{%
8104         \gdef\df@tag{%
8105           \maketag@@@{\Hy@make@anchor#1}%
8106           \def\@currentlabel{#1}%
8107         }%
8108       }%
8109       \def\Hy@make@df@tag@@@#1{%
8110         \gdef\df@tag{%
8111           \tagform@{\Hy@make@anchor#1}%
8112         }%
8113       }%
8114     }%
8115   }%
```

```

8112     \toks@{\exp{\p@equation{#1}}%
8113     \edef\@currentlabel{\the\toks@}%
8114     }%
8115   }%
8116   \let\HyOrg@make@df@tag@@\make@df@tag@@
8117   \let\HyOrg@make@df@tag@@@\make@df@tag@@@
8118   \let\make@df@tag@@\Hy@make@df@tag@@
8119   \let\make@df@tag@@@\Hy@make@df@tag@@@
8120   }{}}
8121 }{}

```

This code I simply cannot remember what I was trying to achieve. The final result seems to do nothing anyway.

```

\let\H@tagform@\tagform@
\def\tagform@#1{%
  \maketag@@@\{\hyper@anchor{\@currentHref}%
  {(\ignorespaces#1\unskip)}\}%
}
\def\eqref#1{\textup{\H@tagform@\{\ref{#1}\}}}

```

40.1 \addtoreset and \numberwithin patches

\addtoreset puts a counter to the reset list of another counter. After a reset the counter starts again with perhaps already used values. Therefore the hyperref version of the counter print command \theHcounter is redefined in order to add the parent counter.

```

8122 \@ifundefined{hyper@nopatch@counter}
8123 {
8124   \let\HyOrg@addtoreset\@addtoreset
8125   \def\@addtoreset#1#2{%
8126     \HyOrg@addtoreset{#1}{#2}%
8127     \expandafter\xdef\csname theH#1\endcsname{%
8128       \expandafter\noexpand
8129         \csname the\@ifundefined{theH#2}{}H#2\endcsname
8130       .\noexpand\the\noexpand\value{#1}%
8131     }%
8132   }
8133 }{}

```

\numberwithin A appropriate definition of hyperref's companion counter (\theH...) is added for correct link names.

```

8134 </packageEnd>
8135 <*check>
8136 \checkpackage{amsmath}[1999/12/14 - 2000/06/06]
8137 \checkcommand\newcommand{\numberwithin}[3]{\arabic}{%
8138   \@ifundefined{c@#2}{\nocounterr{#2}}{%
8139     \@ifundefined{c@#3}{\nocnterr{#3}}{%
8140       \addtoreset{#2}{#3}%
8141       \exp\xdef\csname the#2\endcsname{%
8142         \exp\@nx\csname the#3\endcsname .\@nx#1{#2}}%
8143     }%
8144   }%
8145 }%

```

```

8146 }%
8147 </check>
8148 <*packageEnd>
8149 \@ifundefined{hyper@nopatch@counter}
8150 {
8151   \@ifpackageloaded{amsmath}{%
8152     \renewcommand*{\numberwithin}[3]{\arabic}{%
8153       \@ifundefined{c@\#2}{\nocounterr{\#2}}{%
8154         \@ifundefined{c@\#3}{\nocounterr{\#3}}{%
8155           \HyOrg@addtoreset{\#2}{\#3}%
8156           \xp\xdef\csname the\#2\endcsname{%
8157             \xp\@nx\csname the\#3\endcsname .\@nx\#1{\#2}%
8158           }%
8159           \xp\xdef\csname theH\#2\endcsname{%
8160             \xp\@nx
8161               \csname the\@ifundefined{theH\#3}{\H\#3}\endcsname
8162               .\@nx\#1{\#2}%
8163             }%
8164           }%
8165         }%
8166       }%
8167     }{}%
8168   }{}%

```

41 Included figures

Simply intercept the low level graphics package macro.

```

8169 \ifHy@hyperfigures
8170   \let\Hy@Gin@setfile\Gin@setfile
8171   \def\Gin@setfile#1#2#3{%
8172     \hyperimage{\#3}{\Hy@Gin@setfile{\#1}{\#2}{\#3}}%
8173   }%
8174 \fi
8175 \Hy@DisableOption{hyperfigures}

```

42 hyperindex entries

Internal command names are prefixed with `\HyInd@`.

Hyper-indexing works crudely, by forcing code onto the end of the index entry with the `|` feature; this puts a hyperlink around the printed page numbers. It will not proceed if the author has already used the `|` specifier for something like emboldening entries. That would make Makeindex fail (cannot have two `|` specifiers). The solution is for the author to use generic coding, and put in the requisite `\hyperpage` in his/her own macros along with the boldness.

This section is poor stuff; it's open to all sorts of abuse. Sensible large projects will design their own indexing macros any bypass this.

```

8176 \ifHy@hyperindex
8177   \def\HyInd@ParenLeft{()%
8178   \def\HyInd@ParenRight{}%
8179   \def\hyperindexformat#1#2{%
8180     \let\HyOrg@hyperpage\hyperpage

```

```

8181   \let\hyperpage\@firstofone
8182   #1{\HyOrg@hyperpage{#2}}%
8183   \let\hyperpage\HyOrg@hyperpage
8184 }%
8185 \Hy@nextfalse
8186 \@ifpackageloaded{multind}{\Hy@nexttrue}{}
8187 \@ifpackageloaded{index}{\Hy@nexttrue}{}
8188 \@ifpackageloaded{amsidx}{\Hy@nexttrue}{}
8189 \begingroup
8190   \lccode`|= \expandafter` \HyInd@EncapChar\relax
8191   \lccode`/|= `\\ \relax
8192 \lowercase{\endgroup
8193 \ifHy@next
8194   \let\HyInd@org@wrindex\@wrindex
8195   \def\@wrindex#1#2{\HyInd@wrindex{#1}{#2}||\|}%
8196   \def\HyInd@wrindex#1#2#3#4\\{%
8197     \ifx\\#3\\%
8198       \HyInd@org@wrindex{#1}{#2|hyperpage}%
8199     \else
8200       \HyInd@org@wrindex{#1}{#2}{#3}\\%
8201     \fi
8202   }%
8203   \def\HyInd@@@wrindex#1#2#3#4\\{%
8204     \def\Hy@temp@A{#3}%
8205     \ifcase0\ifx\Hy@temp@A\HyInd@ParenLeft 1\fi
8206       \ifx\Hy@temp@A\HyInd@ParenRight 1\fi
8207         \relax
8208       \HyInd@org@wrindex{#1}{%
8209         #2|hyperindexformat{/#3#4}}%
8210     }%
8211   \else
8212     \ifx\\#4\\%
8213       \ifx\Hy@temp@A\HyInd@ParenRight
8214         \HyInd@org@wrindex{#1}{#2}{#3}%
8215       \else
8216         \HyInd@org@wrindex{#1}{#2|#3hyperpage}%
8217       \fi
8218     \else
8219       \HyInd@org@wrindex{#1}{%
8220         #2|#3hyperindexformat{/#4}}%
8221     }%
8222   \fi
8223   \fi
8224 }%
8225 \else
8226   \def\@wrindex#1{\@@wrindex#1||\|}%
8227   \def\@@wrindex#1#2#3\\{%
8228     \if@filesw
8229       \ifx\\#2\\%
8230         \protected@write\@indexfile{}{%
8231           \string\indexentry{#1|hyperpage}{\thepage}%
8232         }%
8233       \else
8234         \HyInd@@@wrindex{#1}{#2}\\%

```

```

8235     \fi
8236     \fi
8237     \endgroup
8238     \esphack
8239 }
8240 \def\HyInd{\@wrindex#1#2#3\\f%
8241   \def\Hy@temp{#2}%
8242   \ifcase0\ifx\Hy@temp@A\HyInd@ParenLeft 1\fi
8243     \ifx\Hy@temp@A\HyInd@ParenRight 1\fi
8244     \relax
8245   \protected@write\@indexfile{}{%
8246     \string\indexentry{%
8247       #1|hyperindexformat{/#2#3}%
8248     }{\thepage}%
8249   }%
8250 \else
8251   \ifx\\#3\\%
8252     \ifx\Hy@temp@A\HyInd@ParenRight
8253       \HyInd@DefKey{#1}%
8254     \ltx@ifundefined{\HyInd@(\HyInd@key)}{%
8255       \let\Hy@temp\ltx@empty
8256     }{%
8257       \expandafter\let\expandafter\Hy@temp
8258         \csname HyInd@(\HyInd@key)\endcsname
8259     }%
8260   \protected@write\@indexfile{}{%
8261     \string\indexentry{#1|#2\Hy@temp}{\thepage}%
8262   }%
8263 \else
8264   \protected@write\@indexfile{}{%
8265     \string\indexentry{#1|#2hyperpage}{\thepage}%
8266   }%
8267   \HyInd@DefKey{#1}%
8268   \expandafter
8269   \gdef\csname HyInd@(\HyInd@key)\endcsname{%
8270     hyperpage}%
8271   }%
8272 \fi
8273 \else
8274   \protected@write\@indexfile{}{%
8275     \string\indexentry{%
8276       #1|#2hyperindexformat{/#3}%
8277     }{\thepage}%
8278   }%
8279   \ifx\Hy@temp@A\HyInd@ParenLeft
8280     \HyInd@DefKey{#1}%
8281     \expandafter
8282     \gdef\csname HyInd@(\HyInd@key)\endcsname{%
8283       hyperindexformat{/#3}%
8284     }%
8285     \fi
8286   \fi
8287 \fi
8288 }

```

```

8289 \def\HyInd@DefKey#1{%
8290   \begingroup
8291     \let\protect\@unexpandable@protect
8292     \edef\Hy@temp{\#1}%
8293     \ltx@onelvel@sanitize\Hy@temp
8294     \global\let\HyInd@key\Hy@temp
8295   \endgroup
8296 }%
8297 \fi
8298 }%
8299 \fi
8300 \Hy@DisableOption{hyperindex}
8301 \Hy@DisableOption{encap}

```

\nohyperpage The definition of \nohyperpage is just a precaution. It is used to mark code that does not belong to a page number, but \nohyperpage is never executed.

```
8302 \def\nohyperpage#1{#1}
```

This again is quite flaky, but allow for the common situation of a page range separated by en-rule. We split this into two different hyperlinked pages.

```

8303 \def\hyperpage#1{%
8304   \HyInd@hyperpage#1\nohyperpage{}@\nil
8305 }
8306 \def\HyInd@hyperpage#1\nohyperpage#2#3@\nil{%
8307   \HyInd@hyperpage{\#1}%
8308   \#2%
8309   \def\Hy@temp{\#3}%
8310   \ifx\Hy@temp\empty
8311   \else
8312     \ltx@ReturnAfterFi{%
8313       \HyInd@hyperpage#3@\nil
8314     }%
8315   \fi
8316 }
8317 \def\HyInd@@hyperpage#1{@hyperpage#1---\\}
8318 \def@hyperpage#1--#2--#3\\{%
8319   \ifx\\#2\\%
8320     \@commahyperpage{\#1}%
8321   \else
8322     \HyInd@pagelink{\#1}--\HyInd@pagelink{\#2}%
8323   \fi
8324 }
8325 \def@commahyperpage#1{@commahyperpage#1, ,\\}
8326 \def@commahyperpage#1, #2,#3\\{%
8327   \ifx\\#2\\%
8328     \HyInd@pagelink{\#1}%
8329   \else
8330     \HyInd@pagelink{\#1}, \HyInd@pagelink{\#2}%
8331   \fi
8332 }

```

The argument of \hyperpage can be empty. And the line breaking algorithm of Makeindex can introduce spaces. So we have to remove them.

```
8333 \def\HyInd@pagelink#1{%
```

```

8334 \begingroup
8335 \toks@={}%
8336 \HyInd@removespaces#1 \@nil
8337 \endgroup
8338 }
8339 \def\HyInd@removespaces#1 #2 \@nil{%
8340 \toks@=\expandafter{\the\toks@#1}%
8341 \ifx\#2\%
8342 \edef\x{\the\toks@}%
8343 \ifx\x\empty
8344 \else
8345 \hyperlink{page.\the\toks@}{\the\toks@}%
8346 \fi
8347 \else
8348 \ltx@ReturnAfterFi{%
8349 \HyInd@removespaces#2 \@nil
8350 }%
8351 \fi
8352 }

```

This breaks TeX4ht, so leave it to last. Emend \csetref to put out a hypertext link as well as its normal text (which is used as an anchor). (\endinput have to be on the same line like \fi, or you have to use \expandafter before.)

change 2022-11-13: added an \empty for issue#261.

```

8353 \ifHy@texht
8354 \expandafter\endinput
8355 \fi
8356 \let\real@csetref\csetref
8357 \def\csetref#1#2#3{%
8358 \csname extract group, refname
8359 \ifx#1\relax
8360 \protect\G@refundefinedtrue
8361 \nfss@text{\reset@font\bfseries ??}%
8362 \c@latex@warning{%
8363 Reference `#3' on page \thepage \space undefined%
8364 }%
8365 \expandafter\Hy@csetref@link#1\empty\empty\empty\@nil{#2}%
8366 \fi
8367 }

```

\Hy@csetref@link extracts the reference information entries, because \hyper@link does not expand arguments for the automatic link type detection.

```

8368 \def\Hy@csetref@link#1#2#3#4#5#6\@nil#7{%
8369 \begingroup
8370 \toks0={\hyper@link{#5}{#4}}%
8371 \toks1=\expandafter{\#7\#1\#2\#3\#4\#5}%
8372 \edef\x{\endgroup
8373 \the\toks0 {\the\toks1 }%
8374 }%
8375 \x
8376 }
8377 \def\pagesetref#1#2#3{%
8378 \csname extract macro, ref
8379 \ifx\#1\relax
8380 \protect\G@refundefinedtrue
8381 \nfss@text{\reset@font\bfseries ??}%

```

```

8381   \@latex@warning{%
8382     Reference `#3' on page \thepage\space undefined%
8383   }%
8384 \else
8385   \protect\hyper@link
8386   {\expandafter\@fifthoffive#1}%
8387   {page.\expandafter\@secondoffive#1}%
8388   {\expandafter\@secondoffive#1}%
8389 \fi
8390 }

8391 </packageEnd>
8392 <*check>
8393 \checklateX
8394 \checkcommand\def\@setref#1#2#3{%
8395   \ifx#1\relax
8396     \protect\G@refundefinedtrue
8397     \nfss@text{\reset@font\bfseries ??}%
8398     \@latex@warning{%
8399       Reference `#3' on page \thepage\space undefined%
8400     }%
8401   \else
8402     \expandafter#2#1\null
8403   \fi
8404 }
8405 </check>
8406 <*packageEnd>

```

Now some extended referencing. `\ref*` and `\pageref*` are not linked, and `\autoref` prefixes with a tag based on the type.

```

8407 \def\HyRef@StarSetRef#1{%
8408   \begingroup
8409   \Hy@safe@activestruE
8410   \let\protect\@unexpandable@protect
8411   \edef\x{\#1}%
8412   \onelevel@sanitize\x
8413   \edef\x{\endgroup
8414   \noexpand\HyRef@@StarSetRef
8415   \expandafter\noexpand\csname r@\x\endcsname{\x}%
8416 }%
8417 \x
8418 }
8419 \def\HyRef@@StarSetRef#1#2#3{%
8420   \ifx#1\@undefined
8421   \let#1\relax
8422   \fi
8423   \real@setref#1#3{#2}%
8424 }
8425 \def\@refstar#1{%
8426   \HyRef@StarSetRef{\#1}\@firstoffive
8427 }
8428 \def\@pagerefstar#1{%
8429   \HyRef@StarSetRef{\#1}\@secondoffive
8430 }
8431 \def\@namerefstar#1{%

```

```

8432 \HyRef@StarSetRef{\#1}\@thirdoffive
8433 }
8434 \def\@Refstar#1{%
8435 \HyRef@StarSetRef{\#1}\HyRef@MakeUppercaseFirstOfFive
8436 }%
8437 \def\HyRef@MakeUppercaseFirstOfFive#1#2#3#4#5{%
8438 \MakeUppercase#1%
8439 }%
8440 \def\HyRef@Ref#1{%
8441 \hyperref{\#1}{\Ref{\#1}}%
8442 }%
8443 \Hy@AtBeginDocument{%
8444 \@ifpackageloaded{variorref}{%

```

This are the patches for a variorref newer after 2019-09 Older versions are no longer supported. If \hyper@nopatch@variorref is defined we don't patch but assume that variorref handles the hyperlinks.

```

8445 \@ifundefined{hyper@nopatch@variorref}{%
8446 {
8447 \renewcommand\Vref@star[2][]{%
8448 \begingroup
8449 \let\T@pageref\@pagerefstar
8450 \Ref*{\#2}
8451 \vpageref{\#1}{\#2}%
8452 \endgroup
8453 }%
8454 \renewcommand\VR@f[2][]{%
8455 \begingroup
8456 \let\T@pageref\@pagerefstar
8457 \hyperref{\#2}{%
8458 \Ref*{\#2}
8459 \vpageref{\#1}{\#2}%
8460 }%
8461 \endgroup
8462 }%
8463 \renewcommand\VR@f[2][]{%
8464 \begingroup
8465 \let\T@pageref\@pagerefstar
8466 \hyperref{\#2}{%
8467 \ref*{\#2}
8468 \vpageref{\#1}{\#2}%
8469 }%
8470 \endgroup
8471 }%
8472 \renewcommand\vr@star[2][]{%
8473 \begingroup
8474 \let\T@pageref\@pagerefstar
8475 \ref*{\#2}
8476 \vpageref{\#1}{\#2}%
8477 \endgroup
8478 }%
8479 }{}%
8480 }{}%
8481 }

```

```

8482 \DeclareRobustCommand*\{\autoref\}{%
8483   \@ifstar{%
8484     \HyRef@\autorefname\pageref*%
8485   }\HyRef@\autoref
8486 }
8487 \def\HyRef@\autoref#1{%
8488   \hyperref[\#1]{\HyRef@\autorefname\pageref*\#1}}%
8489 }
8490 \def\HyRef@\autorefname{%
8491   \ltx@ifundefined{pageautorefname}{%
8492     \ltx@ifundefined{pagename}{%
8493       \Hy@Warning{No autoref name for `page'}}%
8494     }{%
8495       \pagename\nobreakspace
8496     }%
8497   }{%
8498     \pageautorefname\nobreakspace
8499   }%
8500 }

```

\leavevmode is added to make package wrapfigure happy, if \autoref starts a paragraph.

```

8501 \NewDocumentCommand\autoref{s}
8502   {\leavevmode
8503   \IfBooleanTF{#1}{\HyRef@\autoref\@gobbletwo}{\HyRef@\autoref\hyper@\@link}}
8504 \def\HyRef@\autoref#1#2{%
8505   \begingroup
8506     \Hy@safe@activestru e
8507     \expandafter\HyRef@\autosetref\csname r@#2\endcsname{#1}%
8508   \endgroup
8509 }
8510 \def\HyRef@\autosetref#1#2#3{%
8511   link command, csname, refname
8512   \HyRef@\ShowKeysRef{#2}%
8513   \ifcase 0\ifx#1\relax 1\fi\ifx#1\Hy@varioref@undefined 1\fi\relax
8514     \edef\HyRef@thisref{%
8515       \expandafter\@fourthoffive#1\empty\empty\empty
8516     }%
8517     \expandafter\HyRef@\testreftype\HyRef@thisref.\relax
8518     \Hy@safe@activesfalse
8519     #3{%
8520       \expandafter\@fifthoffive#1\empty\empty\empty
8521     }%
8522     \expandafter\@fourthoffive#1\empty\empty\empty
8523     \HyRef@currentHtag
8524     \expandafter\@firstoffive#1\empty\empty\empty
8525     \null
8526   }%
8527 \else
8528   \protect\G@refundefinedtrue
8529   \nfss@text{\reset@font\bfseries ??}%
8530   \clatex@warning{%
8531     Reference `#2' on page \thepage\space undefined}%
8532   }%

```

```

8533 \fi
8534 }
8535 \def\HyRef@testreftype#1.#2\\{%
8536 \ltx@ifundefined{\#1autorefname}{%
8537 \ltx@ifundefined{\#1name}{%
8538 \HyRef@StripStar#1\\*\\\@nil{\#1}%
8539 \ltx@ifundefined{\HyRef@name autorefname}{%
8540 \ltx@ifundefined{\HyRef@name name}{%
8541 \def\HyRef@currentHtag{}%
8542 \Hy@Warning{No autoref name for `#1'}%
8543 }{%
8544 \edef\HyRef@currentHtag{%
8545 \expandafter\noexpand\csname\HyRef@name name\endcsname
8546 \noexpand~%
8547 }%
8548 }%
8549 }{%
8550 \edef\HyRef@currentHtag{%
8551 \expandafter\noexpand
8552 \csname\HyRef@name autorefname\endcsname
8553 \noexpand~%
8554 }%
8555 }%
8556 }{%
8557 \edef\HyRef@currentHtag{%
8558 \expandafter\noexpand\csname#1name\endcsname
8559 \noexpand~%
8560 }%
8561 }%
8562 }{%
8563 \edef\HyRef@currentHtag{%
8564 \expandafter\noexpand\csname#1autorefname\endcsname
8565 \noexpand~%
8566 }%
8567 }%
8568 }
8569 \def\HyRef@StripStar#1\\#2\\@nil#3{%
8570 \def\HyRef@name{\#2}%
8571 \ifx\HyRef@name\HyRef@CaseStar
8572 \def\HyRef@name{\#1}%
8573 \else
8574 \def\HyRef@name{\#3}%
8575 \fi
8576 }
8577 \def\HyRef@CaseStar{*\\}
8578 \def\HyRef@currentHtag{}}

```

Support for package showkeys.

```
\HyRef@ShowKeysRef
8579 \let\HyRef@ShowKeysRef@gobble
8580 \def\HyRef@ShowKeysInit{%
8581 \ifcsname SK@@label\endcsname
8582 \ifx\SK@ref\@empty
8583 \else
```

```

8584     \def\HyRef@ShowKeysRef{%
8585         \SK@\SK@@ref
8586     }%
8587     \fi
8588 \fi
8589 }
8590 \AddToHook{package/showkeys/after}{\HyRef@ShowKeysInit}

```

Defaults for the names that `\autoref` uses.

```

8591 \providecommand*\AMSAutorefname{\equationautorefname}
8592 \providecommand*\Hfootnoteautorefname{\footnoteautorefname}
8593 \providecommand*\Itemautorefname{\itemautorefname}
8594 \providecommand*\itemautorefname{item}
8595 \providecommand*\equationautorefname{Equation}
8596 \providecommand*\footnoteautorefname{footnote}
8597 \providecommand*\itemautorefname{item}
8598 \providecommand*\figureautorefname{Figure}
8599 \providecommand*\tableautorefname{Table}
8600 \providecommand*\partautorefname{Part}
8601 \providecommand*\appendixautorefname{Appendix}
8602 \providecommand*\chapterautorefname{chapter}
8603 \providecommand*\sectionautorefname{section}
8604 \providecommand*\subsectionautorefname{subsection}
8605 \providecommand*\subsubsectionautorefname{subsubsection}
8606 \providecommand*\paragraphautorefname{paragraph}
8607 \providecommand*\ subparagraphautorefname{subparagraph}
8608 \providecommand*\FancyVerbLineautorefname{line}
8609 \providecommand*\theoremautorefname{Theorem}
8610 \providecommand*\pageautorefname{page}
8611 </packageEnd>

```

43 Configuration files

43.1 PS/PDF strings

Some drivers write PS or PDF strings. These strings are delimited by parentheses, therefore a lonely unmatched parenthesis must be avoided to avoid PS or PDF syntax errors. Also the backslash character itself has to be protected.

`\Hy@pstringdef` Therefore such strings should be passed through `\Hy@pstringdef`. The first argument holds a macro for the result, the second argument is the string that needs protecting. Since version 1.30.0 pdfTeX offers `\pdfescapestring`.

```

8612 <*pdftex | dvipdfm | xetex | vtex | pdfmarkbase | dviwindo>
8613 \begingroup\expandafter\expandafter\expandafter\endgroup
8614 \expandafter\ifx\csname pdf@escapestring\endcsname\relax
8615   \begingroup
8616     \catcode`\\=0 %
8617     \@makeother\\%
8618   |\@firstofone{|\endgroup
8619   |def|Hy@pstringdef#1#2{%
8620     |begingroup
8621       |edef~{|string~}%

```

```

8622     |xdef|Hy@gtemp{#2}%
8623     |endgroup
8624     |let#1|Hy@gtemp
8625     |@onellevel@sanitize#1%
8626     |edef#1{|expandafter|Hy@ExchangeBackslash#1\|@nil}%
8627     |edef#1{|expandafter|Hy@ExchangeLeftParenthesis#1(|@nil}%
8628     |edef#1{|expandafter|Hy@ExchangeRightParenthesis#1)|@nil}%
8629   }%
8630   |def|Hy@ExchangeBackslash#1\#2|@nil{%
8631     #1%
8632     |ifx|\#2|\%
8633     |else
8634       \\
8635       |ltx@ReturnAfterFi{%
8636         |Hy@ExchangeBackslash#2|@nil
8637       }%
8638     |fi
8639   }%
8640 }%
8641 \def\Hy@ExchangeLeftParenthesis#1(#2\@nil{%
8642   #1%
8643   \ifx\#2\\%
8644   \else
8645     \@backslashchar%
8646     \ltx@ReturnAfterFi{%
8647       \Hy@ExchangeLeftParenthesis#2\@nil
8648     }%
8649   \fi
8650 }%
8651 \def\Hy@ExchangeRightParenthesis#1)#2\@nil{%
8652   #1%
8653   \ifx\#2\\%
8654   \else
8655     \@backslashchar%
8656     \ltx@ReturnAfterFi{%
8657       \Hy@ExchangeRightParenthesis#2\@nil
8658     }%
8659   \fi
8660 }%
8661 \else
8662   \def\Hy@pstringdef#1#2{%
8663     \begingroup
8664     \edef~{\string~}%
8665     \xdef\Hy@gtemp{\pdf@escapestring{#2}}%
8666   \endgroup
8667   \let#1\Hy@gtemp
8668 }%
8669 \fi
8670 </pdftex | dvipdfm | xetex | vtex | pdfmarkbase | dviwindo>

```

43.2 pdftex

```

8671 <*pdftex>
8672 \providecommand*\XR@ext}{pdf}

```

```

8673 \Hy@setbreaklinks{true}
8674 \def\HyPat@ObjRef{%
8675   [0-9]*[1-9][0-9]* 0 R%
8676 }

This driver is for Han The Thanh's TeX variant which produces PDF directly.
This has new primitives to do PDF things, which usually translate almost directly
to PDF code, so there is a lot of flexibility which we do not at present harness.

Set PDF version if requested by option pdfversion.
• pdfTeX 1.10a, 2003-01-16: \pdfoptionpdfminorversion

• pdfTeX 1.30, 2005-08-081: \pdfminorversion

8677 \def\Hy@pdfminorversion{\pdfoptionpdfminorversion}%
8678 \def\Hy@pdfminorversion{\pdfminorversion}%
8679 \ifHy@ocgcolorlinks
8680   \ifnum\Hy@pdfmajorminor@version<105 %
8681     \kvsetkeys{Hyp}{pdfversion=1.5}%
8682   \fi
8683 \fi
8684 \ifHy@setpdfversion
8685   \ifnum\Hy@pdf@majorminor@version<105 %
8686     \ltx@ifundefined{pdfobjcompresslevel}{%
8687       }{%
8688         \ifHy@verbose
8689           \Hy@InfoNoLine{%
8690             PDF object streams are disabled, because they are%
8691             \MessageBreak
8692             not supported in requested PDF version %
8693             \Hy@pdf@majorversion.\Hy@pdf@minorversion
8694           }%
8695         \fi
8696         \pdfobjcompresslevel=\ltx@zero
8697       }%
8698     \fi
8699   \ifnum\Hy@pdfmajorminor@version=\Hy@pdf@majorminor@version\relax
8700   \else
8701     \let\Hy@temp\ltx@empty
8702     \def\Hy@temp@A#1#2{%
8703       \ifnum#1>\ltx@zero
8704         \edef\Hy@temp{%
8705           \Hy@temp
8706           \space\space
8707           \the#1\space #2%
8708         \ifnum#1=\ltx@one\else s\fi
8709           \MessageBreak
8710         }%
8711       \fi
8712     }%
8713   \Hy@temp@A\pdflastobj{PDF object}%
8714   \Hy@temp@A\pdflastxform{form XObject}%
8715   \Hy@temp@A\pdflastximage{image XObject}%
8716   \Hy@temp@A\pdflastannot{annotation}%
8717   \ltx@ifundefined{pdflastlink}{%
8718     }{%

```

```

8719     \Hy@temp@A\pdflastlink{link}%
8720   }%
8721   \ifx\Hy@temp\ltx@empty
8722     \Hy@pdfmajorversion=\Hy@pdf@majorversion\relax
8723     \Hy@pdfminorversion=\Hy@pdf@minorversion\relax
8724   \else
8725     \let\Hy@temp@A\ltx@empty
8726     \ifnum\Hy@pdf@majorminor@version=104 %
8727       \IfFileExists{pdf14.sty}{%
8728         \def\Hy@temp@A{%
8729           \MessageBreak
8730           Or \string\RequirePackage{pdf14} can be used%
8731           \MessageBreak
8732           before \string\documentclass\space as shortcut%
8733         }%
8734       }{%
8735     \fi
8736   \Hy@WarningNoLine{%
8737     The PDF version number could not be set,\MessageBreak
8738     because some PDF objects are already written:%
8739     \MessageBreak
8740     \Hy@temp
8741     The version should be set as early as possible:%
8742     \MessageBreak
8743     \space\space
8744     \expandafter\string\Hy@pdfmajorversion=\Hy@pdf@majorversion, %
8745     \expandafter\string\Hy@pdfminorversion=\Hy@pdf@minorversion
8746     \string\relax
8747     \ifnum\Hy@pdf@majorminor@version<105 %
8748       \ltx@ifundefined{pdfobjcompresslevel}{%
8749         }{%
8750           \MessageBreak
8751           \space\space
8752           \string\pdfobjcompresslevel=0\string\relax
8753         }%
8754       \fi
8755     \Hy@temp@A
8756   }%
8757   \fi
8758 \fi
8759 \PackageInfo{hyperref}{%
8760   \expandafter\string\Hy@pdfmajorversion.%
8761   \expandafter\string\Hy@pdfminorversion
8762   :=\number\Hy@pdf@majorversion.\number\Hy@pdf@minorversion\space
8763 }%
8764 \fi
8765 \edef\Hy@pdf@majorversion{\number\Hy@pdfmajorversion}%
8766 \edef\Hy@pdf@minorversion{\number\Hy@pdfminorversion}%
8767 \Hy@DisableOption{pdfversion}%
8768 \ifHy@ocgcolorlinks
8769   \pdf@ifdraftmode{}{%
8770     \immediate\pdfobj{%
8771       <<%
8772       /Type/OCG%

```

```

8773 /Name(View)%
8774 /Usage<<%
8775 /Print<<%
8776 /PrintState/OFF%
8777 >>%
8778 /View<<%
8779 /ViewState/ON%
8780 >>%
8781 >>%
8782 >>%
8783 }%
8784 \edef\OBJ@OCG@view{\the\pdflastobj\space 0 R}%
8785 \immediate\pdfobj{%
8786 <<%
8787 /Type/OCG%
8788 /Name(Print)%
8789 /Usage<<%
8790 /Print<<%
8791 /PrintState/ON%
8792 >>%
8793 /View<<%
8794 /ViewState/OFF%
8795 >>%
8796 >>%
8797 >>%
8798 }%
8799 \edef\OBJ@OCG@print{\the\pdflastobj\space 0 R}%
8800 \immediate\pdfobj{%
8801 [%%
8802 \OBJ@OCG@view\space\OBJ@OCG@print%
8803 ]%%
8804 }%
8805 \edef\OBJ@OCGs{\the\pdflastobj\space 0 R}%
8806 \pdfcatalog{%
8807 /OCProperties<<%
8808 /OCGs \OBJ@OCGs%
8809 /D<<%
8810 /OFF[\OBJ@OCG@print]%
8811 /AS[%%
8812 <<%
8813 /Event/View%
8814 /OCGs \OBJ@OCGs%
8815 /Category[/View]%
8816 >>%
8817 <<%
8818 /Event/Print%
8819 /OCGs \OBJ@OCGs%
8820 /Category[/Print]%
8821 >>%
8822 <<%
8823 /Event/Export%
8824 /OCGs \OBJ@OCGs%
8825 /Category[/Print]%
8826 >>%

```

```

8827      }%
8828      >>%
8829      >>%
8830      }%
8831      \begingroup
8832      \edef\x{\endgroup
8833      \pdfpageresources{%
8834      \the\pdfpageresources
8835      /Properties<<%
8836      /OCView \OBJ@OCG@view
8837      /OCPrint \OBJ@OCG@print
8838      >>%
8839      }%
8840      }%
8841      \x
8842      }%
8843      \Hy@AtBeginDocument{%
8844      \def\Hy@colorlink#1{%
8845      \begingroup
8846      \ifHy@ocgcolorlinks
8847      \def\Hy@ocgcolor{\#1}%
8848      \setbox0=\hbox\bgroup\color@begingroup
8849      \else
8850      \HyColor@UseColor#1%
8851      \fi
8852      }%
8853      \def\Hy@endcolorlink{%
8854      \ifHy@ocgcolorlinks
8855      \color@endgroup\egroup
8856      \mbox{%
8857      \pdfliteral page{/OC/OCPrint BDC}%
8858      \rlap{\copy0}%
8859      \pdfliteral page{EMC/OC/OCView BDC}%
8860      \begingroup
8861      \expandafter\HyColor@UseColor\Hy@ocgcolor
8862      \box0 %
8863      \endgroup
8864      \pdfliteral page{EMC}%
8865      }%
8866      \fi
8867      \endgroup
8868      }%
8869      }%
8870      \else
8871      \Hy@DisableOption{ocgcolorlinks}%
8872      \fi

```

First, allow for some changes and additions to pdftex syntax:

```

8873 \def\setpdflinkmargin#1{%
8874   \begingroup
8875   \setlength{\dimen@}{\#1}%
8876   \expandafter\endgroup
8877   \expandafter\pdflinkmargin\the\dimen@\relax
8878 }

```

```

8879 \pdflinkmargin{1pt} %

First set up the default linking
8880 \providecommand*{\@pdfview}{XYZ}

First define the anchors:
8881 \Hy@WrapperDef{\new@pdflink#1}{%
8882   \ifhmode
8883     \savesf\spacefactor
8884   \fi
8885   \Hy@SaveLastskip
8886   \Hy@VerboseAnchor{#1}%
8887   \Hy@PStringDef{\Hy@PStringDest}{\HyperDestNameFilter{#1}}%
8888   \Hy@DestName\Hy@PStringDest\@pdfview
8889   \Hy@RestoreLastskip
8890   \ifhmode
8891     \spacefactor\savesf
8892   \fi
8893 }
8894 \let\pdf@endanchor\empty

```

\Hy@DestName Wrap the call of \pdfdest name in \Hy@DestName. Then it can easier be catched by package hypdestopt.

```

8895 \def{\Hy@DestName#1#2}{%
8896   \pdfdest name{#1}{#2}\relax
8897 }

```

Now the links; the interesting part here is the set of attributes which define how the link looks. We probably want to add a border and color it, but there are other choices. This directly translates to PDF code, so consult the manual for how to change this. We will add an interface at some point.

```

8898 \providecommand*{\@pdfborder}{0 0 1}
8899 \providecommand*{\@pdfborderstyle}{}
8900 \def{\Hy@undefinedname}{UNDEFINED}
8901 \def{\find@pdflink#1#2}{%
8902   \leavevmodo
8903   \protected@edef{\Hy@testname}{#2}%
8904   \ifx{\Hy@testname}{\empty}
8905     \Hy@Warning{%
8906       Empty destination name,\MessageBreak
8907       using `{\Hy@undefinedname}'%
8908     }%
8909   \let{\Hy@testname}{\Hy@undefinedname}
8910   \else
8911     \Hy@PStringDef{\Hy@testname}{%
8912       \expandafter{\HyperDestNameFilter}\expandafter{\Hy@testname}}%
8913   }%
8914   \fi
8915   \Hy@StartlinkName{%
8916     \ifHy@pdflatex /F 4\fi
8917     \Hy@setpdfborder
8918     \Hy@setpdfhighlight
8919     \ifx{\CurrentBorderColor}{\relax}
8920     \else

```

```

8921     /C[\CurrentBorderColor]%
8922     \fi
8923 } \Hy@testname
8924 \expandafter\Hy@colorlink\csname @#1color\endcsname
8925 }
8926 \def\Hy@StartlinkName#1#2{%
8927   \pdfstartlink attr{#1}goto name{#2}\relax
8928 }
8929 \def\close@pdflink{%
8930   \Hy@endcolorlink
8931   \Hy@VerboseLinkStop
8932   \pdfendlink
8933 }
8934 \def\hyper@anchor#1{%
8935   \new@pdflink{#1}\anchor@spot\pdf@endanchor
8936 }
8937 \def\hyper@anchorstart#1{%
8938   \new@pdflink{#1}%
8939   \Hy@activeanchortrue
8940 }
8941 \def\hyper@anchorend{%
8942   \pdf@endanchor
8943   \Hy@activeanchorfalse
8944 }
8945 \def\hyper@linkstart#1#2{%
8946   \Hy@VerboseLinkStart{#1}{#2}%
8947   \ltx@ifundefined{@#1bordercolor}{%
8948     \let\CurrentBorderColor\relax
8949   }{%
8950     \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
8951   }%
8952   \find@pdflink{#1}{#2}%
8953 }
8954 \def\hyper@linkend{\close@pdflink}
8955 \def\hyper@link#1#2#3{%
8956   \Hy@VerboseLinkStart{#1}{#2}%
8957   \ltx@ifundefined{@#1bordercolor}{%
8958     \let\CurrentBorderColor\relax
8959   }{%
8960     \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
8961   }%
8962   \find@pdflink{#1}{#2}#3\Hy@xspace@end
8963   \close@pdflink
8964 }
8965 \let\CurrentBorderColor\@linkbordercolor
8966 \def\hyper@linkurl#1#2{%
8967   \begingroup
8968     \Hy@pstringdef\Hy@pstringURI{#2}%
8969     \hyper@chars
8970     \leavevmode
8971     \pdfstartlink
8972     attr{%
8973       \Hy@setpdfborder
8974       \Hy@setpdfhighlight

```

```

8975   \ifx\@urlbordercolor\relax
8976   \else
8977     /C[\@urlbordercolor]%
8978   \fi
8979 }%
8980 user{%
8981   /Subtype/Link%
8982   \ifHy@pdflatex /F 4\fi
8983 /A<<%
8984   /Type/Action%
8985   /S/URI%
8986   /URI(\Hy@pstringURI)%
8987   \ifHy@href@ismap
8988     /IsMap true%
8989   \fi
8990   \Hy@href@nextactionraw
8991 >>%
8992 }%
8993 \relax
8994 \Hy@colorlink\@urlcolor#1\Hy@xspace@end
8995 \close@pdflink
8996 \endgroup
8997 }
8998 \def\hyper@linkfile#1#2#3{%
8999   \begingroup
9000   \def\Hy@pstringF{\#2}%
9001   \Hy@CleanupFile\Hy@pstringF
9002   \Hy@pstringdef\Hy@pstringF\Hy@pstringF
9003   \Hy@pstringdef\Hy@pstringD{\#3}%
9004   \Hy@MakeRemoteAction
9005   \leavevmode
9006   \pdfstartlink
9007     attr{%
9008       \Hy@setpdfborder
9009       \Hy@setpdfhighlight
9010       \ifx\@filebordercolor\relax
9011       \else
9012         /C[\@filebordercolor]%
9013       \fi
9014     }%
9015   user {%
9016     /Subtype/Link%
9017     \ifHy@pdflatex /F 4\fi
9018     /A<<%
9019     /F(\Hy@pstringF)%
9020     /S/GoToR%
9021     \Hy@SetNewWindow

```

If #3 is empty, page 0; if its a number, Page number, otherwise a named destination.

```
\afterassignment\xxx\count@=0\foo!%
```

```
\def\xxx#1{%
\ifx\xxx#1\xxx
```

```

        foo was an integer
\else
    it wasnt
\fi}

9022      \ifx\\#3\\%
9023          /D[\Hy@href@page\@pdfremotestartview]%
9024      \else
9025          /D(\Hy@pstringD)%
9026      \fi
9027          \Hy@href@nextactionraw
9028      >>%
9029  }%
9030      \relax
9031  \Hy@colorlink\@filecolor#1\Hy@xspace@end
9032  \close@pdflink
9033 \endgroup
9034 }

9035 \def\@hyper@launch run:#1\\#2#3{%
9036   \begingroup
9037     \Hy@pstringdef\Hy@pstringF{#1}%
9038     \Hy@pstringdef\Hy@pstringP{#3}%
9039     \leavevmode
9040     \pdfstartlink
9041       attr{%
9042         \Hy@setpdfborder
9043         \Hy@setpdfhighlight
9044         \ifx\@runbordercolor\relax
9045         \else
9046           /C[\@runbordercolor]%
9047         \fi
9048     }%
9049     user {%
9050       /Subtype/Link%
9051       \ifHy@pdflatex /F 4\fi
9052       /A<<%
9053         /F(\Hy@pstringF)%
9054         /S/Launch%
9055         \Hy@SetNewWindow
9056         \ifx\\#3\\%
9057         \else
9058           /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
9059         \fi
9060         \Hy@href@nextactionraw
9061       >>%
9062     }%
9063     \relax
9064   \Hy@colorlink\@runcolor#2\Hy@xspace@end
9065   \close@pdflink
9066 \endgroup
9067 }

\PDF@SetupDox

```

```

9068 \def\PDF@SetupDoc{%
9069   \ifx\@pdfpagescrop\@empty
9070   \else
9071     \edef\process@me{%
9072       \pdfpagesattr={%
9073         /CropBox[\@pdfpagescrop]%
9074         \expandafter\ifx\expandafter\\\the\pdfpagesattr\\%
9075         \else
9076           ^~J\the\pdfpagesattr
9077         \fi
9078       }%
9079     }%
9080     \process@me
9081   \fi
9082 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
9083 \pdfcatalog{%
9084   /PageMode/\@pdffagemode
9085   \ifx\@baseurl\@empty
9086   \else
9087     /URI<</Base(\Hy@pstringB)>>%
9088   \fi
9089 }%
9090 \ifx\@pdfstartpage\@empty
9091 \else
9092   \ifx\@pdfstartview\@empty
9093   \else
9094     openaction goto page\@pdfstartpage{\@pdfstartview}%
9095   \fi
9096 \fi
9097 \edef\Hy@temp{%
9098   \ifHy@pdftoolbar\else /HideToolbar true\fi
9099   \ifHy@pdfmenubar\else /HideMenubar true\fi
9100   \ifHy@pdfwindowui\else /HideWindowUI true\fi
9101   \ifHy@pdffitwindow /FitWindow true\fi
9102   \ifHy@pdfcenterwindow /CenterWindow true\fi
9103   \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
9104   \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
9105   \Hy@UseNameKey{Direction}\@pdfdirection
9106   \Hy@UseNameKey{ViewArea}\@pdfviewarea
9107   \Hy@UseNameKey{ViewClip}\@pdfviewclip
9108   \Hy@UseNameKey{PrintArea}\@pdfprintarea
9109   \Hy@UseNameKey{PrintClip}\@pdfprintclip
9110   \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
9111   \Hy@UseNameKey{Duplex}\@pdfduplex
9112   \ifx\@pdfpicktraybypdfsize\@empty
9113   \else
9114     /PickTrayByPDFSize \@pdfpicktraybypdfsize
9115   \fi
9116   \ifx\@pdfprintpagerange\@empty
9117   \else
9118     /PrintPageRange[\@pdfprintpagerange]%
9119   \fi
9120   \ifx\@pdfnumcopies\@empty
9121   \else

```

```

9122     /NumCopies \@pdfnumcopies
9123     \fi
9124   }%
9125 \pdfcatalog{%
9126   \ifx\Hy@temp\@empty
9127   \else
9128     /ViewerPreferences<<\Hy@temp>>%
9129   \fi
9130 \Hy@UseNameKey{PageLayout}\@pdfpagelayout
9131 \ifx\@pdflang\relax
9132 \else
9133   /Lang(\@pdflang)%
9134 \fi
9135 }%
9136 }

\PDF@FinishDoc

9137 \def\PDF@FinishDoc{%
9138   \pdf@ifdraftmode{}{%
9139     \Hy@UseMaketitleInfos
9140     \HyInfo@GenerateAddons
9141     \pdfinfo{%
9142       /Author(\@pdffauthor)%
9143       /Title(\@pdftitle)%
9144       /Subject(\@pdfsubject)%
9145       /Creator(\@pdfcreator)%
9146       \ifx\@pdfcreationdate\@empty
9147       \else
9148         /CreationDate(\@pdfcreationdate)%
9149       \fi
9150       \ifx\@pdfmoddate\@empty
9151       \else
9152         /ModDate(\@pdfmoddate)%
9153       \fi
9154       \ifx\@pdfproducer\relax
9155       \else
9156         /Producer(\@pdfproducer)%
9157       \fi
9158       /Keywords(\@pdfkeywords)%
9159       \ifx\@pdftrapped\@empty
9160       \else
9161         /Trapped/\@pdftrapped
9162       \fi
9163       \HyInfo@Addons
9164     }%
9165   }%
9166   \Hy@DisableOption{pdffauthor}%
9167   \Hy@DisableOption{pdftitle}%
9168   \Hy@DisableOption{pdfsubject}%
9169   \Hy@DisableOption{pdfcreator}%
9170   \Hy@DisableOption{addtopdfcreator}%
9171   \Hy@DisableOption{pdfcreationdate}%
9172   \Hy@DisableOption{pdfmoddate}%
9173   \Hy@DisableOption{pdfproducer}%

```

```

9174 \Hy@DisableOption{pdfkeywords}%
9175 \Hy@DisableOption{pdftrapped}%
9176 \Hy@DisableOption{pdfinfo}%
9177 }

```

\hyper@pagetransition \@pdfpagetransition is initialized with \relax. So it indicates, if option pdfpage-transition is used. First previous /Trans entries are removed. If a new /Trans key exists, it is appended to \pdfpageattr.

```

9178 \def\hyper@pagetransition{%
9179   \ifx\@pdfpagetransition\relax
9180   \else
9181     \expandafter\Hy@RemoveTransPageAttr
9182     \the\pdfpageattr^J/Trans{}>>\END
9183     \ifx\@pdfpagetransition\empty
9184     \else
9185       \edef\@processme{%
9186         \global\pdfpageattr{%
9187           \the\pdfpageattr
9188           ^J/Trans << /S /@\pdfpagetransition\space >>%
9189         }%
9190       }%
9191       \@processme
9192     \fi
9193   \fi
9194 }

```

\Hy@RemoveTransPageAttr Macro \Hy@RemoveTransPageAttr removes a /Trans entry from \pdfpageattr. It is called with the end marker ^J/Trans{}>>\END. The trick is the empty group that does not appear in legal \pdfpageattr code. It appears in argument #2 and shows, whether the parameter text catches a really /Trans object or the end marker.

```

9195 \gdef\Hy@RemoveTransPageAttr#1^J/Trans#2#3>>#4\END{%
9196   \ifx\\#2\\%
9197     \global\pdfpageattr{#1}%
9198   \else
9199     \Hy@RemoveTransPageAttr#1#4\END
9200   \fi
9201 }

```

\hyper@pageduration \@pdfpageduration is initialized with \relax. So it indicates, if option pdfpageduration is used. First previous /Dur entries are removed. If a new /Dur key exists, it is appended to \pdfpageattr.

```

9202 \def\hyper@pageduration{%
9203   \ifx\@pdfpageduration\relax
9204   \else
9205     \expandafter
9206     \Hy@RemoveDurPageAttr\the\pdfpageattr^J/Dur{} \END
9207     \ifx\@pdfpageduration\empty
9208     \else
9209       \edef\@processme{%
9210         \global\pdfpageattr{%
9211           \the\pdfpageattr
9212           ^J/Dur \@pdfpageduration\space

```

```

9213      }%
9214      }%
9215      \c@processme
9216      \fi
9217      \fi
9218 }

\Hy@RemoveDurPageAttr Macro \Hy@RemoveDurPageAttr removes a /Dur entry from \pdfpageattr. It
is called with the end marker ^^J/Dur{} \END. The trick is the empty group
that does not appear in legal \pdfpageattr code. It appears in argument #2 and
shows, whether the parameter text catches a really /Dur object or the end marker.
9219 \gdef\Hy@RemoveDurPageAttr#1^^J/Dur#2#3 #4\END{%
9220   \ifx\#2\%
9221   \global\pdfpageattr{\#1}%
9222   \else
9223   \Hy@RemoveDurPageAttr#1#4\END
9224   \fi
9225 }

9226 \pdf@ifdraftmode{}{%
9227   \g@addto@macro\Hy@EveryPageHook{%
9228     \hyper@pagetransition
9229     \hyper@pageduration
9230   }%
9231 }

```

Also XeTeX support \pdfforwidth and \pdfforheight, but it does not provide \pdforigin and \pdfvorigin.

```

9232 </pdftex>
9233 <*pdftex | xetex>
9234 \Hy@AtBeginDocument{%
9235   \ifHy@setpagesize
9236     \expandafter\@firstofone
9237   \else
9238     \expandafter\@gobble
9239   \fi
9240   }%
9241   \@ifclassloaded{seminar}{%
9242 <*pdftex>
9243   \setlength{\pdforigin}{1truein}%
9244   \setlength{\pdfvorigin}{1truein}%
9245 </pdftex>
9246   \ifportrait
9247     \ifdim\paperwidth=\z@
9248     \else
9249       \setlength{\pdfforwidth}{\strip@pt\paperwidth truept}%
9250     \fi
9251     \ifdim\paperheight=\z@
9252     \else
9253       \setlength{\pdfforheight}{\strip@pt\paperheight truept}%
9254     \fi
9255   \else
9256     \ifdim\paperheight=\z@
9257     \else

```

```

9258     \setlength{\pdfpagewidth}{\strip@pt\paperheight truept}%
9259     \fi
9260     \ifdim\paperwidth=\z@
9261     \else
9262     \setlength{\pdfpageheight}{\strip@pt\paperwidth truept}%
9263     \fi
9264   \fi
9265 }%
9266 \ifnum\mag=\@m
9267   \ifdim\stockwidth>\z@
9268     \ifdim\stockheight>\z@
9269       \setlength{\pdfpagewidth}{\stockwidth}%
9270       \setlength{\pdfpageheight}{\stockheight}%
9271     \else
9272       \ifdim\paperwidth>\z@
9273         \ifdim\paperheight>\z@
9274           \setlength{\pdfpagewidth}{\paperwidth}%
9275           \setlength{\pdfpageheight}{\paperheight}%
9276         \fi
9277       \fi
9278     \fi
9279   \else
9280     \ifdim\stockwidth=\z@
9281       \ifdim\paperwidth>\z@
9282         \ifdim\paperheight>\z@
9283           \setlength{\pdfpagewidth}{\paperwidth}%
9284           \setlength{\pdfpageheight}{\paperheight}%
9285         \fi
9286       \fi
9287     \fi
9288   \fi
9289 \fi
9290 }%
9291 }%
9292 \Hy@DisableOption{setpagesize}%
9293 }
9294 </pdftex | xetex>
9295 <*pdftex>
9296 \def\Acrobatmenu#1#2{%
9297   \Hy@Acrobatmenu{#1}{#2}%
9298   \leavevmode
9299   \EdefEscapeName\Hy@temp@menu{#1}%
9300   \pdfstartlink
9301     attr{%
9302       \Hy@setpdfborder
9303       \Hy@setpdfhighlight
9304       \ifx\@menubordercolor\relax
9305       \else
9306         /C[\@menubordercolor]%
9307       \fi
9308     }%
9309   user{%
9310     /Subtype/Link%
9311     \ifHy@pdflatex /F 4\fi

```

```

9312     /A<<%
9313         /S/Named%
9314         /N/\Hy@temp@menu
9315         \Hy@href@nextactionraw
9316     >>%
9317     }%
9318     \relax
9319     \Hy@colorlink\@menucolor#2%
9320     \close@pdflink
9321 }%
9322 }

```

43.2.1 Fix for problem with different nesting levels

\AtBeginShipoutFirst adds an additional box layer around the first output page. This disturbs pdfTEX's low level link commands \pdfstartlink and \pdfendlink, if a link is broken across the first and second output page.

The problem could be fixed by replacing \AtBeginShipoutFirst, because the box layer is not necessary for pdfTEX— no \specials need to be inserted. However it's easier to add an additional box level for the pages after the first one. Also \AtBeginShipoutFirst could be invoked independently from hyperref.

Since version 2011/10/05 v1.16 of package ‘atbegshi’ \AtBeginShipoutFirst does not add a additional box layer.

change 2020-10-01: the code has been removed as outdated.

```
9323 </pdftex>
```

43.3 hypertex

The HyperTEX specification (this is borrowed from an article by Arthur Smith) says that conformant viewers/translators must recognize the following set of \special commands:

```

href: html:<a href = "href_string">
name: html:<a name = "name_string">
end: html:</a>
image: html:<img src = "href_string">
base_name: html:<base href = "href_string">

```

The *href*, *name* and *end* commands are used to do the basic hypertext operations of establishing links between sections of documents. The *image* command is intended (as with current html viewers) to place an image of arbitrary graphical format on the page in the current location. The *base_name* command is be used to communicate to the *dvi* viewer the full (URL) location of the current document so that files specified by relative URL's may be retrieved correctly.

The *href* and *name* commands must be paired with an *end* command later in the TEX file — the TEX commands between the two ends of a pair form an *anchor* in the document. In the case of an *href* command, the *anchor* is to be highlighted in the *dvi* viewer, and when clicked on will cause the scene to shift to the destination specified by *href_string*. The *anchor* associated with

a name command represents a possible location to which other hypertext links may refer, either as local references (of the form `href="#name_string"` with the `name_string` identical to the one in the name command) or as part of a URL (of the form `URL#name_string`). Here `href_string` is a valid URL or local identifier, while `name_string` could be any string at all: the only caveat is that ‘`”`’ characters should be escaped with a backslash (`\`), and if it looks like a URL name it may cause problems.

```

9324 <*hypertex>
9325 \providecommand*\XR@ext}{dvi}
9326 \let\PDF@FinishDoc\ltx@empty
9327 \def\PDF@SetupDoc{%
9328   \ifx\@baseurl\@empty
9329   \else
9330     \special{html:<base href="\@baseurl">}%
9331   \fi
9332 }
9333 \Hy@WrapperDef\hyper@anchor#1{%
9334   \Hy@SaveLastskip
9335   \Hy@VerboseAnchor{#1}%
9336   \begingroup
9337     \let\protect=\string
9338     \hyper@chars
9339     \special{html:<a name=%
9340       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
9341   \endgroup
9342   \Hy@activeanchortrue
9343   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
9344   \special{html:</a>}%
9345   \Hy@activeanchorfalse
9346   \Hy@RestoreLastskip
9347 }
9348 \Hy@WrapperDef\hyper@anchorstart#1{%
9349   \Hy@SaveLastskip
9350   \Hy@VerboseAnchor{#1}%
9351   \begingroup
9352     \hyper@chars
9353     \special{html:<a name=%
9354       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
9355   \endgroup
9356   \Hy@activeanchortrue
9357 }
9358 \def\hyper@anchorend{%
9359   \special{html:</a>}%
9360   \Hy@activeanchorfalse
9361   \Hy@RestoreLastskip
9362 }
9363 \def\@urlytype{url}
9364 \def\hyper@linkstart#1#2{%
9365   \Hy@VerboseLinkStart{#1}{#2}%
9366   \expandafter\Hy@colorlink\csname @#1color\endcsname
9367   \def\Hy@tempa{#1}%
9368   \ifx\Hy@tempa\@urlytype
9369     \special{html:<a href="\hyper@quote#2\hyper@quote">}%

```

```

9370 \else
9371 \begingroup
9372 \hyper@chars
9373 \special{html:<a href=%
9374 \hyper@quote\#\HyperDestNameFilter{\#2}\hyper@quote>}%
9375 \endgroup
9376 \fi
9377 }
9378 \def\hyper@linkend{%
9379 \special{html:</a>}%
9380 \Hy@endcolorlink
9381 }
9382 \def\hyper@linkfile#1#2#3{%
9383 \hyper@linkurl{\#1}{\Hy@linkfileprefix#2\ifx\\#3\\ \else\\#3\fi}%
9384 }
9385 \def\hyper@linkurl#1#2{%

```

If we want to raise up the final link `\special`, we need to get its height; ask me why L^AT_EX constructs make this totally foul up, and make us revert to basic T_EX. I do not know.

```

9386 \leavevmode
9387 \ifHy@raiselinks
9388 \Hy@SaveSpaceFactor
9389 \Hy@SaveSavedSpaceFactor
9390 \sbox{\tempboxa{\Hy@RestoreSpaceFactor#1}}%
9391 \Hy@RestoreSavedSpaceFactor
9392 \clinkdim\dp\tempboxa
9393 \lower\clinkdim\hbox{%
9394 \hyper@chars
9395 \special{html:<a href=\hyper@quote\#\hyper@quote>}%
9396 }%
9397 \Hy@colorlink\curlcolor
9398 \Hy@RestoreSpaceFactor
9399 #1%
9400 \Hy@SaveSpaceFactor
9401 \clinkdim\ht\tempboxa

```

Because of the interaction with the dvihps processor, we have to subtract a little from the height. This is not clean, or checked. Check with Mark Doyle about what gives here. It may not be needed with the new dvips (Jan 1997).

```

9402 \advance\clinkdim by -6.5\p@
9403 \raise\clinkdim\hbox{\special{html:</a>}%
9404 \Hy@endcolorlink
9405 \Hy@RestoreSpaceFactor
9406 \else
9407 \begingroup
9408 \hyper@chars
9409 \special{html:<a href=\hyper@quote\#\hyper@quote>}%
9410 \Hy@colorlink\curlcolor#1\Hy@xspace@end
9411 \special{html:</a>}%
9412 \Hy@endcolorlink
9413 \endgroup
9414 \fi
9415 }

```

Very poor implementation of \hyper@link without considering #1.

```
9416 \def\hyper@link#1#2#3{%
9417   \Hy@VerboseLinkStart{#1}{#2}%
9418   \hyper@linkurl{#3}{\#\HyperDestNameFilter{#2}}%
9419 }

9420 \def\hyper@image#1#2{%
9421   \begingroup
9422   \hyper@chars
9423   \special{html:<img src=\hyper@quote#1\hyper@quote>}%
9424   \endgroup
9425 }
9426 </hypertex>
9427 <*dviwindo>
```

43.4 dviwindo

[This was developed by David Carlisle]. Within a file dviwindo hyperlinking is used, for external URL's a call to \wwwbrowser is made. (You can define this command before or after loading the hyperref package if the default c:/netscape/netscape is not suitable) Dviwindo could in fact handle external links to dvi files on the same machine without calling a web browser, but that would mean parsing the URL to recognise such, and this is currently not done.

This was more or less blindly copied from the hypertex cfg. For dviwindo, LATEX must specify the size of the active area for links. For some hooks this information is available but for some, the start and end of the link are specified separately in which case a fixed size area of 1000000sp wide by \baselineskip high is used.

```
9428 \providetcommand*\XR@ext}{dvi}
9429 \providetcommand*\wwwbrowser{c:\string\netscape\string\netscape}
9430 \Hy@WrapperDef\hyper@anchor#1{%
9431   \Hy@SaveLastskip
9432   \Hy@VerboseAnchor{#1}%
9433   \begingroup
9434   \let\protect=\string
9435   \special{mark: #1}%
9436   \endgroup
9437   \Hy@activeanchortrue
9438   \Hy@colorlink@\anchorcolor\anchor@spot\Hy@endcolorlink
9439   \Hy@activeanchorfalse
9440   \Hy@RestoreLastskip
9441 }
9442 \Hy@WrapperDef\hyper@anchorstart#1{%
9443   \Hy@SaveLastskip
9444   \Hy@VerboseAnchor{#1}%
9445   \special{mark: #1}%
9446   \Hy@activeanchortrue
9447 }
9448 \def\hyper@anchorend{%
9449   \Hy@activeanchorfalse
9450   \Hy@RestoreLastskip
9451 }
9452 \def\hyper@linkstart#1#2{%
```

```

9453 \Hy@VerboseLinkStart{#1}{#2}%
9454 \expandafter\Hy@colorlink\csname @#1color\endcsname
9455 \special{button: %
9456 10000000 %
9457 \number\baselineskip\space
9458 #2%
9459 }%
9460 }
9461 \def\hyper@linkend{%
9462 \Hy@endcolorlink
9463 }
9464 \def\hyper@link#1#2#3{%
9465 \Hy@VerboseLinkStart{#1}{#2}%
9466 \leavevmode
9467 \ifHy@raiselinks
9468 \Hy@SaveSpaceFactor
9469 \Hy@SaveSavedSpaceFactor
9470 \sbox\@tempboxa{\Hy@RestoreSpaceFactor#3}%
9471 \Hy@RestoreSavedSpaceFactor
9472 \linkdim\dp\@tempboxa
9473 \lower\linkdim\hbox{%
9474 \special{button: %
9475 \number\wd\@tempboxa\space
9476 \number\ht\@tempboxa\space
9477 #2%
9478 }%
9479 \expandafter\Hy@colorlink\csname @#1color\endcsname
9480 \Hy@RestoreSpaceFactor
9481 #3\Hy@xspace@end
9482 \Hy@SaveSpaceFactor
9483 \Hy@endcolorlink
9484 }%
9485 \linkdim\ht\@tempboxa
9486 \advance\linkdim by -6.5\p@
9487 \raise\linkdim\hbox{}%
9488 \Hy@RestoreSpaceFactor
9489 \else
9490 \special{button: %
9491 \number\wd\@tempboxa\space
9492 \number\ht\@tempboxa\space
9493 #2%
9494 }%
9495 \expandafter\Hy@colorlink\csname @#1color\endcsname
9496 #3\Hy@xspace@end
9497 \Hy@endcolorlink
9498 \fi
9499 }
9500 \def\hyper@linkurl#1#2{%
9501 \begingroup
9502 \hyper@chars
9503 \leavevmode
9504 \ifHy@raiselinks
9505 \Hy@SaveSpaceFactor
9506 \Hy@SaveSavedSpaceFactor

```

```

9507   \sbox{@tempboxa{\Hy@RestoreSpaceFactor#1}%
9508   \Hy@RestoreSavedSpaceFactor
9509   \linkdim\dp\@tempboxa
9510   \lower\linkdim\hbox{%
9511     \special{button: %
9512       \number\wd\@tempboxa\space
9513       \number\ht\@tempboxa\space
9514       launch: \wwwbrowser\space
9515       #2%
9516     }%
9517     \Hy@colorlink\curlcolor
9518       \Hy@RestoreSpaceFactor
9519       #1\Hy@xspace@end
9520       \Hy@SaveSpaceFactor
9521       \Hy@endcolorlink
9522     }%
9523     \linkdim\ht\@tempboxa
9524     \advance\linkdim by -6.5\p@
9525     \raise\linkdim\hbox{%
9526       \Hy@RestoreSpaceFactor
9527     \else
9528       \special{button: %
9529         \number\wd\@tempboxa\space
9530         \number\ht\@tempboxa\space
9531         launch: \wwwbrowser\space
9532         #2%
9533       }%
9534       \Hy@colorlink\curlcolor
9535         #1\Hy@xspace@end
9536       \Hy@endcolorlink
9537     \fi
9538   \endgroup
9539 }
9540 \def\hyper@linkfile#1#2#3{%
9541   \begingroup
9542     \hyper@chars
9543     \leavevmode
9544     \ifHy@raiselinks
9545       \Hy@SaveSpaceFactor
9546       \Hy@SaveSavedSpaceFactor
9547       \sbox{@tempboxa{\Hy@RestoreSpaceFactor#1}%
9548       \Hy@RestoreSavedSpaceFactor
9549       \linkdim\dp\@tempboxa
9550       \lower\linkdim\hbox{%
9551         \special{button: %
9552           \number\wd\@tempboxa\space
9553           \number\ht\@tempboxa\space
9554           #3,%
9555           file: #2%
9556         }%
9557         \Hy@colorlink\filecolor
9558           \Hy@RestoreSpaceFactor
9559           #1\Hy@xspace@end
9560           \Hy@SaveSpaceFactor

```

```

9561     \Hy@endcolorlink
9562   }%
9563   \@linkdim\ht\@tempboxa
9564   \advance\@linkdim by -6.5\p@
9565   \raise\@linkdim\hbox{}%
9566   \Hy@RestoreSpaceFactor
9567 \else
9568   \special{button: %
9569     \number\wd\@tempboxa\space
9570     \number\ht\@tempboxa\space
9571     #3,%
9572     file: #2%
9573   }%
9574   \Hy@colorlink\@filecolor
9575   #1\Hy@xspace\end
9576   \Hy@endcolorlink
9577 \fi
9578 \endgroup
9579 }
9580 \HyInfo@AddonUnsupportedtrue
9581 \def\PDF@FinishDoc{%
9582   \Hy@UseMaketitleInfos
9583   \HyInfo@TrappedUnsupported
9584   \special{PDF: Keywords \@pdfkeywords}%
9585   \special{PDF: Title \@pdftitle}%
9586   \special{PDF: Creator \@pdfcreator}%
9587   \ifx\@pdfcreationdate\@empty
9588   \else
9589     \special{PDF: CreationDate \@pdfcreationdate}%
9590   \fi
9591   \ifx\@pdfmoddate\@empty
9592   \else
9593     \special{PDF: ModDate \@pdfmoddate}%
9594   \fi
9595   \special{PDF: Author \@pdfauthor}%
9596   \ifx\@pdfproducer\relax
9597   \else
9598     \special{PDF: Producer \@pdfproducer}%
9599   \fi
9600   \special{PDF: Subject \@pdfsubject}%
9601   \Hy@DisableOption{pdfauthor}%
9602   \Hy@DisableOption{pdftitle}%
9603   \Hy@DisableOption{pdfsubject}%
9604   \Hy@DisableOption{pdfcreator}%
9605   \Hy@DisableOption{addtopdfcreator}%
9606   \Hy@DisableOption{pdfcreationdate}%
9607   \Hy@DisableOption{pdfcreationdate}%
9608   \Hy@DisableOption{pdfmoddate}%
9609   \Hy@DisableOption{pdfproducer}%
9610   \Hy@DisableOption{pdfkeywords}%
9611   \Hy@DisableOption{pdftrapped}%
9612   \Hy@DisableOption{pdfinfo}%
9613 }
9614 \def\PDF@SetupDoc{%

```

```

9615 \ifx\@baseurl\@empty
9616 \else
9617 \special{PDF: Base \@baseurl}%
9618 \fi
9619 \ifx\@pdfpagescrop\@empty\else
9620 \special{PDF: BBox \@pdfpagescrop}%
9621 \fi
9622 \def\Hy@temp{}%
9623 \ifx\@pdfstartpage\@empty
9624 \else
9625 \ifx\@pdfstartview\@empty
9626 \else
9627 \edef\Hy@temp{%
9628 ,Page=\@pdfstartpage
9629 ,View=\@pdfstartview
9630 }%
9631 \fi
9632 \fi
9633 \edef\Hy@temp{%
9634 \noexpand\pdfmark{%
9635 pdfmark=/DOCVIEW,%
9636 PageMode=/\@pdfpagemode
9637 \Hy@temp
9638 }%
9639 }%
9640 \Hy@temp
9641 \ifx\@pdfpagescrop\@empty
9642 \else
9643 \pdfmark{pdfmark=/PAGES,CropBox=\@pdfpagescrop}%
9644 \fi
9645 \edef\Hy@temp{%
9646 \ifHy@pdftoolbar\else /HideToolbar true\fi
9647 \ifHy@pdfmenubar\else /HideMenubar true\fi
9648 \ifHy@pdfwindowui\else /HideWindowUI true\fi
9649 \ifHy@pdffitwindow /FitWindow true\fi
9650 \ifHy@pdfcenterwindow /CenterWindow true\fi
9651 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
9652 \Hy@UseNameKey{NonFullScreenMode}\@pdfnonfullscreenpagemode
9653 \Hy@UseNameKey{Direction}\@pdfdirection
9654 \Hy@UseNameKey{ViewArea}\@pdfviewarea
9655 \Hy@UseNameKey{ViewClip}\@pdfviewclip
9656 \Hy@UseNameKey{PrintArea}\@pdfprintarea
9657 \Hy@UseNameKey{PrintClip}\@pdfprintclip
9658 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
9659 \Hy@UseNameKey{Duplex}\@pdfduplex
9660 \ifx\@pdfpicktraybypdfsize\@empty
9661 \else
9662 /PickTrayByPDFSize \@pdfpicktraybypdfsize
9663 \fi
9664 \ifx\@pdfprintpagerange\@empty
9665 \else
9666 /PrintPageRange[\@pdfprintpagerange]%
9667 \fi
9668 \ifx\@pdfnumcopies\@empty

```

```

9669 \else
9670   /NumCopies \@pdfnumcopies
9671 \fi
9672 }%
9673 \pdfmark{pdfmark=/PUT,%
9674   Raw={%
9675     \string{Catalog\string}<<%
9676     \ifx\Hy@temp\@empty
9677     \else
9678       /ViewerPreferences<<\Hy@temp>>%
9679     \fi
9680   \Hy@UseNameKey{PageLayout}\@pdfpagelayout
9681   \ifx\@pdflang\relax
9682   \else
9683     /Lang(\@pdflang)%
9684   \fi
9685 >>%
9686 }%
9687 }%
9688 }
9689 </dviwindo>
9690 <*dvipdfm | xetex>

```

43.5 dvipdfm/xetex dvi to PDF converter

Provided by Mark Wicks (mwicks@kettering.edu)

(x)dvipdfmx replaces destination names by numbers. This makes it impossible to link from an external document with xr-hyper, so from version 7.00j on this is suppressed with a config special.

```

9691 \special{dvipdfmx:config C 0x0010}
9692 \providecommand*\XR@ext{\pdf}
9693 \Hy@setbreaklinks{true}
9694 \def\HyPat@ObjRef{%
9695   @[^ ]+%
9696 }
9697 \newsavebox{\pdfm@box}
9698 \def\@pdfm@mark#1{\special{pdf:#1}}
9699 \Hy@WrapperDef\@pdfm@dest#1{%
9700   \Hy@SaveLastskip
9701   \Hy@VerboseAnchor{#1}%
9702   \begingroup
9703   \Hy@Pstringdef\Hy@PstringDest{\HyperDestNameFilter{#1}}%
9704   \def\x{XYZ}%
9705   \ifx\x\@pdfview
9706     \def\x{XYZ @xpos @ypos null}%
9707   \else
9708     \def\x{FitH}%
9709     \ifx\x\@pdfview
9710       \def\x{FitH @ypos}%
9711     \else
9712       \def\x{FitBH}%
9713       \ifx\x\@pdfview
9714         \def\x{FitBH @ypos}%

```

```

9715 \else
9716   \def\x{FitV}%
9717   \ifx\x\@pdfview
9718     \def\x{FitV @xpos}%
9719   \else
9720     \def\x{FitBV}%
9721   \ifx\x\@pdfview
9722     \def\x{FitBV @xpos}%
9723   \else
9724     \def\x{Fit}%
9725   \ifx\x\@pdfview
9726     \let\x\@pdfview
9727   \else
9728     \def\x{FitB}%
9729   \ifx\x\@pdfview
9730     \let\x\@pdfview
9731   \else
9732     \def\x{FitR}%
9733   \ifx\x\@pdfview
9734     \Hy@Warning{\`pdfview=FitR' is not supported}%
9735     \def\x{XYZ @xpos @ypos null}%
9736   \else
9737     \onelevel@sanitize\@pdfview
9738   \Hy@Warning{%
9739     Unknown value `@\pdfview' for pdfview%
9740   }%
9741   \def\x{XYZ @xpos @ypos null}%
9742   \fi
9743   \fi
9744   \fi
9745   \fi
9746   \fi
9747   \fi
9748   \fi
9749   \fi
9750   \pdfmark{dest (\Hy@pstringDest) [@thispage /\x]}%
9751 \endgroup
9752 \Hy@RestoreLastskip
9753 }
9754 \providecommand*\@pdfview{XYZ}
9755 \providecommand*\@pdfborder{0 0 1}
9756 \providecommand*\@pdfborderstyle{}
9757 \def\hyper@anchor#1{%
9758   \pdfmark{dest{#1}}%
9759 }
9760 \def\hyper@anchorstart#1{%
9761   \Hy@activeanchortrue
9762   \pdfmark{dest{#1}}%
9763 }
9764 \def\hyper@anchorend{%
9765   \Hy@activeanchorfalse
9766 }
9767 \newcounter{Hy@AnnotLevel}

```

```

9768 \ifHy@ocgcolorlinks
9769 \def\OBJ@OCG@view{\OCG@view}%
9770 \@pdfm@mark{%
9771   obj \OBJ@OCG@view <<%
9772     /Type/OCG%
9773     /Name(View)%
9774     /Usage<<%
9775       /Print<<%
9776         /PrintState/OFF%
9777       >>%
9778     /View<<%
9779       /ViewState/ON%
9780     >>%
9781   >>%
9782   >>%
9783 }%
9784 \@pdfm@mark{close \OBJ@OCG@view}%
9785 \def\OBJ@OCG@print{\OCG@print}%
9786 \@pdfm@mark{%
9787   obj \OBJ@OCG@print <<%
9788     /Type/OCG%
9789     /Name(Print)%
9790     /Usage<<%
9791       /Print<<%
9792         /PrintState/ON%
9793       >>%
9794     /View<<%
9795       /ViewState/OFF%
9796     >>%
9797   >>%
9798   >>%
9799 }%
9800 \@pdfm@mark{close \OBJ@OCG@print}%
9801 \def\OBJ@OCGs{\OCGs}%
9802 \@pdfm@mark{%
9803   obj \OBJ@OCGs [%
9804     \OBJ@OCG@view\space\OBJ@OCG@print
9805   ]%
9806 }%
9807 \@pdfm@mark{close \OBJ@OCGs}%
9808 \@pdfm@mark{%
9809   put @catalog <<%
9810     /OCProperties<<%
9811       /OCGs \OBJ@OCGs
9812     /D<<%
9813       /OFF[\OBJ@OCG@print]%
9814     /AS[%
9815       <<%
9816         /Event/View%
9817         /OCGs \OBJ@OCGs
9818         /Category[/View]%
9819       >>%
9820       <<%
9821         /Event/Print%

```

```

9822      /OCGs \OBJ@OCGs
9823      /Category[/Print]%
9824      >>%
9825      <<%
9826      /Event/Export%
9827      /OCGs \OBJ@OCGs
9828      /Category[/Print]%
9829      >>%
9830      ]%
9831      >>%
9832      >>%
9833      >>%
9834  }%
9835 \AtBeginShipout{%
9836   \setbox\AtBeginShipoutBox=\hbox{%
9837     \copy\AtBeginShipoutBox
9838     \pdfmark{%
9839       put @resources <<%
9840       /Properties<<%
9841         /OCView \OBJ@OCG@view
9842         /OCPrint \OBJ@OCG@print
9843       >>%
9844     >>%
9845   }%
9846 }%
9847 }%
9848 \Hy@AtBeginDocument{%
9849   \def\Hy@colorlink#1{%
9850     \begingroup
9851       \ifHy@ocgcolorlinks
9852         \def\Hy@ocgcolor{\#1}%
9853         \setbox0=\hbox\bgroup\color@begingroup
9854       \else
9855         \HyColor@UseColor{\#1}%
9856       \fi
9857   }%
9858   \def\Hy@endcolorlink{%
9859     \ifHy@ocgcolorlinks
9860       \color@endgroup\egroup
9861       \mbox{%
9862         \pdfmark{content /OC/OCPrint BDC}%
9863         \rlap{\copy0}%
9864         \pdfmark{content EMC/OC/OCView BDC}%
9865       \begingroup
9866         \expandafter\HyColor@UseColor\Hy@ocgcolor
9867         \box0 %
9868       \endgroup
9869       \pdfmark{content EMC}%
9870     }%
9871   \fi
9872 }%
9873 }%
9874 }%
9875 \else

```

```

9876 \Hy@DisableOption{ocgcolorlinks}%
9877 \fi
Use primitive counter arithmetic here to avoid amsmath redefining \stepcounter
(github issue/13)
9878 \def\Hy@BeginAnnot#1{%
9879 \global\advance\c@Hy@AnnotLevel\@ne
9880 \ifnum\c@Hy@AnnotLevel=\@ne
9881 #1%
9882 \fi
9883 }
9884 \def\Hy@EndAnnot{%
9885 \ifnum\value{Hy@AnnotLevel}=\@ne
9886 \Hy@endcolorlink
9887 \c@pdfm@mark{eann}%
9888 \fi
9889 \global\advance\c@Hy@AnnotLevel\m@ne
9890 }

9891 \def\Hy@undefinedname{UNDEFINED}
9892 \def\hyper@linkstart#1#2{%
9893 \Hy@VerboseLinkStart{#1}{#2}%
9894 \leavevmode
9895 \Hy@BeginAnnot{%
9896 \protected@edef\Hy@testname{#2}%
9897 \ifx\Hy@testname\empty
9898 \Hy@Warning{%
9899 Empty destination name,\MessageBreak
9900 using `\'\Hy@undefinedname'%
9901 }%
9902 \let\Hy@testname\Hy@undefinedname
9903 \else
9904 \Hy@cpstringdef\Hy@testname{%
9905 \expandafter\HyperDestNameFilter\expandafter{%
9906 \Hy@testname
9907 }%
9908 }%
9909 \fi
9910 \c@pdfm@mark{%
9911 \bann<<%
9912 /Type/Annot%
9913 /Subtype/Link%
9914 \ifHy@pdflatex /F 4\fi
9915 \Hy@setpdfborder
9916 \Hy@setpdfhighlight
9917 \expandafter\ifx\csname @#1bordercolor\endcsname\relax
9918 \else
9919 /C[\csname @#1bordercolor\endcsname]%
9920 \fi
9921 /A<<%
9922 /S/GoTo%
9923 /D(\Hy@testname)%
9924 \Hy@href@nextactionraw
9925 >>%
9926 >>%

```

```

9927    }%
9928    \expandafter\Hy@colorlink\csname @#1color\endcsname
9929  }%
9930 }
9931 \def\hyper@linkend{\Hy@EndAnnot}%
9932 \def\hyper@link#1#2#3{%
9933   \hyper@linkstart{#1}{#2}{#3}\Hy@xspace@end\hyper@linkend
9934 }
9935 \def\hyper@linkfile#1#2#3{%
9936   \leavevemode
9937   \Hy@BeginAnnot{%
9938     \def\Hy@pstringF{#2}%
9939     \Hy@CleanupFile\Hy@pstringF
9940     \Hy@pstringdef\Hy@pstringF\Hy@pstringF
9941     \Hy@pstringdef\Hy@pstringD{#3}%
9942     \Hy@MakeRemoteAction
9943     \pdfmark{%
9944       bann<<%
9945       /Type/Annot%
9946       /Subtype/Link%
9947       \ifHy@pdflatex /F 4\fi
9948       \Hy@setpdfborder
9949       \Hy@setpdfhighlight
9950       \ifx\@filebordercolor\relax
9951       \else
9952         /C[\@filebordercolor]%
9953       \fi
9954       /A<<%
9955         /S/GoToR%
9956         /F(\Hy@pstringF)%
9957         /D%
9958         \ifx\@#3\%
9959           [\Hy@href@page\pdfremotestartview]%
9960         \else
9961           (\Hy@pstringD)%
9962         \fi
9963         \Hy@SetNewWindow
9964         \Hy@href@nextactionraw
9965         >>%
9966       >>%
9967     }%
9968     \Hy@colorlink\@filecolor
9969   }%
9970   #1\Hy@xspace@end
9971   \Hy@EndAnnot
9972 }
9973 \def\@hyper@launch run:#1\#2#3{%
9974   \leavevemode
9975   \Hy@BeginAnnot{%
9976     \Hy@pstringdef\Hy@pstringF{#1}%
9977     \Hy@pstringdef\Hy@pstringP{#3}%
9978     \pdfmark{%
9979       bann<<%
9980       /Type/Annot%

```

```

9981      /Subtype/Link%
9982      \ifHy@pdfa /F 4\fi
9983      \Hy@setpdfborder
9984      \Hy@setpdfhighlight
9985      \ifx\@runbordercolor\relax
9986      \else
9987          /C[\@runbordercolor]%
9988      \fi
9989      /A<<%
9990          /F(\Hy@pstringF)%
9991          /S/Launch%
9992          \Hy@SetNewWindow
9993          \ifx\\#3\\%
9994          \else
9995              /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
9996          \fi
9997          \Hy@href@nextactionraw
9998      >>%
9999      >>%
10000  }%
10001  \Hy@colorlink\@runcolor
10002 }%
10003 #2\Hy@xspace@end
10004 \Hy@EndAnnot
10005 }
10006 \def\hyper@linkurl#1#2{%
10007   \leavevemode
10008   \Hy@BeginAnnot{%
10009     \Hy@pstringdef\Hy@pstringURI{#2}%
10010     \@pdfm@mark{%
10011       bann<<%
10012       /Type/Annot%
10013       /Subtype/Link%
10014       \ifHy@pdfa /F 4\fi
10015       \Hy@setpdfborder
10016       \Hy@setpdfhighlight
10017       \ifx\@urlbordercolor\relax
10018       \else
10019           /C[\@urlbordercolor]%
10020       \fi
10021       /A<<%
10022           /S/URI%
10023           /URI(\Hy@pstringURI)%
10024           \ifHy@href@ismap
10025               /IsMap true%
10026           \fi
10027           \Hy@href@nextactionraw
10028       >>%
10029     >>%
10030   }%
10031   \Hy@colorlink\@urlcolor
10032 }%
10033 #1\Hy@xspace@end
10034 \Hy@EndAnnot

```

```

10035 }
10036 \def\Acrobatmenu#1#2{%
10037   \Hy@Acrobatmenu{#1}{#2}{%
10038     \Hy@BeginAnnot{%
10039       \EdefEscapeName\Hy@temp@menu{#1}{%
10040         \Cpdfm@mark{%
10041           bann<<%
10042             /Type/Annot%
10043             /Subtype/Link%
10044             \ifHy@pdfa /F 4\fi
10045             \Hy@setpdfborder
10046             \Hy@setpdffhighlight
10047             \ifx\@menubordercolor\relax
10048               \else
10049                 /C[\@menubordercolor]%
10050               \fi
10051             /A<<%
10052               /S/Named%
10053               /N/\Hy@temp@menu
10054               \Hy@href@nextactionraw
10055             >>%
10056             >>%
10057           }%
10058           \Hy@colorlink\@menucolor
10059         }%
10060       #2\Hy@xspace@end
10061       \Hy@EndAnnot
10062     }%
10063   }
10064
10065 \def\PDF@FinishDoc{%
10066   \Hy@UseMaketitleInfos
10067   \HyInfo@GenerateAddons
10068   \Cpdfm@mark{%
10069     docinfo<<%
10070       /Title(\@pdftitle)%
10071       /Subject(\@pdfsubject)%
10072       /Creator(\@pdfcreator)%
10073       \ifx\@pdfcreationdate\@empty
10074         \else
10075           /CreationDate(\@pdfcreationdate)%
10076         \fi
10077         \ifx\@pdfmoddate\@empty
10078           \else
10079             /ModDate(\@pdfmoddate)%
10080           \fi
10081           /Author(\@pdfauthor)%
10082           \ifx\@pdfproducer\relax
10083             \else
10084               /Producer(\@pdfproducer)%
10085             \fi
10086             /Keywords(\@pdfkeywords)%
10087             \ifx\@pdftrapped\@empty
10088               \else

```

```

10089      /Trapped/\@pdftrapped
10090      \fi
10091      \HyInfo@Addons
10092      >>%
10093  }%
10094  \Hy@DisableOption{pdfauthor}%
10095  \Hy@DisableOption{pdftitle}%
10096  \Hy@DisableOption{pdfsubject}%
10097  \Hy@DisableOption{pdfcreator}%
10098  \Hy@DisableOption{addtopdfcreator}%
10099  \Hy@DisableOption{pdfcreationdate}%
10100  \Hy@DisableOption{pdfcreationdate}%
10101  \Hy@DisableOption{pdfmoddate}%
10102  \Hy@DisableOption{pdfproducer}%
10103  \Hy@DisableOption{pdfkeywords}%
10104  \Hy@DisableOption{pdftrapped}%
10105  \Hy@DisableOption{pdfinfo}%
10106 }

10107 \def\PDF@SetupDoc{%
10108   \edef\Hy@temp{%
10109     \ifHy@pdftoolbar\else /HideToolbar true\fi
10110     \ifHy@pdfmenubar\else /HideMenubar true\fi
10111     \ifHy@pdfwindowui\else /HideWindowUI true\fi
10112     \ifHy@pdffitwindow /FitWindow true\fi
10113     \ifHy@pdfcenterwindow /CenterWindow true\fi
10114     \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
10115     \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
10116     \Hy@UseNameKey{Direction}\@pdfdirection
10117     \Hy@UseNameKey{ViewArea}\@pdfviewarea
10118     \Hy@UseNameKey{ViewClip}\@pdfviewclip
10119     \Hy@UseNameKey{PrintArea}\@pdfprintarea
10120     \Hy@UseNameKey{PrintClip}\@pdfprintclip
10121     \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
10122     \Hy@UseNameKey{Duplex}\@pdfduplex
10123     \ifx\@pdfpicktraybypdfsize\@empty
10124     \else
10125       /PickTrayByPDFSize \@pdfpicktraybypdfsize
10126     \fi
10127     \ifx\@pdfprintpagerange\@empty
10128     \else
10129       /PrintPageRange[\@pdfprintpagerange]%
10130     \fi
10131     \ifx\@pdfnumcopies\@empty
10132     \else
10133       /NumCopies \@pdfnumcopies
10134     \fi
10135  }%
10136  \Hy@pstringdef\Hy@pstringB{\@baseurl}%
10137  \@pdfm@mark{%
10138    docview<<%
10139    \ifx\@pdfstartpage\@empty
10140    \else
10141      \ifx\@pdfstartview\@empty
10142        \else

```

```

10143      /OpenAction[@page\@pdfstartpage\@pdfstartview]%
10144      \fi
10145      \fi
10146      \ifx\@baseurl\@empty
10147      \else
10148          /URI<</Base(\Hy@pstringB)>>%
10149      \fi
10150      /PageMode/\@pdfpagemode
10151      \ifx\Hy@temp\@empty
10152      \else
10153          /ViewerPreferences<<\Hy@temp>>%
10154      \fi
10155      \Hy@UseNameKey{PageLayout}\@pdfpagelayout
10156      \ifx\@pdflang\relax
10157      \else
10158          /Lang(\@pdflang)%
10159      \fi
10160      >>%
10161  }%
10162 \ifx\@pdfpagescrop\@empty
10163 \else
10164     \@pdfm@mark{put @pages <</CropBox[\@pdfpagescrop]>>}%
10165 \fi
10166 }
10167 </dvipdfm | xetex>
10168 <*dvipdfm | xetex>

\hyper@pagetransition
10169 \def\hyper@pagetransition{%
10170   \ifx\@pdfpagetransition\relax
10171   \else
10172     \ifx\@pdfpagetransition\@empty
10173     \else
10174       \special{pdf:put @thispage %
10175         <</Trans<</S/\@pdfpagetransition>>>}%
10176     }%
10177   \fi
10178 \fi
10179 }

\hyper@pageduration
10180 \def\hyper@pageduration{%
10181   \ifx\@pdfpageduration\relax
10182   \else
10183     \ifx\@pdfpageduration\@empty
10184     \else
10185       \special{pdf:put @thispage %
10186         <</Dur \@pdfpageduration>>}%
10187     }%
10188   \fi
10189 \fi
10190 }

10191 \g@addto@macro\Hy@EveryPageBoxHook{%

```

```

10192 \hyper@pagetransition
10193 \hyper@pageduration
10194 }
10195 </dvipdfm | xetex>

```

Xe^TE_X uses pdf^TE_X's method `\pdfpagewidth` and `\pdfpageheight` for setting the paper size.

```

10196 <*dvipdfm>
10197 \AtBeginShipoutFirst{%
10198   \ifHy@setpagesize
10199     \begingroup
10200       \ifnum\mag=\@m
10201         \ifdim\stockwidth>\z@
10202           \ifdim\stockheight>\z@
10203             \special{papersize=\the\stockwidth,\the\stockheight}%
10204           \else
10205             \ifdim\paperwidth>\z@
10206               \ifdim\paperheight>\z@
10207                 \special{papersize=\the\paperwidth,\the\paperheight}%
10208               \fi
10209             \fi
10210           \fi
10211         \else
10212           \ifdim\stockwidth=\z@
10213             \ifdim\paperwidth>\z@
10214               \ifdim\paperheight>\z@
10215                 \special{papersize=\the\paperwidth,\the\paperheight}%
10216               \fi
10217             \fi
10218           \fi
10219         \fi
10220       \fi
10221     \endgroup
10222   \fi
10223   \Hy@DisableOption{setpagesize}%
10224 }
10225 </dvipdfm>

```

43.6 V^Te_X typesetting system

Provided by MicroPress, May 1998. They require V^Te_X version 6.02 or newer; see <http://www.micropress-inc.com/> for details.

```

10226 <*vtexhtml>
10227 \providecommand*\XR@ext{.htm}
10228 \RequirePackage{vtexhtml}
10229 \newif\if@Localurl
10230 \let\PDF@FinishDoc\ltx@empty
10231 \def\PDF@SetupDoc{%
10232   \ifx\@baseurl\@empty
10233   \else
10234     \special{!direct <base href="\@baseurl">}%
10235   \fi
10236 }

```

```

10237 \def\@urltype{url}
10238 \def\hyper@link#1#2#3{%
10239   \Hy@VerboseLinkStart{#1}{#2}%
10240   \leavevmode
10241   \special{!direct <a href=%
10242     \hyper@quote\hyper@hash\HyperDestNameFilter{#2}\hyper@quote>}%
10243   #3\Hy@xspace@end
10244   \special{!direct </a>}%
10245 }
10246 \def\hyper@linkurl#1#2{%
10247   \begingroup
10248   \hyper@chars
10249   \leavevmode
10250   \MathBSuppress=1\relax
10251   \special{!direct <a href=%
10252     \hyper@quote\HyperDestNameFilter{#2}\hyper@quote>}%
10253   #1\Hy@xspace@end
10254   \MathBSuppress=0\relax
10255   \special{!direct </a>}%
10256   \endgroup
10257 }
10258 \def\hyper@linkfile#1#2#3{%
10259   \hyper@linkurl{#1}{\Hy@linkfileprefix#2\ifx\\#3\\else\\#3\fi}%
10260 }
10261 \def\hyper@linkstart#1#2{%
10262   \Hy@VerboseLinkStart{#1}{#2}%
10263   \def\Hy@tempa{#1}\ifx\Hy@tempa\@urltype
10264   \@Localurltrue
10265   \special{!direct <a href=\hyper@quote#2\hyper@quote>}%
10266   \else
10267   \@Localurlfalse
10268   \begingroup
10269   \hyper@chars
10270   \special{!aref \HyperDestNameFilter{#2}}%
10271   \endgroup
10272   \fi
10273 }
10274 \def\hyper@linkend{%
10275   \if@Localurl
10276   \special{!endaref}%
10277   \else
10278   \special{!direct </a>}%
10279   \fi
10280 }
10281 \Hy@WrapperDef\hyper@anchorstart#1{%
10282   \Hy@SaveLastskip
10283   \Hy@VerboseAnchor{#1}%
10284   \begingroup
10285   \hyper@chars
10286   \special{!aname #1}%
10287   \special{!direct <a name=%
10288     \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
10289   \endgroup
10290   \Hy@activeanchortrue

```

```

10291 }
10292 \def\hyper@anchorend{%
10293   \special{!direct </a>}%
10294   \Hy@activeanchorfalse
10295   \Hy@RestoreLastskip
10296 }
10297 \Hy@WrapperDef\hyper@anchor{\#1}{%
10298   \Hy@SaveLastskip
10299   \Hy@VerboseAnchor{\#1}%
10300   \begingroup
10301     \let\protect=\string
10302     \hyper@chars
10303     \leavevmode
10304     \special{!aname \#1}%
10305     \special{!direct <a name=%}
10306       \hyper@quote\HyperDestNameFilter{\#1}\hyper@quote}%
10307   \endgroup
10308   \Hy@activeanchortrue
10309   \bgroup\anchor@spot\egroup
10310   \special{!direct </a>}%
10311   \Hy@activeanchorfalse
10312   \Hy@RestoreLastskip
10313 }
10314 \def\@Form[\#1]{%
10315   \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10316 }
10317 \let\@endForm\ltx@empty
10318 \def\@Gauge[\#1]\#2\#3\#4{%
  parameters, label, minimum, maximum
10319   \Hy@Message{Sorry, TeXpider does not yet support FORM gauges}%
10320 }
10321 \def\@TextField[\#1]\#2{%
  parameters, label
10322   \Hy@Message{Sorry, TeXpider does not yet support FORM text fields}%
10323 }
10324 \def\@CheckBox[\#1]\#2{%
  parameters, label
10325   \Hy@Message{Sorry, TeXpider does not yet support FORM checkboxes}%
10326 }
10327 \def\@ChoiceMenu[\#1]\#2\#3{%
  parameters, label, choices
10328   \Hy@Message{Sorry, TeXpider does not yet support FORM choice menus}%
10329 }
10330 \def\@PushButton[\#1]\#2{%
  parameters, label
10331   \Hy@Message{Sorry, TeXpider does not yet support FORM pushbuttons}%
10332 }
10333 \def\@Reset[\#1]\#2{%
10334   \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10335 }
10336 \def\@Submit[\#1]\#2{%
10337   \Hy@Message{Sorry, TeXpider does not yet support FORMs}%
10338 }
10339 </vtexhtml>
10340 <*vtx>

```

VTeX version 6.68 supports `\mediawidth` and `\mediaheight`. The `\ifx` construct is better than a `\csname`, because it avoids the definition and the hash table entry of a previous undefined macro.

```

10341 \ifcsname mediaheight\endcsname
10342   \ifHy@setpagesize
10343     \providecommand*\VTeXInitMediaSize}{%
10344     \ifnum\mag=\@m
10345       \ifdim\stockwidth>\z@
10346         \ifdim\stockheight>\z@
10347           \setlength\mediaheight\stockheight
10348           \setlength\mediawidth\stockwidth
10349     \else
10350       \ifdim\paperwidth>\z@
10351         \ifdim\paperheight>\z@
10352           \setlength\mediaheight\paperheight
10353           \setlength\mediawidth\paperwidth
10354         \fi
10355       \fi
10356     \fi
10357   \else
10358     \ifdim\stockwidth=\z@
10359       \ifdim\paperwidth>\z@
10360         \ifdim\paperheight>\z@
10361           \setlength\mediaheight\paperheight
10362           \setlength\mediawidth\paperwidth
10363         \fi
10364       \fi
10365     \fi
10366   \fi
10367 \fi
10368 }%
10369 \Hy@AtBeginDocument{\VTeXInitMediaSize}%
10370 \fi
10371 \Hy@DisableOption{setpagesize}%
10372 \fi

```

Older versions of VTeX require xyz in lower case.

```

10373 \providecommand*\pdfview{xyz}
10374 \providecommand*\pdfborder{0 0 1}
10375 \providecommand*\pdfborderstyle{}
10376 \let\CurrentBorderColor\linkbordercolor
10377 \Hy@WrapperDef\hyper@anchor#1{%
10378   \Hy@SaveLastskip
10379   \Hy@VerboseAnchor{#1}%
10380   \begingroup
10381   \let\protect=\string
10382   \hyper@chars
10383   \special{!aname \HyperDestNameFilter{#1};\pdfview}%
10384 \endgroup
10385 \Hy@activeanchortrue
10386 \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
10387 \Hy@activeanchorfalse
10388 \Hy@RestoreLastskip
10389 }
10390 \Hy@WrapperDef\hyper@anchorstart#1{%
10391   \Hy@SaveLastskip
10392   \Hy@VerboseAnchor{#1}%
10393   \begingroup

```

```

10394   \hyper@chars
10395   \special{!aname \HyperDestNameFilter{\#1};\@pdfview}%
10396   \endgroup
10397   \Hy@activeanchortrue
10398 }
10399 \def\hyper@anchorend{%
10400   \Hy@activeanchorfalse
10401   \Hy@RestoreLastskip
10402 }
10403 \def\@urltype{url}
10404 \def\Hy@undefinedname{UNDEFINED}
10405 \def\hyper@linkstart{\#1\#2{%
10406   \Hy@VerboseLinkStart{\#1}{\#2}%
10407   \Hy@pstringdef\Hy@pstringURI{\#2}%
10408   \expandafter\Hy@colorlink\csname \#1color\endcsname
10409   \ltx@ifundefined{\#1bordercolor}{%
10410     \let\CurrentBorderColor\relax
10411   }{%
10412     \edef\CurrentBorderColor{%
10413       \csname \#1bordercolor\endcsname
10414     }%
10415   }%
10416   \def\Hy@tempa{\#1}%
10417   \ifx\Hy@tempa\@urltype
10418     \special{!%
10419       aref <u=/Type/Action/S/URI/URI(\Hy@pstringURI)%
10420       \ifHy@href@ismap
10421         /IsMap true%
10422       \fi
10423       \Hy@href@nextactionraw
10424     }%
10425     a=<%
10426     \ifHy@pdfa /F 4\fi
10427     \Hy@setpdfborder
10428     \ifx\CurrentBorderColor\relax
10429     \else
10430       /C [\CurrentBorderColor]%
10431     \fi
10432     >%
10433   }%
10434 \else
10435   \protected@edef\Hy@testname{\#2}%
10436   \ifx\Hy@testname\empty
10437     \Hy@Warning{%
10438       Empty destination name,\MessageBreak
10439       using `\'\Hy@undefinedname'%
10440     }%
10441     \let\Hy@testname\Hy@undefinedname
10442   \fi
10443   \special{!%
10444     aref \expandafter\HyperDestNameFilter
10445       \expandafter{\Hy@testname};%
10446     a=<%
10447     \ifHy@pdfa /F 4\fi

```

```

10448      \Hy@setpdfborder
10449      \ifx\CurrentBorderColor\relax
10450      \else
10451      /C [\CurrentBorderColor]%
10452      \fi
10453      >%
10454  }%
10455 \fi
10456 }
10457 \def\hyper@linkend{%
10458   \special{!endaref}%
10459   \Hy@endcolorlink
10460 }
10461 \def\hyper@linkfile#1#2#3{%
10462   \leavevmode
10463   \def\Hy@pstringF{\#2}%
10464   \Hy@CleanupFile\Hy@pstringF
10465   \special{!%
10466     aref <%
10467     \ifnum\Hy@VTeXversion>753 \ifHy@pdfnewwindow n\fi\fi
10468     f=\Hy@pstringF>\#3;%
10469     a=<%
10470     \ifHy@pdfa /F 4\fi
10471     \Hy@setpdfborder
10472     \ifx\@filebordercolor\relax
10473     \else
10474     /C [\@filebordercolor]%
10475     \fi
10476   >%
10477 }%
10478 \Hy@colorlink\@filecolor
10479   #1\Hy@xspace@end
10480 \Hy@endcolorlink
10481 \special{!endaref}%
10482 }
10483 \def\hyper@linkurl#1#2{%
10484   \begingroup
10485   \Hy@pstringdef\Hy@pstringURI{\#2}%
10486   \hyper@chars
10487   \leavevmode
10488   \special{!%
10489     aref <u=/Type/Action/S/URI/URI(\Hy@pstringURI)%
10490     \ifHy@href@ismap
10491       /IsMap true%
10492     \fi
10493     \Hy@href@nextactionraw
10494   >,%
10495   a=<%
10496   \ifHy@pdfa /F 4\fi
10497   \Hy@setpdfborder
10498   \ifx\@urlbordercolor\relax
10499   \else
10500   /C [\@urlbordercolor]%
10501   \fi

```

```

10502      >%
10503    }%
10504    \Hy@colorlink\@urlcolor
10505    #1\Hy@xspace@end
10506    \Hy@endcolorlink
10507    \special{!endaref}%
10508    \endgroup
10509 }
10510 \def\hyper@link#1#2#3{%
10511   \Hy@VerboseLinkStart{#1}{#2}%
10512   \ltx@ifundefined{@#1bordercolor}{%
10513     \let\CurrentBorderColor\relax
10514   }{%
10515     \edef\CurrentBorderColor{\csname @#1bordercolor\endcsname}%
10516   }%
10517   \leavevmode
10518   \protected@edef\Hy@testname{#2}%
10519   \ifx\Hy@testname\empty
10520     \Hy@Warning{%
10521       Empty destination name,\MessageBreak
10522       using `\'\Hy@undefinedname'%
10523     }%
10524   \let\Hy@testname\Hy@undefinedname
10525   \fi
10526   \special{!%
10527     aref \expandafter\HyperDestNameFilter
10528     \expandafter{\Hy@testname};%
10529   a=<%
10530     \ifHy@pdfa /F 4\fi
10531     \Hy@setpdfborder
10532     \ifx\CurrentBorderColor\relax
10533     \else
10534       /C [\CurrentBorderColor]%
10535     \fi
10536   >%
10537 }%
10538   \expandafter
10539   \Hy@colorlink\csname @#1color\endcsname
10540   #3\Hy@xspace@end
10541   \Hy@endcolorlink
10542   \special{!endaref}%
10543 }
10544 \def\hyper@image#1#2{%
10545   \hyper@linkurl{#2}{#1}%
10546 }
10547 \def\@hyper@launch run:#1\\#2#3{%
10548   \Hy@pstringdef\Hy@pstringF{#1}%
10549   \Hy@pstringdef\Hy@pstringP{#3}%
10550   \leavevmode
10551   \special{!aref %
10552     <u=%
10553     /Type/Action%
10554     /S/Launch%
10555     /F(\Hy@pstringF)%

```

```

10556 \Hy@SetNewWindow
10557 \ifx\\#3\\%
10558 \else
10559 /Win<</F(\Hy@pstringF)/P(\Hy@pstringP)>>%
10560 \fi
10561 \Hy@Chref@nextactionraw
10562 >%
10563 a=<%
10564 \ifHy@pdfa /F 4\fi
10565 \Hy@setpdfborder
10566 \ifx\@runbordercolor\relax
10567 \else
10568 /C[\@runbordercolor]%
10569 \fi
10570 >%
10571 }%
10572 \Hy@colorlink\@runcolor
10573 #2\Hy@xspace@end
10574 \Hy@endcolorlink
10575 \special{!endaref}%
10576 }
10577 \def\Acrobatmenu#1#2{%
10578 \EedefEscapeName\Hy@temp@menu{\#1}%
10579 \Hy@Acrobatmenu{\#1}{\#2}%
10580 \special{!%
10581 \aref <u=/S /Named /N /\Hy@temp@menu>;%
10582 a=<%
10583 \ifHy@pdfa /F 4\fi
10584 \Hy@setpdfborder
10585 \ifx\@menubordercolor\relax
10586 \else
10587 /C[\@menubordercolor]%
10588 \fi
10589 >%
10590 }%
10591 \Hy@colorlink\@menucolor
10592 #2\Hy@xspace@end
10593 \Hy@endcolorlink
10594 \special{!endaref}%
10595 }%
10596 }

```

The following code (transition effects) is made by Alex Kostin.

The code below makes sense for VTeX 7.02 or later.

Please never use `\@ifundefined{VTeXversion}{..}{..}` *globally*.

```

10597 \ifnum\Hy@VTeXversion<702 %
10598 \else
10599 \def\hyper@pagetransition{%
10600 \ifx\@pdfpagetransition\relax
10601 \else
10602 \ifx\@pdfpagetransition\@empty

```

Standard incantation.

1. Does an old entry have to be deleted? 2. If 1=yes, how to delete?

```

10603 \else

```

```

10604     \hvtex@parse@trans\@pdfpagetransition
10605     \fi
10606     \fi
10607 }%

```

I have to write an “honest” parser to convert raw PDF code into VTeX \special. (AVK)

Syntax of VTeX \special{!trans <transition_effect>}:

```

<transition_effect> ::= <transition_style>[,<transition_duration>]
<transition_style> ::= <Blinds_effect> | <Box_effect> |
    <Dissolve_effect> | <Glitter_effect> |
    <Split_effect> | <Wipe_effect>
<Blinds_effect> ::= B[<effect_dimension>]
<Box_effect> ::= X[<effect_motion>]
<Dissolve_effect> ::= D
<Glitter_effect> ::= G[<effect_direction>]
<Split_effect> ::= S[<effect_motion>][<effect_dimension>]
<Wipe_effect> ::= W[<effect_direction>]
<Replace_effect> ::= R
<effect_direction> ::= <number>
<effect_dimension> ::= H | V
<effect_motion> ::= I | O
<transition_duration> ::= <number>

```

Transition codes:

```

10608 \def\hvtex@trans@effect@Blinds{\def\hvtex@trans@code{B}}%
10609 \def\hvtex@trans@effect@Box{\def\hvtex@trans@code{X}}%
10610 \def\hvtex@trans@effect@Dissolve{\def\hvtex@trans@code{D}}%
10611 \def\hvtex@trans@effect@Glitter{\def\hvtex@trans@code{G}}%
10612 \def\hvtex@trans@effect@Split{\def\hvtex@trans@code{S}}%
10613 \def\hvtex@trans@effect@Wipe{\def\hvtex@trans@code{W}}%
10614 \def\hvtex@trans@effect@R{\def\hvtex@trans@code{R}}%

```

Optional parameters:

```

10615 \def\hvtex@par@dimension{/Dm}%
10616 \def\hvtex@par@direction{/Di}%
10617 \def\hvtex@par@duration{/D}%
10618 \def\hvtex@par@motion{/M}%

```

Tokenizer:

```

10619 \def\hvtex@gettoken{%
10620   \expandafter\hvtex@gettoken@\hvtex@buffer\@nil
10621 }%

```

Notice that tokens in the input buffer must be space delimited.

```

10622 \def\hvtex@gettoken@#1 #2\@nil{%
10623   \edef\hvtex@token{#1}%
10624   \edef\hvtex@buffer{#2}%
10625 }%
10626 \def\hvtex@parse@trans#1{%

```

Initializing code:

```

10627 \let\hvtex@trans@code\empty
10628 \let\hvtex@param@dimension\empty
10629 \let\hvtex@param@direction\empty

```

```
10630 \let\hvtex@param@duration\@empty
10631 \let\hvtex@param@motion\@empty
10632 \edef\hvtex@buffer{\#1\space}%
```

First token is the PDF transition name without escape.

```
10633 \hvtex@gettoken
10634 \ifx\hvtex@token\@empty
```

Leading space(s)?

```
10635 \ifx\hvtex@buffer\@empty
```

The buffer is empty, nothing to do.

```
10636 \else
10637 \hvtex@gettoken
10638 \fi
10639 \fi
10640 \csname hvtex@trans@effect@\hvtex@token\endcsname
```

Now is time to parse optional parameters.

```
10641 \hvtex@trans@params
10642 }%
```

Reentrant macro to parse optional parameters.

```
10643 \def\hvtex@trans@params{%
10644 \ifx\hvtex@buffer\@empty
10645 \else
10646 \hvtex@gettoken
10647 \let\hvtex@trans@par\hvtex@token
10648 \ifx\hvtex@buffer\@empty
10649 \else
10650 \hvtex@gettoken
10651 \ifx\hvtex@trans@par\hvtex@par@duration
```

/D is the effect duration in seconds. VTeX special takes it in milliseconds.

```
10652 \let\hvtex@param@duration\hvtex@token
10653 \else \ifx\hvtex@trans@par\hvtex@par@motion
```

/M can be either /I or /O

```
10654 \expandafter\edef\expandafter\hvtex@param@motion
10655 \expandafter{\expandafter\@gobble\hvtex@token}%
10656 \else \ifx\hvtex@trans@par\hvtex@par@dimension
```

/Dm can be either /H or /V

```
10657 \expandafter\edef\expandafter\hvtex@param@dimension
10658 \expandafter{\expandafter\@gobble\hvtex@token}%
10659 \else \ifx\hvtex@trans@par\hvtex@par@direction
```

Valid values for /Di are 0, 270, 315 (the Glitter effect) or 0, 90, 180, 270 (the Wipe effect).

```
10660 \let\hvtex@param@direction\hvtex@token
10661 \fi\fi\fi\fi
10662 \fi
10663 \fi
10664 \ifx\hvtex@buffer\@empty
10665 \let\next\hvtex@produce@trans
10666 \else
10667 \let\next\hvtex@trans@params
10668 \fi
```

```

10669   \next
10670 }%
Merge <transition_effect> and issue the special when possible. Too lazy to
validate optional parameters.
10671 \def\hvtex@produce@trans{%
10672   \let\vtx@trans@special\empty
10673   \if S\hvtex@trans@code
10674     \edef\vtx@trans@special{\hvtex@trans@code
10675       \hvtex@param@dimension\hvtex@param@motion}%
10676   \else\if B\hvtex@trans@code
10677     \edef\vtx@trans@special{%
10678       \hvtex@trans@code\hvtex@param@dimension
10679     }%
10680   \else\if X\hvtex@trans@code
10681     \edef\vtx@trans@special{%
10682       \hvtex@trans@code\hvtex@param@motion
10683     }%
10684   \else\if W\hvtex@trans@code
10685     \edef\vtx@trans@special{%
10686       \hvtex@trans@code\hvtex@param@direction
10687     }%
10688   \else\if D\hvtex@trans@code
10689     \let\vtx@trans@special\hvtex@trans@code
10690   \else\if R\hvtex@trans@code
10691     \let\vtx@trans@special\hvtex@trans@code
10692   \else\if G\hvtex@trans@code
10693     \edef\vtx@trans@special{%
10694       \hvtex@trans@code\hvtex@param@direction
10695     }%
10696   \fi\fi\fi\fi\fi
10697 \ifx\vtx@trans@special\empty
10698 \else
10699   \ifx\hvtex@param@duration\empty
10700   \else
10701     \setlength{\dimen@}{\hvtex@param@duration\p@}%

```

I'm not guilty of possible overflow.

```

10702   \multiply\dimen@\@m
10703   \edef\vtx@trans@special{%
10704     \vtx@trans@special,\strip@pt\dimen@
10705   }%
10706 \fi

```

And all the mess is just for this.

```

10707   \special{!trans \vtx@trans@special}%
10708 \fi
10709 }%
10710 \def\hyper@pageduration{%
10711   \ifx\@pdfpageduration\relax
10712   \else
10713     \ifx\@pdfpageduration\empty
10714     \special{!duration-}%
10715   \else
10716     \special{!duration \@pdfpageduration}%

```

```

10717   \fi
10718   \fi
10719 }%
10720 \g@addto@macro\Hy@EveryPageBoxHook{%
10721   \hyper@pagetransition
10722   \hyper@pageduration
10723 }%
10724 \fi

```

Caution: In opposite to the other drivers, the argument of `\special{!onopen #1}` is a reference name. The VTeX's postscript mode will work with a version higher than 7.0x.

The command `\VTeXOS` is defined since version 7.45. Magic values encode the operating system:

- 1: WinTel
- 2: Linux
- 3: OS/2
- 4: Mac OS
- 5: Mac OS/X

```

10725 \ifx\@pdfproducer\relax
10726 \def\@pdfproducer{\VTeX}%
10727 \ifnum\Hy@VTeXversion>\z@
10728   \count@\VTeXversion
10729   \divide\count@ 100 %
10730   \edef\@pdfproducer{\@pdfproducer\space v\the\count@}%
10731   \multiply\count@ -100 %
10732   \advance\count@\VTeXversion
10733 \edef\@pdfproducer{%
10734   \@pdfproducer
10735   .\ifnum\count@<10 0\fi\the\count@
10736   \ifx\VTeXOS\undefined\else
10737     \ifnum\VTeXOS>0 %
10738       \ifnum\VTeXOS<6 %
10739         \space(%
10740         \ifcase\VTeXOS
10741           \or Windows\or Linux\or OS/2\or Mac OS\or Mac OS/X%
10742           \fi
10743         )%
10744       \fi
10745     \fi
10746   \fi
10747   ,\space
10748   \ifnum\OpMode=\@ne PDF\else PS\fi
10749   \space backend%
10750   \ifx\gexmode\undefined\else
10751     \ifnum\gexmode>\z@\space with GeX\fi
10752   \fi
10753 }%
10754 \fi
10755 \fi

```

Current `!pdffinfo` key syntax:

Key	Field	Type
a	Author	String
b	CropBox	String
c	Creator	String
k	Keywords	String
l	PageLayout	PS
p	PageMode	PS
r	Producer	String
s	Subject	String
t	Title	String
u	URI	PS
v	ViewPreferences	PS

Note: PS objects that are dicts are in <<<...>>> (yuck; no choice).

```

10756 \def\PDF@SetupDoc{%
10757   \ifx\@pdfpagescrop\@empty
10758   \else
10759     \special{!pdfinfo b=<\@pdfpagescrop>}%
10760   \fi
10761   \ifx\@pdfstartpage\@empty
10762   \else
10763     \ifx\@pdfstartview\@empty
10764     \else
10765       \special{!onopen Page\@pdfstartpage}%
10766     \fi
10767   \fi
10768   \special{!pdfinfo p=</\@pdfpagemode>}%
10769   \ifx\@baseurl\@empty
10770   \else
10771     \special{!pdfinfo u=<<</Base (\@baseurl)>>>}%
10772   \fi
10773   \special{!pdfinfo v=<<<%
10774     \ifHy@pdftoolbar\else /HideToolbar true\fi
10775     \ifHy@pdfmenubar\else /HideMenubar true\fi
10776     \ifHy@pdfwindowui\else /HideWindowUI true\fi
10777     \ifHy@pdffitwindow /FitWindow true\fi
10778     \ifHy@pdfcenterwindow /CenterWindow true\fi
10779     \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
10780     \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
10781     \Hy@UseNameKey{Direction}\@pdfdirection
10782     \Hy@UseNameKey{ViewArea}\@pdfviewarea
10783     \Hy@UseNameKey{ViewClip}\@pdfviewclip
10784     \Hy@UseNameKey{PrintArea}\@pdfprintarea
10785     \Hy@UseNameKey{PrintClip}\@pdfprintclip
10786     \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
10787     \Hy@UseNameKey{Duplex}\@pdfduplex
10788     \ifx\@pdfpicktraybypdfsize\@empty
10789     \else
10790       /PickTrayByPDFSize \@pdfpicktraybypdfsize
10791     \fi
10792     \ifx\@pdfprintpagerange\@empty
10793     \else
10794       /PrintPageRange[\@pdfprintpagerange]%
10795   \fi

```

```

10796   \ifx\@pdfnumcopies\@empty
10797   \else
10798     /NumCopies \@pdfnumcopies
10799   \fi
10800 >>> }%
10801 \ifx\@pdfpagelayout\@empty
10802 \else
10803   \special{!pdfinfo l=</\@pdfpagelayout\space>}%
10804   \fi
10805 }%
10806 \HyInfo@AddonUnsupportedtrue
10807 \define@key{Hyp}{pdfcreationdate}{%
10808   \Hy@Warning{%
10809     VTeX does not support pdfcreationdate.\MessageBreak
10810     Therefore its setting is ignored%
10811   }%
10812 }
10813 \define@key{Hyp}{pdfmoddate}{%
10814   \Hy@Warning{%
10815     VTeX does not support pdfmoddate.\MessageBreak
10816     Therefore its setting is ignored%
10817   }%
10818 }
10819 \def\PDF@FinishDoc{%
10820   \Hy@UseMaketitleInfos
10821   \HyInfo@TrappedUnsupported
10822   \special{!pdfinfo a=<\@pdfauthor>}%
10823   \special{!pdfinfo t=<\@pdftitle>}%
10824   \special{!pdfinfo s=<\@pdfsubject>}%
10825   \special{!pdfinfo c=<\@pdfcreator>}%
10826   \ifx\@pdfproducer\relax
10827   \else
10828     \special{!pdfinfo r=<\@pdfproducer>}%
10829   \fi
10830   \special{!pdfinfo k=<\@pdfkeywords>}%
10831   \Hy@DisableOption{pdfauthor}%
10832   \Hy@DisableOption{pdftitle}%
10833   \Hy@DisableOption{pdfsubject}%
10834   \Hy@DisableOption{pdfcreator}%
10835   \Hy@DisableOption{addtopdfcreator}%
10836   \Hy@DisableOption{pdfcreationdate}%
10837   \Hy@DisableOption{pdfcreationdate}%
10838   \Hy@DisableOption{pdfmoddate}%
10839   \Hy@DisableOption{pdfproducer}%
10840   \Hy@DisableOption{pdfkeywords}%
10841   \Hy@DisableOption{pdftrapped}%
10842   \Hy@DisableOption{pdfinfo}%
10843 }
10844 </vtex>

```

43.7 Fix for Adobe bug number 466320

If a destination occurs at the very begin of a page, the destination is moved to the previous page by Adobe Distiller 5. As workaround Adobe suggests:

```
/showpage {
    //showpage
    clippath stroke erasemode
} bind def
```

But unfortunately this fix generates an empty page at the end of the document. Therefore another fix is used by writing some clipped text.

```
10845 <dviwindo>\def\literalps@out{\special{ps:#1}}%
10846 <packageEnd>\providecommand*\Hy@DistillerDestFix{}%
10847 {*pdfmark | dviwindo}
10848 \def\Hy@DistillerDestFix{%
10849   \begingroup
10850     \let\x\literalps@out
```

The fix has to be passed unchanged through GeX, if VTeX in PostScript mode with GeX is used.

```
10851 \ifnum \@ifundefined{OpMode}{0}{%
10852   \@ifundefined{gexmode}{0}{%
10853     \ifnum\gexmode>0 \OpMode\else 0\fi
10854   }>1 %
10855   \def\x##1{%
10856     \immediate\special{!=##1}%
10857   }%
10858 \fi
10859 \x{%
10860   /product where{%
10861     pop %
10862     product(Distiller)search{%
10863       pop pop pop %
10864       version(.)search{%
10865         exch pop exch pop%
10866         (3011)eq{%
10867           gsave %
10868           newpath 0 0 moveto closepath clip%
10869           /Courier findfont 10 scalefont setfont %
10870           72 72 moveto(.)show %
10871           grestore%
10872         }if%
10873         }{pop}ifelse%
10874         }{pop}ifelse%
10875       }if%
10876     }%
10877   \endgroup
10878 }
10879 </pdfmark | dviwindo>
```

43.8 Direct pdfmark support

Drivers that load `pdfmark.def` have to provide the correct macro definitions of

```

\@pdfproducer for document information
\literalps@out PostScript output
\headerps@out PostScript output that goes in the header area

```

and the correct definitions of the following PostScript procedures:

H.S	start of anchor, link or rect
#1 H.A	end of anchor, argument=baselineskip in pt
#1 H.L	end of link, argument=baselineskip in pt
H.R	end of rect
H.B	raw rect code

```

10880 <*pdfmark>
10881 \Hy@breaklinks@unsupported
10882 \def\HyPat@ObjRef{%
10883   \{{[^{}]+}\}%
10884 }
10885 \Hy@WrapperDef\hyper@anchor#1{%
10886   \Hy@SaveLastskip
10887   \Hy@VerboseAnchor{#1}%
10888   \begingroup
10889     \pdfmark[\anchor@spot]{%
10890       pdfmark=/DEST,%
10891       linktype=anchor,%
10892       View=/@\pdfview \@pdfviewparams,%
10893       DestAnchor={#1}%
10894     }%
10895   \endgroup
10896   \Hy@RestoreLastskip
10897 }
10898 \ltx@ifundefined{hyper@anchorstart}{}{\endinput}
10899 \Hy@WrapperDef\hyper@anchorstart#1{%
10900   \Hy@SaveLastskip
10901   \Hy@VerboseAnchor{#1}%
10902   \literalps@out{H.S}%
10903   \Hy@AllowHyphens
10904   \xdef\hyper@currentanchor{#1}%
10905   \Hy@activeanchortrue
10906 }
10907 \def\hyper@anchorend{%
10908   \literalps@out{\strip@pt@and@otherjunk\baselineskip\space H.A}%
10909   \pdfmark{%
10910     pdfmark=/DEST,%
10911     linktype=anchor,%
10912     View=/@\pdfview \@pdfviewparams,%
10913     DestAnchor=\hyper@currentanchor,%
10914   }%
10915   \Hy@activeanchorfalse
10916   \Hy@RestoreLastskip
10917 }
10918 \def\hyper@linkstart#1#2{%
10919   \Hy@VerboseLinkStart{#1}{#2}%
10920   \ifHy@breaklinks
10921   \else
10922     \leavevmode

```

```

10923 \ifmmode
10924   \def\Hy@LinkMath{$}%
10925 \else
10926   \let\Hy@LinkMath\ltx@empty
10927 \fi
10928 \Hy@SaveSpaceFactor
10929 \hbox\bgroup
10930 \Hy@RestoreSpaceFactor
10931 \Hy@LinkMath
10932 \fi
10933 \expandafter\Hy@colorlink\csname @#1color\endcsname
10934 \literalps@out{H.S}%
10935 \Hy@AllowHyphens
10936 \xdef\hyper@currentanchor{#2}%
10937 \gdef\hyper@currentlinktype{#1}%
10938 }
10939 \def\hyper@linkend{%
10940 \literalps@out{\strip@pt@and@otherjunk\baselineskip\space H.L}%
10941 \ltx@IfUndefined{@\hyper@currentlinktype bordercolor}{%
10942 \let\Hy@tempcolor\relax
10943 }{%
10944 \edef\Hy@tempcolor{%
10945 \csname @\hyper@currentlinktype bordercolor\endcsname
10946 }%
10947 }%
10948 \pdfmark{%
10949 pdfmark=/ANN,%
10950 linktype=link,%
10951 Subtype=/Link,%
10952 PDFAFlags=4,%
10953 Dest=\hyper@currentanchor,%
10954 AcroHighlight=\@pdfhighlight,%
10955 Border=\@pdfborder,%
10956 BorderStyle=\@pdfborderstyle,%
10957 Color=\Hy@tempcolor,%
10958 Raw=H.B%
10959 }%
10960 \Hy@endcolorlink
10961 \ifHy@breaklinks
10962 \else
10963 \Hy@LinkMath
10964 \Hy@SaveSpaceFactor
10965 \egroup
10966 \Hy@RestoreSpaceFactor
10967 \fi
10968 }

```

We have to allow for `\baselineskip` having an optional stretch and shrink (you meet this in slide packages, for instance), so we need to strip off the junk. David Carlisle, of course, wrote this bit of code.

```

10969 \begingroup
10970 \catcode`P=12 %
10971 \catcode`T=12 %
10972 \lowercase{\endgroup}

```

```

10973 \gdef\rem@ptetc#1.#2PT#3{#1\ifnum#2>\z@\#2\fi}%
10974 }
10975 \def\strip@pt@and@otherjunk#1{\expandafter\rem@ptetc\the#1!}

\hyper@pagetransition
10976 \def\hyper@pagetransition{%
10977 \ifx\@pdfpagetransition\relax
10978 \else
10979 \ifx\@pdfpagetransition\empty
10980 % 1. Does an old entry have to be deleted?
10981 % 2. If 1=yes, how to delete?
10982 \else
10983 \pdfmark{%
10984 pdfmark=/PUT,%
10985 Raw={%
10986 \string{ThisPage\string}%
10987 <</Trans << /S /\@pdfpagetransition\space >>>%
10988 }%
10989 }%
10990 \fi
10991 \fi
10992 }

\hyper@pageduration
10993 \def\hyper@pageduration{%
10994 \ifx\@pdfpageduration\relax
10995 \else
10996 \ifx\@pdfpageduration\empty
10997 % 1. Does an old entry have to be deleted?
10998 % 2. If 1=yes, how to delete?
10999 \else
11000 \pdfmark{%
11001 pdfmark=/PUT,%
11002 Raw={%
11003 \string{ThisPage\string}%
11004 <</Dur \@pdfpageduration>>%
11005 }%
11006 }%
11007 \fi
11008 \fi
11009 }

11010 \g@addto@macro\Hy@EveryPageBoxHook{%
11011 \hyper@pagetransition
11012 \hyper@pageduration
11013 }

11014 \def\hyper@image#1#2{%
11015 \hyper@linkurl{#2}{#1}%
11016 }
11017 \def\Hy@undefinedname{UNDEFINED}
11018 \def\hyper@link#1#2#3{%
11019 \Hy@VerboseLinkStart{#1}{#2}%
11020 \ltx@ifundefined{@#1bordercolor}{%
11021 \let\Hy@tempcolor\relax

```

```

11022  }{%
11023   \edef\Hy@tempcolor{\csname @#1bordercolor\endcsname}%
11024  }%
11025  \begingroup
11026   \protected@edef\Hy@testname{\#2}%
11027   \ifx\Hy@testname\empty
11028     \Hy@Warning{%
11029       Empty destination name,\MessageBreak
11030       using `\'\Hy@undefinedname'%
11031     }%
11032     \let\Hy@testname\Hy@undefinedname
11033   \fi
11034   \pdfmark[{\#3}]{%
11035     Color=\Hy@tempcolor,%
11036     linktype={\#1},%
11037     AcroHighlight=\@pdfhighlight,%
11038     Border=\@pdfborder,%
11039     BorderStyle=\@pdfborderstyle,%
11040     pdfmark=/ANN,%
11041     Subtype=/Link,%
11042     PDFAFlags=4,%
11043     Dest=\Hy@testname
11044   }%
11045   \endgroup
11046 }
11047 \newtoks\pdf@docset
11048 \def\PDF@FinishDoc{%
11049   \Hy@UseMaketitleInfos
11050   \Hy@Info@GenerateAddons
11051   \let\Hy@temp\empty
11052   \ifx\@pdfcreationdate\empty
11053     \else
11054       \def\Hy@temp{CreationDate=\@pdfcreationdate,}%
11055     \fi
11056   \ifx\@pdfmoddate\empty
11057     \else
11058       \expandafter\def\expandafter\Hy@temp\expandafter{%
11059         \Hy@temp
11060         ModDate=\@pdfmoddate,%
11061       }%
11062     \fi
11063   \ifx\@pdfproducer\relax
11064     \else
11065       \expandafter\def\expandafter\Hy@temp\expandafter{%
11066         \Hy@temp
11067         Producer=\@pdfproducer,%
11068       }%
11069     \fi
11070   \expandafter
11071   \pdfmark\expandafter{%
11072     \Hy@temp
11073     pdfmark=/DOCINFO,%
11074     Title=\@pdftitle,%
11075     Subject=\@pdfsubject,%

```

```

11076 Creator=\@pdfcreator,%
11077 Author=\@pdfauthor,%
11078 Keywords=\@pdfkeywords,%
11079 Trapped=\@pdftrapped
11080 }%
11081 \ifx\HyInfo@Addons\@empty
11082 \else
11083 \pdfmark{%
11084 pdfmark=/DOCINFO,%
11085 Raw={\HyInfo@Addons}%
11086 }%
11087 \fi
11088 \Hy@DisableOption{pdfauthor}%
11089 \Hy@DisableOption{pdftitle}%
11090 \Hy@DisableOption{pdfsubject}%
11091 \Hy@DisableOption{pdfcreator}%
11092 \Hy@DisableOption{addtopdfcreator}%
11093 \Hy@DisableOption{pdfcreationdate}%
11094 \Hy@DisableOption{pdfcreationdate}%
11095 \Hy@DisableOption{pdfmoddate}%
11096 \Hy@DisableOption{pdfproducer}%
11097 \Hy@DisableOption{pdfkeywords}%
11098 \Hy@DisableOption{pdftrapped}%
11099 \Hy@DisableOption{pdfinfo}%
11100 }
11101 \def\PDF@SetupDoc{%
11102 \def\Hy@temp{}%
11103 \ifx\@pdfstartpage\@empty
11104 \else
11105 \ifx\@pdfstartview\@empty
11106 \else
11107 \edef\Hy@temp{%
11108 ,Page=\@pdfstartpage
11109 ,View=\@pdfstartview
11110 }%
11111 \fi
11112 \fi
11113 \edef\Hy@temp{%
11114 \noexpand\pdfmark{%
11115 pdfmark=/DOCVIEW,%
11116 PageMode=/\@pdfpagemode
11117 \Hy@temp
11118 }%
11119 }%
11120 \Hy@temp
11121 \ifx\@pdfpagescrop\@empty
11122 \else
11123 \pdfmark{pdfmark=/PAGES,CropBox=\@pdfpagescrop}%
11124 \fi
11125 \edef\Hy@temp{%
11126 \ifHy@pdftoolbar\else /HideToolbar true\fi
11127 \ifHy@pdfmenubar\else /HideMenubar true\fi
11128 \ifHy@pdfwindowui\else /HideWindowUI true\fi
11129 \ifHy@pdffitwindow /FitWindow true\fi

```

```

11130 \ifHy@pdfcenterwindow /CenterWindow true\fi
11131 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
11132 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
11133 \Hy@UseNameKey{Direction}\@pdfdirection
11134 \Hy@UseNameKey{ViewArea}\@pdfviewarea
11135 \Hy@UseNameKey{ViewClip}\@pdfviewclip
11136 \Hy@UseNameKey{PrintArea}\@pdfprintarea
11137 \Hy@UseNameKey{PrintClip}\@pdfprintclip
11138 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
11139 \Hy@UseNameKey{Duplex}\@pdfduplex
11140 \ifx\@pdfpicktraybypdfsize\@empty
11141 \else
11142   /PickTrayByPDFSize \@pdfpicktraybypdfsize
11143 \fi
11144 \ifx\@pdfprintpagerange\@empty
11145 \else
11146   /PrintPageRange[\@pdfprintpagerange]%
11147 \fi
11148 \ifx\@pdfnumcopies\@empty
11149 \else
11150   /NumCopies \@pdfnumcopies
11151 \fi
11152 }%
11153 \Hy@PStringDef\Hy@PStringB{\@baseurl}%
11154 \pdfmark{%
11155   pdfmark=/PUT,%
11156   Raw={%
11157     \string{Catalog\string}<<%
11158     \ifx\Hy@temp\@empty
11159     \else
11160       /ViewerPreferences<<\Hy@temp>>%
11161     \fi
11162     \Hy@UseNameKey{PageLayout}\@pdfpagelayout
11163     \ifx\@pdflang\relax
11164     \else
11165       /Lang(\@pdflang)%
11166     \fi
11167     \ifx\@baseurl\@empty
11168     \else
11169       /URI<</Base(\Hy@PStringB)>>%
11170     \fi
11171   >>%
11172 }%
11173 }%
11174 }%
11175 </pdfmark>
11176 <*pdfmarkbase>

```

We define a single macro, pdfmark, which uses the ‘keyval’ system to define the various allowable keys; these are *exactly* as listed in the pdfmark reference for Acrobat 3.0. The only addition is pdfmark which specifies the type of pdfmark to create (like ANN, LINK etc). The surrounding round and square brackets in the pdfmark commands are supplied, but you have to put in / characters as needed for the values.

```

11177 \newif\ifHy@pdfmarkerror
11178 \def\pdfmark{\@ifnextchar[{\pdfmark@}{\pdfmark@[]}}
11179 \def\pdfmark@[#1]#2{%
11180   \Hy@pdfmarkerrorfalse
11181   \edef\@processme{\noexpand\pdf@toks={\the\pdf@defaulttoks}}%
11182   \@processme
11183   \let\pdf@type\relax
11184   \let\pdf@objdef\ltx@empty
11185   \kvsetkeys{PDF}{#2}%
11186   \ifHy@pdfmarkerror
11187   \else
11188     \ifx\pdf@type\relax
11189       \Hy@WarningNoLine{no pdfmark type specified in #2!!}%
11190       \ifx\\#1\\%
11191       \else
11192         \pdf@rect{#1}%
11193       \fi
11194     \else
11195       \ifx\\#1\\%
11196         \literalps@out{%
11197           [
11198           \ifx\pdf@objdef\ltx@empty
11199             \else
11200               /_objdef\string{\pdf@objdef\string}%
11201             \fi
11202             \the\pdf@toks\space\pdf@type\space pdfmark%
11203           }%
11204         \else
11205           \ltx@ifundefined{@\pdf@linktype color}{%
11206             \Hy@colorlink\@linkcolor
11207           }{%
11208             \expandafter\Hy@colorlink
11209               \csname @\pdf@linktype color\endcsname
11210           }%
11211           \pdf@rect{#1}%
11212           \literalps@out{%
11213             [
11214             \ifx\pdf@objdef\ltx@empty
11215               \else
11216                 /_objdef\string{\pdf@objdef\string}%
11217               \fi
11218               \the\pdf@toks\space\pdf@type\space pdfmark%
11219             }%
11220             \Hy@endcolorlink
11221           \fi
11222         \fi
11223       \fi
11224 }

```

The complicated bit is working out the right enclosing rectangle of some piece of \TeX text, needed by the /Rect key. This solution originates with Toby Thain (tobyt@netspace.net.au).

For the case breaklinks is enabled, I have added two hooks, the first one for package setouterhbox, it provides a hopefully better method without setting the

text twice.

```
\usepackage[hyperref]{setouterhbox}
```

With the second hook, also you can set the text twice, e.g.:

```
\long\def\Hy@setouterhbox#1#2{\long\def\my@temp{#2}}
\def\Hy@breaklinksunhbox#1{\my@temp}

11225 \newsavebox{\pdf@box}
11226 \providecommand*\Hy@setouterhbox{\sbox}
11227 \providecommand*\Hy@breaklinksunhbox{\unhbox}
11228 \def\Hy@DEST{/DEST}
11229 \def\pdf@rect#1{%
11230   \begingroup
11231     \chardef\x=1 %
11232     \def\Hy@temp{#1}%
11233     \ifx\Hy@temp\ltx@empty
11234       \chardef\x=0 %
11235     \else
11236       \def\y{\anchor@spot}%
11237       \ifx\Hy@temp\y
11238         \def\y{\relax}%
11239         \ifx\anchor@spot\y
11240           \chardef\x=0 %
11241         \fi
11242       \fi
11243     \fi
11244   \expandafter\endgroup
11245   \ifcase\x
11246     \literalps@out{H.S}%
11247     \literalps@out{H.R}%
11248   \else
11249     \leavevmode
11250     \Hy@SaveSpaceFactor
11251     \ifmmode
11252       \def\Hy@LinkMath{$}%
11253     \else
11254       \let\Hy@LinkMath\ltx@empty
11255     \fi
11256   \ifHy@breaklinks
11257     \Hy@setouterhbox\pdf@box{%
11258       \Hy@RestoreSpaceFactor
11259       \Hy@LinkMath
11260       \Hy@AllowHyphens#1\Hy@xspace@end
11261       \Hy@LinkMath
11262       \Hy@SaveSpaceFactor
11263     }%
11264   \else
11265     \sbox\pdf@box{%
11266       \Hy@RestoreSpaceFactor
11267       \Hy@LinkMath
11268       #1\Hy@xspace@end
11269       \Hy@LinkMath
11270       \Hy@SaveSpaceFactor
11271     }
```

```

11271      }%
11272      \fi
11273      \dimen@ht\pdf@box
11274      \ifdim\dp\pdf@box=\z@
11275          \literalps@out{H.S}%
11276      \else
11277          \lower\dp\pdf@box\hbox{\literalps@out{H.S}}%
11278      \fi

```

If the text has to be horizontal mode stuff then just unbox the saved box like this, which saves executing it twice, which can mess up counters etc (thanks DPC...).

```

11279      \ifHy@breaklinks
11280          \ifhmode
11281              \Hy@breaklinksunhbox\pdf@box
11282          \else
11283              \box\pdf@box
11284          \fi
11285      \else
11286          \expandafter\box\pdf@box
11287      \fi

```

but if it can have multiple paragraphs you'd need one of these, but in that case the measured box size would be wrong anyway.

```

\ifHy@breaklinks#1\else\box\pdf@box\fi
\ifHy@breaklinks{#1}\else\box\pdf@box\fi

11288      \ifdim\dimen@=\z@
11289          \literalps@out{H.R}%
11290      \else
11291          \raise\dimen@\hbox{\literalps@out{H.R}}%
11292      \fi
11293      \Hy@RestoreSpaceFactor
11294  \fi
11295  \ifx\pdf@type\Hy@DEST
11296  \else
11297      \pdf@addtoksx{H.B}%
11298  \fi
11299 }

```

All the supplied material is stored in a token list; since I do not feel sure I quite understand these, things may not work as expected with expansion. We'll have to experiment.

```

11300 \newtoks\pdf@toks
11301 \newtoks\pdf@defaulttoks
11302 \pdf@defaulttoks={}
11303 \def\pdf@addtoks#1#2{%
11304   \edef\@processme{\pdf@toks{\the\pdf@toks/#2 #1}}%
11305   \@processme
11306 }
11307 \def\pdf@addtoksx#1{%
11308   \edef\@processme{\pdf@toks{\the\pdf@toks\space #1}}%
11309   \@processme
11310 }
11311 \def\PDFdefaults#1{%

```

```

11312 \pdf@defaulttoks={#1}%
11313 }

This is the list of allowed keys. See the Acrobat manual for an explanation.

11314 % what is the type of pdfmark?
11315 \define@key{PDF}{pdfmark}{\def\pdf@type{#1}}
11316 % what is the link type?
11317 \define@key{PDF}{linktype}{\def\pdf@linktype{#1}}
11318 \def\pdf@linktype{link}
11319 % named object?
11320 \define@key{PDF}{objdef}{\edef\pdf@objdef{#1}}
11321 \let\pdf@objdef\ltx@empty
11322 % parameter is a stream of PDF
11323 \define@key{PDF}{Raw}{\pdf@addtoksx{#1}}
11324 % parameter is a name
11325 \define@key{PDF}{Action}{\pdf@addtoks{#1}{Action}}
11326 % parameter is a array
11327 \define@key{PDF}{Border}{%
11328 \edef\Hy@temp{#1}%
11329 \ifx\Hy@temp\@empty
11330 \else
11331 \pdf@addtoks{[#1]\Hy@BorderArrayPatch}{Border}%
11332 \fi
11333 }
11334 \let\Hy@BorderArrayPatch\@empty
11335 % parameter is a dictionary
11336 \define@key{PDF}{BorderStyle}{%
11337 \edef\Hy@temp{#1}%
11338 \ifx\Hy@temp\@empty
11339 \else
11340 \pdf@addtoks{<<#1>>}{BS}%
11341 \fi
11342 }
11343 % parameter is a array
11344 \define@key{PDF}{Color}{%
11345 \ifx\relax#1\relax
11346 \else
11347 \pdf@addtoks{[#1]}{Color}%
11348 \fi
11349 }
11350 % parameter is a string
11351 \define@key{PDF}{Contents}{\pdf@addtoks{(#1)}{Contents}}
11352 % parameter is a integer
11353 \define@key{PDF}{Count}{\pdf@addtoks{#1}{Count}}
11354 % parameter is a array
11355 \define@key{PDF}{CropBox}{\pdf@addtoks{[#1]}{CropBox}}%
11356 % parameter is a string
11357 \define@key{PDF}{DOSFile}{\pdf@addtoks{(#1)}{DOSFile}}
11358 % parameter is a string or file
11359 \define@key{PDF}{DataSource}{\pdf@addtoks{(#1)}{DataSource}}
11360 % parameter is a destination
11361 \define@key{PDF}{Dest}{%
11362 \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{#1}}%
11363 \ifx\Hy@pstringDest\@empty
11364 \Hy@pdfmarkerrortrue

```

```

11365   \Hy@Warning{Destination with empty name ignored}%
11366 \else
11367 \pdf@addtoks{(\Hy@pstringDest) cvn}{Dest}%
11368 \fi
11369 }
11370 \define@key{PDF}{DestAnchor}{%
11371 \Hy@pstringdef\Hy@pstringDest{\HyperDestNameFilter{\#1}}%
11372 \ifx\Hy@pstringDest\@empty
11373 \Hy@pdfmarkerrortrue
11374 \Hy@Warning{Destination with empty name ignored}%
11375 \else
11376 \pdf@addtoks{(\Hy@pstringDest) cvn}{Dest}%
11377 \fi
11378 }
11379 % parameter is a string
11380 \define@key{PDF}{Dir}{\pdf@addtoks{\#1}{Dir}}
11381 % parameter is a string
11382 \define@key{PDF}{File}{\pdf@addtoks{\#1}{File}}
11383 % parameter is a int
11384 \define@key{PDF}{Flags}{\pdf@addtoks{\#1}{Flags}}
11385 \define@key{PDF}{PDFAFlags}{%
11386 \ifHy@pdfa
11387 \pdf@addtoks{\#1}{F}%
11388 \fi
11389 }
11390 % parameter is a name
11391 \define@key{PDF}{AcroHighlight}{%
11392 \begingroup
11393 \edef\x{\#1}%
11394 \expandafter\endgroup\ifx\x\@empty
11395 \else
11396 \pdf@addtoks{\#1}{H}%
11397 \fi
11398 }
11399 % parameter is a string
11400 \define@key{PDF}{ID}{\pdf@addtoks{\#1}{ID}}% hash-ok
11401 % parameter is a string
11402 \define@key{PDF}{MacFile}{\pdf@addtoks{\#1}{MacFile}}
11403 % parameter is a string
11404 \define@key{PDF}{ModDate}{\pdf@addtoks{\#1}{ModDate}}
11405 % parameter is a string
11406 \define@key{PDF}{Op}{\pdf@addtoks{\#1}{Op}}
11407 % parameter is a Boolean
11408 \define@key{PDF}{Open}{\pdf@addtoks{\#1}{Open}}
11409 % parameter is a integer or name
11410 \define@key{PDF}{Page}{\pdf@addtoks{\#1}{Page}}
11411 % parameter is a name
11412 \define@key{PDF}{PageMode}{\pdf@addtoks{\#1}{PageMode}}
11413 % parameter is a string
11414 \define@key{PDF}{Params}{\pdf@addtoks{\#1}{Params}}
11415 % parameter is a array
11416 \define@key{PDF}{Rect}{\pdf@addtoks{\#1}{Rect}}% hash-ok
11417 % parameter is a integer
11418 \define@key{PDF}{SrcPg}{\pdf@addtoks{\#1}{SrcPg}}

```

```

11419 % parameter is a name
11420 \define@key{PDF}{Subtype}{\pdf@addtoks{\#1}{Subtype}}
11421 % parameter is a string
11422 \define@key{PDF}{Title}{\pdf@addtoks{(\#1)}{Title}}
11423 % parameter is a string
11424 \define@key{PDF}{Unix}{\pdf@addtoks{(\#1)}{Unix}}
11425 % parameter is a string
11426 \define@key{PDF}{UnixFile}{\pdf@addtoks{(\#1)}{UnixFile}}
11427 % parameter is an array
11428 \define@key{PDF}{View}{\pdf@addtoks{(\#1)}{View}}% hash-ok
11429 % parameter is a string
11430 \define@key{PDF}{WinFile}{\pdf@addtoks{(\#1)}{WinFile}}

```

These are the keys used in the DOCINFO section.

```

11431 \define@key{PDF}{Author}{\pdf@addtoks{(\#1)}{Author}}
11432 \define@key{PDF}{Creator}{\pdf@addtoks{(\#1)}{Creator}}
11433 \define@key{PDF}{CreationDate}{\pdf@addtoks{(\#1)}{CreationDate}}
11434 \define@key{PDF}{ModDate}{\pdf@addtoks{(\#1)}{ModDate}}
11435 \define@key{PDF}{Producer}{\pdf@addtoks{(\#1)}{Producer}}
11436 \define@key{PDF}{Subject}{\pdf@addtoks{(\#1)}{Subject}}
11437 \define@key{PDF}{Keywords}{\pdf@addtoks{(\#1)}{Keywords}}
11438 \define@key{PDF}{ModDate}{\pdf@addtoks{(\#1)}{ModDate}}
11439 \define@key{PDF}{Base}{\pdf@addtoks{(\#1)}{Base}}
11440 \define@key{PDF}{URI}{\pdf@addtoks{(\#1)}{URI}}
11441 \define@key{PDF}{Trapped}{%
11442   \edef\Hy@temp{\#1}%
11443   \ifx\Hy@temp\empty%
11444   \else%
11445     \pdf@addtoks{/ \#1}{Trapped}%
11446   \fi%
11447 }%
11448 </pdfmarkbase>
11449 <*pdfmark>
11450 \def\Acrobatmenu#1#2{%
11451   \EdefEscapeName\Hy@temp@menu{\#1}%
11452   \Hy@Acrobatmenu{\#1}{\#2}{%
11453     \pdfmark[{\#2}]{%
11454       linktype=menu,%
11455       pdfmark=/ANN,%
11456       AcroHighlight=\@pdfhighlight,%
11457       Border=\@pdfborder,%
11458       BorderStyle=\@pdfborderstyle,%
11459       Color=\@menubordercolor,%
11460       Action={<</Subtype/Named/N/\Hy@temp@menu>>},%
11461       Subtype=/Link,%
11462       PDFAFlags=4%
11463     }%
11464   }%
11465 }%
11466 }

```

And now for some useful examples:

```

11467 \def\PDFNextPage{\@ifnextchar[\{\PDFNextPage@{}\PDFNextPage@[]\}]{%
11468 \def\PDFNextPage@[#1]{%
11469   \pdfmark[{\#2}]{%

```

```

11470    #1,%
11471    Border=\@pdfborder,%
11472    BorderStyle=\@pdfborderstyle,%
11473    Color=.2 .1 .5,%
11474    pdfmark=/ANN,%
11475    Subtype=/Link,%
11476    PDFAFlags=4,%
11477    Page=/Next%
11478  }%
11479 }
11480 \def\PDFPreviousPage{%
11481   \@ifnextchar[{ \PDFPreviousPage@}{\PDFPreviousPage@[]}%
11482 }
11483 \def\PDFPreviousPage@[#1]#2{%
11484   \pdfmark[{-#2}]{%
11485     #1,%
11486     Border=\@pdfborder,%
11487     BorderStyle=\@pdfborderstyle,%
11488     Color=.4 .4 .1,%
11489     pdfmark=/ANN,%
11490     Subtype=/Link,%
11491     PDFAFlags=4,%
11492     Page=/Prev%
11493   }%
11494 }
11495 \def\PDFOpen#1{%
11496   \pdfmark{#1,pdfmark=/DOCVIEW}%
11497 }

```

This will only work if you use Distiller 2.1 or higher.

```

11498 \def\hyper@linkurl#1#2{%
11499   \begingroup
11500     \Hy@pstringdef\Hy@pstringURI{#2}%
11501     \hyper@chars
11502     \leavevmode
11503     \pdfmark[{-#1}]{%
11504       pdfmark=/ANN,%
11505       linktype=url,%
11506       AcroHighlight=\@pdfhighlight,%
11507       Border=\@pdfborder,%
11508       BorderStyle=\@pdfborderstyle,%
11509       Color=\@urlbordercolor,%
11510       Action={<<%
11511         /Subtype/URI%
11512         /URI(\Hy@pstringURI)%
11513         \ifHy@href@ismap
11514           /IsMap true%
11515         \fi
11516       >>}%
11517     Subtype=/Link,%
11518     PDFAFlags=4%
11519   }%
11520   \endgroup
11521 }
11522 \def\hyper@linkfile#1#2#3{%

```

```

11523 \begingroup
11524 \def\Hy@pstringF{\#2}%
11525 \Hy@CleanupFile\Hy@pstringF
11526 \Hy@pstringdef\Hy@pstringF\Hy@pstringF
11527 \Hy@pstringdef\Hy@pstringD{\#3}%
11528 \Hy@MakeRemoteAction
11529 \leavevmode
11530 \pdfmark{\#1}{%
11531 pdfmark=/ANN,%
11532 Subtype=/Link,%
11533 PDFAFlags=4,%
11534 AcroHighlight=\@pdfhighlight,%
11535 Border=\@pdfborder,%
11536 BorderStyle=\@pdfborderstyle,%
11537 linktype=file,%
11538 Color=\@filebordercolor,%
11539 Action={%
11540 <<%
11541 /S/GoToR%
11542 \Hy@SetNewWindow
11543 /F(\Hy@pstringF)%
11544 /D%
11545 \ifx\\#3\\%
11546 [\Hy@href@page\@pdfremotestartview]%
11547 \else
11548 (\Hy@pstringD)cvn%
11549 \fi
11550 \Hy@href@nextactionraw
11551 >>%
11552 }%
11553 }%
11554 \endgroup
11555 }
11556 \def\@hyper@launch{run:#1\\#2#3}{%
11557 \begingroup
11558 \Hy@pstringdef\Hy@pstringF{\#1}%
11559 \Hy@pstringdef\Hy@pstringP{\#3}%
11560 \leavevmode
11561 \pdfmark{\#2}{%
11562 pdfmark=/ANN,%
11563 Subtype=/Link,%
11564 PDFAFlags=4,%
11565 AcroHighlight=\@pdfhighlight,%
11566 Border=\@pdfborder,%
11567 BorderStyle=\@pdfborderstyle,%
11568 linktype=run,%
11569 Color=\@runbordercolor,%
11570 Action={%
11571 <<%
11572 /S/Launch%
11573 \Hy@SetNewWindow
11574 /F(\Hy@pstringF)%
11575 \ifx\\#3\\%
11576 \else

```

```

11577      /Win<</P(\Hy@pstringP)/F(\Hy@pstringF)>>%
11578      \fi
11579      \Hy@href@nextactionraw
11580      >>%
11581      }%
11582      }%
11583      \endgroup
11584 }
11585 </pdfmark>

```

Unfortunately, some parts of the `pdfmark` PostScript code depend on vagaries of the dvi driver. We isolate here all the problems.

43.9 Rokicki's dvips

`dvips` thinks in 10ths of a big point, its coordinate space is resolution dependent, and its *y* axis starts at the top of the page. Other drivers can and will be different!

The work is done in `SDict`, because we add in some header definitions in a moment.

```

11586 <*dvips>
11587 \providecommand*{\XR@ext}{pdf}
11588 \let\Hy@raisedlink\ltx@empty
11589 \def\literalps@out#1{\special{ps:SDict begin #1 end}}%
11590 \def\headerps@out#1{\special{! #1}}%
11591 \input{pdfmark.def}%
11592 \ifx\@pdfproducer\relax
11593 \def\@pdfproducer{dvips + Distiller}%
11594 \fi
11595 \providecommand*{\@pdfborder}{0 0 1}
11596 \providecommand*{\@pdfborderstyle}{}
11597 \providecommand*{\@pdfview}{XYZ}
11598 \providecommand*{\@pdfviewparams}{H.V}
11599 \def\Hy@BorderArrayPatch{BorderArrayPatch}
11600 \g@addto@macro\Hy@FirstPageHook{%
11601 \headerps@out{%

```

Unless I am going mad, this *appears* to be the relationship between the default coordinate system (PDF), and `dvips`:

```

/DvipsToPDF { .01383701 div Resolution div } def
/PDFToDvips { .01383701 mul Resolution mul } def

```

the latter's coordinates are resolution dependent, but what that .01383701 is, who knows? well, almost everyone except me, I expect...And yes, Maarten Gelderman <mgelderman@econ.vu.nl> points out that its 1/72.27 (the number of points to an inch, big points to inch is 1/72). This also suggests that the code would be more understandable (and exact) if 0.013 div would be replaced by 72.27 mul, so here we go. If this isn't right, I'll revert it.

```

11602 /DvipsToPDF{72.27 mul Resolution div} def%
11603 /PDFToDvips{72.27 div Resolution mul} def%
11604 /BPToDvips{72 div Resolution mul} def

```

The values inside the /Border array are not taken literally, but interpreted by ghostscript using the resolution of the dvi driver. I don't know how other distiller programs behaves in this manner.

Note GhostScript changed its behaviour here and later versions do not need this scaling, so test the PostScript interpreter is GhostScript and if so check its version.

If using gs and release > 9.27 no-op, otherwise patch.

```

11605 product (Ghostscript) search {pop pop pop revision 927 gt}%
11606 {pop false} ifelse%
11607 {%
11608 /BorderArrayPatch{} def%
11609 }%
11610 {%
11611 /BorderArrayPatch{%
11612 [exch{%
11613 dup dup type/integertype eq exch type/realtypes eq or%
11614 {BPToDvips}if%
11615 }forall]%
11616 }def%
11617 } ifelse

```

The rectangle around the links starts off *exactly* the size of the box; we will to make it slightly bigger, 1 point on all sides.

```

11618 /HyperBorder {1 PDFToDvips} def%
11619 /H.V {pdf@hoff pdf@voff null} def%
11620 /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%

```

H.S (start of anchor, link, or rect) stores the *x* and *y* coordinates of the current point, in PDF coordinates

```

11621 /H.S {%
11622 currentpoint %
11623 HyperBorder add /pdf@lly exch def %
11624 dup DvipsToPDF 72 add /pdf@hoff exch def %
11625 HyperBorder sub /pdf@llx exch def%
11626 } def%

```

The calculation of upper left *y* is done without raising the point in T_EX, by simply adding on the current \baselineskip to the current *y*. This is usually too much, so we remove a notional 2 points.

We have to see what the current baselineskip is, and convert it to the dvips coordinate system.

Argument: baselineskip in pt. The *x* and *y* coordinates of the current point, minus the baselineskip

```

11627 /H.L {%
11628 2 sub dup%
11629 /HyperBasePt exch def %
11630 PDFToDvips /HyperBaseDvips exch def %
11631 currentpoint %
11632 HyperBaseDvips sub /pdf@ury exch def%
11633 /pdf@urx exch def%
11634 } def%
11635 /H.A {%
11636 H.L %
11637 % |/pdf@voff| = the distance from the top of the page to a point

```

```

11638 % |\baselineskip| above the current point in PDF coordinates
11639     currentpoint exch pop %
11640     vsize 72 sub exch DvipsToPDF %
11641     HyperBasePt sub % baseline skip
11642     sub /pdf@voff exch def%
11643 } def%
11644 /H.R {%
11645     currentpoint %
11646     HyperBorder sub /pdf@ury exch def %
11647     HyperBorder add /pdf@urx exch def %
11648 % |/pdf@voff| = the distance from the top of the page to the current point, in
11649 % PDF coordinates
11650     currentpoint exch pop vsize 72 sub %
11651     exch DvipsToPDF sub /pdf@voff exch def%
11652 } def%
11653 }%
11654 }
11655 \AtBeginShipoutFirst{%
11656 \ifHy@setpagesize
11657 \begingroup
11658 \ifnum\mag=\@m
11659 \ifdim\stockwidth>\z@
11660 \ifdim\stockheight>\z@
11661 \special{papersize=\the\stockwidth,\the\stockheight}%
11662 \else
11663 \ifdim\paperwidth>\z@
11664 \ifdim\paperheight>\z@
11665 \special{papersize=\the\paperwidth,\the\paperheight}%
11666 \fi
11667 \fi
11668 \fi
11669 \else
11670 \ifdim\stockwidth=\z@
11671 \ifdim\paperwidth>\z@
11672 \ifdim\paperheight>\z@
11673 \special{papersize=\the\paperwidth,\the\paperheight}%
11674 \fi
11675 \fi
11676 \fi
11677 \fi
11678 \fi
11679 \endgroup
11680 \fi
11681 \Hy@DisableOption{setpagesize}%
11682 }

11683 \def\setpdfinkmargin#1{%
11684 \begingroup
11685 \setlength{\dimen@\{#1}\%
11686 \literalps@out{%
11687 /HyperBorder{\strip@pt\dimen@\space PDFToDvips}def%
11688 }%
11689 \endgroup
11690 }

```

```
11691 </dvips>
```

43.10 VTeX's vtexpdfmark driver

This part is derived from the dvips (many names reflect this).

The origin seems to be the same as TeX's origin, 1 in from the left and 1 in downwards from the top. The direction of the y axis is downwards, the opposite of the dvips case. Units seems to be pt or bp.

```
11692 <*vtexpdfmark>
11693 \providecommand*\XR@ext{pdf}
11694 \let\Hy@raisedlink\ltx@empty
11695 \def\literalps@out#1{\special{pS:#1}}%
11696 \def\headerps@out#1{\immediate\special{pS:#1}}%
11697 \input{pdfmark.def}%
11698 \ifx\@pdfproducer\relax
11699   \ifnum\OpMode=\@ne
11700     \def\@pdfproducer{VTeX}%
11701   \else
11702     \def\@pdfproducer{VTeX + Distiller}%
11703   \fi
11704 \fi
11705 \providecommand*\@pdfborder{0 0 1}
11706 \providecommand*\@pdfborderstyle{}
11707 \providecommand*\@pdfview{XYZ}
11708 \providecommand*\@pdfviewparams{ H.V}
11709 \g@addto@macro\Hy@FirstPageHook{%
11710   \headerps@out{%
11711     /vsize {\Hy@pageheight} def%}
```

The rectangle around the links starts off *exactly* the size of the box; we will to make it slightly bigger, 1 point on all sides.

```
11712   /HyperBorder {1} def%
11713   /H.V {pdf@hoff pdf@voff null} def%
11714   /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%
11715   /H.S {%
11716     currentpoint %
11717     HyperBorder sub%
11718     /pdf@lly exch def %
11719     dup 72 add /pdf@hoff exch def %
11720     HyperBorder sub%
11721     /pdf@llx exch def%
11722   } def%
```

The x and y coordinates of the current point, minus the \baselineskip: $\text{pdf@ury} = Y_c + \text{HyperBasePt} + \text{HyperBorder}$, $\text{pdf@urx} = X_c + \text{HyperBorder}$

```
11723   /H.L {%
11724     2 sub%
11725     /HyperBasePt exch def %
11726     currentpoint %
```

```

11727     HyperBasePt add HyperBorder add%
11728     /pdf@ury exch def %
11729     HyperBorder add%
11730     /pdf@urx exch def%
11731 } def%
11732 /H.A {%
11733   H.L %
11734   currentpoint exch pop %
11735   vsize 72 sub exch %
11736   HyperBasePt add add%
11737   /pdf@voff exch def%
11738 } def%
11739 pdf@ury =  $Y_c + \text{HyperBorder}$ , pdf@urx =  $X_c + \text{HyperBorder}$ 
11740 /H.R {%
11741   currentpoint %
11742   HyperBorder add%
11743   /pdf@ury exch def %
11744   HyperBorder add%
11745   /pdf@urx exch def %
11746   currentpoint exch pop vsize 72 sub add%
11747   /pdf@voff exch def%
11748 } def%
11749 }%
11750 \def\setpdflinkmargin#1{%
11751 \begingroup
11752 \setlength{\dimen@}{#1}%
11753 \literalps@out{%
11754 /HyperBorder{\strip@pt\dimen@}def%
11755 }%
11756 \endgroup
11757 }
11758 </vtexpdfmark>

```

43.11 Textures

```

11759 <*textures>
11760 \providecommand*\XR@ext{pdf}

```

At the suggestion of Jacques Distler (distler@golem.ph.utexas.edu), try to derive a suitable driver for Textures. This was initially a copy of dvips, with some guesses about Textures behaviour. Ross Moore (ross@maths.mq.edu.au) has added modifications for better compatibility, and to support use of pdfmark.

Start by defining a macro that expands to the end-of-line character. This will be used to format the appearance of PostScript code, to enhance readability, and avoid excessively long lines which might otherwise become broken to bad places.

\Hy@ps@CR The macro \Hy@ps@CR contains the end-of-line character.

```

11761 \begingroup
11762 \obeylines %
11763 \gdef\Hy@ps@CR{\noexpand
11764 }%
11765 \endgroup %

```

Textures has two types of `\special` command for inserting PostScript code directly into the dvi output. The ‘postscript’ way preserves TeX’s idea of where on the page the `\special` occurred, but it wraps the contents with a `save-restore` pair, and adjusts the user-space coordinate system for local drawing commands. The ‘rawpostscript’ way simply inserts code, without regard for the location on the page.

Thus, to put arbitrary PostScript coding at a fixed location requires using *both* `\special` constructions. It works by pushing the device-space coordinates onto the operand stack, where they can be used to transform back to the correct user-space coordinates for the whole page, within a ‘rawpostscript’ `\special`.

```
11766 \def\literalps@out#1{%
11767   \special{postscript 0 0 transform}%
11768   \special{rawpostscript itransform moveto\Hy@ps@CR #1}%
11769 }%
11770 %
```

The ‘prepostscript’ is a 3rd kind of `\special`, used for inserting definitions into the dictionaries, before page-building begins. These are to be available for use on all pages.

```
11771 \def\headerps@out#1{%
11772   \special{%
11773     prepostscript TeXdict begin\Hy@ps@CR
11774       #1\Hy@ps@CR
11775     end%
11776   }%
11777 }%
11778 %
```

To correctly support the `pdfmark` method, for embedding PDF definitions with `.ps` files in a non-intrusive way, an appropriate definition needs to be made *before* the file `pdfmark.def` is read. Other parameters are best set afterwards.

```
11779 \g@addto@macro\Hy@FirstPageHook{%
11780   \headerps@out{%
11781     /betterpdfmark {%
11782       systemdict begin %
11783         dup /BP eq%
11784         {cleartomark gsave nulldevice []%
11785           {dup /EP eq%
11786             {cleartomark cleartomark grestore}%
11787             {cleartomark}%
11788             ifelse%
11789           }ifelse %
11790         end%
11791       }def\Hy@ps@CR
11792       __pdfmark__ not{/pdfmark /betterpdfmark load def}if%
11793     }% end of \headerps@out
11794 }% end of \AtBeginShipoutFirst
11795 %
11796 \input{pdfmark.def}%
11797 %
11798 \ifx\@pdfproducer\relax
11799   \def\@pdfproducer{Textures + Distiller}%
11800 \fi
```

```

11801 \providecommand*{\@pdfborder}{\def\@pdfborder{#1\relax}}
11802 \providecommand*{\@pdfborderstyle}{\def\@pdfborderstyle{}}
11803 \providecommand*{\@pdfview}{\def\@pdfview{XYZ}}
11804 \providecommand*{\@pdfviewparams}{\def\@pdfviewparams{H.V}}
11805 %

```

These are called at the start and end of unboxed links; their job is to leave available PS variables called `pdf@llx pdf@lly pdf@urx pdf@ury`, which are the coordinates of the bounding rectangle of the link, and `pdf@hoff pdf@voff` which are the PDF page offsets. The Rect pair are called at the LL and UR corners of a box known to TeX.

```

11806 \Hy@AtBeginDocument{%
11807   \headerps@out{%

```

Textures lives in normal points, I think. So conversion from one coordinate system to another involves doing nothing.

```

11808   /vsize {\Hy@pageheight} def%
11809   /DvipsToPDF {} def%
11810   /PDFToDvips {} def%
11811   /BPToDvips {} def%
11812   /HyperBorder { 1 PDFToDvips } def\Hy@ps@CR
11813   /H.V {pdf@hoff pdf@voff null} def\Hy@ps@CR
11814   /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def\Hy@ps@CR
11815   /H.S {%
11816     currentpoint %
11817     HyperBorder add /pdf@lly exch def %
11818     dup DvipsToPDF 72 add /pdf@hoff exch def %
11819     HyperBorder sub /pdf@llx exch def%
11820   } def\Hy@ps@CR
11821   /H.L {%
11822     2 sub %
11823     PDFToDvips /HyperBase exch def %
11824     currentpoint %
11825     HyperBase sub /pdf@ury exch def%
11826     /pdf@urx exch def%
11827   } def\Hy@ps@CR
11828   /H.A {%
11829     H.L %
11830     currentpoint exch pop %
11831     vsize 72 sub exch DvipsToPDF %
11832     HyperBase sub % baseline skip
11833     sub /pdf@voff exch def%
11834   } def\Hy@ps@CR
11835   /H.R {%
11836     currentpoint %
11837     HyperBorder sub /pdf@ury exch def %
11838     HyperBorder add /pdf@urx exch def %
11839     currentpoint exch pop vsize 72 sub %
11840     exch DvipsToPDF sub /pdf@voff exch def%
11841   } def\Hy@ps@CR
11842 }%
11843 }

11844 \def\setpdflinkmargin#1{%
11845   \begingroup

```

```

11846   \setlength{\dimen@}{\#1}%
11847   \literalps@out{%
11848     /HyperBorder{\strip@pt\dimen@\space PDFToDvips}def%
11849   }%
11850   \endgroup
11851 }

11852 \Hy@AtBeginDocument{%
11853   \ifHy@colorlinks
11854     \headerps@out{/PDFBorder{/Border [0 0 0]}def}%
11855   \fi
11856 }

Textures provides built-in support for HyperTeX specials so this part combines code from hypertex.def with what is established by loading pdfmark.def, or any other driver.

11857 \expandafter\let\expandafter\keepPDF@SetupDoc
11858 \csname PDF@SetupDoc\endcsname
11859 \def\PDF@SetupDoc{%
11860   \ifx\@baseurl\@empty
11861   \else
11862     \special{html:<base href="\@baseurl">}%
11863   \fi
11864   \keepPDF@SetupDoc
11865 }
11866 \Hy@WrapperDef\hyper@anchor{\#1}{%
11867   \Hy@SaveLastskip
11868   \Hy@VerboseAnchor{\#1}%
11869   \begingroup
11870   \let\protect=\string
11871   \special{html:<a name=%
11872     \hyper@quote\HyperDestNameFilter{\#1}\hyper@quote>}%
11873   \endgroup
11874   \Hy@activeanchortrue
11875   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
11876   \special{html:</a>}%
11877   \Hy@activeanchorfalse
11878   \Hy@RestoreLastskip
11879 }
11880 \Hy@WrapperDef\hyper@anchorstart{\#1}{%
11881   \Hy@SaveLastskip
11882   \Hy@VerboseAnchor{\#1}%
11883   \begingroup
11884   \hyper@chars
11885   \special{html:<a name=%
11886     \hyper@quote\HyperDestNameFilter{\#1}\hyper@quote>}%
11887   \endgroup
11888   \Hy@activeanchortrue
11889 }
11890 \def\hyper@anchorend{%
11891   \special{html:</a>}%
11892   \Hy@activeanchorfalse
11893   \Hy@RestoreLastskip
11894 }
11895 \def\@urltype{url}

```

```

11896 \def\hyper@linkstart#1#2{%
11897   \Hy@VerboseLinkStart{#1}{#2}%
11898   \expandafter\Hy@colorlink\csname @#1color\endcsname
11899   \def\Hy@tempa{#1}%
11900   \ifx\Hy@tempa\@urlype
11901     \special{html:<a href=\hyper@quote#2\hyper@quote>}%
11902   \else
11903     \begingroup
11904       \hyper@chars
11905       \special{%
11906         html:<a href=%
11907           \hyper@quote\#\HyperDestNameFilter{#2}\hyper@quote%}
11908       }%
11909     \endgroup
11910   \fi
11911 }
11912 \def\hyper@linkend{%
11913   \special{html:</a>}%
11914   \Hy@endcolorlink
11915 }
11916 \def\hyper@linkfile#1#2#3{%
11917   \hyper@linkurl{#1}%
11918   \Hy@linkfileprefix#2\ifx\\#3\\else\\##3\fi
11919 }%
11920 }
11921 \def\hyper@linkurl#1#2{%
11922   \leavevemode
11923   \ifHy@raiselinks
11924     \Hy@SaveSpaceFactor
11925     \Hy@SaveSavedSpaceFactor
11926     \sbox{\@tempboxa{\Hy@RestoreSpaceFactor#1}}%
11927     \Hy@RestoreSavedSpaceFactor
11928     \linkdim\dp\@tempboxa
11929     \lower\linkdim\hbox{%
11930       \hyper@chars
11931       \special{html:<a href=\hyper@quote#2\hyper@quote>}%
11932     }%
11933     \Hy@colorlink\@urlcolor
11934     \Hy@RestoreSpaceFactor
11935     #1\Hy@xspace@end
11936     \Hy@SaveSpaceFactor
11937     \linkdim\ht\@tempboxa
11938     \advance\linkdim by -6.5\p@
11939     \raise\linkdim\hbox{\special{html:</a>}}%
11940   \Hy@endcolorlink
11941   \Hy@RestoreSpaceFactor
11942 \else
11943   \begingroup
11944     \hyper@chars
11945     \special{html:<a href=\hyper@quote#2\hyper@quote>}%
11946     \Hy@colorlink\@urlcolor#1\Hy@xspace@end
11947     \special{html:</a>}%
11948     \Hy@endcolorlink
11949   \endgroup

```

```

11950 \fi
11951 }

Very poor implementation of \hyper@link without considering #1.

11952 \def\hyper@link#1#2#3{%
11953 \Hy@VerboseLinkStart{#1}{#2}%
11954 \hyper@linkurl{#3}{\#HyperDestNameFilter{#2}}%
11955 }
11956 \def\hyper@image#1#2{%
11957 \begingroup
11958 \hyper@chars
11959 \special{html:<img src=\hyper@quote#1\hyper@quote>}%
11960 \endgroup
11961 }
11962 </textures>

```

43.12 dvipsone

```

11963 % \subsection{dvipsone driver}
11964 % Over-ride the default setup macro in pdfmark driver to use Y\&Y
11965 % |\special| commands.
11966 (*dvipsone)
11967 \providecommand*\XR@ext{pdf}
11968 \let\Hy@raisedlink\ltx@empty
11969 \providecommand*\@pdfborder{0 0 1}
11970 \providecommand*\@pdfborderstyle{}
11971 \def\literalps@out#1{\special{ps:#1}}%
11972 \def\headerps@out#1{\special{headertext=#1}}%
11973 \input{pdfmark.def}%
11974 \HyInfo@AddonUnsupportedtrue
11975 \def\PDF@FinishDoc{%
11976 \Hy@UseMaketitleInfos
11977 \HyInfo@TrappedUnsupported
11978 \special{PDF: Keywords \@pdfkeywords}%
11979 \special{PDF: Title \@pdftitle}%
11980 \special{PDF: Creator \@pdfcreator}%
11981 \ifx\@pdfcreationdate\empty
11982 \else
11983 \special{PDF: CreationDate \@pdfcreationdate}%
11984 \fi
11985 \ifx\@pdfmoddate\empty
11986 \else
11987 \special{PDF: ModDate \@pdfmoddate}%
11988 \fi
11989 \special{PDF: Author \@pdfauthor}%
11990 \ifx\@pdfproducer\relax
11991 \else
11992 \special{PDF: Producer \@pdfproducer}%
11993 \fi
11994 \special{PDF: Subject \@pdfsubject}%
11995 \Hy@DisableOption{pdfauthor}%
11996 \Hy@DisableOption{pdftitle}%
11997 \Hy@DisableOption{pdfsubject}%
11998 \Hy@DisableOption{pdfcreator}%

```

```

11999 \Hy@DisableOption{addtopdfcreator}%
12000 \Hy@DisableOption{pdfcreationdate}%
12001 \Hy@DisableOption{pdfcreationdate}%
12002 \Hy@DisableOption{pdfmoddate}%
12003 \Hy@DisableOption{pdfproducer}%
12004 \Hy@DisableOption{pdfkeywords}%
12005 \Hy@DisableOption{pdftrapped}%
12006 \Hy@DisableOption{pdffinfo}%
12007 }
12008 \def\PDF@SetupDoc{%
12009 \def\Hy@temp{}%
12010 \ifx\@pdfstartpage\@empty
12011 \else
12012 \ifx\@pdfstartview\@empty
12013 \else
12014 \edef\Hy@temp{%
12015 ,Page=\@pdfstartpage
12016 ,View=\@pdfstartview
12017 }%
12018 \fi
12019 \fi
12020 \edef\Hy@temp{%
12021 \noexpand\pdfmark{%
12022 pdfmark=/DOCVIEW,%
12023 PageMode=/\@pdfpagemode
12024 \Hy@temp
12025 }%
12026 }%
12027 \Hy@temp
12028 \ifx\@pdffpagescrop\@empty
12029 \else
12030 \pdfmark{pdfmark=/PAGES,CropBox=\@pdffpagescrop}%
12031 \fi
12032 \edef\Hy@temp{%
12033 \ifHy@pdftoolbar\else /HideToolbar true\fi
12034 \ifHy@pdfmenubar\else /HideMenubar true\fi
12035 \ifHy@pdfwindowui\else /HideWindowUI true\fi
12036 \ifHy@pdffitwindow /FitWindow true\fi
12037 \ifHy@pdfcenterwindow /CenterWindow true\fi
12038 \ifHy@pdfdisplaydoctitle /DisplayDocTitle true\fi
12039 \Hy@UseNameKey{NonFullScreenPageMode}\@pdfnonfullscreenpagemode
12040 \Hy@UseNameKey{Direction}\@pdfdirection
12041 \Hy@UseNameKey{ViewArea}\@pdfviewarea
12042 \Hy@UseNameKey{ViewClip}\@pdfviewclip
12043 \Hy@UseNameKey{PrintArea}\@pdfprintarea
12044 \Hy@UseNameKey{PrintClip}\@pdfprintclip
12045 \Hy@UseNameKey{PrintScaling}\@pdfprintscaling
12046 \Hy@UseNameKey{Duplex}\@pdfduplex
12047 \ifx\@pdfpicktraybypdfsize\@empty
12048 \else
12049 /PickTrayByPDFSize \@pdfpicktraybypdfsize
12050 \fi
12051 \ifx\@pdfprintpagerange\@empty
12052 \else

```

```

12053   /PrintPageRange[\@pdfprintpagerange]%
12054   \fi
12055   \ifx\@pdfnumcopies\@empty
12056   \else
12057     /NumCopies \@pdfnumcopies
12058   \fi
12059 }
12060 \Hy@pstringdef\Hy@pstringB{\@baseurl}%
12061 \pdfmark{%
12062   pdfmark=/PUT,%
12063   Raw={%
12064     \string{Catalog\string}<<%
12065     \ifx\Hy@temp\@empty
12066     \else
12067       /ViewerPreferences<<\Hy@temp>>%
12068     \fi
12069     \Hy@UseNameKey{PageLayout}\@pdfpagelayout
12070     \ifx\@pdflang\relax
12071     \else
12072       /Lang(\@pdflang)%
12073     \fi
12074     \ifx\@baseurl\@empty
12075     \else
12076       /URI<</Base(\Hy@pstringB)>>%
12077     \fi
12078   >>%
12079 }
12080 }
12081 }
12082 \providecommand*\@pdfview{XYZ}
12083 \providecommand*\@pdfviewparams{ %
12084   gsave revscl currentpoint grestore %
12085   72 add exch pop null exch null%
12086 }
12087 \def\Hy@BorderArrayPatch{BorderArrayPatch}

```

These are called at the start and end of unboxed links; their job is to leave available PS variables called `pdf@llx pdf@lly pdf@urx pdf@ury`, which are the coordinates of the bounding rectangle of the link, and `pdf@hoff pdf@voff` which are the PDF page offsets. These latter are currently not used in the dvipsone setup. The Rect pair are called at the LL and UR corners of a box known to TeX.

```

12088 \g@addto@macro\Hy@FirstPageHook{%
12089   \headerps@out{%
dvipsone lives in scaled points; does this mean 65536 or 65781?
12090   /DvipsToPDF { 65781 div } def%
12091   /PDFToDvips { 65781 mul } def%
12092   /BPToDvips{65781 mul}def%
12093   /HyperBorder { 1 PDFToDvips } def%
12094   /H.B {/Rect[pdf@llx pdf@lly pdf@urx pdf@ury]} def%

```

The values inside the /Boder array are not taken literally, but interpreted by ghostscript using the resolution of the dvi driver. I don't know how other distiller programs behaves in this manner.

```
12095   /BorderArrayPatch{%
```

```

12096 [exch{%
12097   dup dup type/integertype eq exch type/realtytype eq or%
12098   {BPToDvips}if%
12099 }forall]%
12100 }def%
12101 /H.S {%
12102   currentpoint %
12103   HyperBorder add /pdf@lly exch def %
12104   dup DvipsToPDF 72 add /pdf@hoff exch def %
12105   HyperBorder sub /pdf@llx exch def%
12106 } def%
12107 /H.L {%
12108   2 sub %
12109   PDFToDvips /HyperBase exch def %
12110   currentpoint %
12111   HyperBase sub /pdf@ury exch def%
12112   /pdf@urx exch def%
12113 } def%
12114 /H.A {%
12115   H.L %
12116   currentpoint exch pop %
12117   HyperBase sub % baseline skip
12118   DvipsToPDF /pdf@voff exch def%
12119 } def%
12120 /H.R {%
12121   currentpoint %
12122   HyperBorder sub /pdf@ury exch def %
12123   HyperBorder add /pdf@urx exch def %
12124   currentpoint exch pop DvipsToPDF /pdf@voff exch def%
12125 } def%
12126 }%
12127 }

12128 \def\setpdfinkmargin#1{%
12129   \begingroup
12130   \setlength{\dimen@}{#1}%
12131   \literalps@out{%
12132     /HyperBorder{\strip@pt\dimen@\space PDFToDvips}def%
12133   }%
12134   \endgroup
12135 }

12136 </dvipsone>

```

43.13 TeX4ht

```

12137 <*tex4ht>
12138 \providecommand*\XR@ext{html}
12139 \let\Hy@raisedlink\ltx@empty
12140 \@ifpackageloaded{tex4ht}{%
12141   \Hy@Info{tex4ht is already loaded}%
12142 }{%
12143   \RequirePackage[htex4ht]{tex4ht}%
12144 }
12145 \hyperlinkfileprefix{%
12146 \let\PDF@FinishDoc\ltx@empty

```

```

12147 \def\PDF@SetupDoc{%
12148   \ifx\@baseurl\@empty
12149   \else
12150     \special{t4ht=<base href="\@baseurl">}%
12151   \fi
12152 }
12153 \Hy@WrapperDef\hyper@anchor#1{%
12154   \Hy@SaveLastskip
12155   \Hy@VerboseAnchor{#1}%
12156   \begingroup
12157     \let\protect=\string
12158     \special{t4ht=<a name=%
12159       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12160   \endgroup
12161   \Hy@activeanchortrue
12162   \Hy@colorlink\@anchorcolor\anchor@spot\Hy@endcolorlink
12163   \special{t4ht=</a>}%
12164   \Hy@activeanchorfalse
12165   \Hy@RestoreLastskip
12166 }
12167 \Hy@WrapperDef\hyper@anchorstart#1{%
12168   \Hy@SaveLastskip
12169   \Hy@VerboseAnchor{#1}%
12170   \begingroup
12171     \hyper@chars\special{t4ht=<a name=%
12172       \hyper@quote\HyperDestNameFilter{#1}\hyper@quote>}%
12173   \endgroup
12174   \Hy@activeanchortrue
12175 }
12176 \def\hyper@anchorend{%
12177   \special{t4ht=</a>}%
12178   \Hy@activeanchorfalse
12179   \Hy@RestoreLastskip
12180 }
12181 \def\curltype{url}
12182 \def\hyper@linkstart#1#2{%
12183   \Hy@VerboseLinkStart{#1}{#2}%
12184   \expandafter\Hy@colorlink\csname @#1color\endcsname
12185   \def\Hy@tempa{#1}%
12186   \ifx\Hy@tempa\curltype
12187     \special{t4ht=<a href=\hyper@quote#2\hyper@quote>}%
12188   \else
12189     \begingroup
12190       \hyper@chars
12191       \special{t4ht=<a href=%
12192         \hyper@quote\#\HyperDestNameFilter{#2}\hyper@quote>}%
12193     \endgroup
12194   \fi
12195 }
12196 \def\hyper@linkend{%
12197   \special{t4ht=</a>}%
12198   \Hy@endcolorlink
12199 }
12200 \def\hyper@linkfile#1#2#3{%

```

```

12201 \hyper@linkurl{\#1}{\Hy@linkfileprefix\#2\ifx\\#3\\\else##3\fi}%
12202 }
12203 \def\hyper@linkurl#1#2{%
12204 \leavevemode
12205 \ifHy@raiselinks
12206 \Hy@SaveSpaceFactor
12207 \Hy@SaveSavedSpaceFactor
12208 \sbox{\tempboxa{\Hy@RestoreSpaceFactor\#1}}%
12209 \Hy@RestoreSavedSpaceFactor
12210 \linkdim\dp\tempboxa
12211 \lower\linkdim\hbox{%
12212 \begingroup
12213 \hyper@chars
12214 \special{%
12215 t4ht=<a href=\hyper@quote\hyper@quote>%
12216 }%
12217 \endgroup
12218 }%
12219 \Hy@colorlink\curlcolor
12220 \Hy@RestoreSpaceFactor
12221 #1\Hy@xspace@end
12222 \Hy@SaveSpaceFactor
12223 \Hy@endcolorlink
12224 \linkdim\ht\tempboxa
12225 \advance\linkdim by -6.5\p@
12226 \raise\linkdim\hbox{\special{t4ht=</a>}}%
12227 \Hy@RestoreSpaceFactor
12228 \else
12229 \begingroup
12230 \hyper@chars
12231 \special{t4ht=<a href=\hyper@quote\hyper@quote>}}%
12232 \Hy@colorlink\curlcolor
12233 #1\Hy@xspace@end
12234 \Hy@endcolorlink
12235 \special{t4ht=</a>}%
12236 \endgroup
12237 \fi
12238 }

```

Poor implementation of \hyper@link without considering #1.

```

12239 \def\hyper@link#1#2#3{%
12240 \Hy@VerboseLinkStart{\#1}{\#2}}%
12241 \hyper@linkurl{\#3}{\#\HyperDestNameFilter{\#2}}%
12242 }
12243 \def\hyper@image#1#2{%
12244 \begingroup
12245 \hyper@chars
12246 \special{t4ht=<img src=\hyper@quote\hyper@quote>}}%
12247 \endgroup
12248 }
12249 \let\autoref\ref
12250 \ifx \rEfLiNK \UnDef
12251 \def\rEfLiNK {\#1#2{\#2}}%
12252 \fi
12253 \let\backref\ltx@gobble

```

Fix for tex4ht.

```

12254 \AtBeginDocument{%
12255   \expandafter
12256   \let\expandafter\Hy@OrgMakeLabel\csname Make:Label\endcsname
12257   \expandafter\def\csname Make:Label\endcsname#1#2{%
12258     \ifhmode
12259       \Hy@SaveSpaceFactor
12260     \else
12261       \global\Hy@SavedSpaceFactor=1000 %
12262     \fi
12263   \Hy@OrgMakeLabel{#1}{%
12264     \Hy@RestoreSpaceFactor
12265     #2\Hy@xspace\end%
12266     \Hy@SaveSpaceFactor
12267   }%
12268   \Hy@RestoreSpaceFactor
12269 }%
12270 }
12271 </tex4ht>
12272 <*tex4htcfg>
12273 \IfFileExists{\jobname.cfg}{\endinput}{}%
12274 \Preamble{html}%
12275 \begin{document}%
12276 \EndPreamble
12277 \def\TeX{\TeX}
12278 \def\OMEGA{\Omega}
12279 \def\LaTeX{\LaTeX}
12280 \def\LaTeXe{\LaTeXe}
12281 \def\c{\c}
12282 \def\mf{\mf}
12283 \def\mp{\mp}
12284 </tex4htcfg>
```

44 Driver-specific form support

44.1 pdfmarks

change 2020-06-20: added /Euro to encoding

```

12285 <*pdfmark>
12286 \long\def\@Form[#1]{%
12287   \g@addto@macro\Hy@FirstPageHook{%
12288     \headerps@out{%
12289   [%
12290     /_objdef{pdfDocEncoding}%
12291     /type/dict%
12292     /OBJ pdfmark%
12293   [%
12294     {pdfDocEncoding}%
12295     <<%
12296     /Type/Encoding%
12297     /Differences[%
12298       24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek/ring%
12299       /tilde %
12300       39/quotesingle %
```

```

12301    96/grave %
12302    128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
12303    /fraction/guilingleft/guilingleft/minus/perthousand%
12304    /quotedblbase/quotedblleft/quotedblright/quotelleft%
12305    /quoteright/quotesinglbase/trademark/fi/fi/Lslash/OE/Scaron%
12306    /Ydieresis/Zcaron/dotlessi/lslash/oe/scaron/zcaron %
12307    160/Euro %
12308    164/currency %
12309    166/brokenbar %
12310    168/dieresis/copyright/ordfeminine %
12311    172/logicalnot/.notdef/registered/macron/degree/plusminus%
12312    /twosuperior/threesuperior/acute/mu %
12313    183/periodcentered/cedilla/onesuperior/ordmasculine %
12314    188/onequarter/onehalf/threequarters %
12315    192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
12316    /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave%
12317    /Iacute/Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute%
12318    /Ocircumflex/Otilde/Odieresis/multiply/Oslash/Ugrave%
12319    /Uacute/Ucircumflex/Udieresis/Yacute/Thorn/germandbls%
12320    /grave/aacute/acircumflex/tilde/adieresis/aring/ae%
12321    /ccedilla/egrave/eacute/ecircumflex/edieresis/igrave%
12322    /iacute/icircumflex/idieresis/eth/ntilde/ograve/oacute%
12323    /ocircumflex/otilde/odieresis/divide/oslash/ugrave/uacute%
12324    /ucircumflex/udieresis/yacute/thorn/ydieresis%
12325    ]%
12326    >>%
12327 /PUT pdfmark%
12328 [%]
12329  /_objdef{ZaDb}%
12330  /type/dict%
12331 /OBJ pdfmark%
12332 [%]
12333  {ZaDb}%
12334  <<%
12335  /Type/Font%
12336  /Subtype/Type1%
12337  /Name/ZaDb%
12338  /BaseFont/ZapfDingbats%
12339  >>%
12340 /PUT pdfmark%
12341 [%]
12342  /_objdef{Helv}%
12343  /type/dict%
12344 /OBJ pdfmark%
12345 [%]
12346  {Helv}%
12347  <<%
12348  /Type/Font%
12349  /Subtype/Type1%
12350  /Name/Helv%
12351  /BaseFont/Helvetica%
12352  /Encoding{pdfDocEncoding}%
12353  >>%
12354 /PUT pdfmark%

```

```
12355 [%  
12356 /_objdef{aform}%">  
12357 /type/dict%  
12358 /OBJ pdfmark%  
12359 [%  
12360 /_objdef{afields}%">  
12361 /type/array%  
12362 /OBJ pdfmark%  
12363 [%  
12364 /_objdef{corder}%">  
12365 /type/array%  
12366 /OBJ pdfmark%  
12367 {  
12368 [%  
12369 /BBox[0 0 100 100]%">  
12370 /_objdef{Check}%">  
12371 /BP pdfmark %  
12372 1 0 0 setrgbcolor%  
12373 /ZapfDingbats 80 selectfont %  
12374 20 20 moveto%  
12375 (4)show%  
12376 [/EP pdfmark%  
12377 [%  
12378 /BBox[0 0 100 100]%">  
12379 /_objdef{Cross}%">  
12380 /BP pdfmark %  
12381 1 0 0 setrgbcolor%  
12382 /ZapfDingbats 80 selectfont %  
12383 20 20 moveto%  
12384 (8)show%  
12385 [/EP pdfmark%  
12386 [%  
12387 /BBox[0 0 250 100]%">  
12388 /_objdef{Submit}%">  
12389 /BP pdfmark %  
12390 0.6 setgray %  
12391 0 0 250 100 rectfill %  
12392 1 setgray %  
12393 2 2 moveto %  
12394 2 98 lineto %  
12395 248 98 lineto %  
12396 246 96 lineto %  
12397 4 96 lineto %  
12398 4 4 lineto %  
12399 fill %  
12400 0.34 setgray %  
12401 248 98 moveto %  
12402 248 2 lineto %  
12403 2 2 lineto %  
12404 4 4 lineto %  
12405 246 4 lineto %  
12406 246 96 lineto %  
12407 fill%  
12408 /Helvetica 76 selectfont %
```

```

12409 0 setgray %
12410 8 22.5 moveto%
12411 (Submit)show%
12412 [/EP pdfmark%
12413 [%]
12414 /BBox[0 0 250 100]%
12415 /_objdef{SubmitP}%
12416 /BP pdfmark %
12417 0.6 setgray %
12418 0 0 250 100 rectfill %
12419 0.34 setgray %
12420 2 2 moveto %
12421 2 98 lineto %
12422 248 98 lineto %
12423 246 96 lineto %
12424 4 96 lineto %
12425 4 4 lineto %
12426 fill %
12427 1 setgray %
12428 248 98 moveto %
12429 248 2 lineto %
12430 2 2 lineto %
12431 4 4 lineto %
12432 246 4 lineto %
12433 246 96 lineto %
12434 fill%
12435 /Helvetica 76 selectfont %
12436 0 setgray %
12437 10 20.5 moveto%
12438 (Submit)show%
12439 [/EP pdfmark%
12440 } ?pdfmark%
12441 [%]
12442 {aform}%
12443 <<%
12444 /Fields{afields}%
12445 /DR<<%
12446 /Font<<%
12447 /ZaDb{ZaDb}%
12448 /Helv{Helv}%
12449 >>%
12450 >>%
12451 /DA(/Helv 10 Tf 0 g)%
12452 /CO{corder}%
12453 \ifHy@pdfa
12454 \else
12455 \ifHyField@NeedAppearances
12456 /NeedAppearances true%
12457 \fi
12458 \fi
12459 >>%
12460 /PUT pdfmark%
12461 [%]
12462 {Catalog}%

```

```

12463  <<%
12464  /AcroForm{aform}%
12465  >>%
12466 /PUT pdfmark%
12467 }}%
12468 \kvsetkeys{Form}{#1}%
12469 }
12470 \let\@endForm\ltx@empty
12471 \def\@Gauge[#1]#2#3#4{%
  parameters, label, minimum, maximum
12472 \Hy@Message{Sorry, pdfmark drivers do not support FORM gauges}%
12473 }

12474 \newcount\HyField@AnnotCount
12475 \HyField@AnnotCount=\z@
12476 \def\HyField@AdvanceAnnotCount{%
12477 \global\advance\HyField@AnnotCount\@ne
12478 }
12479 \def\HyField@TheAnnotCount{%
12480 \the\HyField@AnnotCount
12481 }

12482 \edef\Fld@pageobjref{/P\string{ThisPage}\string{}}
12483 \def\HyField@AddToFields#1{%
12484 \pdfmark{%
12485 pdfmark=/APPEND,%
12486 Raw={%
12487 \string{afields}\string{}%
12488 \string{#1\HyField@TheAnnotCount}\string{}%
12489 }%
12490 }%
12491 \ifx\Fld@calculate@code\ltx@empty
12492 \else
12493 \pdfmark{%
12494 pdfmark=/APPEND,%
12495 Raw={%
12496 \string{corder}\string{}%
12497 \string{#1\HyField@TheAnnotCount}\string{}%
12498 }%
12499 }%
12500 \fi
12501 }

12502 \def\@TextField[#1]#2{%
  parameters, label
12503 \def\Fld@name{#2}%
12504 \let\Fld@default\ltx@empty
12505 \let\Fld@value\@empty
12506 \def\Fld@width{\DefaultWidthofText}%
12507 \def\Fld@height{%
12508 \ifFld@multiline
12509 \DefaultHeightofTextMultiline
12510 \else
12511 \DefaultHeightofText
12512 \fi
12513 }%
12514 \begingroup
12515 \expandafter\HyField@SetKeys\expandafter{%

```

```

12516     \DefaultOptionsofText,#1%
12517 }%
12518 \HyField@FlagsText
12519 \ifFld@hidden\def\Fld@width{1sp}\fi
12520 \ifx\Fld@value\@empty\def\Fld@value{\Fld@default}\fi
12521 \HyField@AdvanceAnnotCount
12522 \LayoutTextField{#2}{%
12523     \leavevmode
12524     \Hy@escapeform\PDFForm@Text
12525     \pdfmark[\MakeTextField{\Fld@width}{\Fld@height}]{%
12526         pdfmark=/ANN,%
12527         objdef=text\HyField@TheAnnotCount,%
12528         Raw={\PDFForm@Text}%
12529     }%
12530 }%
12531 \HyField@AddToFields{text}%
12532 \endgroup
12533 }
12534 \def\@ChoiceMenu[#1]#2#3{%
parameters, label, choices
12535 \def\Fld@name{#2}%
12536 \let\Fld@default\relax
12537 \let\Fld@value\relax
12538 \def\Fld@width{\DefaultWidthofChoiceMenu}%
12539 \def\Fld@height{\DefaultHeightofChoiceMenu}%
12540 \begingroup
12541 \Fld@menulength=0 %
12542 \tempdima\z@
12543 \for\curropt:=#3\do{%
12544     \expandafter\Fld@checkkequals\curropt==\%
12545     \Hy@StepCount\Fld@menulength
12546     \settowidth{\tempdimb}{\currDisplay}%
12547     \ifdim\tempdimb>\tempdima\tempdima\tempdimb\fi
12548 }%
12549 \advance\tempdima by 15\p@
12550 \begingroup
12551 \HyField@SetKeys{#1}%
12552 \edef\x{\endgroup
12553 \noexpand\expandafter
12554 \noexpand\HyField@SetKeys
12555 \noexpand\expandafter{%
12556     \expandafter\noexpand\csname DefaultOptionsof%
12557     \ifFld@radio
12558         Radio%
12559     \else
12560         \ifFld@combo
12561             \ifFld@popdown
12562                 PopdownBox%
12563             \else
12564                 ComboBox%
12565             \fi
12566             \else
12567                 ListBox%
12568             \fi
12569     \fi

```

```

12570      \endcsname
12571  }
12572  }\x
12573  \HyField@SetKeys{\#1}%
12574  \ifFld@hidden\def\Fld@width{1sp}\fi
12575  \ifx\Fld@value\relax
12576  \let\Fld@value\Fld@default
12577  \fi
12578  \LayoutChoiceField{\#2}{%
12579  \ifFld@radio
12580  \HyField@FlagsRadioButton
12581  \@@Radio{\#3}%
12582  \else
12583  \begingroup
12584  \HyField@FlagsChoice
12585  \ifdim\Fld@width<@\tempdima
12586  \ifdim@\tempdima<1cm@\tempdima1cm\fi
12587  \edef\Fld@width{\the@\tempdima}%
12588  \fi
12589  \ifFld@combo
12590  \else
12591  \tempdima=\the\Fld@menulength\Fld@charsize
12592  \advance@\tempdima by \Fld@borderwidth bp %
12593  \advance@\tempdima by \Fld@borderwidth bp %
12594  \edef\Fld@height{\the@\tempdima}%
12595  \fi
12596  \@@Listbox{\#3}%
12597  \endgroup
12598  \fi
12599  }%
12600 \endgroup
12601 }
12602 \def\@@Radio#1{%
12603 \Fld@listcount=0 %
12604 \EdefEscapeName\Fld@default{\Fld@default}%
12605 \for\curropt:=#1\do{%
12606 \expandafter\Fld@checkequals\curropt==\\%
12607 \EdefEscapeName\currValue{\currValue}%
12608 \Hy@StepCount\Fld@listcount
12609 \currDisplay\space
12610 \Hy@escapeform\PDFForm@Radio
12611 \ifnum\Fld@listcount=1 %
12612 \HyField@AdvanceAnnotCount
12613 \fi
12614 \pdfmark[\MakeRadioField{\Fld@width}{\Fld@height}]{%
12615 pdfmark=/ANN,%
12616 objdef=\ifnum\Fld@listcount=1 radio\HyField@TheAnnotCount\fi,%
12617 Raw={%
12618 \PDFForm@Radio /AP <</N <</\currValue\space {Check}>>>>%
12619 }%
12620 } % deliberate space between radio buttons
12621 \ifnum\Fld@listcount=1 %
12622 \HyField@AddToFields{radio}%
12623 \fi

```

```

12624  }%
12625 }
12626 \newcount\Fld@listcount
12627 \def\@@Listbox#1{%
12628   \HyField@PDFChoices{#1}%
12629   \Hy@escapeform\PDFForm@List
12630   \HyField@AdvanceAnnotCount
12631   \pdfmark[\MakeChoiceField{\Fld@width}{\Fld@height}]{%
12632     pdfmark=/ANN,%
12633     objdef=list\HyField@TheAnnotCount,%
12634     Raw={\PDFForm@List}%
12635   }%
12636   \HyField@AddToFields{list}%
12637 }
12638 \def\@PushButton[#1]#2{%
parameters, label
12639   \def\Fld@name{#2}%
12640   \begingroup
12641     \expandafter\HyField@SetKeys\expandafter{%
12642       \DefaultOptionsofPushButton,#1%
12643     }%
12644   \ifHy@pdfa
12645     \Hy@Error{%
12646       PDF/A: Push button with JavaScript is prohibited%
12647     }%
12648     \LayoutPushButtonField{%
12649       \leavevmode
12650       \MakeButtonField{#2}%
12651     }%
12652   \else
12653     \HyField@FlagsPushButton
12654     \ifFld@hidden\def\Fld@width{1sp}\fi
12655     \HyField@AdvanceAnnotCount
12656     \LayoutPushButtonField{%
12657       \leavevmode
12658       \Hy@escapeform\PDFForm@Push
12659       \pdfmark[\MakeButtonField{#2}]{%
12660         pdfmark=/ANN,%
12661         objdef=push\HyField@TheAnnotCount,%
12662         Raw={\PDFForm@Push}%
12663       }%
12664     }%
12665     \HyField@AddToFields{push}%
12666   \fi
12667   \endgroup
12668 }
12669 \def\@Submit[#1]#2{%
12670   \def\Fld@width{\DefaultWidthofSubmit}%
12671   \def\Fld@height{\DefaultHeightofSubmit}%
12672   \begingroup
12673     \expandafter\HyField@SetKeys\expandafter{%
12674       \DefaultOptionsofSubmit,#1%
12675     }%
12676     \HyField@FlagsPushButton
12677     \HyField@FlagsSubmit

```

```

12678 \ifFld@hidden\def\Fld@width{1sp}\fi
12679 \Hy@escapeform\PDFForm@Submit
12680 \HyField@AdvanceAnnotCount
12681 \pdfmark[\MakeButtonField{\#2}]{%
12682 pdfmark=/ANN,%
12683 objdef=submit\HyField@TheAnnotCount,%
12684 Raw={\PDFForm@Submit /AP<</N{Submit}/D{SubmitP}>>}%
12685 }%
12686 \HyField@AddToFields{submit}%
12687 \endgroup
12688 }
12689 \def\@Reset[#1]{%
12690 \def\Fld@width{\DefaultWidthofReset}%
12691 \def\Fld@height{\DefaultHeightofReset}%
12692 \begingroup
12693 \expandafter\HyField@SetKeys\expandafter{%
12694 \DefaultOptionsofReset,#1}%
12695 }%
12696 \leavevmode
12697 \ifHy@pdfa
12698 \Hy@Error{%
12699 PDF/A: Reset action is prohibited%
12700 }\@ehc
12701 \MakeButtonField{\#2}%
12702 \else
12703 \HyField@FlagsPushButton
12704 \ifFld@hidden\def\Fld@width{1sp}\fi
12705 \Hy@escapeform\PDFForm@Reset
12706 \HyField@AdvanceAnnotCount
12707 \pdfmark[\MakeButtonField{\#2}]{%
12708 pdfmark=/ANN,%
12709 objdef=reset\HyField@TheAnnotCount,%
12710 Raw={\PDFForm@Reset}%
12711 }%
12712 \HyField@AddToFields{reset}%
12713 \fi
12714 \endgroup
12715 }%
12716 \def\@CheckBox[#1]{% parameters, label
12717 \def\Fld@name{\#2}%
12718 \def\Fld@default{0}%
12719 \begingroup
12720 \def\Fld@width{\DefaultWidthofCheckBox}%
12721 \def\Fld@height{\DefaultHeightofCheckBox}%
12722 \expandafter\HyField@SetKeys\expandafter{%
12723 \DefaultOptionsofCheckBox,#1}%
12724 }%
12725 \HyField@FlagsCheckBox
12726 \ifFld@hidden\def\Fld@width{1sp}\fi
12727 \HyField@AdvanceAnnotCount
12728 \LayoutCheckField{\#2}{%
12729 \leavevmode
12730 \Hy@escapeform\PDFForm@Check
12731 \pdfmark[\MakeCheckField{\Fld@width}{\Fld@height}]{%

```

```

12732     pdfmark=/ANN,%
12733     objdef=check\HyField@TheAnnotCount,%
12734     Raw={\PDFForm@Check}%
12735   }%
12736 }%
12737 \HyField@AddToFields{check}%
12738 \endgroup
12739 }
12740 
```

44.2 HyperTeX

```

12741 <*hypertex>
12742 \def\@Form[#1]{%
12743   \Hy@Message{Sorry, HyperTeX does not support FORMs}%
12744 }
12745 \let\@endForm\ltx@empty
12746 \def\@Gauge[#1]#2#3#4{%
12747   parameters, label, minimum, maximum
12748   \Hy@Message{Sorry, HyperTeX does not support FORM gauges}%
12749 }
12750 \def\@TextField[#1]#2{%
12751   parameters, label
12752   \Hy@Message{Sorry, HyperTeX does not support FORM text fields}%
12753 }
12754 \def\@CheckBox[#1]#2{%
12755   parameters, label
12756   \Hy@Message{Sorry, HyperTeX does not support FORM checkboxes}%
12757 }
12758 \def\@ChoiceMenu[#1]#2#3{%
12759   parameters, label, choices
12760   \Hy@Message{Sorry, HyperTeX does not support FORM choice menus}%
12761 }
12762 \def\@PushButton[#1]#2{%
12763   parameters, label
12764   \Hy@Message{Sorry, HyperTeX does not support FORM pushbuttons}%
12765 }
12766 \def\@Reset[#1]#2{%
12767   \Hy@Message{Sorry, HyperTeX does not support FORMs}%
12768 }
12769 \def\@Submit[#1]#2{%
12770   \Hy@Message{Sorry, HyperTeX does not support FORMs}%
12771 }
12772 }
12773 \def\@endForm{\HCode{</form>}}
12774 \def\@Gauge[#1]#2#3#4{%
12775   parameters, label, minimum, maximum
12776   \Hy@Message{Sorry, HyperTeX does not support gauges}%
12777 }
12778 \def\@TextField[#1]#2{%
12779   let\Hy@reserved@a\empty
12780   def\Fl@name{#2}%
12781   let\Fl@default\ltx@empty
12782 }
```

44.3 TeX4ht

```

12768 <*tex4ht>
12769 \def\@Form[#1]{%
12770   \kvsetkeys{Form}{#1}%
12771   \HCode{<form action="\Form@action" method="\Form@method">}%
12772 }
12773 \def\@endForm{\HCode{</form>}}
12774 \def\@Gauge[#1]#2#3#4{%
12775   parameters, label, minimum, maximum
12776   \Hy@Message{Sorry, TeX4ht does not support gauges}%
12777 }
12778 \def\@TextField[#1]#2{%
12779   let\Hy@reserved@a\empty
12780   def\Fl@name{#2}%
12781   let\Fl@default\ltx@empty
12782 }
```

```

12781 \bgroup
12782   \Field@toks={ }%
12783   \kvsetkeys{Field}{#1}%
12784   \HCode{<label for="\Fld@name">#2</label>}%
12785   \ifFld@password
12786     \@@PasswordField
12787   \else
12788     \@@TextField
12789   \fi
12790 \egroup
12791 }
12792 \def\@@PasswordField{%
12793   \HCode{%
12794     <input type="password" %
12795     id="\Fld@name" %
12796     name="\Fld@name" %
12797     \ifFld@hidden type="hidden" \fi
12798     value="\Fld@default" %
12799     \the\Field@toks
12800   }%
12801 }%
12802 }
12803 \def\@@TextField{%
12804   \ifFld@multiline
12805     \HCode{<textarea %
12806       \ifFld@readonly readonly \fi
12807       id="\Fld@name" %
12808       name="\Fld@name" %
12809       \ifFld@hidden type="hidden" \fi
12810       \the\Field@toks>%
12811   }%
12812   \Fld@default
12813   \HCode{</textarea>}%
12814 \else
12815   \HCode{<input type="textbox" %
12816     \ifFld@readonly readonly \fi
12817     id="\Fld@name" %
12818     name="\Fld@name" %
12819     \ifFld@hidden type="hidden" \fi
12820     value="\Fld@default" %
12821     \the\Field@toks>%
12822   }%
12823 \fi
12824 }
12825 \def\@ChoiceMenu[#1]#2#3{%
parameters, label, choices
12826 \def\Fld@name{#2}%
12827 \let\Fld@default\ltx@empty
12828 \let\Hy@reserved@a\relax
12829 \begingroup
12830   \expandafter\Fld@findlength#3\\%
12831   \Field@toks={ }%
12832   \kvsetkeys{Field}{#1}%
12833   #2%
12834   \ifFld@radio

```

```

12835     \expandafter\@@Radio#3\\%
12836   \else
12837     \expandafter\@@Menu#3\\%
12838   \fi
12839 \endgroup
12840 }
12841 \def\Fld@findlength#1\\{%
12842   \Fld@menulength=0 %
12843   \for\curropt:=#1\do{\Hy@StepCount\Fld@menulength}%
12844 }
12845 \def\@@Menu#1\\{%
12846   \HCode{<select size="\the\Fld@menulength" %
12847     name="\Fld@name" %
12848     \the\Field@toks>%
12849 }%
12850   \for\curropt:=#1\do{%
12851     \expandafter\Fld@checkequals\curropt==\\%
12852     \HCode{<option %
12853       \ifx\curropt\Fld@default selected \fi
12854       value="@currValue">\currDisplay</option>%
12855     }%
12856   }%
12857   \HCode{</select>}%
12858 }
12859 \def\@@Radio#1\\{%
12860   \for\curropt:=#1\do{%
12861     \expandafter\fld@checkequals\curropt==\\%
12862     \HCode{<input type="radio" %
12863       \ifx\curropt\Fld@default checked \fi
12864       name="\Fld@name" %
12865       value="@currValue" %
12866       \the\Field@toks>%
12867     }%
12868     \currDisplay
12869   }%
12870 }
12871 \def\@PushButton[#1]#2{%
  parameters, label
12872   \def\Fld@name{#2}%
12873   \bgroup
12874     \Field@toks={ }%
12875     \kvsetkeys{Field}{#1}%
12876     \HCode{<input type="button" %
12877       name="\Fld@name" %
12878       value="#2" %
12879       \the\Field@toks>%
12880     }%
12881     \HCode{</button>}%
12882   \egroup
12883 }
12884 \def\@Submit[#1]#2{%
12885   \HCode{<button type="submit">#2</button>}%
12886 }
12887 \def\@Reset[#1]#2{%
12888   \HCode{<button type="reset">#2</button>}%

```

```

12889 }
12890 \def\@CheckBox[#1]{% parameters, label
12891   \let\Hy@reserved@a\empty
12892   \def\Fl@name{#2}%
12893   \def\Fl@default{0}%
12894   \bgroup
12895     \Field@toks={ }%
12896     \kvsetkeys[Field]{#1}%
12897     \HCode{<input type="checkbox" %
12898       \ifFl@checked checked \fi
12899       \ifFl@disabled disabled \fi
12900       \ifFl@readonly readonly \fi
12901       name="\Fl@name" %
12902       \ifFl@hidden type="hidden" \fi
12903       value="\Fl@default" %
12904       \the\Field@toks>}%
12905     #2%
12906   }%
12907   \egroup
12908 }
12909 </tex4ht>

```

44.4 pdfTeX

```

12910 <*pdftex>
12911 \def\@Gauge[#1]{% parameters, label, minimum, maximum
12912   \Hy@Message{Sorry, pdftex does not support FORM gauges}%
12913 }
12914 \def\MakeFieldObject#1{%
12915   \immediate\pdfxform 0 %
12916   \expandafter\edef\csname #2\endcsname{%
12917     \the\pdflastxform\space 0 R%
12918   }%
12919 % \hbox to 0pt{\hskip-\maxdimen\pdfrefxform \the\pdflastxform}%
12920 }%
12921 \let\HyField@afields\ltx@empty
12922 \let\HyField@cofields\ltx@empty
12923 \@ifundefined{pdflastlink}%
12924 {%
12925   \let\HyField@AddToFields\relax
12926   \PackageInfo{hyperref}{%
12927     You need pdfTeX 1.40.0 for setting the /Fields entry.%
12928     \MessageBreak
12929     Adobe Reader/Acrobat accepts an empty /Field array,%
12930     \MessageBreak
12931     but other PDF viewers might complain%
12932   }%
12933 }%
12934 \let\HyField@AuxAddToFields\ltx@gobble
12935 \let\HyField@AuxAddToCoFields\ltx@gobbletwo
12936 \def\HyField@AfterAuxOpen{\Hy@AtBeginDocument}%

```

Insertion sort for calculation field list. In case of equal sort keys (for example, if ‘calculatesortkey’ is not used at all) the keys keep document calling order.

```
12937 \def\HyField@ABD@AuxAddToCoFields#1#2{%
```

```

12938 \begingroup
12939   \Hy@safe@activestru
12940   \let\ltx@secondoftwo\relax
12941   \ifx\HyField@cofields\ltx@empty
12942     \xdef\HyField@cofields{%
12943       \ltx@secondoftwo{\#1}{\#2 0 R}%
12944     }%
12945   \else
12946     \let\ltx@secondoftwo\relax
12947     \def\HyField@AddCoField##1##2##3{%
12948       \ifx##1\ltx@empty
12949         \ltx@secondoftwo{\#1}{\#2 0 R}%
12950       \expandafter\ltx@gobble
12951     \else
12952       \ifnum\pdfstrcmp{##2}{##1}>0\ltx@zero
12953         \ltx@secondoftwo{\#1}{\#2 0 R}%
12954         \ltx@secondoftwo{##2}{##3}%
12955         \expandafter\expandafter\expandafter\ltx@gobble
12956       \else
12957         \ltx@secondoftwo{##2}{##3}%
12958       \fi
12959     \fi
12960     \HyField@AddCoField
12961   }%
12962   \xdef\HyField@cofields{%
12963     \expandafter\HyField@AddCoField
12964     \HyField@cofields\ltx@empty\ltx@empty\ltx@empty
12965   }%
12966   \fi
12967 \endgroup
12968 }%
12969 \Hy@AtBeginDocument{%
12970   \if@filesw
12971     \immediate\write\@mainaux{%
12972       \string\providetcommand\string\HyField@AuxAddToFields[1]{}}%
12973     }%
12974     \immediate\write\@mainaux{%
12975       \string\providetcommand\string\HyField@AuxAddToCoFields[2]{}}%
12976     }%
12977   \fi
12978 \let\HyField@AfterAuxOpen\@firstofone
12979 \def\HyField@AuxAddToFields#1{%
12980   \xdef\HyField@afIELDS{%
12981     \ifx\HyField@afIELDS\empty
12982       \else
12983         \HyField@afIELDS
12984       \space
12985     \fi
12986     \#1 0 R%
12987   }%
12988 }%
12989 \let\HyField@AuxAddToCoFields\HyField@ABD@AuxAddToCoFields
12990 }%
12991 \def\HyField@AddToFields{%

```

```

12992 \expandafter\HyField@@AddToFields\expandafter{%
12993   \the\pdflastlink
12994 }%
12995 \ifx\Fld@calculate@code\ltx@empty
12996 \else
12997   \begingroup
12998     \Hy@safe@activestru
12999     \edef\Hy@temp{%
13000       \endgroup
13001       \if@filesw
13002         \write\@mainaux{%
13003           \string\HyField@AuxAddToCoFields{%
13004             \Fld@calculate@sortkey
13005           }%
13006           \the\pdflastlink
13007         }%
13008       }%
13009       \fi
13010     }%
13011     \Hy@temp
13012   \fi
13013 }%
13014 \def\HyField@@AddToFields#1{%
13015   \HyField@AfterAuxOpen{%
13016     \if@filesw
13017       \write\@mainaux{%
13018         \string\HyField@AuxAddToFields{#1}%
13019       }%
13020     \fi
13021   }%
13022 }%
13023 }
13024 \def\@Form[#1]{%
13025   \@ifundefined{textcolor}{\let\textcolor@gobble}{}
13026   \kvsetkeys[Form]{#1}%
13027   \pdf@ifdraftmode{}{%
13028     \Hy@FormObjects
13029     \ifnum\pdftexversion>13 %
13030       \pdffrefobj\OBJ@pdfdocencoding
13031       \pdffrefobj\OBJ@ZaDb
13032       \pdffrefobj\OBJ@Helv
13033     \fi
13034     \AtVeryEndDocument{%
13035       \immediate\pdfobj{%
13036         <<%
13037         /Fields[\HyField@afIELDS]%
13038         \ifx\HyField@coFIELDS\ltx@empty
13039         \else
13040           /CO[\romannumeral-\`Q\HyField@coFIELDS]%
13041         \fi
13042         /DR<<%
13043         /Font<<%
13044           /ZaDb \OBJ@ZaDb\space 0 R%
13045           /Helv \OBJ@Helv\space 0 R%

```

```

13046      >>%
13047      >>%
13048      /DA(/Helv 10 Tf 0 g)%
13049      \ifHy@pdflatex
13050      \else
13051          \ifHyField@NeedAppearances
13052              /NeedAppearances true%
13053          \fi
13054          \fi
13055      >>%
13056  }%
13057  \edef\OBJ@acroform{\the\pdflastobj}%
13058  \pdfcatalog{/AcroForm \OBJ@acroform\space 0 R}%
13059 }%
13060 }%
13061 \MakeFieldObject{%
Same as \ding{123} of package pifont.
13062 \begingroup
13063   \fontfamily{pzd}%
13064   \fontencoding{U}%
13065   \fontseries{m}%
13066   \fontshape{n}%
13067   \selectfont
13068   \char123 %
13069 \endgroup
13070 \{Ding\}%
13071 \MakeFieldObject{%
13072   \fbox{\textcolor{yellow}{\textsf{Submit}}}}%
13073 \{Submit\}%
13074 \MakeFieldObject{%
13075   \fbox{\textcolor{yellow}{\textsf{SubmitP}}}}%
13076 \{SubmitP\}%
13077 }
13078 \let\@endForm\ltx@empty
13079 \let\HyAnn@AbsPageLabel\ltx@empty
13080 \let\Fl@r@pageobjref\ltx@empty
13081 \ltx@ifundefined{pdfpageref}{%
13082 }{%
13083 \ltx@ifpackageloaded{zref-abspage}{%
13084   \newcount\HyAnn@Count
13085   \HyAnn@Count=\ltx@zero
13086   \def\HyAnn@AbsPageLabel{%
13087     \global\advance\HyAnn@Count by\ltx@one
13088     \zref@labelbyprops{\HyAnn@\the\HyAnn@Count}{abspage}%
13089     \zref@refused{\HyAnn@\the\HyAnn@Count}%
13090   }%
13091   \def\Fl@r@pageobjref{%
13092     \zref@ifrefundefined{\HyAnn@\the\HyAnn@Count}{%
13093       \zref@ifrefcontainsprop{\HyAnn@\the\HyAnn@Count}{abspage}{%
13094         /P \pdfpageref
13095         \zref@extractdefault{\HyAnn@\the\HyAnn@Count}{abspage}{1} %
13096         \space 0 R%
13097       }%
13098     }%

```

```

13099      }%
13100      }%
13101      }%
13102  }{%
13103  }%
13104 }

13105 \def\@TextField[#1]{% parameters, label
13106   \def\Fld@name{#2}%
13107   \let\Fld@default\ltx@empty
13108   \let\Fld@value\empty
13109   \def\Fld@width{\DefaultWidthofText}%
13110   \def\Fld@height{%
13111     \ifFld@multiline
13112       \DefaultHeightofTextMultiline
13113     \else
13114       \DefaultHeightofText
13115     \fi
13116   }%
13117   \begingroup
13118   \expandafter\HyField@SetKeys\expandafter{%
13119     \DefaultOptionsofText,#1}%
13120   }%
13121   \PDFForm@Name
13122   \HyField@FlagsText
13123   \ifFld@hidden\def\Fld@width{1sp}\fi
13124   \ifx\Fld@value\empty\def\Fld@value{\Fld@default}\fi
13125   \LayoutTextField{#2}{%
13126     \leavevmode
13127     \HyAnn@AbsPageLabel
13128     \Hy@escapeform\PDFForm@Text
13129     \pdfstartlink user {\PDFForm@Text}\relax
13130     \MakeTextField{\Fld@width}{\Fld@height}\pdfendlink
13131     \HyField@AddToFields
13132   }%
13133   \endgroup
13134 }

13135 \def\@ChoiceMenu[#1]{% parameters, label, choices
13136   \def\Fld@name{#2}%
13137   \let\Fld@default\relax
13138   \let\Fld@value\relax
13139   \def\Fld@width{\DefaultWidthofChoiceMenu}%
13140   \def\Fld@height{\DefaultHeightofChoiceMenu}%
13141   \begingroup
13142   \Fld@menulength=0 %
13143   \tempdima\z@
13144   \@for\curropt:=#3\do{%
13145     \expandafter\Fld@checkequals\curropt==\%
13146     \Hy@StepCount\Fld@menulength
13147     \settowidth{\tempdimb}{\currDisplay}%
13148     \ifdim\tempdimb>\tempdima\tempdima\tempdimb\fi
13149   }%
13150   \advance\tempdima by 15\p@
13151   \begingroup
13152     \HyField@SetKeys{#1}%

```

```

13153 \edef\x{\endgroup
13154   \noexpand\expandafter
13155   \noexpand\HyField@SetKeys
13156   \noexpand\expandafter{%
13157     \expandafter\noexpand\csname DefaultOptionsof%
13158       \ifFld@radio
13159         Radio%
13160       \else
13161         \ifFld@combo
13162           \ifFld@popdown
13163             PopdownBox%
13164           \else
13165             ComboBox%
13166           \fi
13167         \else
13168           ListBox%
13169         \fi
13170       \fi
13171     \endcsname
13172   }%
13173 }\x
13174 \HyField@SetKeys{#1}%
13175 \PDFForm@Name
13176 \ifFld@hidden\def\Fld@width{1sp}\fi
13177 \ifx\Fld@value\relax
13178   \let\Fld@value\Fld@default
13179 \fi
13180 \LayoutChoiceField{#2}{%
13181   \ifFld@radio
13182     \HyField@FlagsRadioButton
13183     \@@Radio{#3}%
13184   \else
13185     \begingroup
13186       \HyField@FlagsChoice
13187       \ifdim\Fld@width<@\tempdima
13188         \ifdim@\tempdima<1cm@\tempdima1cm\fi
13189         \edef\Fld@width{\the@\tempdima}%
13190       \fi
13191     \ifFld@combo
13192     \else
13193       \tempdima=\the\Fld@menulength\Fld@charsize
13194       \advance\tempdima by \Fld@borderwidth bp %
13195       \advance\tempdima by \Fld@borderwidth bp %
13196       \edef\Fld@height{\the\tempdima}%
13197     \fi
13198     \@@Listbox{#3}%
13199   \endgroup
13200 \fi
13201 }%
13202 \endgroup
13203 }
13204 \def\@@Radio#1{%
13205   \Fld@listcount=0 %
13206   \EdefEscapeName\Fld@default{\Fld@default}%

```

```

13207  \@for\@curropt:=#1\do{%
13208    \expandafter\Fld@checkequals\@curropt==\\%
13209    \EdefEscapeName\@currValue{\@currValue}%
13210    \Hy@StepCount\Fld@listcount
13211    \@currDisplay\space
13212    \leavevmode
13213    \HyAnn@AbsPageLabel
13214    \Hy@escapeform\PDFForm@Radio
13215    \pdfstartlink user {%
13216      \PDFForm@Radio
13217      /AP<<%
13218      /N<<%

```

Laurent.Guilope@math.univ-nantes.fr (Laurent Guilope) persuades me that this was wrong: `\Fld@name\the\Fld@listcount`. But I leave it here to remind me that it is untested.

```

13219      /\@currValue\space \DingObject
13220      >>%
13221      >>%
13222    }%
13223    \relax
13224    \MakeRadioField{\Fld@width}{\Fld@height}\pdfendlink
13225    \ifnum\Fld@listcount=1 %
13226      \HyField@AddToFields
13227    \fi
13228    \space % deliberate space between radio buttons
13229  }%
13230 }
13231 \newcount\Fld@listcount
13232 \def\@Listbox#1{%
13233   \HyField@PDFChoices{#1}%
13234   \leavevmode
13235   \HyAnn@AbsPageLabel
13236   \Hy@escapeform\PDFForm@List
13237   \pdfstartlink user {\PDFForm@List}\relax
13238   \MakeChoiceField{\Fld@width}{\Fld@height}%
13239   \pdfendlink
13240   \HyField@AddToFields
13241 }
13242 \def\@PushButton[#1]#2{%
  parameters, label
13243   \def\Fld@name{#2}%
13244   \begingroup
13245     \expandafter\HyField@SetKeys\expandafter{%
13246       \DefaultOptionsofPushButton,#1%
13247     }%
13248     \PDFForm@Name
13249     \ifHy@pdfa
13250       \Hy@Error{%
13251         PDF/A: Push button with JavaScript is prohibited%
13252       }@\ehc
13253       \LayoutPushButtonField{%
13254         \leavevmode
13255         \MakeButtonField{#2}%
13256       }%

```

```

13257 \else
13258   \HyField@FlagsPushButton
13259   \ifFld@hidden\def\fld@width{1sp}\fi
13260   \LayoutPushButtonField{%
13261     \leavevmode
13262     \HyAnn@AbsPageLabel
13263     \Hy@escapeform\PDFForm@Push
13264     \pdfstartlink user {\PDFForm@Push}\relax
13265     \MakeButtonField{#2}%
13266     \pdfendlink
13267     \HyField@AddToFields
13268   }%
13269 \fi
13270 \endgroup
13271 }
13272 \def@\Submit[#1]{%
13273   \def\fld@width{\DefaultWidthofSubmit}%
13274   \def\fld@height{\DefaultHeightofSubmit}%
13275   \begingroup
13276     \expandafter\HyField@SetKeys\expandafter{%
13277       \DefaultOptionsofSubmit,#1}%
13278   }%
13279   \HyField@FlagsPushButton
13280   \HyField@FlagsSubmit
13281   \ifFld@hidden\def\fld@width{1sp}\fi
13282   \leavevmode
13283   \HyAnn@AbsPageLabel
13284   \Hy@escapeform\PDFForm@Submit
13285   \pdfstartlink user {%
13286     \PDFForm@Submit
13287     /AP<>/N \SubmitObject/D \SubmitPObject>>%
13288   }%
13289   \relax
13290   \MakeButtonField{#2}%
13291   \pdfendlink
13292   \HyField@AddToFields
13293 \endgroup
13294 }
13295 \def@\Reset[#1]{%
13296   \def\fld@width{\DefaultWidthofReset}%
13297   \def\fld@height{\DefaultHeightofReset}%
13298   \begingroup
13299     \expandafter\HyField@SetKeys\expandafter{%
13300       \DefaultOptionsofReset,#1}%
13301   }%
13302   \leavevmode
13303   \ifHy@pdflatex
13304     \Hy@Error{%
13305       PDF/A: Reset action is prohibited%
13306     }\@ehc
13307     \MakeButtonField{#2}%
13308   \else
13309     \HyField@FlagsPushButton
13310     \ifFld@hidden\def\fld@width{1sp}\fi

```

```

13311   \HyAnn@AbsPageLabel
13312   \Hy@escapeform\PDFForm@Reset
13313   \pdfstartlink user {\PDFForm@Reset}\relax
13314   \MakeButtonField{#2}%
13315   \pdfendlink
13316   \HyField@AddToFields
13317   \fi
13318 \endgroup
13319 }
13320 \def\@CheckBox[#1]{% parameters, label
13321   \def\Fld@name{#2}%
13322   \def\Fld@default{0}%
13323   \begingroup
13324     \def\Fld@width{\DefaultWidthofCheckBox}%
13325     \def\Fld@height{\DefaultHeightofCheckBox}%
13326     \expandafter\HyField@SetKeys\expandafter{%
13327       \DefaultOptionsofCheckBox,#1}%
13328   }%
13329   \PDFForm@Name
13330   \HyField@FlagsCheckBox
13331   \ifFld@hidden\def\Fld@width{1sp}\fi
13332   \LayoutCheckField{#2}{%
13333     \leavevmode
13334     \HyAnn@AbsPageLabel
13335     \Hy@escapeform\PDFForm@Check
13336     \pdfstartlink user {\PDFForm@Check}\relax
13337     \MakeCheckField{\Fld@width}{\Fld@height}%
13338     \pdfendlink
13339     \HyField@AddToFields
13340   }%
13341 \endgroup
13342 }
13343 \def\Hy@FormObjects{%
13344   \pdfobj {%
13345     <<%
13346     /Type/Encoding%
13347     /Differences{%
13348       24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek%
13349       /ring/tilde %
13350       39/quotesingle %
13351       96/grave %
13352       128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
13353       /fraction/guilsinglleft/guilsinglright/minus/perthousand%
13354       /quotedblbase/quotedblleft/quotedblrigh/quotelleft%
13355       /quoteright/quotesinglbase/trademark/fi/fl/Lslash/OE%
13356       /Scaron/Ydieresis/Zcaron/dotlessi/lslash/oe/scaron/zcaron %
13357       160/Euro %
13358       164/currency %
13359       166/brokenbar %
13360       168/dieresis/copyright/ordfeminine %
13361       172/logicalnot/notdef/registered/macron/degree/plusminus%
13362       /twosuperior/threesuperior/acute/mu %
13363       183/periodcentered/cedilla/onesuperior/ordmasculine %
13364       188/onequarter/onehalf/threequarters %

```

```

13365   192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
13366   /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave%
13367   /Iacute/Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute%
13368   /Ocircumflex/Otilde/Odieresis/multiply/Oslash/Ugrave%
13369   /Uacute/Ucircumflex/Udieresis/Yacute/Thorn/germandbls%
13370   /agrave/aacute/acircumflex/tilde/adieresis/aring/ae%
13371   /ccedilla/egrave/eacute/ecircumflex/edieresis/igrave%
13372   /iacute/icircumflex/idieresis/eth/ntilde/ograve/oacute%
13373   /ocircumflex/otilde/odieresis/divide/oslash/ugrave%
13374   /uacute/ucircumflex/udieresis/yacute/thorn/ydieresis%
13375   ]%
13376   >>%
13377 }%
13378 \xdef\OBJ@pdfdocencoding{\the\pdflastobj}%
13379 \pdfobj{%
13380   <<%
13381   /Type/Font%
13382   /Subtype/Type1%
13383   /Name/ZaDb%
13384   /BaseFont/ZapfDingbats%
13385   >>%
13386 }%
13387 \xdef\OBJ@ZaDb{\the\pdflastobj}%
13388 \pdfobj{%
13389   <<%
13390   /Type/Font%
13391   /Subtype/Type1%
13392   /Name/Helv%
13393   /BaseFont/Helvetica%
13394   /Encoding \OBJ@pdfdocencoding\space 0 R%
13395   >>%
13396 }%
13397 \xdef\OBJ@Helv{\the\pdflastobj}%
13398 \global\let\Hy@FormObjects\relax
13399 }
13400 
```

44.5 dvipdfm, xetex

D. P. Story adapted the pdfTeX forms part for dvipdfm, of which version 0.12.7b or higher is required because of a bug.

```
13401 <*dvipdfm | xetex>
```

```
\@Gauge
13402 \def\@Gauge[#1]#2#3#4{%
  parameters, label, minimum, maximum
  \Hy@Message{Sorry, dvipdfm/XeTeX does not support FORM gauges}%
}
13404 }

\@Form
13405 \def\@Form[#1]{%
13406   \@ifundefined{textcolor}{\let\textcolor\@gobble}{}%
13407   \kvsetkeys{Form}{#1}%
13408   \Hy@FormObjects
13409   \pdfmark{obj @afields []}%
}
```

```

13410  \@pdfm@mark{obj @corder []}%
13411  \@pdfm@mark{%
13412    obj @aform <<%
13413      /Fields @afields%
13414      /DR<<%
13415        /Font<<%
13416          /ZaDb @OBJZaDb%
13417          /Helv @OBJHelv%
13418        >>%
13419      >>%
13420      /DA(/Helv 10 Tf 0 g)%
13421      /CO @corder%
13422      \ifHy@pdfa
13423      \else
13424        \ifHyField@NeedAppearances
13425          /NeedAppearances true%
13426        \fi
13427      \fi
13428    >>%
13429  }%
13430  \@pdfm@mark{put @catalog <</AcroForm @aform>>}%
13431 }

\@endForm
13432 \let\@endForm\ltx@empty

\dvipdfm@setdim \dvipdfm@setdim sets dimensions for ann using \pdfm@box.
13433 \def\dvipdfm@setdim{%
13434   height \the\ht\pdfm@box\space
13435   width \the\wd\pdfm@box\space
13436   depth \the\dp\pdfm@box\space
13437 }

\HyField@AnnotCount
13438 \newcount\HyField@AnnotCount
13439 \HyField@AnnotCount=\z@

\HyField@AdvanceAnnotCount
13440 \def\HyField@AdvanceAnnotCount{%
13441   \global\advance\HyField@AnnotCount\@ne
13442 }

\HyField@TheAnnotCount
13443 \def\HyField@TheAnnotCount{%
13444   \the\HyField@AnnotCount
13445 }

\Fld@pageobjref
13446 \def\Fld@pageobjref{/P @thispage}%

\HyField@AddToFields
13447 \def\HyField@AddToFields#1{%
13448   \@pdfm@mark{put @afields @#1\HyField@TheAnnotCount}%

```

```

13449 \ifx\Fld@calculate@code\ltx@empty
13450 \else
13451 \c@pdfm@mark{put @corder @#1\HyField@TheAnnotCount}%
13452 \fi
13453 }

\@TextField
13454 \def\@TextField[#1]{% parameters, label
13455 \def\Fld@name{#2}%
13456 \let\Fld@default\ltx@empty
13457 \let\Fld@value\empty
13458 \def\Fld@width{\DefaultWidthofText}%
13459 \def\Fld@height{%
13460 \ifFld@multiline
13461 \DefaultHeightofTextMultiline
13462 \else
13463 \DefaultHeightofText
13464 \fi
13465 }%
13466 \begingroup
13467 \expandafter\HyField@SetKeys\expandafter{%
13468 \DefaultOptionsofText,#1}%
13469 }%
13470 \PDFForm@Name
13471 \HyField@FlagsText
13472 \ifFld@hidden\def\Fld@width{1sp}\fi
13473 \ifx\Fld@value\empty\def\Fld@value{\Fld@default}\fi
13474 \setbox\pdfm@box=\hbox{%
13475 \MakeTextField{\Fld@width}{\Fld@height}%
13476 }%
13477 \HyField@AdvanceAnnotCount
13478 \LayoutTextField{#2}{%
13479 \leavevmode
13480 \Hy@escapeform\PDFForm@Text
13481 \c@pdfm@mark{%
13482 ann @text\HyField@TheAnnotCount\space
13483 \dvipdfm@setdim << \PDFForm@Text >>}%
13484 }%
13485 }%
13486 \unhbox\pdfm@box
13487 \HyField@AddToFields{text}%
13488 % record in @fields array
13489 \endgroup
13490 }

\@ChoiceMenu
13491 \def\@ChoiceMenu[#1]{% parameters, label, choices
13492 \def\Fld@name{#2}%
13493 \let\Fld@default\relax
13494 \let\Fld@value\relax
13495 \def\Fld@width{\DefaultWidthofChoiceMenu}%
13496 \def\Fld@height{\DefaultHeightofChoiceMenu}%
13497 \begingroup
13498 \Fld@menulength=0 %

```

```

13499  \@tempdima\z@
13500  \for\curropt:=#3\do{%
13501    \expandafter\Fld@checkeqs\curropt==\\%
13502    \Hy@StepCount\Fld@menulength
13503    \settowidth{\@tempdima}{\currDisplay}%
13504    \ifdim\@tempdima>\@tempdima\@tempdima\@tempdima\fi
13505  }%
13506  \advance\@tempdima by 15\p@
13507  \begingroup
13508    \HyField@SetKeys{#1}%
13509  \edef\x{\endgroup
13510    \noexpand\expandafter
13511    \noexpand\HyField@SetKeys
13512    \noexpand\expandafter{%
13513      \expandafter\noexpand\csname DefaultOptions\%
13514        \ifFld@radio
13515          Radio%
13516        \else
13517          \ifFld@combo
13518            \ifFld@popdown
13519              PopdownBox%
13520            \else
13521              ComboBox%
13522            \fi
13523            \else
13524              ListBox%
13525            \fi
13526            \fi
13527          \endcsname
13528        }%
13529    }\x
13530  \HyField@SetKeys{#1}%
13531  \PDFForm@Name
13532  \ifFld@hidden\def\Fld@width{1sp}\fi
13533  \ifx\Fld@value\relax
13534  \let\Fld@value\Fld@default
13535  \fi
13536  \LayoutChoiceField{#2}{%
13537  \ifFld@radio
13538    \HyField@FlagsRadioButton
13539    \@@Radio{#3}%
13540  \else
13541    \begingroup
13542      \HyField@FlagsChoice
13543      \ifdim\Fld@width<\@tempdima
13544        \ifdim\@tempdima<1cm\@tempdima1cm\fi
13545        \edef\Fld@width{\the\@tempdima}%
13546      \fi
13547      \ifFld@combo
13548      \else
13549        \@tempdima=\the\Fld@menulength\Fld@charsize
13550        \advance\@tempdima by \Fld@borderwidth bp %
13551        \advance\@tempdima by \Fld@borderwidth bp %
13552        \edef\Fld@height{\the\@tempdima}%

```

```

13553      \fi
13554      \@@Listbox{#3}%
13555      \endgroup
13556      \fi
13557  }%
13558 \endgroup
13559 }

\@@Radio
13560 \def\@@Radio#1{%
13561   \Fld@listcount=0 %
13562   \EdefEscapeName{\Fld@default}{\Fld@default}%
13563   \setbox\pdfm@box=\hbox{%
13564     \MakeRadioField{\Fld@width}{\Fld@height}%
13565   }%
13566   \@for\@curropt:=#1\do{%
13567     \expandafter\Fld@checkequals\@curropt==\\%
13568     \EdefEscapeName{\currValue}{\currValue}%
13569     \Hy@StepCount\Fld@listcount
13570     \currDisplay\space
13571     \leavevmode
13572     \Hy@escapeform\PDFForm@Radio
13573     \ifnum\Fld@listcount=1 %
13574       \HyField@AdvanceAnnotCount
13575     \fi
13576     \pdfm@mark{%
13577       ann %
13578       \ifnum\Fld@listcount=1 %
13579         @radio\HyField@TheAnnotCount%
13580       \space
13581     \fi
13582     \dvipdfm@setdim
13583     <<%
13584     \PDFForm@Radio
13585     /AP<</N<</\currValue /null>>>%
13586     >>%
13587   }%
13588   \unhcop\pdfm@box\space% deliberate space between radio buttons
13589   \ifnum\Fld@listcount=1 %
13590     \HyField@AddToFields{radio}%
13591   \fi
13592 }%
13593 }

\Fld@listcount
13594 \newcount\Fld@listcount

\@@Listbox
13595 \def\@@Listbox#1{%
13596   \HyField@PDFChoices{#1}%
13597   \setbox\pdfm@box=\hbox{%
13598     \MakeChoiceField{\Fld@width}{\Fld@height}%
13599   }%
13600   \leavevmode

```

```

13601 \Hy@escapeform\PDFForm@List
13602 \HyField@AdvanceAnnotCount
13603 \pdfm@mark{%
13604   ann @list\HyField@TheAnnotCount\space
13605   \dvipdfm@setdim
13606   <<\PDFForm@List>>%
13607 }%
13608 \unhbox\pdfm@box
13609 \HyField@AddToFields{list}%
13610 }

\@PushButton
13611 \def\@PushButton[#1]{% parameters, label
13612   \def\Fld@name{#2}%
13613   \begingroup
13614     \expandafter\HyField@SetKeys\expandafter{%
13615       \DefaultOptionsofPushButton,#1%
13616 }%
13617   \PDFForm@Name
13618   \ifHy@pdfa
13619     \Hy@Error{%
13620       PDF/A: Push button with JavaScript is prohibited%
13621     }\@ehc
13622     \LayoutPushButtonField{%
13623       \leavevmode
13624       \MakeButtonField{#2}%
13625     }%
13626   \else
13627     \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}%
13628     \HyField@FlagsPushButton
13629     \ifFld@hidden\def\Fld@width{1sp}\fi
13630     \HyField@AdvanceAnnotCount
13631     \LayoutPushButtonField{%
13632       \leavevmode
13633       \Hy@escapeform\PDFForm@Push
13634       \pdfm@mark{%
13635         ann @push\HyField@TheAnnotCount\space
13636         \dvipdfm@setdim
13637         <<\PDFForm@Push>>%
13638       }%
13639     }%
13640     \unhbox\pdfm@box
13641     \HyField@AddToFields{push}%
13642   \fi
13643 \endgroup
13644 }

\@Submit
13645 \def\@Submit[#1]{%
13646   \def\Fld@width{\DefaultWidthofSubmit}%
13647   \def\Fld@height{\DefaultHeightofSubmit}%
13648   \begingroup
13649     \expandafter\HyField@SetKeys\expandafter{%
13650       \DefaultOptionsofSubmit,#1%

```

```

13651    }%
13652    \HyField@FlagsPushButton
13653    \HyField@FlagsSubmit
13654    \ifFld@hidden\def\Fld@width{1sp}\fi
13655    \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}%
13656    \leavevmode
13657    \Hy@Escapeform\PDFForm@Submit
13658    \HyField@AdvanceAnnotCount
13659    \@pdfm@mark{%
13660      ann @submit\HyField@TheAnnotCount\space
13661      \dvipdfm@setdim
13662      <<\PDFForm@Submit>>%
13663    }%
13664    \unhbox\pdfm@box%
13665    \HyField@AddToFields{submit}%
13666  \endgroup
13667 }

\@Reset
13668 \def\@Reset[#1]{%
13669   \def\Fld@width{\DefaultWidthofReset}%
13670   \def\Fld@height{\DefaultHeightofReset}%
13671   \begingroup
13672     \expandafter\HyField@SetKeys\expandafter{%
13673       \DefaultOptionsofReset,#1%
13674     }%
13675     \leavevmode
13676     \ifHy@pdflatex
13677       \Hy@Error{%
13678         PDF/A: Reset action is prohibited%
13679       }@\ehc
13680       \MakeButtonField{#2}%
13681     \else
13682       \HyField@FlagsPushButton
13683       \ifFld@hidden\def\Fld@width{1sp}\fi
13684       \setbox\pdfm@box=\hbox{\MakeButtonField{#2}}%
13685       \Hy@Escapeform\PDFForm@Reset
13686       \HyField@AdvanceAnnotCount
13687       \@pdfm@mark{%
13688         ann @reset\HyField@TheAnnotCount\space
13689         \dvipdfm@setdim
13690         <<\PDFForm@Reset>>%
13691       }%
13692       \unhbox\pdfm@box
13693       \HyField@AddToFields{reset}%
13694     \fi
13695   \endgroup
13696 }

\@CheckBox
13697 \def\@CheckBox[#1]{%
13698   \def\Fld@name{#1}%
13699   \def\Fld@default{0}%
13700   \begingroup

```

```

13701 \def\Fl@width{\DefaultWidthofCheckBox}%
13702 \def\Fl@height{\DefaultHeightofCheckBox}%
13703 \expandafter\HyField@SetKeys\expandafter{%
13704   \DefaultOptionsofCheckBox,#1%
13705 }%
13706 \PDFForm@Name
13707 \HyField@FlagsCheckBox
13708 \ifFl@hidden\def\Fl@width{1sp}\fi
13709 \setbox\pdfm@box=\hbox{%
13710   \MakeCheckField{\Fl@width}{\Fl@height}%
13711 }%
13712 \HyField@AdvanceAnnotCount
13713 \LayoutCheckField{#2}{%
13714   \leavevmode
13715   \Hy@escapeform\PDFForm@Check
13716   \pdfm@mark{%
13717     ann @check\HyField@TheAnnotCount\space
13718     \dvipdfm@setdim
13719     <<\PDFForm@Check>>%
13720   }%
13721   \unhbox\pdfm@box
13722   \HyField@AddToFields{check}%
13723 }%
13724 \endgroup
13725 }

13726 \def\Hy@FormObjects{%
13727   @pdfm@mark{obj @OBJpdfdocencoding}%
13728   <<%
13729   /Type/Encoding%
13730   /Differences{%
13731     24/breve/caron/circumflex/dotaccent/hungarumlaut/ogonek/ring/tilde %
13732     39/quotesingle %
13733     96/grave %
13734     128/bullet/dagger/daggerdbl/ellipsis/emdash/endash/florin%
13735     /fraction/guilsinglleft/guilsinglright/minus/perthousand%
13736     /quotedblbase/quotedblleft/quotedblright/quotelleft/quoteright%
13737     /quotesinglbase/trademark/fi/fl/Lslash/OE/Scaron/Ydieresis%
13738     /Zcaron/dotlessi/lslash/oe/scaron/zcaron %
13739     160/Euro %
13740     164/currency %
13741     166/brokenbar %
13742     168/dieresis/copyright/ordfeminine %
13743     172/logicalnot/.notdef/registered/macron/degree/plusminus%
13744     /twosuperior/threesuperior/acute/mu %
13745     183/periodcentered/cedilla/onesuperior/ordmasculine %
13746     188/onequarter/onehalf/threequarters %
13747     192/Agrave/Aacute/Acircumflex/Atilde/Adieresis/Aring/AE%
13748     /Ccedilla/Egrave/Eacute/Ecircumflex/Edieresis/Igrave/Iacute%
13749     /Icircumflex/Idieresis/Eth/Ntilde/Ograve/Oacute/Ocircumflex%
13750     /Otilde/Odieresis/multiply/Oslash/Ugrave/Uacute/Ucircumflex%
13751     /Udieresis/Yacute/Thorn/germandbls/agrave/aacute/acircumflex%
13752     /atilde/adieresis/aring/ae/ccedilla/egrave/eacute%
13753     /ecircumflex/edieresis/igrave/iacute/icircumflex/idieresis%

```

```

13754      /eth/ntilde/ograve/oacute/ocircumflex/otilde/odieresis%
13755      /divide/oslash/ugrave/uacute/ucircumflex/udieresis/yacute%
13756      /thorn/ydieresis%
13757      ]%
13758      >>%
13759  }%
13760 \@pdfm@mark{obj @OBJZaDb%
13761   <<%
13762     /Type/Font%
13763     /Subtype/Type1%
13764     /Name/ZaDb%
13765     /BaseFont/ZapfDingbats%
13766     >>%
13767  }%
13768 \@pdfm@mark{obj @OBJHelv%
13769   <<%
13770     /Type/Font%
13771     /Subtype/Type1%
13772     /Name/Helv%
13773     /BaseFont/Helvetica%
13774     /Encoding @OBJpdfdocencoding%
13775     >>%
13776  }%
13777 \global\let\Hy@FormObjects\relax
13778 }
13779 </dvipdfm | xetex>

```

44.6 Common forms part

```

13780 <*pdfform>

\Fl@pageobjref
13781 \providecommand*\Fl@pageobjref{}}

\Hy@escapestring
13782 \ifundefined{pdf@escapestring}%
13783 {%
13784   \let\Hy@escapestring\@firstofone
13785   \def\Hy@escapeform##1{%
13786     \ifHy@pdfescapeform
13787       \def\Hy@escapestring##1{%
13788         \noexpand\Hy@escapestring{\noexpand##1}%
13789       }%
13790       \edef\Hy@temp{##1}%
13791       \expandafter\Hy@escapeform\Hy@temp\Hy@escapestring{}@\nil
13792       \def\Hy@escapestring##1{%
13793         \ifundefined{Hy@esc@\string##1}{%
13794           ##1%
13795           \ThisShouldNotHappen
13796         }{%
13797           \csname Hy@esc@\string##1\endcsname
13798         }%
13799       }%
13800     \else

```

```

13801     \let\Hy@escapestring\@firstofone
13802     \fi
13803 }%
13804 \def\Hy@escapeform#1\Hy@escapestring#2#3\@nil{%
13805   \ifx\#3\%
13806   \else
13807     \expandafter
13808     \Hy@pstringdef\csname Hy@esc@\string#2\endcsname{#2}%
13809     \ltx@ReturnAfterFi{%
13810       \Hy@escapeform#3\@nil
13811     }%
13812   \fi
13813 }%
13814 }{%
13815 \def\Hy@escapeform#1{%
13816   \ifHy@pdfescapeform
13817     \let\Hy@escapestring\pdfescapestring
13818   \else
13819     \let\Hy@escapestring\@firstofone
13820   \fi
13821 }%
13822 \Hy@escapeform{}%
13823 }

\PDFForm@Name
13824 \def\PDFForm@Name{%
13825   \PDFForm@@Name\Fld@name
13826   \ifx\Fld@altname\relax
13827   \else
13828     \PDFForm@@Name\Fld@altname
13829   \fi
13830   \ifx\Fld@mappingname\relax
13831   \else
13832     \PDFForm@@Name\Fld@mappingname
13833   \fi
13834 }

\PDFForm@@Name
13835 \def\PDFForm@@Name#1{%
13836   \begingroup
13837   \ifnum\Hy@pdf@majorminor@version<105 % implementation note 117, PDF spec 1.7
13838     \ifHy@unicode
13839       \Hy@unicodedefalse
13840     \fi
13841   \fi
13842   \pdfstringdef\Hy@gtemp#1%
13843   \endgroup
13844   \let#1\Hy@gtemp
13845 }

\Fld@additionalactions
13846 \def\Fld@additionalactions{%
K input (keystroke) format

```

```

13847 \ifx\Fld@keystroke@code\@empty
13848 \else
13849 /K<</S/JavaScript/JS(\Hy@escapestring{\Fld@keystroke@code})>>%
13850 \fi
F display format
13851 \ifx\Fld@format@code\@empty
13852 \else
13853 /F<</S/JavaScript/JS(\Hy@escapestring{\Fld@format@code})>>%
13854 \fi
V validation
13855 \ifx\Fld@validate@code\@empty
13856 \else
13857 /V<</S/JavaScript/JS(\Hy@escapestring{\Fld@validate@code})>>%
13858 \fi
C calculation
13859 \ifx\Fld@calculate@code\@empty
13860 \else
13861 /C<</S/JavaScript/JS(\Hy@escapestring{\Fld@calculate@code})>>%
13862 \fi
Fo receiving the input focus
13863 \ifx\Fld@onfocus@code\@empty
13864 \else
13865 /Fo<</S/JavaScript/JS(\Hy@escapestring{\Fld@onfocus@code})>>%
13866 \fi
Bl loosing the input focus (blurred)
13867 \ifx\Fld@onblur@code\@empty
13868 \else
13869 /Bl<</S/JavaScript/JS(\Hy@escapestring{\Fld@onblur@code})>>%
13870 \fi
D pressing the mouse button (down)
13871 \ifx\Fld@onmousedown@code\@empty
13872 \else
13873 /D<</S/JavaScript/JS(\Hy@escapestring{\Fld@onmousedown@code})>>%
13874 \fi
U releasing the mouse button (up)
13875 \ifx\Fld@onmouseup@code\@empty
13876 \else
13877 /U<</S/JavaScript/JS(\Hy@escapestring{\Fld@onmouseup@code})>>%
13878 \fi
E cursor enters the annotation's active area.
13879 \ifx\Fld@onenter@code\@empty
13880 \else
13881 /E<</S/JavaScript/JS(\Hy@escapestring{\Fld@onenter@code})>>%
13882 \fi
X cursor exits the annotation's active area.
13883 \ifx\Fld@onexit@code\@empty
13884 \else
13885 /X<</S/JavaScript/JS(\Hy@escapestring{\Fld@onexit@code})>>%
13886 \fi

```

```

13887 }
13888 \def\Fld@additionalactions{%
13889   \if-\Fld@additionalactions-%
13890   \else
13891     \ifHy@pdfa
13892   \else
13893     /AA<<\Fld@additionalactions>>%
13894   \fi
13895 \fi
13896 }

\Fld@annotnames
13897 \def\Fld@annotnames{%
13898   /T(\Fld@name)%
13899   \ifx\Fld@altname\relax
13900   \else
13901     /TU(\Fld@altname)%
13902   \fi
13903   \ifx\Fld@mappingname\relax
13904   \else
13905     /TM(\Fld@mappingname)%
13906   \fi
13907 }

\PDFForm@Check
13908 \def\PDFForm@Check{%
13909   /Subtype/Widget%
13910   \Fld@annotflags
13911   \Fld@pageobjref
13912   \Fld@annotnames
13913   /FT/Btn%
13914   \Fld@flags
13915   /Q \Fld@align
13916   /BS<</W \Fld@borderwidth /S/\Fld@borderstyle>>%
13917   /AP<< /N <</Yes<>>> >> %new string /Yes is from below
13918   /MK<<%
13919   \ifnum\Fld@rotation=\z@
13920   \else
13921     /R \Fld@rotation
13922   \fi
13923   \ifx\Fld@bordercolor\relax
13924   \else
13925     /BC[\Fld@bordercolor]%
13926   \fi
13927   \ifx\Fld@bcolor\relax
13928   \else
13929     /BG[\Fld@bcolor]%
13930   \fi
13931   /CA(\Hy@escapestring{\Fld@cbsymbol})%
13932 >>%
13933   /DA(/ZaDb \strip@pt\Fld@charsize\space Tf%
13934     \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
13935   /H/P%
13936   \ifFld@checked /V/Yes/AS/Yes\else /V/Off/AS/Off\fi

```

```

13937 \Fld@additionalactions
13938 }

\PDFForm@Push
13939 \ifHy@pdfa
13940 \else
13941 \def\PDFForm@Push{%
13942 /Subtype/Widget%
13943 \Fld@annotflags
13944 \Fld@pageobjref
13945 \Fld@annotnames
13946 /FT/Btn%
13947 \Fld@flags
13948 /H/P%
13949 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
13950 \ifcase0\ifnum\Fld@rotation=\z@\ \else 1\fi
13951 \ifx\Fld@bordercolor\relax\else 1\fi
13952 \space
13953 \else
13954 /MK<<%
13955 \ifnum\Fld@rotation=\z@
13956 \else
13957 /R \Fld@rotation
13958 \fi
13959 \ifx\Fld@bordercolor\relax
13960 \else
13961 /BC[\Fld@bordercolor]%
13962 \fi
13963 >>%
13964 \fi
13965 /A<</S/JavaScript/JS(\Hy@escapestring{\Fld@onclick@code})>>%
13966 \Fld@additionalactions
13967 }%
13968 \fi

\PDFForm@List
13969 \def\PDFForm@List{%
13970 /Subtype/Widget%
13971 \Fld@annotflags
13972 \Fld@pageobjref
13973 \Fld@annotnames
13974 /FT/Ch%
13975 \Fld@flags
13976 /Q \Fld@align
13977 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
13978 \ifcase0\ifnum\Fld@rotation=\z@\ \else 1\fi
13979 \ifx\Fld@bordercolor\relax\else 1\fi
13980 \ifx\fld@bcolor\relax \else 1\fi
13981 \space
13982 \else
13983 /MK<<%
13984 \ifnum\Fld@rotation=\z@
13985 \else
13986 /R \Fld@rotation

```

```

13987   \fi
13988   \ifx\Fld@bordercolor\relax
13989   \else
13990     /BC[\Fld@bordercolor]%
13991   \fi
13992   \ifx\Fld@bcolor\relax
13993   \else
13994     /BG[\Fld@bcolor]%
13995   \fi
13996   >>%
13997 \fi
13998 /DA(/Helv \strip@pt\Fld@charsize\space Tf%
13999   \ifx\Fld@color\@empty\else\space\Fld@color\fi)%
14000 \Fld@choices
14001 \Fld@additionalactions
14002 }

```

\PDFForm@Radio

```

14003 \def\PDFForm@Radio{%
14004   /Subtype/Widget%
14005   \Fld@annotflags
14006   \Fld@pageobjref
14007   \Fld@annotnames
14008   /FT/Btn%
14009   \Fld@flags
14010   /H/P%
14011   /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14012   /MK<<%
14013   \ifnum\Fld@rotation=\z@
14014   \else
14015     /R \Fld@rotation
14016   \fi
14017   \ifx\Fld@bordercolor\relax
14018   \else
14019     /BC[\Fld@bordercolor]%
14020   \fi
14021   \ifx\Fld@bcolor\relax
14022   \else
14023     /BG[\Fld@bcolor]%
14024   \fi
14025   /CA(\Hy@escapestring{\Fld@radiosymbol})%
14026 >>%
14027 /DA(/ZaDb \strip@pt\Fld@charsize\space Tf%
14028   \ifx\Fld@color\@empty\else\space\Fld@color\fi)%

```

New code, the default value is used for all buttons

```

14029   \ifx\Fld@default\@empty
14030     /V/Off%
14031     /DV/Off%
14032   \else
14033     /V/\Fld@default
14034     /DV/\Fld@default
14035   \fi
14036   \Fld@additionalactions
14037 }

```

```

\PDFForm@Text
14038 \def\PDFForm@Text{%
14039   /Subtype/Widget%
14040   \Fld@annotflags
14041   \Fld@pageobjref
14042   \Fld@annotnames
14043   /FT/Tx%
14044   \Fld@flags
14045   /Q \Fld@align
14046   /BS<</W \Fld@borderwidth\space /S /\Fld@borderstyle>>%
14047   \ifcase0\ifnum\Fld@rotation=\z@\ else 1\fi
14048     \ifx\Fld@bordercolor\relax\else 1\fi
14049     \ifx\Fld@bcolor\relax    \else 1\fi
14050     \space
14051   \else
14052     /MK<<%
14053       \ifnum\Fld@rotation=\z@
14054       \else
14055         /R \Fld@rotation
14056       \fi
14057       \ifx\Fld@bordercolor\relax
14058       \else
14059         /BC[\Fld@bordercolor]%
14060       \fi
14061       \ifx\Fld@bcolor\relax
14062       \else
14063         /BG[\Fld@bcolor]%
14064       \fi
14065     >>%
14066   \fi
14067   /DA(/Helv \strip@pt\Fld@charsize\space Tf%
14068     \ifx\Fld@color\empty\else\space\Fld@color\fi)%
14069   /DV(\Hy@escapestring{\Fld@default})%
14070   /V(\Hy@escapestring{\Fld@value})%
14071   \Fld@additionalactions
14072   \ifnum\Fld@maxlen>\z@/MaxLen \Fld@maxlen \fi
14073 }

```

```

\PDFForm@Submit
14074 \def\PDFForm@Submit{%
14075   /Subtype/Widget%
14076   \Fld@annotflags
14077   \Fld@pageobjref
14078   \Fld@annotnames
14079   /FT/Btn%
14080   \Fld@flags
14081   /H/P%
14082   /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14083   \ifcase0\ifnum\Fld@rotation=\z@\ else 1\fi
14084     \ifx\Fld@bordercolor\relax\else 1\fi
14085     \space
14086   \else
14087     /MK<<%
14088       \ifnum\Fld@rotation=\z@

```

```

14089    \else
14090        /R \Fld@rotation
14091    \fi
14092    \ifx\Fld@bordercolor\relax
14093    \else
14094        /BC[\Fld@bordercolor]%
14095    \fi
14096    >>%
14097 \fi
14098 /A<<%
14099 /S/SubmitForm%
14100 /F<<%
14101 /FS/URL%
14102 /F(\Hy@escapestring{\Form@action})%
14103 >>%
14104 \Fld@submitflags
14105 >>%
14106 \Fld@additionalactions
14107 }

\PDFForm@Reset
14108 \ifHy@pdflatex
14109 \else
14110 \def\PDFForm@Reset{%
14111 /Subtype/Widget%
14112 \Fld@annotflags
14113 \Fld@pageobjref
14114 \Fld@annotnames
14115 /FT/Btn%
14116 \Fld@flags
14117 /H/P%
14118 /DA(/Helv \strip@pt\Fld@charsize\space Tf 0 0 1 rg)%
14119 \ifcase0\ifnum\Fld@rotation=\z@\ \else 1\fi
14120 \ifx\Fld@bordercolor\relax\else 1\fi
14121 \space
14122 \else
14123 /MK<<%
14124 \ifnum\Fld@rotation=\z@
14125 \else
14126 /R \Fld@rotation
14127 \fi
14128 \ifx\Fld@bordercolor\relax
14129 \else
14130 /BC[\Fld@bordercolor]%
14131 \fi
14132 % /CA (Clear)
14133 % /AC (Done)
14134 >>%
14135 \fi
14136 /BS<</W \Fld@borderwidth/S/\Fld@borderstyle>>%
14137 /A<</S/ResetForm>>%
14138 \Fld@additionalactions
14139 }%
14140 \fi

```

```
14141 {/pdfform}
14142 {*packageEnd}
```

45 Bookmarks in the PDF file

This was originally developed by Yannis Haralambous (it was the separate `repere.sty`); it needed the `repere` or `makebook.pl` post-processor to work properly. Now redundant, as it is done entirely in L^AT_EX macros.

To write out the current section title, and its rationalized number, we have to intercept the `\@sect` command, which is rather dangerous. But how else to see the information we need? We do the *same* for `\@sect`, giving anchors to unnumbered sections. This allows things like bibliographies to get bookmarks when used with a manual `\addcontentsline`

```
14143 \def\phantomsection{%
14144   \Hy@MakeCurrentHrefAuto{section}*%}
14145   \Hy@raisedlink{\hyper@anchorstart{\@currentHref}\hyper@anchorend}%
14146 }
14147 {*}packageEnd}
```

45.1 Bookmarks

```
14148 {*}outlines}
```

This section was written by Heiko Oberdiek; the code replaces an earlier version by David Carlisle.

The first part of bookmark code is in section 6. Further documentation is available as paper and slides of the talk, that Heiko Oberdiek has given at the EuroTeX'99 meeting in Heidelberg. See `paper.pdf` and `slides.pdf` in the `doc` directory of `hyperref`.

When using the right-to-left typesetting based on ε-T_EX, the order of the `\BOOKMARK` commands written to the `\@outlinefile` could appear wrong, because of mis-feature of ε-T_EX's implementation (that it processes the shipped outlines left-to-right, instead of the order in which they appear in the document). The wrong order will appear when the file contains two bookmarks on the same line typeset right-to-left.

To work around this problem, the `bookmark@seq@number` counter is used to write the bookmark's sequential number into a comment in the `\@outlinefile`, which could be used to post-process it to achieve the proper ordering of `\BOOKMARK` commands in that file.

```
14149 \def\Hy@writebookmark#1#2#3#4#5{%
14150   % section number, text, label, level, file
14151   \ifx\WriteBookmarks\relax%
14152   \else
14153     \ifnum#4>\Hy@bookmarksdepth\relax
14154     \else
14155       \c@writetorep{#1}{#2}{#3}{#4}{#5}%
14156     \fi
14157   \fi
14158 }
14159 \def\Hy@currentbookmarklevel{0}
14160 \def\Hy@numberline#1{#1 }
```

```

14161 \def\@@writetorep#1#2#3#4#5{%
14162   \begingroup
14163     \edef\Hy@tempa{#5}%
14164     \ifx\Hy@tempa\Hy@bookmarkstype
14165       \edef\Hy@level{#4}%
14166       \ifx\Hy@levelcheck Y%
14167         \atempcpta\Hy@level\relax
14168         \advance\atempcpta by -1 %
14169         \ifnum\Hy@currentbookmarklevel<\atempcpta
14170           \advance\atempcpta by -\Hy@currentbookmarklevel\relax
14171           \advance\atempcpta by 1 %
14172           \Hy@Warning{%
14173             Difference (\the\atempcpta) between bookmark levels is %
14174             greater \MessageBreak than one, level fixed%
14175           }%
14176           \atempcpta\Hy@currentbookmarklevel
14177           \advance\atempcpta by 1 %
14178           \edef\Hy@level{\the\atempcpta}%
14179         \fi
14180       \else
14181         \global\let\Hy@levelcheck Y%
14182       \fi
14183       \global\let\Hy@currentbookmarklevel\Hy@level
14184       \atempcpta\Hy@level\relax
14185       \expandafter\xdef\csname Parent\Hy@level\endcsname{#3}%
14186       \advance\atempcpta by -1 %
14187       \edef\Hy@tempa{#3}%
14188       \edef\Hy@tempb{\csname Parent\the\atempcpta\endcsname}%
14189       \ifx\Hy@tempa\Hy@tempb
14190         \Hy@Warning{%
14191           The anchor of a bookmark and its parent's must not%
14192           \MessageBreak be the same. Added a new anchor%
14193         }%
14194         \phantomsection
14195       \fi
14196     \ifHy@bookmarksnumbered
14197       \let\numberline\Hy@numberline
14198       \let\booknumberline\Hy@numberline
14199       \let\partnumberline\Hy@numberline
14200       \let\chapternumberline\Hy@numberline
14201     \else
14202       \let\numberline@gobble
14203       \let\booknumberline@gobble
14204       \let\partnumberline@gobble
14205       \let\chapternumberline@gobble
14206     \fi
14207     \pdfstringdef\Hy@tempa{#2}%
14208     \HyPsd@SanitizeForOutFile\Hy@tempa
14209     \if@filesw
14210       \stepcounter{bookmark@seq@number}%
14211       \c@ifundefined{@outlinefile}{%
14212         }{%
14213           \protected@write{@outlinefile}{\%}
14214           \protect\BOOKMARK

```

```

14215      [\\Hy@level][\\@bookmarkopenstatus{\\Hy@level}]{#3}%
14216      {\\Hy@tempa}{\\Hy@tempb}%
14217      \\@percentchar\\space\\thebookmark@seq@number
14218      }%
14219      }%
14220      \\fi
14221      \\fi
14222  \\endgroup
14223 }
14224 \\newcounter{bookmark@seq@number}

14225 \\begingroup
14226   \\lccode`(`=\\{%
14227   \\lccode`)=\\}%
14228   \\lccode`1=\\z@%
14229   \\lccode`2=\\z@%
14230   \\lccode`3=\\z@%
14231   \\lccode`5=\\z@%
14232   \\lccode`7=\\z@%
14233   \\lccode`\\#=\\z@%
14234   \\lccode`\\`=\\z@%
14235   \\lccode`\\{=\\z@%
14236   \\lccode`\\}=\\z@%
14237 \\lowercase{%
14238   \\endgroup
14239   \\def\\HyPsd@SanitizeForOutFile#1{%
14240     \\@onelevel@sanitize\\Hy@tempa
14241     \\escapechar`\\%
14242     \\edef\\Hy@tempa{%
14243       \\expandafter\\HyPsd@SanitizeOut@BraceLeft\\Hy@tempa(\\@nil
14244     }%
14245     \\edef\\Hy@tempa{%
14246       \\expandafter\\HyPsd@SanitizeOut@BraceRight\\Hy@tempa)\\@nil
14247     }%
14248   }%
14249   \\def\\HyPsd@SanitizeOut@BraceLeft#1(#2\\@nil{%
14250     #1%
14251     \\ifx\\#2\\%
14252       \\expandafter\\ltx@gobble
14253     \\else
14254       \\expandafter\\ltx@firstofone
14255     \\fi
14256   }%
14257   \\string\\173%
14258   \\HyPsd@SanitizeOut@BraceLeft#2\\@nil
14259   }%
14260 }%
14261 \\def\\HyPsd@SanitizeOut@BraceRight#1)#2\\@nil{%
14262   #1%
14263   \\ifx\\#2\\%
14264     \\expandafter\\ltx@gobble
14265   \\else
14266     \\expandafter\\ltx@firstofone
14267   \\fi
14268 }%

```

```

14269     \string\175%
14270     \HyPsd@SanitizeOut@BraceRight#2\@nil
14271   }%
14272 }%
14273 }

```

In the call of \BOOKMARK the braces around #4 are omitted, because it is not likely, that the level number contains].

```

14274 \newcommand{\currentpdfbookmark}{%
14275   \pdfbookmark[\Hy@currentbookmarklevel]{%
14276   }{%
14277   \newcommand{\subpdfbookmark}{%
14278     \tempcnta\Hy@currentbookmarklevel
14279     \Hy@StepCount\tempcnta
14280     \expandafter\pdfbookmark\expandafter[\the\tempcnta]{%
14281   }{%
14282   \newcommand{\belowpdfbookmark}[2]{%
14283     \tempcnta\Hy@currentbookmarklevel
14284     \Hy@StepCount\tempcnta
14285     \expandafter\pdfbookmark\expandafter[\the\tempcnta]{#1}{#2}{%
14286     \advance\tempcnta by -1 %
14287     \xdef\Hy@currentbookmarklevel{\the\tempcnta}%
14288   }

```

Tobias Oetiker rightly points out that we need a way to force a bookmark entry. So we introduce \pdfbookmark, with two parameters, the title, and a symbolic name. By default this is at level 1, but we can reset that with the optional first argument.

```

14289 \renewcommand\pdfbookmark[3][0]{%
14290   \Hy@writebookmark{}{#2}{#3.#1}{#1}{toc}%
14291   \hyper@anchorstart{#3.#1}\hyper@anchorend
14292 }
14293 \def\BOOKMARK{%
14294   \ifnextchar{\@BOOKMARK}{\@BOOKMARK[1][-]}{%
14295   }
14296   \def\@BOOKMARK[#1]{%
14297     \ifnextchar{\@BOOKMARK[#1]}{\@BOOKMARK[#1][-]}{%
14298   }

```

The macros for calculating structure of outlines are derived from those by Petr Olsak used in the texinfopdf macros.

45.1.1 Rerun warning

\Hy@OutlineRerunCheck

```

14299 \RequirePackage{rerunfilecheck}[2009/12/10]
14300 \def\Hy@OutlineRerunCheck{%
14301   \RerunFileCheck{\jobname.out}{%
14302     \immediate\closeout\outlinefile
14303   }{%
14304     Rerun to get outlines right\MessageBreak
14305     or use package `bookmark'%
14306   }%
14307 }

```

45.1.2 Driver stuff

The VTEX section was written originally by VTEX, but then amended by Denis Girou (denis.girou@idris.fr), then by Taco Hoekwater (taco.hoekwater@wkcap.nl). The problem is that VTEX, with its close integration of the PDF backend, does look at the contents of bookmarks, escaping \ and the like.

```
14308 {*vtex}
14309 \newcount\@serial\@counter\@serial\@counter=1\relax
```

\hv@pdf@char Plain octal codes doesn't work with versions below 6.50. So for early versions hex numbers have to be used. It would be possible to program this instead of the large \ifcase, but I'm too lazy to sort that out now.

```
14310 \begingroup
14311   \catcode`'=12 %
14312   \ifnum\Hy@VTeXversion<650 %
14313     \catcode`'=12 %
14314     \gdef\hv@pdf@char{\#1\#2\#3{%
14315       \char
14316       \ifcase'\#1\#2\#3 %
14317         "00\or"01\or"02\or"03\or"04\or"05\or"06\or"07%
14318         \or"08\or"09\or"0A\or"0B\or"0C\or"0D\or"0E\or"0F%
14319         \or"10\or"11\or"12\or"13\or"14\or"15\or"16\or"17%
14320         \or"18\or"19\or"1A\or"1B\or"1C\or"1D\or"1E\or"1F%
14321         \or"20\or"21\or"22\or"23\or"24\or"25\or"26\or"27%
14322         \or"28\or"29\or"2A\or"2B\or"2C\or"2D\or"2E\or"2F%
14323         \or"30\or"31\or"32\or"33\or"34\or"35\or"36\or"37%
14324         \or"38\or"39\or"3A\or"3B\or"3C\or"3D\or"3E\or"3F%
14325         \or"40\or"41\or"42\or"43\or"44\or"45\or"46\or"47%
14326         \or"48\or"49\or"4A\or"4B\or"4C\or"4D\or"4E\or"4F%
14327         \or"50\or"51\or"52\or"53\or"54\or"55\or"56\or"57%
14328         \or"58\or"59\or"5A\or"5B\or"5C\or"5D\or"5E\or"5F%
14329         \or"60\or"61\or"62\or"63\or"64\or"65\or"66\or"67%
14330         \or"68\or"69\or"6A\or"6B\or"6C\or"6D\or"6E\or"6F%
14331         \or"70\or"71\or"72\or"73\or"74\or"75\or"76\or"77%
14332         \or"78\or"79\or"7A\or"7B\or"7C\or"7D\or"7E\or"7F%
14333         \or"80\or"81\or"82\or"83\or"84\or"85\or"86\or"87%
14334         \or"88\or"89\or"8A\or"8B\or"8C\or"8D\or"8E\or"8F%
14335         \or"90\or"91\or"92\or"93\or"94\or"95\or"96\or"97%
14336         \or"98\or"99\or"9A\or"9B\or"9C\or"9D\or"9E\or"9F%
14337         \or"A0\or"A1\or"A2\or"A3\or"A4\or"A5\or"A6\or"A7%
14338         \or"A8\or"A9\or"AA\or"AB\or"AC\or"AD\or"AE\or"AF%
14339         \or"B0\or"B1\or"B2\or"B3\or"B4\or"B5\or"B6\or"B7%
14340         \or"B8\or"B9\or"BA\or"BB\or"BC\or"BD\or"BE\or"BF%
14341         \or"C0\or"C1\or"C2\or"C3\or"C4\or"C5\or"C6\or"C7%
14342         \or"C8\or"C9\or"CA\or"CB\or"CC\or"CD\or"CE\or"CF%
14343         \or"D0\or"D1\or"D2\or"D3\or"D4\or"D5\or"D6\or"D7%
14344         \or"D8\or"D9\or"DA\or"DB\or"DC\or"DD\or"DE\or"DF%
14345         \or"E0\or"E1\or"E2\or"E3\or"E4\or"E5\or"E6\or"E7%
14346         \or"E8\or"E9\or"EA\or"EB\or"EC\or"ED\or"EE\or"EF%
14347         \or"F0\or"F1\or"F2\or"F3\or"F4\or"F5\or"F6\or"F7%
14348         \or"F8\or"F9\or"FA\or"FB\or"FC\or"FD\or"FE\or"FF%
14349         \fi
14350     }%
```

```

14351 \else
14352 \gdef\hv@pdf@char{\char'}%
14353 \fi
14354 \endgroup

\@@BOOKMARK

14355 \def\@@BOOKMARK[#1][#2]#3#4#5{%
14356 \expandafter\edef\csname @count@#3\endcsname{%
14357 \the\@serial@counter
14358 }%
14359 \edef\@mycount{\the\@serial@counter}%
14360 \Hy@StepCount\@serial@counter
14361 \edef\@parcount{%
14362 \expandafter\ifx\csname @count@#5\endcsname\relax
14363 0%
14364 \else
14365 \csname @count@#5\endcsname
14366 \fi
14367 }%
14368 \immediate\special{%
14369 !outline \HyperDestNameFilter{#3};p=\@parcount,i=\@mycount,%
14370 s=\ifx#2-c\else o\fi,t=#4%
14371 }%
14372 }%

\ReadBookmarks

14373 \def\ReadBookmarks{%
14374 \begingroup
14375 \def\0{\hv@pdf@char 0}%
14376 \def\1{\hv@pdf@char 1}%
14377 \def\2{\hv@pdf@char 2}%
14378 \def\3{\hv@pdf@char 3}%
14379 \def\{{}%
14380 \def\}{}
14381 \def\do##1{%
14382 \ifnum\catcode`##1=\active
14383 \makeother##1%
14384 \else
14385 \ifnum\catcode`##1=6 %
14386 \makeother##1%
14387 \fi
14388 \fi
14389 }%
14390 \dospecials
14391 \Hy@safe@activestru
14392 \InputIfFileExists{\jobname.out}{}{%
14393 \endgroup
14394 \ifx\WriteBookmarks\relax
14395 \else
14396 \if@filesw
14397 \newwrite\outlinefile
14398 \Hy@OutlineRerunCheck
14399 \immediate\openout\outlinefile=\jobname.out\relax
14400 \fi

```

```

14401  \f
14402 }

14403 </vtex>
14404 <*!vtex>
14405 \def\ReadBookmarks{%
14406   \pdf@ifdraftmode{}{%
14407     \begingroup
14408       \def\do##1{%
14409         \ifnum\catcode`##1=\active
14410           \o@makeother##1%
14411         \else
14412           \ifnum\catcode`##1=6 %
14413             \o@makeother##1%
14414           \fi
14415         \fi
14416       }%
14417     \dospecials
14418     \Hy@safe@activestrue
14419     \escapechar=`\%
14420     \def\@@BOOKMARK[##1][##2]##3##4##5{%
14421       \calc@bm@number{##5}%
14422     }%
14423     \InputIfFileExists{\jobname.out}{ }{ }%
14424     \ifx\WriteBookmarks\relax
14425       \global\let\WriteBookmarks\relax
14426     \fi
14427     \def\@@BOOKMARK[##1][##2]##3##4##5{%
14428       \def\Hy@temp{##4}%
14429   (*pdftex)
14430     \Hy@pstringdef\Hy@pstringName{\HyperDestNameFilter{##3}}%
14431     \Hy@OutlineName{}{\Hy@pstringName{%
14432       ##2\check@bm@number{##3}}%
14433     }{%
14434       \expandafter\strip@prefix\meaning\Hy@temp
14435     }%
14436 </pdftex>
14437 <*pdfmark>
14438   \pdfmark{%
14439     pdfmark=/OUT,%
14440     Count={##2\check@bm@number{##3}},%
14441     Dest={##3},%
14442     Title=\expandafter\strip@prefix\meaning\Hy@temp
14443   }%
14444 </pdfmark>
14445 <*dvipdfm | xetex>
14446   \Hy@pstringdef\Hy@pstringName{\HyperDestNameFilter{##3}}%
14447   \o@pdfm@mark{%
14448     outline \ifHy@DvipdfmxOutlineOpen
14449       %
14450       \ifnum##21>\z@
14451       \else
14452         %
14453       \fi

```

```

14454      ] %
14455      \fi
14456      ##1<<%
14457      /Title(\expandafter\strip@prefix\meaning\Hy@temp)%
14458      /A<<%
14459      /S/GoTo%
14460      /D(\Hy@pstringName)%
14461      >>%
14462      >>%
14463      }%
14464 </dvipdfm | xetex>
14465      }%
14466      \begingroup
14467      \def\WriteBookmarks{0}%
14468      \InputIfFileExists{\jobname.out}{}{}%
14469      \endgroup
14470      %{\escapechar`m@ne\InputIfFileExists{\jobname.out}{}{}}
14471      \endgroup
14472      }%
14473 \ifx\WriteBookmarks\relax
14474 \else
14475   \if@filesw
14476     \newwrite\@outlinefile
14477     \Hy@OutlineRerunCheck
14478     \immediate\openout\@outlinefile=\jobname.out\relax
14479   \fi
14480 \fi
14481 }
14482 <*pdftex>
14483 \def\Hy@OutlineName#1#2#3#4{%
14484   \pdfoutline goto name{\#2}count{\#3}{\#4}%
14485 }
14486 </pdftex>
14487 \def\check@bm@number#1{%
14488   \expandafter\ifx\csname B_#1\endcsname\relax
14489   0%
14490 \else
14491   \csname B_#1\endcsname
14492 \fi
14493 }
14494 \def\calc@bm@number#1{%
14495   \tempcnta=\check@bm@number{#1}\relax
14496   \advance\tempcnta by 1 %
14497   \expandafter\xdef\csname B_#1\endcsname{\the\tempcnta}%
14498 }
14499 </!vtex>

14500 \ifHy@implicit
14501 \else
14502   \expandafter\endinput
14503 \fi
14504 </outlines>
14505 <*outlines | hypertex>
14506 \newlength\Hy@SectionHShift

```

```

14507 \def\HyCSectionAnchorHref#1{%
14508   \ifx\protect\@typeset@protect
14509     \Hy@@SectionAnchor{#1}%
14510   \fi
14511 }
14512 \DeclareRobustCommand*\Hy@@SectionAnchor}[1]{%
14513   \leavevmode
14514   \hbox to 0pt{%
14515     \kern-\HyCSectionHShift
14516     \Hy@raisedlink{%
14517       \hyper@anchorstart{#1}\hyper@anchorend
14518     }%
14519     \hss
14520   }%
14521 }
14522 \@ifundefined{hyper@nopatch@sectioning}{%
14523 {
14524   \let\H@old@ssect\@ssect
14525   \def\@ssect#1#2#3#4#5{%
14526     \Hy@MakeCurrentHrefAuto{section*}%
14527     \setlength{\Hy@SectionHShift}{#1}%
14528     \begingroup
14529       \toks@\{\H@old@ssect{#1}{#2}{#3}{#4}\}%
14530       \toks\tw@{\expandafter{%
14531         \expandafter\Hy@SectionAnchorHref\expandafter{\@currentHref}%
14532       }#5%
14533     }%
14534   \edef\x{\endgroup
14535     \the\toks@\{\the\toks\tw@\}%
14536   }\x
14537 }
14538 \let\H@old@schapter\@schapter
14539 \def\@schapter#1{%
14540   \begingroup
14541   \let\@mkboth\@gobbletwo
14542   \Hy@MakeCurrentHrefAuto{\Hy@chapapp*}%
14543   \Hy@raisedlink{%
14544     \hyper@anchorstart{\@currentHref}\hyper@anchorend
14545   }%
14546   \endgroup
14547   \H@old@schapter{#1}%
14548 }

```

If there is no chapter number (`\frontmatter` or `\backmatter`) then the counting by `\refstepcounter{chapter}` is not executed, so there will be no destination for `\ddcontentsline`. So `\@chapter` is overloaded to avoid this:

```

14549 \ltx@ifundefined{@chapter}{}{%
14550   \let\Hy@org@chapter\@chapter
14551   \def\@chapter{%
14552     \def\Hy@next{%
14553       \Hy@MakeCurrentHrefAuto{\Hy@chapapp*}%
14554       \Hy@raisedlink{%
14555         \hyper@anchorstart{\@currentHref}\hyper@anchorend
14556       }%

```

```

14557   }%
14558   \ifnum\c@secnumdepth>\m@ne
14559     \ltx@IfUndefined{if@mainmatter}%
14560     \iftrue{\csname if@mainmatter\endcsname}%
14561       \let\Hy@next\relax
14562     \fi
14563   \fi
14564   \Hy@next
14565   \Hy@org@chapter
14566 }%
14567 }

14568 \let\H@old@part\@part
14569 \@ifundefined{chapter}
14570   {\let\Hy@secnum@part\z@}
14571   {\let\Hy@secnum@part\m@ne}
14572 \def\@part{%
14573   \ifnum\Hy@secnum@part>\c@secnumdepth
14574     \phantomsection
14575   \fi
14576   \H@old@part
14577 }

14578 \let\H@old@spart\@spart
14579 \def\@spart#1{%
14580   \Hy@MakeCurrentHrefAuto{part*}%
14581   \Hy@raisedlink{%
14582     \hyper@anchorstart{\@currentHref}\hyper@anchorend
14583   }%
14584   \H@old@spart{#1}%
14585 }
14586 \let\H@old@sect\@sect
14587 \def\@sect#1#2#3#4#5#6[#7]{%
14588   \ifnum #2>\c@secnumdepth
14589     \expandafter\@firstoftwo
14590   \else
14591     \expandafter\@secondoftwo
14592   \fi
14593 }%
14594   \Hy@MakeCurrentHrefAuto{section*}%
14595   \setlength{\Hy@sectionHShift}{#3}%
14596   \begingroup
14597     \toks@{\H@old@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]}%
14598     \toks@{\tw@{\expandafter{%
14599       \expandafter\Hy@SectionAnchorHref\expandafter{\@currentHref}%
14600       #8}%
14601     }%
14602     \edef\x{\endgroup
14603       \the\toks@\{\the\toks\tw@\}%
14604     }\x
14605   }%
14606   \H@old@sect{#1}{#2}{#3}{#4}{#5}{#6}[{#7}]{#8}%
14607 }%
14608 }
14609 }{}}

```

```

14610 </outlines | hypertex>
14611 <*>outlines</*>
14612 \expandafter\def\csname Parent-4\endcsname{}
14613 \expandafter\def\csname Parent-3\endcsname{}
14614 \expandafter\def\csname Parent-2\endcsname{}
14615 \expandafter\def\csname Parent-1\endcsname{}
14616 \expandafter\def\csname Parent0\endcsname{}
14617 \expandafter\def\csname Parent1\endcsname{}
14618 \expandafter\def\csname Parent2\endcsname{}
14619 \expandafter\def\csname Parent3\endcsname{}
14620 \expandafter\def\csname Parent4\endcsname{}
14621 </outlines>

```

46 Encoding definition files for encodings of PDF strings

This was contributed by Heiko Oberdiek.

46.1 PD1 encoding

```

14622 <*>pd1enc</*>
14623 \DeclareFontEncoding{PD1}{}{}

Accents
14624 \DeclareTextAccent{\`}{PD1}{\textasciigrave}
14625 \DeclareTextAccent{\'}{PD1}{\textacute}
14626 \DeclareTextAccent{\^}{PD1}{\textasciicircum}
14627 \DeclareTextAccent{\~}{PD1}{\texttilde}
14628 \DeclareTextAccent{"}{PD1}{\textasciidieresis}
14629 \DeclareTextAccent{\r}{PD1}{\textring}
14630 \DeclareTextAccent{\v}{PD1}{\textasciicaron}
14631 \DeclareTextAccent{\.}{PD1}{\textdotaccent}
14632 \DeclareTextAccent{\c}{PD1}{\textcedilla}
14633 \DeclareTextAccent{\=}{PD1}{\textasciimacron}
14634 \DeclareTextAccent{\b}{PD1}{\textmacronbelow}
14635 \DeclareTextAccent{\d}{PD1}{\textdotbelow}
14636 \DeclareTextCompositeCommand{\`}{PD1}{\emptyset}{\textasciigrave}
14637 \DeclareTextCompositeCommand{\'}{PD1}{\emptyset}{\textacute}
14638 \DeclareTextCompositeCommand{\^}{PD1}{\emptyset}{\textasciicircum}
14639 \DeclareTextCompositeCommand{\~}{PD1}{\emptyset}{\texttilde}
14640 \DeclareTextCompositeCommand{"}{PD1}{\emptyset}{\textasciidieresis}
14641 \DeclareTextCompositeCommand{\r}{PD1}{\emptyset}{\textring}
14642 \DeclareTextCompositeCommand{\v}{PD1}{\emptyset}{\textasciicaron}
14643 \DeclareTextCompositeCommand{\.}{PD1}{\emptyset}{\textdotaccent}
14644 \DeclareTextCompositeCommand{\c}{PD1}{\emptyset}{\textcedilla}
14645 \DeclareTextCompositeCommand{\=}{PD1}{\emptyset}{\textasciimacron}
14646 \DeclareTextCompositeCommand{\b}{PD1}{\emptyset}{\textmacronbelow}
14647 \DeclareTextCompositeCommand{\d}{PD1}{\emptyset}{\textdotbelow}
14648 \DeclareTextCompositeCommand{\`}{PD1}{\emptyset}{\textasciigrave}
14649 \DeclareTextCompositeCommand{\'}{PD1}{\emptyset}{\textacute}
14650 \DeclareTextCompositeCommand{\^}{PD1}{\emptyset}{\textasciicircum}
14651 \DeclareTextCompositeCommand{\~}{PD1}{\emptyset}{\texttilde}

```

```

14652 \DeclareTextCompositeCommand{\\"}{PD1}{\ }{\textasciidieresis}
14653 \DeclareTextCompositeCommand{\r}{PD1}{\ }{\texttring}
14654 \DeclareTextCompositeCommand{\v}{PD1}{\ }{\textasciicaron}
14655 \DeclareTextCompositeCommand{\.}{PD1}{\ }{\textdotaccent}
14656 \DeclareTextCompositeCommand{\c}{PD1}{\ }{\textcedilla}
14657 \DeclareTextCompositeCommand{\=}{PD1}{\ }{\textasciimacron}
14658 \DeclareTextCompositeCommand{\b}{PD1}{\ }{\textmacronbelow}
14659 \DeclareTextCompositeCommand{\d}{PD1}{\ }{\textdotbelow}
14660 \DeclareTextCommand{\k}{PD1}[1]{\TextSymbolUnavailable{\k{#1}}#1}
14661 \DeclareTextCommand{\t}{PD1}[1]{\TextSymbolUnavailable{\t{#1}}#1}
14662 \DeclareTextCommand{\newtie}{PD1}[1]{%
14663   \TextSymbolUnavailable{\newtie{#1}}#1%
14664 }

```

Special white space escape characters not for use in bookmarks but for other PDF strings.

```

14665 % U+0009 (CHARACTER TABULATION)
14666 \DeclareTextCommand{\textHT}{PD1}{\011}% U+0009
14667 % U+000A (LINE FEED)
14668 \DeclareTextCommand{\textLF}{PD1}{\012}% U+000A
14669 % U+000D (CARRIAGE RETURN)
14670 \DeclareTextCommand{\textCR}{PD1}{\015}% U+000D

```

Accent glyph names

```

14671 % U+02D8 BREVE; breve
14672 \DeclareTextCommand{\textasciibreve}{PD1}{\030}% U+02D8
14673 % U+02C7 CARON; caron
14674 \DeclareTextCommand{\textasciicaron}{PD1}{\031}% U+02C7
14675 % U+02C6 MODIFIER LETTER CIRCUMFLEX ACCENT; circumflex
14676 \DeclareTextCommand{\textcircumflex}{PD1}{\032}% U+02C6
14677 % U+02D9 DOT ABOVE; dotaccent
14678 \DeclareTextCommand{\textdotaccent}{PD1}{\033}% U+02D9
14679 % U+02DD DOUBLE ACUTE ACCENT; hungarumlaut
14680 \DeclareTextCommand{\texthungarumlaut}{PD1}{\034}% U+02DD
14681 % U+02DB OGONEK; ogonek
14682 \DeclareTextCommand{\textogonek}{PD1}{\035}% U+02DB
14683 % U+02DA RING ABOVE; ring
14684 \DeclareTextCommand{\textring}{PD1}{\036}% U+02DA
14685 % U+02DC SMALL TILDE; ilde, *tilde
14686 \DeclareTextCommand{\texttilde}{PD1}{\037}% U+02DC
\040: U+0020 SPACE; *space, spacehackarabic
\041: U+0021 EXCLAMATION MARK; exclam
14687 % U+0022 QUOTATION MARK; quotedbl
14688 \DeclareTextCommand{\textquotedbl}{PD1}{"}% \042 U+0022
14689 % U+0023 NUMBER SIGN; numbersign
14690 \DeclareTextCommand{\textnumbersign}{PD1}{\043}% U+0023
14691 % U+0024 DOLLAR SIGN; dollar
14692 \DeclareTextCommand{\textdollar}{PD1}{\044}% U+0024
14693 % U+0025 PERCENT SIGN; percent
14694 \DeclareTextCommand{\textpercent}{PD1}{\045}% U+0025
14695 % U+0026 AMPERSAND; ampersand
14696 \DeclareTextCommand{\textampersand}{PD1}{\046}% U+0026
\047: U+0027 APOSTROPHE; quotesingle

```

```

14697 % U+0028 LEFT PARENTHESIS; parenleft
14698 \DeclareTextCommand{\textparenleft}{\PD1}{\string\(\}% \050 U+0028
14699 % U+0029 RIGHT PARENTHESIS; parenright
14700 \DeclareTextCommand{\textparenright}{\PD1}{\string\)}% \051 U+0029
\052: U+002A ASTERISK; asterisk
\053: U+002B PLUS SIGN; plus
\054: U+002C COMMA; comma
\055: U+002D HYPHEN-MINUS; hyphen
\056: U+002E FULL STOP; period
14701 % U+002E FULL STOP; period
14702 \DeclareTextCommand{\textdotbelow}{\PD1}{.}% \056 U+002E
\057: U+002F SOLIDUS; slash
\060: U+0030 DIGIT ZERO; zero
...
\071: U+0039 DIGIT NINE; nine
\072: U+003A COLON; colon
\073: U+003B SEMICOLON; semicolon
14703 % U+003C LESS-THAN SIGN; less
14704 \DeclareTextCommand{\textless}{\PD1}{<}% \074 U+003C
\075: U+003D EQUALS SIGN; equal
14705 % U+003E GREATER-THAN SIGN; greater
14706 \DeclareTextCommand{\textgreater}{\PD1}{>}% \076 U+003E
\077: U+003F QUESTION MARK; question
\100: U+0040 COMMERCIAL AT; at
\101: U+0041 LATIN CAPITAL LETTER A; A
...
\132: U+005A LATIN CAPITAL LETTER Z; Z
\133: U+005B LEFT SQUARE BRACKET; bracketleft
14707 % U+005C REVERSE SOLIDUS; backslash
14708 \DeclareTextCommand{\textbackslash}{\PD1}{\134}% U+005C
14709 % "U+2216 SET MINUS" simulated by "U+005C REVERSE SOLIDUS"
14710 \DeclareTextCommand{\textsetminus}{\PD1}{\textbackslash}
\135: U+005D RIGHT SQUARE BRACKET; bracketright
14711 % U+005E CIRCUMFLEX ACCENT; asciicircum
14712 \DeclareTextCommand{\textasciicircum}{\PD1}{\136}% U+005E
14713 % U+005F LOW LINE; underscore
14714 \DeclareTextCommand{\texttunder}{\PD1}{\137}% U+005F
14715 \DeclareTextCommand{\textmacron}{\PD1}{\137}% U+005F
14716 % U+0060 GRAVE ACCENT; grave
14717 \DeclareTextCommand{\textasciigrave}{\PD1}{\140}% U+0060
\141: U+0061 LATIN SMALL LETTER A; a
...
\150: U+0068 LATIN SMALL LETTER H; h
14718 % U+0069 LATIN SMALL LETTER I; i
14719 \DeclareTextCompositeCommand{\.}{\PD1}{i}{i}% \151 U+0069
\152: U+006A LATIN SMALL LETTER J; j
...
\172: U+007A LATIN SMALL LETTER Z; z
14720 % U+007B LEFT CURLY BRACKET; braceleft
14721 \DeclareTextCommand{\textbraceleft}{\PD1}{\173}% U+007B

```

```

14722 % U+007C VERTICAL LINE; *bar, verticalbar
14723 \DeclareTextCommand{\textbar}{\PD1}{|}% U+007C
14724 % U+007D RIGHT CURLY BRACKET; braceright
14725 \DeclareTextCommand{\textbraceright}{\PD1}{\textbraceleft}% U+007D
14726 % U+007E TILDE; asciitilde
14727 \DeclareTextCommand{\textasciitilde}{\PD1}{\texttilde}% U+007E

Slot \textbraceleft (0x7F) is undefined in PDFDocEncoding.
14728 % U+2022 BULLET; bullet
14729 \DeclareTextCommand{\textbullet}{\PD1}{\textbullet}% U+2022
14730 % U+2020 DAGGER; dagger
14731 \DeclareTextCommand{\textdagger}{\PD1}{\textdagger}% U+2020
14732 % U+2021 DOUBLE DAGGER; daggerdbl; \ddagger (LaTeX)
14733 \DeclareTextCommand{\textdaggerdbl}{\PD1}{\textdaggerdbl}% U+2021
14734 \DeclareTextCommand{\textddagger}{\PD1}{\textddagger}% U+2026
14735 % U+2026 HORIZONTAL ELLIPSIS; ellipsis
14736 \DeclareTextCommand{\textellipsis}{\PD1}{\textellipsis}% U+2026
14737 % U+2014 EM DASH; emdash
14738 \DeclareTextCommand{\textemdash}{\PD1}{\textemdash}% U+2014
14739 % U+2013 EN DASH; endash
14740 \DeclareTextCommand{\textendash}{\PD1}{\textendash}% U+2013
14741 % U+0192 LATIN SMALL LETTER F WITH HOOK; florin
14742 \DeclareTextCommand{\textflorin}{\PD1}{\textflorin}% U+0192
14743 % U+2044 FRACTION SLASH; fraction
14744 \DeclareTextCommand{\textfractionsolidus}{\PD1}{\textsolidus}% U+2044
14745 % U+2039 SINGLE LEFT-POINTING ANGLE QUOTATION MARK; guillemotleft
14746 \DeclareTextCommand{\guillemotleft}{\PD1}{\textguillemotleft}% U+2039
14747 % U+203A SINGLE RIGHT-POINTING ANGLE QUOTATION MARK; guillemotright
14748 \DeclareTextCommand{\guillemotright}{\PD1}{\textguillemotright}% U+203A
14749 % U+2212 MINUS SIGN; minus
14750 \DeclareTextCommand{\textminus}{\PD1}{\textminus}% U+2212
14751 % U+2030 PER MILLE SIGN; perthousand
14752 \DeclareTextCommand{\textperthousand}{\PD1}{\textperthousand}% U+2030
14753 % U+201E DOUBLE LOW-9 QUOTATION MARK; quotedblbase
14754 \DeclareTextCommand{\quotedblbase}{\PD1}{\textquoteright}% U+201E
14755 % U+201C LEFT DOUBLE QUOTATION MARK; quotedblleft
14756 \DeclareTextCommand{\textquotedblleft}{\PD1}{\textquoteright}% U+201C
14757 % U+201D RIGHT DOUBLE QUOTATION MARK; quotedblrigh
14758 \DeclareTextCommand{\textquotedblright}{\PD1}{\textquoteright}% U+201D
14759 % U+2018 LEFT SINGLE QUOTATION MARK; quoteleft
14760 \DeclareTextCommand{\textquoteright}{\PD1}{\textquoteright}% U+2018
14761 % U+2019 RIGHT SINGLE QUOTATION MARK; quoteright
14762 \DeclareTextCommand{\textquoteright}{\PD1}{\textquoteright}% U+2019
14763 % U+201A SINGLE LOW-9 QUOTATION MARK; quotesinglbase
14764 \DeclareTextCommand{\quotesinglbase}{\PD1}{\textquoteright}% U+201A
14765 % U+2122 TRADE MARK SIGN; trademark
14766 \DeclareTextCommand{\texttrademark}{\PD1}{\texttrademark}% U+2122
14767 % U+FB01 LATIN SMALL LIGATURE FI; fi
14768 \DeclareTextCommand{\textfi}{\PD1}{\textfi}% U+FB01
14769 % U+FB02 LATIN SMALL LIGATURE FL; fl
14770 \DeclareTextCommand{\textfl}{\PD1}{\textfl}% U+FB02
14771 % U+0141 LATIN CAPITAL LETTER L WITH STROKE; Lslash
14772 \DeclareTextCommand{\textL}{\PD1}{\textL}% U+0141

```

14773 % U+0152 LATIN CAPITAL LIGATURE OE; oe
 14774 \DeclareTextCommand{\OE}{\PD1}{\226} % U+0152
 14775 % U+0160 LATIN CAPITAL LETTER S WITH CARON; scaron
 14776 \DeclareTextCompositeCommand{\v}{\PD1}{S}{\227} % U+0160
 14777 % U+0178 LATIN CAPITAL LETTER Y WITH DIAERESIS; ydieresis
 14778 \DeclareTextCompositeCommand{\v}{\PD1}{Y}{\230} % U+0178
 14779 \DeclareTextCommand{\IJ}{\PD1}{IJ} % ligature U+0049 U+004A
 14780 % U+017D LATIN CAPITAL LETTER Z WITH CARON; zcaron
 14781 \DeclareTextCompositeCommand{\v}{\PD1}{Z}{\231} % U+017D
 14782 % U+0131 LATIN SMALL LETTER DOTLESS I; dotlessi
 14783 \DeclareTextCommand{\i}{\PD1}{\232} % U+0131
 14784 % U+0142 LATIN SMALL LETTER L WITH STROKE; lslash
 14785 \DeclareTextCommand{\l}{\PD1}{\233} % U+0142
 14786 % U+0153 LATIN SMALL LIGATURE OE; oe
 14787 \DeclareTextCommand{\oe}{\PD1}{\234} % U+0153
 14788 % U+0161 LATIN SMALL LETTER S WITH CARON; scaron
 14789 \DeclareTextCompositeCommand{\v}{\PD1}{s}{\235} % U+0161
 14790 % U+017E LATIN SMALL LETTER Z WITH CARON; zcaron
 14791 \DeclareTextCompositeCommand{\v}{\PD1}{z}{\236} % U+017E
 Slot \237 (0x9F) is not defined in PDFDocEncoding.
 The euro \240 is inserted in version 1.3 of the pdf specification.
 14792 % U+20AC EURO SIGN; *Euro, euro
 14793 \DeclareTextCommand{\texteuro}{\PD1}{\240} % U+20AC
 14794 % U+00A1 INVERTED EXCLAMATION MARK; exclamdown
 14795 \DeclareTextCommand{\textexclamdown}{\PD1}{\241} % U+00A1
 14796 % U+00A2 CENT SIGN; cent
 14797 \DeclareTextCommand{\textcent}{\PD1}{\242} % U+00A2
 14798 % U+00A3 POUND SIGN; sterling
 14799 \DeclareTextCommand{\textsterling}{\PD1}{\243} % U+00A3
 14800 % U+00A4 CURRENCY SIGN; currency
 14801 \DeclareTextCommand{\textcurrency}{\PD1}{\244} % U+00A4
 14802 % U+00A5 YEN SIGN; yen
 14803 \DeclareTextCommand{\textyen}{\PD1}{\245} % U+00A5
 14804 % U+00A6 BROKEN BAR; brokenbar
 14805 \DeclareTextCommand{\textbrokenbar}{\PD1}{\246} % U+00A6
 14806 % U+00A7 SECTION SIGN; section
 14807 \DeclareTextCommand{\textsection}{\PD1}{\247} % U+00A7
 14808 % U+00A8 DIAERESIS; dieresis
 14809 \DeclareTextCommand{\textasciidieresis}{\PD1}{\250} % U+00A8
 14810 % U+00A9 COPYRIGHT SIGN; copyright
 14811 \DeclareTextCommand{\textcopyright}{\PD1}{\251} % U+00A9
 14812 % U+00AA FEMININE ORDINAL INDICATOR; ordfeminine
 14813 \DeclareTextCommand{\textordfeminine}{\PD1}{\252} % U+00AA
 14814 % U+00AB LEFT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemetleft
 14815 \DeclareTextCommand{\guillemotleft}{\PD1}{\253} % U+00AB
 14816 \DeclareTextCommand{\guillemetleft}{\PD1}{\253} % U+00AB
 14817 % U+00AC NOT SIGN; logicalnot
 14818 \DeclareTextCommand{\textlogicalnot}{\PD1}{\254} % U+00AC
 14819 \DeclareTextCommand{\textlnot}{\PD1}{\254} % logical not
 No glyph \255 in PDFDocEncoding.
 14820 % U+00AE REGISTERED SIGN; registered
 14821 \DeclareTextCommand{\textregistered}{\PD1}{\256} % U+00AE
 14822 % U+00AF MACRON; *macron, overscore

```

14823 \DeclareTextCommand{\textasciimacron}{\PD1}{\257}%
14824 % U+00B0 DEGREE SIGN; degree
14825 \DeclareTextCommand{\textdegree}{\PD1}{\260}%
14826 % U+00B1 PLUS-MINUS SIGN; plusminus
14827 \DeclareTextCommand{\textplusminus}{\PD1}{\261}%
14828 % U+00B2 SUPERSCRIPT TWO; twosuperior
14829 \DeclareTextCommand{\texttwosuperior}{\PD1}{\262}%
14830 % U+00B3 SUPERSCRIPT THREE; threesuperior
14831 \DeclareTextCommand{\textthreesuperior}{\PD1}{\263}%
14832 % U+00B4 ACUTE ACCENT; acute
14833 \DeclareTextCommand{\textacute}{\PD1}{\264}%
14834 % U+00B5 MICRO SIGN; mu, mui
14835 \DeclareTextCommand{\textmu}{\PD1}{\265}%
14836 % U+00B6 PILCROW SIGN; paragraph
14837 \DeclareTextCommand{\textparagraph}{\PD1}{\266}%
14838 % U+00B7 MIDDLE DOT; middot, *periodcentered
14839 \DeclareTextCommand{\textperiodcentered}{\PD1}{\267}%
14840 % U+00B8 CEDILLA; cedilla
14841 \DeclareTextCommand{\textcedilla}{\PD1}{\270}%
14842 % U+00B9 SUPERSCRIPT ONE; onesuperior
14843 \DeclareTextCommand{\textonesuperior}{\PD1}{\271}%
14844 % U+00BA MASCULINE ORDINAL INDICATOR; ordmasculine
14845 \DeclareTextCommand{\textordmasculine}{\PD1}{\272}%
14846 % U+00BB RIGHT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemetright
14847 \DeclareTextCommand{\guillemotright}{\PD1}{\273}%
14848 \DeclareTextCommand{\guillemetright}{\PD1}{\273}%
14849 % U+00BC VULGAR FRACTION ONE QUARTER; onequarter
14850 \DeclareTextCommand{\textonequarter}{\PD1}{\274}%
14851 % U+00BD VULGAR FRACTION ONE HALF; onehalf
14852 \DeclareTextCommand{\textonehalf}{\PD1}{\275}%
14853 % U+00BE VULGAR FRACTION THREE QUARTERS; threequarters
14854 \DeclareTextCommand{\textthreequarters}{\PD1}{\276}%
14855 % U+00BF INVERTED QUESTION MARK; questiondown
14856 \DeclareTextCommand{\textquestiondown}{\PD1}{\277}%
14857 % U+00C0 LATIN CAPITAL LETTER A WITH GRAVE; Agrave
14858 \DeclareTextCompositeCommand{\`}{\PD1}{A}{\300}%
14859 % U+00C1 LATIN CAPITAL LETTER A WITH ACUTE; Aacute
14860 \DeclareTextCompositeCommand{\'}{\PD1}{A}{\301}%
14861 % U+00C2 LATIN CAPITAL LETTER A WITH CIRCUMFLEX; Acircumflex
14862 \DeclareTextCompositeCommand{\^}{\PD1}{A}{\302}%
14863 % U+00C3 LATIN CAPITAL LETTER A WITH TILDE; Atilde
14864 \DeclareTextCompositeCommand{\~}{\PD1}{A}{\303}%
14865 % U+00C4 LATIN CAPITAL LETTER A WITH DIAERESIS; Adieresis
14866 \DeclareTextCompositeCommand{\"}{\PD1}{A}{\304}%
14867 % U+00C5 LATIN CAPITAL LETTER A WITH RING ABOVE; Aring
14868 \DeclareTextCompositeCommand{\r}{\PD1}{A}{\305}%
14869 % U+00C6 LATIN CAPITAL LETTER AE; AE
14870 \DeclareTextCommand{\AE}{\PD1}{\306}%
14871 % U+00C7 LATIN CAPITAL LETTER C WITH CEDILLA; Ccedilla
14872 \DeclareTextCompositeCommand{\c}{\PD1}{C}{\307}%
14873 % U+00C8 LATIN CAPITAL LETTER E WITH GRAVE; Egrave
14874 \DeclareTextCompositeCommand{\`}{\PD1}{E}{\310}%
14875 % U+00C9 LATIN CAPITAL LETTER E WITH ACUTE; Eacute
14876 \DeclareTextCompositeCommand{\'}{\PD1}{E}{\311}%

```

14877 % U+00CA LATIN CAPITAL LETTER E WITH CIRCUMFLEX; Ecircumflex
14878 \DeclareTextCompositeCommand{\^}{PD1}{E}{\312}% U+00CA
14879 % U+00CB LATIN CAPITAL LETTER E WITH DIAERESIS; Edieresis
14880 \DeclareTextCompositeCommand{\"}{PD1}{E}{\313}% U+00CB
14881 % U+00CC LATIN CAPITAL LETTER I WITH GRAVE; Igrave
14882 \DeclareTextCompositeCommand{\`}{PD1}{I}{\314}% U+00CC
14883 % U+00CD LATIN CAPITAL LETTER I WITH ACUTE; Iacute
14884 \DeclareTextCompositeCommand{\'}{PD1}{I}{\315}% U+00CD
14885 % U+00CE LATIN CAPITAL LETTER I WITH CIRCUMFLEX; Icircumflex
14886 \DeclareTextCompositeCommand{\^}{PD1}{I}{\316}% U+00CE
14887 % U+00CF LATIN CAPITAL LETTER I WITH DIAERESIS; Idieresis
14888 \DeclareTextCompositeCommand{\"}{PD1}{I}{\317}% U+00CF
14889 % U+00D0 LATIN CAPITAL LETTER ETH; Eth
14890 \DeclareTextCommand{\DH}{PD1}{\320}% U+00D0
14891 \DeclareTextCommand{\DJ}{PD1}{\320}% U+00D0
14892 % U+00D1 LATIN CAPITAL LETTER N WITH TILDE; Ntilde
14893 \DeclareTextCompositeCommand{\~}{PD1}{N}{\321}% U+00D1
14894 % U+00D2 LATIN CAPITAL LETTER O WITH GRAVE; Ograve
14895 \DeclareTextCompositeCommand{\`}{PD1}{O}{\322}% U+00D2
14896 % U+00D3 LATIN CAPITAL LETTER O WITH ACUTE; Oacute
14897 \DeclareTextCompositeCommand{\'}{PD1}{O}{\323}% U+00D3
14898 % U+00D4 LATIN CAPITAL LETTER O WITH CIRCUMFLEX; Ocircumflex
14899 \DeclareTextCompositeCommand{\^}{PD1}{O}{\324}% U+00D4
14900 % U+00D5 LATIN CAPITAL LETTER O WITH TILDE; Otilde
14901 \DeclareTextCompositeCommand{\~}{PD1}{O}{\325}% U+00D5
14902 % U+00D6 LATIN CAPITAL LETTER O WITH DIAERESIS; Odieresis
14903 \DeclareTextCompositeCommand{\"}{PD1}{O}{\326}% U+00D6
14904 % U+00D7 MULTIPLICATION SIGN; multiply
14905 \DeclareTextCommand{\textmultiply}{PD1}{\327}% U+00D7
14906 % U+00D8 LATIN CAPITAL LETTER O WITH STROKE; Oslash
14907 \DeclareTextCommand{\O}{PD1}{\330}% U+00D8
14908 % U+00D9 LATIN CAPITAL LETTER U WITH GRAVE; Ugrave
14909 \DeclareTextCompositeCommand{\`}{PD1}{U}{\331}% U+00D9
14910 % U+00DA LATIN CAPITAL LETTER U WITH ACUTE; Uacute
14911 \DeclareTextCompositeCommand{\'}{PD1}{U}{\332}% U+00DA
14912 % U+00DB LATIN CAPITAL LETTER U WITH CIRCUMFLEX; Ucircumflex
14913 \DeclareTextCompositeCommand{\^}{PD1}{U}{\333}% U+00DB
14914 % U+00DC LATIN CAPITAL LETTER U WITH DIAERESIS; Udieresis
14915 \DeclareTextCompositeCommand{\"}{PD1}{U}{\334}% U+00DC
14916 % U+00DD LATIN CAPITAL LETTER Y WITH ACUTE; Yacute
14917 \DeclareTextCompositeCommand{\'}{PD1}{Y}{\335}% U+00DD
14918 % U+00DE LATIN CAPITAL LETTER THORN; Thorn; \TH, \Thorn (wasysym)
14919 \DeclareTextCommand{\TH}{PD1}{\336}% U+00DE
14920 \DeclareTextCommand{\textThorn}{PD1}{\336}/* U+00DE
14921 % U+00DF LATIN SMALL LETTER SHARP S; germandbls
14922 \DeclareTextCommand{\ss}{PD1}{\337}% U+00DF
14923 % U+00E0 LATIN SMALL LETTER A WITH GRAVE; agrave
14924 \DeclareTextCompositeCommand{\`}{PD1}{a}{\340}% U+00E0
14925 % U+00E1 LATIN SMALL LETTER A WITH ACUTE; aacute
14926 \DeclareTextCompositeCommand{\'}{PD1}{a}{\341}% U+00E1
14927 % U+00E2 LATIN SMALL LETTER A WITH CIRCUMFLEX; acircumflex
14928 \DeclareTextCompositeCommand{\^}{PD1}{a}{\342}% U+00E2
14929 % U+00E3 LATIN SMALL LETTER A WITH TILDE; atilde
14930 \DeclareTextCompositeCommand{\~}{PD1}{a}{\343}% U+00E3

14931 % U+00E4 LATIN SMALL LETTER A WITH DIAERESIS; adieresis
14932 \DeclareTextCompositeCommand{\\"}{PD1}{a}{\344}% U+00E4
14933 % U+00E5 LATIN SMALL LETTER A WITH RING ABOVE; aring
14934 \DeclareTextCompositeCommand{\r}{PD1}{a}{\345}% U+00E5
14935 % U+00E6 LATIN SMALL LETTER AE; ae
14936 \DeclareTextCommand{\ae}{PD1}{\346}% U+00E6
14937 % U+00E7 LATIN SMALL LETTER C WITH CEDILLA; ccedilla
14938 \DeclareTextCompositeCommand{\c}{PD1}{c}{\347}% U+00E7
14939 % U+00E8 LATIN SMALL LETTER E WITH GRAVE; egrave
14940 \DeclareTextCompositeCommand{\`}{PD1}{e}{\350}% U+00E8
14941 % U+00E9 LATIN SMALL LETTER E WITH ACUTE; eacute
14942 \DeclareTextCompositeCommand{\'}{PD1}{e}{\351}% U+00E9
14943 % U+00EA LATIN SMALL LETTER E WITH CIRCUMFLEX; ecircumflex
14944 \DeclareTextCompositeCommand{\^}{PD1}{e}{\352}% U+00EA
14945 % U+00EB LATIN SMALL LETTER E WITH DIAERESIS; edieresis
14946 \DeclareTextCompositeCommand{\\"}{PD1}{e}{\353}% U+00EB
14947 % U+00EC LATIN SMALL LETTER I WITH GRAVE; igrave
14948 \DeclareTextCompositeCommand{\`}{PD1}{i}{\354}% U+00EC
14949 \DeclareTextCompositeCommand{\`}{PD1}{i}{\354}% U+00EC
14950 % U+00ED LATIN SMALL LETTER I WITH ACUTE; iacute
14951 \DeclareTextCompositeCommand{\'}{PD1}{i}{\355}% U+00ED
14952 \DeclareTextCompositeCommand{\'}{PD1}{i}{\355}% U+00ED
14953 % U+00EE LATIN SMALL LETTER I WITH CIRCUMFLEX; icircumflex
14954 \DeclareTextCompositeCommand{\^}{PD1}{i}{\356}% U+00EE
14955 \DeclareTextCompositeCommand{\^}{PD1}{i}{\356}% U+00EE
14956 % U+00EF LATIN SMALL LETTER I WITH DIAERESIS; idieresis
14957 \DeclareTextCompositeCommand{\\"}{PD1}{i}{\357}% U+00EF
14958 \DeclareTextCompositeCommand{\\"}{PD1}{i}{\357}% U+00EF
14959 % U+00F0 LATIN SMALL LETTER ETH; eth
14960 \DeclareTextCommand{\dh}{PD1}{\360}% U+00F0
14961 % U+00F1 LATIN SMALL LETTER N WITH TILDE; ntilde
14962 \DeclareTextCompositeCommand{\~}{PD1}{n}{\361}% U+00F1
14963 % U+00F2 LATIN SMALL LETTER O WITH GRAVE; ograve
14964 \DeclareTextCompositeCommand{\`}{PD1}{o}{\362}% U+00F2
14965 % U+00F3 LATIN SMALL LETTER O WITH ACUTE; oacute
14966 \DeclareTextCompositeCommand{\'}{PD1}{o}{\363}% U+00F3
14967 % U+00F4 LATIN SMALL LETTER O WITH CIRCUMFLEX; ocircumflex
14968 \DeclareTextCompositeCommand{\^}{PD1}{o}{\364}% U+00F4
14969 % U+00F5 LATIN SMALL LETTER O WITH TILDE; otilde
14970 \DeclareTextCompositeCommand{\~}{PD1}{o}{\365}% U+00F5
14971 % U+00F6 LATIN SMALL LETTER O WITH DIAERESIS; odieresis
14972 \DeclareTextCompositeCommand{\\"}{PD1}{o}{\366}% U+00F6
14973 % U+00F7 DIVISION SIGN; divide
14974 \DeclareTextCommand{\textdivide}{PD1}{\367}% U+00F7
14975 % U+00F8 LATIN SMALL LETTER O WITH STROKE; oslash
14976 \DeclareTextCommand{\o}{PD1}{\370}% U+00F8
14977 % U+00F9 LATIN SMALL LETTER U WITH GRAVE; ugrave
14978 \DeclareTextCompositeCommand{\`}{PD1}{u}{\371}% U+00F9
14979 % U+00FA LATIN SMALL LETTER U WITH ACUTE; uacute
14980 \DeclareTextCompositeCommand{\'}{PD1}{u}{\372}% U+00FA
14981 % U+00FB LATIN SMALL LETTER U WITH CIRCUMFLEX; ucircumflex
14982 \DeclareTextCompositeCommand{\^}{PD1}{u}{\373}% U+00FB
14983 % U+00FC LATIN SMALL LETTER U WITH DIAERESIS; udieresis
14984 \DeclareTextCompositeCommand{\\"}{PD1}{u}{\374}% U+00FC

```

14985 % U+00FD LATIN SMALL LETTER Y WITH ACUTE; yacute
14986 \DeclareTextCompositeCommand{\'}{PD1}{y}{\375}% U+00FD
14987 % U+00FE LATIN SMALL LETTER THORN; thorn; \th, \thorn (wasysym)
14988 \DeclareTextCommand{\th}{PD1}{\376}% U+00FE
14989 \DeclareTextCommand{\textthorn}{PD1}{\376}/* U+00FE
14990 % U+00FF LATIN SMALL LETTER Y WITH DIAERESIS; ydieresis
14991 \DeclareTextCompositeCommand{\\"}{PD1}{y}{\377}% U+00FF
14992 \DeclareTextCommand{\ij}{PD1}{ij}% ligature U+0069 U+006A

Glyphs that consist of several characters.
14993 \DeclareTextCommand{\SS}{PD1}{SS}%
14994 \DeclareTextCommand{\textcelsius}{PD1}{\textdegree C}%

Aliases (german.sty)
14995 \DeclareTextCommand{\textglqq}{PD1}{\quotedblbase}%
14996 \DeclareTextCommand{\textgrqq}{PD1}{\textquotedblleft}%
14997 \DeclareTextCommand{\textglq}{PD1}{\quotesinglbase}%
14998 \DeclareTextCommand{\textgrq}{PD1}{\textquotelleft}%
14999 \DeclareTextCommand{\textflqq}{PD1}{\guillemetleft}%
15000 \DeclareTextCommand{\textfrqq}{PD1}{\guillemetright}%
15001 \DeclareTextCommand{\textflq}{PD1}{\guilsingleleft}%
15002 \DeclareTextCommand{\textfrq}{PD1}{\guilsinglright}%

Aliases (math names)
15003 \DeclareTextCommand{\textneg}{PD1}{\textlogicalnot}%
15004 \DeclareTextCommand{\texttimes}{PD1}{\textmultiply}%
15005 \DeclareTextCommand{\textdiv}{PD1}{\textdivide}%
15006 \DeclareTextCommand{\textpm}{PD1}{\textplusminus}%
15007 \DeclareTextCommand{\textdot}{PD1}{\textperiodcentered}%
15008 \DeclareTextCommand{\textbeta}{PD1}{\ss}%

Polish aliases. PDF encoding does not have the characters, but it is useful to Poles
to have the plain letters regardless. Requested by Wojciech Myszka (W.Myszka@immt.pwr.wroc.pl).
15009 \DeclareTextCompositeCommand{\k}{PD1}{a}{a}% aogonek
15010 \DeclareTextCompositeCommand{\'}{PD1}{c}{c}% cacute
15011 \DeclareTextCompositeCommand{\k}{PD1}{e}{e}% eogonek
15012 \DeclareTextCompositeCommand{\'}{PD1}{n}{n}% nacute
15013 \DeclareTextCompositeCommand{\'}{PD1}{s}{s}% sacute
15014 \DeclareTextCompositeCommand{\'}{PD1}{z}{z}% zacute
15015 \DeclareTextCompositeCommand{\.}{PD1}{z}{z}% zdot
15016 \DeclareTextCompositeCommand{\k}{PD1}{A}{A}% Aogonek
15017 \DeclareTextCompositeCommand{\'}{PD1}{C}{C}% Cacute
15018 \DeclareTextCompositeCommand{\k}{PD1}{E}{E}% Eogonek
15019 \DeclareTextCompositeCommand{\'}{PD1}{N}{N}% Nacute
15020 \DeclareTextCompositeCommand{\'}{PD1}{S}{S}% Sacute
15021 \DeclareTextCompositeCommand{\'}{PD1}{Z}{Z}% Zacute
15022 \DeclareTextCompositeCommand{\.}{PD1}{Z}{Z}% Zdot
15023 
```

46.2 PU encoding

```

15024 <*puenc>
15025 \DeclareFontEncoding{PU}{}{}
```

46.2.1 NFSS2 accents

```

15026 % U+0300 COMBINING GRAVE ACCENT; gravecmb, *gravecomb
15027 \DeclareTextCommand{\`}{PU}[1]{#1\83\000}% U+0300
15028 % U+0301 COMBINING ACUTE ACCENT; acutecmb, *acutecomb
15029 \DeclareTextCommand{\'}{PU}[1]{#1\83\001}% U+0301
15030 % U+0302 COMBINING CIRCUMFLEX ACCENT; circumflexcmb
15031 \DeclareTextCommand{\^}{PU}[1]{#1\83\002}% U+0302
15032 % U+0303 COMBINING TILDE; tildecmb, *tildecomb
15033 \DeclareTextCommand{\~}{PU}[1]{#1\83\003}% U+0303
15034 % U+0304 COMBINING MACRON; macroncmb
15035 \DeclareTextCommand{\=}{PU}[1]{#1\83\004}% U+0304
15036 % U+0306 COMBINING BREVE; brevecmb
15037 \DeclareTextCommand{\u}{PU}[1]{#1\83\006}% U+0306
15038 \ifx\CYRDZE\@undefined \else
15039 \DeclareTextCommand{\U}{PU}[1]{#1\83\006}% U+0306
15040 \fi
15041 % U+0307 COMBINING DOT ABOVE; dotaccentcmb
15042 \DeclareTextCommand{\.}{PU}[1]{#1\83\007}% U+0307
15043 % U+0308 COMBINING DIAERESIS; dieresiscmb
15044 \DeclareTextCommand{\"}{PU}[1]{#1\83\010}% U+0308
15045 % U+030A COMBINING RING ABOVE; ringcmb
15046 \DeclareTextCommand{\r}{PU}[1]{#1\83\012}% U+030A
15047 % U+030B COMBINING DOUBLE ACUTE ACCENT; hungarumlautcmb
15048 \DeclareTextCommand{\H}{PU}[1]{#1\83\013}% U+030B
15049 % U+030C COMBINING CARON; caroncmb
15050 \DeclareTextCommand{\v}{PU}[1]{#1\83\014}% U+030C
15051 </puenc>
15052 % U+030F COMBINING DOUBLE GRAVE ACCENT; dblgravecmb
15053 <puxtra>\DeclareTextCommand{\G}{PU}[1]{#1\83\017}% U+030F
15054 <*puenc>
15055 \ifx\CYRDZE\@undefined \else
15056 \DeclareTextCommand{\C}{PU}[1]{#1\83\017}% U+030F
15057 \fi
15058 % U+0311 COMBINING INVERTED BREVE; breveinvertedcmb
15059 \DeclareTextCommand{\textinvbreve}{PU}[1]{#1\83\021}% U+0311
15060 \DeclareTextCommand{\newtie}{PU}[1]{#1\83\021}% U+0311
15061 % U+0323 COMBINING DOT BELOW; dotbelowcmb, *dotbelowcomb
15062 \DeclareTextCommand{\d}{PU}[1]{#1\83\043}% U+0323
15063 % U+0324 COMBINING DIAERESIS BELOW; dieresisbelowcmb; \textsubum-
laut (tipa)
15064 \DeclareTextCommand{\textsubumlaut}{PU}[1]{#1\83\044}% U+0324
15065 % U+0325 COMBINING RING BELOW; ringbelowcmb; \textsubring (tipa)
15066 \DeclareTextCommand{\textsubring}{PU}[1]{#1\83\045}% U+0325
15067 % U+0327 COMBINING CEDILLA; cedillacmb
15068 \DeclareTextCommand{\c}{PU}[1]{#1\83\047}% U+0327
15069 % U+0328 COMBINING OGONEK; ogonekcmb
15070 \DeclareTextCommand{\k}{PU}[1]{#1\83\050}% U+0328
15071 % U+032D COMBINING CIRCUMFLEX ACCENT BELOW;
15072 % \textsubcircum (tipa)
15073 \DeclareTextCommand{\textsubcircum}{PU}[1]{#1\83\055}% U+032D
15074 % U+032E COMBINING BREVE BELOW; brevebelowcmb
15075 \DeclareTextCommand{\textsubbreve}{PU}[1]{#1\83\056}% U+032E
15076 % U+0330 COMBINING TILDE BELOW; tildebelowcmb; \textsubtilde (tipa)
15077 \DeclareTextCommand{\textsubtilde}{PU}[1]{#1\83\060}% U+0330
15078 % U+0331 COMBINING MACRON BELOW; macronbelowcmb

```

```

15079 \DeclareTextCommand{\b}{PU}[1]{#1\83\061}% U+0331
15080 % U+0361 COMBINING DOUBLE INVERTED BREVE; breveinverteddou-
blecmb
15081 \DeclareTextCommand{\t}{PU}[1]{#1\83\141}% U+0361
15082 % U+20DD COMBINING ENCLOSING CIRCLE
15083 \DeclareTextCommand{\textcircled}{PU}[1]{#1\9040\335}% U+20DD

    Double accents.

15084 \DeclareTextCommand{\textacutemacron}{PU}[1]{#1\83\001\83\004}% U+0301 U+0304
15085 \DeclareTextCommand{\textgravemacron}{PU}[1]{#1\83\000\83\004}% U+0300 U+0304

    \Cempty is an artefact of the NFSS2 machinery, it gets inserted for empty
arguments and spaces.

15086 \DeclareTextCompositeCommand{\`}{PU}{\Cempty}{\textasciigrave}%
15087 \DeclareTextCompositeCommand{\'}{PU}{\Cempty}{\textacute}%
15088 \DeclareTextCompositeCommand{\^}{PU}{\Cempty}{\textasciicircum}%
15089 \DeclareTextCompositeCommand{\~}{PU}{\Cempty}{\texttilde}%
15090 \DeclareTextCompositeCommand{\"}{PU}{\Cempty}{\textasciidieresis}%
15091 \DeclareTextCompositeCommand{\r}{PU}{\Cempty}{\textring}%
15092 \DeclareTextCompositeCommand{\v}{PU}{\Cempty}{\textasciicaron}%
15093 \DeclareTextCompositeCommand{\.}{PU}{\Cempty}{\textdotaccent}%
15094 \DeclareTextCompositeCommand{\c}{PU}{\Cempty}{\textcedilla}%
15095 \DeclareTextCompositeCommand{\u}{PU}{\Cempty}{\textasciibreve}%
15096 </puenc>
15097 <puxtra>\DeclareTextCompositeCommand{\G}{PU}{\Cempty}{\textdoublegrave}%
15098 </puenc>
15099 \DeclareTextCompositeCommand{\=}{PU}{\Cempty}{\textasciimacron}%
15100 \DeclareTextCompositeCommand{\H}{PU}{\Cempty}{\texthungarumlaut}%
15101 \DeclareTextCompositeCommand{\k}{PU}{\Cempty}{\textogonek}%
15102 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\Cempty}{\text\83\021}}% U+0311
15103 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{\Cempty}{\text\83\044}}% U+0324
15104 \DeclareTextCompositeCommand{\textsubring}{PU}{\Cempty}{\textringlow}%
15105 \DeclareTextCompositeCommand{\textsubcircum}{PU}{\Cempty}{\textcircum-
low}%
15106 \DeclareTextCompositeCommand{\textsubbreve}{PU}{\Cempty}{\text\83\056}}% U+032E
15107 \DeclareTextCompositeCommand{\textsubtilde}{PU}{\Cempty}{\texttildebelow}%
15108 \DeclareTextCompositeCommand{\b}{PU}{\Cempty}{\textmacronbelow}%
15109 \DeclareTextCompositeCommand{\d}{PU}{\Cempty}{\textdotbelow}%
15110 \DeclareTextCompositeCommand{\t}{PU}{\Cempty}{\texttie}%
15111 \DeclareTextCompositeCommand{\newtie}{PU}{\Cempty}{\textnewtie}%
15112 \DeclareTextCompositeCommand{\textcircled}{PU}{\Cempty}{\textbigcircle}%
15113 \DeclareTextCompositeCommand{\textacutemacron}{PU}{\Cempty}{\text\83\001\83\004}}% U+0301 U+0304
15114 \DeclareTextCompositeCommand{\textgravemacron}{PU}{\Cempty}{\text\83\000\83\004}}% U+0300 U+0304
15115 \DeclareTextCompositeCommand{\`}{PU}{\ }{\textasciigrave}%
15116 \DeclareTextCompositeCommand{\'}{PU}{\ }{\textacute}%
15117 \DeclareTextCompositeCommand{\^}{PU}{\ }{\textasciicircum}%
15118 \DeclareTextCompositeCommand{\~}{PU}{\ }{\texttilde}%
15119 \DeclareTextCompositeCommand{\"}{PU}{\ }{\textasciidieresis}%
15120 \DeclareTextCompositeCommand{\r}{PU}{\ }{\textring}%
15121 \DeclareTextCompositeCommand{\v}{PU}{\ }{\textasciicaron}%
15122 \DeclareTextCompositeCommand{\.}{PU}{\ }{\textdotaccent}%
15123 \DeclareTextCompositeCommand{\c}{PU}{\ }{\textcedilla}%
15124 \DeclareTextCompositeCommand{\u}{PU}{\ }{\textasciibreve}%
15125 </puenc>
15126 <puxtra>\DeclareTextCompositeCommand{\G}{PU}{\ }{\textdoublegrave}%

```

```

15127 <*puenc>
15128 \DeclareTextCompositeCommand{\=}{PU}{\ }{\textasciimacron}%
15129 \DeclareTextCompositeCommand{\H}{PU}{\ }{\texthungarumlaut}%
15130 \DeclareTextCompositeCommand{\k}{PU}{\ }{\textogonek}%
15131 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\ }{\text{\83\021}}% U+0311
15132 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{\ }{\text{\83\044}}% U+0324
15133 \DeclareTextCompositeCommand{\textsubring}{PU}{\ }{\textstringlow}%
15134 \DeclareTextCompositeCommand{\textsubcircum}{PU}{\ }{\textcircumlow}%
15135 \DeclareTextCompositeCommand{\textsub breve}{PU}{\ }{\text{\83\056}}% U+032E
15136 \DeclareTextCompositeCommand{\textsubtilde}{PU}{\ }{\texttildebelow}%
15137 \DeclareTextCompositeCommand{\b}{PU}{\ }{\textmacronbelow}%
15138 \DeclareTextCompositeCommand{\d}{PU}{\ }{\textdotbelow}%
15139 \DeclareTextCompositeCommand{\t}{PU}{\ }{\texttie}%
15140 \DeclareTextCompositeCommand{\newtie}{PU}{\ }{\textnewtie}%
15141 \DeclareTextCompositeCommand{\textcircled}{PU}{\ }{\textbigcircle}%
15142 \DeclareTextCompositeCommand{\textacute macron}{PU}{\ }{\text{\83\001\83\004}}% U+0301 U+0304
15143 \DeclareTextCompositeCommand{\textgrave macron}{PU}{\ }{\text{\83\000\83\004}}% U+0300 U+0304

```

Accents for capitals (see encoding TS1)

```

15144 \DeclareTextCommand{\capitalcedilla}{PU}[1]{\c{#1}}%
15145 \DeclareTextCommand{\capitalogonek}{PU}[1]{\k{#1}}%
15146 \DeclareTextCommand{\capitalgrave}{PU}[1]{\`{#1}}%
15147 \DeclareTextCommand{\capitalacute}{PU}[1]{\'{#1}}%
15148 \DeclareTextCommand{\capitalcircumflex}{PU}[1]{\^{\#1}}%
15149 \DeclareTextCommand{\capitaltilde}{PU}[1]{\~{\#1}}%
15150 \DeclareTextCommand{\capitaldieresis}{PU}[1]{\"{\#1}}%
15151 \DeclareTextCommand{\capitalhungarumlaut}{PU}[1]{\H{\#1}}%
15152 \DeclareTextCommand{\capitalring}{PU}[1]{\r{\#1}}%
15153 \DeclareTextCommand{\capitalcaron}{PU}[1]{\v{\#1}}%
15154 \DeclareTextCommand{\capitalbreve}{PU}[1]{\u{\#1}}%
15155 \DeclareTextCommand{\capitalmacron}{PU}[1]{\={#1}}%
15156 \DeclareTextCommand{\capitaldotaccent}{PU}[1]{\.\{#1}}%
15157 \DeclareTextCommand{\capitaltie}{PU}[1]{\t{\#1}}%
15158 \DeclareTextCommand{\capitalnewtie}{PU}[1]{\newtie{\#1}}%

```

46.2.2 Basic Latin: U+0000 to U+007F

Special white space escape characters.

```

15159 % U+0009 (CHARACTER TABULATION)
15160 \DeclareTextCommand{\textHT}{PU}{\80\011}% U+0009
15161 % U+000A (LINE FEED)
15162 \DeclareTextCommand{\textLF}{PU}{\80\012}% U+000A
15163 % U+000D (CARRIAGE RETURN)
15164 \DeclareTextCommand{\textCR}{PU}{\80\015}% U+000D
\80\040: U+0020 SPACE; space, spacehackarabic
\80\041: U+0021 EXCLAMATION MARK; exclam
15165 % U+0022 QUOTATION MARK; quotedbl
15166 \DeclareTextCommand{\textquotedbl}{PU}{"}% \80\042 U+0022
15167 % U+0023 NUMBER SIGN; numbersign
15168 \DeclareTextCommand{\textnumbersign}{PU}{\80\043}% U+0023
15169 % U+0024 DOLLAR SIGN; dollar
15170 \DeclareTextCommand{\textdollar}{PU}{\80\044}% U+0024
15171 %* \textdollar -> \mathdollar
15172 %* \textdollar -> \EyesDollar (marvosym)
15173 % U+0025 PERCENT SIGN; percent

```

```

15174 \DeclareTextCommand{\textpercent}{\PU}{\80\045}% U+0025
15175 % U+0026 AMPERSAND; ampersand
15176 \DeclareTextCommand{\textampersand}{\PU}{\80\046}% U+0026
15177 %* \textampersand -> \binampersand (stmaryrd)
15178 %* \textampersand -> \with (cmll)
15179 % U+0027 APOSTROPHE; quotesingle
15180 \DeclareTextCommand{\textquotesingle}{\PU}{\80\047}% U+0027
15181 % U+0028 LEFT PARENTHESIS; parenleft
15182 \DeclareTextCommand{\textparenleft}{\PU}{\80\050}% U+0028
15183 % U+0029 RIGHT PARENTHESIS; parenright
15184 \DeclareTextCommand{\textparenright}{\PU}{\80\051}% U+0029
15185 % U+002A ASTERISK; asterisk; (?)
15186 \DeclareTextCommand{\textasteriskcentered}{\PU}{\80\052}% U+002A
15187 % U+002B PLUS SIGN; plus; \MVPlus (marvosym)
15188 \DeclareTextCommand{\textMVPlus}{\PU}{\80\053} %* U+002B
15189 % U+002C COMMA; comma; \MVCcomma (marvosym)
15190 \DeclareTextCommand{\textMVCcomma}{\PU}{\80\054} %* U+002C
15191 % U+002D HYPHEN-MINUS; hyphen; \MVMminus (marvosym)
15192 \DeclareTextCommand{\textMVMminus}{\PU}{\80\055} %* U+002D
15193 % U+002E FULL STOP; period; \MVPeriod (marvosym)
15194 \DeclareTextCommand{\textMVPeriod}{\PU}{\80\056} %* U+002E
15195 % U+002F SOLIDUS; slash; \MVDivision (marvosym)
15196 \DeclareTextCommand{\textMVDivision}{\PU}{\80\057} %* U+002F
15197 % U+0030 DIGIT ZERO; zero; \MVZero (marvosym)
15198 \DeclareTextCommand{\textMVZero}{\PU}{\80\060} %* U+0030
15199 % U+0031 DIGIT ONE; one; \MVOne (marvosym)
15200 \DeclareTextCommand{\textMVOne}{\PU}{\80\061} %* U+0031
15201 % U+0032 DIGIT TWO; two; \MVTtwo (marvosym)
15202 \DeclareTextCommand{\textMVTtwo}{\PU}{\80\062} %* U+0032
15203 % U+0033 DIGIT THREE; three; \MVTthree (marvosym)
15204 \DeclareTextCommand{\textMVTthree}{\PU}{\80\063} %* U+0033
15205 % U+0034 DIGIT FOUR; four; \MVFour (marvosym)
15206 \DeclareTextCommand{\textMVFour}{\PU}{\80\064} %* U+0034
15207 % U+0035 DIGIT FIVE; five; \MVFive (marvosym)
15208 \DeclareTextCommand{\textMVFive}{\PU}{\80\065} %* U+0035
15209 % U+0036 DIGIT SIX; six; \MVSix (marvosym)
15210 \DeclareTextCommand{\textMVSix}{\PU}{\80\066} %* U+0036
15211 % U+0037 DIGIT SEVEM; seven; \MVSseven (marvosym)
15212 \DeclareTextCommand{\textMVSseven}{\PU}{\80\067} %* U+0037
15213 % U+0038 DIGIT EIGHT; eight; \MVEight (marvosym)
15214 \DeclareTextCommand{\textMVEight}{\PU}{\80\070} %* U+0038
15215 % U+0039 DIGIT NINE; nine; \MVNine (marvosym)
15216 \DeclareTextCommand{\textMVNine}{\PU}{\80\071} %* U+0039
\80\072: U+003A COLON; colon
\80\073: U+003B SEMICOLON; semicolon
15217 % U+003C LESS-THAN SIGN; less
15218 \DeclareTextCommand{\textless}{\PU}{<}% \80\074 U+003C
\80\075: U+003D EQUALS SIGN; equal
15219 % U+003E GREATER-THAN SIGN; greater
15220 \DeclareTextCommand{\textgreater}{\PU}{>}% \80\076 U+003E
\80\077: U+003F QUESTION MARK; question
15221 % U+0040 COMMERCIAL AT; at; \MVAat (marvosym)

```

```

15222 \DeclareTextCommand{\textMVAt}{PU}{\80\100}/* U+0040
\80\101: U+0041 LATIN CAPITAL LETTER A; A
...
\80\132: U+005A LATIN CAPITAL LETTER Z; Z
\80\133: U+005B LEFT SQUARE BRACKET; bracketleft
15223 % U+005C REVERSE SOLIDUS; backslash
15224 \DeclareTextCommand{\textbackslash}{PU}{\80\134}% U+005C
\80\135: U+005D RIGHT SQUARE BRACKET; bracketright
15225 % U+005E CIRCUMFLEX ACCENT; asciicircum
15226 \DeclareTextCommand{\textasciicircum}{PU}{\80\136}% U+005E
15227 % U+005F LOW LINE; underscore
15228 \DeclareTextCommand{\textunderscore}{PU}{\80\137}% U+005F
15229 /* \textunderscore -> \mathunderscore (LaTeX)
15230 % U+0060 GRAVE ACCENT; grave
15231 \DeclareTextCommand{\textasciigrave}{PU}{\80\140}% U+0060
\80\141: U+0061 LATIN SMALL LETTER A; a
...
\80\150: U+0068 LATIN SMALL LETTER H; h
15232 % U+0069 LATIN SMALL LETTER I; i
15233 \DeclareTextCompositeCommand{.}{PU}{\i}{i} \% \80\151 U+0069
15234 \DeclareTextCompositeCommand{.}{PU}{i}{i} \% \80\151 U+0069
\80\152: U+006A LATIN SMALL LETTER J; j
...
\80\172: U+007A LATIN SMALL LETTER Z; z
15235 % U+007B LEFT CURLY BRACKET; braceleft
15236 \DeclareTextCommand{\textbraceleft}{PU}{\80\173}% U+007B
15237 % U+007C VERTICAL LINE; *bar, verticalbar
15238 \DeclareTextCommand{\textbar}{PU}{\80\174} U+007C
15239 /* \textbar -> \textvertline (tipa)
15240 % U+007D RIGHT CURLY BRACKET; braceright
15241 \DeclareTextCommand{\textbraceright}{PU}{\80\175}% U+007D
15242 % U+007E TILDE; asciitilde
15243 \DeclareTextCommand{\textasciitilde}{PU}{\80\176}% U+007E

```

46.2.3 Latin-1 Supplement: U+0080 to U+00FF

```

\80\240: U+00A0 NO-BREAK SPACE; nbspace, nonbreakingspace
15244 % U+00A1 INVERTED EXCLAMATION MARK; exclamdown
15245 \DeclareTextCommand{\texTEXCLAMDOWN}{PU}{\80\241}% U+00A1
15246 % U+00A2 CENT SIGN; cent
15247 \DeclareTextCommand{\textcent}{PU}{\80\242}% U+00A2
15248 % U+00A3 POUND SIGN; sterling
15249 \DeclareTextCommand{\textsterling}{PU}{\80\243}% U+00A3
15250 /* \textsterling -> \mathsterling (LaTeX)
15251 /* \textsterling -> \pounds (LaTeX)
15252 % U+00A4 CURRENCY SIGN; currency
15253 \DeclareTextCommand{\textcurrency}{PU}{\80\244}% U+00A4
15254 % U+00A5 YEN SIGN; yen
15255 \DeclareTextCommand{\textyen}{PU}{\80\245}% U+00A5
15256 % U+00A6 BROKEN BAR; brokenbar
15257 \DeclareTextCommand{\textbrokenbar}{PU}{\80\246}% U+00A6

```

```

15258 %* \textbrokenbar -> \brokenvert (wasysym)
15259 % U+00A7 SECTION SIGN; section
15260 \DeclareTextCommand{\textsection}{\PU}{\80\247}% U+00A7
15261 %* \textsection -> \mathsection (LaTeX)
15262 %* \textsection -> \S (LaTeX)
15263 % U+00A8 DIAERESIS; dieresis
15264 \DeclareTextCommand{\textasciidieresis}{\PU}{\80\250}% U+00A8
15265 % U+00A9 COPYRIGHT SIGN; copyright
15266 \DeclareTextCommand{\textcopyright}{\PU}{\80\251}%* U+00A9
15267 % U+00AA FEMININE ORDINAL INDICATOR; ordfeminine
15268 \DeclareTextCommand{\textordfeminine}{\PU}{\80\252}% U+00AA
15269 % U+00AB LEFT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemetleft
15270 \DeclareTextCommand{\guillemotleft}{\PU}{\80\253}% U+00AB
15271 \DeclareTextCommand{\guillemetleft}{\PU}{\80\253}% U+00AB
15272 % U+00AC NOT SIGN; logicalnot
15273 \DeclareTextCommand{\textlogicalnot}{\PU}{\80\254}% U+00AC
15274 \DeclareTextCommand{\textlnot}{\PU}{\80\254}% U+00AC
\80\255: U+00AD SOFT HYPHEN; sfthyphen, softhyphen
15275 % U+00AE REGISTERED SIGN; registered
15276 \DeclareTextCommand{\textregistered}{\PU}{\80\256}% U+00AE
15277 % U+00AF MACRON; *macron, overscore
15278 \DeclareTextCommand{\textasciimacron}{\PU}{\80\257}% U+00AF
15279 % U+00B0 DEGREE SIGN; degree
15280 \DeclareTextCommand{\textdegree}{\PU}{\80\260}% U+00B0
15281 % U+00B1 PLUS-MINUS SIGN; plusminus
15282 \DeclareTextCommand{\textplusminus}{\PU}{\80\261}% U+00B1
15283 % U+00B2 SUPERSCRIPT TWO; twosuperior
15284 \DeclareTextCommand{\texttwosuperior}{\PU}{\80\262}%* U+00B2
15285 % U+00B3 SUPERSCRIPT THREE; threesuperior
15286 \DeclareTextCommand{\textthreesuperior}{\PU}{\80\263}%* U+00B3
15287 % U+00B4 ACUTE ACCENT; acute
15288 \DeclareTextCommand{\textacute}{\PU}{\80\264}% U+00B4
15289 \DeclareTextCommand{\textasciiacute}{\PU}{\80\264}% U+00B4
15290 % U+00B5 MICRO SIGN; mu, mu1
15291 \DeclareTextCommand{\textmu}{\PU}{\80\265}% U+00B5
15292 % U+00B6 PILCROW SIGN; paragraph
15293 \DeclareTextCommand{\textparagraph}{\PU}{\80\266}% U+00B6
15294 %* \textparagraph -> \mathparagraph (LaTeX)
15295 % U+00B7 MIDDLE DOT; middot, *periodcentered
15296 \DeclareTextCommand{\textperiodcentered}{\PU}{\80\267}% U+00B7
15297 %* \textperiodcentered -> \MultiplicationDot (marvosym)
15298 %* \textperiodcentered -> \Squaredot (marvosym)
15299 % U+00B8 CEDILLA; cedilla
15300 \DeclareTextCommand{\textcedilla}{\PU}{\80\270}% U+00B8
15301 % U+00B9 SUPERSCRIPT ONE; onesuperior
15302 \DeclareTextCommand{\textonesuperior}{\PU}{\80\271}%* U+00B9
15303 % U+00BA MASCULINE ORDINAL INDICATOR; ordmasculine
15304 \DeclareTextCommand{\textordmasculine}{\PU}{\80\272}% U+00BA
15305 % U+00BB RIGHT-POINTING DOUBLE ANGLE QUOTATION MARK; guillemetright
15306 \DeclareTextCommand{\guillemotright}{\PU}{\80\273}% U+00BB
15307 \DeclareTextCommand{\guillemetright}{\PU}{\80\273}% U+00BB
15308 % U+00BC VULGAR FRACTION ONE QUARTER; onequarter
15309 \DeclareTextCommand{\textonequarter}{\PU}{\80\274}% U+00BC
15310 % U+00BD VULGAR FRACTION ONE HALF; onehalf

```

```

15311 \DeclareTextCommand{\textonehalf}{PU}{\80\275}% U+00BD
15312 % U+00BE VULGAR FRACTION THREE QUARTERS; threequarters
15313 \DeclareTextCommand{\textthreequarters}{PU}{\80\276}% U+00BE
15314 % U+00BF INVERTED QUESTION MARK; questiondown
15315 \DeclareTextCommand{\textquestiondown}{PU}{\80\277}% U+00BF
15316 % U+00C0 LATIN CAPITAL LETTER A WITH GRAVE; Agrave
15317 \DeclareTextCompositeCommand{\`}{PU}{A}{\80\300}% U+00C0
15318 % U+00C1 LATIN CAPITAL LETTER A WITH ACUTE; Aacute
15319 \DeclareTextCompositeCommand{\'}{PU}{A}{\80\301}% U+00C1
15320 % U+00C2 LATIN CAPITAL LETTER A WITH CIRCUMFLEX; Acircumflex
15321 \DeclareTextCompositeCommand{\^}{PU}{A}{\80\302}% U+00C2
15322 % U+00C3 LATIN CAPITAL LETTER A WITH TILDE; Atilde
15323 \DeclareTextCompositeCommand{\~}{PU}{A}{\80\303}% U+00C3
15324 % U+00C4 LATIN CAPITAL LETTER A WITH DIAERESIS; Adieresis
15325 \DeclareTextCompositeCommand{\"}{PU}{A}{\80\304}% U+00C4
15326 % U+00C5 LATIN CAPITAL LETTER A WITH RING ABOVE; Aring
15327 \DeclareTextCompositeCommand{\r}{PU}{A}{\80\305}% U+00C5
15328 % U+00C6 LATIN CAPITAL LETTER AE; AE
15329 \DeclareTextCommand{\AE}{PU}{\80\306}% U+00C6
15330 % U+00C7 LATIN CAPITAL LETTER C WITH CEDILLA; Ccedilla
15331 \DeclareTextCompositeCommand{\c}{PU}{C}{\80\307}% U+00C7
15332 % U+00C8 LATIN CAPITAL LETTER E WITH GRAVE; Egrave
15333 \DeclareTextCompositeCommand{\`}{PU}{E}{\80\310}% U+00C8
15334 % U+00C9 LATIN CAPITAL LETTER E WITH ACUTE; Eacute
15335 \DeclareTextCompositeCommand{\'}{PU}{E}{\80\311}% U+00C9
15336 % U+00CA LATIN CAPITAL LETTER E WITH CIRCUMFLEX; Ecircumflex
15337 \DeclareTextCompositeCommand{\^}{PU}{E}{\80\312}% U+00CA
15338 % U+00CB LATIN CAPITAL LETTER E WITH DIAERESIS; Edieresis
15339 \DeclareTextCompositeCommand{\\"}{PU}{E}{\80\313}% U+00CB
15340 % U+00CC LATIN CAPITAL LETTER I WITH GRAVE; Igrave
15341 \DeclareTextCompositeCommand{\`}{PU}{I}{\80\314}% U+00CC
15342 % U+00CD LATIN CAPITAL LETTER I WITH ACUTE; Iacute
15343 \DeclareTextCompositeCommand{\'}{PU}{I}{\80\315}% U+00CD
15344 % U+00CE LATIN CAPITAL LETTER I WITH CIRCUMFLEX; Icircumflex
15345 \DeclareTextCompositeCommand{\^}{PU}{I}{\80\316}% U+00CE
15346 % U+00CF LATIN CAPITAL LETTER I WITH DIAERESIS; Idieresis
15347 \DeclareTextCompositeCommand{\\"}{PU}{I}{\80\317}% U+00CF
15348 % U+00D0 LATIN CAPITAL LETTER ETH; Eth
15349 \DeclareTextCommand{\DH}{PU}{\80\320}% U+00D0
15350 % U+00D1 LATIN CAPITAL LETTER N WITH TILDE; Ntilde
15351 \DeclareTextCompositeCommand{\~}{PU}{N}{\80\321}% U+00D1
15352 % U+00D2 LATIN CAPITAL LETTER O WITH GRAVE; Ograve
15353 \DeclareTextCompositeCommand{\`}{PU}{O}{\80\322}% U+00D2
15354 % U+00D3 LATIN CAPITAL LETTER O WITH ACUTE; Oacute
15355 \DeclareTextCompositeCommand{\'}{PU}{O}{\80\323}% U+00D3
15356 % U+00D4 LATIN CAPITAL LETTER O WITH CIRCUMFLEX; Ocircumflex
15357 \DeclareTextCompositeCommand{\^}{PU}{O}{\80\324}% U+00D4
15358 % U+00D5 LATIN CAPITAL LETTER O WITH TILDE; Otilde
15359 \DeclareTextCompositeCommand{\~}{PU}{O}{\80\325}% U+00D5
15360 % U+00D6 LATIN CAPITAL LETTER O WITH DIAERESIS; Odieresis
15361 \DeclareTextCompositeCommand{\\"}{PU}{O}{\80\326}% U+00D6
15362 % U+00D7 MULTIPLICATION SIGN; multiply
15363 \DeclareTextCommand{\textmultiply}{PU}{\80\327}% U+00D7
15364 %* \textmultiply -> \vartimes (stmaryrd)

```

```

15365 %* \textmultiply -> \MVMultiplication (marvosym)
15366 % U+00D8 LATIN CAPITAL LETTER O WITH STROKE; Oslash
15367 \DeclareTextCommand{\O}{\PU}{\80\330} U+00D8
15368 % U+00D9 LATIN CAPITAL LETTER U WITH GRAVE; Ugrave
15369 \DeclareTextCompositeCommand{\ }{\PU}{U}{\80\331} U+00D9
15370 % U+00DA LATIN CAPITAL LETTER U WITH ACUTE; Uacute
15371 \DeclareTextCompositeCommand{\ }{\PU}{U}{\80\332} U+00DA
15372 % U+00DB LATIN CAPITAL LETTER U WITH CIRCUMFLEX; Ucircumflex
15373 \DeclareTextCompositeCommand{\^}{\PU}{U}{\80\333} U+00DB
15374 % U+00DC LATIN CAPITAL LETTER U WITH DIAERESIS; Udieresis
15375 \DeclareTextCompositeCommand{\"}{\PU}{U}{\80\334} U+00DC
15376 % U+00DD LATIN CAPITAL LETTER Y WITH ACUTE; Yacute
15377 \DeclareTextCompositeCommand{\'}{\PU}{Y}{\80\335} U+00DD
15378 % U+00DE LATIN CAPITAL LETTER THORN; Thorn; \TH, \Thorn (wasysym)
15379 \DeclareTextCommand{\TH}{\PU}{\80\336} U+00DE
15380 \DeclareTextCommand{\textThorn}{\PU}{\80\336} U+00DE
15381 % U+00DF LATIN SMALL LETTER SHARP S; germandbls
15382 \DeclareTextCommand{\ss}{\PU}{\80\337} U+00DF
15383 % U+00E0 LATIN SMALL LETTER A WITH GRAVE; agrave
15384 \DeclareTextCompositeCommand{\`}{\PU}{a}{\80\340} U+00E0
15385 % U+00E1 LATIN SMALL LETTER A WITH ACUTE; aacute
15386 \DeclareTextCompositeCommand{\'}{\PU}{a}{\80\341} U+00E1
15387 % U+00E2 LATIN SMALL LETTER A WITH CIRCUMFLEX; acircumflex
15388 \DeclareTextCompositeCommand{\^}{\PU}{a}{\80\342} U+00E2
15389 % U+00E3 LATIN SMALL LETTER A WITH TILDE; atilde
15390 \DeclareTextCompositeCommand{\~}{\PU}{a}{\80\343} U+00E3
15391 % U+00E4 LATIN SMALL LETTER A WITH DIAERESIS; adieresis
15392 \DeclareTextCompositeCommand{\"}{\PU}{a}{\80\344} U+00E4
15393 % U+00E5 LATIN SMALL LETTER A WITH RING ABOVE; aring
15394 \DeclareTextCompositeCommand{\r}{\PU}{a}{\80\345} U+00E5
15395 % U+00E6 LATIN SMALL LETTER AE; ae
15396 \DeclareTextCommand{\ae}{\PU}{\80\346} U+00E6
15397 % U+00E7 LATIN SMALL LETTER C WITH CEDILLA; ccedilla
15398 \DeclareTextCompositeCommand{\c}{\PU}{c}{\80\347} U+00E7
15399 % U+00E8 LATIN SMALL LETTER E WITH GRAVE; egrave
15400 \DeclareTextCompositeCommand{\`}{\PU}{e}{\80\350} U+00E8
15401 % U+00E9 LATIN SMALL LETTER E WITH ACUTE; eacute
15402 \DeclareTextCompositeCommand{\'}{\PU}{e}{\80\351} U+00E9
15403 % U+00EA LATIN SMALL LETTER E WITH CIRCUMFLEX; ecircumflex
15404 \DeclareTextCompositeCommand{\^}{\PU}{e}{\80\352} U+00EA
15405 % U+00EB LATIN SMALL LETTER E WITH DIAERESIS; edieresis
15406 \DeclareTextCompositeCommand{\\"}{\PU}{e}{\80\353} U+00EB
15407 % U+00EC LATIN SMALL LETTER I WITH GRAVE; igrave
15408 \DeclareTextCompositeCommand{\`}{\PU}{i}{\80\354} U+00EC
15409 \DeclareTextCompositeCommand{\`}{\PU}{i}{\80\354} U+00EC
15410 % U+00ED LATIN SMALL LETTER I WITH ACUTE; iacute
15411 \DeclareTextCompositeCommand{\'}{\PU}{i}{\80\355} U+00ED
15412 \DeclareTextCompositeCommand{\'}{\PU}{i}{\80\355} U+00ED
15413 % U+00EE LATIN SMALL LETTER I WITH CIRCUMFLEX; icircumflex
15414 \DeclareTextCompositeCommand{\^}{\PU}{i}{\80\356} U+00EE
15415 \DeclareTextCompositeCommand{\^}{\PU}{i}{\80\356} U+00EE
15416 % U+00EF LATIN SMALL LETTER I WITH DIAERESIS; idieresis
15417 \DeclareTextCompositeCommand{\\"}{\PU}{i}{\80\357} U+00EF
15418 \DeclareTextCompositeCommand{\\"}{\PU}{i}{\80\357} U+00EF

```

```

15419 % U+00F0 LATIN SMALL LETTER ETH; eth
15420 \DeclareTextCommand{\dh}{PU}{\80\360}% U+00F0
15421 %* \dh -> \eth (wsuipa, phonetic)
15422 % U+00F1 LATIN SMALL LETTER N WITH TILDE; ntilde
15423 \DeclareTextCompositeCommand{\~}{PU}{n}{\80\361}% U+00F1
15424 % U+00F2 LATIN SMALL LETTER O WITH GRAVE; ograve
15425 \DeclareTextCompositeCommand{\`}{PU}{o}{\80\362}% U+00F2
15426 % U+00F3 LATIN SMALL LETTER O WITH ACUTE; oacute
15427 \DeclareTextCompositeCommand{\'}{PU}{o}{\80\363}% U+00F3
15428 % U+00F4 LATIN SMALL LETTER O WITH CIRCUMFLEX; ocircumflex
15429 \DeclareTextCompositeCommand{\^}{PU}{o}{\80\364}% U+00F4
15430 % U+00F5 LATIN SMALL LETTER O WITH TILDE; otilde
15431 \DeclareTextCompositeCommand{\~}{PU}{o}{\80\365}% U+00F5
15432 % U+00F6 LATIN SMALL LETTER O WITH DIAERESIS; odieresis
15433 \DeclareTextCompositeCommand{\"}{PU}{o}{\80\366}% U+00F6
15434 % U+00F7 DIVISION SIGN; divide
15435 \DeclareTextCommand{\textdivide}{PU}{\80\367}% U+00F7
15436 % U+00F8 LATIN SMALL LETTER O WITH STROKE; oslash
15437 \DeclareTextCommand{\o}{PU}{\80\370}% U+00F8
15438 % U+00F9 LATIN SMALL LETTER U WITH GRAVE; ugrave
15439 \DeclareTextCompositeCommand{\`}{PU}{u}{\80\371}% U+00F9
15440 % U+00FA LATIN SMALL LETTER U WITH ACUTE; uacute
15441 \DeclareTextCompositeCommand{\'}{PU}{u}{\80\372}% U+00FA
15442 % U+00FB LATIN SMALL LETTER U WITH CIRCUMFLEX; ucircumflex
15443 \DeclareTextCompositeCommand{\^}{PU}{u}{\80\373}% U+00FB
15444 % U+00FC LATIN SMALL LETTER U WITH DIAERESIS; udieresis
15445 \DeclareTextCompositeCommand{\"}{PU}{u}{\80\374}% U+00FC
15446 % U+00FD LATIN SMALL LETTER Y WITH ACUTE; yacute
15447 \DeclareTextCompositeCommand{\'}{PU}{y}{\80\375}% U+00FD
15448 % U+00FE LATIN SMALL LETTER THORN; thorn;
15449 % \th, \thorn (wasysym), \texthorn (tipa)
15450 \DeclareTextCommand{\th}{PU}{\80\376}% U+00FE
15451 \DeclareTextCommand{\texthorn}{PU}{\80\376}%* U+00FE
15452 % U+00FF LATIN SMALL LETTER Y WITH DIAERESIS; ydieresis
15453 \DeclareTextCompositeCommand{\\"}{PU}{y}{\80\377}% U+00FF

```

46.2.4 Latin Extended-A: U+0080 to U+017F

```

15454 % U+0100 LATIN CAPITAL LETTER A WITH MACRON; Amacron
15455 \DeclareTextCompositeCommand{\=}{PU}{A}{\81\000}% U+0100
15456 % U+0101 LATIN SMALL LETTER A WITH MACRON; amacron
15457 \DeclareTextCompositeCommand{\=}{PU}{a}{\81\001}% U+0101
15458 % U+0102 LATIN CAPITAL LETTER A WITH BREVE; Abreve
15459 \DeclareTextCompositeCommand{\u}{PU}{A}{\81\002}% U+0102
15460 % U+0103 LATIN SMALL LETTER A WITH BREVE; breve
15461 \DeclareTextCompositeCommand{\u}{PU}{a}{\81\003}% U+0103
15462 % U+0104 LATIN CAPITAL LETTER A WITH OGONEK; Aogonek
15463 \DeclareTextCompositeCommand{\k}{PU}{A}{\81\004}% U+0104
15464 % U+0105 LATIN SMALL LETTER A WITH OGONEK; aogonek
15465 \DeclareTextCompositeCommand{\k}{PU}{a}{\81\005}% U+0105
15466 % U+0106 LATIN CAPITAL LETTER C WITH ACUTE; Cacute
15467 \DeclareTextCompositeCommand{\'}{PU}{C}{\81\006}% U+0106
15468 % U+0107 LATIN SMALL LETTER C WITH ACUTE; cacute
15469 \DeclareTextCompositeCommand{\'}{PU}{c}{\81\007}% U+0107

```

```

15470 % U+0108 LATIN CAPITAL LETTER C WITH CIRCUMFLEX; Ccircumflex
15471 \DeclareTextCompositeCommand{\^}{PU}{C}{\81\010}% U+0108
15472 % U+0109 LATIN SMALL LETTER C WITH CIRCUMFLEX; ccircumflex
15473 \DeclareTextCompositeCommand{\^}{PU}{c}{\81\011}% U+0109
15474 % U+010A LATIN CAPITAL LETTER C WITH DOT ABOVE; Cdot, Cdotac-
cent
15475 \DeclareTextCompositeCommand{\.}{PU}{C}{\81\012}% U+010A
15476 % U+010B LATIN SMALL LETTER C WITH DOT ABOVE; cdot, cdotaccent
15477 \DeclareTextCompositeCommand{\.}{PU}{c}{\81\013}% U+010B
15478 % U+010C LATIN CAPITAL LETTER C WITH CARON; Ccaron
15479 \DeclareTextCompositeCommand{\v}{PU}{C}{\81\014}% U+010C
15480 % U+010D LATIN SMALL LETTER C WITH CARON; ccaron
15481 \DeclareTextCompositeCommand{\v}{PU}{c}{\81\015}% U+010D
15482 % U+010E LATIN CAPITAL LETTER D WITH CARON; Dcaron
15483 \DeclareTextCompositeCommand{\v}{PU}{D}{\81\016}% U+010E
15484 % U+010F LATIN SMALL LETTER D WITH CARON; dcaron
15485 \DeclareTextCompositeCommand{\v}{PU}{d}{\81\017}% U+010F
15486 % U+0110 LATIN CAPITAL LETTER D WITH STROKE; Dcroat, Dslash
15487 \DeclareTextCommand{\DJ}{PU}{\81\020}% U+0110
15488 % U+0111 LATIN SMALL LETTER D WITH STROKE; dcroat, dmacron;
15489 % \textcrd (tipa)
15490 \DeclareTextCommand{\dj}{PU}{\81\021}% U+0111
15491 \DeclareTextCommand{\textcrd}{PU}{\81\021}% U+0111
15492 %* \textcrd -> \crossd (wsuipa)
15493 % An alternate glyph with the stroke through the bowl:
15494 %* \textcrd -> \textbard (tipa)
15495 %* \textcrd -> \bard (wsuipa)
15496 % U+0112 LATIN CAPITAL LETTER E WITH MACRON; Emacron
15497 \DeclareTextCompositeCommand{\=}{PU}{E}{\81\022}% U+0112
15498 % U+0113 LATIN SMALL LETTER E WITH MACRON; emacron
15499 \DeclareTextCompositeCommand{\=}{PU}{e}{\81\023}% U+0113
15500 % U+0114 LATIN CAPITAL LETTER E WITH BREVE; Ebreve
15501 \DeclareTextCompositeCommand{\u}{PU}{E}{\81\024}% U+0114
15502 % U+0115 LATIN SMALL LETTER E WITH BREVE; ebreve
15503 \DeclareTextCompositeCommand{\u}{PU}{e}{\81\025}% U+0115
15504 % U+0116 LATIN CAPITAL LETTER E WITH DOT ABOVE; Edot, Edotaccent
15505 \DeclareTextCompositeCommand{\.}{PU}{E}{\81\026}% U+0116
15506 % U+0117 LATIN SMALL LETTER E WITH DOT ABOVE; edot, edotaccent
15507 \DeclareTextCompositeCommand{\.}{PU}{e}{\81\027}% U+0117
15508 % U+0118 LATIN CAPITAL LETTER E WITH OGONEK; Eogonek
15509 \DeclareTextCompositeCommand{\k}{PU}{E}{\81\030}% U+0118
15510 % U+0119 LATIN SMALL LETTER E WITH OGONEK; eogonek
15511 \DeclareTextCompositeCommand{\k}{PU}{e}{\81\031}% U+0119
15512 % U+011A LATIN CAPITAL LETTER E WITH CARON; Ecaron
15513 \DeclareTextCompositeCommand{\v}{PU}{E}{\81\032}% U+011A
15514 % U+011B LATIN SMALL LETTER E WITH CARON; ecaron
15515 \DeclareTextCompositeCommand{\v}{PU}{e}{\81\033}% U+011B
15516 % U+011C LATIN CAPITAL LETTER G WITH CIRCUMFLEX; Gcircumflex
15517 \DeclareTextCompositeCommand{\^}{PU}{G}{\81\034}% U+011C
15518 % U+011D LATIN SMALL LETTER G WITH CIRCUMFLEX; gcircumflex
15519 \DeclareTextCompositeCommand{\^}{PU}{g}{\81\035}% U+011D
15520 % U+011E LATIN CAPITAL LETTER G WITH BREVE; Gbreve
15521 \DeclareTextCompositeCommand{\u}{PU}{G}{\81\036}% U+011E
15522 % U+011F LATIN SMALL LETTER G WITH BREVE; gbreve

```

```

15523 \DeclareTextCompositeCommand{\u}{PU}{g}{\81\037}% U+011F
15524 % U+0120 LATIN CAPITAL LETTER G WITH DOT ABOVE; Gdot, Gdotac-
cent
15525 \DeclareTextCompositeCommand{\.}{PU}{G}{\81\040}% U+0120
15526 % U+0121 LATIN SMALL LETTER G WITH DOT ABOVE; gdot, gdotaccent
15527 \DeclareTextCompositeCommand{\.}{PU}{g}{\81\041}% U+0121
15528 % U+0122 LATIN CAPITAL LETTER G WITH CEDILLA; Gcedilla, Gcom-
maaccent
15529 \DeclareTextCompositeCommand{\c}{PU}{G}{\81\042}% U+0122
15530 % U+0123 LATIN SMALL LETTER G WITH CEDILLA; gcedilla, gcommaaccent
15531 \DeclareTextCompositeCommand{\c}{PU}{g}{\81\043}% U+0123
15532 % U+0124 LATIN CAPITAL LETTER H WITH CIRCUMFLEX; Hcircumflex
15533 \DeclareTextCompositeCommand{\^}{PU}{H}{\81\044}% U+0124
15534 % U+0125 LATIN SMALL LETTER H WITH CIRCUMFLEX; hcircumflex
15535 \DeclareTextCompositeCommand{\^}{PU}{h}{\81\045}% U+0125
15536 % U+0126 LATIN CAPITAL LETTER H WITH STROKE; Hbar
15537 \DeclareTextCommand{\textHslash}{PU}{\81\046}% U+0126
15538 % U+0127 LATIN SMALL LETTER H WITH STROKE; hbar; \hbar (AmS)
15539 \DeclareTextCommand{\texthbar}{PU}{\81\047}/* U+0127
15540 /* \texthbar -> \textcrh (tipa)
15541 /* \texthbar -> \crossh (wsuipa)
15542 /* \texthbar -> \planck (phonetic)
15543 % U+0128 LATIN CAPITAL LETTER I WITH TILDE; Itilde
15544 \DeclareTextCompositeCommand{\~}{PU}{I}{\81\050}% U+0128
15545 % U+0129 LATIN SMALL LETTER I WITH TILDE; itilde
15546 \DeclareTextCompositeCommand{\~}{PU}{i}{\81\051}% U+0129
15547 \DeclareTextCompositeCommand{\~}{PU}{\i}{\81\051}% U+0129
15548 % U+012A LATIN CAPITAL LETTER I WITH MACRON; Imacron
15549 \DeclareTextCompositeCommand{\=}{PU}{I}{\81\052}% U+012A
15550 % U+012B LATIN SMALL LETTER I WITH MACRON; imacron
15551 \DeclareTextCompositeCommand{\=}{PU}{i}{\81\053}% U+012B
15552 \DeclareTextCompositeCommand{\=}{PU}{\i}{\81\053}% U+012B
15553 % U+012C LATIN CAPITAL LETTER I WITH BREVE; Ibreve
15554 \DeclareTextCompositeCommand{\u}{PU}{I}{\81\054}% U+012C
15555 % U+012D LATIN SMALL LETTER I WITH BREVE; ibreve
15556 \DeclareTextCompositeCommand{\u}{PU}{i}{\81\055}% U+012D
15557 \DeclareTextCompositeCommand{\u}{PU}{\i}{\81\055}% U+012D
15558 % U+012E LATIN CAPITAL LETTER I WITH OGONEK; Igonek
15559 \DeclareTextCompositeCommand{\k}{PU}{I}{\81\056}% U+012E
15560 % U+012F LATIN SMALL LETTER I WITH OGONEK; igonek
15561 \DeclareTextCompositeCommand{\k}{PU}{i}{\81\057}% U+012F
15562 \DeclareTextCompositeCommand{\k}{PU}{\i}{\81\057}% U+012F
15563 % U+0130 LATIN CAPITAL LETTER I WITH DOT ABOVE; Idot, Idotaccent
15564 \DeclareTextCompositeCommand{\.}{PU}{I}{\81\060}% U+0130
15565 % U+0131 LATIN SMALL LETTER DOTLESS I; dotlessi
15566 \DeclareTextCommand{\i}{PU}{\81\061}% U+0131
15567 % U+0132 LATIN CAPITAL LIGATURE IJ; IJ
15568 \DeclareTextCommand{\IJ}{PU}{\81\062}% U+0132
15569 % U+0133 LATIN SMALL LIGATURE IJ; ij
15570 \DeclareTextCommand{\ij}{PU}{\81\063}% U+0133
15571 % U+0134 LATIN CAPITAL LETTER J WITH CIRCUMFLEX; Jcircumflex
15572 \DeclareTextCompositeCommand{\^}{PU}{J}{\81\064}% U+0134
15573 % U+0135 LATIN SMALL LETTER J WITH CIRCUMFLEX; jcircumflex
15574 \DeclareTextCompositeCommand{\^}{PU}{j}{\81\065}% U+0135

```

```

15575 \DeclareTextCompositeCommand{\^}{PU}{j}{\81\065}% U+0135
15576 % U+0136 LATIN CAPITAL LETTER K WITH CEDILLA; Kcedilla, Kcommaaccent
15577 \DeclareTextCompositeCommand{\c}{PU}{K}{\81\066}% U+0136
15578 % U+0137 LATIN SMALL LETTER K WITH CEDILLA; kcedilla, kcommaaccent
15579 \DeclareTextCompositeCommand{\c}{PU}{k}{\81\067}% U+0137

```

The canonical name of U+0138, small letter kra, would be \textkgreenlandic, following the glyph naming convention. However *latex/base/inputenc.dtx* has chosen \textkra.

```

15580 % U+0138 LATIN SMALL LETTER KRA; kgreenlandic
15581 \DeclareTextCommand{\textkra}{PU}{\81\070}% U+0138
15582 % U+0139 LATIN CAPITAL LETTER L WITH ACUTE; Lacute
15583 \DeclareTextCompositeCommand{\'}{PU}{L}{\81\071}% U+0139
15584 % U+013A LATIN SMALL LETTER L WITH ACUTE; lacute
15585 \DeclareTextCompositeCommand{\'}{PU}{l}{\81\072}% U+013A
15586 % U+013B LATIN CAPITAL LETTER L WITH CEDILLA; Lcedilla, Lcommaaccent
15587 \DeclareTextCompositeCommand{\c}{PU}{L}{\81\073}% U+013B
15588 % U+013C LATIN SMALL LETTER L WITH CEDILLA; lcedilla, lcommaaccent
15589 \DeclareTextCompositeCommand{\c}{PU}{l}{\81\074}% U+013C
15590 % U+013D LATIN CAPITAL LETTER L WITH CARON; Lcaron
15591 \DeclareTextCompositeCommand{\v}{PU}{L}{\81\075}% U+013D
15592 % U+013E LATIN SMALL LETTER L WITH CARON; lcaron
15593 \DeclareTextCompositeCommand{\v}{PU}{l}{\81\076}% U+013E

```

There seems to be no variants of letters ‘L’ and ‘l’ with a dot above (reasonable). Therefore the \. accent is reused instead of making a separate accent macro \textmiddledot.

```

15594 % U+013F LATIN CAPITAL LETTER L WITH MIDDLE DOT; Ldot, Ldotaccent
15595 \DeclareTextCompositeCommand{\.}{PU}{L}{\81\077}% U+013F
15596 % U+0140 LATIN SMALL LETTER L WITH MIDDLE DOT; ldot, ldotaccent
15597 \DeclareTextCompositeCommand{\.}{PU}{l}{\81\100}% U+0140
15598 % U+0141 LATIN CAPITAL LETTER L WITH STROKE; Lslash
15599 \DeclareTextCommand{\L}{PU}{\81\101}% U+0141
15600 % U+0142 LATIN SMALL LETTER L WITH STROKE; lslash
15601 \DeclareTextCommand{\l}{PU}{\81\102}% U+0142
15602 % U+0143 LATIN CAPITAL LETTER N WITH ACUTE; Nacute
15603 \DeclareTextCompositeCommand{\'}{PU}{N}{\81\103}% U+0143
15604 % U+0144 LATIN SMALL LETTER N WITH ACUTE; nacute
15605 \DeclareTextCompositeCommand{\'}{PU}{n}{\81\104}% U+0144
15606 % U+0145 LATIN CAPITAL LETTER N WITH CEDILLA; Ncedilla, Ncommaaccent
15607 \DeclareTextCompositeCommand{\c}{PU}{N}{\81\105}% U+0145
15608 % U+0146 LATIN SMALL LETTER N WITH CEDILLA; ncedilla, ncommaaccent
15609 \DeclareTextCompositeCommand{\c}{PU}{n}{\81\106}% U+0146
15610 % U+0147 LATIN CAPITAL LETTER N WITH CARON; Ncaron
15611 \DeclareTextCompositeCommand{\v}{PU}{N}{\81\107}% U+0147
15612 % U+0148 LATIN SMALL LETTER N WITH CARON; ncaron
15613 \DeclareTextCompositeCommand{\v}{PU}{n}{\81\110}% U+0148
15614 % U+0149 LATIN SMALL LETTER N PRECEDED BY APOSTROPHE; napostrophe, quoterightn
15615 \DeclareTextCommand{\textnapostrophe}{PU}{\81\111}% U+0149
15616 % U+014A LATIN CAPITAL LETTER ENG; Eng

```

```

15617 \DeclareTextCommand{\NG}{\PU}{\81\112}% U+014A
15618 % U+014B LATIN SMALL LETTER ENG; eng
15619 \DeclareTextCommand{\ng}{\PU}{\81\113}% U+014B
15620 %* \ng -> \eng (wsuipa)
15621 %* \ng -> \engma (phonetic)
15622 % U+014C LATIN CAPITAL LETTER O WITH MACRON; Omacron
15623 \DeclareTextCompositeCommand{\=}{\PU}{O}{\81\114}% U+014C
15624 % U+014D LATIN SMALL LETTER O WITH MACRON; omacron
15625 \DeclareTextCompositeCommand{\=}{\PU}{o}{\81\115}% U+014D
15626 % U+014E LATIN CAPITAL LETTER O WITH BREVE; Obreve
15627 \DeclareTextCompositeCommand{\u}{\PU}{O}{\81\116}% U+014E
15628 % U+014F LATIN SMALL LETTER O WITH BREVE; obreve
15629 \DeclareTextCompositeCommand{\u}{\PU}{o}{\81\117}% U+014F
15630 % U+0150 LATIN CAPITAL LETTER O WITH DOUBLE ACUTE; Odblacute, Ohungarumlaut
15631 \DeclareTextCompositeCommand{\H}{\PU}{O}{\81\120}% U+0150
15632 % U+0151 LATIN SMALL LETTER O WITH DOUBLE ACUTE; odblacute, ohungarumlaut
15633 \DeclareTextCompositeCommand{\H}{\PU}{o}{\81\121}% U+0151
15634 % U+0152 LATIN CAPITAL LIGATURE OE; oe
15635 \DeclareTextCommand{\OE}{\PU}{\81\122}% U+0152
15636 % U+0153 LATIN SMALL LIGATURE OE; oe
15637 \DeclareTextCommand{\oe}{\PU}{\81\123}% U+0153
15638 % U+0154 LATIN CAPITAL LETTER R WITH ACUTE; Racute
15639 \DeclareTextCompositeCommand{\'}{\PU}{R}{\81\124}% U+0154
15640 % U+0155 LATIN SMALL LETTER R WITH ACUTE; racute
15641 \DeclareTextCompositeCommand{\'}{\PU}{r}{\81\125}% U+0155
15642 % U+0156 LATIN CAPITAL LETTER R WITH CEDILLA; Rcedilla, Rcommaaccent
15643 \DeclareTextCompositeCommand{\c}{\PU}{R}{\81\126}% U+0156
15644 % U+0157 LATIN SMALL LETTER R WITH CEDILLA; rcedilla, rcommaaccent
15645 \DeclareTextCompositeCommand{\c}{\PU}{r}{\81\127}% U+0157
15646 % U+0158 LATIN CAPITAL LETTER R WITH CARON; Rcaron
15647 \DeclareTextCompositeCommand{\v}{\PU}{R}{\81\130}% U+0158
15648 % U+0159 LATIN SMALL LETTER R WITH CARON; rcaron
15649 \DeclareTextCompositeCommand{\v}{\PU}{r}{\81\131}% U+0159
15650 % U+015A LATIN CAPITAL LETTER S WITH ACUTE; Sacute
15651 \DeclareTextCompositeCommand{\'}{\PU}{S}{\81\132}% U+015A
15652 % U+015B LATIN SMALL LETTER S WITH ACUTE; sacute
15653 \DeclareTextCompositeCommand{\'}{\PU}{s}{\81\133}% U+015B
15654 % U+015C LATIN CAPITAL LETTER S WITH CIRCUMFLEX; Scircumflex
15655 \DeclareTextCompositeCommand{\^}{\PU}{S}{\81\134}% U+015C
15656 % U+015D LATIN SMALL LETTER S WITH CIRCUMFLEX; scircumflex
15657 \DeclareTextCompositeCommand{\^}{\PU}{s}{\81\135}% U+015D
15658 % U+015E LATIN CAPITAL LETTER S WITH CEDILLA; Scedilla
15659 \DeclareTextCompositeCommand{\c}{\PU}{S}{\81\136}% U+015E
15660 % U+015F LATIN SMALL LETTER S WITH CEDILLA; scedilla
15661 \DeclareTextCompositeCommand{\c}{\PU}{s}{\81\137}% U+015F
15662 % U+0160 LATIN CAPITAL LETTER S WITH CARON; Scaron
15663 \DeclareTextCompositeCommand{\v}{\PU}{S}{\81\140}% U+0160
15664 % U+0161 LATIN SMALL LETTER S WITH CARON; scaron
15665 \DeclareTextCompositeCommand{\v}{\PU}{s}{\81\141}% U+0161
15666 % U+0162 LATIN CAPITAL LETTER T WITH CEDILLA; Tcedilla, Tcommaaccent

```

```

15667 \DeclareTextCompositeCommand{\c}{PU}{T}{\81\142}% U+0162
15668 % U+0163 LATIN SMALL LETTER T WITH CEDILLA; tcedilla, tcommaaccent
15669 \DeclareTextCompositeCommand{\c}{PU}{t}{\81\143}% U+0163
15670 % U+0164 LATIN CAPITAL LETTER T WITH CARON; Tcaron
15671 \DeclareTextCompositeCommand{\v}{PU}{T}{\81\144}% U+0164
15672 % U+0165 LATIN SMALL LETTER T WITH CARON; tcaron
15673 \DeclareTextCompositeCommand{\v}{PU}{t}{\81\145}% U+0165
15674 % U+0166 LATIN CAPITAL LETTER T WITH STROKE; Tbar
15675 \DeclareTextCommand{\textTslash}{PU}{\81\146}% U+0166
15676 % U+0167 LATIN SMALL LETTER T WITH STROKE; tbar
15677 \DeclareTextCommand{\textttslash}{PU}{\81\147}% U+0167
15678 % U+0168 LATIN CAPITAL LETTER U WITH TILDE; Utilde
15679 \DeclareTextCompositeCommand{\~}{PU}{U}{\81\150}% U+0168
15680 % U+0169 LATIN SMALL LETTER U WITH TILDE; utilde
15681 \DeclareTextCompositeCommand{\~}{PU}{u}{\81\151}% U+0169
15682 % U+016A LATIN CAPITAL LETTER U WITH MACRON; Umacron
15683 \DeclareTextCompositeCommand{\=}{PU}{U}{\81\152}% U+016A
15684 % U+016B LATIN SMALL LETTER U WITH MACRON; umacron
15685 \DeclareTextCompositeCommand{\=}{PU}{u}{\81\153}% U+016B
15686 % U+016C LATIN CAPITAL LETTER U WITH BREVE; Ubreve
15687 \DeclareTextCompositeCommand{\u}{PU}{U}{\81\154}% U+016C
15688 % U+016D LATIN SMALL LETTER U WITH BREVE; ubreve
15689 \DeclareTextCompositeCommand{\u}{PU}{u}{\81\155}% U+016D
15690 % U+016E LATIN CAPITAL LETTER U WITH RING ABOVE; Uring
15691 \DeclareTextCompositeCommand{\r}{PU}{U}{\81\156}% U+016E
15692 % U+016F LATIN SMALL LETTER U WITH RING ABOVE; uring
15693 \DeclareTextCompositeCommand{\r}{PU}{u}{\81\157}% U+016F
15694 % U+0170 LATIN CAPITAL LETTER U WITH DOUBLE ACUTE; Udbla-
cute, Uhngarumlaut
15695 \DeclareTextCompositeCommand{\H}{PU}{U}{\81\160}% U+0170
15696 % U+0171 LATIN SMALL LETTER U WITH DOUBLE ACUTE; udbla-
cute, uhngarumlaut
15697 \DeclareTextCompositeCommand{\H}{PU}{u}{\81\161}% U+0171
15698 % U+0172 LATIN CAPITAL LETTER U WITH OGONEK; Uogonek
15699 \DeclareTextCompositeCommand{\k}{PU}{U}{\81\162}% U+0172
15700 % U+0173 LATIN SMALL LETTER U WITH OGONEK; uogonek
15701 \DeclareTextCompositeCommand{\k}{PU}{u}{\81\163}% U+0173
15702 % U+0174 LATIN CAPITAL LETTER W WITH CIRCUMFLEX; Wcircumflex
15703 \DeclareTextCompositeCommand{\^}{PU}{W}{\81\164}% U+0174
15704 % U+0175 LATIN SMALL LETTER W WITH CIRCUMFLEX; wcircumflex
15705 \DeclareTextCompositeCommand{\^}{PU}{w}{\81\165}% U+0175
15706 % U+0176 LATIN CAPITAL LETTER Y WITH CIRCUMFLEX; Ycircumflex
15707 \DeclareTextCompositeCommand{\^}{PU}{Y}{\81\166}% U+0176
15708 % U+0177 LATIN SMALL LETTER Y WITH CIRCUMFLEX; ycircumflex
15709 \DeclareTextCompositeCommand{\^}{PU}{y}{\81\167}% U+0177
15710 % U+0178 LATIN CAPITAL LETTER Y WITH DIAERESIS; Ydieresis
15711 \DeclareTextCompositeCommand{\"}{PU}{Y}{\81\170}% U+0178
15712 % U+0179 LATIN CAPITAL LETTER Z WITH ACUTE; Zacute
15713 \DeclareTextCompositeCommand{\'}{PU}{Z}{\81\171}% U+0179
15714 % U+017A LATIN SMALL LETTER Z WITH ACUTE; zacute
15715 \DeclareTextCompositeCommand{\'}{PU}{z}{\81\172}% U+017A
15716 % U+017B LATIN CAPITAL LETTER Z WITH DOT ABOVE; Zdot, Zdotaccent
15717 \DeclareTextCompositeCommand{\.}{PU}{Z}{\81\173}% U+017B
15718 % U+017C LATIN SMALL LETTER Z WITH DOT ABOVE; zdot, zdotaccent

```

```

15719 \DeclareTextCompositeCommand{\.{PU}.{z}\{81\174\}%
15720 % U+017D LATIN CAPITAL LETTER Z WITH CARON; Zcaron
15721 \DeclareTextCompositeCommand{\v.{PU}.{Z}\{81\175\}%
15722 % U+017E LATIN SMALL LETTER Z WITH CARON; zcaron
15723 \DeclareTextCompositeCommand{\v.{PU}.{z}\{81\176\}%
15724 % U+017F LATIN SMALL LETTER LONG S; longs, slong
15725 \DeclareTextCommand{\textlongs}{PU}\{81\177\}%

```

46.2.5 Latin Extended-B: U+0180 to U+024F

```

15726 % U+0180 LATIN SMALL LETTER B WITH STROKE; bstroke; \textcrb (tipa)
15727 \DeclareTextCommand{\textcrb}{PU}\{81\200\}%
15728 %* \textcrb -> \crossb (wsuipa)
15729 % An alternate glyph with the stroke through the bowl:
15730 %* \textcrb -> \textbarb (tipa)
15731 %* \textcrb -> \barb (wsuipa)
15732 % U+0181 LATIN CAPITAL LETTER B WITH HOOK; Bhook; \hausaB (phonetic)
15733 \DeclareTextCommand{\texthausaB}{PU}\{81\201\}%
15734 % U+0188 LATIN SMALL LETTER C WITH HOOK; chook; \texthtc (tipa)
15735 \DeclareTextCommand{\texthtc}{PU}\{81\210\}%
15736 % U+018A LATIN CAPITAL LETTER D WITH HOOK; Dhook; \hausaD (phonetic)
15737 \DeclareTextCommand{\texthausaD}{PU}\{81\212\}%
15738 % U+018E LATIN CAPITAL LETTER REVERSED E; Ereversed
15739 \DeclareTextCommand{\textEreversed}{PU}\{81\216\}%
15740 \DeclareTextCommand{\textrevE}{PU}\{81\216\}%
15741 % U+0192 LATIN SMALL LETTER F WITH HOOK; florin
15742 \DeclareTextCommand{\textflorin}{PU}\{81\222\}%
15743 %* \textflorin -> \Florin (marvosym)
15744 % U+0195 LATIN SMALL LETTER HV; hv; \texthvlig (tipa)
15745 \DeclareTextCommand{\texthvlig}{PU}\{81\225\}%
15746 %* \texthvlig -> \hv (wsuipa)
15747 % U+0198 LATIN CAPITAL LETTER K WITH HOOK; Khook; \hausaK (phonetic)
15748 \DeclareTextCommand{\texthausaK}{PU}\{81\230\}%
15749 % U+0199 LATIN SMALL LETTER K WITH HOOK; khook; \texthtk (tipa)
15750 \DeclareTextCommand{\texthtk}{PU}\{81\231\}%
15751 %* \texthtk -> \hausak (phonetic)
15752 % U+019A LATIN SMALL LETTER L WITH BAR; lbar;
15753 % \textbarl (tipa), \barl (wsuipa)
15754 \DeclareTextCommand{\textbarl}{PU}\{81\232\}%
15755 % U+019B LATIN SMALL LETTER LAMBDA WITH STROKE/
15756 % LATIN SMALL LETTER BARRED LAMBDA; lambdastroke;
15757 % \textcrlambda (tipa)
15758 \DeclareTextCommand{\textcrlambda}{PU}\{81\233\}%
15759 %* \textcrlambda -> \crossnilambda (wsuipa)
15760 %* \textcrlambda -> \barlambda (phonetic)
15761 %* \textcrlambda -> \lambdabar (txfonts/pxfonts)
15762 %* \textcrlambda -> \lambdaslash (txfonts/pxfonts)
15763 % U+019E LATIN SMALL LETTER N WITH LONG RIGHT LEG; nlegright-long;
15764 % \textnrleg (tipx)
15765 \DeclareTextCommand{\textPUnrleg}{PU}\{81\236\}%
15766 %* \textPUnrleg -> \textnrleg (tipx)

```

```

15767 % U+01A5 LATIN SMALL LETTER P WITH HOOK; phook; \texthttp (tipa)
15768 \DeclareTextCommand{\texthttp}{\PU}{\81\245}% U+01A5
15769 % U+01AB LATIN SMALL LETTER T WITH PALATAL HOOK; tpalatalhook;
15770 % \textlhookt (tipa)
15771 \DeclareTextCommand{\textlhookt}{\PU}{\81\253}% U+01AB
15772 % U+01AD LATIN SMALL LETTER T WITH HOOK; thook; \texthtt (tipa)
15773 \DeclareTextCommand{\texthtt}{\PU}{\81\255}% U+01AD
15774 % U+01B9 LATIN SMALL LETTER EZH REVERSED/
15775 % LATIN SMALL LETTER REVERSED YOGH; \textrevyogh (tipa)
15776 \DeclareTextCommand{\textrevyogh}{\PU}{\81\271}% U+01B9
15777 % U+01BB LATIN LETTER TWO WITH STROKE; twostroke; \textcrtwo (tipa)
15778 \DeclareTextCommand{\textcrtwo}{\PU}{\81\273}% U+01BB
15779 % U+01BE LATIN LETTER INVERTED GLOTTAL STOP WITH STROKE;
15780 % glottalinvertedstroke; \textcrinvglotstop (tipa)
15781 \DeclareTextCommand{\textcrinvglotstop}{\PU}{\81\276}% U+01BE
15782 % U+01BF LATIN LETTER WYNN; wynn; \textwynn (tipa)
15783 \DeclareTextCommand{\textwynn}{\PU}{\81\277}% U+01BF
15784 % U+01C0 LATIN LETTER DENTAL CLICK/LATIN LETTER PIPE; clickden-
tal;
15785 % \textpipe (tipa)
15786 \DeclareTextCommand{\textpipe}{\PU}{\81\300}% U+01C0
15787 %* \textpipe -> \textpipevar (tipx)
15788 % U+01C1 LATIN LETTER LATERAL CLICK/LATIN LETTER
15789 % DOUBLE PIPE; clicklateral; \textdoublepipe (tipa)
15790 \DeclareTextCommand{\textdoublepipe}{\PU}{\81\301}% U+01C1
15791 %* \textdoublepipe -> \textdoublepipevar (tipx)
15792 % U+01C2 LATIN LETTER ALVEOLAR CLICK/LATIN LETTER PIPE DOU-
BLE BAR;
15793 % clickalveolar; \textdoublebarpipe (tipa)
15794 \DeclareTextCommand{\textdoublebarpipe}{\PU}{\81\302}% U+01C2
15795 %* \textdoublebarpipe -> \textdoublebarpipevar (tipx)
15796 % U+01CD LATIN CAPITAL LETTER A WITH CARON; Acaron
15797 \DeclareTextCompositeCommand{\v}{\PU}{A}{\81\315}% U+01CD
15798 % U+01CE LATIN SMALL LETTER A WITH CARON; acaron
15799 \DeclareTextCompositeCommand{\v}{\PU}{a}{\81\316}% U+01CE
15800 % U+01CF LATIN CAPITAL LETTER I WITH CARON; Icaron
15801 \DeclareTextCompositeCommand{\v}{\PU}{I}{\81\317}% U+01CF
15802 % U+01D0 LATIN SMALL LETTER I WITH CARON; icaron
15803 \DeclareTextCompositeCommand{\v}{\PU}{i}{\81\320}% U+01D0
15804 \DeclareTextCompositeCommand{\v}{\PU}{i}{\81\320}% U+01D0
15805 % U+01D1 LATIN CAPITAL LETTER O WITH CARON; Ocaron
15806 \DeclareTextCompositeCommand{\v}{\PU}{O}{\81\321}% U+01D1
15807 % U+01D2 LATIN SMALL LETTER O WITH CARON; ocaron
15808 \DeclareTextCompositeCommand{\v}{\PU}{o}{\81\322}% U+01D2
15809 % U+01D3 LATIN CAPITAL LETTER U WITH CARON; Ucaron
15810 \DeclareTextCompositeCommand{\v}{\PU}{U}{\81\323}% U+01D3
15811 % U+01D4 LATIN SMALL LETTER U WITH CARON; ucaron
15812 \DeclareTextCompositeCommand{\v}{\PU}{u}{\81\324}% U+01D4
15813 % U+01DD LATIN SMALL LETTER TURNED E; eturned; \inve (wasysym)
15814 \DeclareTextCommand{\textinve}{\PU}{\81\335}%* U+01DD
15815 % U+01E4 LATIN CAPITAL LETTER G WITH STROKE; Gstroke
15816 \DeclareTextCommand{\textGslash}{\PU}{\81\344}% U+01E4
15817 % U+01E5 LATIN SMALL LETTER G WITH STROKE; gstroke
15818 \DeclareTextCommand{\textgslash}{\PU}{\81\345}% U+01E5

```

```

15819 %* \textgslash -> \textcrg (tipa)
15820 % U+01E6 LATIN CAPITAL LETTER G WITH CARON; Gcaron
15821 \DeclareTextCompositeCommand{\v}{PU}{G}{\81\346}% U+01E6
15822 % U+01E7 LATIN SMALL LETTER G WITH CARON; gcaron
15823 \DeclareTextCompositeCommand{\v}{PU}{g}{\81\347}% U+01E7
15824 % U+01E8 LATIN CAPITAL LETTER K WITH CARON; Kcaron
15825 \DeclareTextCompositeCommand{\v}{PU}{K}{\81\350}% U+01E8
15826 % U+01E9 LATIN SMALL LETTER K WITH CARON; kcaron
15827 \DeclareTextCompositeCommand{\v}{PU}{k}{\81\351}% U+01E9
15828 % U+01EA LATIN CAPITAL LETTER O WITH OGONEK; Oogonek
15829 \DeclareTextCompositeCommand{\k}{PU}{O}{\81\352}% U+01EA
15830 % U+01EB LATIN SMALL LETTER O WITH OGONEK; oogonek
15831 \DeclareTextCompositeCommand{\k}{PU}{o}{\81\353}% U+01EB
15832 % U+01F0 LATIN SMALL LETTER J WITH CARON; jcaron
15833 \DeclareTextCompositeCommand{\v}{PU}{j}{\81\360}% U+01F0
15834 \DeclareTextCompositeCommand{\v}{PU}{j}{\81\360}% U+01F0
15835 % U+01F4 LATIN CAPITAL LETTER G WITH ACUTE; Gacute
15836 \DeclareTextCompositeCommand{\v}{PU}{G}{\81\364}% U+01F4
15837 % U+01F5 LATIN SMALL LETTER G WITH ACUTE; gacute
15838 \DeclareTextCompositeCommand{\v}{PU}{g}{\81\365}% U+01F5
15839 % U+01F8 LATIN CAPITAL LETTER N WITH GRAVE
15840 \DeclareTextCompositeCommand{\v}{PU}{N}{\81\370}% U+01F8
15841 % U+01F9 LATIN SMALL LETTER N WITH GRAVE
15842 \DeclareTextCompositeCommand{\v}{PU}{n}{\81\371}% U+01F9
15843 % U+01FC LATIN CAPITAL LETTER AE WITH ACUTE; AEacute
15844 \DeclareTextCompositeCommand{\v}{PU}{AE}{\81\374}% U+01FC
15845 % U+01FD LATIN SMALL LETTER AE WITH ACUTE; aeacute
15846 \DeclareTextCompositeCommand{\v}{PU}{ae}{\81\375}% U+01FD
15847 % U+01FE LATIN CAPITAL LETTER O WITH STROKE AND ACUTE;
15848 % *Oslashacute, Ostrokeacute
15849 \DeclareTextCompositeCommand{\v}{PU}{O}{\81\376}% U+01FE
15850 % U+01FF LATIN SMALL LETTER O WITH STROKE AND ACUTE;
15851 % *oslashacute, ostrokeacute
15852 \DeclareTextCompositeCommand{\v}{PU}{o}{\81\377}% U+01FF
15853 </puenc>
15854 <*puextra>
15855 % U+0200 LATIN CAPITAL LETTER A WITH DOUBLE GRAVE; Adblgrave
15856 \DeclareTextCompositeCommand{\G}{PU}{A}{\82\000}% U+0200
15857 % U+0201 LATIN SMALL LETTER A WITH DOUBLE GRAVE; adblgrave
15858 \DeclareTextCompositeCommand{\G}{PU}{a}{\82\001}% U+0201
15859 % U+0204 LATIN CAPITAL LETTER E WITH DOUBLE GRAVE; Edblgrave
15860 \DeclareTextCompositeCommand{\G}{PU}{E}{\82\004}% U+0204
15861 % U+0205 LATIN SMALL LETTER E WITH DOUBLE GRAVE; edblgrave
15862 \DeclareTextCompositeCommand{\G}{PU}{e}{\82\005}% U+0205
15863 </puextra>
15864 <*puenc>
15865 % U+0206 LATIN CAPITAL LETTER E WITH INVERTED BREVE; Einvert-
edbrev
15866 \DeclareTextCompositeCommand{\textinvbreve}{PU}{E}{\82\006}% U+0206
15867 % U+0207 LATIN SMALL LETTER E WITH INVERTED BREVE; einverted-
breve
15868 \DeclareTextCompositeCommand{\textinvbreve}{PU}{e}{\82\007}% U+0207
15869 </puenc>
15870 <*puextra>

```

```

15871 % U+0208 LATIN CAPITAL LETTER I WITH DOUBLE GRAVE; Idblgrave
15872 \DeclareTextCompositeCommand{\G}{PU}{I}{\82\010}% U+0208
15873 % U+0209 LATIN SMALL LETTER I WITH DOUBLE GRAVE; idblgrave
15874 \DeclareTextCompositeCommand{\G}{PU}{\i}{\82\011}% U+0209
15875 \DeclareTextCompositeCommand{\G}{PU}{i}{\82\011}% U+0209
15876 </puextra>
15877 <*puenc>
15878 % U+020A LATIN CAPITAL LETTER I WITH INVERTED BREVE; linverted-
breve
15879 \DeclareTextCompositeCommand{\textinvbreve}{PU}{I}{\82\012}% U+020A
15880 % U+020B LATIN SMALL LETTER I WITH INVERTED BREVE; iinverted-
breve
15881 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\i}{\82\013}% U+020B
15882 \DeclareTextCompositeCommand{\textinvbreve}{PU}{\i}{\82\013}% U+020B
15883 </puenc>
15884 <*puextra>
15885 % U+020C LATIN CAPITAL LETTER O WITH DOUBLE GRAVE; Odblgrave
15886 \DeclareTextCompositeCommand{\G}{PU}{O}{\82\014}% U+020C
15887 % U+020D LATIN SMALL LETTER O WITH DOUBLE GRAVE; odblgrave
15888 \DeclareTextCompositeCommand{\G}{PU}{o}{\82\015}% U+020D
15889 </puextra>
15890 <*puenc>
15891 % U+020E LATIN CAPITAL LETTER O WITH INVERTED BREVE; Oinvert-
edbrev
15892 \DeclareTextCompositeCommand{\textinvbreve}{PU}{O}{\82\016}% U+020E
15893 % U+020F LATIN SMALL LETTER O WITH INVERTED BREVE; oinverted-
breve
15894 \DeclareTextCompositeCommand{\textinvbreve}{PU}{o}{\82\017}% U+020F
15895 </puenc>
15896 <*puextra>
15897 % U+0210 LATIN CAPITAL LETTER R WITH DOUBLE GRAVE; Rdblgrave
15898 \DeclareTextCompositeCommand{\G}{PU}{R}{\82\020}% U+0210
15899 % U+0211 LATIN SMALL LETTER R WITH DOUBLE GRAVE; rdblgrave
15900 \DeclareTextCompositeCommand{\G}{PU}{r}{\82\021}% U+0211
15901 % U+0214 LATIN CAPITAL LETTER U WITH DOUBLE GRAVE; Udblgrave
15902 \DeclareTextCompositeCommand{\G}{PU}{U}{\82\024}% U+0214
15903 % U+0215 LATIN SMALL LETTER U WITH DOUBLE GRAVE; udblgrave
15904 \DeclareTextCompositeCommand{\G}{PU}{u}{\82\025}% U+0215
15905 </puextra>
15906 <*puenc>
15907 % U+0216 LATIN CAPITAL LETTER U WITH INVERTED BREVE; Uinvert-
edbrev
15908 \DeclareTextCompositeCommand{\textinvbreve}{PU}{U}{\82\026}% U+0216
15909 % U+0217 LATIN SMALL LETTER U WITH INVERTED BREVE; uinverted-
breve
15910 \DeclareTextCompositeCommand{\textinvbreve}{PU}{u}{\82\027}% U+0217
15911 % U+021E LATIN CAPITAL LETTER H WITH CARON
15912 \DeclareTextCompositeCommand{\v}{PU}{H}{\82\036}% U+021E
15913 % U+021F LATIN SMALL LETTER H WITH CARON
15914 \DeclareTextCompositeCommand{\v}{PU}{h}{\82\037}% U+021F
15915 % U+0221 LATIN SMALL LETTER D WITH CURL; \textctd (tipa)
15916 \DeclareTextCommand{\textctd}{PU}{\82\041}% U+0221
15917 % U+0225 LATIN SMALL LETTER Z WITH HOOK; \textcommatailz (tipa)
15918 \DeclareTextCommand{\textcommatailz}{PU}{\82\045}% U+0225

```

```

15919 % U+0226 LATIN CAPITAL LETTER A WITH DOT ABOVE
15920 \DeclareTextCompositeCommand{.}{PU}{A}{\82\046}% U+0226
15921 % U+0227 LATIN SMALL LETTER A WITH DOT ABOVE
15922 \DeclareTextCompositeCommand{.}{PU}{a}{\82\047}% U+0227
15923 % U+0228 LATIN CAPITAL LETTER E WITH CEDILLA
15924 \DeclareTextCompositeCommand{\c}{PU}{E}{\82\050}% U+0228
15925 % U+0229 LATIN SMALL LETTER E WITH CEDILLA
15926 \DeclareTextCompositeCommand{\c}{PU}{e}{\82\051}% U+0229
15927 % U+022E LATIN CAPITAL LETTER O WITH DOT ABOVE
15928 \DeclareTextCompositeCommand{.}{PU}{O}{\82\056}% U+022E
15929 % U+022F LATIN SMALL LETTER O WITH DOT ABOVE
15930 \DeclareTextCompositeCommand{.}{PU}{o}{\82\057}% U+022F
15931 % U+0232 LATIN CAPITAL LETTER Y WITH MACRON
15932 \DeclareTextCompositeCommand{\=}{PU}{Y}{\82\062}% U+0232
15933 % U+0233 LATIN SMALL LETTER Y WITH MACRON
15934 \DeclareTextCompositeCommand{\=}{PU}{y}{\82\063}% U+0233
15935 % U+0235 LATIN SMALL LETTER N WITH CURL; \textctn (tipa)
15936 \DeclareTextCommand{\textctn}{PU}{\82\065}% U+0235
15937 % U+0236 LATIN SMALL LETTER T WITH CURL; \textctt (tipa)
15938 \DeclareTextCommand{\textctt}{PU}{\82\066}% U+0236
15939 % U+0237 LATIN SMALL LETTER DOTLESS J
15940 \DeclareTextCommand{\j}{PU}{\82\067}% U+0237
15941 % U+0238 LATIN SMALL LETTER DB DIGRAPH; \textdblig (tipx)
15942 \DeclareTextCommand{\textPUDblig}{PU}{\82\070}% U+0238
15943 %* \textPUDblig -> \textdblig (tipx)
15944 % U+0239 LATIN SMALL LETTER QP DIGRAPH; \textqplig (tipx)
15945 \DeclareTextCommand{\textPUqplig}{PU}{\82\071}% U+0239
15946 %* \textPUqplig -> \textqplig (tipx)
15947 % U+023C LATIN SMALL LETTER C WITH STROKE; \slashc (wsipa)
15948 \DeclareTextCommand{\textslashc}{PU}{\82\074}%* U+023C
15949 %* \textslashc -> \textcentoldstyle (textcomp)
15950 % With bar instead of stroke:
15951 %* \textslashc -> \textbarc (tipa)

```

46.2.6 IPA Extensions: U+0250 to U+02AF

```

15952 % U+0250 LATIN SMALL LETTER TURNED A; aturned; \textturna (tipa)
15953 \DeclareTextCommand{\textturna}{PU}{\82\120}% U+0250
15954 %* \textturna -> \inva (wasysym)
15955 % U+0251 LATIN SMALL LETTER ALPHA/LATIN SMALL LETTER
15956 % SCRIPT A; ascript; \textscripta (tipa), \scripta (wsipa)
15957 \DeclareTextCommand{\textscripta}{PU}{\82\121}%* U+0251
15958 %* \textscripta -> \vara (phonetic)
15959 % U+0252 LATIN SMALL LETTER TURNED ALPHA; ascriptturned;
15960 % \textturnscripta (tipa)
15961 \DeclareTextCommand{\textturnscripta}{PU}{\82\122}% U+0252
15962 %* \textturnscripta -> \invscripta (wsipa)
15963 %* \textturnscripta -> \rotvara (phonetic)
15964 % U+0253 LATIN CAPITAL LETTER B WITH HOOK; bhook; \texthtb (tipa)
15965 \DeclareTextCommand{\texthtb}{PU}{\82\123}% U+0253
15966 % \texthtb -> \hookb (wsipa)
15967 %* \texthtb -> \hausab (phonetic)
15968 % U+0254 LATIN SMALL LETTER OPEN O; oopen;
15969 % \textopeno (tipa), \openo (wasysym)
15970 \DeclareTextCommand{\textopeno}{PU}{\82\124}%* U+0254

```

```

15971 %* \textopeno -> \varopeno (phonetic)
15972 % U+0255 LATIN SMALL LETTER C WITH CURL; ccurl; \textctc (tipa)
15973 \DeclareTextCommand{\textctc}{\PU}{\82\125}% U+0255
15974 %* \textctc -> \curlyc (wsuipa)
15975 % U+0256 LATIN SMALL LETTER D WITH TAIL; dtail; \textrtaild (tipa)
15976 \DeclareTextCommand{\textrtaild}{\PU}{\82\126}%* U+0256
15977 %* \textrtaild -> \taild (wsuipa)
15978 % U+0257 LATIN SMALL LETTER D WITH HOOK; dhook; \texthtd (tipa)
15979 \DeclareTextCommand{\texthtd}{\PU}{\82\127}% U+0257
15980 %* \texthtd -> \hookd (wsuipa)
15981 %* \texthtd -> \hausad (phonetic)
15982 % U+0258 LATIN SMALL LETTER REVERSED E; eversed;
15983 % \textreve (tipa), \reve (wsuipa)
15984 \DeclareTextCommand{\textreve}{\PU}{\82\130}%* U+0258
15985 % U+0259 LATIN SMALL LETTER SCHWA; schw;
15986 % \textscha (tipa), \schwa (wsuipa, phonetic)
15987 \DeclareTextCommand{\textscha}{\PU}{\82\131}%* U+0259
15988 % U+025A LATIN SMALL LETTER SCHWA WITH HOOK; schwahook;
15989 % \textrhookschwa (tipa)
15990 \DeclareTextCommand{\textrhookschwa}{\PU}{\82\132}% U+025A
15991 %* \textrhookschwa -> \er (wsuipa)
15992 % U+025B LATIN SMALL LETTER OPEN E/LATIN SMALL LETTER EP-
    SILON; eopen;
15993 % \niepsilon (wsuipa)
15994 \DeclareTextCommand{\textniepsilon}{\PU}{\82\133}%* U+025B
15995 %* \textniepsilon -> \epsi (phonetic)
15996 % U+025C LATIN SMALL LETTER REVERSED OPEN E; eopenreversed;
15997 % \textrevepsilon (tipa), \revepsilon (wsuipa)
15998 \DeclareTextCommand{\textrevepsilon}{\PU}{\82\134}%* U+025C
15999 % U+025D LATIN SMALL LETTER REVERSED OPEN E WITH HOOK; eopen-
    reversedhook;
16000 % \textrhookrevepsilon (tipa)
16001 \DeclareTextCommand{\textrhookrevepsilon}{\PU}{\82\135}%* U+025D
16002 %* \textrhookrevepsilon -> \hookrevepsilon (wsuipa)
16003 % U+025E LATIN SMALL LETTER CLOSED REVERSED OPEN E; eopenre-
    versedclosed;
16004 % \textcloserevepsilon (tipa)
16005 \DeclareTextCommand{\textcloserevepsilon}{\PU}{\82\136}% U+025E
16006 %* \textcloserevepsilon -> \closedrevepsilon (wsuipa)
16007 % U+025F LATIN SMALL LETTER DOTLESS J WITH STROKE; jdot-
    lessstroke;
16008 % \textbardotlessj (tipa)
16009 \DeclareTextCommand{\textbardotlessj}{\PU}{\82\137}% U+025F
16010 %* \textbardotlessj -> \barj (phonetic)
16011 % U+0260 LATIN SMALL LETTER G WITH HOOK; ghook; \texthtg (tipa)
16012 \DeclareTextCommand{\texthtg}{\PU}{\82\140}% U+0260
16013 %* \texthtg -> \hookg (wsuipa)
16014 % U+0261 LATIN SMALL LETTER SCRIPT G; gscript;
16015 % \textscriptg (tipa), \scriptg (wsuipa)
16016 \DeclareTextCommand{\textscriptg}{\PU}{\82\141}%* U+0261
16017 %* \textscriptg -> \varg (phonetic)
16018 % U+0262 LATIN LETTER SMALL CAPITAL G; \textscg (tipa), \scg (wsuipa)
16019 \DeclareTextCommand{\textscg}{\PU}{\82\142}%* U+0262
16020 % U+0263 LATIN SMALL LETTER GAMMA; gammalatinsmall;

```

```

16021 % \ipagamma (wsuipa), \vod (phonetic)
16022 \DeclareTextCommand{\textipagamma}{\PU}{\82\143} %* U+0263
16023 %* \textipagamma -> \vod (phonetic)
16024 % U+0264 LATIN SMALL LETTER RAMS HORN; ramshorn;
16025 % \babygamma (wsuipa)
16026 \DeclareTextCommand{\textbabypgamma}{\PU}{\82\144} %* U+0264
16027 % U+0265 LATIN SMALL LETTER TURNED H; hturned; \textturnh (tipa)
16028 \DeclareTextCommand{\textturnh}{\PU}{\82\145} %* U+0265
16029 %* \textturnh -> \invh (wsuipa)
16030 %* \textturnh -> \udesc (phonetic)
16031 % U+0266 LATIN SMALL LETTER H WITH HOOK; hhook; \texthth (tipa)
16032 \DeclareTextCommand{\texthth}{\PU}{\82\146} %* U+0266
16033 %* \texthth -> \hookh (wsuipa)
16034 %* \texthth -> \voicedh (phonetic)
16035 % U+0267 LATIN SMALL LETTER HENG WITH HOOK; henghook; \texthheng (tipa)
16036 \DeclareTextCommand{\texthheng}{\PU}{\82\147} %* U+0267
16037 %* \texthheng -> \hookheng (wsuipa)
16038 % U+0268 LATIN SMALL LETTER I WITH STROKE;
16039 % \textbari (tipa), \bari (wsuipa)
16040 \DeclareTextCommand{\textbari}{\PU}{\82\150} %* U+0268
16041 %* \textbari -> \bari (phonetic)
16042 % U+0269 LATIN SMALL LETTER IOTA; iotalatin; \niiota (wsuipa)
16043 \DeclareTextCommand{\textniiota}{\PU}{\82\151} %* U+0269
16044 %* \textniiota -> \vari (phonetic)
16045 % U+026A LATIN LETTER SMALL CAPITAL I; \textsci (tipa), \sci (wsuipa)
16046 \DeclareTextCommand{\textsci}{\PU}{\82\152} %* U+026A
16047 % U+026B LATIN SMALL LETTER L WITH MIDDLE TILDE; lmiddletilde;
16048 % \textltildel (tipa)
16049 \DeclareTextCommand{\textltildel}{\PU}{\82\153} %* U+026B
16050 %* \textltildel -> \tildel (wsuipa)
16051 % U+026C LATIN SMALL LETTER L WITH BELT; lbel; \textbeltl (tipa)
16052 \DeclareTextCommand{\textbeltl}{\PU}{\82\154} %* U+026C
16053 %* \textbeltl -> \latfric (wsuipa)
16054 % U+026D LATIN SMALL LETTER L WITH RETROFLEX HOOK;
16055 % \hookretroflex; \textrtaill (tipa)
16056 \DeclareTextCommand{\textrtaill}{\PU}{\82\155} %* U+026D
16057 %* \textrtaill -> \taill (wsuipa)
16058 % U+026E LATIN SMALL LETTER LEZH; lezh; \textlyoghl (tipa)
16059 \DeclareTextCommand{\textlyoghl}{\PU}{\82\156} %* U+026E
16060 %* \textlyoghl -> \lz (wsuipa)
16061 % U+026F LATIN SMALL LETTER TURNED M; mturned; \textturnm (tipa)
16062 \DeclareTextCommand{\textturnm}{\PU}{\82\157} %* U+026F
16063 %* \textturnm -> \invm (wsuipa)
16064 %* \textturnm -> \rotm (phonetic)
16065 % U+0270 LATIN SMALL LETTER TURNED M WITH LONG LEG; mlongleg-
16066 % \textturnmrleg (tipa)
16067 \DeclareTextCommand{\textturnmrleg}{\PU}{\82\160} %* U+0270
16068 %* \textturnmrleg -> \legm (wsuipa)
16069 % U+0271 LATIN SMALL LETTER M WITH HOOK; mhook; \textltailm (tipa)
16070 \DeclareTextCommand{\textltailm}{\PU}{\82\161} %* U+0271
16071 %* \textltailm -> \labdentalnas (wsuipa)
16072 %* \textltailm -> \emgma (phonetic)

```

```

16073 % U+0272 LATIN SMALL LETTER N WITH LEFT HOOK; nhookleft; \textltailn (tipa)
16074 \DeclareTextCommand{\textltailn}{\PU}{\82\162}% U+0272
16075 %* \textltailn -> \nj (wsuipa)
16076 %* \textltailn -> \enya (phonetic)
16077 % U+0273 LATIN SMALL LETTER N WITH RETROFLEX HOOK;
16078 % nhookretroflex; \textrtailn (tipa)
16079 \DeclareTextCommand{\textrtailn}{\PU}{\82\163}% U+0273
16080 %* \textrtailn -> \tailn (wsuipa)
16081 % U+0274 LATIN LETTER SMALL CAPITAL N; \textscn (tipa), \scn (wsuipa)
16082 \DeclareTextCommand{\textscn}{\PU}{\82\164}%* U+0274
16083 % U+0275 LATIN CAPITAL LETTER O WITH MIDDLE TILDE/
16084 % LATIN CAPITAL LETTER BARRED O; obarred;
16085 % \textbaro (tipa), \baro (wsuipa)
16086 % But \baro from stmaryrd is different!
16087 \DeclareTextCommand{\textbaro}{\PU}{\82\165}% U+0275
16088 % U+0276 LATIN LETTER SMALL CAPITAL OE; \textscoelig (tipa)
16089 \DeclareTextCommand{\textscoelig}{\PU}{\82\166}% U+0276
16090 % U+0277 LATIN SMALL LETTER CLOSED OMEGA; omegalatinclosed;
16091 % \textcloseomega (tipa)
16092 \DeclareTextCommand{\textcloseomega}{\PU}{\82\167}% U+0277
16093 %* \textcloseomega -> \closedniomega (wsuipa)
16094 %* \textcloseomega -> \varomega (phonetic)
16095 % U+0278 LATIN SMALL LETTER PHI; philatin; \niph (wsuipa)
16096 \DeclareTextCommand{\textniph}{\PU}{\82\170}%* U+0278
16097 % U+0279 LATIN SMALL LETTER TURNED R; rturned; \textturnr (tipa)
16098 \DeclareTextCommand{\textturnr}{\PU}{\82\171}% U+0279
16099 %* \textturnr -> \invr (wsuipa)
16100 %* \textturnr -> \rotr (phonetic)
16101 % U+027A LATIN SMALL LETTER TURNED R WITH LONG LEG;
16102 % rlonglegturned; \textturnlongegr (tipa)
16103 \DeclareTextCommand{\textturnlongegr}{\PU}{\82\172}% U+027A
16104 %* \textturnlongegr -> \invlegr (wsuipa)
16105 % U+027B LATIN SMALL LETTER TURNED R WITH HOOK; rhookturned;
16106 % \textturnrrtail (tipa)
16107 \DeclareTextCommand{\textturnrrtail}{\PU}{\82\173}% U+027B
16108 %* \textturnrrtail -> \tailinvr (wsuipa)
16109 % U+027C LATIN SMALL LETTER R WITH LONG LEG; rlongleg; \textlongegr (tipa)
16110 \DeclareTextCommand{\textlongegr}{\PU}{\82\174}%* U+027C
16111 %* \textlongegr -> \legr (wsuipa)
16112 % U+027D LATIN SMALL LETTER R WITH TAIL; rhook; \textrtailr (tipa)
16113 \DeclareTextCommand{\textrtailr}{\PU}{\82\175}% U+027D
16114 %* \textrtailr -> \tailr (wsuipa)
16115 % U+027E LATIN SMALL LETTER R WITH FISHHOOK; rfishhook;
16116 % \textfishhookr (tipa)
16117 \DeclareTextCommand{\textfishhookr}{\PU}{\82\176}% U+027E
16118 %* \textfishhookr -> \flapr (wsuipa)
16119 %* \textfishhookr -> \flap (phonetic)
16120 % U+027F LATIN SMALL LETTER REVERSED R WITH FISHHOOK; rfishhookreversed;
16121 % \textlhtlongi (tipa)
16122 \DeclareTextCommand{\textlhtlongi}{\PU}{\82\177}% U+027F
16123 % U+0280 LATIN LETTER SMALL CAPITAL R; \textscr (tipa), \scr (wsuipa)

```

```

16124 \DeclareTextCommand{\textscr}{\PU}{\82\200}/* U+0280
16125 % U+0281 LATIN LETTER SMALL CAPITAL INVERTED R; Rsmallinverted;
16126 % \textinvscr (tipa), \invscr (wsuipa)
16127 \DeclareTextCommand{\textinvscr}{\PU}{\82\201}/* U+0281
16128 % U+0282 LATIN SMALL LETTER S WITH HOOK; shook; \textrtails (tipa)
16129 \DeclareTextCommand{\textrtails}{\PU}{\82\202}/* U+0282
16130 /* \textrtails -> \tails (wsuipa)
16131 % U+0283 LATIN SMALL LETTER ESH; esh; \textesh (tipa), \esh (wsuipa)
16132 \DeclareTextCommand{\textesh}{\PU}{\82\203}/* U+0283
16133 % U+0284 LATIN SMALL LETTER DOTLESS J WITH STROKE AND HOOK;
16134 % dotlessjstrokehook; \texthtbardotlessj (tipa)
16135 \DeclareTextCommand{\texthtbardotlessj}{\PU}{\82\204}/* U+0284
16136 % U+0285 LATIN SMALL LETTER SQUAT REVERSED ESH; eshsquatre-
16137 % versed;
16138 % \textvibyi (tipa)
16139 \DeclareTextCommand{\textvibyi}{\PU}{\82\205}/* U+0285
16140 % U+0286 LATIN SMALL LETTER ESH WITH CURL; eshcurl; \textctesh (tipa)
16141 /* \textctesh -> \curlyesh (wsuipa)
16142 % U+0287 LATIN SMALL LETTER TURNED T; tturned; \textturnt (tipa)
16143 \DeclareTextCommand{\textturnt}{\PU}{\82\207}/* U+0287
16144 /* \textturnt -> \clickt (wsuipa)
16145 % U+0288 LATIN SMALL LETTER T WITH RETROFLEX HOOK; tretroflex-
16146 % \textrtail (tipa)
16147 \DeclareTextCommand{\textrtail}{\PU}{\82\210}/* U+0288
16148 /* \textrtail -> \tailt (wsuipa)
16149 % U+0289 LATIN SMALL LETTER U BAR; ubar;
16150 % \textbaru (tipa), \baru (wsuipa)
16151 \DeclareTextCommand{\textbaru}{\PU}{\82\211}/* U+0289
16152 /* \textbaru -> \ubar (phonetic)
16153 % U+028A LATIN SMALL LETTER UPSILON; \niupsilon (wsuipa)
16154 \DeclareTextCommand{\textniupsilon}{\PU}{\82\212}/* U+028A
16155 /* \textniupsilon -> \rotOmega (phonetic)
16156 % U+028B LATIN SMALL LETTER V WITH HOOK/LATIN SMALL LET-
16157 % TER SCRIPT V;
16158 % \textscriptv (tipa), \scriptv (wsuipa)
16159 % U+028C LATIN SMALL LETTER TURNED V; vturned; \textturnv (tipa)
16160 \DeclareTextCommand{\textturnv}{\PU}{\82\214}/* U+028C
16161 /* \textturnv -> \invv (wsuipa)
16162 /* \textturnv -> \pwedge (phonetic)
16163 % U+028D LATIN SMALL LETTER TURNED W; wturned; \textturnw (tipa)
16164 \DeclareTextCommand{\textturnw}{\PU}{\82\215}/* U+028D
16165 /* \textturnw -> \invw (wsuipa)
16166 /* \textturnw -> \rotw (phonetic)
16167 % U+028E LATIN SMALL LETTER TURNED Y; yturned; \textturny (tipa)
16168 \DeclareTextCommand{\textturny}{\PU}{\82\216}/* U+028E
16169 /* \textturny -> \invy (wsuipa)
16170 /* \textturny -> \roty (phonetic)
16171 % U+028F LATIN LETTER SMALL CAPITAL Y; \textscy (tipa), \scy (wsuipa)
16172 \DeclareTextCommand{\textscy}{\PU}{\82\217}/* U+028F
16173 % U+0290 LATIN SMALL LETTER Z WITH RETROFLEX HOOK; zretroflex-
16174 % hook;

```

```

16174 % \texttailz (tipa)
16175 \DeclareTextCommand{\texttailz}{\PU}{\82\220}% U+0290
16176 %* \texttailz -> \tailz (wsuipa)
16177 % U+0291 LATIN SMALL LETTER Z WITH CURL; zcurl; \textcz (tipa)
16178 \DeclareTextCommand{\textcz}{\PU}{\82\221}% U+0291
16179 %* \textcz -> \curlyz (wsuipa)
16180 % U+0292 LATIN SMALL LETTER EZH/LATIN SMALL LETTER YOGH; ezh;
16181 % \textyogh (tipa), \yogh (wsuipa)
16182 \DeclareTextCommand{\textyogh}{\PU}{\82\222}%* U+0292
16183 % U+0293 LATIN SMALL LETTER EZH WITH CURL/LATIN SMALL LET-
TER YOGH CURL;
16184 % ezhcurl; \textctyogh (tipa)
16185 \DeclareTextCommand{\textctyogh}{\PU}{\82\223}% U+0293
16186 %* \textctyogh -> \curlyyogh (wsuipa)
16187 % U+0294 LATIN LETTER GLOTTAL STOP; glottalstop;
16188 % \textglotstop (tipa), \glotstop (wsuipa)
16189 \DeclareTextCommand{\textglotstop}{\PU}{\82\224}%* U+0294
16190 %* \textglotstop -> \ejective (wsuipa)
16191 %* \textglotstop -> \glottal (phonetic)
16192 % U+0295 LATIN LETTER PHARYNGEAL VOICED FRICATIVE/
16193 % LATIN LETTER REVERSED GLOTTAL STOP; glottalstopreversed;
16194 % \textrevglotstop (tipa), \revglotstop (wsuipa)
16195 \DeclareTextCommand{\textrevglotstop}{\PU}{\82\225}%* U+0295
16196 %* \textrevglotstop -> \reveject (wsuipa)
16197 % U+0296 LATIN LETTER INVERTED GLOTTAL STOP; glottalstopinverted;
16198 % \textinvglotstop (tipa), \invglotstop (wsuipa)
16199 \DeclareTextCommand{\textinvglotstop}{\PU}{\82\226}%* U+0296
16200 % U+0297 LATIN LETTER STRETCHED C; cstretched; \textstretchc (tipa)
16201 \DeclareTextCommand{\textstretchc}{\PU}{\82\227}% U+0297
16202 %* \textstretchc -> \clickc (wsuipa)
16203 %* \textstretchc -> \textstretchvar (tipx)
16204 % U+0298 LATIN LETTER BILABIAL CLICK; bilabialclick;
16205 % \textbullseye (tipa)
16206 \DeclareTextCommand{\textbullseye}{\PU}{\82\230}% U+0298
16207 %* \textbullseye -> \clickb (wsuipa)
16208 %* \textbullseye -> \textObullseye (tipx)
16209 % U+0299 LATIN LETTER SMALL CAPITAL B; \textscb (tipa)
16210 \DeclareTextCommand{\textscb}{\PU}{\82\231}% U+0299
16211 % U+029A LATIN SMALL LETTER CLOSED OPEN E; eopenclosed;
16212 % \textclosepsilon (tipa)
16213 \DeclareTextCommand{\textclosepsilon}{\PU}{\82\232}% U+029A
16214 % U+029B LATIN LETTER SMALL CAPITAL G WITH HOOK; Gsmallhook;
16215 % \texthtscg (tipa)
16216 \DeclareTextCommand{\texthtscg}{\PU}{\82\233}% U+029B
16217 % U+029C LATIN LETTER SMALL CAPITAL H; \textsch (tipa)
16218 \DeclareTextCommand{\textsch}{\PU}{\82\234}% U+029C
16219 % U+029D LATIN SMALL LETTER J WITH CROSS-TAIL; jcrossed-
tail; \textcdj (tipa)
16220 \DeclareTextCommand{\textctj}{\PU}{\82\235}% U+029D
16221 %* \textctj -> \textctjvar (tipx)
16222 % U+029E LATIN SMALL LETTER TURNED K; kturned; \textturnk (tipa)
16223 \DeclareTextCommand{\textturnk}{\PU}{\82\236}% U+029E
16224 %* \textturnk -> \textturnsck (tipx)
16225 % U+029F LATIN LETTER SMALL CAPITAL L; \textscl (tipa)

```

```

16226 \DeclareTextCommand{\textsc}{\PU{\82\237}}% U+029F
16227 % U+02A0 LATIN SMALL LETTER Q WITH HOOK; qhook; \texthtq (tipa)
16228 \DeclareTextCommand{\texthtq}{\PU{\82\240}}% U+02A0
16229 % U+02A1 LATIN LETTER GLOTTAL STOP WITH STROKE; glottalstop-
    stroke;
16230 % \textbarglotstop (tipa)
16231 \DeclareTextCommand{\textbarglotstop}{\PU{\82\241}}% U+02A1
16232 % U+02A2 LATIN LETTER REVERSED GLOTTAL STOP WITH STROKE/
16233 %   LATIN LETTER REVERSED GLOTTAL STOP BAR; glottalstopstrokere-
    versed;
16234 % \textbarrevglotstop (tipa)
16235 \DeclareTextCommand{\textbarrevglotstop}{\PU{\82\242}}% U+02A2
16236 % U+02A3 LATIN SMALL LETTER DZ DIGRAPH; dzaltone; \textdzlig (tipa)
16237 \DeclareTextCommand{\textdzlig}{\PU{\82\243}}% U+02A3
16238 %* \textdzlig -> \dz (wsupipa)
16239 % U+02A4 LATIN SMALL LETTER DEZH DIGRAPH; dezh; \textdyogh-
    lig (tipa)
16240 \DeclareTextCommand{\textdyoghlig}{\PU{\82\244}}% U+02A4
16241 % U+02A5 LATIN SMALL LETTER DZ DIGRAPH WITH CURL; dzcurl;
16242 % \textdctzlig (tipa)
16243 \DeclareTextCommand{\textdctzlig}{\PU{\82\245}}% U+02A5
16244 % U+02A6 LATIN SMALL LETTER TS DIGRAPH; ts; \texttslig (tipa)
16245 \DeclareTextCommand{\texttslig}{\PU{\82\246}}% U+02A6
16246 % U+02A7 LATIN SMALL LETTER TESH DIGRAPH; tesh; \textteshlig (tipa)
16247 \DeclareTextCommand{\textteshlig}{\PU{\82\247}}% U+02A7
16248 %* \textteshlig -> \tesh (wsupipa)
16249 % U+02A8 LATIN SMALL LETTER TC DIGRAPH WITH CURL; tcurl;
16250 % \texttctclig (tipa)
16251 \DeclareTextCommand{\texttctclig}{\PU{\82\250}}% U+02A8
16252 % U+02AE LATIN SMALL LETTER TURNED H WITH FISHHOOK;
16253 % \textlhtlongy (tipa)
16254 \DeclareTextCommand{\textlhtlongy}{\PU{\82\256}}% U+02AE
16255 % U+02AF LATIN SMALL LETTER TURNED H WITH FISHHOOK AND TAIL;
16256 % \textvibyy (tipa)
16257 \DeclareTextCommand{\textvibyy}{\PU{\82\257}}% U+02AF

```

46.2.7 Spacing Modifier Letters: U+02B0 to U+02FF

```

16258 % U+02BD MODIFIER LETTER REVERSED COMMA;
16259 % commareversedmod, afii64937; \textrevapostrophe (tipa)
16260 \DeclareTextCommand{\textrevapostrophe}{\PU{\82\275}}% U+02BD
16261 % U+02C0 MODIFIER LETTER GLOTTAL STOP; glottalstopmod;
16262 % \textraiseglotstop (tipa)
16263 \DeclareTextCommand{\textraiseglotstop}{\PU{\82\300}}% U+02C0
16264 % U+02C2 MODIFIER LETTER LEFT ARROWHEAD; arrowheadleftmod;
16265 % \textlptr (tipa)
16266 \DeclareTextCommand{\textlptr}{\PU{\82\302}}% U+02C2
16267 % U+02C3 MODIFIER LETTER RIGHT ARROWHEAD; arrowheadrightmod;
16268 % \textrptr (tipa)
16269 \DeclareTextCommand{\textrptr}{\PU{\82\303}}% U+02C3
16270 % U+02C7 CARON; caron
16271 \DeclareTextCommand{\textasciicaron}{\PU{\82\307}}% U+02C7
16272 % U+02C8 MODIFIER LETTER VERTICAL LINE; verticalinemod;
16273 % \textprimstress (tipa)
16274 \DeclareTextCommand{\textprimstress}{\PU{\82\310}}% U+02C8

```

```

16275 % U+02CC MODIFIER LETTER LOW VERTICAL LINE; verticallinelowmod;
16276 % \textsecstress (tipa)
16277 \DeclareTextCommand{\textsecstress}{PU}{\82\314}% U+02CC
16278 % U+02D0 MODIFIER LETTER TRIANGULAR COLON; colontriangularmod;
16279 % \textlengthmark (tipa)
16280 \DeclareTextCommand{\textlengthmark}{PU}{\82\320}% U+02D0
16281 % U+02D1 MODIFIER LETTER HALF TRIANGULAR COLON; colontriangularhalfmod;
16282 % \texthalflength (tipa)
16283 \DeclareTextCommand{\texthalflength}{PU}{\82\321}% U+02D1
16284 % U+02D8 BREVE; breve
16285 \DeclareTextCommand{\textasciibreve}{PU}{\82\330}% U+02D8
16286 % U+02D9 DOT ABOVE; dotaccent
16287 \DeclareTextCommand{\textdotaccent}{PU}{\82\331}% U+02D9
16288 % U+02DA RING ABOVE; ring
16289 \DeclareTextCommand{\textring}{PU}{\82\332}% U+02DA
16290 % U+02DB OGONEK; ogonek
16291 \DeclareTextCommand{\textogonek}{PU}{\82\333}% U+02DB
16292 % U+02DC SMALL TILDE; ilde, *tilde
16293 \DeclareTextCommand{\texttilde}{PU}{\82\334}% U+02DC
16294 % U+02DD DOUBLE ACUTE ACCENT; hungarumlaut
16295 \DeclareTextCommand{\texthungarumlaut}{PU}{\82\335}% U+02DD
16296 \DeclareTextCommand{\textacutedbl}{PU}{\82\335}% U+02DD
16297 % U+02F3 MODIFIER LETTER LOW RING
16298 \DeclareTextCommand{\textringlow}{PU}{\82\363}% U+02F3
16299 % U+02F5 MODIFIER LETTER MIDDLE DOUBLE GRAVE ACCENT
16300 \DeclareTextCommand{\textgravedbl}{PU}{\82\365}% U+02F5
16301 % U+02F7 MODIFIER LETTER LOW TILDE
16302 \DeclareTextCommand{\texttildelow}{PU}{\82\367}% U+02F7
16303 % U+02F9 MODIFIER LETTER BEGIN HIGH TONE; \textopencorner (tipa)
16304 \DeclareTextCommand{\textopencorner}{PU}{\82\371}% U+02F9
16305 % U+02FA MODIFIER LETTER END HIGH TONE; \textcorner (tipa)
16306 \DeclareTextCommand{\textcorner}{PU}{\82\372}% U+02FA

```

46.2.8 Combining Diacritical Marks: U+0300 to U+036F

```

16307 % U+030F COMBINING DOUBLE GRAVE ACCENT; dblgravecmb
16308 \DeclareTextCommand{\textdoublegrave}{PU}{\83\017}% U+030F
16309 % U+0311 COMBINING INVERTED BREVE; breveinvertedcmb
16310 \DeclareTextCommand{\textnewtie}{PU}{\83\021}% U+0311
16311 % U+0323 COMBINING DOT BELOW; dotbelowcmb, *dotbelowcomb
16312 \DeclareTextCommand{\textdotbelow}{PU}{\83\043}% U+0323
16313 % U+0331 COMBINING MACRON BELOW; macronbelowcmb
16314 \DeclareTextCommand{\textmacronbelow}{PU}{\83\061}% U+0331
16315 % U+0361 COMBINING DOUBLE INVERTED BREVE; breveinverteddoublecmb
16316 \DeclareTextCommand{\texttie}{PU}{\83\141}% U+0361

```

46.2.9 Greek and Coptic: U+0370 to U+03FF

Greek is only loaded if \textBeta is defined.

```

16317 \ifx\textBeta\undefined \else
16318 \input{puenc-greek.def}
16319 \fi
16320 \end{puenc}

```

46.2.10 Cyrillic: U+0400 to U+04FF

Thanks to Vladimir Volovich (vvv@vvv.vsu.ru) for the help with the Cyrillic glyph names. Cyrillic only loaded if \CYRDZE is defined.

```
16321 <*puenc>
16322 \ifx\CYRDZE\@undefined \else
16323 % U+0400 CYRILLIC CAPITAL LETTER IE WITH GRAVE
16324 \DeclareTextCompositeCommand{\`}{PU}{\CYRE}{\84\000}% U+0400
16325 % U+0401 CYRILLIC CAPITAL LETTER IO; Iocyrillic, *afii10023
16326 \DeclareTextCommand{\CYRYO}{PU}{\84\001}% U+0401
16327 \DeclareTextCompositeCommand{\"}{PU}{\CYRE}{\84\001}% U+0401
16328 % U+0402 CYRILLIC CAPITAL LETTER DJE; Djecyrillic, *afii10051
16329 \DeclareTextCommand{\CYRDJE}{PU}{\84\002}% U+0402
16330 % U+0403 CYRILLIC CAPITAL LETTER GJE; Gjecyrillic, *afii10052
16331 \DeclareTextCompositeCommand{\'}{PU}{\CYRG}{\84\003}% U+0403
16332 % U+0404 CYRILLIC CAPITAL LETTER UKRAINIAN IE; Ecyrillic, *afii10053
16333 \DeclareTextCommand{\CYRIE}{PU}{\84\004}% U+0404
16334 % U+0405 CYRILLIC CAPITAL LETTER DZE; Dzecyrillic, *afii10054
16335 \DeclareTextCommand{\CYRDZE}{PU}{\84\005}% U+0405
16336 % U+0406 CYRILLIC CAPITAL LETTER BYELORUSSIAN-UKRAINIAN I;
16337 % Icyrillic, *afii10055
16338 \DeclareTextCommand{\CYRII}{PU}{\84\006}% U+0406
16339 % U+0407 CYRILLIC CAPITAL LETTER YI; Yicyrillic, *afii10056
16340 \DeclareTextCommand{\CYRYI}{PU}{\84\007}% U+0407
16341 \DeclareTextCompositeCommand{\"}{PU}{\CYRII}{\84\007}% U+0407
16342 % U+0408 CYRILLIC CAPITAL LETTER JE; Jecyrillic, *afii10057
16343 \DeclareTextCommand{\CYRJE}{PU}{\84\010}% U+0408
16344 % U+0409 CYRILLIC CAPITAL LETTER LJE; Ljecyrillic, *afii10058
16345 \DeclareTextCommand{\CYRLJE}{PU}{\84\011}% U+0409
16346 % U+040A CYRILLIC CAPITAL LETTER NJE; Njecyrillic, *afii10059
16347 \DeclareTextCommand{\CYRNJE}{PU}{\84\012}% U+040A
16348 % U+040B CYRILLIC CAPITAL LETTER TSHE; Tshecyrillic, *afii10060
16349 \DeclareTextCommand{\CYRTSHE}{PU}{\84\013}% U+040B
16350 % U+040C CYRILLIC CAPITAL LETTER KJE; Kjecyrillic, *afii10061
16351 \DeclareTextCompositeCommand{\'}{PU}{\CYRK}{\84\014}% U+040C
16352 % U+040D CYRILLIC CAPITAL LETTER I WITH GRAVE
16353 \DeclareTextCompositeCommand{\`}{PU}{\CYRI}{\84\015}% U+040D
16354 % U+040E CYRILLIC CAPITAL LETTER SHORT U; Ushortcyrillic, *afii10062
16355 \DeclareTextCommand{\CYRUSHRT}{PU}{\84\016}% U+040E
16356 \DeclareTextCompositeCommand{\U}{PU}{\CYRU}{\84\016}% U+040E
16357 % U+040F CYRILLIC CAPITAL LETTER DZHE; Dzhecyrillic, *afii10145
16358 \DeclareTextCommand{\CYRDZHE}{PU}{\84\017}% U+040F
16359 % U+0410 CYRILLIC CAPITAL LETTER A; Acyrillic, *afii10017
16360 \DeclareTextCommand{\CYRA}{PU}{\84\020}% U+0410
16361 % U+0411 CYRILLIC CAPITAL LETTER BE; Becyrillic, *afii10018
16362 \DeclareTextCommand{\CYRB}{PU}{\84\021}% U+0411
16363 % U+0412 CYRILLIC CAPITAL LETTER VE; Vecyrillic, *afii10019
16364 \DeclareTextCommand{\CYRV}{PU}{\84\022}% U+0412
16365 % U+0413 CYRILLIC CAPITAL LETTER GHE; Gecyrillic, *afii10020
16366 \DeclareTextCommand{\CYRG}{PU}{\84\023}% U+0413
16367 % U+0414 CYRILLIC CAPITAL LETTER DE; Decyrillic, *afii10021
16368 \DeclareTextCommand{\CYRD}{PU}{\84\024}% U+0414
16369 % U+0415 CYRILLIC CAPITAL LETTER IE; Iecyrillic, *afii10022
16370 \DeclareTextCommand{\CYRE}{PU}{\84\025}% U+0415
```

16371 % U+0416 CYRILLIC CAPITAL LETTER ZHE; Zhecyrillic, *afii10024
16372 \DeclareTextCommand{\CYRZH}{PU}{\84\026}% U+0416
16373 % U+0417 CYRILLIC CAPITAL LETTER ZE; Zecyrillic, *afii10025
16374 \DeclareTextCommand{\CYRZ}{PU}{\84\027}% U+0417
16375 % U+0418 CYRILLIC CAPITAL LETTER I; Iicyrillic, *afii10026
16376 \DeclareTextCommand{\CYRI}{PU}{\84\030}% U+0418
16377 % U+0419 CYRILLIC CAPITAL LETTER SHORT I; Iishortcyrillic, *afii10027
16378 \DeclareTextCommand{\CYRISHRT}{PU}{\84\031}% U+0419
16379 \DeclareTextCompositeCommand{\U}{PU}{\CYRI}{\84\031}% U+0419
16380 % U+041A CYRILLIC CAPITAL LETTER KA; Kacyrillic, *afii10028
16381 \DeclareTextCommand{\CYRK}{PU}{\84\032}% U+041A
16382 % U+041B CYRILLIC CAPITAL LETTER EL; Elcyrillic, *afii10029
16383 \DeclareTextCommand{\CYRL}{PU}{\84\033}% U+041B
16384 % U+041C CYRILLIC CAPITAL LETTER EM; Emcyrillic, *afii10030
16385 \DeclareTextCommand{\CYRM}{PU}{\84\034}% U+041C
16386 % U+041D CYRILLIC CAPITAL LETTER EN; Encyrillic, *afii10031
16387 \DeclareTextCommand{\CYRN}{PU}{\84\035}% U+041D
16388 % U+041E CYRILLIC CAPITAL LETTER O; Ocyrillic, *afii10032
16389 \DeclareTextCommand{\CYRO}{PU}{\84\036}% U+041E
16390 % U+041F CYRILLIC CAPITAL LETTER PE; Pecyrillic, *afii10033
16391 \DeclareTextCommand{\CYRP}{PU}{\84\037}% U+041F
16392 % U+0420 CYRILLIC CAPITAL LETTER ER; Ercyrillic, *afii10034
16393 \DeclareTextCommand{\CYRR}{PU}{\84\040}% U+0420
16394 % U+0421 CYRILLIC CAPITAL LETTER ES; Escyrillic, *afii10035
16395 \DeclareTextCommand{\CYRS}{PU}{\84\041}% U+0421
16396 % U+0422 CYRILLIC CAPITAL LETTER TE; Tecyrillic, *afii10036
16397 \DeclareTextCommand{\CYRT}{PU}{\84\042}% U+0422
16398 % U+0423 CYRILLIC CAPITAL LETTER U; Ucyrillic, *afii10037
16399 \DeclareTextCommand{\CYRU}{PU}{\84\043}% U+0423
16400 % U+0424 CYRILLIC CAPITAL LETTER EF; Efçyrillic, *afii10038
16401 \DeclareTextCommand{\CYRF}{PU}{\84\044}% U+0424
16402 % U+0425 CYRILLIC CAPITAL LETTER HA; Khacyrillic, *afii10039
16403 \DeclareTextCommand{\CYRH}{PU}{\84\045}% U+0425
16404 % U+0426 CYRILLIC CAPITAL LETTER TSE; Tsecyrillic, *afii10040
16405 \DeclareTextCommand{\CYRC}{PU}{\84\046}% U+0426
16406 % U+0427 CYRILLIC CAPITAL LETTER CHE; Checyrillic, *afii10041
16407 \DeclareTextCommand{\CYRCH}{PU}{\84\047}% U+0427
16408 % U+0428 CYRILLIC CAPITAL LETTER SHA; Shacyrillic, *afii10042
16409 \DeclareTextCommand{\CYRSH}{PU}{\84\050}% U+0428
16410 % U+0429 CYRILLIC CAPITAL LETTER SHCHA; Shchacyrillic, *afii10043
16411 \DeclareTextCommand{\CYRSHCH}{PU}{\84\051}% U+0429
16412 % U+042A CYRILLIC CAPITAL LETTER HARD SIGN;
16413 % Hardsigncyrillic, *afii10044
16414 \DeclareTextCommand{\CYRHRDSN}{PU}{\84\052}% U+042A
16415 % U+042B CYRILLIC CAPITAL LETTER YERU; Yericyrillic, *afii10045
16416 \DeclareTextCommand{\CYRERY}{PU}{\84\053}% U+042B
16417 % U+042C CYRILLIC CAPITAL LETTER SOFT SIGN;
16418 % Softsigncyrillic, *afii10046
16419 \DeclareTextCommand{\CYRSFTSN}{PU}{\84\054}% U+042C
16420 % U+042D CYRILLIC CAPITAL LETTER E; Ereversedcyrillic, *afii10047
16421 \DeclareTextCommand{\CYREREV}{PU}{\84\055}% U+042D
16422 % U+042E CYRILLIC CAPITAL LETTER YU; IUcyrillic, *afii10048
16423 \DeclareTextCommand{\CYRYU}{PU}{\84\056}% U+042E
16424 % U+042F CYRILLIC CAPITAL LETTER YA; IAcyrillic, *afii10049

```

16425 \DeclareTextCommand{\CYRYA}{PU}{\84\057}% U+042F
16426 % U+0430 CYRILLIC SMALL LETTER A; acyrillic, *afii10065
16427 \DeclareTextCommand{\cyra}{PU}{\84\060}% U+0430
16428 % U+0431 CYRILLIC SMALL LETTER BE; *afii10066, becyrillic
16429 \DeclareTextCommand{\cyrb}{PU}{\84\061}% U+0431
16430 % U+0432 CYRILLIC SMALL LETTER VE; *afii10067, vecyrillic
16431 \DeclareTextCommand{\cyrv}{PU}{\84\062}% U+0432
16432 % U+0433 CYRILLIC SMALL LETTER GHE; *afii10068, gecyrillic
16433 \DeclareTextCommand{\cyrg}{PU}{\84\063}% U+0433
16434 % U+0434 CYRILLIC SMALL LETTER DE; *afii10069, decyrillic
16435 \DeclareTextCommand{\cyrd}{PU}{\84\064}% U+0434
16436 % U+0435 CYRILLIC SMALL LETTER IE; *afii10070, iecyrillic
16437 \DeclareTextCommand{\cyre}{PU}{\84\065}% U+0435
16438 % U+0436 CYRILLIC SMALL LETTER ZHE; *afii10072, zhecyrillic
16439 \DeclareTextCommand{\cyrzh}{PU}{\84\066}% U+0436
16440 % U+0437 CYRILLIC SMALL LETTER ZE; *afii10073, zecyrillic
16441 \DeclareTextCommand{\cyrz}{PU}{\84\067}% U+0437
16442 % U+0438 CYRILLIC SMALL LETTER I; *afii10074, iicyrillic
16443 \DeclareTextCommand{\ciri}{PU}{\84\070}% U+0438
16444 % U+0439 CYRILLIC SMALL LETTER SHORT I; *afii10075, iishortcyrillic
16445 \DeclareTextCommand{\cyrishrt}{PU}{\84\071}% U+0439
16446 \DeclareTextCompositeCommand{\U}{PU}{\ciri}{\84\071}% U+0439
16447 % U+043A CYRILLIC SMALL LETTER KA; *afii10076, kacyrillic
16448 \DeclareTextCommand{\cyrk}{PU}{\84\072}% U+043A
16449 % U+043B CYRILLIC SMALL LETTER EL; *afii10077, elcyrillic
16450 \DeclareTextCommand{\cyrI}{PU}{\84\073}% U+043B
16451 % U+043C CYRILLIC SMALL LETTER EM; *afii10078, emcyrillic
16452 \DeclareTextCommand{\cymr}{PU}{\84\074}% U+043C
16453 % U+043D CYRILLIC SMALL LETTER EN; *afii10079, encyrillic
16454 \DeclareTextCommand{\cyrn}{PU}{\84\075}% U+043D
16455 % U+043E CYRILLIC SMALL LETTER O; *afii10080, ocyrillic
16456 \DeclareTextCommand{\cyro}{PU}{\84\076}% U+043E
16457 % U+043F CYRILLIC SMALL LETTER PE; *afii10081, pecyrillic
16458 \DeclareTextCommand{\cypg}{PU}{\84\077}% U+043F
16459 % U+0440 CYRILLIC SMALL LETTER ER; *afii10082, ercyrillic
16460 \DeclareTextCommand{\cyrr}{PU}{\84\100}% U+0440
16461 % U+0441 CYRILLIC SMALL LETTER ES; *afii10083, escyrillic
16462 \DeclareTextCommand{\crys}{PU}{\84\101}% U+0441
16463 % U+0442 CYRILLIC SMALL LETTER TE; *afii10084, tecyrillic
16464 \DeclareTextCommand{\cyrt}{PU}{\84\102}% U+0442
16465 % U+0443 CYRILLIC SMALL LETTER U; *afii10085, ucyrillic
16466 \DeclareTextCommand{\cyrU}{PU}{\84\103}% U+0443
16467 % U+0444 CYRILLIC SMALL LETTER EF; *afii10086, efcyrillic
16468 \DeclareTextCommand{\cyrf}{PU}{\84\104}% U+0444
16469 % U+0445 CYRILLIC SMALL LETTER HA; *afii10087, khacyrillic
16470 \DeclareTextCommand{\cyrh}{PU}{\84\105}% U+0445
16471 % U+0446 CYRILLIC SMALL LETTER TSE; *afii10088, tsccyrillic
16472 \DeclareTextCommand{\cycr}{PU}{\84\106}% U+0446
16473 % U+0447 CYRILLIC SMALL LETTER CHE; *afii10089, checyrillic
16474 \DeclareTextCommand{\cyrch}{PU}{\84\107}% U+0447
16475 % U+0448 CYRILLIC SMALL LETTER SHA; *afii10090, shacyrillic
16476 \DeclareTextCommand{\cyrsh}{PU}{\84\110}% U+0448
16477 % U+0449 CYRILLIC SMALL LETTER SHCHA; *afii10091, shchacyrillic
16478 \DeclareTextCommand{\cyrshch}{PU}{\84\111}% U+0449

```

```

16479 % U+044A CYRILLIC SMALL LETTER HARD SIGN; *afii10092, hardsigncyrillic
16480 \DeclareTextCommand{\cyhrdsn}{PU}{\84\112}% U+044A
16481 %* \cyhrdsn -> \hardsign (tipa)
16482 % U+044B CYRILLIC SMALL LETTER YERU; *afii10093, yericyrillic
16483 \DeclareTextCommand{\cyrery}{PU}{\84\113}% U+044B
16484 % U+044C CYRILLIC SMALL LETTER SOFT SIGN; *afii10094, softsigncyrillic
16485 \DeclareTextCommand{\cyrftsn}{PU}{\84\114}% U+044C
16486 %* \cyrftsn -> \softsign (tipa)
16487 % U+044D CYRILLIC SMALL LETTER E; *afii10095, ereversedcyrillic
16488 \DeclareTextCommand{\cyrerev}{PU}{\84\115}% U+044D
16489 % U+044E CYRILLIC SMALL LETTER YU; *afii10096, iucyrillic
16490 \DeclareTextCommand{\cyyru}{PU}{\84\116}% U+044E
16491 % U+044F CYRILLIC SMALL LETTER YA; *afii10097, iacyrillic
16492 \DeclareTextCommand{\cyyra}{PU}{\84\117}% U+044F
16493 % U+0450 CYRILLIC SMALL LETTER IE WITH GRAVE
16494 \DeclareTextCompositeCommand{\`}{PU}{\cyre}{\84\120}% U+0450
16495 % U+0451 CYRILLIC SMALL LETTER IO; *afii10071, iocyrillic
16496 \DeclareTextCommand{\cyyro}{PU}{\84\121}% U+0451
16497 \DeclareTextCompositeCommand{\\"}{PU}{\cyre}{\84\121}% U+0451
16498 % U+0452 CYRILLIC SMALL LETTER DJE; *afii10099, djecyrillic
16499 \DeclareTextCommand{\cyyrdje}{PU}{\84\122}% U+0452
16500 % U+0453 CYRILLIC SMALL LETTER GJE; *afii10100, gjecyrillic
16501 \DeclareTextCompositeCommand{\'}{PU}{\cyrg}{\84\123}% U+0453
16502 % U+0454 CYRILLIC SMALL LETTER UKRAINIAN IE; *afii10101, ecyrillic
16503 \DeclareTextCommand{\cyyrie}{PU}{\84\124}% U+0454
16504 % U+0455 CYRILLIC SMALL LETTER DZE; *afii10102, dzecyrillic
16505 \DeclareTextCommand{\cyyrdze}{PU}{\84\125}% U+0455
16506 % U+0456 CYRILLIC SMALL LETTER BYELORUSSIAN-UKRAINIAN I;
16507 % *afii10103, icyrillic
16508 \DeclareTextCommand{\cyyrii}{PU}{\84\126}% U+0456
16509 % U+0457 CYRILLIC SMALL LETTER YI; *afii10104, yicyrillic
16510 \DeclareTextCommand{\cyyryi}{PU}{\84\127}% U+0457
16511 \DeclareTextCompositeCommand{\\"}{PU}{\cyyrii}{\84\127}% U+0457
16512 % U+0458 CYRILLIC SMALL LETTER JE; *afii10105, jecyrillic
16513 \DeclareTextCommand{\cyyrje}{PU}{\84\130}% U+0458
16514 % U+0459 CYRILLIC SMALL LETTER LJE; *afii10106, ljecyrillic
16515 \DeclareTextCommand{\cyyrlje}{PU}{\84\131}% U+0459
16516 % U+045A CYRILLIC SMALL LETTER NJE; *afii10107, njecyrillic
16517 \DeclareTextCommand{\cyyrnje}{PU}{\84\132}% U+045A
16518 % U+045B CYRILLIC SMALL LETTER TSHE; *afii10108, tshecyrillic
16519 \DeclareTextCommand{\cyyrtshe}{PU}{\84\133}% U+045B
16520 % U+045C CYRILLIC SMALL LETTER KJE; *afii10109, kjecyrillic
16521 \DeclareTextCompositeCommand{\'}{PU}{\cyyrk}{\84\134}% U+045C
16522 % U+045D CYRILLIC SMALL LETTER I WITH GRAVE
16523 \DeclareTextCompositeCommand{\`}{PU}{\cyyri}{\84\135}% U+045D
16524 % U+045E CYRILLIC SMALL LETTER SHORT U; *afii10110, ushortcyrillic
16525 \DeclareTextCommand{\cyyrushrt}{PU}{\84\136}% U+045E
16526 \DeclareTextCompositeCommand{\U}{PU}{\cyyru}{\84\136}% U+045E
16527 % U+045F CYRILLIC SMALL LETTER DZHE; *afii10193, dzhecyrillic
16528 \DeclareTextCommand{\cyyrdzhe}{PU}{\84\137}% U+045F
16529 % U+0460 CYRILLIC CAPITAL LETTER OMEGA; Omegacyrillic
16530 \DeclareTextCommand{\CYROMEGA}{PU}{\84\140}% U+0460
16531 % U+0461 CYRILLIC SMALL LETTER OMEGA; omegacyrillic

```

```

16532 \DeclareTextCommand{\cyromega}{PU}{\84\141}% U+0461
16533 % U+0462 CYRILLIC CAPITAL LETTER YAT; Yatcyrillic, *afii10146
16534 \DeclareTextCommand{\CYRYAT}{PU}{\84\142}% U+0462
16535 % U+0463 CYRILLIC SMALL LETTER YAT; *afii10194, yatcyrillic
16536 \DeclareTextCommand{\crysya}{PU}{\84\143}% U+0463
16537 % U+0464 CYRILLIC CAPITAL LETTER IOTIFIED E; Eiotifiedcyrillic
16538 \DeclareTextCommand{\CYRIOTE}{PU}{\84\144}% U+0464
16539 % U+0465 CYRILLIC SMALL LETTER IOTIFIED E; eiotifiedcyrillic
16540 \DeclareTextCommand{\crysio}{PU}{\84\145}% U+0465
16541 % U+0466 CYRILLIC CAPITAL LETTER LITTLE YUS; Yuslittlecyrillic
16542 \DeclareTextCommand{\CYRLYUS}{PU}{\84\146}% U+0466
16543 % U+0467 CYRILLIC SMALL LETTER LITTLE YUS; yuslittlecyrillic
16544 \DeclareTextCommand{\cryslyus}{PU}{\84\147}% U+0467
16545 % U+0468 CYRILLIC CAPITAL LETTER IOTIFIED LITTLE YUS; Yuslittlei-
otifiedcyrillic
16546 \DeclareTextCommand{\CYRIOTLYUS}{PU}{\84\150}% U+0468
16547 % U+0469 CYRILLIC SMALL LETTER IOTIFIED LITTLE YUS; yuslittleioti-
fiedcyrillic
16548 \DeclareTextCommand{\crysotlyus}{PU}{\84\151}% U+0469
16549 % U+046A CYRILLIC CAPITAL LETTER BIG YUS; Yusbigcyrillic
16550 \DeclareTextCommand{\CYRBYUS}{PU}{\84\152}% U+046A
16551 % U+046B CYRILLIC SMALL LETTER BIG YUS; yusbigcyrillic
16552 \DeclareTextCommand{\crysbyus}{PU}{\84\153}% U+046B
16553 % U+046C CYRILLIC CAPITAL LETTER IOTIFIED BIG YUS; Yusbigiotified-
cyrillic
16554 \DeclareTextCommand{\CYRIOTBYUS}{PU}{\84\154}% U+046C
16555 % U+046D CYRILLIC SMALL LETTER IOTIFIED BIG YUS; yusbigiotified-
cyrillic
16556 \DeclareTextCommand{\crysotbyus}{PU}{\84\155}% U+046D
16557 % U+046E CYRILLIC CAPITAL LETTER KSI; Ksicyrillic
16558 \DeclareTextCommand{\CYRKSI}{PU}{\84\156}% U+046E
16559 % U+046F CYRILLIC SMALL LETTER KSI; ksicyrillic
16560 \DeclareTextCommand{\cyrksi}{PU}{\84\157}% U+046F
16561 % U+0470 CYRILLIC CAPITAL LETTER PSI; Psicyrillic
16562 \DeclareTextCommand{\CYRPSI}{PU}{\84\160}% U+0470
16563 % U+0471 CYRILLIC SMALL LETTER PSI; psicyrillic
16564 \DeclareTextCommand{\cyrpsi}{PU}{\84\161}% U+0471
16565 % U+0472 CYRILLIC CAPITAL LETTER FITA; Fitacyrillic, *afii10147
16566 \DeclareTextCommand{\CYRFITA}{PU}{\84\162}% U+0472
16567 % U+0473 CYRILLIC SMALL LETTER FITA; *afii10195, fitacyrillic
16568 \DeclareTextCommand{\cyrfita}{PU}{\84\163}% U+0473
16569 % U+0474 CYRILLIC CAPITAL LETTER IZHITSA; Izhitsacyrillic, *afii10148
16570 \DeclareTextCommand{\CYRIZH}{PU}{\84\164}% U+0474
16571 % U+0475 CYRILLIC SMALL LETTER IZHITSA; *afii10196, izhitsacyrillic
16572 \DeclareTextCommand{\cyrizh}{PU}{\84\165}% U+0475
16573 % U+0476 CYRILLIC CAPITAL LETTER IZHITSA WITH DOUBLE
16574 % GRAVE ACCENT; Izhitsadblgravecyrillic
16575 \DeclareTextCompositeCommand{\C}{PU}{\CYRIZH}{\84\166}% U+0476
16576 % U+0477 CYRILLIC SMALL LETTER IZHITSA WITH DOUBLE
16577 % GRAVE ACCENT; izhitsadblgravecyrillic
16578 \DeclareTextCompositeCommand{\C}{PU}{\cyrizh}{\84\167}% U+0477
16579 % U+0478 CYRILLIC CAPITAL LETTER UK; Ukcyrillic
16580 \DeclareTextCommand{\CYRUK}{PU}{\84\170}% U+0478
16581 % U+0479 CYRILLIC SMALL LETTER UK; ukcyrillic

```

```

16582 \DeclareTextCommand{\cyruk}{PU}{\84\171}% U+0479
16583 % U+047A CYRILLIC CAPITAL LETTER ROUND OMEGA; Omegaroundcyrillic
16584 \DeclareTextCommand{\CYROMEGARND}{PU}{\84\172}% U+047A
16585 % U+047B CYRILLIC SMALL LETTER ROUND OMEGA; omegaroundcyrillic
16586 \DeclareTextCommand{\cyromegarnd}{PU}{\84\173}% U+047B
16587 % U+047C CYRILLIC CAPITAL LETTER OMEGA WITH TITLO; Omegatitlocyrillic
16588 \DeclareTextCommand{\CYROMEGATITLO}{PU}{\84\174}% U+047C
16589 % U+047D CYRILLIC SMALL LETTER OMEGA WITH TITLO; omegatitlocyrillic
16590 \DeclareTextCommand{\cyromegatitlo}{PU}{\84\175}% U+047D
16591 % U+047E CYRILLIC CAPITAL LETTER OT; Otcyrillic
16592 \DeclareTextCommand{\CYROT}{PU}{\84\176}% U+047E
16593 % U+047F CYRILLIC SMALL LETTER OT; otcyrillic
16594 \DeclareTextCommand{\cyrot}{PU}{\84\177}% U+047F
16595 % U+0480 CYRILLIC CAPITAL LETTER KOPPA; Koppacyrillic
16596 \DeclareTextCommand{\CYRKOPPA}{PU}{\84\200}% U+0480
16597 % U+0481 CYRILLIC SMALL LETTER KOPPA; koppacyrillic
16598 \DeclareTextCommand{\cyrkoppa}{PU}{\84\201}% U+0481
16599 % U+0482 CYRILLIC THOUSANDS SIGN; thousandcyrillic
16600 \DeclareTextCommand{\cyrthousands}{PU}{\84\202}% U+0482
\84\203: U+0483 COMBINING CYRILLIC TITLO; titlocyrilliccmb
\84\204: U+0484 COMBINING CYRILLIC PALATALIZATION; palatalizationcyrilliccmb
\84\205: U+0485 COMBINING CYRILLIC DASIA PNEUMATA; dasiapneumatacyrilliccmb
\84\206: U+0486 COMBINING CYRILLIC PSILI PNEUMATA; psilipneumatacyrilliccmb
\84\207: U+0487 COMBINING CYRILLIC POKRYTIE
\84\210: U+0488 COMBINING CYRILLIC HUNDRED THOUSANDS SIGN
\84\211: U+0489 COMBINING CYRILLIC MILLIONS SIGN
16601 % U+048A CYRILLIC CAPITAL LETTER SHORT I WITH TAIL
16602 \DeclareTextCommand{\CYRISHRTDSC}{PU}{\84\212}% U+048A
16603 % U+048B CYRILLIC SMALL LETTER SHORT I WITH TAIL
16604 \DeclareTextCommand{\cyrishrtsc}{PU}{\84\213}% U+048B
16605 % U+048C CYRILLIC CAPITAL LETTER SEMISOFT SIGN
16606 \DeclareTextCommand{\CYRSEMISFTSN}{PU}{\84\214}% U+048C
16607 % U+048D CYRILLIC SMALL LETTER SEMISOFT SIGN
16608 \DeclareTextCommand{\cyrsemisftsn}{PU}{\84\215}% U+048D
16609 % U+048E CYRILLIC CAPITAL LETTER ER WITH TICK
16610 \DeclareTextCommand{\CYRRTICK}{PU}{\84\216}% U+048E
16611 % U+048F CYRILLIC SMALL LETTER ER WITH TICK
16612 \DeclareTextCommand{\cyrrtick}{PU}{\84\217}% U+048F
16613 % U+0490 CYRILLIC CAPITAL LETTER GHE WITH UPTURN; Gheupturncyrillic, *afii10050
16614 \DeclareTextCommand{\CYRGUP}{PU}{\84\220}% U+0490
16615 % U+0491 CYRILLIC SMALL LETTER GHE WITH UPTURN; *afii10098, gheupturncyrillic
16616 \DeclareTextCommand{\cyrgup}{PU}{\84\221}% U+0491
16617 % U+0492 CYRILLIC CAPITAL LETTER GHE WITH STROKE; Ghestrokecyrillic
16618 \DeclareTextCommand{\CYRGHCRS}{PU}{\84\222}% U+0492

```

```

16619 % U+0493 CYRILLIC SMALL LETTER GHE WITH STROKE; ghestrokecyrillic
16620 \DeclareTextCommand{\cyrghcrs}{PU}{\84\223}% U+0493
16621 % U+0494 CYRILLIC CAPITAL LETTER GHE WITH MIDDLE HOOK;
16622 % Ghemiddlehookcyrillic
16623 \DeclareTextCommand{\CYRGHK}{PU}{\84\224}% U+0494
16624 % U+0495 CYRILLIC SMALL LETTER GHE WITH MIDDLE HOOK;
16625 % ghemiddlehookcyrillic
16626 \DeclareTextCommand{\cyrghk}{PU}{\84\225}% U+0495
16627 % U+0496 CYRILLIC CAPITAL LETTER ZHE WITH DESCENDER;
16628 % Zhedescendercyrillic
16629 \DeclareTextCommand{\CYRZHDSC}{PU}{\84\226}% U+0496
16630 % U+0497 CYRILLIC SMALL LETTER ZHE WITH DESCENDER;
16631 % zhedescendercyrillic
16632 \DeclareTextCommand{\cyrzhdsc}{PU}{\84\227}% U+0497
16633 % U+0498 CYRILLIC CAPITAL LETTER ZE WITH DESCENDER; Zedescen-
16634 \DeclareTextCommand{\CYRZDSC}{PU}{\84\230}% U+0498
16635 \DeclareTextCompositeCommand{\c}{PU}{\CYRZ}{\84\230}% U+0498
16636 % U+0499 CYRILLIC SMALL LETTER ZE WITH DESCENDER; zedescen-
16637 \DeclareTextCommand{\cyrzdsc}{PU}{\84\231}% U+0499
16638 \DeclareTextCompositeCommand{\c}{PU}{\cyrz}{\84\231}% U+0499
16639 % U+049A CYRILLIC CAPITAL LETTER KA WITH DESCENDER; Kadescen-
16640 \DeclareTextCommand{\CYRKDSC}{PU}{\84\232}% U+049A
16641 % U+049B CYRILLIC SMALL LETTER KA WITH DESCENDER; kadescen-
16642 \DeclareTextCommand{\cyrkdsc}{PU}{\84\233}% U+049B
16643 % U+049C CYRILLIC CAPITAL LETTER KA WITH VERTICAL STROKE;
16644 % Kaverticalstrokecyrillic
16645 \DeclareTextCommand{\CYRKVCRS}{PU}{\84\234}% U+049C
16646 % U+049D CYRILLIC SMALL LETTER KA WITH VERTICAL STROKE;
16647 % kaverticalstrokecyrillic
16648 \DeclareTextCommand{\cyrkvcrs}{PU}{\84\235}% U+049D
16649 % U+049E CYRILLIC CAPITAL LETTER KA WITH STROKE; Kastrokecyrillic
16650 \DeclareTextCommand{\CYRKHCRS}{PU}{\84\236}% U+049E
16651 % U+049F CYRILLIC SMALL LETTER KA WITH STROKE; kastrokecyrillic
16652 \DeclareTextCommand{\cyrkhcrs}{PU}{\84\237}% U+049F
16653 % U+04A0 CYRILLIC CAPITAL LETTER BASHKIR KA; Kabashkircyrillic
16654 \DeclareTextCommand{\CYRKBEAK}{PU}{\84\240}% U+04A0
16655 % U+04A1 CYRILLIC SMALL LETTER BASHKIR KA; kabashkircyrillic
16656 \DeclareTextCommand{\cyrkbeak}{PU}{\84\241}% U+04A1
16657 % U+04A2 CYRILLIC CAPITAL LETTER EN WITH DESCENDER; Endescen-
16658 \DeclareTextCommand{\CYRNDSC}{PU}{\84\242}% U+04A2
16659 % U+04A3 CYRILLIC SMALL LETTER EN WITH DESCENDER; endescender-
16660 \DeclareTextCommand{\cyrndsc}{PU}{\84\243}% U+04A3
16661 % U+04A4 CYRILLIC CAPITAL LIGATURE EN GHE; Enghecyrillic
16662 \DeclareTextCommand{\CYRNG}{PU}{\84\244}% U+04A4
16663 % U+04A5 CYRILLIC SMALL LIGATURE EN GHE; enghecyrillic
16664 \DeclareTextCommand{\cyrng}{PU}{\84\245}% U+04A5
16665 % U+04A6 CYRILLIC CAPITAL LETTER PE WITH MIDDLE HOOK; Pemid-
16666 % U+04A7 CYRILLIC SMALL LETTER PE WITH MIDDLE HOOK; Pemid-
16667 % U+04A8 CYRILLIC CAPITAL LETTER RE WITH MIDDLE HOOK; Peremid-
16668 % U+04A9 CYRILLIC SMALL LETTER RE WITH MIDDLE HOOK; peremid-

```

```

16666 \DeclareTextCommand{\CYRPHK}{PU}{\84\246}% U+04A6
16667 % U+04A7 CYRILLIC SMALL LETTER PE WITH MIDDLE HOOK; pemiddle-
      hookcyrillic
16668 \DeclareTextCommand{\cyrphk}{PU}{\84\247}% U+04A7
16669 % U+04A8 CYRILLIC CAPITAL LETTER ABKHASIAN HA; Haabkhasiancyril-
      lic
16670 \DeclareTextCommand{\CYRABHHA}{PU}{\84\250}% U+04A8
16671 % U+04A9 CYRILLIC SMALL LETTER ABKHASIAN HA; haabkhasiancyrillic
16672 \DeclareTextCommand{\cyrabhha}{PU}{\84\251}% U+04A9
16673 % U+04AA CYRILLIC CAPITAL LETTER ES WITH DESCENDER; Esdescen-
      dercyrillic
16674 \DeclareTextCommand{\CYRSDSC}{PU}{\84\252}% U+04AA
16675 \DeclareTextCompositeCommand{\CYRSDSC}{PU}{\CYRS}{\84\252}% U+04AA
16676 % U+04AB CYRILLIC SMALL LETTER ES WITH DESCENDER; esdescender-
      cyrillic
16677 \DeclareTextCommand{\cyrsdsc}{PU}{\84\253}% U+04AB
16678 \DeclareTextCompositeCommand{\k}{PU}{\crys}{\84\253}% U+04AB
16679 % U+04AC CYRILLIC CAPITAL LETTER TE WITH DESCENDER; Tedescen-
      dercyrillic
16680 \DeclareTextCommand{\CYRTDSC}{PU}{\84\254}% U+04AC
16681 % U+04AD CYRILLIC SMALL LETTER TE WITH DESCENDER; tedescen-
      dercyrillic
16682 \DeclareTextCommand{\cyrtdsc}{PU}{\84\255}% U+04AD
16683 % U+04AE CYRILLIC CAPITAL LETTER STRAIGHT U; Ustraightcyrillic
16684 \DeclareTextCommand{\CYRY}{PU}{\84\256}% U+04AE
16685 % U+04AF CYRILLIC SMALL LETTER STRAIGHT U; ustraightcyrillic
16686 \DeclareTextCommand{\ciry}{PU}{\84\257}% U+04AF
16687 % U+04B0 CYRILLIC CAPITAL LETTER STRAIGHT U WITH STROKE; Us-
      traightstrokecyrillic
16688 \DeclareTextCommand{\CYRYHCRS}{PU}{\84\260}% U+04B0
16689 % U+04B1 CYRILLIC SMALL LETTER STRAIGHT U WITH STROKE; us-
      straightstrokecyrillic
16690 \DeclareTextCommand{\ciryhcrs}{PU}{\84\261}% U+04B1
16691 % U+04B2 CYRILLIC CAPITAL LETTER HA WITH DESCENDER; Hadescen-
      dercyrillic
16692 \DeclareTextCommand{\CYRHDESC}{PU}{\84\262}% U+04B2
16693 % U+04B3 CYRILLIC SMALL LETTER HA WITH DESCENDER; hadescen-
      dercyrillic
16694 \DeclareTextCommand{\cyrhdesc}{PU}{\84\263}% U+04B3
16695 % U+04B4 CYRILLIC CAPITAL LIGATURE TE TSE; Tetsecyrillic
16696 \DeclareTextCommand{\CYRTETSE}{PU}{\84\264}% U+04B4
16697 % U+04B5 CYRILLIC SMALL LIGATURE TE TSE; tetsecyrillic
16698 \DeclareTextCommand{\cyrtetse}{PU}{\84\265}% U+04B5
16699 % U+04B6 CYRILLIC CAPITAL LETTER CHE WITH DESCENDER;
16700 % Chedescendercyrillic
16701 \DeclareTextCommand{\CYRCHRDSC}{PU}{\84\266}% U+04B6
16702 % U+04B7 CYRILLIC SMALL LETTER CHE WITH DESCENDER; chedescen-
      dercyrillic
16703 \DeclareTextCommand{\cyrchrdsc}{PU}{\84\267}% U+04B7
16704 % U+04B8 CYRILLIC CAPITAL LETTER CHE WITH VERTICAL STROKE;
16705 % Cheverticalstrokecyrillic
16706 \DeclareTextCommand{\CYRCHVCRS}{PU}{\84\270}% U+04B8
16707 % U+04B9 CYRILLIC SMALL LETTER CHE WITH VERTICAL STROKE;
16708 % cheverticalstrokecyrillic

```

```

16709 \DeclareTextCommand{\cyrchvcrs}{PU}{\84\271}% U+04B9
16710 % U+04BA CYRILLIC CAPITAL LETTER SHHA; Shhacyrillic
16711 \DeclareTextCommand{\CYRSHHA}{PU}{\84\272}% U+04BA
16712 % U+04BB CYRILLIC SMALL LETTER SHHA; shhacyrillic
16713 \DeclareTextCommand{\cyrshha}{PU}{\84\273}% U+04BB
16714 % U+04BC CYRILLIC CAPITAL LETTER ABKHASIAN CHE; Cheabkhasian-
    cyrillic
16715 \DeclareTextCommand{\CYRABHCH}{PU}{\84\274}% U+04BC
16716 % U+04BD CYRILLIC SMALL LETTER ABKHASIAN CHE; cheabkhasiancyril-
    lic
16717 \DeclareTextCommand{\cyrabhch}{PU}{\84\275}% U+04BD
16718 % U+04BE CYRILLIC CAPITAL LETTER ABKHASIAN CHE WITH DESCEN-
    DER; Chedescenderabkhasiancyrillic
16719 \DeclareTextCommand{\CYRABHHDSC}{PU}{\84\276}% U+04BE
16720 \DeclareTextCompositeCommand{\k}{PU}{\CYRABHCH}{\84\276}% U+04BE
16721 % U+04BF CYRILLIC SMALL LETTER ABKHASIAN CHE WITH DESCEN-
    DER; chedescenderabkhasiancyrillic
16722 \DeclareTextCommand{\cyrabhchdsc}{PU}{\84\277}% U+04BF
16723 \DeclareTextCompositeCommand{\k}{PU}{\cyrabhch}{\84\277}% U+04BF
16724 % U+04C0 CYRILLIC LETTER PALOCHKA; palochkacyrillic
16725 \DeclareTextCommand{\CYRpalochnka}{PU}{\84\300}% U+04C0
16726 % U+04C1 CYRILLIC CAPITAL LETTER ZHE WITH BREVE; Zhebrevecyrillic
16727 \DeclareTextCompositeCommand{\U}{PU}{\CYRZH}{\84\301}% U+04C1
16728 % U+04C2 CYRILLIC SMALL LETTER ZHE WITH BREVE; zhebrevecyrillic
16729 \DeclareTextCompositeCommand{\U}{PU}{\cyrzh}{\84\302}% U+04C2
16730 % U+04C3 CYRILLIC CAPITAL LETTER KA WITH HOOK; Kahookcyrillic
16731 \DeclareTextCommand{\CYRKHK}{PU}{\84\303}% U+04C3
16732 % U+04C4 CYRILLIC SMALL LETTER KA WITH HOOK; kahookcyrillic
16733 \DeclareTextCommand{\cyrkhk}{PU}{\84\304}% U+04C4
16734 % U+04C5 CYRILLIC CAPITAL LETTER EL WITH TAIL
16735 \DeclareTextCommand{\CYRLDSC}{PU}{\84\305}% U+04C5
16736 % U+04C6 CYRILLIC SMALL LETTER EL WITH TAIL
16737 \DeclareTextCommand{\cyrldsc}{PU}{\84\306}% U+04C6
16738 % U+04C7 CYRILLIC CAPITAL LETTER EN WITH HOOK; Enhookcyrillic
16739 \DeclareTextCommand{\CYRNHK}{PU}{\84\307}% U+04C7
16740 % U+04C8 CYRILLIC SMALL LETTER EN WITH HOOK; enhookcyrillic
16741 \DeclareTextCommand{\cyrnhk}{PU}{\84\310}% U+04C8
16742 % U+04CB CYRILLIC CAPITAL LETTER KHAKASSIAN CHE; Chekhakas-
    siancyrillic
16743 \DeclareTextCommand{\CYRCHLDSC}{PU}{\84\313}% U+04CB
16744 % U+04CC CYRILLIC SMALL LETTER KHAKASSIAN CHE; chehkassian-
    cyrillic
16745 \DeclareTextCommand{\cyrchldsc}{PU}{\84\314}% U+04CC
16746 % U+04CD CYRILLIC CAPITAL LETTER EM WITH TAIL
16747 \DeclareTextCommand{\CYRMDSC}{PU}{\84\315}% U+04CD
16748 % U+04CE CYRILLIC SMALL LETTER EM WITH TAIL
16749 \DeclareTextCommand{\cyrmdsc}{PU}{\84\316}% U+04CE
\84\317: U+04CF CYRILLIC SMALL LETTER PALOCHKA
16750 % U+04D0 CYRILLIC CAPITAL LETTER A WITH BREVE; Abrevecyrillic
16751 \DeclareTextCompositeCommand{\U}{PU}{\CYRA}{\84\320}% U+04D0
16752 % U+04D1 CYRILLIC SMALL LETTER A WITH BREVE; abrevecyrillic
16753 \DeclareTextCompositeCommand{\U}{PU}{\cyla}{\84\321}% U+04D1
16754 % U+04D2 CYRILLIC CAPITAL LETTER A WITH DIAERESIS; Adieresiscyril-
    lic

```

```

16755 \DeclareTextCompositeCommand{\\"}{PU}{\CYRA}{\84\322}% U+04D2
16756 % U+04D3 CYRILLIC SMALL LETTER A WITH DIAERESIS; adieresiscyrillic
16757 \DeclareTextCompositeCommand{\\"}{PU}{\cyra}{\84\323}% U+04D3
16758 % U+04D4 CYRILLIC CAPITAL LIGATURE A IE; Aiecyrillic
16759 \DeclareTextCommand{\CYRAE}{PU}{\84\324}% U+04D4
16760 % U+04D5 CYRILLIC SMALL LIGATURE A IE; aiecyrillic
16761 \DeclareTextCommand{\cyrae}{PU}{\84\325}% U+04D5
16762 % U+04D6 CYRILLIC CAPITAL LETTER IE WITH BREVE; Iebrevacyrillic
16763 \DeclareTextCompositeCommand{\U}{PU}{\CYRE}{\84\326}% U+04D6
16764 % U+04D7 CYRILLIC SMALL LETTER IE WITH BREVE; iebrevacyrillic
16765 \DeclareTextCompositeCommand{\U}{PU}{\cyre}{\84\327}% U+04D7
16766 % U+04D8 CYRILLIC CAPITAL LETTER SCHWA; Schwacyrillic
16767 \DeclareTextCommand{\CYRSCHWA}{PU}{\84\330}% U+04D8
16768 % U+04D9 CYRILLIC SMALL LETTER SCHWA; *afii10846, schwacyrillic
16769 \DeclareTextCommand{\cyrschwa}{PU}{\84\331}% U+04D9
16770 % U+04DA CYRILLIC CAPITAL LETTER SCHWA WITH DIAERESIS;
16771 % Schwadieresiscyrillic
16772 \DeclareTextCompositeCommand{\\"}{PU}{\CYRSCHWA}{\84\332}% U+04DA
16773 % U+04DB CYRILLIC SMALL LETTER SCHWA WITH DIAERESIS;
16774 % schwadieresiscyrillic
16775 \DeclareTextCompositeCommand{\\"}{PU}{\cyrschwa}{\84\333}% U+04DB
16776 % U+04DC CYRILLIC CAPITAL LETTER ZHE WITH DIAERESIS; Zhediere-
    siscyrillic
16777 \DeclareTextCompositeCommand{\\"}{PU}{\CYRZH}{\84\334}% U+04DC
16778 % U+04DD CYRILLIC SMALL LETTER ZHE WITH DIAERESIS; zhedieres-
    cyrillic
16779 \DeclareTextCompositeCommand{\\"}{PU}{\cyrzh}{\84\335}% U+04DD
16780 % U+04DE CYRILLIC CAPITAL LETTER ZE WITH DIAERESIS; Zedieres-
    cyrillic
16781 \DeclareTextCompositeCommand{\\"}{PU}{\CYRZ}{\84\336}% U+04DE
16782 % U+04DF CYRILLIC SMALL LETTER ZE WITH DIAERESIS; zedieresiscyril-
    lic
16783 \DeclareTextCompositeCommand{\\"}{PU}{\cyrz}{\84\337}% U+04DF
16784 % U+04E0 CYRILLIC CAPITAL LETTER ABKHASIAN DZE; Dzeabkhasian-
    cyrillic
16785 \DeclareTextCommand{\CYRABHDZE}{PU}{\84\340}% U+04E0
16786 % U+04E1 CYRILLIC SMALL LETTER ABKHASIAN DZE; dzeabkhasiancyril-
    lic
16787 \DeclareTextCommand{\cyrabhdze}{PU}{\84\341}% U+04E1
16788 % U+04E2 CYRILLIC CAPITAL LETTER I WITH MACRON; Imacroncyrillic
16789 \DeclareTextCompositeCommand{\=\\"}{PU}{\CYRI}{\84\342}% U+04E2
16790 % U+04E3 CYRILLIC SMALL LETTER I WITH MACRON; imacroncyrillic
16791 \DeclareTextCompositeCommand{\=\\"}{PU}{\cyri}{\84\343}% U+04E3
16792 % U+04E4 CYRILLIC CAPITAL LETTER I WITH DIAERESIS; Idieresiscyrillic
16793 \DeclareTextCompositeCommand{\\"}{PU}{\CYRI}{\84\344}% U+04E4
16794 % U+04E5 CYRILLIC SMALL LETTER I WITH DIAERESIS; idieresiscyrillic
16795 \DeclareTextCompositeCommand{\\"}{PU}{\cyri}{\84\345}% U+04E5
16796 % U+04E6 CYRILLIC CAPITAL LETTER O WITH DIAERESIS; Odieresiscyril-
    lic
16797 \DeclareTextCompositeCommand{\\"}{PU}{\CYRO}{\84\346}% U+04E6
16798 % U+04E7 CYRILLIC SMALL LETTER O WITH DIAERESIS; odieresiscyrillic
16799 \DeclareTextCompositeCommand{\\"}{PU}{\cyro}{\84\347}% U+04E7
16800 % U+04E8 CYRILLIC CAPITAL LETTER BARRED O; Obarredcyrillic
16801 \DeclareTextCommand{\CYROTLD}{PU}{\84\350}% U+04E8

```

16802 % U+04E9 CYRILLIC SMALL LETTER BARRED O; obarredcyrillic
 16803 \DeclareTextCommand{\cyrotld}{PU}{\84\351} % U+04E9
 16804 % U+04EA CYRILLIC CAPITAL LETTER BARRED O WITH DIAERESIS;
 16805 % Obarreddieresiscyrillic
 16806 \DeclareTextCompositeCommand{"}{PU}{CYROTLD}{\84\352} % U+04EA
 16807 % U+04EB CYRILLIC SMALL LETTER BARRED O WITH DIAERESIS;
 16808 % obarreddieresiscyrillic
 16809 \DeclareTextCompositeCommand{"}{PU}{\cyrotld}{\84\353} % U+04EB
 16810 % U+04EC CYRILLIC CAPITAL LETTER E WITH DIAERESIS
 16811 \DeclareTextCompositeCommand{"}{PU}{CYREREV}{\84\354} % U+04EC
 16812 % U+04ED CYRILLIC SMALL LETTER E WITH DIAERESIS
 16813 \DeclareTextCompositeCommand{"}{PU}{\cyreref}{\84\355} % U+04ED
 16814 % U+04EE CYRILLIC CAPITAL LETTER U WITH MACRON; Umacroncyrillic
 16815 \DeclareTextCompositeCommand{=}{PU}{CYRU}{\84\356} % U+04EE
 16816 % U+04EF CYRILLIC SMALL LETTER U WITH MACRON; umacroncyrillic
 16817 \DeclareTextCompositeCommand{=}{PU}{\cyru}{\84\357} % U+04EF
 16818 % U+04F0 CYRILLIC CAPITAL LETTER U WITH DIAERESIS; Udieresiscyrillic
 16819 \DeclareTextCompositeCommand{"}{PU}{CYRU}{\84\360} % U+04F0
 16820 % U+04F1 CYRILLIC SMALL LETTER U WITH DIAERESIS; udieresiscyrillic
 16821 \DeclareTextCompositeCommand{"}{PU}{\cyru}{\84\361} % U+04F1
 16822 % U+04F2 CYRILLIC CAPITAL LETTER U WITH DOUBLE ACUTE; Uhun-
 garumlautcyrillic
 16823 \DeclareTextCompositeCommand{H}{PU}{CYRU}{\84\362} % U+04F2
 16824 % U+04F3 CYRILLIC SMALL LETTER U WITH DOUBLE ACUTE; uhun-
 garumlautcyrillic
 16825 \DeclareTextCompositeCommand{H}{PU}{\cyru}{\84\363} % U+04F3
 16826 % U+04F4 CYRILLIC CAPITAL LETTER CHE WITH DIAERESIS; Chediere-
 siscyrillic
 16827 \DeclareTextCompositeCommand{"}{PU}{CYRCH}{\84\364} % U+04F4
 16828 % U+04F5 CYRILLIC SMALL LETTER CHE WITH DIAERESIS; chedieres-
 siscyrillic
 16829 \DeclareTextCompositeCommand{"}{PU}{\cyrch}{\84\365} % U+04F5
 16830 % U+04F6 CYRILLIC CAPITAL LETTER GHE WITH DESCENDER
 16831 \DeclareTextCommand{CYRGDSC}{PU}{\84\366} % U+04F6
 16832 % U+04F7 CYRILLIC SMALL LETTER GHE WITH DESCENDER
 16833 \DeclareTextCommand{cyrgdsc}{PU}{\84\367} % U+04F7
 16834 % U+04F8 CYRILLIC CAPITAL LETTER YERU WITH DIAERESIS; Yerudiere-
 siscyrillic
 16835 \DeclareTextCompositeCommand{"}{PU}{CYRERY}{\84\370} % U+04F8
 16836 % U+04F9 CYRILLIC SMALL LETTER YERU WITH DIAERESIS; yerudiere-
 siscyrillic
 16837 \DeclareTextCompositeCommand{"}{PU}{\cyrery}{\84\371} % U+04F9
 \84\372: U+04FA CYRILLIC CAPITAL LETTER GHE WITH STROKE AND
 HOOK
 \84\373: U+04FB CYRILLIC SMALL LETTER GHE WITH STROKE AND
 HOOK
 16838 % U+04FC CYRILLIC CAPITAL LETTER HA WITH HOOK
 16839 \DeclareTextCommand{CYRHHK}{PU}{\84\374} % U+04FC
 16840 % U+04FD CYRILLIC SMALL LETTER HA WITH HOOK
 16841 \DeclareTextCommand{cyrhhk}{PU}{\84\375} % U+04FD
 16842 \fi
 \84\376: U+04FE CYRILLIC CAPITAL LETTER HA WITH STROKE

\84\377: U+04FF CYRILLIC SMALL LETTER HA WITH STROKE

46.2.11 Hebrew: U+0590 to U+05FF

Macro names are taken from he8enc.def. hebrew is only loaded if \hebdalet is defined

```
16843 \ifx\hebdalet\@undefined\else
16844 % U+05C3 HEBREW PUNCTUATION SOF PASUQ
16845 \DeclareTextCommand{\sofpasuq}{PU}{\85\303}% U+05C3
16846 % U+05D0 HEBREW LETTER ALEF
16847 \DeclareTextCommand{\hebalef}{PU}{\85\320}% U+05D0
16848 % U+05D1 HEBREW LETTER BET
16849 \DeclareTextCommand{\hebbet}{PU}{\85\321}% U+05D1
16850 % U+05D2 HEBREW LETTER GIMEL
16851 \DeclareTextCommand{\hebgimel}{PU}{\85\322}% U+05D2
16852 % U+05D3 HEBREW LETTER DALET
16853 \DeclareTextCommand{\hebdalet}{PU}{\85\323}% U+05D3
16854 % U+05D4 HEBREW LETTER HE
16855 \DeclareTextCommand{\hebbe}{PU}{\85\324}% U+05D4
16856 % U+05D5 HEBREW LETTER VAV
16857 \DeclareTextCommand{\hebvav}{PU}{\85\325}% U+05D5
16858 % U+05D6 HEBREW LETTER ZAYIN
16859 \DeclareTextCommand{\hebzayin}{PU}{\85\326}% U+05D6
16860 % U+05D7 HEBREW LETTER HET
16861 \DeclareTextCommand{\hebhet}{PU}{\85\327}% U+05D7
16862 % U+05D8 HEBREW LETTER TET
16863 \DeclareTextCommand{\hebtet}{PU}{\85\330}% U+05D8
16864 % U+05D9 HEBREW LETTER YOD
16865 \DeclareTextCommand{\hebyod}{PU}{\85\331}% U+05D9
16866 % U+05DA HEBREW LETTER FINAL KAF
16867 \DeclareTextCommand{\hebfinalkaf}{PU}{\85\332}% U+05DA
16868 % U+05DB HEBREW LETTER KAF
16869 \DeclareTextCommand{\hebkaf}{PU}{\85\333}% U+05DB
16870 % U+05DC HEBREW LETTER LAMED
16871 \DeclareTextCommand{\heblamed}{PU}{\85\334}% U+05DC
16872 % U+05DD HEBREW LETTER FINAL MEM
16873 \DeclareTextCommand{\hebfinalmem}{PU}{\85\335}% U+05DD
16874 % U+05DE HEBREW LETTER MEM
16875 \DeclareTextCommand{\hebmem}{PU}{\85\336}% U+05DE
16876 % U+05DF HEBREW LETTER FINAL NUN
16877 \DeclareTextCommand{\hebfinalnun}{PU}{\85\337}% U+05DF
16878 % U+05E0 HEBREW LETTER NUN
16879 \DeclareTextCommand{\hebnun}{PU}{\85\340}% U+05E0
16880 % U+05E1 HEBREW LETTER SAMEKH
16881 \DeclareTextCommand{\hebsamekh}{PU}{\85\341}% U+05E1
16882 % U+05E2 HEBREW LETTER AYIN
16883 \DeclareTextCommand{\hebayin}{PU}{\85\342}% U+05E2
16884 % U+05E3 HEBREW LETTER FINAL PE
16885 \DeclareTextCommand{\hebfinalpe}{PU}{\85\343}% U+05E3
16886 % U+05E4 HEBREW LETTER PE
16887 \DeclareTextCommand{\hebpe}{PU}{\85\344}% U+05E4
16888 % U+05E5 HEBREW LETTER FINAL TSADI
16889 \DeclareTextCommand{\hebfinaltsadi}{PU}{\85\345}% U+05E5
16890 % U+05E6 HEBREW LETTER TSADI
```

```

16891 \DeclareTextCommand{\hebtsadi}{PU}{\85\346}% U+05E6
16892 % U+05E7 HEBREW LETTER QOF
16893 \DeclareTextCommand{\hebqof}{PU}{\85\347}% U+05E7
16894 % U+05E8 HEBREW LETTER RESH
16895 \DeclareTextCommand{\hebreish}{PU}{\85\350}% U+05E8
16896 % U+05E9 HEBREW LETTER SHIN
16897 \DeclareTextCommand{\hebshin}{PU}{\85\351}% U+05E9
16898 %* \hebshin -> \hebsin (he8)
16899 % U+05EA HEBREW LETTER TAV
16900 \DeclareTextCommand{\hebtav}{PU}{\85\352}% U+05EA
16901 % U+05F0 HEBREW LIGATURE YIDDISH DOUBLE VAV
16902 \DeclareTextCommand{\doublevav}{PU}{\85\360}% U+05F0
16903 % U+05F1 HEBREW LIGATURE YIDDISH VAV YOD
16904 \DeclareTextCommand{\vavyod}{PU}{\85\361}% U+05F1
16905 % U+05F2 HEBREW LIGATURE YIDDISH DOUBLE YOD
16906 \DeclareTextCommand{\doubleyod}{PU}{\85\362}% U+05F2
16907 \fi

```

46.2.12 Thai: U+0E00 to U+0E7F

```

16908 % U+0E3F THAI CURRENCY SYMBOL BAHT; bahtthai
16909 \DeclareTextCommand{\textbaht}{PU}{\9016\077}% U+0E3F

```

46.2.13 Phonetic Extensions: U+1D00 to U+1D7F

```

16910 % U+1D00 LATIN LETTER SMALL CAPITAL A; \textsca (tipa)
16911 \DeclareTextCommand{\textsca}{PU}{\9035\000}% U+1D00
16912 % U+1D05 LATIN LETTER SMALL CAPITAL D; \scd (wsuipa)
16913 \DeclareTextCommand{\textscd}{PU}{\9035\005} %* U+1D05
16914 % U+1D07 LATIN LETTER SMALL CAPITAL E; \textsce (tipa)
16915 \DeclareTextCommand{\textsce}{PU}{\9035\007}% U+1D07
16916 % U+1D0A LATIN LETTER SMALL CAPITAL J; \textscj (tipa)
16917 \DeclareTextCommand{\textscj}{PU}{\9035\012}% U+1D0A
16918 % U+1D0B LATIN LETTER SMALL CAPITAL K; \textsck (tipx)
16919 \DeclareTextCommand{\textPUsck}{PU}{\9035\013}% U+1D0B
16920 %* \textPUsck -> \textsck (tipx)
16921 % U+1D0D LATIN LETTER SMALL CAPITAL M; \textscm (tipx)
16922 \DeclareTextCommand{\textPUscm}{PU}{\9035\015}% U+1D0D
16923 %* \textPUscm -> \textscm (tipx)
16924 % U+1D18 LATIN LETTER SMALL CAPITAL P; \textscp (tipx)
16925 \DeclareTextCommand{\textPUscp}{PU}{\9035\030}% U+1D18
16926 %* \textPUscp -> \textscp (tipx)
16927 % U+1D19 LATIN LETTER SMALL CAPITAL REVERSED R; \textrevscr (tipx)
16928 \DeclareTextCommand{\textPRevscr}{PU}{\9035\031}% U+1D19
16929 %* \textPRevscr -> \textrevscr (tipx)
16930 % U+1D1C LATIN LETTER SMALL CAPITAL U; \textscu (tipa), \scu (wsuipa)
16931 \DeclareTextCommand{\textscu}{PU}{\9035\034} %* U+1D1C
16932 % U+1D62 LATIN SUBSCRIPT SMALL LETTER I
16933 \DeclareTextCommand{\textiinferior}{PU}{\9035\142} %* U+1D62
16934 % U+1D63 LATIN SUBSCRIPT SMALL LETTER R
16935 \DeclareTextCommand{\textrinferior}{PU}{\9035\143} %* U+1D63
16936 % U+1D64 LATIN SUBSCRIPT SMALL LETTER U
16937 \DeclareTextCommand{\textuinferior}{PU}{\9035\144} %* U+1D64
16938 % U+1D65 LATIN SUBSCRIPT SMALL LETTER V
16939 \DeclareTextCommand{\textvinferior}{PU}{\9035\145} %* U+1D65

```

```

16940 % U+1D66 GREEK SUBSCRIPT SMALL LETTER BETA
16941 \DeclareTextCommand{\textbetainferior}{PU}{\9035\146}/* U+1D66
16942 % U+1D67 GREEK SUBSCRIPT SMALL LETTER GAMMA
16943 \DeclareTextCommand{\textgammainferior}{PU}{\9035\147}/* U+1D67
16944 % U+1D68 GREEK SUBSCRIPT SMALL LETTER RHO
16945 \DeclareTextCommand{\textrhoinferior}{PU}{\9035\150}/* U+1D68
16946 % U+1D69 GREEK SUBSCRIPT SMALL LETTER PHI
16947 \DeclareTextCommand{\textphiinferior}{PU}{\9035\151}/* U+1D69
16948 % U+1D6A GREEK SUBSCRIPT SMALL LETTER CHI
16949 \DeclareTextCommand{\textchiinferior}{PU}{\9035\152}/* U+1D6A
16950 % U+1D7B LATIN SMALL CAPITAL LETTER I WITH STROKE;
16951 % \barsci (wsuipa)
16952 \DeclareTextCommand{\textbarsci}{PU}{\9035\173}/* U+1D7B
16953 % U+1D7D LATIN SMALL LETTER P WITH STROKE; \barp (wsuipa)
16954 \DeclareTextCommand{\textbarp}{PU}{\9035\175}/* U+1D7D
16955 % U+1D7E LATIN SMALL CAPITAL LETTER U WITH STROKE;
16956 % \barscu (wsuipa)
16957 \DeclareTextCommand{\textbarscu}{PU}{\9035\176}/* U+1D7E

```

46.2.14 Phonetic Extensions Supplement: U+1D80 to U+1DBF

```

16958 % U+1D8F LATIN SMALL LETTER A WITH RETROFLEX HOOK; \textrhooka (tipx)
16959 \DeclareTextCommand{\textPURhooka}{PU}{\9035\217}/* U+1D8F
16960 /* \textPURhooka -> \textrhooka (tipx)
16961 % U+1D91 LATIN SMALL LETTER D WITH HOOK AND TAIL; \texthrtaild (tipa)
16962 \DeclareTextCommand{\texthrtaild}{PU}{\9035\221}/* U+1D91
16963 % U+1D92 LATIN SMALL LETTER E WITH RETROFLEX HOOK; \textrhooke (tipx)
16964 \DeclareTextCommand{\textPURhooke}{PU}{\9035\222}/* U+1D92
16965 /* \textPURhooke -> \textrhooke (tipx)
16966 % U+1D93 LATIN SMALL LETTER OPEN E WITH RETROFLEX HOOK;
16967 % \textrhookepsilon (tipx)
16968 \DeclareTextCommand{\textPURhookepsilon}{PU}{\9035\223}/* U+1D93
16969 /* \textPURhookepsilon -> \textrhookepsilon (tipx)
16970 % U+1D97 LATIN SMALL LETTER OPEN O WITH RETROFLEX HOOK;
16971 % \textrhookopeno (tipx)
16972 \DeclareTextCommand{\textPURhookopeno}{PU}{\9035\227}/* U+1D97
16973 /* \textPURhookopeno -> \textrhookopeno (tipx)

```

46.2.15 Latin Extended Additional: U+1E00 to U+1EFF

```

16974 % U+1E00 LATIN CAPITAL LETTER A WITH RING BELOW; Aringbelow
16975 \DeclareTextCompositeCommand{\textsubring}{PU}{A}{\9036\000}/* U+1E00
16976 % U+1E01 LATIN SMALL LETTER A WITH RING BELOW; aringbelow
16977 \DeclareTextCompositeCommand{\textsubring}{PU}{a}{\9036\001}/* U+1E01
16978 % U+1E02 LATIN CAPITAL LETTER B WITH DOT ABOVE; Bdotaccent
16979 \DeclareTextCompositeCommand{\.}{PU}{B}{\9036\002}/* U+1E02
16980 % U+1E03 LATIN SMALL LETTER B WITH DOT ABOVE; bdotaccent
16981 \DeclareTextCompositeCommand{\.}{PU}{b}{\9036\003}/* U+1E03
16982 % U+1E04 LATIN CAPITAL LETTER B WITH DOT BELOW; Bdotbelow
16983 \DeclareTextCompositeCommand{\d}{PU}{B}{\9036\004}/* U+1E04
16984 % U+1E05 LATIN SMALL LETTER B WITH DOT BELOW; bdotbelow
16985 \DeclareTextCompositeCommand{\d}{PU}{b}{\9036\005}/* U+1E05
16986 % U+1E06 LATIN CAPITAL LETTER B WITH LINE BELOW; Blinebelow

```

```

16987 \DeclareTextCompositeCommand{\b}{PU}{B}{\9036\006}% U+1E06
16988 % U+1E07 LATIN SMALL LETTER B WITH LINE BELOW; blinebelow
16989 \DeclareTextCompositeCommand{\b}{PU}{b}{\9036\007}% U+1E07
16990 % U+1E0A LATIN CAPITAL LETTER D WITH DOT ABOVE; Ddotaccent
16991 \DeclareTextCompositeCommand{\.}{PU}{D}{\9036\012}% U+1E0A
16992 % U+1E0B LATIN SMALL LETTER D WITH DOT ABOVE; ddotaccent
16993 \DeclareTextCompositeCommand{\.}{PU}{d}{\9036\013}% U+1E0B
16994 % U+1E0C LATIN CAPITAL LETTER D WITH DOT BELOW; Ddotbelow
16995 \DeclareTextCompositeCommand{\d}{PU}{D}{\9036\014}% U+1E0C
16996 % U+1E0D LATIN SMALL LETTER D WITH DOT BELOW; ddotbelow
16997 \DeclareTextCompositeCommand{\d}{PU}{d}{\9036\015}% U+1E0D
16998 % U+1E0E LATIN CAPITAL LETTER D WITH LINE BELOW; Dlinebelow
16999 \DeclareTextCompositeCommand{\b}{PU}{D}{\9036\016}% U+1E0E
17000 % U+1E0F LATIN SMALL LETTER D WITH LINE BELOW; dlinebelow
17001 \DeclareTextCompositeCommand{\b}{PU}{d}{\9036\017}% U+1E0F
17002 % U+1E10 LATIN CAPITAL LETTER D WITH CEDILLA; Dcedilla
17003 \DeclareTextCompositeCommand{\c}{PU}{D}{\9036\020}% U+1E10
17004 % U+1E11 LATIN SMALL LETTER D WITH CEDILLA; dcedilla
17005 \DeclareTextCompositeCommand{\c}{PU}{d}{\9036\021}% U+1E11
17006 % U+1E12 LATIN CAPITAL LETTER D WITH CIRCUMFLEX BELOW; Dcircumflexbelow
17007 \DeclareTextCompositeCommand{\textsubcircum}{PU}{D}{\9036\022}% U+1E12
17008 % U+1E13 LATIN SMALL LETTER D WITH CIRCUMFLEX BELOW; dcircumflexbelow
17009 \DeclareTextCompositeCommand{\textsubcircum}{PU}{d}{\9036\023}% U+1E13
17010 % U+1E14 LATIN CAPITAL LETTER E WITH MACRON AND GRAVE;
17011 % Emacrongrave
17012 \DeclareTextCompositeCommand{\textgravemacron}{PU}{E}{\9036\024}% U+1E14
17013 % U+1E15 LATIN SMALL LETTER E WITH MACRON AND GRAVE;
17014 % emacrongrave
17015 \DeclareTextCompositeCommand{\textgravemacron}{PU}{e}{\9036\025}% U+1E15
17016 % U+1E16 LATIN CAPITAL LETTER E WITH MACRON AND ACUTE;
17017 % Emacronacute
17018 \DeclareTextCompositeCommand{\textacutemacron}{PU}{E}{\9036\026}% U+1E16
17019 % U+1E17 LATIN SMALL LETTER E WITH MACRON AND ACUTE;
17020 % emacronacute
17021 \DeclareTextCompositeCommand{\textacutemacron}{PU}{e}{\9036\027}% U+1E17
17022 % U+1E18 LATIN CAPITAL LETTER E WITH CIRCUMFLEX BELOW; Ecircumflexbelow
17023 \DeclareTextCompositeCommand{\textsubcircum}{PU}{E}{\9036\030}% U+1E18
17024 % U+1E19 LATIN SMALL LETTER E WITH CIRCUMFLEX BELOW; ecircumflexbelow
17025 \DeclareTextCompositeCommand{\textsubcircum}{PU}{e}{\9036\031}% U+1E19
17026 % U+1E1A LATIN CAPITAL LETTER E WITH TILDE BELOW; Etildebelow
17027 \DeclareTextCompositeCommand{\textsubtilde}{PU}{E}{\9036\032}% U+1E1A
17028 % U+1E1B LATIN SMALL LETTER E WITH TILDE BELOW; etildebelow
17029 \DeclareTextCompositeCommand{\textsubtilde}{PU}{e}{\9036\033}% U+1E1B
17030 % U+1E1E LATIN CAPITAL LETTER F WITH DOT ABOVE; Fdotaccent
17031 \DeclareTextCompositeCommand{\.}{PU}{F}{\9036\036}% U+1E1E
17032 % U+1E1F LATIN SMALL LETTER F WITH DOT ABOVE; fdotaccent
17033 \DeclareTextCompositeCommand{\.}{PU}{f}{\9036\037}% U+1E1F
17034 % U+1E20 LATIN CAPITAL LETTER G WITH MACRON; Gmacron
17035 \DeclareTextCompositeCommand{\=}{PU}{G}{\9036\040}% U+1E20
17036 % U+1E21 LATIN SMALL LETTER G WITH MACRON; gmacron

```

```

17037 \DeclareTextCompositeCommand{\=}{PU}{g}{\9036\041}%
17038 % U+1E22 LATIN CAPITAL LETTER H WITH DOT ABOVE; Hdotaccent
17039 \DeclareTextCompositeCommand{\.}{PU}{H}{\9036\042}%
17040 % U+1E23 LATIN SMALL LETTER H WITH DOT ABOVE; hdotaccent
17041 \DeclareTextCompositeCommand{\.}{PU}{h}{\9036\043}%
17042 % U+1E24 LATIN CAPITAL LETTER H WITH DOT BELOW; Hdotbelow
17043 \DeclareTextCompositeCommand{\d}{PU}{H}{\9036\044}%
17044 % U+1E25 LATIN SMALL LETTER H WITH DOT BELOW; hdotbelow
17045 \DeclareTextCompositeCommand{\d}{PU}{h}{\9036\045}%
17046 % U+1E26 LATIN CAPITAL LETTER H WITH DIAERESIS; Hdieresis
17047 \DeclareTextCompositeCommand{\"}{PU}{H}{\9036\046}%
17048 % U+1E27 LATIN SMALL LETTER H WITH DIAERESIS; hdieresis
17049 \DeclareTextCompositeCommand{\"}{PU}{h}{\9036\047}%
17050 % U+1E28 LATIN CAPITAL LETTER H WITH CEDILLA; Hcedilla
17051 \DeclareTextCompositeCommand{\c}{PU}{H}{\9036\050}%
17052 % U+1E29 LATIN SMALL LETTER H WITH CEDILLA; hcedilla
17053 \DeclareTextCompositeCommand{\c}{PU}{h}{\9036\051}%
17054 % U+1E2A LATIN CAPITAL LETTER H WITH BREVE BELOW; Hbrevebelow
17055 \DeclareTextCompositeCommand{\textsub breve}{PU}{H}{\9036\052}%
17056 % U+1E2B LATIN SMALL LETTER H WITH BREVE BELOW; hbrevebelow
17057 \DeclareTextCompositeCommand{\textsub breve}{PU}{h}{\9036\053}%
17058 % U+1E2C LATIN CAPITAL LETTER I WITH TILDE BELOW; Itildebelow
17059 \DeclareTextCompositeCommand{\textsub tilde}{PU}{I}{\9036\054}%
17060 % U+1E2D LATIN SMALL LETTER I WITH TILDE BELOW; itildebelow
17061 \DeclareTextCompositeCommand{\textsub tilde}{PU}{i}{\9036\055}%
17062 % U+1E30 LATIN CAPITAL LETTER K WITH ACUTE; Kacute
17063 \DeclareTextCompositeCommand{\'}{PU}{K}{\9036\060}%
17064 % U+1E31 LATIN SMALL LETTER K WITH ACUTE; kacute
17065 \DeclareTextCompositeCommand{\'}{PU}{k}{\9036\061}%
17066 % U+1E32 LATIN CAPITAL LETTER K WITH DOT BELOW; Kdotbelow
17067 \DeclareTextCompositeCommand{\d}{PU}{K}{\9036\062}%
17068 % U+1E33 LATIN SMALL LETTER K WITH DOT BELOW; kdotbelow
17069 \DeclareTextCompositeCommand{\d}{PU}{k}{\9036\063}%
17070 % U+1E34 LATIN CAPITAL LETTER K WITH LINE BELOW; Klinebelow
17071 \DeclareTextCompositeCommand{\b}{PU}{K}{\9036\064}%
17072 % U+1E35 LATIN SMALL LETTER K WITH LINE BELOW; klinebelow
17073 \DeclareTextCompositeCommand{\b}{PU}{k}{\9036\065}%
17074 % U+1E36 LATIN CAPITAL LETTER L WITH DOT BELOW; Ldotbelow
17075 \DeclareTextCompositeCommand{\d}{PU}{L}{\9036\066}%
17076 % U+1E37 LATIN SMALL LETTER L WITH DOT BELOW; ldotbelow
17077 \DeclareTextCompositeCommand{\d}{PU}{l}{\9036\067}%
17078 % U+1E3A LATIN CAPITAL LETTER L WITH LINE BELOW; Llinebelow
17079 \DeclareTextCompositeCommand{\b}{PU}{L}{\9036\072}%
17080 % U+1E3B LATIN SMALL LETTER L WITH LINE BELOW; llinebelow
17081 \DeclareTextCompositeCommand{\b}{PU}{l}{\9036\073}%
17082 % U+1E3C LATIN CAPITAL LETTER L WITH CIRCUMFLEX BELOW; Lcircumflexbelow
17083 \DeclareTextCompositeCommand{\textsub circum}{PU}{L}{\9036\074}%
17084 % U+1E3D LATIN SMALL LETTER L WITH CIRCUMFLEX BELOW; lcircumflexbelow
17085 \DeclareTextCompositeCommand{\textsub circum}{PU}{l}{\9036\075}%
17086 % U+1E3E LATIN CAPITAL LETTER M WITH ACUTE; Macute
17087 \DeclareTextCompositeCommand{\'}{PU}{M}{\9036\076}%
17088 % U+1E3F LATIN SMALL LETTER M WITH ACUTE; macute

```

```

17089 \DeclareTextCompositeCommand{\'}{PU}{m}{\9036\077}% U+1E3F
17090 % U+1E40 LATIN CAPITAL LETTER M WITH DOT ABOVE; Mdotaccent
17091 \DeclareTextCompositeCommand{\.}{PU}{M}{\9036\100}% U+1E40
17092 % U+1E41 LATIN SMALL LETTER M WITH DOT ABOVE; mdotaccent
17093 \DeclareTextCompositeCommand{\.}{PU}{m}{\9036\101}% U+1E41
17094 % U+1E42 LATIN CAPITAL LETTER M WITH DOT BELOW; Mdotbelow
17095 \DeclareTextCompositeCommand{\d}{PU}{M}{\9036\102}% U+1E42
17096 % U+1E43 LATIN SMALL LETTER M WITH DOT BELOW; mdotbelow
17097 \DeclareTextCompositeCommand{\d}{PU}{m}{\9036\103}% U+1E43
17098 % U+1E44 LATIN CAPITAL LETTER N WITH DOT ABOVE; Ndotaccent
17099 \DeclareTextCompositeCommand{\.}{PU}{N}{\9036\104}% U+1E44
17100 % U+1E45 LATIN SMALL LETTER N WITH DOT ABOVE; ndotaccent
17101 \DeclareTextCompositeCommand{\.}{PU}{n}{\9036\105}% U+1E45
17102 % U+1E46 LATIN CAPITAL LETTER N WITH DOT BELOW; Ndotbelow
17103 \DeclareTextCompositeCommand{\d}{PU}{N}{\9036\106}% U+1E46
17104 % U+1E47 LATIN SMALL LETTER N WITH DOT BELOW; ndotbelow
17105 \DeclareTextCompositeCommand{\d}{PU}{n}{\9036\107}% U+1E47
17106 % U+1E48 LATIN CAPITAL LETTER N WITH LINE BELOW; Nlinebelow
17107 \DeclareTextCompositeCommand{\b}{PU}{N}{\9036\110}% U+1E48
17108 % U+1E49 LATIN SMALL LETTER N WITH LINE BELOW; nlinebelow
17109 \DeclareTextCompositeCommand{\b}{PU}{n}{\9036\111}% U+1E49
17110 % U+1E4A LATIN CAPITAL LETTER N WITH CIRCUMFLEX BELOW; Ncircumflexbelow
17111 \DeclareTextCompositeCommand{\textsubcircum}{PU}{N}{\9036\112}% U+1E4A
17112 % U+1E4B LATIN SMALL LETTER N WITH CIRCUMFLEX BELOW; ncircumflexbelow
17113 \DeclareTextCompositeCommand{\textsubcircum}{PU}{n}{\9036\113}% U+1E4B
17114 % U+1E50 LATIN CAPITAL LETTER O WITH MACRON AND GRAVE;
17115 % Omacrongrave
17116 \DeclareTextCompositeCommand{\textgravemacron}{PU}{O}{\9036\120}% U+1E50
17117 % U+1E51 LATIN SMALL LETTER O WITH MACRON AND GRAVE;
17118 % omacrongrave
17119 \DeclareTextCompositeCommand{\textgravemacron}{PU}{o}{\9036\121}% U+1E51
17120 % U+1E52 LATIN CAPITAL LETTER O WITH MACRON AND ACUTE;
17121 % Omacronacute
17122 \DeclareTextCompositeCommand{\textacutemacron}{PU}{O}{\9036\122}% U+1E52
17123 % U+1E53 LATIN SMALL LETTER O WITH MACRON AND ACUTE;
17124 % omacronacute
17125 \DeclareTextCompositeCommand{\textacutemacron}{PU}{o}{\9036\123}% U+1E53
17126 % U+1E54 LATIN CAPITAL LETTER P WITH ACUTE; Pacute
17127 \DeclareTextCompositeCommand{\'}{PU}{P}{\9036\124}% U+1E54
17128 % U+1E55 LATIN SMALL LETTER P WITH ACUTE; pacute
17129 \DeclareTextCompositeCommand{\'}{PU}{p}{\9036\125}% U+1E55
17130 % U+1E56 LATIN CAPITAL LETTER P WITH DOT ABOVE; Pdotaccent
17131 \DeclareTextCompositeCommand{\.}{PU}{P}{\9036\126}% U+1E56
17132 % U+1E57 LATIN SMALL LETTER P WITH DOT ABOVE; pdotaccent
17133 \DeclareTextCompositeCommand{\.}{PU}{p}{\9036\127}% U+1E57
17134 % U+1E58 LATIN CAPITAL LETTER R WITH DOT ABOVE; Rdotaccent
17135 \DeclareTextCompositeCommand{\.}{PU}{R}{\9036\130}% U+1E58
17136 % U+1E59 LATIN SMALL LETTER R WITH DOT ABOVE; rdotaccent
17137 \DeclareTextCompositeCommand{\.}{PU}{r}{\9036\131}% U+1E59
17138 % U+1E5A LATIN CAPITAL LETTER R WITH DOT BELOW; Rdotbelow
17139 \DeclareTextCompositeCommand{\d}{PU}{R}{\9036\132}% U+1E5A
17140 % U+1E5B LATIN SMALL LETTER R WITH DOT BELOW; rdotbelow

```

```

17141 \DeclareTextCompositeCommand{\d}{PU}{r}{\9036\133}%
17142 % U+1E5E LATIN CAPITAL LETTER R WITH LINE BELOW; Rlinebelow
17143 \DeclareTextCompositeCommand{\b}{PU}{R}{\9036\136}%
17144 % U+1E5F LATIN SMALL LETTER R WITH LINE BELOW; rlinebelow
17145 \DeclareTextCompositeCommand{\b}{PU}{r}{\9036\137}%
17146 % U+1E60 LATIN CAPITAL LETTER S WITH DOT ABOVE; Sdotaccent
17147 \DeclareTextCompositeCommand{\.}{PU}{S}{\9036\140}%
17148 % U+1E61 LATIN SMALL LETTER S WITH DOT ABOVE; sdotaccent
17149 \DeclareTextCompositeCommand{\.}{PU}{s}{\9036\141}%
17150 % U+1E62 LATIN CAPITAL LETTER S WITH DOT BELOW; Sdotbelow
17151 \DeclareTextCompositeCommand{\d}{PU}{S}{\9036\142}%
17152 % U+1E63 LATIN SMALL LETTER S WITH DOT BELOW; sdotbelow
17153 \DeclareTextCompositeCommand{\d}{PU}{s}{\9036\143}%
17154 % U+1E6A LATIN CAPITAL LETTER T WITH DOT ABOVE; Tdotaccent
17155 \DeclareTextCompositeCommand{\.}{PU}{T}{\9036\152}%
17156 % U+1E6B LATIN SMALL LETTER T WITH DOT ABOVE; tdotaccent
17157 \DeclareTextCompositeCommand{\.}{PU}{t}{\9036\153}%
17158 % U+1E6C LATIN CAPITAL LETTER T WITH DOT BELOW; Tdotbelow
17159 \DeclareTextCompositeCommand{\d}{PU}{T}{\9036\154}%
17160 % U+1E6D LATIN SMALL LETTER T WITH DOT BELOW; tdotbelow
17161 \DeclareTextCompositeCommand{\d}{PU}{t}{\9036\155}%
17162 % U+1E6E LATIN CAPITAL LETTER T WITH LINE BELOW; Tlinebelow
17163 \DeclareTextCompositeCommand{\b}{PU}{T}{\9036\156}%
17164 % U+1E6F LATIN SMALL LETTER T WITH LINE BELOW; tlinebelow
17165 \DeclareTextCompositeCommand{\b}{PU}{t}{\9036\157}%
17166 % U+1E70 LATIN CAPITAL LETTER T WITH CIRCUMFLEX BELOW; Tcircumflexbelow
17167 \DeclareTextCompositeCommand{\textsubcircum}{PU}{T}{\9036\160}%
17168 % U+1E71 LATIN SMALL LETTER T WITH CIRCUMFLEX BELOW; tcircumflexbelow
17169 \DeclareTextCompositeCommand{\textsubcircum}{PU}{t}{\9036\161}%
17170 % U+1E72 LATIN CAPITAL LETTER U WITH DIAERESIS BELOW; Udiere-sisbelow
17171 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{U}{\9036\162}%
17172 % U+1E73 LATIN SMALL LETTER U WITH DIAERESIS BELOW; udieresisbelow
17173 \DeclareTextCompositeCommand{\textsubumlaut}{PU}{u}{\9036\163}%
17174 % U+1E74 LATIN CAPITAL LETTER U WITH TILDE BELOW; Utildebelow
17175 \DeclareTextCompositeCommand{\textsubtilde}{PU}{U}{\9036\164}%
17176 % U+1E75 LATIN SMALL LETTER U WITH TILDE BELOW; utildebelow
17177 \DeclareTextCompositeCommand{\textsubtilde}{PU}{u}{\9036\165}%
17178 % U+1E76 LATIN CAPITAL LETTER U WITH CIRCUMFLEX BELOW; Ucircumflexbelow
17179 \DeclareTextCompositeCommand{\textsubcircum}{PU}{U}{\9036\166}%
17180 % U+1E77 LATIN SMALL LETTER U WITH CIRCUMFLEX BELOW; ucircumflexbelow
17181 \DeclareTextCompositeCommand{\textsubcircum}{PU}{u}{\9036\167}%
17182 % U+1E7C LATIN CAPITAL LETTER V WITH TILDE; Vtilde
17183 \DeclareTextCompositeCommand{\~}{PU}{V}{\9036\174}%
17184 % U+1E7D LATIN SMALL LETTER V WITH TILDE; vtilde
17185 \DeclareTextCompositeCommand{\~}{PU}{v}{\9036\175}%
17186 % U+1E7E LATIN CAPITAL LETTER V WITH DOT BELOW; Vdotbelow
17187 \DeclareTextCompositeCommand{\d}{PU}{V}{\9036\176}%
17188 % U+1E7F LATIN SMALL LETTER V WITH DOT BELOW; vdotbelow

```

```

17189 \DeclareTextCompositeCommand{\d}{PU}{v}{\9036\177}%
17190 % U+1E80 LATIN CAPITAL LETTER W WITH GRAVE; Wgrave
17191 \DeclareTextCompositeCommand{\`}{PU}{w}{\9036\200}%
17192 % U+1E81 LATIN SMALL LETTER W WITH GRAVE; wgrave
17193 \DeclareTextCompositeCommand{\`}{PU}{w}{\9036\201}%
17194 % U+1E82 LATIN CAPITAL LETTER W WITH ACUTE; Wacute
17195 \DeclareTextCompositeCommand{\'}{PU}{w}{\9036\202}%
17196 % U+1E83 LATIN SMALL LETTER W WITH ACUTE; wacute
17197 \DeclareTextCompositeCommand{\'}{PU}{w}{\9036\203}%
17198 % U+1E84 LATIN CAPITAL LETTER W WITH DIAERESIS; Wdieresis
17199 \DeclareTextCompositeCommand{\"}{PU}{w}{\9036\204}%
17200 % U+1E85 LATIN SMALL LETTER W WITH DIAERESIS; wdieresis
17201 \DeclareTextCompositeCommand{\"}{PU}{w}{\9036\205}%
17202 % U+1E86 LATIN CAPITAL LETTER W WITH DOT ABOVE; Wdotaccent
17203 \DeclareTextCompositeCommand{\.}{PU}{w}{\9036\206}%
17204 % U+1E87 LATIN SMALL LETTER W WITH DOT ABOVE; wdotaccent
17205 \DeclareTextCompositeCommand{\.}{PU}{w}{\9036\207}%
17206 % U+1E88 LATIN CAPITAL LETTER W WITH DOT BELOW; wdotbelow
17207 \DeclareTextCompositeCommand{\d}{PU}{w}{\9036\210}%
17208 % U+1E89 LATIN SMALL LETTER W WITH DOT BELOW; wdotbelow
17209 \DeclareTextCompositeCommand{\d}{PU}{w}{\9036\211}%
17210 % U+1E8A LATIN CAPITAL LETTER X WITH DOT ABOVE; Xdotaccent
17211 \DeclareTextCompositeCommand{\.}{PU}{x}{\9036\212}%
17212 % U+1E8B LATIN SMALL LETTER X WITH DOT ABOVE; xdotaccent
17213 \DeclareTextCompositeCommand{\.}{PU}{x}{\9036\213}%
17214 % U+1E8C LATIN CAPITAL LETTER X WITH DIAERESIS; Xdieresis
17215 \DeclareTextCompositeCommand{\"}{PU}{x}{\9036\214}%
17216 % U+1E8D LATIN SMALL LETTER X WITH DIAERESIS; xdieresis
17217 \DeclareTextCompositeCommand{\"}{PU}{x}{\9036\215}%
17218 % U+1E8E LATIN CAPITAL LETTER Y WITH DOT ABOVE; Ydotaccent
17219 \DeclareTextCompositeCommand{\.}{PU}{y}{\9036\216}%
17220 % U+1E8F LATIN SMALL LETTER Y WITH DOT ABOVE; ydotaccent
17221 \DeclareTextCompositeCommand{\.}{PU}{y}{\9036\217}%
17222 % U+1E90 LATIN CAPITAL LETTER Z WITH CIRCUMFLEX; Zcircumflex
17223 \DeclareTextCompositeCommand{\^}{PU}{z}{\9036\220}%
17224 % U+1E91 LATIN SMALL LETTER Z WITH CIRCUMFLEX; zcircumflex
17225 \DeclareTextCompositeCommand{\^}{PU}{z}{\9036\221}%
17226 % U+1E92 LATIN CAPITAL LETTER Z WITH DOT BELOW; zdotbelow
17227 \DeclareTextCompositeCommand{\d}{PU}{z}{\9036\222}%
17228 % U+1E93 LATIN SMALL LETTER Z WITH DOT BELOW; zdotbelow
17229 \DeclareTextCompositeCommand{\d}{PU}{z}{\9036\223}%
17230 % U+1E94 LATIN CAPITAL LETTER Z WITH LINE BELOW; Zlinebelow
17231 \DeclareTextCompositeCommand{\b}{PU}{z}{\9036\224}%
17232 % U+1E95 LATIN SMALL LETTER Z WITH LINE BELOW; zlinebelow
17233 \DeclareTextCompositeCommand{\b}{PU}{z}{\9036\225}%
17234 % U+1E96 LATIN SMALL LETTER H WITH LINE BELOW; hlinebelow
17235 \DeclareTextCompositeCommand{\b}{PU}{h}{\9036\226}%
17236 % U+1E97 LATIN SMALL LETTER T WITH DIAERESIS; tdieresis
17237 \DeclareTextCompositeCommand{\"}{PU}{t}{\9036\227}%
17238 % U+1E98 LATIN SMALL LETTER W WITH RING ABOVE; wring
17239 \DeclareTextCompositeCommand{\r}{PU}{w}{\9036\230}%
17240 % U+1E99 LATIN SMALL LETTER Y WITH RING ABOVE; yring
17241 \DeclareTextCompositeCommand{\r}{PU}{y}{\9036\231}%
17242 % U+1E9B LATIN SMALL LETTER LONG S WITH DOT ABOVE; slongdo-

```

```

taccent
17243 \DeclareTextCompositeCommand{\.}{PU}{\textlongs}{\9036\233}% U+1E9B
17244 % U+1EA0 LATIN CAPITAL LETTER A WITH DOT BELOW; Adotbelow
17245 \DeclareTextCompositeCommand{\d}{PU}{A}{\9036\240}% U+1EA0
17246 % U+1EA1 LATIN SMALL LETTER A WITH DOT BELOW; adotbelow
17247 \DeclareTextCompositeCommand{\d}{PU}{a}{\9036\241}% U+1EA1
17248 % U+1EB8 LATIN CAPITAL LETTER E WITH DOT BELOW; Edotbelow
17249 \DeclareTextCompositeCommand{\d}{PU}{E}{\9036\270}% U+1EB8
17250 % U+1EB9 LATIN SMALL LETTER E WITH DOT BELOW; edotbelow
17251 \DeclareTextCompositeCommand{\d}{PU}{e}{\9036\271}% U+1EB9
17252 % U+1EBC LATIN CAPITAL LETTER E WITH TILDE; Etilde
17253 \DeclareTextCompositeCommand{\~}{PU}{E}{\9036\274}% U+1EBC
17254 % U+1EBD LATIN SMALL LETTER E WITH TILDE; etilde
17255 \DeclareTextCompositeCommand{\~}{PU}{e}{\9036\275}% U+1EBD
17256 % U+1ECA LATIN CAPITAL LETTER I WITH DOT BELOW; Idotbelow
17257 \DeclareTextCompositeCommand{\d}{PU}{I}{\9036\312}% U+1ECA
17258 % U+1ECB LATIN SMALL LETTER I WITH DOT BELOW; idotbelow
17259 \DeclareTextCompositeCommand{\d}{PU}{i}{\9036\313}% U+1ECB
17260 % U+1ECC LATIN CAPITAL LETTER O WITH DOT BELOW; Odotbelow
17261 \DeclareTextCompositeCommand{\d}{PU}{O}{\9036\314}% U+1ECC
17262 % U+1ECD LATIN SMALL LETTER O WITH DOT BELOW; odotbelow
17263 \DeclareTextCompositeCommand{\d}{PU}{o}{\9036\315}% U+1ECD
17264 % U+1EE4 LATIN CAPITAL LETTER U WITH DOT BELOW; Udotbelow
17265 \DeclareTextCompositeCommand{\d}{PU}{U}{\9036\344}% U+1EE4
17266 % U+1EE5 LATIN SMALL LETTER U WITH DOT BELOW; udotbelow
17267 \DeclareTextCompositeCommand{\d}{PU}{u}{\9036\345}% U+1EE5
17268 % U+1EF2 LATIN CAPITAL LETTER Y WITH GRAVE; Ygrave
17269 \DeclareTextCompositeCommand{\`}{PU}{Y}{\9036\362}% U+1EF2
17270 % U+1EF3 LATIN SMALL LETTER Y WITH GRAVE; ygrave
17271 \DeclareTextCompositeCommand{\`}{PU}{y}{\9036\363}% U+1EF3
17272 % U+1EF4 LATIN CAPITAL LETTER Y WITH DOT BELOW; Ydotbelow
17273 \DeclareTextCompositeCommand{\d}{PU}{Y}{\9036\364}% U+1EF4
17274 % U+1EF5 LATIN SMALL LETTER Y WITH DOT BELOW; ydotbelow
17275 \DeclareTextCompositeCommand{\d}{PU}{y}{\9036\365}% U+1EF5
17276 % U+1EF8 LATIN CAPITAL LETTER Y WITH TILDE; Ytilde
17277 \DeclareTextCompositeCommand{\~}{PU}{Y}{\9036\370}% U+1EF8
17278 % U+1EF9 LATIN SMALL LETTER Y WITH TILDE; ytilde
17279 \DeclareTextCompositeCommand{\~}{PU}{y}{\9036\371}% U+1EF9

```

46.2.16 General Punctuation: U+2000 to U+206F

```

17280 % U+200C ZERO WIDTH NON-JOINER; *af61664, zerowidthnonjoiner
17281 \DeclareTextCommand{\textcompwordmark}{PU}{\9040\014}% U+200C
17282 % U+2013 EN DASH; endash
17283 \DeclareTextCommand{\textendash}{PU}{\9040\023}% U+2013
17284 % U+2014 EM DASH; emdash
17285 \DeclareTextCommand{\textemdash}{PU}{\9040\024}% U+2014
17286 % U+2016 DOUBLE VERTICAL LINE; dblverticalbar
17287 \DeclareTextCommand{\textbardbl}{PU}{\9040\026}% U+2016
17288 %* \textbardbl -> \textdoublevertline (tipa)
17289 % U+2018 LEFT SINGLE QUOTATION MARK; quoteleft
17290 \DeclareTextCommand{\textquotleft}{PU}{\9040\030}% U+2018
17291 % U+2019 RIGHT SINGLE QUOTATION MARK; quoteright
17292 \DeclareTextCommand{\textquotright}{PU}{\9040\031}% U+2019
17293 % U+201A SINGLE LOW-9 QUOTATION MARK; quotesinglbase

```

```

17294 \DeclareTextCommand{\quotesinglbase}{PU}{\9040\032}% U+201A
17295 % U+201C LEFT DOUBLE QUOTATION MARK; quotedblleft
17296 \DeclareTextCommand{\textquotedblleft}{PU}{\9040\034}% U+201C
17297 % U+201D RIGHT DOUBLE QUOTATION MARK; quotedblright
17298 \DeclareTextCommand{\textquotedblright}{PU}{\9040\035}% U+201D
17299 % U+201E DOUBLE LOW-9 QUOTATION MARK; quotedblbase
17300 \DeclareTextCommand{\quotedblbase}{PU}{\9040\036}% U+201E
17301 % U+2020 DAGGER; dagger
17302 \DeclareTextCommand{\textdagger}{PU}{\9040\040}/* U+2020
17303 %* \textdagger -> \dag (LaTeX)
17304 % U+2021 DOUBLE DAGGER; daggerdbl; \ddagger (LaTeX)
17305 \DeclareTextCommand{\textdaggerdbl}{PU}{\9040\041}% U+2021
17306 %* \textdaggerdbl -> \ddagger (LaTeX)
17307 %* \textdaggerdbl -> \ddag (LaTeX)
17308 % U+2022 BULLET; bullet
17309 \DeclareTextCommand{\textbullet}{PU}{\9040\042}/* U+2022
17310 % U+2025 TWO DOT LEADER; \hdotfor (MnSymbol)
17311 \DeclareTextCommand{\texthdotfor}{PU}{\9040\045}/* U+2025
17312 % U+2026 HORIZONTAL ELLIPSIS; ellipsis
17313 \DeclareTextCommand{\textellipsis}{PU}{\9040\046}% U+2026
17314 %* \textellipsis -> \mathellipsis
17315 % U+2030 PER MILLE SIGN; perthousand
17316 \DeclareTextCommand{\textperthousand}{PU}{\9040\060}% U+2030
17317 % U+2031 PER TEN THOUSAND SIGN
17318 \DeclareTextCommand{\textpertenthousand}{PU}{\9040\061}% U+2031
17319 % U+2032 PRIME; minute; \prime (MnSymbol)
17320 \DeclareTextCommand{\textprime}{PU}{\9040\062}/* U+2032
17321 % U+2033 DOUBLE PRIME; \second (mathabx)
17322 \DeclareTextCommand{\textsecond}{PU}{\9040\063}/* U+2033
17323 % U+2034 TRIPLE PRIME; \third (mathabx)
17324 \DeclareTextCommand{\textthird}{PU}{\9040\064}/* U+2034
17325 % U+2035 REVERSED PRIME; \backprime (AmS)
17326 \DeclareTextCommand{\textbackprime}{PU}{\9040\065}/* U+2035
17327 % U+2039 SINGLE LEFT-POINTING ANGLE QUOTATION MARK; guilsinglleft
17328 \DeclareTextCommand{\guilsinglleft}{PU}{\9040\071}% U+2039
17329 % U+203A SINGLE RIGHT-POINTING ANGLE QUOTATION MARK; guilsinglright
17330 \DeclareTextCommand{\guilsinglright}{PU}{\9040\072}% U+203A
17331 % U+203B REFERENCE MARK; referencemark
17332 \DeclareTextCommand{\textreferencemark}{PU}{\9040\073}% U+203B
17333 % U+203D INTERROBANG
17334 \DeclareTextCommand{\textinterrobang}{PU}{\9040\075}% U+203D
17335 % U+2044 FRACTION SLASH; fraction
17336 \DeclareTextCommand{\textfractionsolidus}{PU}{\9040\104}% U+2044
17337 % U+2045 LEFT SQUARE BRACKET WITH QUILL
17338 \DeclareTextCommand{\textlquill}{PU}{\9040\105}% U+2045
17339 % U+2046 RIGHT SQUARE BRACKET WITH QUILL
17340 \DeclareTextCommand{\textrquill}{PU}{\9040\106}% U+2046
17341 % U+2052 COMMERCIAL MINUS SIGN
17342 \DeclareTextCommand{\textdiscount}{PU}{\9040\122}% U+2052
17343 % U+2056 THREE DOT PUNCTUATION; \lefttherefore (MnSymbol)
17344 \DeclareTextCommand{\textlefttherefore}{PU}{\9040\126}/* U+2056
17345 % U+2057 QUADRUPLE PRIME; \fourth (mathabx)

```

```
17346 \DeclareTextCommand{\textfourth}{PU}{\9040\127}/* U+2057  
17347 % U+2058 FOUR DOT PUNCTUATION; \diamondddots (MnSymbol)  
17348 \DeclareTextCommand{\textdiamondddots}{PU}{\9040\130}/* U+2058
```

46.2.17 Superscripts and Subscripts: U+2070 to U+209F

```
17349 % U+2070 SUPERSCRIPT ZERO; zerosuperior  
17350 \DeclareTextCommand{\textzerosuperior}{PU}{\9040\160}/* U+2070  
17351 % U+2071 SUPERSCRIPT LATIN SMALL LETTER I  
17352 \DeclareTextCommand{\textisuperior}{PU}{\9040\161}/* U+2071  
17353 % U+2074 SUPERSCRIPT FOUR; foursuperior  
17354 \DeclareTextCommand{\textfoursuperior}{PU}{\9040\164}/* U+2074  
17355 % U+2075 SUPERSCRIPT FIVE; fivesuperior  
17356 \DeclareTextCommand{\textfivesuperior}{PU}{\9040\165}/* U+2075  
17357 % U+2076 SUPERSCRIPT SIX; sixsuperior  
17358 \DeclareTextCommand{\textsixsuperior}{PU}{\9040\166}/* U+2076  
17359 % U+2077 SUPERSCRIPT SEVEN; sevensuperior  
17360 \DeclareTextCommand{\textsevensuperior}{PU}{\9040\167}/* U+2077  
17361 % U+2078 SUPERSCRIPT EIGHT; eightsuperior  
17362 \DeclareTextCommand{\texteightsuperior}{PU}{\9040\170}/* U+2078  
17363 % U+2079 SUPERSCRIPT NINE; ninesuperior  
17364 \DeclareTextCommand{\textninesuperior}{PU}{\9040\171}/* U+2079  
17365 % U+207A SUPERSCRIPT PLUS SIGN; plussuperior  
17366 \DeclareTextCommand{\textplussuperior}{PU}{\9040\172}/* U+207A  
17367 % U+207B SUPERSCRIPT MINUS  
17368 \DeclareTextCommand{\textminussuperior}{PU}{\9040\173}/* U+207B  
17369 % U+207C SUPERSCRIPT EQUALS SIGN; equalsuperior  
17370 \DeclareTextCommand{\textequalsuperior}{PU}{\9040\174}/* U+207C  
17371 % U+207D SUPERSCRIPT LEFT PARENTHESIS; parenleftsuperior  
17372 \DeclareTextCommand{\textparenleftsuperior}{PU}{\9040\175}/* U+207D  
17373 % U+207E SUPERSCRIPT RIGHT PARENTHESIS; parenrightsuperior  
17374 \DeclareTextCommand{\textparenrightsuperior}{PU}{\9040\176}/* U+207E  
17375 % U+207F SUPERSCRIPT LATIN SMALL LETTER N; nsuperior  
17376 \DeclareTextCommand{\textnsuperior}{PU}{\9040\177}/* U+207F  
17377 % U+2080 SUBSCRIPT ZERO; zeroinferior  
17378 \DeclareTextCommand{\textzeroinferior}{PU}{\9040\200}/* U+2080  
17379 % U+2081 SUBSCRIPT ONE; oneinferior  
17380 \DeclareTextCommand{\textoneinferior}{PU}{\9040\201}/* U+2081  
17381 % U+2082 SUBSCRIPT TWO; twoinferior  
17382 \DeclareTextCommand{\texttwoinferior}{PU}{\9040\202}/* U+2082  
17383 % U+2083 SUBSCRIPT THREE; threeinferior  
17384 \DeclareTextCommand{\textthreeinferior}{PU}{\9040\203}/* U+2083  
17385 % U+2084 SUBSCRIPT FOUR; fourinferior  
17386 \DeclareTextCommand{\textfourinferior}{PU}{\9040\204}/* U+2084  
17387 % U+2085 SUBSCRIPT FIVE; fiveinferior  
17388 \DeclareTextCommand{\textfiveinferior}{PU}{\9040\205}/* U+2085  
17389 % U+2086 SUBSCRIPT SIX; sixinferior  
17390 \DeclareTextCommand{\textsixinferior}{PU}{\9040\206}/* U+2086  
17391 % U+2087 SUBSCRIPT SEVEN; seveninferior  
17392 \DeclareTextCommand{\textseveninferior}{PU}{\9040\207}/* U+2087  
17393 % U+2088 SUBSCRIPT EIGHT; eightinferior  
17394 \DeclareTextCommand{\texteightinferior}{PU}{\9040\210}/* U+2088  
17395 % U+2089 SUBSCRIPT NINE; nineinferior  
17396 \DeclareTextCommand{\textnineinferior}{PU}{\9040\211}/* U+2089  
17397 % U+208A SUBSCRIPT PLUS SIGN
```

```

17398 \DeclareTextCommand{\textplusinferior}{PU}{\9040\212}/* U+208A
17399 % U+208B SUBSCRIPT MINUS
17400 \DeclareTextCommand{\textminusinferior}{PU}{\9040\213}/* U+208B
17401 % U+208C SUBSCRIPT EQUALS SIGN
17402 \DeclareTextCommand{\texteqsinferior}{PU}{\9040\214}/* U+208C
17403 % U+208D SUBSCRIPT LEFT PARENTHESIS; parenleftinferior
17404 \DeclareTextCommand{\textparenleftinferior}{PU}{\9040\215}/* U+208D
17405 % U+208E SUBSCRIPT RIGHT PARENTHESIS; parenrightinferior
17406 \DeclareTextCommand{\textparenrightinferior}{PU}{\9040\216}/* U+208E
17407 % U+2090 LATIN SUBSCRIPT SMALL LETTER A
17408 \DeclareTextCommand{\textainferior}{PU}{\9040\220}/* U+2090
17409 % U+2091 LATIN SUBSCRIPT SMALL LETTER E
17410 \DeclareTextCommand{\texteinferior}{PU}{\9040\221}/* U+2091
17411 % U+2092 LATIN SUBSCRIPT SMALL LETTER O
17412 \DeclareTextCommand{\textoinferior}{PU}{\9040\222}/* U+2092
17413 % U+2093 LATIN SUBSCRIPT SMALL LETTER X
17414 \DeclareTextCommand{\textxinferior}{PU}{\9040\223}/* U+2093
17415 % U+2094 LATIN SUBSCRIPT SMALL LETTER SCHWA
17416 \DeclareTextCommand{\textschwainferior}{PU}{\9040\224}/* U+2094
17417 % U+2095 LATIN SUBSCRIPT SMALL LETTER H
17418 \DeclareTextCommand{\texthinferior}{PU}{\9040\225}/* U+2095
17419 % U+2096 LATIN SUBSCRIPT SMALL LETTER K
17420 \DeclareTextCommand{\textkinferior}{PU}{\9040\226}/* U+2096
17421 % U+2097 LATIN SUBSCRIPT SMALL LETTER L
17422 \DeclareTextCommand{\textlinferior}{PU}{\9040\227}/* U+2097
17423 % U+2098 LATIN SUBSCRIPT SMALL LETTER M
17424 \DeclareTextCommand{\textminferior}{PU}{\9040\230}/* U+2098
17425 % U+2099 LATIN SUBSCRIPT SMALL LETTER N
17426 \DeclareTextCommand{\textninferior}{PU}{\9040\231}/* U+2099
17427 % U+209A LATIN SUBSCRIPT SMALL LETTER P
17428 \DeclareTextCommand{\textpinferior}{PU}{\9040\232}/* U+209A
17429 % U+209B LATIN SUBSCRIPT SMALL LETTER S
17430 \DeclareTextCommand{\textsinferior}{PU}{\9040\233}/* U+209B
17431 % U+209C LATIN SUBSCRIPT SMALL LETTER T
17432 \DeclareTextCommand{\texttinferior}{PU}{\9040\234}/* U+209C

```

46.2.18 Currency Symbols: U+20A0 to U+20CF

```

17433 % U+20A1 COLON SIGN; *colonmonetary, colonsign
17434 \DeclareTextCommand{\textcolonmonetary}{PU}{\9040\241}/* U+20A1
17435 % U+20A4 LIRA SIGN; afi08941, *lira
17436 \DeclareTextCommand{\textlira}{PU}{\9040\244}/* U+20A4
17437 % U+20A6 NAIRA SIGN
17438 \DeclareTextCommand{\textnaira}{PU}{\9040\246}/* U+20A6
17439 % U+20A7 PESETA SIGN; peseta
17440 \DeclareTextCommand{\textpeseta}{PU}{\9040\247}/* U+20A7
17441 % U+20A9 WON SIGN; won
17442 \DeclareTextCommand{\textwon}{PU}{\9040\251}/* U+20A9
17443 % U+20AB DONG SIGN; dong
17444 \DeclareTextCommand{\textdong}{PU}{\9040\253}/* U+20AB
17445 % U+20AC EURO SIGN; *Euro, euro
17446 \DeclareTextCommand{\texteuro}{PU}{\9040\254}/* U+20AC
17447 %* \texteuro -> \EurDig (marvosym)
17448 %* \texteuro -> \EURdig (marvosym)
17449 %* \texteuro -> \EurHv (marvosym)

```

```

17450 %* \texteuro -> \EURhv (marvosym)
17451 %* \texteuro -> \EurCr (marvosym)
17452 %* \texteuro -> \EURcr (marvosym)
17453 %* \texteuro -> \EurTm (marvosym)
17454 %* \texteuro -> \EURtm (marvosym)
17455 %* \texteuro -> \Eur (marvosym)
17456 % U+20B0 GERMAN PENNY SIGN; \Deleatur (marvosym)
17457 \DeclareTextCommand{\textDeleatur}{\PU}{\9040\260} %* U+20B0
17458 %* \textDeleatur -> \Denarius (marvosym)
17459 % U+20B1 PESO SIGN
17460 \DeclareTextCommand{\textpeso}{\PU}{\9040\261} % U+20B1
17461 % U+20B2 GUARANI SIGN
17462 \DeclareTextCommand{\textguarani}{\PU}{\9040\262} % U+20B2

```

46.2.19 Letterlike Symbols: U+2100 to U+214F

```

17463 % U+2103 DEGREE CELSIUS; centigrade
17464 \DeclareTextCommand{\textcelsius}{\PU}{\9041\003} % U+2103
17465 % U+210F PLANCK CONSTANT OVER TWO PI; \hslash (AmS)
17466 \DeclareTextCommand{\texthslash}{\PU}{\9041\017} %* U+210F
17467 % U+2111 BLACK-LETTER CAPITAL I (=imaginary part); Ifraktur; \Im (LaTeX)
17468 \DeclareTextCommand{\textIm}{\PU}{\9041\021} %* U+2111
17469 % U+2113 SCRIPT SMALL L (=ell, liter); afii61289, lsquare; \ell (LaTeX)
17470 \DeclareTextCommand{\textell}{\PU}{\9041\023} %* U+2113
17471 % U+2116 NUMERO SIGN; *afii61352, numero
17472 \DeclareTextCommand{\textnumero}{\PU}{\9041\026} % U+2116
17473 % U+2117 SOUND RECORDING COPYRIGHT
17474 \DeclareTextCommand{\textcircledP}{\PU}{\9041\027} % U+2117
17475 % U+2118 SCRIPT CAPITAL P (=Weierstrass elliptic function);
17476 % weierstrass; \wp (LaTeX)
17477 \DeclareTextCommand{\textwp}{\PU}{\9041\030} %* U+2118
17478 % U+211C BLACK-LETTER CAPITAL R (=real part); Rfraktur; \Re (LaTeX)
17479 \DeclareTextCommand{\textRe}{\PU}{\9041\034} %* U+211C
17480 % U+211E PRESCRIPTION TAKE; prescription
17481 \DeclareTextCommand{\textrecipe}{\PU}{\9041\036} % U+211E
17482 % U+2120 SERVICE MARK
17483 \DeclareTextCommand{\textservicemark}{\PU}{\9041\040} % U+2120
17484 % U+2122 TRADE MARK SIGN; trademark
17485 \DeclareTextCommand{\texttrademark}{\PU}{\9041\042} % U+2122
17486 % U+2126 OHM SIGN; Ohm, Omega
17487 \DeclareTextCommand{\textohm}{\PU}{\9041\046} % U+2126
17488 % U+2127 INVERTED OHM SIGN
17489 \DeclareTextCommand{\textmho}{\PU}{\9041\047} %* U+2127
17490 %* \textmho -> \agemO (wasysym)
17491 % U+2129 TURNED GREEK SMALL LETTER IOTA; \riota (phonetic)
17492 \DeclareTextCommand{\textriota}{\PU}{\9041\051} %* U+2129
17493 % U+212B ANGSTROM SIGN; angstrom
17494 \DeclareTextCommand{\textangstrom}{\PU}{\9041\053} % U+212B
17495 % U+212E ESTIMATED SYMBOL; estimated
17496 \DeclareTextCommand{\textestimated}{\PU}{\9041\056} % U+212E
17497 %* \textestimated -> \EstimatedSign (marvosym)
17498 %* \textestimated -> \Ecommerce (marvosym)
17499 % U+2132 TURNED CAPITAL F; \Finv (AmS)
17500 \DeclareTextCommand{\textFinv}{\PU}{\9041\062} %* U+2132

```

```

17501 % U+2135 ALEF SYMBOL; aleph; \aleph (LaTeX)
17502 \DeclareTextCommand{\textaleph}{PU}{\9041\065}%' U+2135
17503 % U+2136 BET SYMBOL; \beth (AmS, MnSymbol)
17504 \DeclareTextCommand{\textbeth}{PU}{\9041\066}%' U+2136
17505 % U+2137 GIMEL SYMBOL; \gimel (AmS, MnSymbol)
17506 \DeclareTextCommand{\textgimel}{PU}{\9041\067}%' U+2137
17507 % U+2138 DALET SYMBOL; \daleth (AmS, MnSymbol)
17508 \DeclareTextCommand{\textdaleth}{PU}{\9041\070}%' U+2138
17509 % U+213B FACSIMILE SIGN; \fax (marvosym)
17510 \DeclareTextCommand{\textfax}{PU}{\9041\073}%' U+213B
17511 % U+2141 TURNED SANS-SERIF CAPITAL G (=game); \Game
17512 \DeclareTextCommand{\textGame}{PU}{\9041\101}%' U+2141
17513 % U+214B TURNED AMPERSAND; \invamp (txfonts/pxfonts)
17514 \DeclareTextCommand{\textinvamp}{PU}{\9041\113}%' U+214B
17515 %* \textinvamp -> \bindnasrepma (stmaryrd)
17516 %* \textinvamp -> \parr (cml1)

```

46.2.20 Number Forms: U+2150 to U+218F

```

17517 % U+2150 VULGAR FRACTION ONE SEVENTH
17518 \DeclareTextCommand{\textoneseventh}{PU}{\9041\120}%' U+2150
17519 % U+2151 VULGAR FRACTION ONE NINTH
17520 \DeclareTextCommand{\textoneninth}{PU}{\9041\121}%' U+2151
17521 % U+2152 VULGAR FRACTION ONE TENTH
17522 \DeclareTextCommand{\textonetenth}{PU}{\9041\122}%' U+2152
17523 % U+2153 VULGAR FRACTION ONE THIRD; onethird
17524 \DeclareTextCommand{\textonethird}{PU}{\9041\123}%' U+2153
17525 % U+2154 VULGAR FRACTION TWO THIRDS; twothirds
17526 \DeclareTextCommand{\texttwothirds}{PU}{\9041\124}%' U+2154
17527 % U+2155 VULGAR FRACTION ONE FIFTH
17528 \DeclareTextCommand{\textonefifth}{PU}{\9041\125}%' U+2155
17529 % U+2156 VULGAR FRACTION TWO FIFTHS
17530 \DeclareTextCommand{\texttwofifths}{PU}{\9041\126}%' U+2156
17531 % U+2157 VULGAR FRACTION THREE FIFTHS
17532 \DeclareTextCommand{\textthreefifths}{PU}{\9041\127}%' U+2157
17533 % U+2158 VULGAR FRACTION FOUR FIFTHS
17534 \DeclareTextCommand{\textfourfifths}{PU}{\9041\130}%' U+2158
17535 % U+2159 VULGAR FRACTION ONE SIXTH
17536 \DeclareTextCommand{\textonesixth}{PU}{\9041\131}%' U+2159
17537 % U+215A VULGAR FRACTION FIVE SIXTHS
17538 \DeclareTextCommand{\textfivesixths}{PU}{\9041\132}%' U+215A
17539 % U+215B VULGAR FRACTION ONE EIGHTH; oneeighth
17540 \DeclareTextCommand{\textoneeighth}{PU}{\9041\133}%' U+215B
17541 % U+215C VULGAR FRACTION THREE EIGHTHS; threeeighths
17542 \DeclareTextCommand{\textthreeeighths}{PU}{\9041\134}%' U+215C
17543 % U+215D VULGAR FRACTION FIVE EIGHTHS; fiveeighths
17544 \DeclareTextCommand{\textfiveeighths}{PU}{\9041\135}%' U+215D
17545 % U+215E VULGAR FRACTION SEVEN EIGHTHS; seveneighths
17546 \DeclareTextCommand{\textseveneighths}{PU}{\9041\136}%' U+215E
17547 % U+2184 LATIN SMALL LETTER REVERSED C
17548 \DeclareTextCommand{\textrevc}{PU}{\9041\204}%' U+2184
17549 % U+2189 VULGAR FRACTION ZERO THIRDS
17550 \DeclareTextCommand{\textzerothirds}{PU}{\9041\211}%' U+2189

```

46.2.21 Arrows: U+2190 to U+21FF

```

17551 % U+2190 LEFTWARDS ARROW; arrowleft
17552 \DeclareTextCommand{\textleftarrow}{\PU}{\9041\220}/* U+2190
17553 % U+2191 UPWARDS ARROW; arrowup
17554 \DeclareTextCommand{\textuparrow}{\PU}{\9041\221}/* U+2191
17555 % U+2192 RIGHTWARDS ARROW; arrowright
17556 \DeclareTextCommand{\textrightarrow}{\PU}{\9041\222}/* U+2192
17557 /* \textrightarrow -> \MVRightArrow (marvosym)
17558 /* \textrightarrow -> \MVRrightarrow (marvosym)
17559 % U+2193 DOWNWARDS ARROW; arrowdown
17560 \DeclareTextCommand{\textdownarrow}{\PU}{\9041\223}/* U+2193
17561 /* \textdownarrow -> \MVArrowDown (marvosym)
17562 /* \textdownarrow -> \Force (marvosym)
17563 % U+2194 LEFT RIGHT ARROW; arrowboth; \leftrightarrow (LaTeX)
17564 \DeclareTextCommand{\textleftrightarrow}{\PU}{\9041\224}/* U+2194
17565 % U+2195 UP DOWN ARROW; arrowupdn; \updownarrow (LaTeX)
17566 \DeclareTextCommand{\textupdownarrow}{\PU}{\9041\225}/* U+2195
17567 % U+2196 NORTH WEST ARROW; arrowupleft; \nwarrow (LaTeX)
17568 \DeclareTextCommand{\textnwarrow}{\PU}{\9041\226}/* U+2196
17569 % U+2197 NORTH EAST ARROW; arrowupright; \nearrow (LaTeX)
17570 \DeclareTextCommand{\textnearrow}{\PU}{\9041\227}/* U+2197
17571 /* \textnearrow -> \textglobrise (tipa)
17572 % U+2198 SOUTH EAST ARROW; arrowdownright; \searrow (LaTeX)
17573 \DeclareTextCommand{\textsearrow}{\PU}{\9041\230}/* U+2198
17574 /* \textsearrow -> \textglobfall (tipa)
17575 % U+2199 SOUTH WEST ARROW; arrowdownleft; \swarrow (LaTeX)
17576 \DeclareTextCommand{\textswarrow}{\PU}{\9041\231}/* U+2199
17577 % U+219A LEFTWARDS ARROW WITH STROKE; \nleftarrow (AmS)
17578 \DeclareTextCommand{\textnleftarrow}{\PU}{\9041\232}/* U+219A
17579 % U+219B RIGHTWARDS ARROW WITH STROKE; \nrightarrow (AmS)
17580 \DeclareTextCommand{\textnrightarrow}{\PU}{\9041\233}/* U+219B
17581 % U+219E LEFTWARDS TWO HEADED ARROW; \twoheadleftarrow (AmS)
17582 \DeclareTextCommand{\texttwoheadleftarrow}{\PU}{\9041\236}/* U+219E
17583 % \ntwoheadleftarrow (txfonts/pxfonts)
17584 \DeclareTextCommand{\textntwoheadleftarrow}{\PU}{\9041\236\83\070}/* U+219E U+0338
17585 % U+219F UPWARDS TWO HEADED ARROW; \twoheaduparrow (MnSymbol)
17586 \DeclareTextCommand{\texttwoheaduparrow}{\PU}{\9041\237}/* U+219F
17587 % U+21A0 RIGHTWARDS TWO HEADED ARROW;
17588 % \twoheadrightarrow (AmS)
17589 \DeclareTextCommand{\texttwoheadrightarrow}{\PU}{\9041\240}/* U+21A0
17590 % \ntwoheadrightarrow (txfonts/pxfonts)
17591 \DeclareTextCommand{\textntwoheadrightarrow}{\PU}{\9041\240\83\070}/* U+21A0 U+0338
17592 % U+21A1 DOWNWARDS TWO HEADED ARROW; \twoheaddownarrow (Mn-
    Symbol)
17593 \DeclareTextCommand{\texttwoheaddownarrow}{\PU}{\9041\241}/* U+21A1
17594 % U+21A2 LEFTWARDS ARROW WITH TAIL; \leftarrowtail (AmS)
17595 \DeclareTextCommand{\textleftarrowtail}{\PU}{\9041\242}/* U+21A2
17596 % U+21A3 RIGHTWARDS ARROW WITH TAIL; \rightarrowtail (AmS)
17597 \DeclareTextCommand{\textrightarrowtail}{\PU}{\9041\243}/* U+21A3
17598 % U+21A6 RIGHTWARDS ARROW FROM BAR; \mapsto (LaTeX)
17599 \DeclareTextCommand{\textmapsto}{\PU}{\9041\246}/* U+21A6
17600 % U+21A9 LEFTWARDS ARROW WITH HOOK; \hookleftarrow (LaTeX)
17601 \DeclareTextCommand{\texthookleftarrow}{\PU}{\9041\251}/* U+21A9
17602 % U+21AA RIGHTWARDS ARROW WITH HOOK; \hookrightarrow (LaTeX)
17603 \DeclareTextCommand{\texthookrightarrow}{\PU}{\9041\252}/* U+21AA

```

```

17604 % U+21AB LEFTWARDS ARROW WITH LOOP; \looparrowleft (AmS)
17605 \DeclareTextCommand{\textlooparrowleft}{\PU}{\U{9041}{253}}%* U+21AB
17606 % U+21AC RIGHTWARDS ARROW WITH LOOP; \looparrowright (AmS)
17607 \DeclareTextCommand{\textlooparrowright}{\PU}{\U{9041}{254}}%* U+21AC
17608 % U+21AE LEFT RIGHT ARROW WITH STROKE; \nlefrightharow (AmS)
17609 \DeclareTextCommand{\textnlefrightharow}{\PU}{\U{9041}{256}}%* U+21AE
17610 % U+21AF DOWNWARDS ZIGZAG ARROW; \lightning (stmaryrd)
17611 \DeclareTextCommand{\textlightning}{\PU}{\U{9041}{257}}%* U+21AF
17612 %* \textlightning -> \Lightning (marvosym)
17613 % U+21B5 DOWNWARDS ARROW WITH CORNER LEFTWARDS;
17614 % \dlsh (mathabx)
17615 \DeclareTextCommand{\textdlsh}{\PU}{\U{9041}{265}}%* U+21B5
17616 % U+21B6 ANTICLOCKWISE TOP SEMICIRCLE ARROW;
17617 % \curvearrowleft (AmS)
17618 \DeclareTextCommand{\textcurvearrowleft}{\PU}{\U{9041}{266}}%* U+21B6
17619 % U+21B7 CLOCKWISE TOP SEMICIRCLE ARROW; \curvearrowright (AmS)
17620 \DeclareTextCommand{\textcurvearrowright}{\PU}{\U{9041}{267}}%* U+21B7
17621 % U+21BC LEFTWARDS HARPOON WITH BARB UPWARDS; harpoonleft-
barup;
17622 % \leftharpoonup (LaTeX)
17623 \DeclareTextCommand{\textleftharpoonup}{\PU}{\U{9041}{274}}%* U+21BC
17624 % U+21BD LEFTWARDS HARPOON WITH BARB DOWNWARDS;
17625 % \leftharpoondown (LaTeX)
17626 \DeclareTextCommand{\textleftharpoondown}{\PU}{\U{9041}{275}}%* U+21BD
17627 % U+21BE UPWARDS HARPOON WITH BARB RIGHTWARDS;
17628 % \upharpoonright (AmS)
17629 \DeclareTextCommand{\textupharpoonright}{\PU}{\U{9041}{276}}%* U+21BE
17630 % U+21BF UPWARDS HARPOON WITH BARB LEFTWARDS;
17631 % \upharpoonleft (AmS)
17632 \DeclareTextCommand{\textupharpoonleft}{\PU}{\U{9041}{277}}%* U+21BF
17633 % U+21C0 RIGHTWARDS HARPOON WITH BARB UPWARDS; harpoonright-
barup
17634 % \rightharpoonup (LaTeX)
17635 \DeclareTextCommand{\textrightharpoonup}{\PU}{\U{9041}{300}}%* U+21C0
17636 % U+21C1 RIGHTWARDS HARPOON WITH BARB DOWNWARDS;
17637 % \rightharpoondown (LaTeX)
17638 \DeclareTextCommand{\textrightharpoondown}{\PU}{\U{9041}{301}}%* U+21C1
17639 % U+21C2 DOWNWARDS HARPOON WITH BARB RIGHTWARDS;
17640 % \downharpoonright (AmS)
17641 \DeclareTextCommand{\textdownharpoonright}{\PU}{\U{9041}{302}}%* U+21C2
17642 % U+21C3 DOWNWARDS HARPOON WITH BARB LEFTWARDS;
17643 % \downharpoonleft (AmS)
17644 \DeclareTextCommand{\textdownharpoonleft}{\PU}{\U{9041}{303}}%* U+21C3
17645 % U+21C4 RIGHTWARDS ARROW OVER LEFTWARDS ARROW;
17646 % arrowrightoverleft; \rightleftarrows (MnSymbol)
17647 \DeclareTextCommand{\textrightleftarrows}{\PU}{\U{9041}{304}}%* U+21C4
17648 % U+21C5 UPWARDS ARROW LEFTWARDS OF DOWNWARDS ARROW; ar-
rowupleftofdown;
17649 % \updownarrows (MnSymbol)
17650 \DeclareTextCommand{\textupdownarrows}{\PU}{\U{9041}{305}}%* U+21C5
17651 % U+21C6 LEFTWARDS ARROW OVER RIGHTWARDS ARROW; arrowleft-
override;
17652 % \leftrightarrows (AmS)
17653 \DeclareTextCommand{\textleftrightarrows}{\PU}{\U{9041}{306}}%* U+21C6

```

```

17654 % U+21C7 LEFTWARDS PAIRED ARROWS; \leftleftarrows (AmS)
17655 \DeclareTextCommand{\textleftleftarrows}{\PU}{\9041\307}/* U+21C7
17656 % U+21C8 UPWARDS PAIRED ARROWS; \upuparrows (AmS)
17657 \DeclareTextCommand{\textupuparrows}{\PU}{\9041\310}/* U+21C8
17658 % U+21C9 RIGHTWARDS PAIRED ARROWS; \rightrightarrows (AmS)
17659 \DeclareTextCommand{\textrightrightarrows}{\PU}{\9041\311}/* U+21C9
17660 % U+21CA DOWNWARDS PAIRED ARROWS; \downdownarrows (AmS)
17661 \DeclareTextCommand{\textdowndownarrows}{\PU}{\9041\312}/* U+21CA
17662 % U+21CB LEFTWARDS HARPOON OVER RIGHTWARDS HARPOON;
17663 % \leftrightharpoons (AmS);
17664 \DeclareTextCommand{\textleftrightharpoons}{\PU}{\9041\313}/* U+21CB
17665 % U+21CC RIGHTWARDS HARPOON OVER LEFTWARDS HARPOON;
17666 % \rightleftharpoons (LaTeX, AmS)
17667 \DeclareTextCommand{\textrightleftharpoons}{\PU}{\9041\314}/* U+21CC
17668 % U+21CD LEFTWARDS DOUBLE ARROW WITH STROKE; arrowleftdblstroke;
17669 % \nLeftarrow (AmS)
17670 \DeclareTextCommand{\textnLeftarrow}{\PU}{\9041\315}/* U+21CD
17671 % U+21CE LEFT RIGHT DOUBLE ARROW WITH STROKE; \nLeftrightarrow (AmS)
17672 \DeclareTextCommand{\textnLeftrightarrow}{\PU}{\9041\316}/* U+21CE
17673 % U+21CF RIGHTWARDS DOUBLE ARROW WITH STROKE; arrowrightdblstroke;
17674 % \nRrightarrow (AmS)
17675 \DeclareTextCommand{\textnRrightarrow}{\PU}{\9041\317}/* U+21CF
17676 % U+21D0 LEFTWARDS DOUBLE ARROW; arrowdblleft, arrowleftdbl;
17677 % \Leftrightarrow (LaTeX)
17678 \DeclareTextCommand{\textLeftarrow}{\PU}{\9041\320}/* U+21D0
17679 % U+21D1 UPWARDS DOUBLE ARROW; arrowdblup; \Uparrow (LaTeX)
17680 \DeclareTextCommand{\textUparrow}{\PU}{\9041\321}/* U+21D1
17681 % U+21D2 RIGHTWARDS DOUBLE ARROW; arrowdblright, dblarrowright;
17682 % \Rrightarrow (LaTeX)
17683 \DeclareTextCommand{\textRrightarrow}{\PU}{\9041\322}/* U+21D2
17684 /* \textRrightarrow -> \Conclusion (marvosym)
17685 % U+21D3 DOWNWARDS DOUBLE ARROW; arrowdbldown; \Downarrow (LaTeX)
17686 \DeclareTextCommand{\textDownarrow}{\PU}{\9041\323}/* U+21D3
17687 % U+21D4 LEFT RIGHT DOUBLE ARROW; arrowdblboth;
17688 % \Leftrightarrow (LaTeX)
17689 \DeclareTextCommand{\textLeftrightarrow}{\PU}{\9041\324}/* U+21D4
17690 /* \textLeftrightarrow -> \Equivalence (marvosym)
17691 % U+21D5 UP DOWN DOUBLE ARROW; \Updownarrow (LaTeX)
17692 \DeclareTextCommand{\textUpdownarrow}{\PU}{\9041\325}/* U+21D5
17693 % U+21D6 NORTH WEST DOUBLE ARROW; \Nwarrow (MnSymbol)
17694 \DeclareTextCommand{\textNwarrow}{\PU}{\9041\326}/* U+21D6
17695 % U+21D7 NORTH EAST DOUBLE ARROW; \Nearrow (MnSymbol)
17696 \DeclareTextCommand{\textNearrow}{\PU}{\9041\327}/* U+21D7
17697 % U+21D8 SOUTH EAST DOUBLE ARROW; \Searrow (MnSymbol)
17698 \DeclareTextCommand{\textSearrow}{\PU}{\9041\330}/* U+21D8
17699 % U+21D9 SOUTH WEST DOUBLE ARROW; \Swarrow (MnSymbol)
17700 \DeclareTextCommand{\textSwarrow}{\PU}{\9041\331}/* U+21D9
17701 % U+21DA LEFTWARDS TRIPLE ARROW; \Lleftarrow (AmS)
17702 \DeclareTextCommand{\textLleftarrow}{\PU}{\9041\332}/* U+21DA
17703 % U+21DB RIGHTWARDS TRIPLE ARROW; \Rrightarrow (MnSymbol)

```

```

17704 \DeclareTextCommand{\textRightarrow}{\PU}{\U041333}/* U+21DB
17705 % U+21DC LEFTWARDS SQUIGGLE ARROW; \leftsquigarrow (mathabx)
17706 \DeclareTextCommand{\textleftsquigarrow}{\PU}{\U041334}/* U+21DC
17707 % U+21DD RIGHTWARDS SQUIGGLE ARROW; \rightsquigarrow (mathabx)
17708 \DeclareTextCommand{\textrightsquigarrow}{\PU}{\U041335}/* U+21DD
17709 % U+21E0 LEFTWARDS DASHED ARROW; arrowdashleft;
17710 % \dashleftarrow (AmS)
17711 \DeclareTextCommand{\textdashleftarrow}{\PU}{\U041340}/* U+21E0
17712 /* \textdashleftarrow -> \dashedleftarrow (MnSymbol)
17713 % U+21E1 UPWARDS DASHED ARROW; arrowdashup; \dasheduparrow (Mn-
    Symbol)
17714 \DeclareTextCommand{\textdasheduparrow}{\PU}{\U041341}/* U+21E1
17715 % U+21E2 RIGHTWARDS DASHED ARROW; arrowdashright; \dashrightarrow
    (AmS)
17716 \DeclareTextCommand{\textdashrightarrow}{\PU}{\U041342}/* U+21E2
17717 /* \textdashrightarrow -> \dashedrightarrow (MnSymbol)
17718 % U+21E3 DOWNWARDS DASHED ARROW; arrowdashdown; \dasheddownar-
    row (MnSymbol)
17719 \DeclareTextCommand{\textdasheddownarrow}{\PU}{\U041343}/* U+21E3
17720 % U+21E8 RIGHTWARDS WHITE ARROW; \pointer (wasysym)
17721 \DeclareTextCommand{\textpointer}{\PU}{\U041350}/* U+21E8
17722 % U+21F5 DOWNWARDS ARROW LEFTWARDS OF UPWARDS ARROW;
17723 % \downuparrows (MnSymbol)
17724 \DeclareTextCommand{\textdownuparrows}{\PU}{\U041365}/* U+21F5
17725 % U+21FD LEFTWARDS OPEN-HEADED ARROW; \leftarrowtriangle (stmaryrd)
17726 \DeclareTextCommand{\textleftarrowtriangle}{\PU}{\U041375}/* U+21FD
17727 % U+21FE RIGHTWARDS OPEN-HEADED ARROW; \rightarrowtriangle (stmaryrd)
17728 \DeclareTextCommand{\textrightarrowtriangle}{\PU}{\U041376}/* U+21FE
17729 % U+21FF LEFT RIGHT OPEN-HEADED ARROW; \leftrightarrowtri-
    gle (stmaryrd)
17730 \DeclareTextCommand{\textleftrightarrowtriangle}{\PU}{\U041377}/* U+21FF

```

46.2.22 Mathematical Operators: U+2200 to U+22FF

```

17731 % U+2200 FOR ALL; forall; \forall (LaTeX)
17732 \DeclareTextCommand{\textforall}{\PU}{\U042000}/* U+2200
17733 % U+2201 COMPLEMENT; \complement (AmS)
17734 \DeclareTextCommand{\textcomplement}{\PU}{\U042001}/* U+2201
17735 % U+2202 PARTIAL DIFFERENTIAL; partialdiff; \partial (LaTeX)
17736 \DeclareTextCommand{\textpartial}{\PU}{\U042002}/* U+2202
17737 % U+2203 THERE EXISTS; existential; \exists (LaTeX)
17738 \DeclareTextCommand{\textexists}{\PU}{\U042003}/* U+2203
17739 % U+2204 THERE DOES NOT EXIST; \notexists (AmS)
17740 \DeclareTextCommand{\textnexists}{\PU}{\U042004}/* U+2204
17741 % U+2205 EMPTY SET; emptyset; \emptyset (LaTeX), \varnothing (AmS)
17742 \DeclareTextCommand{\textemptyset}{\PU}{\U042005}/* U+2205
17743 /* \textemptyset -> \varnothing (AmS)
17744 % U+2206 INCREMENT; increment, Deta; \triangle (LaTeX)
17745 \DeclareTextCommand{\texttriangle}{\PU}{\U042006}/* U+2206
17746 % U+2207 NABLA; nabla, gradient; \nabla (LaTeX)
17747 \DeclareTextCommand{\textnabla}{\PU}{\U042007}/* U+2207
17748 % U+2208 ELEMENT OF; element; \in (LaTeX)
17749 \DeclareTextCommand{\textin}{\PU}{\U042010}/* U+2208
17750 % U+2209 NOT AN ELEMENT OF; notelement, notelementof; \notin (LaTeX)
17751 \DeclareTextCommand{\textnotin}{\PU}{\U042011}/* U+2209

```

```

17752 % U+220A SMALL ELEMENT OF; \smallin (mathdesign)
17753 \DeclareTextCommand{\textsmallin}{\PU}{\U9042\012} %* U+220A
17754 % U+220B CONTAINS AS MEMBER; suchthat; \ni (LaTeX)
17755 \DeclareTextCommand{\textni}{\PU}{\U9042\013} %* U+220B
17756 %* \textni -> \owns (mathabx)
17757 % U+220C DOES NOT CONTAIN AS MEMBER; \notowner (mathabx)
17758 \DeclareTextCommand{\textnotowner}{\PU}{\U9042\014} %* U+220C
17759 %* \textnotowner -> \notni (txfonts/pffonts)
17760 % U+220D SMALL CONTAINS AS MEMBER; \smallowns (mathdesign)
17761 \DeclareTextCommand{\textsmallowns}{\PU}{\U9042\015} %* U+220D
17762 % U+220F N-ARY PRODUCT; \prod (LaTeX)
17763 \DeclareTextCommand{\textprod}{\PU}{\U9042\017} %* U+220F
17764 % U+2210 N-ARY COPRODUCT; \amalg (LaTeX)
17765 \DeclareTextCommand{\textamalg}{\PU}{\U9042\020} %* U+2210
17766 % U+2211 N-ARY SUMMATION; summation; \sum (LaTeX)
17767 \DeclareTextCommand{\textsum}{\PU}{\U9042\021} %* U+2211
17768 % U+2212 MINUS SIGN; minus
17769 \DeclareTextCommand{\textminus}{\PU}{\U9042\022} %* U+2212
17770 % U+2213 MINUS-OR-PLUS SIGN; minusplus; \mp (LaTeX)
17771 \DeclareTextCommand{\textmp}{\PU}{\U9042\023} %* U+2213
17772 % U+2214 DOT PLUS; \dotplus (AmS)
17773 \DeclareTextCommand{\textdotplus}{\PU}{\U9042\024} %* U+2214
17774 % U+2215 DIVISION SLASH; divisionslash; \Divides (marvosym)
17775 \DeclareTextCommand{\textDivides}{\PU}{\U9042\025} %* U+2215
17776 % \DividesNot (marvosym)
17777 \DeclareTextCommand{\textDividesNot}{\PU}{\U9042\025\U9040\322} %* U+2215 U+20D2
17778 % U+2216 SET MINUS; \setminus (LaTeX)
17779 \DeclareTextCommand{\textsetminus}{\PU}{\U9042\026} %* U+2216
17780 % U+2217 ASTERISK OPERATOR; asteriskmath; \ast (LaTeX)
17781 \DeclareTextCommand{\textast}{\PU}{\U9042\027} %* U+2217
17782 % U+2218 RING OPERATOR; \circ (LaTeX)
17783 \DeclareTextCommand{\textcirc}{\PU}{\U9042\030} %* U+2218
17784 % U+2219 BULLET OPERATOR; bulletoperator; \bullet (LaTeX)
17785 \DeclareTextCommand{\textbulletoperator}{\PU}{\U9042\031} %* U+2219
17786 % U+221A SQUARE ROOT; radical
17787 \DeclareTextCommand{\textsurd}{\PU}{\U9042\032} %* U+221A
17788 % U+221D PROPORTIONAL TO; proportional; \propto (LaTeX)
17789 \DeclareTextCommand{\textpropto}{\PU}{\U9042\035} %* U+221D
17790 %* \textpropto -> \varprop (wasysym)
17791 % U+221E INFINITY; infinity; \infty (LaTeX)
17792 \DeclareTextCommand{\textinfty}{\PU}{\U9042\036} %* U+221E
17793 % U+2220 ANGLE; angle; \angle (LaTeX)
17794 \DeclareTextCommand{\textangle}{\PU}{\U9042\040} %* U+2220
17795 % U+2221 MEASURED ANGLE; \measuredangle (mathabx, MnSymbol)
17796 \DeclareTextCommand{\textmeasuredangle}{\PU}{\U9042\041} %* U+2221
17797 % U+2222 SPHERICAL ANGLE; \sphericalangle (AmS)
17798 \DeclareTextCommand{\textsphericalangle}{\PU}{\U9042\042} %* U+2222
17799 %* \textsphericalangle -> \varangle (wasysym)
17800 %* \textsphericalangle -> \Anglesign (marvosym)
17801 %* \textsphericalangle -> \AngleSign (marvosym)
17802 % U+2223 DIVIDES; divides; \mid (LaTeX)
17803 \DeclareTextCommand{\textmid}{\PU}{\U9042\043} %* U+2223
17804 % U+2224 DOES NOT DIVIDE; \nmid (AmS)
17805 \DeclareTextCommand{\textnmid}{\PU}{\U9042\044} %* U+2224

```

```

17806 %* \textnmid -> \notdivides (mathabx)
17807 % U+2225 PARALLEL TO; parallel; \parallel (LaTeX)
17808 \DeclareTextCommand{\textparallel}{\PU}{\9042\045} %* U+2225
17809 % U+2226 NOT PARALLEL TO; notparallel; \nparallel (AmS)
17810 \DeclareTextCommand{\textnparallel}{\PU}{\9042\046} %* U+2226
17811 %* \textnparallel -> nUpdownline (MnSymbol)
17812 % U+2227 LOGICAL AND; logicaland; \wedge (LaTeX)
17813 \DeclareTextCommand{\textwedge}{\PU}{\9042\047} %* U+2227
17814 % \owedge (stmaryrd)
17815 \DeclareTextCommand{\textowedge}{\PU}{\9042\047\9040\335} %* U+2227 U+20DD
17816 %* \textowedge -> \varowedge (stmaryrd)
17817 % U+2228 LOGICAL OR; logicalor; \vee (LaTeX)
17818 \DeclareTextCommand{\textvee}{\PU}{\9042\050} %* U+2228
17819 % \ovee (stmaryrd)
17820 \DeclareTextCommand{\textovee}{\PU}{\9042\050\9040\335} %* U+2228 U+20DD
17821 %* \textovee -> \varovee (stmaryrd)
17822 % U+2229 INTERSECTION; intersection; \cap (LaTeX)
17823 \DeclareTextCommand{\textcap}{\PU}{\9042\051} %* U+2229
17824 % U+222A UNION; union; \cup (LaTeX)
17825 \DeclareTextCommand{\textcup}{\PU}{\9042\052} %* U+222A
17826 % U+222B INTEGRAL; integral; \int (LaTeX)
17827 \DeclareTextCommand{\textint}{\PU}{\9042\053} %* U+222B
17828 %* \textint -> \varint (wasysym)
17829 % U+222C DOUBLE INTEGRAL; dblintegral; \iint (AmS)
17830 \DeclareTextCommand{\textiint}{\PU}{\9042\054} %* U+222C
17831 % U+222D TRIPLE INTEGRAL; \iiint (AmS)
17832 \DeclareTextCommand{\textiiint}{\PU}{\9042\055} %* U+222D
17833 % U+222E CONTOUR INTEGRAL; contourintegral; \oint (LaTeX)
17834 \DeclareTextCommand{\textoint}{\PU}{\9042\056} %* U+222E
17835 %* \textoint -> \varoint (wasysym)
17836 % U+222F SURFACE INTEGRAL; \oiint (wasysym)
17837 \DeclareTextCommand{\textoiint}{\PU}{\9042\057} %* U+222F
17838 % U+2232 CLOCKWISE CONTOUR INTEGRAL;
17839 % \ointclockwise (txfonts/pxfonts)
17840 \DeclareTextCommand{\textointclockwise}{\PU}{\9042\062} %* U+2232
17841 % U+2233 ANTICLOCKWISE CONTOUR INTEGRAL; \ointcclockwise (tx-
  fonts/pxfonts)
17842 \DeclareTextCommand{\textointcclockwise}{\PU}{\9042\063} %* U+2233
17843 % U+2234 THEREFORE; therefore; \therefore (AmS)
17844 \DeclareTextCommand{\textttherefore}{\PU}{\9042\064} %* U+2234
17845 %* \textttherefore -> uptherefore (MnSymbol)
17846 % U+2235 BECAUSE; because; \because (AmS)
17847 \DeclareTextCommand{\textbecause}{\PU}{\9042\065} %* U+2235
17848 %* \textbecause -> \downtherefore (MnSymbol)
17849 % U+2236 RATIO; \vdotdot (MnSymbol)
17850 \DeclareTextCommand{\textvdotdot}{\PU}{\9042\066} %* U+2236
17851 % U+2237 PROPORTION; \squardots (MnSymbol)
17852 \DeclareTextCommand{\textssquaredots}{\PU}{\9042\067} %* U+2237
17853 % U+2238 DOT MINUS; \dotminus (MnSymbol)
17854 \DeclareTextCommand{\textdotminus}{\PU}{\9042\070} %* U+2238
17855 %* \textdotminus -> \textdotdiv (mathabx)
17856 % U+2239 EXCESS; \eqcolon (txfonts/pxfonts)
17857 \DeclareTextCommand{\texteqcolon}{\PU}{\9042\071} %* U+2239
17858 % U+223C TILDE OPERATOR; similar; \sim (LaTeX)

```

```

17859 \DeclareTextCommand{\textsim}{\PU}{\9042\074}/* U+223C
17860 /* \textsim -> \AC (wasysym)
17861 % U+223D REVERSED TILDE; reversedtilde; \backsim (AmS)
17862 \DeclareTextCommand{\textbacksim}{\PU}{\9042\075}/* U+223D
17863 % \nbacksim (txfonts/pxfonts)
17864 \DeclareTextCommand{\textnbacksim}{\PU}{\9042\075\83\070}/* U+223D U+0338
17865 % U+2240 WREATH PRODUCT; \wr (LaTeX)
17866 \DeclareTextCommand{\textwr}{\PU}{\9042\100}/* U+2240
17867 /* \textwr -> \wreath (MnSymbol)
17868 % U+2241 NOT TILDE; \nsim (AmS)
17869 \DeclareTextCommand{\textnsim}{\PU}{\9042\101}/* U+2241
17870 % U+2242 MINUS TILDE; \eqsim (MnSymbol)
17871 \DeclareTextCommand{\texteqsim}{\PU}{\9042\102}/* U+2242
17872 % \neqsim (MnSymbol)
17873 \DeclareTextCommand{\textneqsim}{\PU}{\9042\102\83\070}/* U+2242 U+0338
17874 % U+2243 ASYMPTOTICALLY EQUAL TO; asymptoticallyequal; \simeq (La-
    TeX)
17875 \DeclareTextCommand{\textssimeq}{\PU}{\9042\103}/* U+2243
17876 % U+2244 NOT ASYMPTOTICALLY EQUAL TO; \nsimeq (txfonts/pxfonts)
17877 \DeclareTextCommand{\textnsimeq}{\PU}{\9042\104}/* U+2244
17878 % U+2245 APPROXIMATELY EQUAL TO; approximatelyequal; \cong (LaTeX)
17879 \DeclareTextCommand{\textcong}{\PU}{\9042\105}/* U+2245
17880 % U+2247 NEITHER APPROXIMATELY NOR ACTUALLY EQUAL TO;
17881 % \ncong (AmS)
17882 \DeclareTextCommand{\textncong}{\PU}{\9042\107}/* U+2247
17883 % U+2248 ALMOST EQUAL TO; \approxeq (AmS)
17884 \DeclareTextCommand{\textapprox}{\PU}{\9042\110}/* U+2248
17885 % U+2249 NOT ALMOST EQUAL TO; \napprox (txfonts/pxfonts0
17886 \DeclareTextCommand{\textnapprox}{\PU}{\9042\111}/* U+2249
17887 /* \textnapprox -> \nthickapprox (txfonts/pxfonts)
17888 % U+224A ALMOST EQUAL OR EQUAL TO; \approxeq (AmS)
17889 \DeclareTextCommand{\textapproxeq}{\PU}{\9042\112}/* U+224A
17890 % \napproxeq (txfonts/pxfonts)
17891 \DeclareTextCommand{\textnapproxeq}{\PU}{\9042\112\83\070}/* U+224A U+0338
17892 % U+224B TRIPLE TILDE; \triplesim (MnSymbol)
17893 \DeclareTextCommand{\texttriplesim}{\PU}{\9042\113}/* U+224B
17894 /* \texttriplesim -> \VHF (wasysym)
17895 % \ntriplesim (MnSymbol)
17896 \DeclareTextCommand{\textntriplesim}{\PU}{\9042\113\83\070}/* U+224B U+0338
17897 % U+224C ALL EQUAL TO; \allequal; \backcong (MnSymbol)
17898 \DeclareTextCommand{\textbackcong}{\PU}{\9042\114}/* U+224C
17899 % \nbackcong (MnSymbol)
17900 \DeclareTextCommand{\textnbackcong}{\PU}{\9042\114\83\070}/* U+224C U+0338
17901 % U+224D EQUIVALENT TO; \asymp (LaTeX)
17902 \DeclareTextCommand{\textasymp}{\PU}{\9042\115}/* U+224D
17903 % \nasym (txfonts/pxfonts)
17904 \DeclareTextCommand{\textnasymp}{\PU}{\9042\115\83\070}/* U+224D U+0338
17905 /* \textnasymp -> \notasymp (mathabx)
17906 % U+224E GEOMETRICALLY EQUIVALENT TO; \Bumpeq (AmS)
17907 \DeclareTextCommand{\textBumpeq}{\PU}{\9042\116}/* U+224E
17908 % \nBumpeq (txfonts/pxfonts)
17909 \DeclareTextCommand{\textnBumpeq}{\PU}{\9042\116\83\070}/* U+224E U+0338
17910 % U+224F DIFFERENCE BETWEEN; \bumpeq (AmS)
17911 \DeclareTextCommand{\textbumpeq}{\PU}{\9042\117}/* U+224F

```

```

17912 % \nbumpmeq (txfonts/pxfonts)
17913 \DeclareTextCommand{\textnbumpmeq}{PU}{\9042\117\83\070}/* U+224F U+0338
17914 % U+2250 APPROACHES THE LIMIT; approaches; \doteq (LaTeX)
17915 \DeclareTextCommand{\textdoteq}{PU}{\9042\120}/* U+2250
17916 % \ndoteq (MnSymbol)
17917 \DeclareTextCommand{\textndoteq}{PU}{\9042\120\83\070}/* U+2250 U+0338
17918 % U+2251 GEOMETRICALLY EQUAL TO; geometricallyequal;
17919 % \doteqdot (AmS)
17920 \DeclareTextCommand{\textdoteqdot}{PU}{\9042\121}/* U+2251
17921 /* \textdoteqdot -> \Doteq (MnSymbol)
17922 % \nDoteq (MnSymbol)
17923 \DeclareTextCommand{\textnDoteq}{PU}{\9042\121\83\070}/* U+2251 U+0338
17924 % U+2252 APPROXIMATELY EQUAL TO OR THE IMAGE OF; approx-
    equalorimage;
17925 % \fallingdotseq (AmS)
17926 \DeclareTextCommand{\textfallingdoteq}{PU}{\9042\122}/* U+2252
17927 % \nfallingdotseq (MnSymbol)
17928 \DeclareTextCommand{\textnfallingdoteq}{PU}{\9042\122\83\070}/* U+2252 U+0338
17929 % U+2253 IMAGE OF OR APPROXIMATELY EQUAL TO; imageorapproxi-
    matelyequal;
17930 % \risingdotseq (AmS)
17931 \DeclareTextCommand{\textrisingdoteq}{PU}{\9042\123}/* U+2253
17932 % \nrisingdoteq (MnSymbol)
17933 \DeclareTextCommand{\textnrisingdoteq}{PU}{\9042\123\83\070}/* U+2253 U+0338
17934 % U+2254 COLON EQUALS; \colonequals (colonequals)
17935 \DeclareTextCommand{\textcolonequals}{PU}{\9042\124}/* U+2254
17936 % U+2255 EQUALS COLON; \equalscolon (colonequals)
17937 \DeclareTextCommand{\texteqcolon}{PU}{\9042\125}/* U+2255
17938 % U+2256 RING IN EQUAL TO; \eqcirc (AmS)
17939 \DeclareTextCommand{\texteqcirc}{PU}{\9042\126}/* U+2256
17940 % \neqcirc (MnSymbol)
17941 \DeclareTextCommand{\textneqcirc}{PU}{\9042\126\83\070}/* U+2256 U+0338
17942 % U+2257 RING EQUAL TO; \circeq (AmS)
17943 \DeclareTextCommand{\textcirceq}{PU}{\9042\127}/* U+2257
17944 % \ncirceq (MnSymbol)
17945 \DeclareTextCommand{\textncirceq}{PU}{\9042\127\83\070}/* U+2257 U+0338
17946 % U+2259 ESTIMATES; \hateq (MnSymbol)
17947 \DeclareTextCommand{\texthateq}{PU}{\9042\131}/* U+2259
17948 /* \texthateq -> \corresponds (mathabx)
17949 /* \texthateq -> \Corresponds (marvosym)
17950 % \nhateq (MnSymbol)
17951 \DeclareTextCommand{\textnhateq}{PU}{\9042\131\83\070}/* U+2259 U+0338
17952 % U+225C DELTA EQUAL TO; \triangleeq (AmS)
17953 \DeclareTextCommand{\texttriangleeq}{PU}{\9042\134}/* U+225C
17954 % U+2260 NOT EQUAL TO; notequal; \ne (LaTeX), \neq (LaTeX)
17955 \DeclareTextCommand{\textneq}{PU}{\9042\140}/* U+2260
17956 \DeclareTextCommand{\textne}{PU}{\9042\140}/* U+2260
17957 /* \textne -> \nequal (MnSymbol)
17958 % U+2261 IDENTICAL TO; equivalence; \equiv (LaTeX)
17959 \DeclareTextCommand{\textequiv}{PU}{\9042\141}/* U+2261
17960 /* \textequiv -> \Congruent (marvosym)
17961 % U+2262 NOT IDENTICAL TO; notidentical; \nequiv (txfonts/pxfonts)
17962 \DeclareTextCommand{\textnequiv}{PU}{\9042\142}/* U+2262
17963 /* \textnequiv -> \NotCongruent (marvosym)

```

```

17964 %* \textnequiv -> \notequiv (mathabx)
17965 % U+2264 LESS-THAN OR EQUAL TO; lessequal; \le (LaTeX), \leq (LaTeX)
17966 \DeclareTextCommand{\textleq}{\PU}{\9042\144} %* U+2264
17967 \DeclareTextCommand{\textle}{\PU}{\9042\144} %* U+2264
17968 %* \textle -> \LessOrEqual (marvosym)
17969 % U+2265 GREATER-THAN OR EQUAL TO; greaterequal;
17970 % \ge (LaTeX), \geq (LaTeX)
17971 \DeclareTextCommand{\textgeq}{\PU}{\9042\145} %* U+2265
17972 \DeclareTextCommand{\textge}{\PU}{\9042\145} %* U+2265
17973 %* \textge -> \LargerOrEqual (marvosym)
17974 % U+2266 LESS-THAN OVER EQUAL TO; lessoverequal; \leqq (AmS)
17975 \DeclareTextCommand{\textleqq}{\PU}{\9042\146} %* U+2266
17976 % \nleqq (txfonts/pxfonts)
17977 \DeclareTextCommand{\textnleqq}{\PU}{\9042\146\83\070} %* U+2266 U+0338
17978 % U+2267 GREATER-THAN OVER EQUAL TO; greateroverequal; \geqq (AmS)
17979 \DeclareTextCommand{\textgeqq}{\PU}{\9042\147} %* U+2267
17980 % \ngeqq (txfonts/pxfonts)
17981 \DeclareTextCommand{\textngeqq}{\PU}{\9042\147\83\070} %* U+2267 U+0338
17982 % U+2268 LESS-THAN BUT NOT EQUAL TO; \nleq (AmS)
17983 \DeclareTextCommand{\textnleq}{\PU}{\9042\150} %* U+2268
17984 % U+2269 GREATER-THAN BUT NOT EQUAL TO; \gneq (AmS)
17985 \DeclareTextCommand{\textgneq}{\PU}{\9042\151} %* U+2269
17986 % U+226A MUCH LESS-THAN; muchless; \ll (LaTeX)
17987 \DeclareTextCommand{\textll}{\PU}{\9042\152} %* U+226A
17988 % \nll (txfonts/pxfonts)
17989 \DeclareTextCommand{\textnll}{\PU}{\9042\152\83\070} %* U+226A U+0338
17990 % U+226B MUCH GREATER-THAN; muchgreater; \gg (LaTeX)
17991 \DeclareTextCommand{\textgg}{\PU}{\9042\153} %* U+226B
17992 % \ngg (txfonts/pxfonts)
17993 \DeclareTextCommand{\textngg}{\PU}{\9042\153\83\070} %* U+226B U+0338
17994 % U+226C BETWEEN; \between (AmS)
17995 \DeclareTextCommand{\textbetween}{\PU}{\9042\154} %* U+226C
17996 % U+226E NOT LESS-THAN; notless; \nless (AmS)
17997 \DeclareTextCommand{\textnless}{\PU}{\9042\156} %* U+226E
17998 % U+226F NOT GREATER-THAN; notgreater; \ngtr (AmS)
17999 \DeclareTextCommand{\textngtr}{\PU}{\9042\157} %* U+226F
18000 % U+2270 NEITHER LESS-THAN NOR EQUAL TO; notlessnor equal;
18001 % \nleq (AmS)
18002 \DeclareTextCommand{\textnleq}{\PU}{\9042\160} %* U+2270
18003 % U+2271 NEITHER GREATER-THAN NOR EQUAL TO; notgreater nor equal;
18004 \DeclareTextCommand{\textngeq}{\PU}{\9042\161} %* U+2271
18005 % U+2272 LESS-THAN OR EQUIVALENT TO; lessorequivalent; \lessim (AmS)
18006 \DeclareTextCommand{\textlessim}{\PU}{\9042\162} %* U+2272
18007 %* \textlessim -> \apprle (wasysym)
18008 % U+2273 GREATER-THAN OR EQUIVALENT TO; greaterorequivalent; \gtrsim (AmS)
18009 \DeclareTextCommand{\textgtrsim}{\PU}{\9042\163} %* U+2273
18010 %* \textgtrsim -> \apprge (wasysym)
18011 % U+2274 NEITHER LESS-THAN NOR EQUIVALENT TO; \nlessim (tx-
18012 \DeclareTextCommand{\textnlessim}{\PU}{\9042\164} %* U+2274
18013 % U+2275 NEITHER GREATER-THAN NOR EQUIVALENT TO; \ngtrsim (tx-

```

```

18014 \DeclareTextCommand{\textngtrsim}{\PU}{\9042\165}/* U+2275
18015 % U+2276 LESS-THAN OR GREATER-THAN; lessorgreater; \lessgtr (AmS)
18016 \DeclareTextCommand{\textlessgtr}{\PU}{\9042\166}/* U+2276
18017 % U+2277 GREATER-THAN OR LESS-THAN; greaterorless; \gtrless (AmS)
18018 \DeclareTextCommand{\textgtrless}{\PU}{\9042\167}/* U+2277
18019 % U+2278 NEITHER LESS-THAN NOR GREATER-THAN; \ngtrless (tx-
    fonts/pxfonts)
18020 \DeclareTextCommand{\textngtrless}{\PU}{\9042\170}/* U+2278
18021 % U+2279 NEITHER GREATER-THAN NOR LESS-THAN; \nlessgtr (tx-
    fonts/pxfonts)
18022 \DeclareTextCommand{\textnlessgtr}{\PU}{\9042\171}/* U+2279
18023 % U+227A PRECEDES; precedes; \prec (LaTeX)
18024 \DeclareTextCommand{\textprec}{\PU}{\9042\172}/* U+227A
18025 % U+227B SUCCEEDS; succeeds; \succ (LaTeX)
18026 \DeclareTextCommand{\textsucc}{\PU}{\9042\173}/* U+227B
18027 % U+227C PRECEDES OR EQUAL TO; \preccurlyeq (AmS)
18028 \DeclareTextCommand{\textpreccurlyeq}{\PU}{\9042\174}/* U+227C
18029 % U+227D SUCCEEDS OR EQUAL TO; \succcurlyeq (AmS)
18030 \DeclareTextCommand{\textsucccurlyeq}{\PU}{\9042\175}/* U+227D
18031 % U+227E PRECEDES OR EQUIVALENT TO; \precsim (AmS)
18032 \DeclareTextCommand{\textprecsim}{\PU}{\9042\176}/* U+227E
18033 % \nprecsim (txfonts/pxfonts)
18034 \DeclareTextCommand{\textnprecsim}{\PU}{\9042\176\83\070}/* U+227E U+0338
18035 % U+227F SUCCEEDS OR EQUIVALENT TO; \succsim (AmS)
18036 \DeclareTextCommand{\textsuccsim}{\PU}{\9042\177}/* U+227F
18037 % \nsuccsim (txfonts/pxfonts)
18038 \DeclareTextCommand{\textnsuccsim}{\PU}{\9042\177\83\070}/* U+227F U+0338
18039 % U+2280 DOES NOT PRECEDE; \notprecedes; \nprec (AmS)
18040 \DeclareTextCommand{\textnprec}{\PU}{\9042\200}/* U+2280
18041 % U+2281 DOES NOT SUCCEED; \notsucceeds; \nsucc (AmS)
18042 \DeclareTextCommand{\textnsucc}{\PU}{\9042\201}/* U+2281
18043 % U+2282 SUBSET OF; \propersubset; \subset (LaTeX)
18044 \DeclareTextCommand{\textsubset}{\PU}{\9042\202}/* U+2282
18045 % U+2283 SUPERSET OF; \propersuperset; \supset (LaTeX)
18046 \DeclareTextCommand{\textsupset}{\PU}{\9042\203}/* U+2283
18047 % U+2284 NOT A SUBSET OF; \notsubset; \nssubset (mathabx)
18048 \DeclareTextCommand{\textnsubset}{\PU}{\9042\204}/* U+2284
18049 % U+2285 NOT A SUPERSET OF; \notsuperset; \nsupset (mathabx)
18050 \DeclareTextCommand{\textnsupset}{\PU}{\9042\205}/* U+2285
18051 % U+2286 SUBSET OF OR EQUAL TO; \reflexsubset; \subsequeq (LaTeX)
18052 \DeclareTextCommand{\textsubsequeq}{\PU}{\9042\206}/* U+2286
18053 % U+2287 SUPERSET OF OR EQUAL TO; \reflexsuperset; \supseteqq (LaTeX)
18054 \DeclareTextCommand{\textsupseteqq}{\PU}{\9042\207}/* U+2287
18055 % U+2288 NEITHER A SUBSET OF NOR EQUAL TO; \nsubsequeq (AmS)
18056 \DeclareTextCommand{\textnsubsequeq}{\PU}{\9042\210}/* U+2288
18057 % U+2289 NEITHER A SUPERSET OF NOR EQUAL TO; \nsupseteqq (AmS)
18058 \DeclareTextCommand{\textnsupseteqq}{\PU}{\9042\211}/* U+2289
18059 % U+228A SUBSET OF WITH NOT EQUAL TO; \subsetnotequal; \subset-
    neq (AmS)
18060 \DeclareTextCommand{\textsubsetneq}{\PU}{\9042\212}/* U+228A
18061 % U+228B SUPERSET OF WITH NOT EQUAL TO; \supersetnotequal; \supset-
    neq (AmS)
18062 \DeclareTextCommand{\textsupsetneq}{\PU}{\9042\213}/* U+228B
18063 % U+228D MULTISET MULTIPLICATION; \cupdot (MnSymbol)

```

```

18064 \DeclareTextCommand{\textcupdot}{\PU}{\U042\215}/* U+228D
18065 % U+228E MULTISSET UNION; \cupplus (MnSymbol)
18066 \DeclareTextCommand{\textcupplus}{\PU}{\U042\216}/* U+228E
18067 % U+228F SQUARE IMAGE OF; \sqsubset (latexsym, ...)
18068 \DeclareTextCommand{\textsqsubset}{\PU}{\U042\217}/* U+228F
18069 % \nsqsubset (txfonts/pxfonts)
18070 \DeclareTextCommand{\textnsqsubset}{\PU}{\U042\217\83\070}/* U+228F U+0338
18071 % U+2290 SQUARE ORIGINAL OF; \sqsupset (latexsym, ...)
18072 \DeclareTextCommand{\textsqsupset}{\PU}{\U042\220}/* U+2290
18073 % \nsqsupset (txfonts/pxfonts)
18074 \DeclareTextCommand{\textnsqsupset}{\PU}{\U042\220\83\070}/* U+2290 U+0338
18075 % U+2291 SQUARE IMAGE OF OR EQUAL TO; \sqsubsetreq (LaTeX)
18076 \DeclareTextCommand{\textsqsubsetreq}{\PU}{\U042\221}/* U+2291
18077 % \nsqsubsetreq (txfonts/pxfonts)
18078 \DeclareTextCommand{\textnsqsubsetreq}{\PU}{\U042\221\83\070}/* U+2291 U+0338
18079 % U+2292 SQUARE ORIGINAL OF OR EQUAL TO; \sqsupsetreq (LaTeX)
18080 \DeclareTextCommand{\textsqsupsetreq}{\PU}{\U042\222}/* U+2292
18081 % \nsqsupsetreq (txfonts/pxfonts)
18082 \DeclareTextCommand{\textnsqsupsetreq}{\PU}{\U042\222\83\070}/* U+2292 U+0338
18083 % U+2293 SQUARE CAP; \sqcap (LaTeX)
18084 \DeclareTextCommand{\textsqcap}{\PU}{\U042\223}/* U+2293
18085 % U+2294 SQUARE CUP; \sqcup (LaTeX)
18086 \DeclareTextCommand{\textsqcup}{\PU}{\U042\224}/* U+2294
18087 % U+2295 CIRCLED PLUS; circleplus; \oplus (LaTeX)
18088 \DeclareTextCommand{\textoplus}{\PU}{\U042\225}/* U+2295
18089 /* \textoplus -> \varoplus (stmaryrd)
18090 % U+2296 CIRCLED MINUS; minuscircle; \ominus (LaTeX)
18091 \DeclareTextCommand{\textminus}{\PU}{\U042\226}/* U+2296
18092 /* \textminus -> \varminus (stmaryrd)
18093 % U+2297 CIRCLED TIMES; circlemultiply; \otimes (LaTeX)
18094 \DeclareTextCommand{\texttimes}{\PU}{\U042\227}/* U+2297
18095 /* \texttimes -> \varotimes (stmaryrd)
18096 % U+2298 CIRCLED DIVISION SLASH; \oslash (LaTeX)
18097 \DeclareTextCommand{\textslash}{\PU}{\U042\230}/* U+2298
18098 /* \textslash -> \varoslash (stmaryrd)
18099 % U+2299 CIRCLED DOT OPERATOR; circle(d?)ot; \odot (LaTeX)
18100 \DeclareTextCommand{\textdot}{\PU}{\U042\231}/* U+2299
18101 /* \textdot -> \varodot (stmaryrd)
18102 % U+229A CIRCLED RING OPERATOR; \circledcirc (AmS)
18103 \DeclareTextCommand{\textcircledcirc}{\PU}{\U042\232}/* U+229A
18104 /* \textcircledcirc -> \ocirc (mathabx)
18105 /* \textcircledcirc -> \varocircle (stmaryrd)
18106 % U+229B CIRCLED ASTERISK OPERATOR; \circledast (AmS)
18107 \DeclareTextCommand{\textcircledast}{\PU}{\U042\233}/* U+229B
18108 /* \textcircledast -> \varoast (stmaryrd)
18109 /* \textcircledast -> \oasterisk (mathabx)
18110 % U+229D CIRCLED DASH; \circleddash (AmS)
18111 \DeclareTextCommand{\textcircleddash}{\PU}{\U042\235}/* U+229D
18112 % U+229E SQUARED PLUS; \boxplus (AmS)
18113 \DeclareTextCommand{\textboxplus}{\PU}{\U042\236}/* U+229E
18114 % U+229F SQUARED MINUS; \boxminus (AmS)
18115 \DeclareTextCommand{\textboxminus}{\PU}{\U042\237}/* U+229F
18116 % U+22A0 SQUARED TIMES; \boxtimes (AmS)
18117 \DeclareTextCommand{\textboxtimes}{\PU}{\U042\240}/* U+22A0

```

```

18118 % U+22A1 SQUARED DOT OPERATOR; \boxdot (AmS)
18119 \DeclareTextCommand{\textboxdot}{\PU}{\9042\241}/* U+22A1
18120 % U+22A2 RIGHT TACK; \vdash (LaTeX)
18121 \DeclareTextCommand{\textvdash}{\PU}{\9042\242}/* U+22A2
18122 /* \textvdash -> \rightvdash (MnSymbol)
18123 % U+22A3 LEFT TACK; \tackleft; \dashv (LaTeX)
18124 \DeclareTextCommand{\textdashv}{\PU}{\9042\243}/* U+22A3
18125 /* \textdashv -> \leftvdash (MnSymbol)
18126 % \ndashv (mathabx)
18127 \DeclareTextCommand{\textndashv}{\PU}{\9042\243\83\070}/* U+22A3 U+0338
18128 /* \textndashv -> \nleftvdash (MnSymbol)
18129 % U+22A4 DOWN TACK (=top); \tackdown; \top (LaTeX)
18130 \DeclareTextCommand{\texttop}{\PU}{\9042\244}/* U+22A4
18131 /* \texttop -> \downvdash (MnSymbol)
18132 % \downvdash (MnSymbol)
18133 \DeclareTextCommand{\textndownvdash}{\PU}{\9042\244\83\070}/* U+22A4 U+0338
18134 % U+22A5 UP TACK (=base, bottom); \bot (LaTeX)
18135 \DeclareTextCommand{\textbot}{\PU}{\9042\245}/* U+22A5
18136 /* \textbot -> \upvdash (MnSymbol)
18137 % \upvdash (MnSymbol)
18138 \DeclareTextCommand{\textnupvdash}{\PU}{\9042\245\83\070}/* U+22A5 U+0338
18139 /* \textnupvdash -> \nperp (MnSymbol)
18140 % U+22A8 TRUE; \vDash (AmS)
18141 \DeclareTextCommand{\textvDash}{\PU}{\9042\250}/* U+22A8
18142 /* \textvDash -> \models (LaTeX)
18143 /* \textvDash -> \rightmodels (MnSymbol)
18144 % U+22A9 FORCES; \Vdash (AmS)
18145 \DeclareTextCommand{\textVdash}{\PU}{\9042\251}/* U+22A9
18146 /* \textVdash -> \rightVdash (MnSymbol)
18147 % U+22AA TRIPLE VERTICAL BAR RIGHT TURNSTILE; \Vvdash (AmS)
18148 \DeclareTextCommand{\textVvdash}{\PU}{\9042\252}/* U+22AA
18149 % \nVdash (mathabx)
18150 \DeclareTextCommand{\textnVdash}{\PU}{\9042\252\83\070}/* U+22AA U+0338
18151 % U+22AB DOUBLE VERTICAL BAR DOUBLE RIGHT TURNSTILE;
18152 % \VDash (mathabx)
18153 \DeclareTextCommand{\textVDash}{\PU}{\9042\253}/* U+22AB
18154 /* \textVDash -> \rightModels (MnSymbol)
18155 % U+22AC DOES NOT PROVE; \nvdash (AmS)
18156 \DeclareTextCommand{\textnvdash}{\PU}{\9042\254}/* U+22AC
18157 /* \textnvdash -> \nrightvdash (MnSymbol)
18158 % U+22AD NOT TRUE; \nvDash (AmS)
18159 \DeclareTextCommand{\textnvDash}{\PU}{\9042\255}/* U+22AD
18160 /* \textnvDash -> \nrightmodels (MnSymbol)
18161 /* \textnvDash -> \nmodels (MnSymbol)
18162 % U+22AE DOES NOT FORCE; \nVdash (txfonts/pxfonts)
18163 \DeclareTextCommand{\textnVdash}{\PU}{\9042\256}/* U+22AE
18164 /* \textnVdash -> \nrightVdash (MnSymbol)
18165 % U+22AF NEGATED DOUBLE VERTICAL BAR DOUBLE RIGHT TURN-
    STILE; \nVDash (AmS)
18166 \DeclareTextCommand{\textnVDash}{\PU}{\9042\257}/* U+22AF
18167 /* \textnVDash -> \nrightModels (MnSymbol)
18168 % U+22B2 NORMAL SUBGROUP OF; \lhd (latexsym, ...)
18169 \DeclareTextCommand{\textlhd}{\PU}{\9042\262}/* U+22B2
18170 /* \textlhd -> \lessclosed (MnSymbol)

```

```

18171 % U+22B3 CONTAINS AS NORMAL SUBGROUP; \rhd (latexsym, ...)
18172 \DeclareTextCommand{\textrhd}{\PU}{\9042\263} %* U+22B3
18173 %* \textrhd -> \gtrclosed (MnSymbol)
18174 % U+22B4 NORMAL SUBGROUP OF OR EQUAL TO; \unlhd (latexsym, ...)
18175 \DeclareTextCommand{\textunlhd}{\PU}{\9042\264} %* U+22B4
18176 %* \textunlhd -> \leqclosed (MnSymbol)
18177 %* \textunlhd -> \trianglelefteq (MnSymbol)
18178 % U+22B5 CONTAINS AS NORMAL SUBGROUP OR EQUAL TO; \unrhd (la-
    texsym, ...)
18179 \DeclareTextCommand{\textunrhd}{\PU}{\9042\265} %* U+22B5
18180 %* \textunrhd -> \geqclosed (MnSymbol)
18181 %* \textunrhd -> \trianglerighteq (MnSymbol)
18182 % U+22B6 ORIGINAL OF; \multimapdotbothA (txfonts/pxfonts)
18183 \DeclareTextCommand{\textmultimapdotbothA}{\PU}{\9042\266} %* U+22B6
18184 % U+22B7 IMAGE OF; \multimapdotbothB (txfonts/pxfonts)
18185 \DeclareTextCommand{\textmultimapdotbothB}{\PU}{\9042\267} %* U+22B7
18186 % U+22B8 MULTIMAP; \multimap (AmS, txfonts/pxfonts)
18187 \DeclareTextCommand{\textmultimap}{\PU}{\9042\270} %* U+22B8
18188 % U+22BB XOR; \veebar (AmS)
18189 \DeclareTextCommand{\textveebar}{\PU}{\9042\273} %* U+22BB
18190 % U+22BC NAND; \barwedge (mathabx)
18191 \DeclareTextCommand{\textbarwedge}{\PU}{\9042\274} %* U+22BC
18192 % U+22C6 STAR OPERATOR; \star (LaTeX)
18193 \DeclareTextCommand{\textstar}{\PU}{\9042\306} %* U+22C6
18194 % U+22C7 DIVISION TIMES; \divideontimes (AmS)
18195 \DeclareTextCommand{\textdivideontimes}{\PU}{\9042\307} %* U+22C7
18196 % U+22C8 BOWTIE; \bowtie (LaTeX)
18197 \DeclareTextCommand{\textbowtie}{\PU}{\9042\310} %* U+22C8
18198 %* \textbowtie -> \Bowtie (wasysym)
18199 % U+22C9 LEFT NORMAL FACTOR SEMIDIRECT PRODUCT; \ltimes (AmS)
18200 \DeclareTextCommand{\textltimes}{\PU}{\9042\311} %* U+22C9
18201 % U+22CA RIGHT NORMAL FACTOR SEMIDIRECT PRODUCT;
18202 % \rtimes (AmS)
18203 \DeclareTextCommand{\textrtimes}{\PU}{\9042\312} %* U+22CA
18204 % U+22CB LEFT SEMIDIRECT PRODUCT; \leftthreetimes (AmS)
18205 \DeclareTextCommand{\textleftthreetimes}{\PU}{\9042\313} %* U+22CB
18206 % U+22CC RIGHT SEMIDIRECT PRODUCT; \rightthreetimes (AmS)
18207 \DeclareTextCommand{\textrightthreetimes}{\PU}{\9042\314} %* U+22CC
18208 % U+22CD REVERSED TILDE EQUALS; \backsimeq (AmS)
18209 \DeclareTextCommand{\textbacksimeq}{\PU}{\9042\315} %* U+22CD
18210 % \nbacksimeq (txfonts/pxfonts)
18211 \DeclareTextCommand{\texttnbacksimeq}{\PU}{\9042\315\83\070} %* U+22CD U+0338
18212 % U+22CE CURLY LOGICAL OR; curlyor; \curlyvee (AmS)
18213 \DeclareTextCommand{\textcurlyvee}{\PU}{\9042\316} %* U+22CE
18214 %* \textcurlyvee -> \varcurlyvee (stmaryrd)
18215 % U+22CF CURLY LOGICAL AND; curlyand; \curlywedge (AmS)
18216 \DeclareTextCommand{\textcurlywedge}{\PU}{\9042\317} %* U+22CF
18217 %* \textcurlywedge -> \varcurlywedge (stmaryrd)
18218 % U+22D0 DOUBLE SUBSET; \Subset (AmS)
18219 \DeclareTextCommand{\textSubset}{\PU}{\9042\320} %* U+22D0
18220 % \nSubset (txfonts/pxfonts)
18221 \DeclareTextCommand{\texttnSubset}{\PU}{\9042\320\83\070} %* U+22D0 U+0338
18222 % U+22D1 DOUBLE SUPERSET; \Supset (AmS)
18223 \DeclareTextCommand{\textSupset}{\PU}{\9042\321} %* U+22D1

```

```

18224 % \nSupset (txfonts/pxfonts)
18225 \DeclareTextCommand{\textnSupset}{PU}{\9042\321\83\070}/* U+22D1 U+0338
18226 % U+22D2 DOUBLE INTERSECTION; \Cap (AmS)
18227 \DeclareTextCommand{\textCap}{PU}{\9042\322}/* U+22D2
18228 /* \textCap -> \doublecap (mathabx)
18229 % U+22D3 DOUBLE UNION; \Cup (AmS)
18230 \DeclareTextCommand{\textCup}{PU}{\9042\323}/* U+22D3
18231 /* \textCup -> \doublecup (mathabx)
18232 % U+22D4 PITCHFORK; \pitchfork (mathabx)
18233 \DeclareTextCommand{\textpitchfork}{PU}{\9042\324}/* U+22D4
18234 % U+22D6 LESS-THAN WITH DOT; \lessdot (AmS)
18235 \DeclareTextCommand{\textlessdot}{PU}{\9042\326}/* U+22D6
18236 % U+22D7 GREATER-THAN WITH DOT; \gtrdot (AmS)
18237 \DeclareTextCommand{\textgtrdot}{PU}{\9042\327}/* U+22D7
18238 % U+22D8 VERY MUCH LESS-THAN; \lll (AmS)
18239 \DeclareTextCommand{\textlll}{PU}{\9042\330}/* U+22D8
18240 % U+22D9 VERY MUCH GREATER-THAN; \ggg (AmS)
18241 \DeclareTextCommand{\textggg}{PU}{\9042\331}/* U+22D9
18242 % U+22DA LESS-THAN EQUAL TO OR GREATER-THAN; lessequalorgreater;
18243 % \lesseqgtr (AmS)
18244 \DeclareTextCommand{\textlesseqgtr}{PU}{\9042\332}/* U+22DA
18245 % U+22DB GREATER-THAN EQUAL TO OR LESS-THAN; greaterequalorless;
18246 % \gtreqless (AmS)
18247 \DeclareTextCommand{\textgtreqless}{PU}{\9042\333}/* U+22DB
18248 % U+22DE EQUAL TO OR PRECEDES; \curlyeqprec (MnSymbol)
18249 \DeclareTextCommand{\textcurlyeqprec}{PU}{\9042\336}/* U+22DE
18250 % \ncurlyeqprec (mathabx)
18251 \DeclareTextCommand{\textncurlyeqprec}{PU}{\9042\336\83\070}/* U+22DE U+0338
18252 % U+22DF EQUAL TO OR SUCCEEDS; \curlyeqsucc (MnSymbol)
18253 \DeclareTextCommand{\textcurlyeqsucc}{PU}{\9042\337}/* U+22DF
18254 % \ncurlyeqsucc (mathabx)
18255 \DeclareTextCommand{\textncurlyeqsucc}{PU}{\9042\337\83\070}/* U+22DF U+0338
18256 % U+22E0 DOES NOT PRECEDE OR EQUAL; \npreccurlyeq (txfonts/pxfonts)
18257 \DeclareTextCommand{\textnpreccurlyeq}{PU}{\9042\340}/* U+22E0
18258 % U+22E1 DOES NOT SUCCEED OR EQUAL; \nsucccurlyeq (txfonts/pxfonts)
18259 \DeclareTextCommand{\textnsucccurlyeq}{PU}{\9042\341}/* U+22E1
18260 % U+22E2 NOT SQUARE IMAGE OF OR EQUAL TO; \nsqsubseteq (tx-
    fonts/pxfonts)
18261 \DeclareTextCommand{\textnqsubseteq}{PU}{\9042\342}/* U+22E2
18262 % U+22E3 NOT SQUARE ORIGINAL OF OR EQUAL TO; \nsqsupseteq (tx-
    fonts/pxfonts)
18263 \DeclareTextCommand{\textnqsupseteq}{PU}{\9042\343}/* U+22E3
18264 % U+22E4 SQUARE IMAGE OF OR NOT EQUAL TO; \sqsubsetneq (mathabx)
18265 \DeclareTextCommand{\textsqsubsetneq}{PU}{\9042\344}/* U+22E4
18266 /* \textsqsubsetneq -> \varsqsubsetneq (mathabx)
18267 % U+22E5 SQUARE ORIGINAL OF OR NOT EQUAL TO; \sqsupsetneq (math-
    abx)
18268 \DeclareTextCommand{\textsqsupsetneq}{PU}{\9042\345}/* U+22E5
18269 /* \textsqsupsetneq -> \varsqsupsetneq (mathabx)
18270 % U+22E6 LESS-THAN BUT NOT EQUIVALENT TO; \lnsim (AmS)
18271 \DeclareTextCommand{\textlnsim}{PU}{\9042\346}/* U+22E6
18272 % U+22E7 GREATER-THAN BUT NOT EQUIVALENT TO; \gnsim (AmS)
18273 \DeclareTextCommand{\textgnsim}{PU}{\9042\347}/* U+22E7
18274 % U+22E8 PRECEDES BUT NOT EQUIVALENT TO; \precsim (AmS)

```

```

18275 \DeclareTextCommand{\textprecnsim}{\PU}{\9042\350}/* U+22E8
18276 % U+22E9 SUCCEEDS BUT NOT EQUIVALENT TO; \succnsim (AmS)
18277 \DeclareTextCommand{\textsuccnsim}{\PU}{\9042\351}/* U+22E9
18278 % U+22EA NOT NORMAL SUBGROUP OF; \ntriangleleft (AmS)
18279 \DeclareTextCommand{\textntriangleleft}{\PU}{\9042\352}/* U+22EA
18280 /* \textntriangleleft -> \nlessclosed (MnSymbol)
18281 % U+22EB DOES NOT CONTAIN AS NORMAL SUBGROUP; \ntriangleright (AmS)
18282 \DeclareTextCommand{\textntriangleright}{\PU}{\9042\353}/* U+22EB
18283 /* \textntriangleright -> \ngtrclosed (MnSymbol)
18284 % U+22EC NOT NORMAL SUBGROUP OF OR EQUAL TO;
18285 % \ntrianglelefteq (AmS)
18286 \DeclareTextCommand{\textntrianglelefteq}{\PU}{\9042\354}/* U+22EC
18287 % U+22ED DOES NOT CONTAIN AS NORMAL SUBGROUP OR EQUAL;
18288 % \ntrianglerighteq (AmS)
18289 \DeclareTextCommand{\textntrianglerighteq}{\PU}{\9042\355}/* U+22ED
18290 /* \textntrianglerighteq -> \textngeqclosed
18291 % U+22EE VERTICAL ELLIPSIS; ellipsisvertical; \vdots (LaTeX)
18292 \DeclareTextCommand{\textvdots}{\PU}{\9042\356}/* U+22EE
18293 % U+22EF MIDLINE HORIZONTAL ELLIPSIS; \cdots (LaTeX)
18294 \DeclareTextCommand{\textcdots}{\PU}{\9042\357}/* U+22EF
18295 % U+22F0 UP RIGHT DIAGONAL ELLIPSIS; \udots (MnSymbol)
18296 \DeclareTextCommand{\textudots}{\PU}{\9042\360}/* U+22F0
18297 % U+22F1 DOWN RIGHT DIAGONAL ELLIPSIS; \ddots (LaTeX)
18298 \DeclareTextCommand{\textddots}{\PU}{\9042\361}/* U+22F1
18299 % U+22F6 ELEMENT OF WITH OVERBAR; \barin (mathabx)
18300 \DeclareTextCommand{\textbarin}{\PU}{\9042\366}/* U+22F6

```

46.2.23 Miscellaneous Technical: U+2300 to U+23FF

```

18301 % U+2300 DIAMETER SIGN; \diameter (mathabx,wasysym)
18302 \DeclareTextCommand{\textdiameter}{\PU}{\9043\000}/* U+2300
18303 % U+2310 REVERSED NOT SIGN; \backneg (MnSymbol)
18304 \DeclareTextCommand{\textbackneg}{\PU}{\9043\020}/* U+2310
18305 % U+2311 SQUARE LOZENGE; \wasylozenge (wasysym)
18306 \DeclareTextCommand{\textwasylozenge}{\PU}{\9043\021}/* U+2311
18307 % U+2319 TURNED NOT SIGN; \invbackneg (MnSymbol)
18308 \DeclareTextCommand{\textinvbackneg}{\PU}{\9043\031}/* U+2319
18309 % U+231A WATCH; \clock (wasysym)
18310 \DeclareTextCommand{\textclock}{\PU}{\9043\032}/* U+231A
18311 /* \textclock -> \Clocklogo (marvosym)
18312 /* \textclock -> \ClockLogo (marvosym)
18313 % U+231C TOP LEFT CORNER; \ulcorner (AmS)
18314 \DeclareTextCommand{\textulcorner}{\PU}{\9043\034}/* U+231C
18315 % U+231D TOP RIGHT CORNER; \urcorner (AmS)
18316 \DeclareTextCommand{\texturcorner}{\PU}{\9043\035}/* U+231D
18317 % U+231E BOTTOM LEFT CORNER; \llcorner (AmS)
18318 \DeclareTextCommand{\textllcorner}{\PU}{\9043\036}/* U+231E
18319 % U+231F BOTTOM RIGHT CORNER; \lrcorner (AmS)
18320 \DeclareTextCommand{\textlrcorner}{\PU}{\9043\037}/* U+231F
18321 % U+2322 FROWN; \frown (LaTeX)
18322 \DeclareTextCommand{\textfrown}{\PU}{\9043\042}/* U+2322
18323 % U+2323 SMILE; \smile (LaTeX)
18324 \DeclareTextCommand{\textsmile}{\PU}{\9043\043}/* U+2323
18325 % U+2328 KEYBOARD; \Keyboard (marvosym)

```

```

18326 \DeclareTextCommand{\textKeyboard}{\PU}{\U9043\050}/* U+2328
18327 % U+2329 LEFT-POINTING ANGLE BRACKET; angleleft; \langle (LaTeX)
18328 \DeclareTextCommand{\textlangle}{\PU}{\U9043\051}/* U+2329
18329 % U+232A RIGHT-POINTING ANGLE BRACKET; angleright; \rangle (LaTeX)
18330 \DeclareTextCommand{\textrangle}{\PU}{\U9043\052}/* U+232A
18331 % U+2339 APL FUNCTIONAL SYMBOL QUAD DIVIDE; \APLinv (wasysym)
18332 \DeclareTextCommand{\textAPLinv}{\PU}{\U9043\071}/* U+2339
18333 % U+233C APL FUNCTIONAL SYMBOL QUAD CIRCLE; \Tumbler (mar-
    vosym)
18334 \DeclareTextCommand{\textTumbler}{\PU}{\U9043\074}/* U+233C
18335 % U+233D APL FUNCTIONAL SYMBOL CIRCLE STILE; \baro (stmaryrd)
18336 \DeclareTextCommand{\textstmaryrdbaro}{\PU}{\U9043\075}/* U+233D
18337 /* \textstmaryrdbaro -> \baro (stmaryrd)
18338 % U+233F APL FUNCTIONAL SYMBOL SLASH BAR; \notslash (wasysym)
18339 \DeclareTextCommand{\textnotslash}{\PU}{\U9043\077}/* U+233F
18340 % U+2340 APL FUNCTIONAL SYMBOL BACKSLASH BAR;
18341 % \notbackslash (wasysym)
18342 \DeclareTextCommand{\textnotbackslash}{\PU}{\U9043\100}/* U+2340
18343 % U+2342 APL FUNCTIONAL SYMBOL QUAD BACKSLASH; \boxback-
    slash (mathabx)
18344 \DeclareTextCommand{\textboxbackslash}{\PU}{\U9043\102}/* U+2342
18345 % U+2347 APL FUNCTIONAL SYMBOL QUAD LEFTWARDS ARROW;
18346 % \APLleftarrowbox (wasysym)
18347 \DeclareTextCommand{\textAPLleftarrowbox}{\PU}{\U9043\107}/* U+2347
18348 % U+2348 APL FUNCTIONAL SYMBOL QUAD RIGHTWARDS ARROW;
18349 % \APLrightarrowbox (wasysym)
18350 \DeclareTextCommand{\textAPLrightarrowbox}{\PU}{\U9043\110}/* U+2348
18351 % U+2350 APL FUNCTIONAL SYMBOL QUAD UPWARDS ARROW; \APLu-
    parrowbox (wasysym)
18352 \DeclareTextCommand{\textAPLuparrowbox}{\PU}{\U9043\120}/* U+2350
18353 % U+2357 APL FUNCTIONAL SYMBOL QUAD DOWNWARDS ARROW;
18354 % \APLdownarrowbox (wasysym)
18355 \DeclareTextCommand{\textAPLdownarrowbox}{\PU}{\U9043\127}/* U+2357
18356 % U+235E APL FUNCTIONAL SYMBOL QUOTE QUAD;
18357 % \APLinput (wasysym)
18358 \DeclareTextCommand{\textAPLinput}{\PU}{\U9043\136}/* U+235E
18359 % U+2370 APL FUNCTIONAL SYMBOL QUAD QUESTION; \Request (china2e)
18360 \DeclareTextCommand{\textRequest}{\PU}{\U9043\160}/* U+2370
18361 % U+2393 DIRECT CURRENT SYMBOL FORM TWO; \Beam (marvosym)
18362 \DeclareTextCommand{\textBeam}{\PU}{\U9043\223}/* U+2393
18363 % U+2394 SOFTWARE-FUNCTION SYMBOL; \hexagon (wasysym)
18364 \DeclareTextCommand{\texthexagon}{\PU}{\U9043\224}/* U+2394
18365 % U+2395 APL FUNCTIONAL SYMBOL QUAD; \APLbox (wasysym)
18366 \DeclareTextCommand{\textAPLbox}{\PU}{\U9043\225}/* U+2395
18367 % U+23ED BLACK RIGHT-POINTING DOUBLE TRIANGLE WITH VERTI-
    CAL BAR;
18368 % \ForwardToIndex (marvosym)
18369 \DeclareTextCommand{\textForwardToIndex}{\PU}{\U9043\355}/* U+23ED
18370 % U+23EE BLACK LEFT-POINTING DOUBLE TRIANGLE WITH VERTI-
    CAL BAR;
18371 % \RewindToIndex (marvosym)
18372 \DeclareTextCommand{\textRewindToIndex}{\PU}{\U9043\356}/* U+23EE

```

46.2.24 Control Pictures: U+2400 to U+243F

```
18373 % U+2422 BLANK SYMBOL
18374 \DeclareTextCommand{\textblank}{PU}{\9044\042}% U+2422
18375 % U+2423 OPEN BOX; blank
18376 \DeclareTextCommand{\textvisiblespace}{PU}{\9044\043}% U+2423
```

46.2.25 Optical Character Recognition: U+2440 to U+245F

```
18377 % U+244A OCR DOUBLE BACKSLASH; \bbslash (stmaryrd)
18378 \DeclareTextCommand{\textbbslash}{PU}{\9044\112}/* U+244A
18379 /* \textbbslash -> \varparallelinv (txfonts/pxfonts)
```

46.2.26 Enclosed Alphanumerics: U+2460 to U+24FF

```
18380 % U+2460 CIRCLED DIGIT ONE; onecircle
18381 \DeclareTextCompositeCommand{\textcircled}{PU}{1}{\9044\140}% U+2460
18382 % U+2461 CIRCLED DIGIT TWO; twocircle
18383 \DeclareTextCompositeCommand{\textcircled}{PU}{2}{\9044\141}% U+2461
18384 % U+2462 CIRCLED DIGIT THREE; threecircle
18385 \DeclareTextCompositeCommand{\textcircled}{PU}{3}{\9044\142}% U+2462
18386 % U+2463 CIRCLED DIGIT FOUR; fourcircle
18387 \DeclareTextCompositeCommand{\textcircled}{PU}{4}{\9044\143}% U+2463
18388 % U+2464 CIRCLED DIGIT FIVE; fivecircle
18389 \DeclareTextCompositeCommand{\textcircled}{PU}{5}{\9044\144}% U+2464
18390 % U+2465 CIRCLED DIGIT SIX; sixcircle
18391 \DeclareTextCompositeCommand{\textcircled}{PU}{6}{\9044\145}% U+2465
18392 % U+2466 CIRCLED DIGIT SEVEN; sevencircle
18393 \DeclareTextCompositeCommand{\textcircled}{PU}{7}{\9044\146}% U+2466
18394 % U+2467 CIRCLED DIGIT EIGHT; eightcircle
18395 \DeclareTextCompositeCommand{\textcircled}{PU}{8}{\9044\147}% U+2467
18396 % U+2468 CIRCLED DIGIT NINE; ninecircle
18397 \DeclareTextCompositeCommand{\textcircled}{PU}{9}{\9044\150}% U+2468
18398 % U+2469 CIRCLED NUMBER TEN; tencircle
18399 \DeclareTextCompositeCommand{\textcircled}{PU}{10}{\9044\151}% U+2469
18400 % U+246A CIRCLED NUMBER ELEVEN; elevencircle
18401 \DeclareTextCompositeCommand{\textcircled}{PU}{11}{\9044\152}% U+246A
18402 % U+246B CIRCLED NUMBER TWELVE; twelvecircle
18403 \DeclareTextCompositeCommand{\textcircled}{PU}{12}{\9044\153}% U+246B
18404 % U+246C CIRCLED NUMBER THIRTEEN; thirteencircle
18405 \DeclareTextCompositeCommand{\textcircled}{PU}{13}{\9044\154}% U+246C
18406 % U+246D CIRCLED NUMBER FOURTEEN; fourteencircle
18407 \DeclareTextCompositeCommand{\textcircled}{PU}{14}{\9044\155}% U+246D
18408 % U+246E CIRCLED NUMBER FIFTEEN; fifteencircle
18409 \DeclareTextCompositeCommand{\textcircled}{PU}{15}{\9044\156}% U+246E
18410 % U+246F CIRCLED NUMBER SIXTEEN; sixteencircle
18411 \DeclareTextCompositeCommand{\textcircled}{PU}{16}{\9044\157}% U+246F
18412 % U+2470 CIRCLED NUMBER SEVENTEEN; seventeencircle
18413 \DeclareTextCompositeCommand{\textcircled}{PU}{17}{\9044\160}% U+2470
18414 % U+2471 CIRCLED NUMBER EIGHTEEN; eighteencircle
18415 \DeclareTextCompositeCommand{\textcircled}{PU}{18}{\9044\161}% U+2471
18416 % U+2472 CIRCLED NUMBER NINETEEN; nineteencircle
18417 \DeclareTextCompositeCommand{\textcircled}{PU}{19}{\9044\162}% U+2472
18418 % U+2473 CIRCLED NUMBER TWENTY; twentycircle
18419 \DeclareTextCompositeCommand{\textcircled}{PU}{20}{\9044\163}% U+2473
18420 % U+24B6 CIRCLED LATIN CAPITAL LETTER A; Acircle
18421 \DeclareTextCompositeCommand{\textcircled}{PU}{A}{\9044\266}% U+24B6
18422 % \CircledA (marvosym)
```

```

18423 \DeclareTextCommand{\textCircledA}{PU}{\9044\266}/* U+24B6
18424 %* \textCircledA -> \CleaningA
18425 % U+24B7 CIRCLED LATIN CAPITAL LETTER B; Bcircle
18426 \DeclareTextCompositeCommand{\textcircled}{PU}{B}{\9044\267}% U+24B7
18427 % U+24B8 CIRCLED LATIN CAPITAL LETTER C; Ccircle
18428 \DeclareTextCompositeCommand{\textcircled}{PU}{C}{\9044\270}% U+24B8
18429 % U+24B9 CIRCLED LATIN CAPITAL LETTER D; Dcircle
18430 \DeclareTextCompositeCommand{\textcircled}{PU}{D}{\9044\271}% U+24B9
18431 % U+24BA CIRCLED LATIN CAPITAL LETTER E; Ecircle
18432 \DeclareTextCompositeCommand{\textcircled}{PU}{E}{\9044\272}% U+24BA
18433 % U+24BB CIRCLED LATIN CAPITAL LETTER F; Fcircle
18434 \DeclareTextCompositeCommand{\textcircled}{PU}{F}{\9044\273}% U+24BB
18435 % \CleaningF (marvosym)
18436 \DeclareTextCommand{\textCleaningF}{PU}{\9044\273}/* U+24BB
18437 % \CleaningFF (marvosym)
18438 \DeclareTextCommand{\textCleaningFF}{PU}{\9044\273\83\062}/* U+24BB U+0332
18439 % U+24BC CIRCLED LATIN CAPITAL LETTER G; Gcircle
18440 \DeclareTextCompositeCommand{\textcircled}{PU}{G}{\9044\274}% U+24BC
18441 % U+24BD CIRCLED LATIN CAPITAL LETTER H; Hcircle
18442 \DeclareTextCompositeCommand{\textcircled}{PU}{H}{\9044\275}% U+24BD
18443 % U+24BE CIRCLED LATIN CAPITAL LETTER I; Icircle
18444 \DeclareTextCompositeCommand{\textcircled}{PU}{I}{\9044\276}% U+24BE
18445 % U+24BF CIRCLED LATIN CAPITAL LETTER J; Jcircle
18446 \DeclareTextCompositeCommand{\textcircled}{PU}{J}{\9044\277}% U+24BF
18447 % U+24C0 CIRCLED LATIN CAPITAL LETTER K; Kcircle
18448 \DeclareTextCompositeCommand{\textcircled}{PU}{K}{\9044\300}% U+24C0
18449 % U+24C1 CIRCLED LATIN CAPITAL LETTER L; Lcircle
18450 \DeclareTextCompositeCommand{\textcircled}{PU}{L}{\9044\301}% U+24C1
18451 % U+24C2 CIRCLED LATIN CAPITAL LETTER M; Mcircle
18452 \DeclareTextCompositeCommand{\textcircled}{PU}{M}{\9044\302}% U+24C2
18453 % U+24C3 CIRCLED LATIN CAPITAL LETTER N; Ncircle
18454 \DeclareTextCompositeCommand{\textcircled}{PU}{N}{\9044\303}% U+24C3
18455 % U+24C4 CIRCLED LATIN CAPITAL LETTER O; Ocircle
18456 \DeclareTextCompositeCommand{\textcircled}{PU}{O}{\9044\304}% U+24C4
18457 % U+24C5 CIRCLED LATIN CAPITAL LETTER P; Pcircle
18458 \DeclareTextCompositeCommand{\textcircled}{PU}{P}{\9044\305}% U+24C5
18459 % \CleaningP (marvosym)
18460 \DeclareTextCommand{\textCleaningP}{PU}{\9044\305}/* U+24C5
18461 % \CleaningPP (marvosym)
18462 \DeclareTextCommand{\textCleaningPP}{PU}{\9044\305\83\062}/* U+24C5 U+0332
18463 % U+24C6 CIRCLED LATIN CAPITAL LETTER Q; Qcircle
18464 \DeclareTextCompositeCommand{\textcircled}{PU}{Q}{\9044\306}% U+24C6
18465 % U+24C7 CIRCLED LATIN CAPITAL LETTER R; Rcircle
18466 \DeclareTextCompositeCommand{\textcircled}{PU}{R}{\9044\307}% U+24C7
18467 % U+24C8 CIRCLED LATIN CAPITAL LETTER S; Scircle
18468 \DeclareTextCompositeCommand{\textcircled}{PU}{S}{\9044\310}% U+24C8
18469 % U+24C9 CIRCLED LATIN CAPITAL LETTER T; Tcircle
18470 \DeclareTextCompositeCommand{\textcircled}{PU}{T}{\9044\311}% U+24C9
18471 % U+24CA CIRCLED LATIN CAPITAL LETTER U; Ucircle
18472 \DeclareTextCompositeCommand{\textcircled}{PU}{U}{\9044\312}% U+24CA
18473 % U+24CB CIRCLED LATIN CAPITAL LETTER V; Vcircle
18474 \DeclareTextCompositeCommand{\textcircled}{PU}{V}{\9044\313}% U+24CB
18475 % U+24CC CIRCLED LATIN CAPITAL LETTER W; Wcircle
18476 \DeclareTextCompositeCommand{\textcircled}{PU}{W}{\9044\314}% U+24CC

```

```

18477 % U+24CD CIRCLED LATIN CAPITAL LETTER X; Xcircle
18478 \DeclareTextCompositeCommand{\textcircled}{PU}{X}{\9044\315}% U+24CD
18479 % U+24CE CIRCLED LATIN CAPITAL LETTER Y; Ycircle
18480 \DeclareTextCompositeCommand{\textcircled}{PU}{Y}{\9044\316}% U+24CE
18481 % U+24CF CIRCLED LATIN CAPITAL LETTER Z; Zcircle
18482 \DeclareTextCompositeCommand{\textcircled}{PU}{Z}{\9044\317}% U+24CF
18483 % U+24D0 CIRCLED LATIN SMALL LETTER A; acircle
18484 \DeclareTextCompositeCommand{\textcircled}{PU}{a}{\9044\320}% U+24D0
18485 % U+24D1 CIRCLED LATIN SMALL LETTER B; bcircle
18486 \DeclareTextCompositeCommand{\textcircled}{PU}{b}{\9044\321}% U+24D1
18487 % U+24D2 CIRCLED LATIN SMALL LETTER C; ccircle
18488 \DeclareTextCompositeCommand{\textcircled}{PU}{c}{\9044\322}% U+24D2
18489 % U+24D3 CIRCLED LATIN SMALL LETTER D; dcircle
18490 \DeclareTextCompositeCommand{\textcircled}{PU}{d}{\9044\323}% U+24D3
18491 % U+24D4 CIRCLED LATIN SMALL LETTER E; ecircle
18492 \DeclareTextCompositeCommand{\textcircled}{PU}{e}{\9044\324}% U+24D4
18493 % U+24D5 CIRCLED LATIN SMALL LETTER F; fcircle
18494 \DeclareTextCompositeCommand{\textcircled}{PU}{f}{\9044\325}% U+24D5
18495 % U+24D6 CIRCLED LATIN SMALL LETTER G; gcircle
18496 \DeclareTextCompositeCommand{\textcircled}{PU}{g}{\9044\326}% U+24D6
18497 % U+24D7 CIRCLED LATIN SMALL LETTER H; hcircle
18498 \DeclareTextCompositeCommand{\textcircled}{PU}{h}{\9044\327}% U+24D7
18499 % U+24D8 CIRCLED LATIN SMALL LETTER I; icircle
18500 \DeclareTextCompositeCommand{\textcircled}{PU}{i}{\9044\330}% U+24D8
18501 % U+24D9 CIRCLED LATIN SMALL LETTER J; jcircle
18502 \DeclareTextCompositeCommand{\textcircled}{PU}{j}{\9044\331}% U+24D9
18503 % U+24DA CIRCLED LATIN SMALL LETTER K; kcircle
18504 \DeclareTextCompositeCommand{\textcircled}{PU}{k}{\9044\332}% U+24DA
18505 % U+24DB CIRCLED LATIN SMALL LETTER L; lcircle
18506 \DeclareTextCompositeCommand{\textcircled}{PU}{l}{\9044\333}% U+24DB
18507 % U+24DC CIRCLED LATIN SMALL LETTER M; mcircle
18508 \DeclareTextCompositeCommand{\textcircled}{PU}{m}{\9044\334}% U+24DC
18509 % U+24DD CIRCLED LATIN SMALL LETTER N; ncircle
18510 \DeclareTextCompositeCommand{\textcircled}{PU}{n}{\9044\335}% U+24DD
18511 % U+24DE CIRCLED LATIN SMALL LETTER O; ocircle
18512 \DeclareTextCompositeCommand{\textcircled}{PU}{o}{\9044\336}% U+24DE
18513 % U+24DF CIRCLED LATIN SMALL LETTER P; pcircle
18514 \DeclareTextCompositeCommand{\textcircled}{PU}{p}{\9044\337}% U+24DF
18515 % U+24E0 CIRCLED LATIN SMALL LETTER Q; qcircle
18516 \DeclareTextCompositeCommand{\textcircled}{PU}{q}{\9044\340}% U+24E0
18517 % U+24E1 CIRCLED LATIN SMALL LETTER R; rcircle
18518 \DeclareTextCompositeCommand{\textcircled}{PU}{r}{\9044\341}% U+24E1
18519 % U+24E2 CIRCLED LATIN SMALL LETTER S; scircle
18520 \DeclareTextCompositeCommand{\textcircled}{PU}{s}{\9044\342}% U+24E2
18521 % U+24E3 CIRCLED LATIN SMALL LETTER T; tcircle
18522 \DeclareTextCompositeCommand{\textcircled}{PU}{t}{\9044\343}% U+24E3
18523 % U+24E4 CIRCLED LATIN SMALL LETTER U; ucircle
18524 \DeclareTextCompositeCommand{\textcircled}{PU}{u}{\9044\344}% U+24E4
18525 % U+24E5 CIRCLED LATIN SMALL LETTER V; vcircle
18526 \DeclareTextCompositeCommand{\textcircled}{PU}{v}{\9044\345}% U+24E5
18527 % U+24E6 CIRCLED LATIN SMALL LETTER W; wcircle
18528 \DeclareTextCompositeCommand{\textcircled}{PU}{w}{\9044\346}% U+24E6
18529 % U+24E7 CIRCLED LATIN SMALL LETTER X; xcircle
18530 \DeclareTextCompositeCommand{\textcircled}{PU}{x}{\9044\347}% U+24E7

```

```

18531 % U+24E8 CIRCLED LATIN SMALL LETTER Y; ycircle
18532 \DeclareTextCompositeCommand{\textcircled}{PU}{y}{\9044\350}% U+24E8
18533 % U+24E9 CIRCLED LATIN SMALL LETTER Z; zcircle
18534 \DeclareTextCompositeCommand{\textcircled}{PU}{z}{\9044\351}% U+24E9
18535 % U+24EA CIRCLED DIGIT ZERO
18536 \DeclareTextCompositeCommand{\textcircled}{PU}{0}{\9044\352}% U+24EA

```

46.2.27 Box Drawing: U+2500 to 257F

```

18537 % U+2504 BOX DRAWINGS LIGHT TRIPLE DASH HORIZONTAL; \Cutting-
Line (marvosym)
18538 \DeclareTextCommand{\textCuttingLine}{PU}{\9045\004}/* U+2504
18539 /* \textCuttingLine -> \Kutline (marvosym)
18540 /* \textCuttingLine -> \CutLine (marvosym)
18541 /* \textCuttingLine -> \Cutline (marvosym)

```

46.2.28 Geometric Shapes: U+25A0 to U+25FF

```

18542 % U+25B2 BLACK UP-POINTING TRIANGLE; \UParrow (wasysym)
18543 \DeclareTextCommand{\textUParrow}{PU}{\9045\262}/* U+25B2
18544 /* \textUParrow -> \MoveUp (marvosym)
18545 % U+25B3 WHITE UP-POINTING TRIANGLE; whiteuppointingtriangle;
18546 % \bigtriangleup (LaTeX)
18547 \DeclareTextCommand{\textbigtriangleup}{PU}{\9045\263}/* U+25B3
18548 /* \textbigtriangleup -> \APLup (wasysym)
18549 /* \textbigtriangleup -> \Bleech (marvosym)
18550 % U+25B6 BLACK RIGHT-POINTING TRIANGLE; \Forward (marvosym)
18551 \DeclareTextCommand{\textForward}{PU}{\9045\266}/* U+25B6
18552 % U+25B7 WHITE RIGHT-POINTING TRIANGLE (= z notation range restric-
tion);
18553 % whiterightpointingtriangle; \triangleright (LaTeX)
18554 \DeclareTextCommand{\texttriangleright}{PU}{\9045\267}/* U+25B7
18555 % U+25BA BLACK RIGHT-POINTING POINTER; \RHD (wasysym)
18556 \DeclareTextCommand{\textRHD}{PU}{\9045\272}/* U+25BA
18557 % U+25BC BLACK DOWN-POINTING TRIANGLE; \DOWNarrow (wasysym)
18558 \DeclareTextCommand{\textDOWNarrow}{PU}{\9045\274}/* U+25BC
18559 /* \textDOWNarrow -> \MoveDown (marvosym)
18560 % U+25BD WHITE DOWN-POINTING TRIANGLE; whitedownpointingtri-
angle;
18561 % \bigtriangledown (LaTeX)
18562 \DeclareTextCommand{\textbigtriangledown}{PU}{\9045\275}/* U+25BD
18563 /* \textbigtriangledown -> \APLdown (wasysym)
18564 % U+25C0 BLACK LEFT-POINTING TRIANGLE; \Rewind (marvosym)
18565 \DeclareTextCommand{\textRewind}{PU}{\9045\300}/* U+25C0
18566 % U+25C1 WHITE RIGHT-POINTING TRIANGLE (= z notation domain re-
striction);
18567 % whiteleftpointingtriangle; \triangleleft (LaTeX)
18568 \DeclareTextCommand{\texttriangleleft}{PU}{\9045\301}/* U+25C1
18569 % U+25C4 BLACK LEFT-POINTING POINTER; \LHD (wasysym)
18570 \DeclareTextCommand{\textLHD}{PU}{\9045\304}/* U+25C4
18571 % U+25C7 WHITE DIAMOND; whitediamond; \diamond (LaTeX)
18572 \DeclareTextCommand{\textdiamond}{PU}{\9045\307}/* U+25C7
18573 /* \textdiamond -> \Diamond (wasysym)
18574 % U+25CA LOZENGE; lozenge; \lozenge (AmS)
18575 \DeclareTextCommand{\textlozenge}{PU}{\9045\312}/* U+25CA
18576 % U+25D6 LEFT HALF BLACK CIRCLE; \LEFTCIRCLE (wasysym)

```

```

18577 \DeclareTextCommand{\textLEFTCIRCLE}{\PU}{\U+9045\326}/* U+25D6
18578 % U+25D7 RIGHT HALF BLACK CIRCLE; \RIGHTCIRCLE (wasysym)
18579 \DeclareTextCommand{\textRIGHTCIRCLE}{\PU}{\U+9045\327}/* U+25D7
18580 % U+25E6 WHITE BULLET; *openbullet, whitebullet
18581 \DeclareTextCommand{\textopenbullet}{\PU}{\U+9045\346}/* U+25E6
18582 % U+25EB WHITE SQUARE WITH VERTICAL BISECTING LINE;
18583 % \boxbar (stmaryrd)
18584 \DeclareTextCommand{\textboxbar}{\PU}{\U+9045\353}/* U+25EB
18585 % U+25EF LARGE CIRCLE; largecircle
18586 \DeclareTextCommand{\textbigcircle}{\PU}{\U+9045\357}/* U+25EF
18587 /* \textbigcircle -> \varbigcirc (stmaryrd)
18588 %

```

46.2.29 Miscellaneous Symbols: U+2600 to U+26FF

```

18589 % U+2601 CLOUD; \Cloud (ifsym)
18590 \DeclareTextCommand{\textCloud}{\PU}{\U+9046\001}/* U+2601
18591 % U+2605 BLACK STAR; \FiveStar (bbding)
18592 \DeclareTextCommand{\textFiveStar}{\PU}{\U+9046\005}/* U+2605
18593 % U+2606 WHITE STAR; \FiveStarOpen (bbding)
18594 \DeclareTextCommand{\textFiveStarOpen}{\PU}{\U+9046\006}/* U+2606
18595 % U+260E BLACK TELEPHONE; telephoneblack; \Phone (bbding)
18596 \DeclareTextCommand{\textPhone}{\PU}{\U+9046\016}/* U+260E
18597 /* \textPhone -> \Telefon (marvosym)
18598 % U+2610 BALLOT BOX; \boxempty (stmaryrd)
18599 \DeclareTextCommand{\textboxempty}{\PU}{\U+9046\020}/* U+2610
18600 /* \textboxempty -> \Box (wasysym)
18601 % U+2611 BALLOT BOX WITH CHECK; \Checkedbox (marvosym)
18602 \DeclareTextCommand{\textCheckedbox}{\PU}{\U+9046\021}/* U+2611
18603 /* \textCheckedbox -> \CheckedBox (marvosym)
18604 % U+2612 BALLOT BOX WITH X; \Crossedbox (marvosym)
18605 \DeclareTextCommand{\textCrossedbox}{\PU}{\U+9046\022}/* U+2612
18606 /* \textCrossedbox -> \XBox (wasysym)
18607 /* \textCrossedbox -> \CrossedBox (marvosym)
18608 % U+2615 HOT BEVERAGE; \Coffeecup (marvosym)
18609 \DeclareTextCommand{\textCoffeecup}{\PU}{\U+9046\025}/* U+2615
18610 % U+261A BLACK LEFT POINTING INDEX; \HandCuffLeft (bbding)
18611 \DeclareTextCommand{\textHandCuffLeft}{\PU}{\U+9046\032}/* U+261A
18612 % U+261B BLACK RIGHT POINTING INDEX; \HandCuffRight (bbding)
18613 \DeclareTextCommand{\textHandCuffRight}{\PU}{\U+9046\033}/* U+261B
18614 % U+261C WHITE LEFT POINTING INDEX; \HandLeft (bbding)
18615 \DeclareTextCommand{\textHandLeft}{\PU}{\U+9046\034}/* U+261C
18616 /* \textHandLeft -> \rightpointleft (fourier)
18617 % U+261E WHITE RIGHT POINTING INDEX; \HandRight (bbding)
18618 \DeclareTextCommand{\textHandRight}{\PU}{\U+9046\036}/* U+261E
18619 /* \textHandRight -> \leftpointright (fourier)
18620 /* \textHandRight -> \PointingHand (marvosym)
18621 /* \textHandRight -> \Pointinghand (marvosym)
18622 % U+2622 RADIOACTIVE SIGN; \Radioactivity (marvosym)
18623 \DeclareTextCommand{\textRadioactivity}{\PU}{\U+9046\042}/* U+2622
18624 /* \textRadioactivity -> \Radiation (ifsym)
18625 % U+2623 BIOHAZARD SIGN; \Biohazard (marvosym)
18626 \DeclareTextCommand{\textBiohazard}{\PU}{\U+9046\043}/* U+2623
18627 % U+2625 ANKH; \Ankh (marvosym)
18628 \DeclareTextCommand{\textAnkh}{\PU}{\U+9046\045}/* U+2625

```

```

18629 % U+262F YIN YANG; \YinYang (marvosym)
18630 \DeclareTextCommand{\textYinYang}{PU}{\U{9046}\U{057}}%* U+262F
18631 %* \textYinYang -> \Yinyang (marvosym)
18632 %* \textYinYang -> \YingYang (marvosym)
18633 %* \textYinYang -> \Yingyang (marvosym)
18634 % U+2639 WHITE FROWNING FACE; \frownie (wasysym)
18635 \DeclareTextCommand{\textfrownie}{PU}{\U{9046}\U{071}}%* U+2639
18636 %* \textfrownie -> \Frowny (marvosym)
18637 % U+263A WHITE SMILING FACE; \smiley (wasysym)
18638 \DeclareTextCommand{\textsmiley}{PU}{\U{9046}\U{072}}%* U+263A
18639 %* \textsmiley -> \Smiley (marvosym)
18640 % U+263B BLACK SMILING FACE; \blacksmiley (wasysym)
18641 \DeclareTextCommand{\textblacksmiley}{PU}{\U{9046}\U{073}}%* U+263B
18642 % U+263C WHITE SUN WITH RAYS; \sun (wasysym)
18643 \DeclareTextCommand{\textsun}{PU}{\U{9046}\U{074}}%* U+263C
18644 %* \textsun -> \Sun (marvosym)
18645 % U+263D FIRST QUARTER MOON; \leftmoon (wasysym, mathabx)
18646 \DeclareTextCommand{\textleftmoon}{PU}{\U{9046}\U{075}}%* U+263D
18647 % U+263E LAST QUARTER MOON; \rightmoon (wasysym, mathabx)
18648 \DeclareTextCommand{\textrightmoon}{PU}{\U{9046}\U{076}}%* U+263E
18649 % U+263F MERCURY; \mercury (wasysym)
18650 \DeclareTextCommand{\textmercury}{PU}{\U{9046}\U{077}}%* U+263F
18651 %* \textmercury -> \Mercury (marvosym)
18652 % U+2640 FEMALE SIGN; female; \female (wasysym)
18653 \DeclareTextCommand{\textPUfemale}{PU}{\U{9046}\U{100}}%* U+2640
18654 %* \textPUfemale -> \textfemale (tipx)
18655 %* \textPUfemale -> \female (wasysym)
18656 %* \textPUfemale -> \venus (wasysym)
18657 %* \textPUfemale -> \Venus (marvosym)
18658 %* \textPUfemale -> \Female (marvosym)
18659 % U+2641 EARTH; \earth (wasysym)
18660 \DeclareTextCommand{\textearth}{PU}{\U{9046}\U{101}}%* U+2641
18661 %* \textearth -> \Earth (marvosym)
18662 % U+2642 MALE SIGN; male; mars; \male (wasysym)
18663 \DeclareTextCommand{\textmale}{PU}{\U{9046}\U{102}}%* U+2642
18664 %* \textmale -> \mars (wasysym)
18665 %* \textmale -> \Mars (marvosym)
18666 %* \textmale -> \Male (marvosym)
18667 % U+2643 JUPITER; \jupiter (wasysym)
18668 \DeclareTextCommand{\textjupiter}{PU}{\U{9046}\U{103}}%* U+2643
18669 %* \textjupiter -> \Jupiter (marvosym)
18670 % U+2644 SATURN; \saturn (wasysym)
18671 \DeclareTextCommand{\textsaturn}{PU}{\U{9046}\U{104}}%* U+2644
18672 %* \textsaturn -> \Saturn (marvosym)
18673 % U+2645 URANUS; \uranus (wasysym)
18674 \DeclareTextCommand{\texturanus}{PU}{\U{9046}\U{105}}%* U+2645
18675 %* \texturanus -> \Uranus (marvosym)
18676 % U+2646 NEPTUNE; \neptune (wasysym)
18677 \DeclareTextCommand{\textneptune}{PU}{\U{9046}\U{106}}%* U+2646
18678 %* \textneptune -> \Neptune (marvosym)
18679 % U+2647 PLUTO; \pluto (wasysym)
18680 \DeclareTextCommand{\textpluto}{PU}{\U{9046}\U{107}}%* U+2647
18681 %* \textpluto -> \Pluto (marvosym)
18682 % U+2648 ARIES; \aries (wasysym)

```

```

18683 \DeclareTextCommand{\textaries}{\PU}{\U{9046}\U{110}}%* U+2648
18684 %* \textaries -> \Aries (marvosym)
18685 % U+2649 TAURUS; \taurus (wasysym)
18686 \DeclareTextCommand{\texttaurus}{\PU}{\U{9046}\U{111}}%* U+2649
18687 %* \texttaurus -> \Taurus (marvosym)
18688 % U+264A GEMINI; \gemini (wasysym)
18689 \DeclareTextCommand{\textgemini}{\PU}{\U{9046}\U{112}}%* U+264A
18690 %* \textgemini -> \Gemini (marvosym)
18691 % U+264B CANCER; \cancer (wasysym)
18692 \DeclareTextCommand{\textcancer}{\PU}{\U{9046}\U{113}}%* U+264B
18693 %* \textcancer -> \Cancer (marvosym)
18694 % U+264C LEO; \leo (wasysym)
18695 \DeclareTextCommand{\textleo}{\PU}{\U{9046}\U{114}}%* U+264C
18696 %* \textleo -> \Leo (marvosym)
18697 % U+264D VIRGO; \virgo (wasysym)
18698 \DeclareTextCommand{\textvirgo}{\PU}{\U{9046}\U{115}}%* U+264D
18699 %* \textvirgo -> \Virgo (marvosym)
18700 % U+264E LIBRA; \libra (wasysym)
18701 \DeclareTextCommand{\textlibra}{\PU}{\U{9046}\U{116}}%* U+264E
18702 %* \textlibra -> \Libra (marvosym)
18703 % U+264F SCORPIO; \scorpio (wasysym)
18704 \DeclareTextCommand{\textscorpio}{\PU}{\U{9046}\U{117}}%* U+264F
18705 %* \textscorpio -> \Scorpio (marvosym)
18706 % U+2650 SAGITTARIUS; \sagittarius (wasysym)
18707 \DeclareTextCommand{\textsagittarius}{\PU}{\U{9046}\U{120}}%* U+2650
18708 %* \textsagittarius -> \Sagittarius (marvosym)
18709 % U+2651 CAPRICORN; \capricornus (wasysym)
18710 \DeclareTextCommand{\textcapricornus}{\PU}{\U{9046}\U{121}}%* U+2651
18711 %* \textcapricornus -> \Capricorn (marvosym)
18712 % U+2652 AQUARIUS; \aquarius (wasysym)
18713 \DeclareTextCommand{\textaquarius}{\PU}{\U{9046}\U{122}}%* U+2652
18714 %* \textaquarius -> \Aquarius (marvosym)
18715 % U+2653 PISCES; \pisces (wasysym)
18716 \DeclareTextCommand{\textpisces}{\PU}{\U{9046}\U{123}}%* U+2653
18717 %* \textpisces -> \Pisces (marvosym)
18718 % U+2660 BLACK SPADE SUIT; spade, spadesuitblack; \spadesuit (LaTeX)
18719 \DeclareTextCommand{\textspadesuitblack}{\PU}{\U{9046}\U{140}}% U+2660
18720 %* \textspadesuitblack -> \spadesuit (MnSymbol)
18721 % U+2661 WHITE HEART SUIT; heartsuitwhite; \heartsuit (LaTeX)
18722 \DeclareTextCommand{\textheartsuitwhite}{\PU}{\U{9046}\U{141}}% U+2661
18723 %* \textheartsuitwhite -> \Heart (marvosym)
18724 %* \textheartsuitwhite -> \heartsuit (MnSymbol)
18725 % U+2662 WHITE DIAMOND SUIT; diamondsuitwhite; \diamondsuit (LaTeX)
18726 \DeclareTextCommand{\textdiamondsuitwhite}{\PU}{\U{9046}\U{142}}% U+2662
18727 %* \textdiamondsuitwhite -> \diamondsuit (MnSymbol)
18728 % U+2663 BLACK CLUB SUIT; club, clubsuitblack; \clubsuit (LaTeX)
18729 \DeclareTextCommand{\textclubsuitblack}{\PU}{\U{9046}\U{143}}% U+2663
18730 %* \textclubsuitblack -> \clubsuit (MnSymbol)
18731 % U+2664 WHITE SPADE SUIT; spadesuitwhite
18732 \DeclareTextCommand{\textspadesuitwhite}{\PU}{\U{9046}\U{144}}% U+2664
18733 % U+2665 BLACK HEART SUIT; heartsuitblack, heart
18734 \DeclareTextCommand{\textheartsuitblack}{\PU}{\U{9046}\U{145}}% U+2665
18735 % U+2666 BLACK DIAMOND SUIT; diamond
18736 \DeclareTextCommand{\textdiamondsuitblack}{\PU}{\U{9046}\U{146}}% U+2666

```

```

18737 % U+2667 WHITE CLUB SUIT; clubsuitwhite
18738 \DeclareTextCommand{\textclubsuitwhite}{PU}{\9046\147}%
18739 % U+2669 QUARTER NOTE; quarternote; \quarternote (wasysym, arev)
18740 \DeclareTextCommand{\textquarternote}{PU}{\9046\151}%
18741 % U+266A EIGHTH NOTE; musicalnote; \textmusicalnote (textcomp)
18742 \DeclareTextCommand{\textmusicalnote}{PU}{\9046\152}%
18743 %* \textmusicalnote -> \eighthnote (wasysym, arev)
18744 % U+266B BEAMED EIGHTH NOTES; eighthnotebeamed; \twonotes (wasysym)
18745 \DeclareTextCommand{\texttwonotes}{PU}{\9046\153}%
18746 % U+266C BEAMED SIXTEENTH NOTES; beamedsixteenthnotes; \sixteenth-
    note (arev)
18747 \DeclareTextCommand{\textsixteenthnote}{PU}{\9046\154}%
18748 % U+266D MUSIC FLAT SIGN; musicflatsign; \flat (LaTeX)
18749 \DeclareTextCommand{\textflat}{PU}{\9046\155}%
18750 % U+266E MUSIC NATURAL SIGN; \natural (LaTeX)
18751 \DeclareTextCommand{\textnatural}{PU}{\9046\156}%
18752 % U+266F MUSIC SHARP SIGN; musicsharpsign; \sharp (LaTeX)
18753 \DeclareTextCommand{\textsharp}{PU}{\9046\157}%
18754 % U+2672 UNIVERSAL RECYCLING SYMBOL; \recycle (recycle)
18755 \DeclareTextCommand{\textrecycle}{PU}{\9046\162}%
18756 %* \textrecycle -> \Recycling (marvosym)
18757 % U+267F WHEELCHAIR SYMBOL; \Wheelchair (marvosym)
18758 \DeclareTextCommand{\textWheelchair}{PU}{\9046\177}%
18759 % U+2691 BLACK FLAG; \Flag (ifsym)
18760 \DeclareTextCommand{\textFlag}{PU}{\9046\221}%
18761 %* \textFlag -> \VarFlag (ifsym)
18762 % U+2692 HAMMER AND PICK; \MineSign (marvosym)
18763 \DeclareTextCommand{\textMineSign}{PU}{\9046\222}%
18764 % U+2694 CROSSED SWORDS; \dsmilitary (dictsym)
18765 \DeclareTextCommand{\textdsmilitary}{PU}{\9046\224}%
18766 %* \textdsmilitary -> \textxswup (fourier)
18767 % U+2695 STAFF OF AESCULAPIUS; \dsmedical (dictsym)
18768 \DeclareTextCommand{\textdsmedical}{PU}{\9046\225}%
18769 % U+2696 SCALES; \dsjuridical (dictsym)
18770 \DeclareTextCommand{\textdsjuridical}{PU}{\9046\226}%
18771 % U+2697 ALEMBIC; \dschemical (dictsym)
18772 \DeclareTextCommand{\textdschemical}{PU}{\9046\227}%
18773 % U+2698 FLOWER; \dsbiological (dictsym)
18774 \DeclareTextCommand{\textdsbiological}{PU}{\9046\230}%
18775 % U+269A STAFF OF HERMES; \dscommercial (dictsym)
18776 \DeclareTextCommand{\textdscommercial}{PU}{\9046\232}%
18777 % U+269D OUTLINED WHITE STAR; \manstar (manfnt)
18778 \DeclareTextCommand{\textmanstar}{PU}{\9046\235}%
18779 % U+26A0 WARNING SIGN; \danger (fourier)
18780 \DeclareTextCommand{\textdanger}{PU}{\9046\240}%
18781 % U+26A2 DOUBLED FEMALE SIGN; \FemaleFemale (marvosym)
18782 \DeclareTextCommand{\textFemaleFemale}{PU}{\9046\242}%
18783 % U+26A3 DOUBLED MALE SIGN; \MaleMale (marvosym)
18784 \DeclareTextCommand{\textMaleMale}{PU}{\9046\243}%
18785 % U+26A4 INTERLOCKED FEMALE AND MALE SIGN; \FemaleMale (mar-
    vosym)
18786 \DeclareTextCommand{\textFemaleMale}{PU}{\9046\244}%
18787 % U+26A5 MALE AND FEMALE SIGN; \Hermaphrodite (marvosym)
18788 \DeclareTextCommand{\textHermaphrodite}{PU}{\9046\245}%

```

```

18789 % U+26AA MEDIUM WHITE CIRCLE; \Neutral (marvosym)
18790 \DeclareTextCommand{\textNeutral}{PU}{\9046\252}/* U+26AA
18791 % U+26AD MARRIAGE SYMBOL
18792 \DeclareTextCommand{\textmarried}{PU}{\9046\255}/* U+26AD
18793 % U+26AE DIVORCE SYMBOL
18794 \DeclareTextCommand{\textdivorced}{PU}{\9046\256}/* U+26AE
18795 % U+26B2 NEUTER; \textuncrfemale (tipx)
18796 \DeclareTextCommand{\textPUuncrfemale}{PU}{\9046\262}/* U+26B2
18797 /* \textPUuncrfemale -> \textuncrfemale (tipx)
18798 % U+26B9 SEXTILE; \hexstar (wasysym)
18799 \DeclareTextCommand{\texthexstar}{PU}{\9046\271}/* U+26B9
18800 % U+26BD SOCCER BALL; \Football (marvosym)
18801 \DeclareTextCommand{\textSoccerBall}{PU}{\9046\275}/* U+26BD
18802 /* \textSoccerBall -> \Football (marvosym)
18803 % U+26C5 SUN BEHIND CLOUD; \SunCloud (ifsym)
18804 \DeclareTextCommand{\textSunCloud}{PU}{\9046\305}/* U+26C5
18805 % U+26C6 RAIN; \Rain (ifsym)
18806 \DeclareTextCommand{\textRain}{PU}{\9046\306}/* U+26C6
18807 % U+26D4 NO ENTRY; \noway (fourier)
18808 \DeclareTextCommand{\textnoway}{PU}{\9046\324}/* U+26D4
18809 % U+26F0 MOUNTAIN; \Mountain (ifsym)
18810 \DeclareTextCommand{\textMountain}{PU}{\9046\360}/* U+26F0
18811 % U+26FA TENT; \Tent (ifsym)
18812 \DeclareTextCommand{\textTent}{PU}{\9046\372}/* U+26FA

```

46.2.30 Dingbats: U+2700 to U+27BF

```

18813 % U+2701 UPPER BLADE SCISSORS; \ScissorRightBrokenBottom (bbding)
18814 \DeclareTextCommand{\textScissorRightBrokenBottom}{PU}{\9047\001}/* U+2701
18815 /* \textScissorRightBrokenBottom -> \CutLeft (marvosym)
18816 /* \textScissorRightBrokenBottom -> \Cutright (marvosym)
18817 % U+2702 BLACK SCISSORS; \ScissorRight (bbding)
18818 \DeclareTextCommand{\textScissorRight}{PU}{\9047\002}/* U+2702
18819 /* \textScissorRight -> \RightScissors (marvosym)
18820 /* \textScissorRight -> \Leftscissors (marvosym)
18821 % U+2703 LOWER BLADE SCISSORS; \ScissorRightBrokenTop (bbding)
18822 \DeclareTextCommand{\textScissorRightBrokenTop}{PU}{\9047\003}/* U+2703
18823 % U+2704 WHITE SCISSORS; \ScissorHollowRight (bbding)
18824 \DeclareTextCommand{\textScissorHollowRight}{PU}{\9047\004}/* U+2704
18825 % U+2706 TELEPHONE LOCATION SIGN; \PhoneHandset (bbding)
18826 \DeclareTextCommand{\textPhoneHandset}{PU}{\9047\006}/* U+2706
18827 % U+2707 TAPE DRIVE; \Tape (bbding)
18828 \DeclareTextCommand{\textTape}{PU}{\9047\007}/* U+2707
18829 % U+2708 AIRPLANE; \Plane (bbding)
18830 \DeclareTextCommand{\textPlane}{PU}{\9047\010}/* U+2708
18831 % U+2709 ENVELOPE; \Envelope (bbding),
18832 \DeclareTextCommand{\textEnvelope}{PU}{\9047\011}/* U+2709
18833 /* \textEnvelope -> \Letter (marvosym)
18834 % U+270C VICTORY HAND; \Peace (bbding)
18835 \DeclareTextCommand{\textPeace}{PU}{\9047\014}/* U+270C
18836 % U+270D WRITING HAND; \WritingHand (marvosym)
18837 \DeclareTextCommand{\textWritingHand}{PU}{\9047\015}/* U+270D
18838 /* \textWritingHand -> \Writinghand (marvosym)
18839 % U+270E LOWER RIGHT PENCIL; \PencilRightDown (bbding)
18840 \DeclareTextCommand{\textPencilRightDown}{PU}{\9047\016}/* U+270E

```

```

18841 % U+270F PENCIL; \PencilRight (bbding)
18842 \DeclareTextCommand{\textPencilRight}{PU}{\9047\017}/* U+270F
18843 % U+2710 UPPER RIGHT PENCIL; \PencilRightUp (bbding)
18844 \DeclareTextCommand{\textPencilRightUp}{PU}{\9047\020}/* U+2710
18845 % U+2711 WHITE NIB; \NibRight (bbding)
18846 \DeclareTextCommand{\textNibRight}{PU}{\9047\021}/* U+2711
18847 % U+2712 BLACK NIB; \NibSolidRight (bbding)
18848 \DeclareTextCommand{\textNibSolidRight}{PU}{\9047\022}/* U+2712
18849 % U+2713 CHECK MARK; checkmark; \Checkmark (bbding)
18850 \DeclareTextCommand{\textCheckmark}{PU}{\9047\023}/* U+2713
18851 /* \textCheckmark -> \checkmark (MnSymbol)
18852 % U+2714 HEAVY CHECK MARK; \CheckmarkBold (bbding)
18853 \DeclareTextCommand{\textCheckmarkBold}{PU}{\9047\024}/* U+2714
18854 % U+2715 MULTIPLICATION X; \XSolid (bbding)
18855 \DeclareTextCommand{\textXSolid}{PU}{\9047\025}/* U+2715
18856 % U+2716 HEAVY MULTIPLICATION X; \XSolidBold (bbding)
18857 \DeclareTextCommand{\textXSolidBold}{PU}{\9047\026}/* U+2716
18858 % U+2717 BALLOT X; \XSolidBrush (bbding)
18859 \DeclareTextCommand{\textXSolidBrush}{PU}{\9047\027}/* U+2717
18860 % U+2719 OUTLINED GREEK CROSS; \PlusOutline (bbding)
18861 \DeclareTextCommand{\textPlusOutline}{PU}{\9047\031}/* U+2719
18862 % U+271A HEAVY GREEK CROSS; \Plus (bbding)
18863 \DeclareTextCommand{\textPlus}{PU}{\9047\032}/* U+271A
18864 % U+271B OPEN CENTRE CROSS; \PlusThinCenterOpen (bbding)
18865 \DeclareTextCommand{\textPlusThinCenterOpen}{PU}{\9047\033}/* U+271B
18866 % U+271C HEAVY OPEN CENTRE CROSS; \PlusCenterOpen (bbding)
18867 \DeclareTextCommand{\textPlusCenterOpen}{PU}{\9047\034}/* U+271C
18868 % U+271D LATIN CROSS; \Cross (bbding)
18869 \DeclareTextCommand{\textCross}{PU}{\9047\035}/* U+271D
18870 % U+271E SHADOWED WHITE LATIN CROSS; \CrossOpenShadow (bbding)
18871 \DeclareTextCommand{\textCrossOpenShadow}{PU}{\9047\036}/* U+271E
18872 % U+271F OUTLINED LATIN CROSS; \CrossOutline (bbding)
18873 \DeclareTextCommand{\textCrossOutline}{PU}{\9047\037}/* U+271F
18874 % U+2720 MALTESE CROSS; \CrossMaltese (bbding)
18875 \DeclareTextCommand{\textCrossMaltese}{PU}{\9047\040}/* U+2720
18876 % U+2721 STAR OF DAVID; \DavidStar (bbding)
18877 \DeclareTextCommand{\textDavidStar}{PU}{\9047\041}/* U+2721
18878 /* \textDavidStar -> \davidstar (wasysym)
18879 % U+2722 FOUR TEARDROP-SPOKED ASTERISK; \FourAsterisk (bbding)
18880 \DeclareTextCommand{\textFourAsterisk}{PU}{\9047\042}/* U+2722
18881 % U+2723 FOUR BALLOON-SPOKED ASTERISK; \JackStar (bbding)
18882 \DeclareTextCommand{\textJackStar}{PU}{\9047\043}/* U+2723
18883 % U+2724 HEAVY FOUR BALLOON-SPOKED ASTERISK; \JackStarBold (bb-
ding)
18884 \DeclareTextCommand{\textJackStarBold}{PU}{\9047\044}/* U+2724
18885 % U+2725 FOUR CLUB-SPOKED ASTERISK; \CrossClowerTips (bbding)
18886 \DeclareTextCommand{\textClowerTips}{PU}{\9047\045}/* U+2725
18887 % U+2726 BLACK FOUR POINTED STAR; \FourStar (bbding)
18888 \DeclareTextCommand{\textFourStar}{PU}{\9047\046}/* U+2726
18889 % U+2727 WHITE FOUR POINTED STAR; \FourStarOpen (bbding)
18890 \DeclareTextCommand{\textFourStarOpen}{PU}{\9047\047}/* U+2727
18891 % U+272A CIRCLED WHITE STAR; \FiveStarOpenCircled (bbding)
18892 \DeclareTextCommand{\textFiveStarOpenCircled}{PU}{\9047\052}/* U+272A
18893 % U+272B OPEN CENTRE BLACK STAR; \FiveStarCenterOpen (bbding)

```

```

18894 \DeclareTextCommand{\textFiveStarCenterOpen}{PU}{\9047\053}/* U+272B
18895 % U+272C BLACK CENTRE WHITE STAR; \FiveStarOpenDotted (bbding)
18896 \DeclareTextCommand{\textFiveStarOpenDotted}{PU}{\9047\054}/* U+272C
18897 % U+272D OUTLINED BLACK STAR; \FiveStarOutline (bbding)
18898 \DeclareTextCommand{\textFiveStarOutline}{PU}{\9047\055}/* U+272D
18899 % U+272E HEAVY OUTLINED BLACK STAR; \FiveStarOutlineHeavy (bbding)
18900 \DeclareTextCommand{\textFiveStarOutlineHeavy}{PU}{\9047\056}/* U+272E
18901 % U+272F PINWHEEL STAR; \FiveStarConvex (bbding)
18902 \DeclareTextCommand{\textFiveStarConvex}{PU}{\9047\057}/* U+272F
18903 % U+2730 SHADOWED WHITE STAR; \FiveStarShadow (bbding)
18904 \DeclareTextCommand{\textFiveStarShadow}{PU}{\9047\060}/* U+2730
18905 % U+2731 HEAVY ASTERISK; \AsteriskBold (bbding)
18906 \DeclareTextCommand{\textAsteriskBold}{PU}{\9047\061}/* U+2731
18907 % U+2732 OPEN CENTRE ASTERISK; \AsteriskCenterOpen (bbding)
18908 \DeclareTextCommand{\textAsteriskCenterOpen}{PU}{\9047\062}/* U+2732
18909 % U+2734 EIGHT POINTED BLACK STAR; \EightStarTaper (bbding)
18910 \DeclareTextCommand{\textEightStarTaper}{PU}{\9047\064}/* U+2734
18911 % U+2735 EIGHT POINTED PINWHEEL STAR; \EightStarConvex (bbding)
18912 \DeclareTextCommand{\textEightStarConvex}{PU}{\9047\065}/* U+2735
18913 % U+2736 SIX POINTED BLACK STAR; \SixStar (bbding)
18914 \DeclareTextCommand{\textSixStar}{PU}{\9047\066}/* U+2736
18915 % U+2737 EIGHT POINTED RECTILINEAR BLACK STAR; \EightStar (bbding)
18916 \DeclareTextCommand{\textEightStar}{PU}{\9047\067}/* U+2737
18917 % U+2738 HEAVY EIGHT POINTED RECTILINEAR BLACK STAR; \EightStarBold (bbding)
18918 \DeclareTextCommand{\textEightStarBold}{PU}{\9047\070}/* U+2738
18919 % U+2739 TWELVE POINTED BLACK STAR; \TwelveStar (bbding)
18920 \DeclareTextCommand{\textTwelveStar}{PU}{\9047\071}/* U+2739
18921 % U+273A SIXTEEN POINTED ASTERISK; \SixteenStarLight (bbding)
18922 \DeclareTextCommand{\textSixteenStarLight}{PU}{\9047\072}/* U+273A
18923 % U+273B TEARDROP-SPOKED ASTERISK; \SixFlowerPetalRemoved (bbding)
18924 \DeclareTextCommand{\textSixFlowerPetalRemoved}{PU}{\9047\073}/* U+273B
18925 % U+273C OPEN CENTRE TEARDROP-SPOKED ASTERISK;
18926 % \SixFlowerOpenCenter (bbding)
18927 \DeclareTextCommand{\textSixFlowerOpenCenter}{PU}{\9047\074}/* U+273C
18928 % U+273D HEAVY TEARDROP-SPOKED ASTERISK; \Asterisk (bbding)
18929 \DeclareTextCommand{\textAsterisk}{PU}{\9047\075}/* U+273D
18930 % U+273E SIX PETALLED BLACK AND WHITE FLORETTE; \SixFlowerAlternate (bbding)
18931 \DeclareTextCommand{\textSixFlowerAlternate}{PU}{\9047\076}/* U+273E
18932 % U+273F BLACK FLORETTE; \FiveFlowerPetal (bbding)
18933 \DeclareTextCommand{\textFiveFlowerPetal}{PU}{\9047\077}/* U+273F
18934 % U+2740 WHITE FLORETTE; \FiveFlowerOpen (bbding)
18935 \DeclareTextCommand{\textFiveFlowerOpen}{PU}{\9047\100}/* U+2740
18936 % U+2741 EIGHT PETALLED OUTLINED BLACK FLORETTE; \EightFlowerPetal (bbding)
18937 \DeclareTextCommand{\textEightFlowerPetal}{PU}{\9047\101}/* U+2741
18938 % U+2742 CIRCLED OPEN CENTRE EIGHT POINTED STAR; \SunshineOpenCircled (bbding)
18939 \DeclareTextCommand{\textSunshineOpenCircled}{PU}{\9047\102}/* U+2742
18940 % U+2743 HEAVY TEARDROP-SPOKED PINWHEEL ASTERISK; \SixFlowerAltPetal (bbding)

```

```

18941 \DeclareTextCommand{\textSixFlowerAltPetal}{PU}{\9047\103}/* U+2743
18942 % U+2744 SNOWFLAKE; \SnowflakeChevron (bbding)
18943 \DeclareTextCommand{\textSnowflakeChevron}{PU}{\9047\104}/* U+2744
18944 % U+2745 TIGHT TRIFOLIATE SNOWFLAKE; \Snowflake (bbding)
18945 \DeclareTextCommand{\textSnowflake}{PU}{\9047\105}/* U+2745
18946 % U+2746 HEAVY CHEVRON SNOWFLAKE; \SnowflakeChevronBold (bbding)
18947 \DeclareTextCommand{\textSnowflakeChevronBold}{PU}{\9047\106}/* U+2746
18948 % U+2747 SPARKLE; \Sparkle (bbding)
18949 \DeclareTextCommand{\textSparkle}{PU}{\9047\107}/* U+2747
18950 % U+2748 HEAVY SPARKLE; \SparkleBold (bbding)
18951 \DeclareTextCommand{\textSparkleBold}{PU}{\9047\110}/* U+2748
18952 % U+2749 BALLOON-SPOKED ASTERISK; \AsteriskRoundedEnds (bbding)
18953 \DeclareTextCommand{\textAsteriskRoundedEnds}{PU}{\9047\111}/* U+2749
18954 % U+274A EIGHT TEARDROP-SPOKED PROPELLER ASTERISK;
18955 % \EightFlowerPetalRemoved (bbding)
18956 \DeclareTextCommand{\textEightFlowerPetalRemoved}{PU}{\9047\112}/* U+274A
18957 % U+274B HEAVY EIGHT TEARDROP-SPOKED PROPELLER ASTERISK;
18958 % \EightAsterisk (bbding)
18959 \DeclareTextCommand{\textEightAsterisk}{PU}{\9047\113}/* U+274B
18960 % U+274D SHADOWED WHITE CIRCLE; \CircleShadow (bbding)
18961 \DeclareTextCommand{\textCircleShadow}{PU}{\9047\115}/* U+274D
18962 % U+274F LOWER RIGHT DROP-SHADOWED WHITE SQUARE;
18963 % \SquareShadowBottomRight (bbding)
18964 \DeclareTextCommand{\textSquareShadowBottomRight}{PU}{\9047\117}/* U+274F
18965 % U+2750 UPPER RIGHT DROP-SHADOWED WHITE SQUARE;
18966 % \SquareShadowTopRight (bbding)
18967 \DeclareTextCommand{\textSquareTopRight}{PU}{\9047\120}/* U+2750
18968 % U+2751 LOWER RIGHT SHADOWED WHITE SQUARE;
18969 % \SquareCastShadowBottomRight (bbding)
18970 \DeclareTextCommand{\textSquareCastShadowBottomRight}{PU}{\9047\121}/* U+2751
18971 % U+2752 UPPER RIGHT SHADOWED WHITE SQUARE;
18972 % \SquareCastShadowTopRight (bbding)
18973 \DeclareTextCommand{\textSquareCastShadowTopRight}{PU}{\9047\122}/* U+2752
18974 % U+2756 BLACK DIAMOND MINUS WHITE X; \OrnamentDiamandSolid (bb-
ding)
18975 \DeclareTextCommand{\textDiamandSolid}{PU}{\9047\126}/* U+2756
18976 % U+2758 LIGHT VERTICAL BAR; \RectangleThin (bbding)
18977 \DeclareTextCommand{\textRectangleThin}{PU}{\9047\130}/* U+2758
18978 % U+2759 MEDIUM VERTICAL BAR; \Rectangle (bbding)
18979 \DeclareTextCommand{\textRectangle}{PU}{\9047\131}/* U+2759
18980 % U+275A HEAVY VERTICAL BAR; \RectangleBold (bbding)
18981 \DeclareTextCommand{\textRectangleBold}{PU}{\9047\132}/* U+275A

46.2.31 Miscellaneous Mathematical Symbols-A: U+27C0 to U+27EF

18982 % U+27C2 PERPENDICULAR; perpendicular; \perp (LaTeX)
18983 \DeclareTextCommand{\textperp}{PU}{\9047\302}/* U+27C2
18984 % \notperp (mathabx)
18985 \DeclareTextCommand{\textnotperp}{PU}{\9047\302\83\070}/* U+27C2 U+0338
18986 % U+27C7 OR WITH DOT INSIDE; \veedot (MnSymbol)
18987 \DeclareTextCommand{\textveedot}{PU}{\9047\307}/* U+27C7
18988 % U+27D1 AND WITH DOT; \wedgedot (MnSymbol)
18989 \DeclareTextCommand{\textwedgedot}{PU}{\9047\321}/* U+27D1
18990 % U+27DC LEFT MULTIMAP; \leftspoon (MnSymbol)
18991 \DeclareTextCommand{\textleftspoon}{PU}{\9047\334}/* U+27DC

```

```

18992 % U+27E6 MATHEMATICAL LEFT WHITE SQUARE BRACKET
18993 \DeclareTextCommand{\textlbrackdbl}{\PU}{\text{lbrackdbl}}%* U+27E6
18994 %* \textlbrackdbl -> \llbracket (stmaryrd)
18995 % U+27E7 MATHEMATICAL RIGHT WHITE SQUARE BRACKET
18996 \DeclareTextCommand{\textrbrackdbl}{\PU}{\text{rbrackdbl}}%* U+27E7
18997 %* \textrbrackdbl -> \rrbracket (stmaryrd)

```

46.2.32 Supplemental Arrows-A: U+27F0 to U+27FF

```

18998 % U+27F2 ANTICLOCKWISE GAPPED CIRCLE ARROW;
18999 % \circlearrowleft (AmS)
19000 \DeclareTextCommand{\textcirclearrowleft}{\PU}{\text{circlearrowleft}}%* U+27F2
19001 % U+27F3 CLOCKWISE GAPPED CIRCLE ARROW; \circlearrowright (AmS)
19002 \DeclareTextCommand{\textcirclearrowright}{\PU}{\text{circlearrowright}}%* U+27F3
19003 % U+27F5 LONG LEFTWARDS ARROW; \longleftarrow (AmS)
19004 \DeclareTextCommand{\textlongleftarrow}{\PU}{\text{longleftarrow}}%* U+27F5
19005 % U+27F6 LONG RIGHTWARDS ARROW; \longrightarrow (AmS)
19006 \DeclareTextCommand{\textlongrightarrow}{\PU}{\text{longrightarrow}}%* U+27F6
19007 % U+27F7 LONG LEFT RIGHT ARROW; \longleftrightarrow (AmS)
19008 \DeclareTextCommand{\textlongleftrightarrow}{\PU}{\text{longleftrightarrow}}%* U+27F7
19009 % U+27F8 LONG LEFTWARDS DOUBLE ARROW; \Longleftarrow (AmS)
19010 \DeclareTextCommand{\textLongleftarrow}{\PU}{\text{Longleftarrow}}%* U+27F8
19011 % U+27F9 LONG RIGHTWARDS DOUBLE ARROW; \Longrightarrow (AmS)
19012 \DeclareTextCommand{\textLongrightarrow}{\PU}{\text{Longrightarrow}}%* U+27F9
19013 % U+27FA LONG LEFT RIGHT DOUBLE ARROW; \Longleftrightarrow (AmS)
19014 \DeclareTextCommand{\textLongleftrightarrow}{\PU}{\text{Longleftrightarrow}}%* U+27FA
19015 % U+27FC LONG RIGHTWARDS ARROW FROM BAR; \longmapsto (AmS)
19016 \DeclareTextCommand{\textlongmapsto}{\PU}{\text{longmapsto}}%* U+27FC
19017 % U+27FD LONG LEFTWARDS DOUBLE ARROW FROM BAR; \Longmapsfrom (stmaryrd)
19018 \DeclareTextCommand{\textLongmapsfrom}{\PU}{\text{Longmapsfrom}}%* U+27FD
19019 % U+27FE LONG RIGHTWARDS DOUBLE ARROW FROM BAR; \Longmapsto (stmaryrd)
19020 \DeclareTextCommand{\textLongmapsto}{\PU}{\text{Longmapsto}}%* U+27FE

```

46.2.33 Supplemental Arrows-B: U+2900 to U+297F

```

19021 % U+2921 NORTH WEST AND SOUTH EAST ARROW; \nwsearrow (MnSymbol)
19022 \DeclareTextCommand{\textnwsearrow}{\PU}{\text{nwsearrow}}%* U+2921
19023 % U+2922 NORTH EAST AND SOUTH WEST ARROW; \neswarro (MnSymbol)
19024 \DeclareTextCommand{\textneswarro}{\PU}{\text{neswarro}}%* U+2922
19025 % U+2923 NORTH WEST ARROW WITH HOOK; \lhooknwarrow (MnSymbol)
19026 \DeclareTextCommand{\textlhooknwarrow}{\PU}{\text{lhooknwarrow}}%* U+2923
19027 % U+2924 NORTH EAST ARROW WITH HOOK; \rhooknearrow (MnSymbol)
19028 \DeclareTextCommand{\textrhooknearrow}{\PU}{\text{rhooknearrow}}%* U+2924
19029 % U+2925 SOUTH EAST ARROW WITH HOOK; \lhooksearrow (MnSymbol)
19030 \DeclareTextCommand{\textlhooksearrow}{\PU}{\text{lhooksearrow}}%* U+2925
19031 % U+2926 SOUTH WEST ARROW WITH HOOK; \rhookswarrow (MnSymbol)
19032 \DeclareTextCommand{\textrhookswarrow}{\PU}{\text{rhookswarrow}}%* U+2926
19033 % U+2933 WAVE ARROW POINTING DIRECTLY RIGHT; \leadsto (wasysym)
19034 \DeclareTextCommand{\textleadsto}{\PU}{\text{leadsto}}%* U+2933
19035 % U+2934 ARROW POINTING RIGHTWARDS THEN CURVING UPWARDS;
19036 % \rcurvearrowne (MnSymbol)
19037 \DeclareTextCommand{\textrcurvearrowne}{\PU}{\text{trcurvearrowne}}%* U+2934

```

```

19038 % U+2935 ARROW POINTING RIGHTWARDS THEN CURVING DOWN-
WARDS;
19039 % \lcurvearrowse (MnSymbol)
19040 \DeclareTextCommand{\textlcurvearrowse}{\PU}{\9051\065}%'* U+2935
19041 % U+2936 ARROW POINTING DOWNWARDS THEN CURVING LEFT-
WARDS;
19042 % \lcurvearrowsw (MnSymbol)
19043 \DeclareTextCommand{\textlcurvearrowsw}{\PU}{\9051\066}%'* U+2936
19044 % U+2937 ARROW POINTING DOWNWARDS THEN CURVING RIGHT-
WARDS;
19045 % \rcurvearrowse (MnSymbol)
19046 \DeclareTextCommand{\textrcurvearrowse}{\PU}{\9051\067}%'* U+2937
19047 % U+2938 RIGHT-SIDE ARC CLOCKWISE ARROW; \lcurvearrowdown (Mn-
Symbol)
19048 \DeclareTextCommand{\textlcurvearrowdown}{\PU}{\9051\070}%'* U+2938
19049 %* \textlcurvearrowdown -> \RightTorque (marvosym)
19050 %* \textlcurvearrowdown -> \Righttorque (marvosym)
19051 % U+2939 LEFT-SIDE ARC ANTICLOCKWISE ARROW;
19052 % \rcurvearrowdown (MnSymbol)
19053 \DeclareTextCommand{\textrcurvearrowdown}{\PU}{\9051\071}%'* U+2939
19054 %* \textrcurvearrowdown -> \LeftTorque (marvosym)
19055 %* \textrcurvearrowdown -> \Lefttorque (marvosym)
19056 % U+293A TOP ARC ANTICLOCKWISE ARROW; \rcurvearrowleft (MnSym-
bol)
19057 \DeclareTextCommand{\textrcurvearrowleft}{\PU}{\9051\072}%'* U+293A
19058 % U+293B BOTTOM ARC ANTICLOCKWISE ARROW;
19059 % \rcurvearrowright (MnSymbol)
19060 \DeclareTextCommand{\textrcurvearrowright}{\PU}{\9051\073}%'* U+293B
19061 % U+294A LEFT BARB UP RIGHT BARB DOWN HARPOON; \leftrighthar-
poon (mathabx)
19062 \DeclareTextCommand{\textleftrightharpoon}{\PU}{\9051\112}%'* U+294A
19063 % U+294B LEFT BARB DOWN RIGHT BARB UP HARPOON; \rightlefthar-
poon (mathabx)
19064 \DeclareTextCommand{\textrightleftharpoon}{\PU}{\9051\113}%'* U+294B
19065 % U+294C UP BARB RIGHT DOWN BARB LEFT HARPOON;
19066 % \updownharpoonrightleft (MnSymbol)
19067 \DeclareTextCommand{\textupdownharpoonrightleft}{\PU}{\9051\114}%'* U+294C
19068 % U+294D UP BARB LEFT DOWN BARB RIGHT HARPOON;
19069 % \updownharpoonleftright (MnSymbol)
19070 \DeclareTextCommand{\textupdownharpoonleftright}{\PU}{\9051\115}%'* U+294D
19071 % U+2962 LEFTWARDS HARPOON WITH BARB UP ABOVE LEFTWARDS
19072 % HARPOON WITH BARB DOWN; \leftleftharpoons (mathabx)
19073 \DeclareTextCommand{\textleftleftharpoons}{\PU}{\9051\142}%'* U+2962
19074 % U+2963 UPWARDS HARPOON WITH BARB LEFT BESIDE UPWARDS
19075 % HARPOON WITH BARB RIGHT; \upupharpoons (mathabx)
19076 \DeclareTextCommand{\textupupharpoons}{\PU}{\9051\143}%'* U+2963
19077 % U+2964 RIGHTWARDS HARPOON WITH BARB UP ABOVE RIGHT-
WARDS HARPOON
19078 % WITH BARB DOWN; \rightrightharpoons (mathabx)
19079 \DeclareTextCommand{\textrightrightharpoons}{\PU}{\9051\144}%'* U+2964
19080 % U+2965 DOWNWARDS HARPOON WITH BARB LEFT BESIDE DOWN-
WARDS HARPOON
19081 % WITH BARB RIGHT; \downdownharpoons (mathabx)
19082 \DeclareTextCommand{\textdowndownharpoons}{\PU}{\9051\145}%'* U+2965

```

```

19083 % U+296A LEFTWARDS HARPOON WITH BARB UP ABOVE LONG DASH;
19084 % \leftbarharpoon (mathabx)
19085 \DeclareTextCommand{\textleftbarharpoon}{PU}{\9051\152}/* U+296A
19086 % U+296B LEFTWARDS HARPOON WITH BARB DOWN BELOW
19087 % LONG DASH; \barleftharpoon (mathabx)
19088 \DeclareTextCommand{\textbarleftharpoon}{PU}{\9051\153}/* U+296B
19089 % U+296C RIGHTWARDS HARPOON WITH BARB UP ABOVE
19090 % LONG DASH; \rightbarharpoon (mathabx)
19091 \DeclareTextCommand{\textrightbarharpoon}{PU}{\9051\154}/* U+296C
19092 % U+296D RIGHTWARDS HARPOON WITH BARB DOWN BELOW
19093 % LONG DASH; \barrightharpoon (mathabx)
19094 \DeclareTextCommand{\textbarrightharpoon}{PU}{\9051\155}/* U+296D
19095 % U+296E UPWARDS HARPOON WITH BARB LEFT BESIDE DOWN-
    WARDS HARPOON
19096 % WITH BARB RIGHT; \updownharpoons (mathabx)
19097 \DeclareTextCommand{\textupdownharpoons}{PU}{\9051\156}/* U+296E
19098 % U+296F DOWNWARDS HARPOON WITH BARB LEFT BESIDE UP-
    WARDS HARPOON
19099 % WITH BARB RIGHT; \downupharpoons (mathabx)
19100 \DeclareTextCommand{\textdownupharpoons}{PU}{\9051\157}/* U+296F
19101 % U+297F DOWN FISH TAIL
19102 \DeclareTextCommand{\textmoo}{PU}{\9051\177\83\066}/* U+297F U+0336

```

46.2.34 Miscellaneous Mathematical Symbols-B: U+2980 to U+29FF

```

19103 % U+2987 Z NOTATION LEFT IMAGE BRACKET; \llparenthesis (stmaryrd)
19104 \DeclareTextCommand{\textllparenthesis}{PU}{\9051\207}/* U+2987
19105 % U+2988 Z NOTATION RIGHT IMAGE BRACKET; \rrparenthesis (stmaryrd)
19106 \DeclareTextCommand{\textrrparenthesis}{PU}{\9051\210}/* U+2988
19107 % U+29B0 REVERSED EMPTY SET; \invdiameter (wasysym)
19108 \DeclareTextCommand{\textinvdiameter}{PU}{\9051\260}/* U+29B0
19109 % U+29B6 CIRCLED VERTICAL BAR; \obar (stmaryrd)
19110 \DeclareTextCommand{\textobar}{PU}{\9051\266}/* U+29B6
19111 /* \textobar -> \textvarobar (stmaryrd)
19112 % U+29B8 CIRCLED REVERSE SOLIDUS; \obslash (stmaryrd)
19113 \DeclareTextCommand{\textobslash}{PU}{\9051\270}/* U+29B8
19114 /* \textobslash -> \circledbslash (txfonts/pfxfonts)
19115 /* \textobslash -> \backslash (mathabx)
19116 /* \textobslash -> \varobslash (stmaryrd)
19117 % U+29BA CIRCLE DIVIDED BY HORIZONTAL BAR AND TOP HALF
19118 % DIVIDED BY VERTICAL BAR; \obot (mathabx)
19119 \DeclareTextCommand{\textobot}{PU}{\9051\272}/* U+29BA
19120 /* \textobot -> \odplus (ulsy)
19121 % U+29BB CIRCLE WITH SUPERIMPOSED X; \NoChemicalCleaning (mar-
    vosym)
19122 \DeclareTextCommand{\textNoChemicalCleaning}{PU}{\9051\273}/* U+29BB
19123 % U+29C0 CIRCLED LESS-THAN; \olessthan (stmaryrd)
19124 \DeclareTextCommand{\textolessthan}{PU}{\9051\300}/* U+29C0
19125 /* \textolessthan -> \varolessthan (stmaryrd)
19126 % U+29C1 CIRCLED GREATER-THAN; \ogreaterthan (stmaryrd)
19127 \DeclareTextCommand{\textogreaterthan}{PU}{\9051\301}/* U+29C1
19128 /* \textogreaterthan -> \varogreaterthan (stmaryrd)
19129 % U+29C4 SQUARED RISING DIAGONAL SLASH; \boxslash (mathabx, stmaryrd)
19130 \DeclareTextCommand{\textboxslash}{PU}{\9051\304}/* U+29C4
19131 % U+29C5 SQUARED FALLING DIAGONAL SLASH; \boxbslash (stmaryrd)

```

```

19132 \DeclareTextCommand{\textboxbslash}{PU}{\9051\305}/* U+29C5
19133 % U+29C6 SQUARED ASTERISK; \boxast (stmaryrd)
19134 \DeclareTextCommand{\textboxast}{PU}{\9051\306}/* U+29C6
19135 % U+29C7 SQUARED SMALL CIRCLE; \boxcircle (stmaryrd)
19136 \DeclareTextCommand{\textboxcircle}{PU}{\9051\307}/* U+29C7
19137 % U+29C8 SQUARED SQUARE; \boxbox (stmaryrd)
19138 \DeclareTextCommand{\textboxbox}{PU}{\9051\310}/* U+29C8
19139 % U+29D3 BLACK BOWTIE; \Valve (marvosym)
19140 \DeclareTextCommand{\textValve}{PU}{\9051\323}/* U+29D3
19141 % U+29DF DOUBLE-ENDED MULTIMAP; \multimapboth (txfonts/pxfonts)
19142 \DeclareTextCommand{\textmultimapboth}{PU}{\9051\337}/* U+29DF
19143 % U+29E2 SHUFFLE PRODUCT; \shuffle (shuffle)
19144 \DeclareTextCommand{\textshuffle}{PU}{\9051\342}/* U+29E2

```

46.2.35 Supplemental Mathematical Operators: U+2A00 to U+2AFF

```

19145 % U+2A04 N-ARY UNION OPERATOR WITH PLUS; \uplus (LaTeX)
19146 \DeclareTextCommand{\textuplus}{PU}{\9052\004}/* U+2A04
19147 % U+2A07 TWO LOGICAL AND OPERATOR; \bigdoublewedge (MnSymbol)
19148 \DeclareTextCommand{\textbigdoublewedge}{PU}{\9052\007}/* U+2A07
19149 % U+2A08 TWO LOGICAL OR OPERATOR; \bigdoublevee (MnSymbol)
19150 \DeclareTextCommand{\textbigdoublevee}{PU}{\9052\010}/* U+2A08
19151 % U+2A1D JOIN; \Join (latexsym, amsfonts, amssymb, mathabx, txfonts,
19152 % pxfonts, wasysym)
19153 \DeclareTextCommand{\textJoin}{PU}{\9052\035}/* U+2A1D
19154 % U+2A1F Z NOTATION SCHEMA COMPOSITION; \fatsemi (stmaryrd)
19155 \DeclareTextCommand{\textfatsemi}{PU}{\9052\037}/* U+2A1F
19156 % U+2A22 PLUS SIGN WITH SMALL CIRCLE ABOVE; \circplus (mathabx)
19157 \DeclareTextCommand{\textcircplus}{PU}{\9052\042}/* U+2A22
19158 % U+2A2A MINUS SIGN WITH DOT BELOW; \minusdot (MnSymbol)
19159 \DeclareTextCommand{\textminusdot}{PU}{\9052\052}/* U+2A2A
19160 /* \textminusdot -> \divdot (mathabx)
19161 % U+2A30 MULTIPLICATION SIGN WITH DOT ABOVE; \dottimes (mathabx)
19162 \DeclareTextCommand{\textdottimes}{PU}{\9052\060}/* U+2A30
19163 % U+2A32 SEMIDIRECT PRODUCT WITH BOTTOM CLOSED;
19164 % \dtimes (mathdesign)
19165 \DeclareTextCommand{\textdtimes}{PU}{\9052\062}/* U+2A32
19166 % U+2A38 CIRCLED DIVISION SIGN; \odiv (mathabx)
19167 \DeclareTextCommand{\textodiv}{PU}{\9052\070}/* U+2A38
19168 % U+2A3C INTERIOR PRODUCT; \invneg (MnSymbol)
19169 \DeclareTextCommand{\textinvneg}{PU}{\9052\074}/* U+2A3C
19170 % U+2A4E DOUBLE SQUARE INTERSECTION; \sqdoublecap (mathabx)
19171 \DeclareTextCommand{\textsqdoublecap}{PU}{\9052\116}/* U+2A4E
19172 /* \textsqdoublecap -> \doublesqcap (MnSymbol)
19173 % U+2A40 INTERSECTION WITH DOT; \capdot (MnSymbol)
19174 \DeclareTextCommand{\textcapdot}{PU}{\9052\100}/* U+2A40
19175 % U+2A4F DOUBLE SQUARE UNION; \sqdoublecup (mathabx)
19176 \DeclareTextCommand{\textsqdoublecup}{PU}{\9052\117}/* U+2A4F
19177 /* \textsqdoublecup -> \doublesqcup (MnSymbol)
19178 % U+2A55 TWO INTERSECTING LOGICAL AND; \doublewedge (MnSymbol)
19179 \DeclareTextCommand{\textdoublewedge}{PU}{\9052\125}/* U+2A55
19180 % U+2A56 TWO INTERSECTING LOGICAL OR; \doublevee (MnSymbol)
19181 \DeclareTextCommand{\textdoublevee}{PU}{\9052\126}/* U+2A56
19182 /* \textdoublevee -> \merge (stmaryrd)
19183 % U+2A5E LOGICAL AND WITH DOUBLE OVERBAR;
```

```

19184 % \doublebarwedge (AmS)
19185 \DeclareTextCommand{\textdoublebarwedge}{PU}{\9052\136}/* U+2A5E
19186 % U+2A63 LOGICAL OR WITH DOUBLE UNDERBAR;
19187 % \veedoublebar (mahtabx)
19188 \DeclareTextCommand{\textveedoublebar}{PU}{\9052\143}/* U+2A63
19189 % U+2A66 EQUALS SIGN WITH DOT BELOW; \eqdot (MnSymbol)
19190 \DeclareTextCommand{\texteqdot}{PU}{\9052\146}/* U+2A66
19191 % \neqdot (MnSymbol)
19192 \DeclareTextCommand{\textneqdot}{PU}{\9052\146\83\070}/* U+2A66 U+0338
19193 % U+2A74 DOUBLE COLON EQUAL; \coloncolonequals (colonequals)
19194 \DeclareTextCommand{\textcoloncolonequals}{PU}{\9052\164}/* U+2A74
19195 % U+2A7D LESS-THAN OR SLANTED EQUAL TO; \eqslant (AmS)
19196 \DeclareTextCommand{\textleqslant}{PU}{\9052\175}/* U+2A7D
19197 % \nleqslant (txfonts/pxfonts)
19198 \DeclareTextCommand{\textnleqslant}{PU}{\9052\175\83\070}/* U+2A7D U+0338
19199 % U+2A7E GREATER-THAN OR SLANTED EQUAL TO; \geqslant (AmS)
19200 \DeclareTextCommand{\textgeqslant}{PU}{\9052\176}/* U+2A7E
19201 % \ngeqslang (txfonts/pxfonts)
19202 \DeclareTextCommand{\textngeqslant}{PU}{\9052\176\83\070}/* U+2A7E U+0338
19203 % U+2A85 LESS-THAN OR APPROXIMATE; \lessapprox (AmS)
19204 \DeclareTextCommand{\textlessapprox}{PU}{\9052\205}/* U+2A85
19205 % \nlessapprox (txfonts/pxfonts)
19206 \DeclareTextCommand{\textnlessapprox}{PU}{\9052\205\83\070}/* U+2A85 U+0338
19207 % U+2A86 GREATER-THAN OR APPROXIMATE; \gtrapprox (AmS)
19208 \DeclareTextCommand{\textgtrapprox}{PU}{\9052\206}/* U+2A86
19209 % \ngtrapprox (txfonts/pxfonts)
19210 \DeclareTextCommand{\textngtrapprox}{PU}{\9052\206\83\070}/* U+2A86 U+0338
19211 % U+2A87 LESS-THAN AND SINGLE-LINE NOT EQUAL TO; \lneq (AmS)
19212 \DeclareTextCommand{\textlneq}{PU}{\9052\207}/* U+2A87
19213 % U+2A88 GREATER-THAN AND SINGLE-LINE NOT EQUAL TO;
19214 % \gneq (AmS)
19215 \DeclareTextCommand{\textgneq}{PU}{\9052\210}/* U+2A88
19216 % U+2A89 LESS-THAN AND NOT APPROXIMATE; \lnapprox (AmS)
19217 \DeclareTextCommand{\textlnapprox}{PU}{\9052\211}/* U+2A89
19218 % U+2A8A GREATER-THAN AND NOT APPROXIMATE; \gnapprox (AmS)
19219 \DeclareTextCommand{\textgnapprox}{PU}{\9052\212}/* U+2A8A
19220 % U+2A8B LESS-THAN ABOVE DOUBLE-LINE EQUAL ABOVE GREATER-
    THAN;
19221 % \lesseqgtr (AmS)
19222 \DeclareTextCommand{\textlesseqgtr}{PU}{\9052\213}/* U+2A8B
19223 % U+2A8C GREATER-THAN ABOVE DOUBLE-LINE EQUAL ABOVE LESS-
    THAN;
19224 % \gtreqless (AmS)
19225 \DeclareTextCommand{\textgtreqless}{PU}{\9052\214}/* U+2A8C
19226 % U+2A95 SLANTED EQUAL TO OR LESS-THAN; \eqslantless (AmS)
19227 \DeclareTextCommand{\texteqslantless}{PU}{\9052\225}/* U+2A95
19228 % U+2A96 SLANTED EQUAL TO OR GREATER-THAN; \eqslantgtr (AmS)
19229 \DeclareTextCommand{\texteqslantgtr}{PU}{\9052\226}/* U+2A96
19230 % U+2AA6 LESS-THAN CLOSED BY CURVE; \leftslice (stmaryrd)
19231 \DeclareTextCommand{\textleftslice}{PU}{\9052\246}/* U+2AA6
19232 % U+2AA7 GREATER-THAN CLOSED BY CURVE; \rightslice (stmaryrd)
19233 \DeclareTextCommand{\textrightslice}{PU}{\9052\247}/* U+2AA7
19234 % U+2AAF PRECEDES ABOVE SINGLE-LINE EQUALS SIGN; \preceq (Mn-
    Symbol)

```

```

19235 \DeclareTextCommand{\textpreceq}{\PU}{\9052\257}/* U+2AAF
19236 % \npreceq (txfonts/pxfonts)
19237 \DeclareTextCommand{\textnpreceq}{\PU}{\9052\257\83\070}/* U+2AAF U+0338
19238 % U+2AB0 SUCCEEDS ABOVE SINGLE-LINE EQUALS SIGN; \succeq (Mn-
    Symbol)
19239 \DeclareTextCommand{\textsucceq}{\PU}{\9052\260}/* U+2AB0
19240 % \nsucceq (txfonts/pxfonts)
19241 \DeclareTextCommand{\textnsucceq}{\PU}{\9052\260\83\070}/* U+2AB0 U+0338
19242 % U+2AB1 PRECEDES ABOVE SINGLE-LINE NOT EQUAL TO; \prec-
    neq (mathabx)
19243 \DeclareTextCommand{\textprecneq}{\PU}{\9052\261}/* U+2AB1
19244 % U+2AB2 SUCCEEDS ABOVE SINGLE-LINE NOT EQUAL TO; \succ-
    neq (mathabx)
19245 \DeclareTextCommand{\textsuccneq}{\PU}{\9052\262}/* U+2AB2
19246 % U+2AB3 PRECEDES ABOVE EQUALS SIGN; \preceqq (txfonts/pxfonts)
19247 \DeclareTextCommand{\textpreceqq}{\PU}{\9052\263}/* U+2AB3
19248 % \npreceqq (txfonts/pxfonts)
19249 \DeclareTextCommand{\textnpreceqq}{\PU}{\9052\263\83\070}/* U+2AB3 U+0338
19250 % U+2AB4 SUCCEEDS ABOVE EQUALS SIGN; \succeqq (txfonts/pxfonts)
19251 \DeclareTextCommand{\textnsuccceqq}{\PU}{\9052\264}/* U+2AB4
19252 % \nsuccceqq (txfonts/pxfonts)
19253 \DeclareTextCommand{\textnsuccceqq}{\PU}{\9052\264\83\070}/* U+2AB4 U+0338
19254 % U+2AB5 PRECEDES ABOVE NOT EQUAL TO; \precneqq (txfonts/pxfonts)
19255 \DeclareTextCommand{\textprecneqq}{\PU}{\9052\265}/* U+2AB5
19256 % U+2AB6 SUCCEEDS ABOVE NOT EQUAL TO; \succcneqq (txfonts/pxfonts)
19257 \DeclareTextCommand{\textsucccneqq}{\PU}{\9052\266}/* U+2AB6
19258 % U+2AB7 PRECEDES ABOVE ALMOST EQUAL TO; \precapprox (AmS)
19259 \DeclareTextCommand{\textprecapprox}{\PU}{\9052\267}/* U+2AB7
19260 % \nprecapprox (txfonts/pxfonts)
19261 \DeclareTextCommand{\textnprecapprox}{\PU}{\9052\267\83\070}/* U+2AB7 U+0338
19262 % U+2AB8 SUCCEEDS ABOVE ALMOST EQUAL TO; \succapprox (AmS)
19263 \DeclareTextCommand{\textsuccapprox}{\PU}{\9052\270}/* U+2AB8
19264 % \nsuccapprox (txfonts/pxfonts)
19265 \DeclareTextCommand{\textnsuccapprox}{\PU}{\9052\270\83\070}/* U+2AB8 U+0338
19266 % U+2AB9 PRECEDES ABOVE NOT ALMOST EQUAL TO; \precnap-
    prox (AmS)
19267 \DeclareTextCommand{\textprecnapprox}{\PU}{\9052\271}/* U+2AB9
19268 % U+2ABA SUCCEEDS ABOVE NOT ALMOST EQUAL TO; \succnap-
    prox (AmS)
19269 \DeclareTextCommand{\textsuccnapprox}{\PU}{\9052\272}/* U+2ABA
19270 % U+2AC5 SUBSET OF ABOVE EQUALS SIGN; \subsetteqq (AmS)
19271 \DeclareTextCommand{\textsubsetteqq}{\PU}{\9052\305}/* U+2AC5
19272 % \nsubsetteqq (txfonts/pxfonts, mathabx)
19273 \DeclareTextCommand{\textnsubsetteqq}{\PU}{\9052\305\83\070}/* U+2AC5 U+0338
19274 % U+2AC6 SUPERSET OF ABOVE EQUALS SIGN; \supsetteqq (AmS)
19275 \DeclareTextCommand{\textsupsetteqq}{\PU}{\9052\306}/* U+2AC6
19276 % \nsupsetteqq (mathabx)
19277 \DeclareTextCommand{\textnsupsetteqq}{\PU}{\9052\306\83\070}/* U+2AC6 U+0338
19278 % U+2AE3 DOUBLE VERTICAL BAR LEFT TURNSTILE
19279 \DeclareTextCommand{\textdashV}{\PU}{\9052\343}/* U+2AE3
19280 /* \textdashV -> \leftVdash (MnSymbol)
19281 % \ndashV (mathabx)
19282 \DeclareTextCommand{\textndashV}{\PU}{\9052\343\83\070}/* U+2AE3 U+0338
19283 /* \textndashV -> \leftVdash (MnSymbol)

```

```

19284 % U+2AE4 VERTICAL BAR DOUBLE LEFT TURNSTILE; \Dashv (mathabx)
19285 \DeclareTextCommand{\textDashv}{\PU}{\9052\344}/* U+2AE4
19286 /* \textDashv -> \leftmodels (MnSymbol)
19287 % \nDashv (mathabx)
19288 \DeclareTextCommand{\textnDashv}{\PU}{\9052\344\83\070}/* U+2AE4 U+0338
19289 /* \textnDashv -> \nleftmodels (MnSymbol)
19290 % U+2AE5 DOUBLE VERTICAL BAR DOUBLE LEFT TURNSTILE;
19291 % \DashV (mathabx)
19292 \DeclareTextCommand{\textDashV}{\PU}{\9052\345}/* U+2AE5
19293 /* \textDashV -> \leftModels (MnSymbol)
19294 % \nDashV (mathabx)
19295 \DeclareTextCommand{\textnDashV}{\PU}{\9052\345\83\070}/* U+2AE5 U+0338
19296 /* \textnDashV -> \nleftModels (MnSymbol)
19297 % U+2AEA DOUBLE DOWN TACK; \downmodels (MnSymbol)
19298 \DeclareTextCommand{\textdownmodels}{\PU}{\9052\352}/* U+2AEA
19299 % \ndownmodels (MnSymbol)
19300 \DeclareTextCommand{\textndownmodels}{\PU}{\9052\352\83\070}/* U+2AEA U+0338
19301 % U+2AEB DOUBLE UP TACK; \upmodels (MnSymbol)
19302 \DeclareTextCommand{\textupmodels}{\PU}{\9052\353}/* U+2AEB
19303 % \upmodels (MnSymbol)
19304 \DeclareTextCommand{\textnupmodels}{\PU}{\9052\353\83\070}/* U+2AEB U+0338
19305 % U+2AEF VERTICAL LINE WITH CIRCLE ABOVE; \upspoon (MnSymbol)
19306 \DeclareTextCommand{\textupspoon}{\PU}{\9052\357}/* U+2AEF
19307 % U+2AF4 TRIPLE VERTICAL BAR BINARY RELATION;
19308 % \interleave (stmaryrd)
19309 \DeclareTextCommand{\textinterleave}{\PU}{\9052\364}/* U+2AF4
19310 % U+2AFD DOUBLE SOLIDUS OPERATOR; \sslash (stmaryrd)
19311 \DeclareTextCommand{\textsslash}{\PU}{\9052\375}/* U+2AFD
19312 /* \textsslash -> \varparallel (txfonts\pxfonts)

```

46.2.36 Miscellaneous Symbols and Arrows: U+2B00 to U+2BFF

```

19313 % U+2B20 WHITE PENTAGON; \pentagon (wasysym)
19314 \DeclareTextCommand{\textpentagon}{\PU}{\9053\040}/* U+2B20
19315 % U+2B21 WHITE HEXAGON; \varhexagon (wasysym)
19316 \DeclareTextCommand{\textvarhexagon}{\PU}{\9053\041}/* U+2B21

```

46.2.37 Latin Extended-C: U+2C60 to U+2C7F

```

19317 % U+2C7C LATIN SUBSCRIPT SMALL LETTER J
19318 \DeclareTextCommand{\textjinferior}{\PU}{\9054\174}/* U+2C7C

```

46.2.38 Supplemental Punctuation: U+2E00 to U+2E7F

```

19319 % U+2E13 DOTTED OBELOS; \slashdiv (MnSymbol)
19320 \DeclareTextCommand{\textslashdiv}{\PU}{\9056\023}/* U+2E13
19321 % U+2E18 INVERTED INTERROBANG; \textinterrobangdown (textcomp)
19322 \DeclareTextCommand{\textinterrobangdown}{\PU}{\9056\030}/* U+2E18
19323 % U+2E2D FIVE DOT MARK; \fivedots (MnSymbol)
19324 \DeclareTextCommand{\textfivedots}{\PU}{\9056\055}/* U+2E2D

```

46.2.39 Modifier Tone Letters: U+A700 to U+A71F

```

19325 % U+A71B MODIFIER LETTER RAISED UP ARROW; \textupstep (tipa)
19326 \DeclareTextCommand{\textupstep}{\PU}{\9247\033}/* U+A71B
19327 % U+A71C MODIFIER LETTER RAISED DOWN ARROW;
19328 % \textdownstep (tipa)
19329 \DeclareTextCommand{\textdownstep}{\PU}{\9247\034}/* U+A71C

```

46.2.40 Latin Extended-D: U+A720 to U+A7FF

```
19330 % U+A727 LATIN SMALL LETTER HENG; \textheng (tipx)
19331 \DeclareTextCommand{\textPUheng}{PU}{\9247\047} % U+A727
19332 %* \textPUheng -> \textheng (tipx)
19333 % U+A72C LATIN CAPITAL LETTER CUATRILLO; \textlhookfour (tipx)
19334 \DeclareTextCommand{\textPULhookfour}{PU}{\9247\054} % U+A72C
19335 %* \textPULhookfour -> \textlhookfour (tipx)
19336 % U+A730 LATIN LETTER SMALL CAPITAL F; \textscf (tipx)
19337 \DeclareTextCommand{\textPUScf}{PU}{\9247\060} % U+A730
19338 %* \textPUScf -> \textscf (tipx)
19339 % U+A735 LATIN SMALL LETTER AO; \textao (tipx)
19340 \DeclareTextCommand{\textPUaolig}{PU}{\9247\065} % U+A735
19341 %* \textPUaolig -> \textao (tipx)
19342 % U+A74F LATIN SMALL LETTER OO; \oo (wsipa)
19343 \DeclareTextCommand{\texttoo}{PU}{\9247\117} %* U+A74F
19344 % U+A788 MODIFIER LETTER LOW CIRCUMFLEX ACCENT
19345 \DeclareTextCommand{\textcircumlow}{PU}{\9247\210} % U+A788
```

46.2.41 Alphabetic Presentation Forms: U+FB00 to U+FB4F

```
19346 % U+FB01 LATIN SMALL LIGATURE FI; fi
19347 \DeclareTextCommand{\textfi}{PU}{\9373\001} % U+FB01
19348 % U+FB02 LATIN SMALL LIGATURE FL; fl
19349 \DeclareTextCommand{\textfl}{PU}{\9373\002} % U+FB02
```

46.2.42 Musical Symbols: U+1D100 to U+1D1FF

```
19350 % U+1D13B MUSICAL SYMBOL WHOLE REST; \GaPa (harmony)
19351 \DeclareTextCommand{\textGaPa}{PU}{\9330\064\9335\073} %* U+1D13B
19352 % U+1D13C MUSICAL SYMBOL HALF REST; \HaPa (harmony)
19353 \DeclareTextCommand{\textHaPa}{PU}{\9330\064\9335\074} %* U+1D13C
19354 % U+1D13D MUSICAL SYMBOL QUARTER REST; \ViPa (harmony)
19355 \DeclareTextCommand{\textViPa}{PU}{\9330\064\9335\075} %* U+1D13D
19356 % U+1D13E MUSICAL SYMBOL EIGHTH REST; \AcPa (harmony)
19357 \DeclareTextCommand{\textAcPa}{PU}{\9330\064\9335\076} %* U+1D13E
19358 % U+1D13F MUSICAL SYMBOL SIXTEENTH REST; \SePa (harmony)
19359 \DeclareTextCommand{\textSePa}{PU}{\9330\064\9335\077} %* U+1D13F
19360 % U+1D140 MUSICAL SYMBOL THIRTY-SECOND REST; \ZwPa (harmony)
19361 \DeclareTextCommand{\textZwPa}{PU}{\9330\064\9335\100} %* U+1D140
19362 % U+1D15D MUSICAL SYMBOL WHOLE NOTE; \fullnote (wasysym)
19363 \DeclareTextCommand{\textfullnote}{PU}{\9330\064\9335\135} %* U+1D15D
19364 %* \textfullnote -> \Ganz (harmony)
19365 % U+1D15E MUSICAL SYMBOL HALF NOTE; \halfnote (wasysym)
19366 \DeclareTextCommand{\texthalfnote}{PU}{\9330\064\9335\136} %* U+1D15E
19367 %* \texthalfnote -> \Halb (harmony)
19368 % U+1D15F MUSICAL SYMBOL QUARTER NOTE; \Vier (harmony)
19369 \DeclareTextCommand{\textVier}{PU}{\9330\064\9335\137} %* U+1D15F
19370 % U+1D160 MUSICAL SYMBOL EIGHTH NOTE; \Acht (harmony)
19371 \DeclareTextCommand{\textAcht}{PU}{\9330\064\9335\140} %* U+1D160
19372 % U+1D161 MUSICAL SYMBOL SIXTEENTH NOTE; \Sech (harmony)
19373 \DeclareTextCommand{\textSech}{PU}{\9330\064\9335\141} %* U+1D161
19374 % U+1D162 MUSICAL SYMBOL THIRTY-SECOND NOTE; \Zwdr (harmony)
19375 \DeclareTextCommand{\textZwdr}{PU}{\9330\064\9335\142} %* U+1D162
```

46.2.43 Miscellaneous Symbols and Pictographs: U+1F300 to U+1F5FF

```

19376 % U+1F30D EARTH GLOBE EUROPE-AFRICA; \Mundus (marvosym)
19377 \DeclareTextCommand{\textMundus}{PU}{\9330\074\9337\015}/* U+1F30D
19378 % U+1F319 CRESCENT MOON; \Moon (marvosym)
19379 \DeclareTextCommand{\textMoon}{PU}{\9330\074\9337\031}/* U+1F319
19380 % U+1F468 MAN; \ManFace (marvosym)
19381 \DeclareTextCommand{\textManFace}{PU}{\9330\075\9334\150}/* U+1F468
19382 % U+1F469 WOMAN; \WomanFace (marvosym)
19383 \DeclareTextCommand{\textWomanFace}{PU}{\9330\075\9334\151}/* U+1F469
19384 /* \textWomanFace -> \Womanface (marvosym)
19385 % U+1F4E0 FAX MACHINE; \Fax (marvosym)
19386 \DeclareTextCommand{\textFax}{PU}{\9330\075\9334\340}/* U+1F4E0
19387 /* \textFax -> \Faxmachine (marvosym)
19388 % U+1F525 FIRE; \Fire (ifsym)
19389 \DeclareTextCommand{\textFire}{PU}{\9330\075\9335\045}/* U+1F525

```

46.2.44 Transport and Map Symbols: U+1F680 to U+1F6FF

```

19390 % U+1F6B2 BICYCLE; \Bicycle (marvosym)
19391 \DeclareTextCommand{\textBicycle}{PU}{\9330\075\9336\262}/* U+1F6B2
19392 % U+1F6B9 MENS SYMBOL; \Gentsroom (marvosym)
19393 \DeclareTextCommand{\textGentsroom}{PU}{\9330\075\9336\271}/* U+1F6B9
19394 % U+1F6BA WOMENS SYMBOL; \Ladiesroom (marvosym)
19395 \DeclareTextCommand{\textLadiesroom}{PU}{\9330\075\9336\272}/* U+1F6BA

```

46.2.45 Miscellaneous

```

19396 \DeclareTextCommand{\SS}{PU}{SS}%
19397 % \textcopyleft (textcomp)
19398 \DeclareTextCommand{\textcopyleft}{PU}{\9041\204\9040\335}/* U+2184 U+20DD
19399 % \ccnc (ccllicenses)
19400 \DeclareTextCommand{\textccnc}{PU}{\80\044\9040\340}/* U+0024 U+20E0
19401 % \ccnd (ccllicenses)
19402 \DeclareTextCommand{\textccnd}{PU}{=\9040\335}/* U+003D U+20DD
19403 % \ccsa (ccllicenses)
19404 \DeclareTextCommand{\textccsa}{PU}{\9047\362\9040\335}/* U+27F2 U+20DD
19405 % \Info (marvosym, china2e)
19406 \DeclareTextCommand{\textInfo}{PU}{\9330\065\9334\042\9040\336}/* U+1D422 U+20DE
19407 % \CESign (marvosym)
19408 \DeclareTextCommand{\textCESign}{PU}{\80\103\80\105}/* U+0043 U+0045
19409 /* \textCESign -> \CEsign (marvosym)

```

46.2.46 Aliases

Aliases (german.sty)

```

19410 \DeclareTextCommand{\textglqq}{PU}{\quotedblbase}%
19411 \DeclareTextCommand{\textgrqq}{PU}{\textquotedblleft}%
19412 \DeclareTextCommand{\textglq}{PU}{\quotingleft}%
19413 \DeclareTextCommand{\textgrq}{PU}{\textquotefirst}%
19414 \DeclareTextCommand{\textflqq}{PU}{\guillemetleft}%
19415 \DeclareTextCommand{\textfrqq}{PU}{\guillemetright}%
19416 \DeclareTextCommand{\textflq}{PU}{\guilsinglleft}%
19417 \DeclareTextCommand{\textfrq}{PU}{\guilsinglright}%

```

Aliases (math names)

```

19418 \DeclareTextCommand{\textneg}{PU}{\textlogicalnot}/*
19419 \DeclareTextCommand{\texttimes}{PU}{\textmultiply}/*
19420 \DeclareTextCommand{\textdiv}{PU}{\textdivide}/*

```

```

19421 \DeclareTextCommand{\textpm}{PU}{\textplusminus}%
19422 \DeclareTextCommand{\textcdot}{PU}{\textperiodcentered}%
19423 
```

46.3 PU encoding, additions for VnTeX

This file is provided by Han The Thanh.

```

19424 <*puvnenc>
19425 \DeclareTextCommand{\abreve}{PU}{\81\003}% U+0103
19426 \DeclareTextCommand{\acircumflex}{PU}{\80\342}% U+00E2
19427 \DeclareTextCommand{\ecircumflex}{PU}{\80\352}% U+00EA
19428 \DeclareTextCommand{\ocircumflex}{PU}{\80\364}% U+00F4
19429 \DeclareTextCommand{\ohorn}{PU}{\81\241}% U+01A1
19430 \DeclareTextCommand{\uhorn}{PU}{\81\260}% U+01B0
19431 \DeclareTextCommand{\ABREVE}{PU}{\81\002}% U+0102
19432 \DeclareTextCommand{\ACIRCUMFLEX}{PU}{\80\302}% U+00C2
19433 \DeclareTextCommand{\ECIRCUMFLEX}{PU}{\80\312}% U+00CA
19434 \DeclareTextCommand{\OCIRCUMFLEX}{PU}{\80\324}% U+00D4
19435 \DeclareTextCommand{\OHORN}{PU}{\81\240}% U+01A0
19436 \DeclareTextCommand{\UHORN}{PU}{\81\257}% U+01AF
19437 \DeclareTextCompositeCommand{\'}{PU}{a}{\80\341}% U+00E1
19438 \DeclareTextCompositeCommand{\d}{PU}{a}{\9036\241}% U+1EA1
19439 \DeclareTextCompositeCommand{\`}{PU}{a}{\80\340}% U+00E0
19440 \DeclareTextCompositeCommand{\h}{PU}{a}{\9036\243}% U+1EA3
19441 \DeclareTextCompositeCommand{\~}{PU}{a}{\80\343}% U+00E3
19442 \DeclareTextCompositeCommand{\'}{PU}{\abreve}{\9036\257}% U+1EAF
19443 \DeclareTextCompositeCommand{\d}{PU}{\abreve}{\9036\267}% U+1EB7
19444 \DeclareTextCompositeCommand{\`}{PU}{\abreve}{\9036\261}% U+1EB1
19445 \DeclareTextCompositeCommand{\h}{PU}{\abreve}{\9036\263}% U+1EB3
19446 \DeclareTextCompositeCommand{\~}{PU}{\abreve}{\9036\265}% U+1EB5
19447 \DeclareTextCompositeCommand{\'}{PU}{\acircumflex}{\9036\245}% U+1EA5
19448 \DeclareTextCompositeCommand{\d}{PU}{\acircumflex}{\9036\255}% U+1EAD
19449 \DeclareTextCompositeCommand{\`}{PU}{\acircumflex}{\9036\247}% U+1EA7
19450 \DeclareTextCompositeCommand{\h}{PU}{\acircumflex}{\9036\251}% U+1EA9
19451 \DeclareTextCompositeCommand{\~}{PU}{\acircumflex}{\9036\253}% U+1EAB
19452 \DeclareTextCompositeCommand{\'}{PU}{e}{\80\351}% U+00E9
19453 \DeclareTextCompositeCommand{\d}{PU}{e}{\9036\271}% U+1EB9
19454 \DeclareTextCompositeCommand{\`}{PU}{e}{\80\350}% U+00E8
19455 \DeclareTextCompositeCommand{\h}{PU}{e}{\9036\273}% U+1EBB
19456 \DeclareTextCompositeCommand{\~}{PU}{e}{\9036\275}% U+1EBD
19457 \DeclareTextCompositeCommand{\'}{PU}{\ecircumflex}{\9036\277}% U+1EBF
19458 \DeclareTextCompositeCommand{\d}{PU}{\ecircumflex}{\9036\307}% U+1EC7
19459 \DeclareTextCompositeCommand{\`}{PU}{\ecircumflex}{\9036\301}% U+1EC1
19460 \DeclareTextCompositeCommand{\h}{PU}{\ecircumflex}{\9036\303}% U+1EC3
19461 \DeclareTextCompositeCommand{\~}{PU}{\ecircumflex}{\9036\305}% U+1EC5
19462 \DeclareTextCompositeCommand{\'}{PU}{i}{\80\355}% U+00ED
19463 \DeclareTextCompositeCommand{\d}{PU}{i}{\9036\313}% U+1ECB
19464 \DeclareTextCompositeCommand{\`}{PU}{i}{\80\354}% U+00EC
19465 \DeclareTextCompositeCommand{\h}{PU}{i}{\9036\311}% U+1EC9
19466 \DeclareTextCompositeCommand{\~}{PU}{i}{\81\051}% U+0129
19467 \DeclareTextCompositeCommand{\'}{PU}{o}{\80\363}% U+00F3
19468 \DeclareTextCompositeCommand{\d}{PU}{o}{\9036\315}% U+1ECD

```

```

19469 \DeclareTextCompositeCommand{\`}{PU}{o}{\80\362}% U+00F2
19470 \DeclareTextCompositeCommand{\h}{PU}{o}{\9036\317}% U+1ECF
19471 \DeclareTextCompositeCommand{\~}{PU}{o}{\80\365}% U+00F5
19472 \DeclareTextCompositeCommand{\'}{PU}{\ocircumflex}{\9036\321}% U+1ED1
19473 \DeclareTextCompositeCommand{\d}{PU}{\ocircumflex}{\9036\331}% U+1ED9
19474 \DeclareTextCompositeCommand{\`}{PU}{\ocircumflex}{\9036\323}% U+1ED3
19475 \DeclareTextCompositeCommand{\h}{PU}{\ocircumflex}{\9036\325}% U+1ED5
19476 \DeclareTextCompositeCommand{\~}{PU}{\ocircumflex}{\9036\327}% U+1ED7
19477 \DeclareTextCompositeCommand{\'}{PU}{\ohorn}{\9036\333}% U+1EDB
19478 \DeclareTextCompositeCommand{\d}{PU}{\ohorn}{\9036\343}% U+1EE3
19479 \DeclareTextCompositeCommand{\`}{PU}{\ohorn}{\9036\335}% U+1EDD
19480 \DeclareTextCompositeCommand{\h}{PU}{\ohorn}{\9036\337}% U+1EDF
19481 \DeclareTextCompositeCommand{\~}{PU}{\ohorn}{\9036\341}% U+1EE1
19482 \DeclareTextCompositeCommand{\'}{PU}{u}{\80\372}% U+00FA
19483 \DeclareTextCompositeCommand{\d}{PU}{u}{\9036\345}% U+1EE5
19484 \DeclareTextCompositeCommand{\`}{PU}{u}{\80\371}% U+00F9
19485 \DeclareTextCompositeCommand{\h}{PU}{u}{\9036\347}% U+1EE7
19486 \DeclareTextCompositeCommand{\~}{PU}{u}{\81\151}% U+0169
19487 \DeclareTextCompositeCommand{\\"}{PU}{uhorn}{\9036\351}% U+1EE9
19488 \DeclareTextCompositeCommand{\d}{PU}{uhorn}{\9036\361}% U+1EF1
19489 \DeclareTextCompositeCommand{\`}{PU}{uhorn}{\9036\353}% U+1EEB
19490 \DeclareTextCompositeCommand{\h}{PU}{uhorn}{\9036\355}% U+1EED
19491 \DeclareTextCompositeCommand{\~}{PU}{uhorn}{\9036\357}% U+1EEF
19492 \DeclareTextCompositeCommand{\'}{PU}{y}{\80\375}% U+00FD
19493 \DeclareTextCompositeCommand{\d}{PU}{y}{\9036\365}% U+1EF5
19494 \DeclareTextCompositeCommand{\`}{PU}{y}{\9036\363}% U+1EF3
19495 \DeclareTextCompositeCommand{\h}{PU}{y}{\9036\367}% U+1EF7
19496 \DeclareTextCompositeCommand{\~}{PU}{y}{\9036\371}% U+1EF9
19497 \DeclareTextCompositeCommand{\\"}{PU}{A}{\80\301}% U+00C1
19498 \DeclareTextCompositeCommand{\d}{PU}{A}{\9036\240}% U+1EA0
19499 \DeclareTextCompositeCommand{\`}{PU}{A}{\80\300}% U+00C0
19500 \DeclareTextCompositeCommand{\h}{PU}{A}{\9036\242}% U+1EA2
19501 \DeclareTextCompositeCommand{\~}{PU}{A}{\80\303}% U+00C3
19502 \DeclareTextCompositeCommand{\\"}{PU}{ABREVE}{\9036\256}% U+1EAE
19503 \DeclareTextCompositeCommand{\d}{PU}{ABREVE}{\9036\266}% U+1EB6
19504 \DeclareTextCompositeCommand{\`}{PU}{ABREVE}{\9036\260}% U+1EB0
19505 \DeclareTextCompositeCommand{\h}{PU}{ABREVE}{\9036\262}% U+1EB2
19506 \DeclareTextCompositeCommand{\~}{PU}{ABREVE}{\9036\264}% U+1EB4
19507 \DeclareTextCompositeCommand{\'}{PU}{ACIRCUMFLEX}{\9036\244}% U+1EA4
19508 \DeclareTextCompositeCommand{\d}{PU}{ACIRCUMFLEX}{\9036\254}% U+1EAC
19509 \DeclareTextCompositeCommand{\`}{PU}{ACIRCUMFLEX}{\9036\246}% U+1EA6
19510 \DeclareTextCompositeCommand{\h}{PU}{ACIRCUMFLEX}{\9036\250}% U+1EA8
19511 \DeclareTextCompositeCommand{\~}{PU}{ACIRCUMFLEX}{\9036\252}% U+1EAA
19512 \DeclareTextCompositeCommand{\\"}{PU}{E}{\80\311}% U+00C9
19513 \DeclareTextCompositeCommand{\d}{PU}{E}{\9036\270}% U+1EB8
19514 \DeclareTextCompositeCommand{\`}{PU}{E}{\80\310}% U+00C8
19515 \DeclareTextCompositeCommand{\h}{PU}{E}{\9036\272}% U+1EBA
19516 \DeclareTextCompositeCommand{\~}{PU}{E}{\9036\274}% U+1EBC
19517 \DeclareTextCompositeCommand{\'}{PU}{ECIRCUMFLEX}{\9036\276}% U+1EBE
19518 \DeclareTextCompositeCommand{\d}{PU}{ECIRCUMFLEX}{\9036\306}% U+1EC6
19519 \DeclareTextCompositeCommand{\`}{PU}{ECIRCUMFLEX}{\9036\300}% U+1EC0
19520 \DeclareTextCompositeCommand{\h}{PU}{ECIRCUMFLEX}{\9036\302}% U+1EC2
19521 \DeclareTextCompositeCommand{\~}{PU}{ECIRCUMFLEX}{\9036\304}% U+1EC4
19522 \DeclareTextCompositeCommand{\\"}{PU}{I}{\80\315}% U+00CD

```

```

19523 \DeclareTextCompositeCommand{\d}{PU}{I}{\9036\312}% U+1ECA
19524 \DeclareTextCompositeCommand{\`}{PU}{I}{\80\314}% U+00CC
19525 \DeclareTextCompositeCommand{\h}{PU}{I}{\9036\310}% U+1EC8
19526 \DeclareTextCompositeCommand{\ }{PU}{I}{\81\050}% U+0128
19527 \DeclareTextCompositeCommand{\ }{PU}{O}{\80\323}% U+00D3
19528 \DeclareTextCompositeCommand{\d}{PU}{O}{\9036\314}% U+1ECC
19529 \DeclareTextCompositeCommand{\`}{PU}{O}{\80\322}% U+00D2
19530 \DeclareTextCompositeCommand{\h}{PU}{O}{\9036\316}% U+1ECE
19531 \DeclareTextCompositeCommand{\~}{PU}{O}{\80\325}% U+00D5
19532 \DeclareTextCompositeCommand{\'}{PU}{OCIRCUMFLEX}{\9036\320}% U+1ED0
19533 \DeclareTextCompositeCommand{\d}{PU}{OCIRCUMFLEX}{\9036\330}% U+1ED8
19534 \DeclareTextCompositeCommand{\`}{PU}{OCIRCUMFLEX}{\9036\322}% U+1ED2
19535 \DeclareTextCompositeCommand{\h}{PU}{OCIRCUMFLEX}{\9036\324}% U+1ED4
19536 \DeclareTextCompositeCommand{\~}{PU}{OCIRCUMFLEX}{\9036\326}% U+1ED6
19537 \DeclareTextCompositeCommand{\'}{PU}{OHORN}{\9036\332}% U+1EDA
19538 \DeclareTextCompositeCommand{\d}{PU}{OHORN}{\9036\342}% U+1EE2
19539 \DeclareTextCompositeCommand{\`}{PU}{OHORN}{\9036\334}% U+1EDC
19540 \DeclareTextCompositeCommand{\h}{PU}{OHORN}{\9036\336}% U+1EDE
19541 \DeclareTextCompositeCommand{\~}{PU}{OHORN}{\9036\340}% U+1EE0
19542 \DeclareTextCompositeCommand{\'}{PU}{U}{\80\332}% U+00DA
19543 \DeclareTextCompositeCommand{\d}{PU}{U}{\9036\344}% U+1EE4
19544 \DeclareTextCompositeCommand{\`}{PU}{U}{\80\331}% U+00D9
19545 \DeclareTextCompositeCommand{\h}{PU}{U}{\9036\346}% U+1EE6
19546 \DeclareTextCompositeCommand{\~}{PU}{U}{\81\150}% U+0168
19547 \DeclareTextCompositeCommand{\'}{PU}{UHORN}{\9036\350}% U+1EE8
19548 \DeclareTextCompositeCommand{\d}{PU}{UHORN}{\9036\360}% U+1EF0
19549 \DeclareTextCompositeCommand{\`}{PU}{UHORN}{\9036\352}% U+1EEA
19550 \DeclareTextCompositeCommand{\h}{PU}{UHORN}{\9036\354}% U+1EEC
19551 \DeclareTextCompositeCommand{\~}{PU}{UHORN}{\9036\356}% U+1EEE
19552 \DeclareTextCompositeCommand{\'}{PU}{Y}{\80\335}% U+00DD
19553 \DeclareTextCompositeCommand{\d}{PU}{Y}{\9036\364}% U+1EF4
19554 \DeclareTextCompositeCommand{\`}{PU}{Y}{\9036\362}% U+1EF2
19555 \DeclareTextCompositeCommand{\h}{PU}{Y}{\9036\366}% U+1EF6
19556 \DeclareTextCompositeCommand{\~}{PU}{Y}{\9036\370}% U+1EF8
19557 </puvnenc>

```

46.4 PU encoding, additions for Arabi

This file is provided and maintained by Youssef Jabri.

```

19558 (*puarenc)
19559 % U+0621;afii57409;ARABIC LETTER HAMZA
19560 \DeclareTextCommand{\hamza}{PU}{\86\041}% U+0621
19561 % U+0622;afii57410;ARABIC LETTER ALEF WITH MADDA ABOVE
19562 \DeclareTextCommand{\alefmadda}{PU}{\86\042}% U+0622
19563 % U+0623;afii57411;ARABIC LETTER ALEF WITH HAMZA ABOVE
19564 \DeclareTextCommand{\alefhamza}{PU}{\86\043}% U+0623
19565 % U+0624;afii57412;ARABIC LETTER WAW WITH HAMZA ABOVE
19566 \DeclareTextCommand{\wawhamza}{PU}{\86\044}% U+0624
19567 % U+0625;afii57413;ARABIC LETTER ALEF WITH HAMZA BELOW
19568 \DeclareTextCommand{\aleflowerhamza}{PU}{\86\045}% U+0625
19569 % U+0626;afii57414;ARABIC LETTER YEH WITH HAMZA ABOVE
19570 \DeclareTextCommand{\yahamza}{PU}{\86\046}% U+0626
19571 % U+0627;afii57415;ARABIC LETTER ALEF

```

19572 \DeclareTextCommand{\alef}{PU}{\86\047} % U+0627
19573 % U+0628;afii57416;ARABIC LETTER BEH
19574 \DeclareTextCommand{\baa}{PU}{\86\050} % U+0628
19575 % U+0629;afii57417;ARABIC LETTER TEH MARBUTA
19576 \DeclareTextCommand{\T}{PU}{\86\051} % U+0629
19577 % U+062A;afii57418;ARABIC LETTER TEH
19578 \DeclareTextCommand{\taa}{PU}{\86\052} % U+062A
19579 % U+062B;afii57419;ARABIC LETTER THEH
19580 \DeclareTextCommand{\thaa}{PU}{\86\053} % U+062B
19581 % U+062C;afii57420;ARABIC LETTER JEEM
19582 \DeclareTextCommand{\jeem}{PU}{\86\054} % U+062C
19583 % U+062D;afii57421;ARABIC LETTER HAH
19584 \DeclareTextCommand{\Haa}{PU}{\86\055} % U+062D
19585 % U+062E;afii57422;ARABIC LETTER KHAH
19586 \DeclareTextCommand{\kha}{PU}{\86\056} % U+062E
19587 % U+062F;afii57423;ARABIC LETTER DAL
19588 \DeclareTextCommand{\dal}{PU}{\86\057} % U+062F
19589 % U+0630;afii57424;ARABIC LETTER THAL
19590 \DeclareTextCommand{\dhal}{PU}{\86\060} % U+0630
19591 % U+0631;afii57425;ARABIC LETTER REH
19592 \DeclareTextCommand{\ra}{PU}{\86\061} % U+0631
19593 % U+0632;afii57426;ARABIC LETTER ZAIN
19594 \DeclareTextCommand{\zay}{PU}{\86\062} % U+0632
19595 % U+0633;afii57427;ARABIC LETTER SEEN
19596 \DeclareTextCommand{\seen}{PU}{\86\063} % U+0633
19597 % U+0634;afii57428;ARABIC LETTER SHEEN
19598 \DeclareTextCommand{\sheen}{PU}{\86\064} % U+0634
19599 % U+0635;afii57429;ARABIC LETTER SAD
19600 \DeclareTextCommand{\sad}{PU}{\86\065} % U+0635
19601 % U+0636;afii57430;ARABIC LETTER DAD
19602 \DeclareTextCommand{\dad}{PU}{\86\066} % U+0636
19603 % U+0637;afii57431;ARABIC LETTER TAH
19604 \DeclareTextCommand{\Ta}{PU}{\86\067} % U+0637
19605 % U+0638;afii57432;ARABIC LETTER ZAH
19606 \DeclareTextCommand{\za}{PU}{\86\070} % U+0638
19607 % U+0639;afii57433;ARABIC LETTER AIN
19608 \DeclareTextCommand{\ayn}{PU}{\86\071} % U+0639
19609 % U+063A;afii57434;ARABIC LETTER GHAIN
19610 \DeclareTextCommand{\ghayn}{PU}{\86\072} % U+063A
19611 % U+0640;afii57440;ARABIC TATWEEL
19612 \DeclareTextCommand{\tatweel}{PU}{\86\100} % U+0640
19613 % U+0641;afii57441;ARABIC LETTER FEH
19614 \DeclareTextCommand{\fa}{PU}{\86\101} % U+0641
19615 % U+0642;afii57442;ARABIC LETTER QAF
19616 \DeclareTextCommand{\qaf}{PU}{\86\102} % U+0642
19617 % U+0643;afii57443;ARABIC LETTER KAF
19618 \DeclareTextCommand{\kaf}{PU}{\86\103} % U+0643
19619 % U+0644;afii57444;ARABIC LETTER LAM
19620 \DeclareTextCommand{\lam}{PU}{\86\104} % U+0644
19621 % U+0645;afii57445;ARABIC LETTER MEEM
19622 \DeclareTextCommand{\meem}{PU}{\86\105} % U+0645
19623 % U+0646;afii57446;ARABIC LETTER NOON
19624 \DeclareTextCommand{\nun}{PU}{\86\106} % U+0646
19625 % U+0647;afii57470;ARABIC LETTER HEH

```

19626 \DeclareTextCommand{\ha}{\PU}{\86\107}% U+0647
19627 % U+0648;afii57448;ARABIC LETTER WAW
19628 \DeclareTextCommand{\waw}{\PU}{\86\110}% U+0648
19629 % U+0649;afii57449;ARABIC LETTER ALEF MAKSURA
19630 \DeclareTextCommand{\alefmaqsura}{\PU}{\86\111}% U+0649
19631 % U+064A;afii57450;ARABIC LETTER YEH
19632 \DeclareTextCommand{\ya}{\PU}{\86\112}% U+064A

19633 % U+064B;afii57451;ARABIC FATHATAN
19634 \DeclareTextCommand{\nasb}{\PU}{\86\113}% U+064B
19635 % U+064C;afii57452;ARABIC DAMMATAN
19636 \DeclareTextCommand{\raff}{\PU}{\86\114}% U+064C
19637 % U+064D;afii57453;ARABIC KASRATAN
19638 \DeclareTextCommand{\jarr}{\PU}{\86\115}% U+064D
19639 % U+064E;afii57454;ARABIC FATHA
19640 \DeclareTextCommand{\fatha}{\PU}{\86\116}% U+064E
19641 % U+064F;afii57455;ARABIC DAMMA
19642 \DeclareTextCommand{\damma}{\PU}{\86\117}% U+064F
19643 % U+0650;afii57456;ARABIC KASRA
19644 \DeclareTextCommand{\kasra}{\PU}{\86\120}% U+0650
19645 % U+0651;afii57457;ARABIC SHADDA
19646 \DeclareTextCommand{\shadda}{\PU}{\86\121}% U+0651
19647 % U+0652;afii57458;ARABIC SUKUN
19648 \DeclareTextCommand{\sukun}{\PU}{\86\122}% U+0652

Farsi

19649 % U+067E ARABIC LETTER PEH; afii57506
19650 \DeclareTextCommand{\peh}{\PU}{\86\176}% U+067E
19651 % U+0686 ARABIC LETTER TCHEH; afii57507
19652 \DeclareTextCommand{\tcheh}{\PU}{\86\206}% U+0686
19653 % U+0698 ARABIC LETTER JEH; afii57508
19654 \DeclareTextCommand{\jeh}{\PU}{\86\230}% U+0698
19655 % U+06A9 ARABIC LETTER KEHEH
19656 \DeclareTextCommand{\farsikaf}{\PU}{\86\251}% U+06A9
19657 % U+06AF ARABIC LETTER GAF; afii57509
19658 \DeclareTextCommand{\gaf}{\PU}{\86\257}% U+06AF
19659 % U+06CC ARABIC LETTER FARSI YEH
19660 \DeclareTextCommand{\farsiya}{\PU}{\86\314}% U+06CC

19661 % U+200C ZERO WIDTH NON-JOINER; afii61664
19662 \DeclareTextCommand{\ZWNJ}{\PU}{\9040\014}% U+200C
19663 % U+200D ZERO WIDTH JOINER; afii301
19664 \DeclareTextCommand{\textEncodingNoboundary}{\PU}{\9040\015}% U+200D
19665 </puarenc>

19666 <*psdextra>
19667 \Hy@VersionCheck{psdextra.def}
19668 \DeclareTextCommand{\textGamma}{\PU}{\83\223}/* U+0393
19669 \DeclareTextCommand{\textDelta}{\PU}{\83\224}/* U+0394
19670 \DeclareTextCommand{\textTheta}{\PU}{\83\230}/* U+0398
19671 \DeclareTextCommand{\textLambda}{\PU}{\83\233}/* U+039B
19672 \DeclareTextCommand{\textXi}{\PU}{\83\236}/* U+039E
19673 \DeclareTextCommand{\textPi}{\PU}{\83\240}/* U+03A0
19674 \DeclareTextCommand{\textSigma}{\PU}{\83\243}/* U+03A3
19675 \DeclareTextCommand{\textUpsilon}{\PU}{\83\245}/* U+03A5
19676 \DeclareTextCommand{\textPhi}{\PU}{\83\246}/* U+03A6

```

```

19677 \DeclareTextCommand{\textChi}{PU}{\83\247}%
19678 \DeclareTextCommand{\textPsi}{PU}{\83\250}%
19679 \DeclareTextCommand{\textOmega}{PU}{\83\251}%
19680 \DeclareTextCommand{\textAlpha}{PU}{\83\261}%
19681 \DeclareTextCommand{\textBeta}{PU}{\83\262}%
19682 \DeclareTextCommand{\textGamma}{PU}{\83\263}%
19683 \DeclareTextCommand{\textDelta}{PU}{\83\264}%
19684 \DeclareTextCommand{\textEpsilon}{PU}{\83\265}%
19685 \DeclareTextCommand{\textZeta}{PU}{\83\266}%
19686 \DeclareTextCommand{\textEta}{PU}{\83\267}%
19687 \DeclareTextCommand{\textTheta}{PU}{\83\270}%
19688 \DeclareTextCommand{\textIota}{PU}{\83\271}%
19689 \DeclareTextCommand{\textKappa}{PU}{\83\272}%
19690 \DeclareTextCommand{\textLambda}{PU}{\83\273}%
19691 \DeclareTextCommand{\textMuGreek}{PU}{\83\274}%
19692 \DeclareTextCommand{\textNu}{PU}{\83\275}%
19693 \DeclareTextCommand{\textXi}{PU}{\83\276}%
19694 \DeclareTextCommand{\textPi}{PU}{\83\300}%
19695 \DeclareTextCommand{\textRho}{PU}{\83\301}%
19696 \DeclareTextCommand{\textVarsigma}{PU}{\83\302}%
19697 \DeclareTextCommand{\textSigma}{PU}{\83\303}%
19698 \DeclareTextCommand{\textTau}{PU}{\83\304}%
19699 \DeclareTextCommand{\textUpsilon}{PU}{\83\305}%
19700 \DeclareTextCommand{\textPhi}{PU}{\83\306}%
19701 \DeclareTextCommand{\textChi}{PU}{\83\307}%
19702 \DeclareTextCommand{\textPsi}{PU}{\83\310}%
19703 \DeclareTextCommand{\textOmega}{PU}{\83\311}%
19704 \newcommand*\psdmapshortnames{%
19705   \let\MVPlus\textMVPlus
19706   \let\MCComma\textMCComma
19707   \let\MMinus\textMMinus
19708   \let\MPPeriod\textMPPeriod
19709   \let\MDivision\textMDivision
19710   \let\Zero\textZero
19711   \let\One\textOne
19712   \let\Two\textTwo
19713   \let\Three\textThree
19714   \let\Four\textFour
19715   \let\Five\textFive
19716   \let\Six\textSix
19717   \let\Seven\textSeven
19718   \let\Eight\textEight
19719   \let\Nine\textNine
19720   \let\At\textAt
19721   \let\Copyright\textCopyright
19722   \let\twosuperior\texttwosuperior
19723   \let\threesuperior\textthreesuperior
19724   \let\onesuperior\textonesuperior
19725   \let\Thorn\textThorn
19726   \let\thorn\textthorn
19727   \let\hbar\texthbar
19728   \let\hausaB\textausaB
19729   \let\hausaD\textausaD
19730   \let\hausaK\textausaK

```

```
19731 \let\barl\textbarl
19732 \let\inve\textinve
19733 \let\slashc\textslashc
19734 \let\scripta\textscripta
19735 \let\openo\textopeno
19736 \let\rtaild\textrtaild
19737 \let\reve\textreve
19738 \let\schwa\textschwa
19739 \let\niepsilon\textniepsilon
19740 \let\revepsilon\textrevepsilon
19741 \let\rhookrevesilon\textrhookrevesilon
19742 \let\scriptg\textscriptg
19743 \let\scg\textscg
19744 \let\ipagamma\textipagamma
19745 \let\babypgamma\textbabypgamma
19746 \let\bari\textbari
19747 \let\niota\textniota
19748 \let\sci\textsci
19749 \let\scn\textscn
19750 \let\niphi\textniph
19751 \let\longlegr\textlonglegr
19752 \let\scr\textscr
19753 \let\invscr\textinvscr
19754 \let\esh\textesh
19755 \let\baru\textbaru
19756 \let\niupsilon\textniupsilon
19757 \let\scriptv\textscriptv
19758 \let\turnv\textturnv
19759 \let\turnw\textturnw
19760 \let\turny\textturny
19761 \let\scy\textscy
19762 \let\yogh\textyogh
19763 \let\glotstop\textglotstop
19764 \let\revglotstop\textrevglotstop
19765 \let\invglotstop\textinvglotstop
19766 \let\Gamma\textGamma
19767 \let\Delta\textDelta
19768 \let\Theta\textTheta
19769 \let\Lambda\textLambda
19770 \let\Xi\textXi
19771 \let\Pi\textPi
19772 \let\Sigma\textSigma
19773 \let\Upsilon\textUpsilon
19774 \let\Phi\textPhi
19775 \let\Psi\textPsi
19776 \let\Omega\textOmega
19777 \let\alpha\textalpha
19778 \let\beta\textbeta
19779 \let\gamma\textgamma
19780 \let\delta\textdelta
19781 \let\epsilon\textepsilon
19782 \let\zeta\textzeta
19783 \let\eta\texteta
19784 \let\theta\texttheta
```

```

19785 \let\iota\textiota
19786 \let\kappa\textkappa
19787 \let\lambda\textlambda
19788 \let\mu\textmu
19789 \let\mu\textmu
19790 \let\nu\textnu
19791 \let\xi\textxi
19792 \let\pi\textpi
19793 \let\rho\textrho
19794 \let\sigma\textsigma
19795 \let\sigma\textsigma
19796 \let\tau\texttau
19797 \let\upsilon\textupsilon
19798 \let\phi\textphi
19799 \let\chi\textchi
19800 \let\psi\textpsi
19801 \let\omega\textomega
19802 \let\varsigma\textvarsigma
19803 \let\scu\textscu
19804 \let\iinferior\textiinferior
19805 \let\rinferior\textrinferior
19806 \let\uinferior\textuinferior
19807 \let\vinferior\textvinferior
19808 \let\bainferior\textbainferior
19809 \let\gmainferior\textgmainferior
19810 \let\rho\textrho
19811 \let\phi\textphi
19812 \let\chi\textchi
19813 \let\barsci\textbarsci
19814 \let\barp\textbarp
19815 \let\barscu\textbarscu
19816 \let\httaild\texthttaild
19817 \let\dagger\textdagger
19818 \let\bullet\textbullet
19819 \let\hdotfor\texthdotfor
19820 \let\prime\textprime
19821 \let\second\textsecond
19822 \let\third\textthird
19823 \let\backprime\textbackprime
19824 \let\lefttherefore\textlefttherefore
19825 \let\fourth\textfourth
19826 \let\diamondddots\textdiamondddots
19827 \let\zerosuperior\textzerosuperior
19828 \let\isuperior\textisuperior
19829 \let\foursuperior\textfoursuperior
19830 \let\fivesuperior\textfivesuperior
19831 \let\sixsuperior\textsixsuperior
19832 \let\sevensuperior\textsevensuperior
19833 \let\eightsuperior\texteightsuperior
19834 \let\ninesuperior\textninesuperior
19835 \let\plussuperior\textplussuperior
19836 \let\minussuperior\textminussuperior
19837 \let>equalsuperior\textqualsuperior
19838 \let\parenleftsuperior\textparenleftsuperior

```

```

19839 \let\parenrightsuperior\textparenrightsuperior
19840 \let\nsuperior\textnsuperior
19841 \let\zeroinferior\textzeroinferior
19842 \let\oneinferior\textoneinferior
19843 \let\twoinferior\texttwoinferior
19844 \let\threeinferior\textthreeinferior
19845 \let\fourinferior\textfourinferior
19846 \let\fiveinferior\textfiveinferior
19847 \let\sixinferior\textsixinferior
19848 \let\seveninferior\textseveninferior
19849 \let\eightinferior\texteightinferior
19850 \let\nineinferior\textnineinferior
19851 \let\plusinferior\textplusinferior
19852 \let\minusinferior\textminusinferior
19853 \let>equalsinferior\textequalsinferior
19854 \let\parenleftinferior\textparenleftinferior
19855 \let\parenrightinferior\textparenrightinferior
19856 \let\ainferior\textainferior
19857 \let\einferior\texteinferior
19858 \let\oinferior\textoinferior
19859 \let\xinferior\textxinferior
19860 \let\schwainferior\textschwainferior
19861 \let\hinferior\texthinferior
19862 \let\kinferior\textkinferior
19863 \let\linferior\textlinferior
19864 \let\minferior\textminferior
19865 \let\ninferior\textninferior
19866 \let\pinferior\textpinferior
19867 \let\sinferior\textsinferior
19868 \let\tinferior\texttinferior
19869 \let\Deleatur\textDeleatur
19870 \let\hslash\texthslash
19871 \let\Im\textIm
19872 \let\ell\textell
19873 \let\wp\textwp
19874 \let\Re\textRe
19875 \let\mho\textmho
19876 \let\riota\textriota
19877 \let\Finv\textFinv
19878 \let\aleph\textaleph
19879 \let\beth\textbeth
19880 \let\gimel\textgimel
19881 \let\daleth\textdaleth
19882 \let\fax\textfax
19883 \let\Game\textGame
19884 \let\leftarrow\textleftarrow
19885 \let\uparrow\textuparrow
19886 \let\rightarrow\textrightarrow
19887 \let\downarrow\textdownarrow
19888 \let\leftrightarrow\textleftrightarrow
19889 \let\updownarrow\textupdownarrow
19890 \let\downarrow\textdownarrow
19891 \let\rightarrow\textrightarrow
19892 \let\leftarrow\textleftarrow

```

```

19893 \let\swarrow\textswarrow
19894 \let\nleftarrow\textnleftarrow
19895 \let\nrightarrow\textnrightarrow
19896 \let\twoheadleftarrow\texttwoheadleftarrow
19897 \let\ntwoheadleftarrow\textntwoheadleftarrow
19898 \let\twoheaduparrow\texttwoheaduparrow
19899 \let\twoheadrightarrow\texttwoheadrightarrow
19900 \let\ntwoheadrightarrow\textntwoheadrightarrow
19901 \let\twoheaddownarrow\texttwoheaddownarrow
19902 \let\leftarrowtail\textleftarrowtail
19903 \let\rightarrowtail\textrightarrowtail
19904 \let\mapsto\textmapsto
19905 \let\hookleftarrow\texthookleftarrow
19906 \let\hookrightarrow\texthookrightarrow
19907 \let\looparrowleft\textlooparrowleft
19908 \let\looparrowright\textlooparrowright
19909 \let\nleftrightarrow\textnleftrightarrow
19910 \let\lightning\textlightning
19911 \let\dlsh\textdlsh
19912 \let\curvearrowleft\textcurvearrowleft
19913 \let\curvearrowright\textcurvearrowright
19914 \let\leftharpoonup\textleftharpoonup
19915 \let\leftharpoondown\textleftharpoondown
19916 \let\upharpoonright\textupharpoonright
19917 \let\upharpoonleft\textupharpoonleft
19918 \let\rightharpoonup\textrightharpoonup
19919 \let\rightharpoondown\textrightharpoondown
19920 \let\downharpoonright\textdownharpoonright
19921 \let\downharpoonleft\textdownharpoonleft
19922 \let\rightleftarrows\textrightleftarrows
19923 \let\updownarrows\textupdownarrows
19924 \let\leftrightarrows\textleftrightarrows
19925 \let\leftleftarrows\textleftleftarrows
19926 \let\upuparrows\textupuparrows
19927 \let\rightrightarrows\textrightrightarrows
19928 \let\downdownarrows\textdowndownarrows
19929 \let\leftrightharpoons\textleftrightharpoons
19930 \let\rightleftharpoons\textrightleftharpoons
19931 \let\nLeftarrow\textnLeftarrow
19932 \let\nLeftrightarrow\textnLeftrightarrow
19933 \let\nRightarrow\textnRightarrow
19934 \let\Leftarrow\textLeftarrow
19935 \let\Uparrow\textUparrow
19936 \let\Rightarrow\textRightarrow
19937 \let\Downarrow\textDownarrow
19938 \let\Leftrightarrow\textLeftrightarrow
19939 \let\Updownarrow\textUpdownarrow
19940 \let\Narrow\textNarrow
19941 \let\Nearrow\textNearrow
19942 \let\Searrow\textSearrow
19943 \let\Swarrow\textSwarrow
19944 \let\Lleftarrow\textLleftarrow
19945 \let\Rrightarrow\textRrightarrow
19946 \let\leftsquigarrow\textleftsquigarrow

```

```

19947 \let\rightsquigarrow\textrightsquigarrow
19948 \let\dashleftarrow\textdashleftarrow
19949 \let\dasheduparrow\textdasheduparrow
19950 \let\dashrightarrow\textdashrightarrow
19951 \let\dasheddownarrow\textdasheddownarrow
19952 \let\pointer\textrpointer
19953 \let\downuparrows\textrdownuparrows
19954 \let\leftarrowtriangle\textrightarrowtriangle
19955 \let\rightarrowtriangle\textrrightarrowtriangle
19956 \let\leftrightarrowtriangle\textrightarrowtriangle
19957 \let\forall\textrforall
19958 \let\complement\textrcomplement
19959 \let\partial\textrpartial
19960 \let\exists\textrexists
19961 \let\nexists\textrnexists
19962 \let\emptyset\textremptyset
19963 \let\triangle\textrtriangle
19964 \let\nabla\textrnabla
19965 \let\in\textrin
19966 \let\notin\textrnotin
19967 \let\smallin\textrsmallin
19968 \let\in\textrni
19969 \let\notowner\textrnotowner
19970 \let\smallowns\textrsmallowns
19971 \let\prod\textrprod
19972 \let\amalg\textramalg
19973 \let\sum\textrsum
19974 \let\mp\textrmp
19975 \let\dotplus\textrdotplus
19976 \let\Divides\textrDivides
19977 \let\DividesNot\textrDividesNot
19978 \let\setminus\textrsetminus
19979 \let\ast\textrast
19980 \let\circ\textrcirc
19981 \let\surd\textrsurd
19982 \let\propto\textrpropto
19983 \let\infty\textrinfinity
19984 \let\angle\textrangle
19985 \let\measuredangle\textrmeasuredangle
19986 \let\sphericalangle\textrsphericalangle
19987 \let\mid\textrmid
19988 \let\nmid\textrnmid
19989 \let\parallel\textrparallel
19990 \let\nparallel\textrnparallel
19991 \let\wedge\textrwedge
19992 \let\owedge\textrowedge
19993 \let\vee\textrvee
19994 \let\ovee\textrovee
19995 \let\cap\textrcap
19996 \let\cup\textrcup
19997 \let\int\textrint
19998 \let\iint\textriint
19999 \let\iiint\textriiint
20000 \let\oint\textroint

```

```

20001 \let\oiint\textoiint
20002 \let\ointclockwise\textointclockwise
20003 \let\ointctr-clockwise\textointctr-clockwise
20004 \let\therefore\texttherefore
20005 \let\because\textbecause
20006 \let\vdotdot\textvdotdot
20007 \let\squaredots\textsquaredots
20008 \let\dotminus\textdotminus
20009 \let\eqcolon\texteqcolon
20010 \let\sim\textsim
20011 \let\backsim\textbacksim
20012 \let\nbacksim\textnbacksim
20013 \let\wr\textwr
20014 \let\nsim\textnsim
20015 \let\eqsim\texteqsim
20016 \let\neqsim\textneqsim
20017 \let\simeq\textsimeq
20018 \let\nsimeq\textnsimeq
20019 \let\cong\textcong
20020 \let\ncong\textncong
20021 \let\approx\textapprox
20022 \let\napprox\textnapprox
20023 \let\approxeq\textapproxeq
20024 \let\napproxeq\textnapproxeq
20025 \let\triplesim\texttriplesim
20026 \let\ntriplesim\textntriplesim
20027 \let\backcong\textbackcong
20028 \let\nbackcong\textnbackcong
20029 \let\asymp\textasymp
20030 \let\nasymp\textnasym
20031 \let\Bumpeq\textBumpeq
20032 \let\nBumpeq\textnBumpeq
20033 \let\bumpeq\textbumpeq
20034 \let\nbumpeq\textnbumpeq
20035 \let\doteq\textdoteq
20036 \let\ndoteq\textndoteq
20037 \let\doteqdot\textdoteqdot
20038 \let\nDoteq\textnDoteq
20039 \let\fallingdoteq\textfallingdoteq
20040 \let\nfallingdoteq\textnfallingdoteq
20041 \let\risingdoteq\textrisingdoteq
20042 \let\nrisingdoteq\textnrisingdoteq
20043 \let\colonequals\textcolonequals
20044 \let\equalscolon\textequalscolon
20045 \let\eqcirc\texteqcirc
20046 \let\neqcirc\textneqcirc
20047 \let\circeq\textcirceq
20048 \let\ncirceq\textncirceq
20049 \let\hateq\texthateq
20050 \let\nhateq\textnhateq
20051 \let\triangleeq\texttriangleeq
20052 \let\neq\textneq
20053 \let\ne\textne
20054 \let\equiv\textequiv

```

```

20055 \let\nequiv\textnequiv
20056 \let\leq\textleq
20057 \let\leqslant\textleqslant
20058 \let\geq\textgeq
20059 \let\geqslant\textgeqslant
20060 \let\leqslant\textleqslant
20061 \let\nleqslant\textnleqslant
20062 \let\geqslant\textgeqslant
20063 \let\ngeqslant\textngeqslant
20064 \let\lneq\textlneq
20065 \let\gneq\textgneq
20066 \let\ll\textll
20067 \let\lneq\textlneq
20068 \let\gg\textgg
20069 \let\ngg\textngg
20070 \let\between\textbetween
20071 \let\nless\textnless
20072 \let\ngtr\textngtr
20073 \let\nleq\textnleq
20074 \let\ngtr\textngtr
20075 \let\lessim\textlessim
20076 \let\gtrsim\textgtrsim
20077 \let\nlessim\textnlessim
20078 \let\ngtrsim\textngtrsim
20079 \let\lessgr\textlessgr
20080 \let\gtrless\textgtrless
20081 \let\ngtrless\textngtrless
20082 \let\nlessgr\textnlessgr
20083 \let\prec\textprec
20084 \let\succ\textsucc
20085 \let\preccurlyeq\textpreccurlyeq
20086 \let\succcurlyeq\textsucccurlyeq
20087 \let\precsim\textprecsim
20088 \let\nprecsim\textnprecsim
20089 \let\sucessim\textsucessim
20090 \let\nsucessim\textnsucessim
20091 \let\nprec\textnprec
20092 \let\nsucc\textnsucc
20093 \let\subset\textsubset
20094 \let\supset\textsupset
20095 \let\nsubset\textnsubset
20096 \let\nsupset\textnsupset
20097 \let\subsetneq\textsubsetneq
20098 \let\supsetneq\textsupsetneq
20099 \let\nsubsetneq\textnsubsetneq
20100 \let\nsupsetneq\textnsupsetneq
20101 \let\subsetneq\textsubsetneq
20102 \let\supsetneq\textsupsetneq
20103 \let\cupdot\textcupdot
20104 \let\cupplus\textcupplus
20105 \let\sqsubset\textsqsubset
20106 \let\sqsupset\textsqsupset
20107 \let\sqsupset\textsqsupset
20108 \let\sqsupset\textsqsupset

```

```

20109 \let\sqsubsetseteq\textsqsubsetseteq
20110 \let\nsqsubsetseteq\textnsqsubsetseteq
20111 \let\sqsupseteq\textsqsupseteq
20112 \let\nsqsupseteq\textnsqsupseteq
20113 \let\sqcap\textsqcap
20114 \let\sqcup\textsqcup
20115 \let\oplus\textoplus
20116 \let\ominus\textominus
20117 \let\otimes\textotimes
20118 \let\oslash\textoslash
20119 \let\odot\textodot
20120 \let\circledcirc\textcircledcirc
20121 \let\circledast\textcircledast
20122 \let\circleddash\textcircleddash
20123 \let\boxplus\textboxplus
20124 \let\boxminus\textboxminus
20125 \let\boxtimes\textboxtimes
20126 \let\boxdot\textboxdot
20127 \let\vdash\textvdash
20128 \let\dashv\textdashv
20129 \let\ndashv\textndashv
20130 \let\top\texttop
20131 \let\ndownv\textndownv
20132 \let\bot\textbot
20133 \let\nupv\textnupv
20134 \let\vDash\textvDash
20135 \let\Vdash\textVdash
20136 \let\Vvdash\textVvdash
20137 \let\nVdash\textnVdash
20138 \let\VDash\textVDash
20139 \let\nvDash\textnvDash
20140 \let\ nvDash\text nvDash
20141 \let\ nVdash\textnVdash
20142 \let\ nVDash\textnVDash
20143 \let\lhd\textlhd
20144 \let\rhd\textrhd
20145 \let\unlhd\textunlhd
20146 \let\unrhd\textunrhd
20147 \let\multimapdotbothA\textmultimapdotbothA
20148 \let\multimapdotbothB\textmultimapdotbothB
20149 \let\multimap\textmultimap
20150 \let\veebar\textveebar
20151 \let\barwedge\textbarwedge
20152 \let\star\textstar
20153 \let\divideontimes\textdivideontimes
20154 \let\bowtie\textbowtie
20155 \let\ltimes\textltimes
20156 \let\rtimes\textrtimes
20157 \let\leftthreetimes\textleftthreetimes
20158 \let\rightthreetimes\textrightthreetimes
20159 \let\backsimeq\textbacksimeq
20160 \let\nbacksimeq\textnbacksimeq
20161 \let\curlyvee\textcurlyvee
20162 \let\curlywedge\textcurlywedge

```

```

20163 \let\Subset\textSubset
20164 \let\nSubset\textnSubset
20165 \let\Supset\textSupset
20166 \let\nSupset\textnSupset
20167 \let\Cap\textCap
20168 \let\Cup\textCup
20169 \let\pitchfork\textpitchfork
20170 \let\lessdot\textlessdot
20171 \let\gtrdot\textgtrdot
20172 \let\lll\textlll
20173 \let\ggg\textggg
20174 \let\lesseqgr\textlesseqgr
20175 \let\gtreqless\textgtreqless
20176 \let\curlyeqprec\textcurlyeqprec
20177 \let\ncurlyeqprec\textncurlyeqprec
20178 \let\curlyeqsucc\textcurlyeqsucc
20179 \let\ncurlyeqsucc\textncurlyeqsucc
20180 \let\preccurlyeq\textnpreccurlyeq
20181 \let\nsucccurlyeq\textnsucccurlyeq
20182 \let\nqsubseteq\textnqsubseteq
20183 \let\nqsupseteq\textnqsupseteq
20184 \let\sqsubsetneq\textsqsubsetneq
20185 \let\sqsupsetneq\textsqsupsetneq
20186 \let\lnsim\textlnsim
20187 \let\gnsim\textgnsim
20188 \let\precnsim\textprecnsim
20189 \let\succnsim\textsuccnsim
20190 \let\ntriangleleft\textntriangleleft
20191 \let\ntriangleright\textntriangleright
20192 \let\ntrianglelefteq\textntrianglelefteq
20193 \let\ntrianglerighteq\textntrianglerighteq
20194 \let\vdots\textvdots
20195 \let\cdots\textcdots
20196 \let\udots\textudots
20197 \let\ddots\textddots
20198 \let\barin\textbarin
20199 \let\diameter\textdiameter
20200 \let\backneg\textbackneg
20201 \let\wasylozenge\textwasylozenge
20202 \let\invbackneg\textinvbackneg
20203 \let\clock\textclock
20204 \let\ulcorner\textulcorner
20205 \let\urcorner\texturcorner
20206 \let\llcorner\textllcorner
20207 \let\lrcorner\textlrcorner
20208 \let\frown\textfrown
20209 \let\smile\textsmile
20210 \let\Keyboard\textKeyboard
20211 \let\langle\textlangle
20212 \let\rangle\textrangle
20213 \let\APLinv\textAPLinv
20214 \let\Tumbler\textTumbler
20215 \let\notslash\textnotslash
20216 \let\notbackslash\textnotbackslash

```

```
20217 \let\boxbackslash\textboxbackslash
20218 \let\APLeftarrowbox\textAPLeftarrowbox
20219 \let\APRightarrowbox\textAPRightarrowbox
20220 \let\APLuparrowbox\textAPLuparrowbox
20221 \let\APLdownarrowbox\textAPLdownarrowbox
20222 \let\APLinput\textAPLinput
20223 \let\Request\textRequest
20224 \let\Beam\textBeam
20225 \let\hexagon\texthexagon
20226 \let\APLbox\textAPLbox
20227 \let\ForwardToIndex\textForwardToIndex
20228 \let\RewindToIndex\textRewindToIndex
20229 \let\bbslash\textbbslash
20230 \let\CircledA\textCircledA
20231 \let\CleaningF\textCleaningF
20232 \let\CleaningFF\textCleaningFF
20233 \let\CleaningP\textCleaningP
20234 \let\CleaningPP\textCleaningPP
20235 \let\CuttingLine\textCuttingLine
20236 \let\UParrow\textUParrow
20237 \let\bigtriangleup\textbigtriangleup
20238 \let\Forward\textForward
20239 \let\triangleright\texttriangleright
20240 \let\RHD\textRHD
20241 \let\DOWNarrow\textDOWNarrow
20242 \let\bigtriangledown\textbigtriangledown
20243 \let\Rewind\textRewind
20244 \let\triangleleft\texttriangleleft
20245 \let\LHD\textLHD
20246 \let\diamond\textdiamond
20247 \let\lozenge\textlozenge
20248 \let\LEFTCIRCLE\textLEFTCIRCLE
20249 \let\RIGHTCIRCLE\textRIGHTCIRCLE
20250 \let\openbullet\textopenbullet
20251 \let\boxbar\textboxbar
20252 \let\bigcircle\textbigcircle
20253 \let\Cloud\textCloud
20254 \let\FiveStar\textFiveStar
20255 \let\FiveStarOpen\textFiveStarOpen
20256 \let\Phone\textPhone
20257 \let\boxempty\textboxempty
20258 \let\Checkedbox\textCheckedbox
20259 \let\Crossedbox\textCrossedbox
20260 \let\Coffeecup\textCoffeecup
20261 \let\HandCuffLeft\textHandCuffLeft
20262 \let\HandCuffRight\textHandCuffRight
20263 \let\HandLeft\textHandLeft
20264 \let\HandRight\textHandRight
20265 \let\Radioactivity\textRadioactivity
20266 \let\Biohazard\textBiohazard
20267 \let\Ankh\textAnkh
20268 \let\YinYang\textYinYang
20269 \let\frownie\textfrownie
20270 \let\smiley\textsmiley
```

```
20271 \let\blacksmiley{textblacksmiley}
20272 \let\sun{textsun}
20273 \let\leftmoon{textleftmoon}
20274 \let\rightmoon{textrightmoon}
20275 \let\mercury{textmercury}
20276 \let\earth{textearth}
20277 \let\male{textmale}
20278 \let\jupiter{textjupiter}
20279 \let\saturn{textsaturn}
20280 \let\uranus{texturanus}
20281 \let\neptune{textneptune}
20282 \let\pluto{textpluto}
20283 \let\aries{textaries}
20284 \let\taurus{texttaurus}
20285 \let\gemini{textgemini}
20286 \let\cancer{textcancer}
20287 \let\leo{textleo}
20288 \let\virgo{textvirgo}
20289 \let\libra{textlibra}
20290 \let\scorpio{textscorpio}
20291 \let\sagittarius{textsagittarius}
20292 \let\capricornus{textcapricornus}
20293 \let\aquarius{textaquarius}
20294 \let\pisces{textpisces}
20295 \let\quarternote{textquarternote}
20296 \let\twonotes{texttwonotes}
20297 \let\sixteenthnote{textsixteenthnote}
20298 \let\flat{textflat}
20299 \let\natural{textnatural}
20300 \let\sharp{textsharp}
20301 \let\recycle{textrecycle}
20302 \let\Wheelchair{textWheelchair}
20303 \let\Flag{textFlag}
20304 \let\MineSign{textMineSign}
20305 \let\dsmilitary{textdsmilitary}
20306 \let\dsmedical{textdsmedical}
20307 \let\dsjuridical{textdsjuridical}
20308 \let\dschemical{textdschemical}
20309 \let\dsbiological{textdsbiological}
20310 \let\dscommercial{textdscommercial}
20311 \let\manstar{textmanstar}
20312 \let\danger{textdanger}
20313 \let\FemaleFemale{textFemaleFemale}
20314 \let\MaleMale{textMaleMale}
20315 \let\FemaleMale{textFemaleMale}
20316 \let\Hermaphrodite{textHermaphrodite}
20317 \let\Neutral{textNeutral}
20318 \let\hexstar{texthexstar}
20319 \let\SunCload{textSunCload}
20320 \let\Rain{textRain}
20321 \let\noway{textnoway}
20322 \let\Mountain{textMountain}
20323 \let\Tent{textTent}
20324 \let\ScissorRight{textScissorRight}
```

```
20325 \let\ScissorRightBrokenTop{textScissorRightBrokenTop}
20326 \let\ScissorHollowRight{textScissorHollowRight}
20327 \let\PhoneHandset{textPhoneHandset}
20328 \let\Tape{textTape}
20329 \let\Plane{textPlane}
20330 \let\Envelope{textEnvelope}
20331 \let\Peace{textPeace}
20332 \let\WritingHand{textWritingHand}
20333 \let\PencilRightDown{textPencilRightDown}
20334 \let\PencilRight{textPencilRight}
20335 \let\PencilRightUp{textPencilRightUp}
20336 \let\NibRight{textNibRight}
20337 \let\NibSolidRight{textNibSolidRight}
20338 \let\Checkmark{textCheckmark}
20339 \let\CheckmarkBold{textCheckmarkBold}
20340 \let\XSolid{textXSolid}
20341 \let\XSolidBold{textXSolidBold}
20342 \let\XSolidBrush{textXSolidBrush}
20343 \let\PlusOutline{textPlusOutline}
20344 \let\Plus{textPlus}
20345 \let\PlusThinCenterOpen{textPlusThinCenterOpen}
20346 \let\PlusCenterOpen{textPlusCenterOpen}
20347 \let\Cross{textCross}
20348 \let\CrossOpenShadow{textCrossOpenShadow}
20349 \let\CrossOutline{textCrossOutline}
20350 \let\CrossMaltese{textCrossMaltese}
20351 \let\DavidStar{textDavidStar}
20352 \let\FourAsterisk{textFourAsterisk}
20353 \let\JackStar{textJackStar}
20354 \let\JackStarBold{textJackStarBold}
20355 \let\ClowerTips{textClowerTips}
20356 \let\FourStar{textFourStar}
20357 \let\FourStarOpen{textFourStarOpen}
20358 \let\FiveStarOpenCircled{textFiveStarOpenCircled}
20359 \let\FiveStarCenterOpen{textFiveStarCenterOpen}
20360 \let\FiveStarOpenDotted{textFiveStarOpenDotted}
20361 \let\FiveStarOutline{textFiveStarOutline}
20362 \let\FiveStarOutlineHeavy{textFiveStarOutlineHeavy}
20363 \let\FiveStarConvex{textFiveStarConvex}
20364 \let\FiveStarShadow{textFiveStarShadow}
20365 \let\AsteriskBold{textAsteriskBold}
20366 \let\AsteriskCenterOpen{textAsteriskCenterOpen}
20367 \let\EightStarTaper{textEightStarTaper}
20368 \let\EightStarConvex{textEightStarConvex}
20369 \let\SixStar{textSixStar}
20370 \let\EightStar{textEightStar}
20371 \let\EightStarBold{textEightStarBold}
20372 \let\TwelveStar{textTwelveStar}
20373 \let\SixteenStarLight{textSixteenStarLight}
20374 \let\SixFlowerPetalRemoved{textSixFlowerPetalRemoved}
20375 \let\SixFlowerOpenCenter{textSixFlowerOpenCenter}
20376 \let\Asterisk{textAsterisk}
20377 \let\SixFlowerAlternate{textSixFlowerAlternate}
20378 \let\FiveFlowerPetal{textFiveFlowerPetal}
```

```

20379 \let\FiveFlowerOpen\textFiveFlowerOpen
20380 \let\EightFlowerPetal\textEightFlowerPetal
20381 \let\SunshineOpenCircled\textSunshineOpenCircled
20382 \let\SixFlowerAltPetal\textSixFlowerAltPetal
20383 \let\SnowflakeChevron\textSnowflakeChevron
20384 \let\Snowflake\textSnowflake
20385 \let\SnowflakeChevronBold\textSnowflakeChevronBold
20386 \let\Sparkle\textSparkle
20387 \let\SparkleBold\textSparkleBold
20388 \let\AsteriskRoundedEnds\textAsteriskRoundedEnds
20389 \let\EightFlowerPetalRemoved\textEightFlowerPetalRemoved
20390 \let\EightAsterisk\textEightAsterisk
20391 \let\CircleShadow\textCircleShadow
20392 \let\SquareShadowBottomRight\textSquareShadowBottomRight
20393 \let\SquareTopRight\textSquareTopRight
20394 \let\SquareCastShadowBottomRight\textSquareCastShadowBottomRight
20395 \let\SquareCastShadowTopRight\textSquareCastShadowTopRight
20396 \let\DiamondSolid\textDiamondSolid
20397 \let\RectangleThin\textRectangleThin
20398 \let\Rectangle\textRectangle
20399 \let\RectangleBold\textRectangleBold
20400 \let\perp\textperp
20401 \let\notperp\textnotperp
20402 \let\veedot\textveedot
20403 \let\wedgedot\textwedgedot
20404 \let\leftspoon\textleftspoon
20405 \let\lbrackdbl\textlbrackdbl
20406 \let\rbrackdbl\textrbrackdbl
20407 \let\circlearrowleft\textcirclearrowleft
20408 \let\circlearrowright\textcirclearrowright
20409 \let\longleftarrow\textlongleftarrow
20410 \let\longrightarrow\textlongrightarrow
20411 \let\longleftrightarrow\textlongleftrightarrow
20412 \let\Longleftarrow\textLongleftarrow
20413 \let\Longrightarrow\textLongrightarrow
20414 \let\Longleftrightarrow\textLongleftrightarrow
20415 \let\longmapsto\textlongmapsto
20416 \let\Longmapsfrom\textLongmapsfrom
20417 \let\Longmapsto\textLongmapsto
20418 \let\nwarrow\textnwarrow
20419 \let\nesarrow\textnesarrow
20420 \let\lhooknarrow\textlhooknarrow
20421 \let\rhooknearrow\textrhooknearrow
20422 \let\lhooksearrow\textlhooksearrow
20423 \let\rhookswarrow\textrhookswarrow
20424 \let\leadsto\textleadsto
20425 \let\rcurvearrowne\textrcurvearrowne
20426 \let\lcurvearrowse\textlcurvearrowse
20427 \let\lcurvearrowsw\textlcurvearrowsw
20428 \let\rcurvearrowse\textrcurvearrowse
20429 \let\lcurvearrowdown\textlcurvearrowdown
20430 \let\rcurvearrowdown\textrcurvearrowdown
20431 \let\rcurvearrowleft\textrcurvearrowleft
20432 \let\rcurvearrowright\textrcurvearrowright

```

```

20433 \let\leftrightharpoon\textleftrightharpoon
20434 \let\rightleftharpoon\textrightleftharpoon
20435 \let\updownharpoonrightleft\textupdownharpoonrightleft
20436 \let\updownharpoonleftright\textupdownharpoonleftright
20437 \let\leftleftharpoons\textleftleftharpoons
20438 \let\upupharpoons\textupupharpoons
20439 \let\rightrightharpoons\textrightrightharpoons
20440 \let\downdownharpoons\textdowndownharpoons
20441 \let\leftbarharpoon\textleftbarharpoon
20442 \let\barleftharpoon\textbarleftharpoon
20443 \let\rightbarharpoon\textrightbarharpoon
20444 \let\ barrightharpoon\textbarrightharpoon
20445 \let\updownharpoons\textupdownharpoons
20446 \let\downupharpoons\textdownupharpoons
20447 \let\moo\textmoo
20448 \let\llparenthesis\textllparenthesis
20449 \let\rrparenthesis\textrrparenthesis
20450 \let\invdiameter\textinvdiameter
20451 \let\obar\textobar
20452 \let\obslash\textobslash
20453 \let\obot\textobot
20454 \let\NoChemicalCleaning\textNoChemicalCleaning
20455 \let\olessthan\textolessthan
20456 \let\ogreaterthan\textogreaterthan
20457 \let\boxslash\textboxslash
20458 \let\boxbslash\textboxbslash
20459 \let\boxast\textboxast
20460 \let\boxcircle\textboxcircle
20461 \let\boxbox\textboxbox
20462 \let\Valve\textValve
20463 \let\multimapboth\textmultimapboth
20464 \let\shuffle\textshuffle
20465 \let\uplus\textuplus
20466 \let\bigdoublewedge\textbigdoublewedge
20467 \let\bigdoublevee\textbigdoublevee
20468 \let\Join\textJoin
20469 \let\fatsemi\textfatsemi
20470 \let\circplus\textcircplus
20471 \let\minusdot\textminusdot
20472 \let\dottimes\textdottimes
20473 \let\dtimes\textdtimes
20474 \let\odiv\textodiv
20475 \let\invneg\textinvneg
20476 \let\sqdoublecap\textsqdoublecap
20477 \let\capdot\textcapdot
20478 \let\sqdoublecup\textsqdoublecup
20479 \let\doublewedge\textdoublewedge
20480 \let\doublevee\textdoublevee
20481 \let\doublebarwedge\textdoublebarwedge
20482 \let\veedoublebar\textveedoublebar
20483 \let\eqdot\texteqdot
20484 \let\neqdot\textneqdot
20485 \let\coloncolonequals\textcoloncolonequals
20486 \let\leqslant\textleqslant

```

```

20487 \let\nleqslant\textnleqslant
20488 \let\geqslant\textgeqslant
20489 \let\ngeslant\textngeslant
20490 \let\lessapprox\textlessapprox
20491 \let\nlessapprox\textnlessapprox
20492 \let\gtrapprox\textgtrapprox
20493 \let\ngtrapprox\textngtrapprox
20494 \let\lneq\textlneq
20495 \let\gneq\textgneq
20496 \let\lnapprox\textlnapprox
20497 \let\gnapprox\textgnapprox
20498 \let\lesseqgtr\textlesseqgtr
20499 \let\gtreqless\textgtreqless
20500 \let\eqslantless\texteqslantless
20501 \let\eqslantgtr\texteqslantgtr
20502 \let\leftslice\textleftslice
20503 \let\rightslice\textrightslice
20504 \let\preceq\textpreceq
20505 \let\npreceq\textnpreceq
20506 \let\succeq\textsucceq
20507 \let\nsucceq\textnsucceq
20508 \let\precneq\textprecneq
20509 \let\succneq\textsuccneq
20510 \let\preceqq\textpreceqq
20511 \let\npreceqq\textnpreceqq
20512 \let\succeqq\textsuccceqq
20513 \let\nsucceqq\textnsuccceqq
20514 \let\precneqq\textprecneqq
20515 \let\succneqq\textsuccneqq
20516 \let\precapprox\textprecapprox
20517 \let\nprecapprox\textnprecapprox
20518 \let\succapprox\textsuccapprox
20519 \let\nsuccapprox\textnsuccapprox
20520 \let\precnapprox\textprecnapprox
20521 \let\succnapprox\textsuccnapprox
20522 \let\subseteqq\textsubseteqq
20523 \let\nsubseteqq\textnsubseteqq
20524 \let\supseteqq\textsupseteqq
20525 \let\nsupseteqq\textnsupseteqq
20526 \let\dashV\textdashV
20527 \let\ndashV\textndashV
20528 \let\Dashv\textDashv
20529 \let\nDashv\textnDashv
20530 \let\DashV\textDashV
20531 \let\nDashV\textnDashV
20532 \let\downmodels\textdownmodels
20533 \let\ndownmodels\textndownmodels
20534 \let\upmodels\textupmodels
20535 \let\nupmodels\textnupmodels
20536 \let\upspoon\textupspoon
20537 \let\interleave\textinterleave
20538 \let\sslash\textslash
20539 \let\pentagon\textpentagon
20540 \let\varhexagon\textvarhexagon

```

```

20541 \let\jinferior{textjinferior}
20542 \let\slashdiv{textslashdiv}
20543 \let\fivedots{textfivedots}
20544 \let\oo{textoo}
20545 \let\GaPa{textGaPa}
20546 \let\HaPa{textHaPa}
20547 \let\ViPa{textViPa}
20548 \let\AcPa{textAcPa}
20549 \let\SePa{textSePa}
20550 \let\ZwPa{textZwPa}
20551 \let\fullnote{textfullnote}
20552 \let\halfnote{texthalfnote}
20553 \let\Vier{textVier}
20554 \let\Acht{textAcht}
20555 \let\Sech{textSech}
20556 \let\Zwdr{textZwdr}
20557 \let\Mundus{textMundus}
20558 \let\Moon{textMoon}
20559 \let\ManFace{textManFace}
20560 \let\WomanFace{textWomanFace}
20561 \let\Fax{textFax}
20562 \let\Fire{textFire}
20563 \let\Bicycle{textBicycle}
20564 \let\Gentsroom{textGentsroom}
20565 \let\Ladiesroom{textLadiesroom}
20566 \let\ccnc{textccnc}
20567 \let\ccsa{textccsa}
20568 \let\Info{textInfo}
20569 \let\CESign{textCESign}
20570 \let\neg{textneg}
20571 \let\times{texttimes}
20572 \let\div{textdiv}
20573 \let\pm{textpm}
20574 \let\cdot{textcdot}
20575 }% \psdmapshortnames
20576 \newcommand*{\psdaliasnames}{%
20577 \let\epsdice{HyPsd@DieFace}
20578 \let\fcdice{HyPsd@DieFace}
20579 \let\MoonPha{HyPsd@MoonPha}
20580 \let\mathdollar{textdollar}
20581 \let\EyesDollar{textdollar}
20582 \let\binampersand{textampersand}
20583 \let\with{textampersand}
20584 \let\mathunderscore{textunderscore}
20585 \let\textvertline{textbar}
20586 \let\mathsterling{textsterling}
20587 \let\pounds{textsterling}
20588 \let\brokenvert{textbrokenbar}
20589 \let\mathsection{textsection}
20590 \let\S{textsection}
20591 \let\mathparagraph{textparagraph}
20592 \let\MultiplicationDot{textperiodcentered}
20593 \let\Squaredot{textperiodcentered}
20594 \let\vartimes{textmultiply}

```

```

20595 \let\MMMultiplication\textmultiply
20596 \let\eth\dh
20597 \let\crossd\textcrd
20598 \let\textbard\textcrd
20599 \let\bard\textcrd
20600 \let\textcrh\texthbar
20601 \let\crossh\texthbar
20602 \let\planck\texthbar
20603 \let\eng\ng
20604 \let\engma\ng
20605 \let\crossb\textcrb
20606 \let\textbarb\textcrb
20607 \let\barb\textcrb
20608 \let\Florin\textflorin
20609 \let\hv\texthvlig
20610 \let\hausak\texthtk
20611 \let\crossnilambda\textcrlambda
20612 \let\barlambda\textcrlambda
20613 \let\lambdabar\textcrlambda
20614 \let\lambdadaslash\textcrlambda
20615 \let\textnrleg\textPUrleg
20616 \let\textpipevar\textpipe
20617 \let\textdoublepipevar\textdoublepipe
20618 \let\textdoublebarpipevar\textdoublebarpipe
20619 \let\textcrg\textgslash
20620 \let\textdblig\textPUDblig
20621 \let\textqplig\textPUqplig
20622 \let\textcentoldstyle\textslashc
20623 \let\textbarc\textslashc
20624 \let\inva\textturna
20625 \let\vara\textscripta
20626 \let\invscripta\textturnscripta
20627 \let\rotvara\textturnscripta
20628 \let\hookb\texthtb
20629 \let\hausab\texthtb
20630 \let\varopeno\textopeno
20631 \let\curlc\textctc
20632 \let\taild\textrtaild
20633 \let\hookd\texthtd
20634 \let\hausad\texthtd
20635 \let\er\textrhookschwa
20636 \let\epsi\textniepsilon
20637 \let\hookrevepsilon\textrhookrevepsilon
20638 \let\closedrevepsilon\textcloserevepsilon
20639 \let\barj\textbardotlessj
20640 \let\hookg\texthtg
20641 \let\varg\textscriptg
20642 \let\vod\textipagamma
20643 \let\invh\textturnh
20644 \let\udesc\textturnh
20645 \let\hookh\texthth
20646 \let\voicedh\texthth
20647 \let\hookheng\texththeng
20648 \let\ibar\textbari

```

```
20649 \let\vari{textniota}
20650 \let\tildel{texttilde}
20651 \let\latfric{textbeltl}
20652 \let\taill{textrtaill}
20653 \let\lz{textlyoghlig}
20654 \let\invm{textturnm}
20655 \let\rotm{textturnm}
20656 \let\legm{textturnmrleg}
20657 \let\labdentalnas{textltailm}
20658 \let\emgma{textltailm}
20659 \let\nj{textltailn}
20660 \let\enya{textltailn}
20661 \let\tailn{textrtailn}
20662 \let\closedniomega{textcloseomega}
20663 \let\varomega{textcloseomega}
20664 \let\invr{textturnr}
20665 \let\rotr{textturnr}
20666 \let\invlegr{textturnlonglegr}
20667 \let\tailinvr{textturnrrtail}
20668 \let\legr{textlonglegr}
20669 \let\tailr{textrtailr}
20670 \let\flapr{textfishhookr}
20671 \let\flap{textfishhookr}
20672 \let\tails{textrtails}
20673 \let\curlyesh{textctesh}
20674 \let\clickt{textturnt}
20675 \let\taitl{textrtailt}
20676 \let\ubar{textbaru}
20677 \let\rotOmega{textniupsilon}
20678 \let\invv{textturnv}
20679 \let\pwedge{textturnv}
20680 \let\invw{textturnw}
20681 \let\rotw{textturnw}
20682 \let\invy{textturny}
20683 \let\roty{textturny}
20684 \let\tailz{textrtailz}
20685 \let\curlyz{textctz}
20686 \let\curlyyogh{textctyogh}
20687 \let\ejective{textglotstop}
20688 \let\glottal{textglotstop}
20689 \let\reveject{textrevglotstop}
20690 \let\clickc{textstretchc}
20691 \let{textstretchcvar}{textstretchc}
20692 \let\clickb{textbulseye}
20693 \let{textO}{textbullseye}
20694 \let{textctjvar}{textctj}
20695 \let{textturnsck}{textturnk}
20696 \let\dz{textdzlig}
20697 \let\tesh{textteshlig}
20698 \let\digamma{textdigammagreek}
20699 \let\hardsign{cyrhrdsn}
20700 \let\softsign{cyrstfn}
20701 \let\hebsin{hebshin}
20702 \let{textsck}{textPUsck}
```

```

20703 \let\textscm{textPUscm}
20704 \let\textscp{textPUscp}
20705 \let\textrevscr{textPUrevscr}
20706 \let\textrhooka{textPUrhooka}
20707 \let\textrhooko{textPUrhooko}
20708 \let\textrhookepsilon{textPUrhookepsilon}
20709 \let\textrhookopeno{textPUrhookopeno}
20710 \let\textdoublevertline{textbardbl}
20711 \let\dag{textdagger}
20712 \let\ddagger{textdaggerdbl}
20713 \let\ddag{textdaggerdbl}
20714 \let\mathellipsis{textellipsis}
20715 \let\EurDig{texteuro}
20716 \let\EURdig{texteuro}
20717 \let\EurHv{texteuro}
20718 \let\EURhv{texteuro}
20719 \let\EurCr{texteuro}
20720 \let\EURcr{texteuro}
20721 \let\EurTm{texteuro}
20722 \let\EURtm{texteuro}
20723 \let\Eur{texteuro}
20724 \let\Denarius{textDeleatur}
20725 \let\agemo{textmho}
20726 \let\EstimatedSign{textestimated}
20727 \let\Ecommerce{textestimated}
20728 \let\bindnasrepma{textinvamp}
20729 \let\parr{textinvamp}
20730 \let\MVRightArrow{textrightarrowarrow}
20731 \let\MVRightarrow{textrightarrowarrow}
20732 \let\MVArrowDown{textdownarrow}
20733 \let\Force{textdownarrow}
20734 \let\textglobrise{textnearrow}
20735 \let\textglobfall{textsearrow}
20736 \let\Lightning{textlightning}
20737 \let\Conclusion{textrightarrowarrow}
20738 \let\dashedleftarrow{textdashleftarrow}
20739 \let\dashedrightarrow{textdashrightarrow}
20740 \let\varnothing{textemptyset}
20741 \let\owns{textni}
20742 \let\notni{textnotowner}
20743 \let\varprop{textproto}
20744 \let\varangle{textsphericalangle}
20745 \let\AngleSign{textsphericalangle}
20746 \let\AngleSign{textsphericalangle}
20747 \let\notdivides{textnmid}
20748 \let\varowedge{textwedge}
20749 \let\varovee{textovee}
20750 \let\varint{textint}
20751 \let\varoint{textoint}
20752 \let\downtherefore{textbecause}
20753 \let\textdotdiv{textdotminus}
20754 \let\AC{textsim}
20755 \let\wreath{textwr}
20756 \let\nthickapprox{textnapprox}

```

```

20757 \let\VHF\texttriplesim
20758 \let\notasymp\textnasymp
20759 \let\Doteq\textdoteqdot
20760 \let\corresponds\texthateq
20761 \let\Corresponds\texthateq
20762 \let\nequal\textneq
20763 \let\Congruent\textequiv
20764 \let\NotCongruent\textnequiv
20765 \let\notequiv\textnequiv
20766 \let\LessOrEqual\textleq
20767 \let\LargerOrEqual\textgeq
20768 \let\apprle\textlessim
20769 \let\apprge\textgtrsim
20770 \let\varoplus\textoplus
20771 \let\varominus\textominus
20772 \let\varotimes\textotimes
20773 \let\varoslash\textoslash
20774 \let\varodot\textodot
20775 \let\ocirc\textcircledcirc
20776 \let\varocircle\textcircledcirc
20777 \let\varoast\textcircledast
20778 \let\oasterisk\textcircledast
20779 \let\rightvDash\textvDash
20780 \let\leftvDash\textdashv
20781 \let\nleftvDash\textndashv
20782 \let\downvDash\texttop
20783 \let\upvDash\textbot
20784 \let\nperp\textnupvDash
20785 \let\models\textvDash
20786 \let\rightmodels\textvDash
20787 \let\rightVdash\textVdash
20788 \let\rightModels\textVDash
20789 \let\nrightvDash\textnvDash
20790 \let\nrightmodels\textnvDash
20791 \let\nmodels\textnvDash
20792 \let\nrightVdash\textnvDash
20793 \let\nrightModels\textnvDash
20794 \let\lessclosed\textlhd
20795 \let\gtrclosed\textrhd
20796 \let\leqclosed\textunlhd
20797 \let\trianglelefteq\textunlhd
20798 \let\geqclosed\textunrhd
20799 \let\trianglerighteq\textunrhd
20800 \let\Bowtie\textbowtie
20801 \let\varcurlyvee\textcurlyvee
20802 \let\varcurlywedge\textcurlywedge
20803 \let\doublecap\textCap
20804 \let\doublecup\textCup
20805 \let\varsqsubsetneq\textsqsubsetneq
20806 \let\varsqsupsetneq\textsqsupsetneq
20807 \let\nlessclosed\textntriangleleft
20808 \let\ngtrclosed\textntriangleright
20809 \let\Clocklogo\textclock
20810 \let\ClockLogo\textclock

```

```
20811 \let\baro\textstmaryrdbaro
20812 \let\varparallelinv\textbbslash
20813 \let\CleaningA\textCircledA
20814 \let\Kutline\textCuttingLine
20815 \let\CutLine\textCuttingLine
20816 \let\Cutline\textCuttingLine
20817 \let\MoveUp\textUParrow
20818 \let\APLup\textbigtriangleup
20819 \let\Bleech\textbigtriangleup
20820 \let\MoveDown\textDOWNarrow
20821 \let\APLdown\textbigtriangledown
20822 \let\Diamond\textdiamond
20823 \let\varbigcirc\textbigcircle
20824 \let\Telefon\textPhone
20825 \let\Box\textboxempty
20826 \let\CheckedBox\textcheckbox
20827 \let\XBox\textCrossedbox
20828 \let\CrossedBox\textCrossedbox
20829 \let\rightpointleft\textHandLeft
20830 \let\leftpointright\textHandRight
20831 \let\PointingHand\textHandRight
20832 \let\Pointinghand\textHandRight
20833 \let\Radiation\textRadioactivity
20834 \let\Yinyang\textYinYang
20835 \let\YingYang\textYinYang
20836 \let\Yingyang\textYinYang
20837 \let\Frowny\textfrownie
20838 \let\Smiley\textsmiley
20839 \let\Sun\textsun
20840 \let\Mercury\textmercury
20841 \let\textfemale\textPUfemale
20842 \let\female\textPUfemale
20843 \let\venus\textPUfemale
20844 \let\Venus\textPUfemale
20845 \let\Female\textPUfemale
20846 \let\Earth\textearth
20847 \let\mars\textmale
20848 \let\Mars\textmale
20849 \let\Male\textmale
20850 \let\Jupiter\textjupiter
20851 \let\Saturn\textsaturn
20852 \let\Uranus\texturanus
20853 \let\Neptune\textneptune
20854 \let\Pluto\textpluto
20855 \let\Aries\textaries
20856 \let\Taurus\texttaurus
20857 \let\Gemini\textgemini
20858 \let\Cancer\textcancer
20859 \let\Leo\textleo
20860 \let\Virgo\textvirgo
20861 \let\Libra\textlibra
20862 \let\Scorpio\textscorpio
20863 \let\Sagittarius\textsagittarius
20864 \let\Capricorn\textcapricornus
```

```
20865 \let\Aquarius\textaquarius
20866 \let\Pisces\textpisces
20867 \let\spadesuit\textspadesuitblack
20868 \let\Heart\textheartsuitwhite
20869 \let\heartsuit\textheartsuitwhite
20870 \let\diamondsuit\textdiamondsuitwhite
20871 \let\clubsuit\textclubsuitblack
20872 \let\ighthnote\textmusicalnote
20873 \let\Recycling\textrecycle
20874 \let\VarFlag\textFlag
20875 \let\textxswup\textdsmilitary
20876 \let\textuncrfemale\textPUuncrfemale
20877 \let\Football\textSoccerBall
20878 \let\CutLeft\textScissorRightBrokenBottom
20879 \let\Cutright\textScissorRightBrokenBottom
20880 \let\RightScissors\textScissorRight
20881 \let\Leftscissors\textScissorRight
20882 \let\Letter\textEnvelope
20883 \let\Writinghand\textWritingHand
20884 \let\checkmark\textCheckmark
20885 \let\davidstar\textDavidStar
20886 \let\llbracket\textlbrackdbl
20887 \let\rrbracket\textrbrackdbl
20888 \let\RightTorque\textlcurvearrowdown
20889 \let\Righttorque\textlcurvearrowdown
20890 \let\LeftTorque\textrcurvearrowdown
20891 \let\Lefttorque\textrcurvearrowdown
20892 \let\textvarobar\textobar
20893 \let\circledbslash\textobslash
20894 \let\obackslash\textobslash
20895 \let\varobslash\textobslash
20896 \let\odplus\textobot
20897 \let\varolessthan\textolessthan
20898 \let\varogreaterthan\textogreaterthan
20899 \let\divdot\textminusdot
20900 \let\doublesqcap\textsqdoublenew
20901 \let\doublesqcup\textsqdoublenew
20902 \let\merge\textdoublevee
20903 \let\leftVdash\textdashV
20904 \let\nleftVdash\textndashV
20905 \let\leftmodels\textDashv
20906 \let\nleftmodels\textnDashv
20907 \let\leftModels\textDashV
20908 \let\nleftModels\textnDashV
20909 \let\varparallel\textsslash
20910 \let\textheng\textPUheng
20911 \let\textilhookfour\textPULhookfour
20912 \let\textscf\textPUsnf
20913 \let\textaolig\textPUaolig
20914 \let\Ganz\textfullnote
20915 \let\Halb\texthalfnote
20916 \let\Womanface\textWomanFace
20917 \let\Faxmachine\textFax
20918 \let\CEsign\textCESign
```

```
20919 }% \psdaliasnames  
20920 </psdextra>
```

47 End of file hycheck.tex

```
20921 <*check>  
20922 \typeout{}  
20923 \begin{document}  
20924 \end{document}  
20925 </check>
```

48 Index

Numbers written in italic refer to the page where the corresponding entry is described; numbers underlined refer to the code line of the definition; numbers in roman refer to the code lines where the entry is used.

Symbols	
\!	195, 220, 1741
\"	202, 227, 3051, 14313, 14628, 14640, 14652, 14778, 14866, 14880, 14888, 14903, 14915, 14932, 14946, 14957, 14958, 14972, 14984, 14991, 15044, 15090, 15119, 15150, 15325, 15339, 15347, 15361, 15375, 15392, 15406, 15417, 15418, 15433, 15445, 15453, 15711, 16327, 16341, 16497, 16511, 16755, 16757, 16772, 16775, 16777, 16779, 16781, 16783, 16793, 16795, 16797, 16799, 16806, 16809, 16811, 16813, 16819, 16821, 16827, 16829, 16835, 16837, 17047, 17049, 17199, 17201, 17215, 17217, 17237
\# .	516, 1826, 1827, 4738, 4749, 4751, 4767, 4799, 4859, 8630, 8632, 9374, 9383, 9418, 10259, 11907, 11918, 11954, 12192, 12201, 12241, 14233
\\$.	184, 209, 314, 517, 4740, 4858
\% .	518, 1741, 1801, 1802, 4737, 4746, 4748, 4800, 8632
\& .	185, 210, 519, 4741, 4752, 4754, 11964
\' .	203, 228, 2991, 3005, 3046, 3048, 3049, 3050, 3051, 3056, 3057, 3059, 3064, 3070, 3074, 3075, 3078, 3121, 3122, 3127, 3128, 3129, 3130, 3131, 3132, 3133, 3134, 3136, 3139, 3146, 3147, 3148, 3149, 3152, 3158, 3171, 14311, 14625, 14637, 14649, 14860, 14876, 14884, 14897, 14911, 14917, 14926, 14942, 14951, 14952, 14966, 14980, 14986, 15010, 15012, 15013, 15014, 15017, 15019, 15020, 15021, 15029, 15087, 15116, 15147, 15319, 15335, 15343, 15355, 15371,
\# .	15377, 15386, 15402, 15411, 15412, 15427, 15441, 15447, 15467, 15469, 15583, 15585, 15603, 15605, 15639, 15641, 15651, 15653, 15713, 15715, 15836, 15838, 15844, 15846, 15849, 15852, 16331, 16351, 16501, 16521, 17063, 17065, 17087, 17089, 17127, 17129, 17195, 17197, 19437, 19442, 19447, 19452, 19457, 19462, 19467, 19472, 19477, 19482, 19487, 19492, 19497, 19502, 19507, 19512, 19517, 19522, 19527, 19532, 19537, 19542, 19547, 19552
\(.	190, 215, 315, 735, 738, 740, 1743, 14379, 14698
\) .	191, 216, 316, 707, 713, 716, 1744, 14380, 14700
* .	318
\+ .	200, 225, 319
\- .	201, 226
\. .	198, 223, 312, 3502, 3915, 14631, 14643, 14655, 14719, 15015, 15022, 15042, 15093, 15122, 15156, 15233, 15234, 15475, 15477, 15505, 15507, 15525, 15527, 15564, 15595, 15597, 15717, 15719, 15920, 15922, 15928, 15930, 16979, 16981, 16991, 16993, 17031, 17033, 17039, 17041, 17091, 17093, 17099, 17101, 17131, 17133, 17135, 17137, 17147, 17149, 17155, 17157, 17203, 17205, 17211, 17213, 17219, 17221, 17243
\/ .	194, 219, 648, 649, 650, 718, 1510, 8191
\: .	189, 214
\; .	199, 224
\< .	196, 221
\= .	167, 173, 180, 183, 14633, 14645, 14657, 15035, 15099, 15128, 15155, 15455, 15457, 15497, 15499, 15549, 15551, 15552, 15623, 15625, 15683, 15685, 15932, 15934, 16789,
\# .	16791, 16815, 16817, 17035, 17037
\> .	197, 222
\? .	320
\@ .	3042
\@@ .	2185
\@@BOOKMARK .	14294, 14297, 14355, 14420, 14427
\@@Listbox .	12596, 12627, 13198, 13232, 13554, 13595
\@@Menu .	12837, 12845
\@@PasswordField .	12786, 12792
\@@Radio .	12581, 12602, 12835, 12859, 13183, 13204, 13539, 13560
\@@TextField .	12788, 12803
\@@commahyperpage .	8325, 8326
\@@hyper@readexternallink .	5153, 5155
\@@hyperef .	4962, 4963
\@@wrindex .	8226, 8227
\@@writetorep .	14155, 14161
\@Alph .	7043, 7045
\@BIBLABEL .	7700, 7706, 7712
\@BOOKMARK .	14294, 14296
\@CheckBox .	6142, 10324, 12716, 12752, 12890, 13320, 13697
\@ChoiceMenu .	6139, 10327, 12534, 12755, 12825, 13135, 13491
\@Form .	5815, 10314, 12286, 12742, 12769, 13024, 13405
\@Gauge .	6148, 10318, 12471, 12746, 12774, 12911, 13402
\@Localurlfalse .	10267
\@Localurltrue .	10264
\@M .	2227, 4845
\@MM .	7457
\@PackageError .	246
\@PackageInfo .	249
\@PackageInfoNoLine .	250
\@PackageWarning .	247
\@PackageWarningNoLine .	248
\@PushButton .	6145, 10330, 12638, 12758, 12871, 13242, 13611
\@Refstar .	4711, 8434
\@Reset .	6154, 10333, 12689, 12761, 12887, 13295, 13668

\@Submit . 6151, 10336, 12669,
 12764, 12884, 13272, [13645](#)
 \@TextField . 6136, 10321, 12502,
 12749, 12777, 13105, [13454](#)
 \@addtoreset . 8124, 8125, 8140
 \@alph 7039, 7041
 \@anchorcolor 3481, 9343, 9438,
 10386, 11875, 12162
 \@arabic 6946, 6962, 7038
 \@auxout 2179, 5010, 5317, 6379,
 7720, 7735, 7752, 7762,
 7781, 7787, 7811
 \@backslashchar
 1044, 1703, 1707, 1710,
 1848, 1865, 1871, 1875,
 1883, 4762, 8645, 8655
 \@baseurl 3488, 3490, 5211, 9082,
 9085, 9328, 9330, 9615,
 9617, 10136, 10146, 10232,
 10234, 10769, 10771, 11153,
 11167, 11860, 11862, 12060,
 12074, 12148, 12150
 \@bibitem 7727, 7759
 \@biblabel 7700, 7748
 \@bookmarkopenstatus . . 4588,
 4605, 14215
 \@bookmarksopenlevel . . 3442,
 3444, 4591
 \@bsphack 2172, 5003, 7785
 \@capstartfalse 7591
 \@caption 7556, 7568, 7611, 7648,
 7650
 \@capttype 2181, 7551, 7555,
 7559, 7566, 7573, 7627,
 7641, 7645, 7648
 \@car 1326, 1342, 1360, 1380,
 3421, 5433
 \@chapter 14550, 14551
 \@cite 7846, 7852
 \@cite@opt 7847, 7853, 7857,
 7867
 \@citebordercolor 3536, 4128
 \@citetcolor 3482
 \@citedata@opt 7848, 7854, 7856
 \@citedatax 7863, 7868
 \@citedatax@opt 7860, [7866](#)
 \@citeseppen 7845, 7851
 \@commahyperpage 8320, 8325
 \@ctrerr 7011, 7020
 \@currDisplay 5903, 12546,
 12609, 12854, 12868, 13147,
 13211, 13503, 13570
 \@currValue 5905, 5907, 5909,
 12607, 12618, 12854, 12865,
 13209, 13219, 13568, 13585
 \@currentHlabel [7090](#)
 \@currentHref 2187, 5055, 5346,
 6259, 6927, 7069, 7071,
 7081, 7083, 7090, 7098,
 7100, 7110, 7153, 7164,
 7166, 7203, 7224, 7228,
 7233, 7256, 7296, 7298,
 7300, 7373, 7383, 7385,
 7386, 7442, 7471, 7571,
 7597, 7601, 7628, 7630,
 7790, 7976, 7999, 8012,
 8019, 8101, 14145, 14531,
 14544, 14555, 14582, 14599
 \@currentcounter 7460
 \@currentlabel 7461, 7783, 7790,
 8106, 8113
 \@currentlabelname 2177, 7374,
 7443, 7472, 7576
 \@currentlabstr 2176, 2184
 \@currname 2297
 \@curropt 12543, 12544, 12605,
 12606, 12843, 12850, 12851,
 12853, 12860, 12861, 12863,
 13144, 13145, 13207, 13208,
 13500, 13501, 13566, 13567
 \@dblarg 7566, 7648
 \@definecounter 8080, 8081
 \@documentclasshook 4209
 \@ehc 2549, 2676, 2702, 2718,
 2753, 2792, 2799, 2810,
 2816, 2854, 4291, 4907,
 5175, 5527, 5651, 5847,
 5880, 6074, 6127, 12647,
 12700, 13252, 13306, 13621,
 13679
 \@ehd 63, 265, 271, 295, [7552](#),
 7642
 \@elt 6934, 6936, 6937, 6942
 \@endForm 5816, 10317, 12470,
 12745, 12773, 13078, [13432](#)
 \@eqnccr 7244
 \@eqnstarfalse 7218, [7247](#)
 \@eqnstartrue 7244
 \@eqnswtrue 7182, 7191
 \@esphack 2193, 5014, 7795, 8238
 \@extra@b@citeb 7685, 7688,
 7705, 7710, 7730
 \@extra@binfo 7684, 7687, 7691
 \@fifthoffive 4997, 8386, [8519](#)
 \@filebordercolor
 3537, 4126, 9010, 9012,
 9950, 9952, 10472, 10474,
 11538
 \@filecolor 3471, 3483, 9031,
 9557, 9574, 9968, 10478
 \@firstoffive 4701, 8426, 8524
 \@firstofone 549,
 550, 551, 552, 553, 554,
 555, 556, 557, 558, 559, 602,
 635, 1246, 4590, 4983, 5781,
 5787, 6037, 6847, 7036,
 7048, 7564, 7646, 7935,
 8181, 9236, 12978, 13784,
 13801, 13819
 \@firstoftwo 618, 890, 6348,
 14589
 \@fnssymbol 7037
 \@footnotemark 7316, 7379,
 7397, 7480, 7492, 7494,
 7506, 7507, 7538, 7540
 \@footnotetext 7315, 7322, 7356,
 7396, 7493, 7495, 7509,
 7510, 7531
 \@for 3513, 5423, 12543, 12605,
 12843, 12850, 12860, 13144,
 13207, 13500, 13566
 \@fourthoffive 4998, 8514, [8521](#)
 \@gobble 49, 56, 117, 542, 543,
 544, 545, 582, 583, 584, 585,
 604, 621, 622, 623, 632, 634,
 897, 1183, 1244, 1263, 1276,
 1280, 1343, 1406, 1407,
 1414, 1419, 1433, 1438,
 2035, 2199, 2493, 2505,
 3888, 4201, 4238, 4293,
 4728, 5766, 6027, 6313,
 6317, 6334, 6336, 6352,
 6353, 6356, 6357, 6359,
 6453, 6821, 6841, 6845,
 7553, 7643, 7975, 8579,
 9238, 10655, 10658, 13025,
 13406, 14202, 14203, 14204,
 14205
 \@gobblefour 548, 658, 940, 941,
 942, 3696
 \@gobbleopt 6359, 6361
 \@gobbletwo 546, 625, 651,
 659, 660, 939, 1361, 1438,
 1442, 2381, 3694, 3695,
 4242, 5712, 6338, 6347,
 6355, 6359, 8503, 14541
 \@harvarditem 7800, 7802
 \@hyper@anchor 5261, 5262
 \@hyper@itemfalse 6878, 6895,
 6910

\@hyper@itemtrue 6879
\@hyper@launch 5181, 5190,
 9035, 9973, 10547, 11556
\@hyper@linkfile 5162, 5165,
 5169, 5201
\@hyper@readexternallink 5156,
 5160
\@hyperdef 4970, 4971
\@hyperpage 8317, 8318
\@hyperref 4950, 4962
\@ifclassloaded 9241
\@ift@r 6363, 7126
\@ifnextchar 12, 88, 103, 123,
 652, 4852, 4950, 4970, 5109,
 5815, 6136, 6139, 6142,
 6145, 6148, 6151, 6154,
 6359, 6409, 6418, 7496,
 7514, 7800, 7858, 11178,
 11467, 11481, 14294, 14297
\@ifpackageloaded
 787, 2167, 2602, 4186,
 4384, 6920, 7093, 7131,
 7141, 7178, 7305, 7393,
 7409, 7449, 7624, 7770,
 7843, 8098, 8151, 8186,
 8187, 8188, 8444, 12140
\@ifpackagewith 3279, 4184
\@ifstar 66, 6295, 6299, 6368,
 6372, 8483
\@ifundefined
 34, 342, 475, 854, 864, 893,
 896, 2294, 2470, 2620, 2641,
 2642, 3297, 3342, 3350,
 3357, 3379, 3419, 4381,
 4382, 5522, 5842, 6292,
 6774, 6888, 6932, 7133,
 7142, 7145, 7146, 7177,
 7221, 7303, 7312, 7549,
 7557, 7575, 7681, 7694,
 7972, 8027, 8078, 8086,
 8092, 8096, 8122, 8129,
 8138, 8139, 8149, 8153,
 8154, 8161, 8445, 10851,
 10852, 12923, 13025, 13406,
 13782, 13793, 14211, 14522,
 14569
\@indexfile 8230, 8245, 8260,
 8264, 8274
\@inmathwarn 510, 511
\@inpc@undefined@ 1910
\@latec@ 6440, 6441
\@latec@error 7552, 7642
\@latec@warning 4990, 8361,
 8381, 8398, 8530
\@lbibitem 7701, 7747
\@linkbordercolor 3538, 4123,
 8965, 10376
\@linkcolor 3480, 11206
\@linkdim 457, 9392, 9393, 9401,
 9402, 9403, 9472, 9473,
 9485, 9486, 9487, 9509,
 9510, 9523, 9524, 9525,
 9549, 9550, 9563, 9564,
 9565, 11928, 11929, 11937,
 11938, 11939, 12210, 12211,
 12224, 12225, 12226
\@listctr 7736, 7763
\@m 9266, 10200, 10344, 10702,
 11658
\@mainaux 5365, 6804, 6812,
 12971, 12974, 13002, 13017
\@makecaption 7592, 7594, 7661
\@makefnmark 7388, 7543
\@makefntext 7462
\@makeother 166, 167,
 179, 180, 182, 183, 188, 189,
 190, 191, 192, 193, 194, 195,
 196, 197, 198, 199, 200, 201,
 202, 203, 4752, 8617, 14383,
 14386, 14410, 14413
\@menubordercolor 3539, 4125,
 9304, 9306, 10047, 10049,
 10585, 10587, 11460
\@menucolor 3485, 9319, 10058,
 10591
\@mkboth 625, 14541
\@mpfn 7319, 7515, 7528
\@mpfootnotetext 7322, 7335,
 7336, 7398
\@mycount 14359, 14369
\@namedef 2138, 2140, 2142,
 2144, 2146, 2148, 2150,
 2152, 2154, 2156, 2158,
 2159, 2160, 2161, 2162,
 2163, 2164, 2165, 2166,
 2317, 2630, 2631, 2632,
 2633, 2634, 2635, 2636,
 3288, 3300, 5533, 5534,
 5535, 5536, 5858, 5859,
 7243, 7246, 7775, 7776,
 7777, 7778
\@namerefstar 4707, 8431
\@nameuse 2181, 2627, 5539,
 5850
\@ne 2568, 2741, 4502, 4576, 4877,
 9879, 9880, 9885, 10748,
 11699, 12477, 13441
\@newctr 8088, 8089
\@newl@bel 5300, 6403, 7687
\@nil 276,
 303, 1238, 1241, 1249, 1326,
 1344, 1362, 1378, 1380,
 1383, 1386, 1389, 1919,
 1921, 1937, 1939, 3421,
 4784, 4788, 4793, 5228,
 5236, 5242, 5244, 5433,
 6018, 6021, 6040, 6428,
 6431, 6438, 6440, 6441,
 6555, 6603, 6604, 6606,
 6629, 6646, 6700, 6702,
 7148, 7157, 7159, 7171,
 8304, 8306, 8313, 8336,
 8339, 8349, 8365, 8368,
 8538, 8569, 8641, 8647,
 8651, 8657, 10620, 10622,
 13791, 13804, 13810, 14243,
 14246, 14249, 14258, 14261,
 14270
\@nocnterr 8139, 8154
\@nocounterr 8138, 8153
\@number 7036, 7935
\@nx 8142, 8157, 8160, 8162
\@onelevel@sanitize 2374, 2378,
 2583, 3420, 4268, 4298,
 4312, 4818, 5223, 5226,
 5239, 5253, 5523, 5759,
 5843, 6656, 6658, 7077,
 8005, 8412, 9737, 14240
\@outlinefile 14213, 14302, 14397,
 14399, 14476, 14478
\@pagerefstar 4703, 8428, 8449,
 8456, 8465, 8474
\@pagesetref 8377
\@parboxrestore 7459, 7584, 7656
\@parcount 14361, 14369
\@part 14568, 14572
\@partaux 5363
\@pdfauthor 3712, 4131, 9142,
 9595, 10081, 10822, 11077,
 11989
\@pdfborder
 3371, 3557, 3558, 3559,
 3566, 3570, 3593, 3595,
 4671, 8898, 9755, 10374,
 10955, 11038, 11458, 11471,
 11486, 11507, 11535, 11566,
 11595, 11705, 11801, 11969
\@pdfborderstyle 3372, 3574,
 3575, 3576, 3585, 3589,
 3597, 3599, 4672, 5989,
 8899, 9756, 10375, 10956,
 11039, 11459, 11472, 11487,

11508, 11536, 11567, 11596,
 11706, 11802, 11970
`\@pdfcreationdate`
 .. 3734, 4134, 9146, 9148,
 9587, 9589, 10073, 10075,
 11052, 11054, 11981, 11983
`\@pdfcreator` . 3724, 3729, 4133,
 9145, 9586, 10072, 10825,
 11076, 11980
`\@pdfdirection` 9105, 9653,
 10116, 10781, 11133, 12040
`\@pdfduplex` 9111, 9659, 10122,
 10787, 11139, 12046
`\@pdfhighlight` 3543, 3551, 3553,
 4129, 10954, 11037, 11457,
 11506, 11534, 11565
`\@pdfkeywords` 3753, 4137, 9158,
 9584, 10086, 10830, 11078,
 11978
`\@pdflang` 4004, 4006, 4007, 4009,
 4011, 4013, 4019, 4049,
 4050, 4052, 4073, 4077,
 4079, 4096, 4105, 4112,
 4144, 9131, 9133, 9681,
 9683, 10156, 10158, 11163,
 11165, 12070, 12072
`\@pdfm@dest` 9699, 9758, 9762
`\@pdfm@mark`
 .. 6792, 9698, 9750, 9770,
 9784, 9786, 9800, 9802,
 9807, 9808, 9838, 9862,
 9864, 9869, 9887, 9910,
 9943, 9978, 10010, 10040,
 10068, 10137, 10164, 13409,
 13410, 13411, 13430, 13448,
 13451, 13481, 13576, 13603,
 13634, 13659, 13687, 13716,
 13727, 13760, 13768, 14447
`\@pdfmoddate`
 .. 3740, 4135, 9150, 9152,
 9591, 9593, 10077, 10079,
 11056, 11060, 11985, 11987
`\@pdfnonfullscreenpagemode` .
 9104, 9652, 10115, 10780,
 11132, 12039
`\@pdfnumcopies` 9120, 9122, 9668,
 9670, 10131, 10133, 10796,
 10798, 11148, 11150, 12055,
 12057
`\@pdfpageduration` . 3498, 9203,
 9207, 9212, 10181, 10183,
 10186, 10711, 10713, 10716,
 10994, 10996, 11004
`\@pdfpagelayout` 9130,
 9680, 10155, 10801, 10803,
 11162, 12069
`\@pdfpagemode` 4370, 4371, 4601,
 4602, 4611, 4612, 9084,
 9636, 10150, 10768, 11116,
 12023
`\@pdfpagescrop` 3958, 4139, 9069,
 9073, 9619, 9620, 9641,
 9643, 10162, 10164, 10757,
 10759, 11121, 11123, 12028,
 12030
`\@pdfpagetransition` . 3494, 9179,
 9183, 9188, 10170, 10172,
 10175, 10600, 10602, 10604,
 10977, 10979, 10987
`\@pdfpicktraybypdfsize`
 .. 9112, 9114, 9660, 9662,
 10123, 10125, 10788, 10790,
 11140, 11142, 12047, 12049
`\@pdfprintarea` 9108, 9656,
 10119, 10784, 11136, 12043
`\@pdfprintclip` 9109, 9657, 10120,
 10785, 11137, 12044
`\@pdfprintpagerange`
 .. 3664, 4143, 9116, 9118,
 9664, 9666, 10127, 10129,
 10792, 10794, 11144, 11146,
 12051, 12053
`\@pdfprintscaling` 9110, 9658,
 10121, 10786, 11138, 12045
`\@pdfproducer`
 .. 3718, 4132, 9154, 9156,
 9596, 9598, 10082, 10084,
 10725, 10726, 10730, 10733,
 10734, 10826, 10828, 11063,
 11067, 11592, 11593, 11698,
 11700, 11702, 11798, 11799,
 11990, 11992
`\@pdfremotestartview`
 .. 3919, 3921, 3922, 3945,
 3949, 3951, 3952, 3954,
 4141, 9023, 9959, 11546
`\@pdfstartpage`
 .. 3902, 3904, 4142, 9090,
 9094, 9623, 9628, 10139,
 10143, 10761, 10765, 11103,
 11108, 12010, 12015
`\@pdfstartview`
 .. 3909, 3911, 4140, 9092,
 9094, 9625, 9629, 10141,
 10143, 10763, 11105, 11109,
 12012, 12016
`\@pdfsubject` . 3747, 4136, 9144,
 9600, 10071, 10824, 11075,
 11994
`\@pdftempa` 5167, 5168, 5171
`\@pdftempwordfile` 5158, 5168
`\@pdftempwordrun` 5159, 5171
`\@pdftitle` 3706, 4130, 9143, 9585,
 10070, 10823, 11074, 11979
`\@pdftrapped` 3758, 3761, 3764,
 3773, 3782, 4138, 9159,
 9161, 10087, 10089, 11079
`\@pdfview` 3890, 8880, 8888,
 9705, 9709, 9713, 9717,
 9721, 9725, 9726, 9729,
 9730, 9733, 9737, 9739,
 9754, 10373, 10383, 10395,
 10892, 10912, 11597, 11707,
 11803, 12082
`\@pdfviewarea` 9106, 9654, 10117,
 10782, 11134, 12041
`\@pdfviewclip` 9107, 9655, 10118,
 10783, 11135, 12042
`\@pdfviewparams` 3892,
 3894, 10892, 10912, 11598,
 11708, 11804, 12083
`\@percentchar` 4747, 4748, 4800,
 14217
`\@processme`
 .. 5891, 5892, 9185, 9191,
 9209, 9215, 11181, 11182,
 11304, 11305, 11308, 11309
`\@protected@testopt` 655
`\@protected@testopt@xargs` 656
`\@refstar` 4699, 8425
`\@runbordercolor`
 .. 3540, 4127, 9044, 9046,
 9985, 9987, 10566, 10568,
 11569
`\@runcolor` 3486, 9064, 10001,
 10572
`\@safe@activesfalse` 608
`\@safe@activestrue` 607
`\@savsf` 8883, 8891
`\@schapter` 14538, 14539
`\@secondoffive` 4705, 8387, 8388,
 8429
`\@secondoftwo` 592, 601, 888,
 1312, 14591
`\@sect` 14586, 14587
`\@seqnrcr` 7244
`\@serial@counter` . 14309, 14357,
 14359, 14360
`\@setminipage` 7586, 7658
`\@setref` 8356, 8357, 8394
`\@sharp` 7148, 7154

\@skiphyperreffalse . 6896, 7716,
 7728
\@skiphyperreftrue . 7702, 7728
\@spaces 253
\@spart 14578, 14579
\@ssect 14524, 14525
\@tempa 7411, 7415, 7418, 7430
\@tempb 7268, 7272
\@tempboxa . 9390, 9392, 9401,
 9470, 9472, 9475, 9476,
 9485, 9491, 9492, 9507,
 9509, 9512, 9513, 9523,
 9529, 9530, 9547, 9549,
 9552, 9553, 9563, 9569,
 9570, 11926, 11928, 11937,
 12208, 12210, 12224
\@tempcnta 1889, 14167, 14168,
 14169, 14170, 14171, 14173,
 14176, 14177, 14178, 14184,
 14186, 14188, 14278, 14279,
 14280, 14283, 14284, 14285,
 14286, 14287, 14495, 14496,
 14497
\@tempdim a . 2230, 6191, 6192,
 6193, 6194, 6195, 6196,
 6197, 6198, 12542, 12547,
 12549, 12585, 12586, 12587,
 12591, 12592, 12593, 12594,
 13143, 13148, 13150, 13187,
 13188, 13189, 13193, 13194,
 13195, 13196, 13499, 13504,
 13506, 13543, 13544, 13545,
 13549, 13550, 13551, 13552
\@tempdim b 12546, 12547,
 13147, 13148, 13503, 13504
\@tempswafalse 7862
\@tempswatrue 7832, 7835, 7838,
 7859
\@temptokena 3266, 3271, 3274,
 3276
\@tfor 7269
\@the@H@page 7902, 7938, 7940,
 7941
\@thefnmark . 7320, 7331, 7422,
 7461, 7478, 7485, 7516,
 7529, 7536
\@thirdoffive 4709, 8432
\@thm 7308, 7309
\@typeset@protect 14508
\@undefined . 355, 358, 444, 446,
 661, 2647, 2707, 3270, 4390,
 4479, 6349, 6383, 6391,
 6402, 6618, 6636, 6681,
 7551, 7615, 7620, 7626,
 7641, 8420, 10736, 10750,
 15038, 15055, 16317, 16322,
 16843
\@unexpandable@protect . 4955,
 8291, 8410
\@unprocessedoptions ... 4549
\@urlbordercolor ... 3541, 4124,
 8975, 8977, 10017, 10019,
 10498, 10500, 11509
\@urlcolor 3484, 8994, 9397, 9410,
 9517, 9534, 10031, 10504,
 11933, 11946, 12219, 12232
\@urlype ... 9363, 9368, 10237,
 10263, 10403, 10417, 11895,
 11900, 12181, 12186
\@whilenum 956
\@wrindex . 8194, 8195, 8226
\@writefile 7788
\@x@sf . 7381, 7390, 7542, 7544
\@xfootnote 7514
\@xfootnotemark ... 7328, 7533
\@xfootnotenext ... 7317, 7526
\@xp ... 8112, 8141, 8142, 8156,
 8157, 8159, 8160
\@xxxii 5065
\{ 192, 217, 313, 3563, 3581, 4919
\{ . 321, 513, 1743, 10883, 14235
\} . 322, 514, 1744, 10883, 14236
\l u 324, 640, 3086, 3089,
 3915, 14648, 14649, 14650,
 14651, 14652, 14653, 14654,
 14655, 14656, 14657, 14658,
 14659, 15115, 15116, 15117,
 15118, 15119, 15120, 15121,
 15122, 15123, 15124, 15126,
 15128, 15129, 15130, 15131,
 15132, 15133, 15134, 15135,
 15136, 15137, 15138, 15139,
 15140, 15141, 15142, 15143
\] 193, 218
\^ 186, 211,
 311, 1841, 1842, 3069, 4735,
 4736, 4744, 14626, 14638,
 14650, 14862, 14878, 14886,
 14899, 14913, 14928, 14944,
 14954, 14955, 14968, 14982,
 15031, 15088, 15117, 15148,
 15321, 15337, 15345, 15357,
 15373, 15388, 15404, 15414,
 15415, 15429, 15443, 15471,
 15473, 15517, 15519, 15533,
 15535, 15572, 15574, 15575,
 15655, 15657, 15703, 15705,
 15707, 15709, 17223, 17225
__ ... 187, 212, 521, 4739, 4756,
 4757, 5027, 5040, 5053
\` 166, 172, 179,
 182, 3005, 3140, 3145, 3150,
 3151, 3154, 3157, 3160,
 3162, 3170, 14234, 14624,
 14636, 14648, 14858, 14874,
 14882, 14895, 14909, 14924,
 14940, 14948, 14949, 14964,
 14978, 15027, 15086, 15115,
 15146, 15317, 15333, 15341,
 15353, 15369, 15384, 15400,
 15408, 15409, 15425, 15439,
 15840, 15842, 16324, 16353,
 16494, 16523, 17191, 17193,
 17269, 17271, 19439, 19444,
 19449, 19454, 19459, 19464,
 19469, 19474, 19479, 19484,
 19489, 19494, 19499, 19504,
 19509, 19514, 19519, 19524,
 19529, 19534, 19539, 19544,
 19549, 19554
\| 188, 213,
 317, 1649, 1742, 1783, 2951,
 4167, 8190, 8616, 8626
\~ 520,
 958, 1897, 3063, 3071, 3072,
 3073, 4760, 14627, 14639,
 14651, 14864, 14893, 14901,
 14930, 14962, 14970, 15033,
 15089, 15118, 15149, 15323,
 15351, 15359, 15390, 15423,
 15431, 15544, 15546, 15547,
 15679, 15681, 17183, 17185,
 17253, 17255, 17277, 17279,
 19441, 19446, 19451, 19456,
 19461, 19466, 19471, 19476,
 19481, 19486, 19491, 19496,
 19501, 19506, 19511, 19516,
 19521, 19526, 19531, 19536,
 19541, 19546, 19551, 19556

Numbers

\3 497, 1002, 1003, 1004,
 1005, 1006, 1007, 1008,
 1009, 1118, 1119, 1120,
 1121, 1122, 1123, 1124,
 1125, 2012, 2148, 2156,
 2158, 14378, 14858, 14860,
 14862, 14864, 14866, 14868,
 14870, 14872, 14874, 14876,
 14878, 14880, 14882, 14884,
 14886, 14888, 14890, 14891,
 14893, 14895, 14897, 14899,

14901, 14903, 14905, 14907,	16819, 16821, 16823, 16825,	19006, 19008, 19010, 19012,
14909, 14911, 14913, 14915,	16827, 16829, 16831, 16833,	19014, 19016, 19018, 19020,
14917, 14919, 14920, 14922,	16835, 16837, 16839, 16841,	19124, 19127, 19130, 19132,
14924, 14926, 14928, 14930,	16845, 16847, 16849, 16851,	19134, 19136, 19138, 19140,
14932, 14934, 14936, 14938,	16853, 16855, 16857, 16859,	19142, 19144, 19271, 19273,
14940, 14942, 14944, 14946,	16861, 16863, 16865, 16867,	19275, 19277, 19279, 19282,
14948, 14949, 14951, 14952,	16869, 16871, 16873, 16875,	19285, 19288, 19292, 19295,
14954, 14955, 14957, 14958,	16877, 16879, 16881, 16883,	19298, 19300, 19302, 19304,
14960, 14962, 14964, 14966,	16885, 16887, 16889, 16891,	19306, 19309, 19311, 19386,
14968, 14970, 14972, 14974,	16893, 16895, 16897, 16900,	19398, 19400, 19402, 19404,
14976, 14978, 14980, 14982,	16902, 16904, 16906, 17257,	19406, 19426, 19427, 19428,
14984, 14986, 14988, 14989,	17259, 17261, 17263, 17265,	19432, 19433, 19434, 19437,
14991, 15083, 15317, 15319,	17267, 17269, 17271, 17273,	19439, 19441, 19452, 19454,
15321, 15323, 15325, 15327,	17275, 17277, 17279, 17635,	19458, 19459, 19460, 19461,
15329, 15331, 15333, 15335,	17638, 17641, 17644, 17647,	19462, 19463, 19464, 19465,
15337, 15339, 15341, 15343,	17650, 17653, 17655, 17657,	19467, 19468, 19469, 19470,
15345, 15347, 15349, 15351,	17659, 17661, 17664, 17667,	19471, 19472, 19473, 19474,
15353, 15355, 15357, 15359,	17670, 17672, 17675, 17678,	19475, 19476, 19477, 19478,
15361, 15363, 15367, 15369,	17680, 17683, 17686, 17689,	19479, 19480, 19481, 19482,
15371, 15373, 15375, 15377,	17692, 17694, 17696, 17698,	19483, 19484, 19485, 19487,
15379, 15380, 15382, 15384,	17700, 17702, 17704, 17706,	19488, 19489, 19490, 19491,
15386, 15388, 15390, 15392,	17708, 17711, 17714, 17716,	19492, 19493, 19494, 19495,
15394, 15396, 15398, 15400,	17719, 17721, 17724, 17726,	19496, 19497, 19499, 19501,
15402, 15404, 15406, 15408,	17728, 17730, 17777, 17815,	19512, 19514, 19518, 19519,
15409, 15411, 15412, 15414,	17820, 18193, 18195, 18197,	19520, 19521, 19522, 19523,
15415, 15417, 15418, 15420,	18200, 18203, 18205, 18207,	19524, 19525, 19527, 19528,
15423, 15425, 15427, 15429,	18209, 18211, 18213, 18216,	19529, 19530, 19531, 19532,
15431, 15433, 15435, 15437,	18219, 18221, 18223, 18225,	19533, 19534, 19535, 19536,
15439, 15441, 15443, 15445,	18227, 18230, 18233, 18235,	19537, 19538, 19539, 19540,
15447, 15450, 15451, 15453,	18237, 18239, 18241, 18244,	19541, 19542, 19543, 19544,
15786, 15790, 15794, 15797,	18247, 18249, 18251, 18253,	19545, 19547, 19548, 19549,
15799, 15801, 15803, 15804,	18255, 18257, 18259, 18261,	19550, 19551, 19552, 19553,
15806, 15808, 15810, 15812,	18263, 18265, 18268, 18271,	19554, 19555, 19556, 19660,
15814, 15816, 15818, 15821,	18273, 18275, 18277, 18279,	19694, 19695, 19696, 19697,
15823, 15825, 15827, 15829,	18282, 18286, 18289, 18292,	19698, 19699, 19700, 19701,
15831, 15833, 15834, 15836,	18294, 18296, 18298, 18300,	19702, 19703
15838, 15840, 15842, 15844,	18369, 18372, 18448, 18450,	\9 . 500, 1022, 1025, 1056, 1940,
15846, 15849, 15852, 16263,	18452, 18454, 18456, 18458,	1955, 1964, 1992, 2012,
16266, 16269, 16271, 16274,	18460, 18462, 18464, 18466,	2048, 2052, 2066, 2070,
16277, 16280, 16283, 16285,	18468, 18470, 18472, 18474,	2078, 2083, 2086, 2120,
16287, 16289, 16291, 16293,	18476, 18478, 18480, 18482,	2124, 2127, 2130, 2140,
16295, 16296, 16298, 16300,	18484, 18486, 18488, 18490,	2142, 2144, 2146, 2148,
16302, 16304, 16306, 16725,	18492, 18494, 18496, 18498,	2150, 2152, 2154, 2156,
16727, 16729, 16731, 16733,	18500, 18502, 18504, 18506,	2158, 15083, 16909, 16911,
16735, 16737, 16739, 16741,	18508, 18510, 18512, 18514,	16913, 16915, 16917, 16919,
16743, 16745, 16747, 16749,	18516, 18518, 18520, 18522,	16922, 16925, 16928, 16931,
16751, 16753, 16755, 16757,	18524, 18526, 18528, 18530,	16933, 16935, 16937, 16939,
16759, 16761, 16763, 16765,	18532, 18534, 18536, 18565,	16941, 16943, 16945, 16947,
16767, 16769, 16772, 16775,	18568, 18570, 18572, 18575,	16949, 16952, 16954, 16957,
16777, 16779, 16781, 16783,	18577, 18579, 18581, 18584,	16959, 16962, 16964, 16968,
16785, 16787, 16789, 16791,	18586, 18804, 18806, 18808,	16972, 16975, 16977, 16979,
16793, 16795, 16797, 16799,	18810, 18812, 18983, 18985,	16981, 16983, 16985, 16987,
16801, 16803, 16806, 16809,	18987, 18989, 18991, 18993,	16989, 16991, 16993, 16995,
16811, 16813, 16815, 16817,	18996, 19000, 19002, 19004,	16997, 16999, 17001, 17003,

17005, 17007, 17009, 17012,
17015, 17018, 17021, 17023,
17025, 17027, 17029, 17031,
17033, 17035, 17037, 17039,
17041, 17043, 17045, 17047,
17049, 17051, 17053, 17055,
17057, 17059, 17061, 17063,
17065, 17067, 17069, 17071,
17073, 17075, 17077, 17079,
17081, 17083, 17085, 17087,
17089, 17091, 17093, 17095,
17097, 17099, 17101, 17103,
17105, 17107, 17109, 17111,
17113, 17116, 17119, 17122,
17125, 17127, 17129, 17131,
17133, 17135, 17137, 17139,
17141, 17143, 17145, 17147,
17149, 17151, 17153, 17155,
17157, 17159, 17161, 17163,
17165, 17167, 17169, 17171,
17173, 17175, 17177, 17179,
17181, 17183, 17185, 17187,
17189, 17191, 17193, 17195,
17197, 17199, 17201, 17203,
17205, 17207, 17209, 17211,
17213, 17215, 17217, 17219,
17221, 17223, 17225, 17227,
17229, 17231, 17233, 17235,
17237, 17239, 17241, 17243,
17245, 17247, 17249, 17251,
17253, 17255, 17257, 17259,
17261, 17263, 17265, 17267,
17269, 17271, 17273, 17275,
17277, 17279, 17281, 17283,
17285, 17287, 17290, 17292,
17294, 17296, 17298, 17300,
17302, 17305, 17309, 17311,
17313, 17316, 17318, 17320,
17322, 17324, 17326, 17328,
17330, 17332, 17334, 17336,
17338, 17340, 17342, 17344,
17346, 17348, 17350, 17352,
17354, 17356, 17358, 17360,
17362, 17364, 17366, 17368,
17370, 17372, 17374, 17376,
17378, 17380, 17382, 17384,
17386, 17388, 17390, 17392,
17394, 17396, 17398, 17400,
17402, 17404, 17406, 17408,
17410, 17412, 17414, 17416,
17418, 17420, 17422, 17424,
17426, 17428, 17430, 17432,
17434, 17436, 17438, 17440,
17442, 17444, 17446, 17457,
17460, 17462, 17464, 17466,
17468, 17470, 17472, 17474,
17477, 17479, 17481, 17483,
17485, 17487, 17489, 17492,
17494, 17496, 17500, 17502,
17504, 17506, 17508, 17510,
17512, 17514, 17518, 17520,
17522, 17524, 17526, 17528,
17530, 17532, 17534, 17536,
17538, 17540, 17542, 17544,
17546, 17548, 17550, 17552,
17554, 17556, 17560, 17564,
17566, 17568, 17570, 17573,
17576, 17578, 17580, 17582,
17584, 17586, 17589, 17591,
17593, 17595, 17597, 17599,
17601, 17603, 17605, 17607,
17609, 17611, 17615, 17618,
17620, 17623, 17626, 17629,
17632, 17635, 17638, 17641,
17644, 17647, 17650, 17653,
17655, 17657, 17659, 17661,
17664, 17667, 17670, 17672,
17675, 17678, 17680, 17683,
17686, 17689, 17692, 17694,
17696, 17698, 17700, 17702,
17704, 17706, 17708, 17711,
17714, 17716, 17719, 17721,
17724, 17726, 17728, 17730,
17732, 17734, 17736, 17738,
17740, 17742, 17745, 17747,
17749, 17751, 17753, 17755,
17758, 17761, 17763, 17765,
17767, 17769, 17771, 17773,
17775, 17777, 17779, 17781,
17783, 17785, 17787, 17789,
17792, 17794, 17796, 17798,
17803, 17805, 17808, 17810,
17813, 17815, 17818, 17820,
17823, 17825, 17827, 17830,
17832, 17834, 17837, 17840,
17842, 17844, 17847, 17850,
17852, 17854, 17857, 17859,
17862, 17864, 17866, 17869,
17871, 17873, 17875, 17877,
17879, 17882, 17884, 17886,
17889, 17891, 17893, 17896,
17898, 17900, 17902, 17904,
17907, 17909, 17911, 17913,
17915, 17917, 17920, 17923,
17926, 17928, 17931, 17933,
17935, 17937, 17939, 17941,
17943, 17945, 17947, 17951,
17953, 17955, 17956, 17959,

18458, 18460, 18462, 18464,	18975, 18977, 18979, 18981,	19479, 19480, 19481, 19483,
18466, 18468, 18470, 18472,	18983, 18985, 18987, 18989,	19485, 19487, 19488, 19489,
18474, 18476, 18478, 18480,	18991, 18993, 18996, 19000,	19490, 19491, 19493, 19494,
18482, 18484, 18486, 18488,	19002, 19004, 19006, 19008,	19495, 19496, 19498, 19500,
18490, 18492, 18494, 18496,	19010, 19012, 19014, 19016,	19502, 19503, 19504, 19505,
18498, 18500, 18502, 18504,	19018, 19020, 19022, 19024,	19506, 19507, 19508, 19509,
18506, 18508, 18510, 18512,	19026, 19028, 19030, 19032,	19510, 19511, 19513, 19515,
18514, 18516, 18518, 18520,	19034, 19037, 19040, 19043,	19516, 19517, 19518, 19519,
18522, 18524, 18526, 18528,	19046, 19048, 19053, 19057,	19520, 19521, 19523, 19525,
18530, 18532, 18534, 18536,	19060, 19062, 19064, 19067,	19528, 19530, 19532, 19533,
18538, 18543, 18547, 18551,	19070, 19073, 19076, 19079,	19534, 19535, 19536, 19537,
18554, 18556, 18558, 18562,	19082, 19085, 19088, 19091,	19538, 19539, 19540, 19541,
18565, 18568, 18570, 18572,	19094, 19097, 19100, 19102,	19543, 19545, 19547, 19548,
18575, 18577, 18579, 18581,	19104, 19106, 19108, 19110,	19549, 19550, 19551, 19553,
18584, 18586, 18588, 18592,	19113, 19119, 19122, 19124,	19554, 19555, 19556, 19662,
18594, 18596, 18599, 18602,	19127, 19130, 19132, 19134,	19664
18605, 18609, 18611, 18613,	19136, 19138, 19140, 19142,	
18615, 18618, 18623, 18626,	19144, 19146, 19148, 19150,	A
18628, 18630, 18635, 18638,	19153, 19155, 19157, 19159,	\a 282, 284, 288, 294
18641, 18643, 18646, 18648,	19162, 19165, 19167, 19169,	\ABREVE 19431, 19502, 19503,
18650, 18653, 18660, 18663,	19171, 19174, 19176, 19179,	19504, 19505, 19506
18668, 18671, 18674, 18677,	19181, 19185, 19188, 19190,	\abreve . . 19425, 19442, 19443,
18680, 18683, 18686, 18689,	19192, 19194, 19196, 19198,	19444, 19445, 19446
18692, 18695, 18698, 18701,	19200, 19202, 19204, 19206,	\AC 17860, 20754
18704, 18707, 18710, 18713,	19208, 19210, 19212, 19215,	\AccFancyVerbLineautorefname
18716, 18719, 18722, 18726,	19217, 19219, 19222, 19225, 3113
18729, 18732, 18734, 18736,	19227, 19229, 19231, 19233,	\Accfootnoteautorefname . 3093
18738, 18740, 18742, 18745,	19235, 19237, 19239, 19241,	\Acctheoremautorefname . 3117
18747, 18749, 18751, 18753,	19243, 19245, 19247, 19249,	\acctonos 3175, 3176, 3177, 3178,
18755, 18758, 18760, 18763,	19251, 19253, 19255, 19257,	3179, 3180, 3181, 3182,
18765, 18768, 18770, 18772,	19259, 19261, 19263, 19265,	3183, 3184, 3185, 3186,
18774, 18776, 18778, 18780,	19267, 19269, 19271, 19273,	3187, 3188, 3189, 3190
18782, 18784, 18786, 18788,	19275, 19277, 19279, 19282,	\Acht 19370, 20554
18790, 18792, 18794, 18796,	19285, 19288, 19292, 19295,	\ACIRCUMFLEX 19432, 19507,
18799, 18801, 18804, 18806,	19298, 19300, 19302, 19304,	19508, 19509, 19510, 19511
18808, 18810, 18812, 18814,	19306, 19309, 19311, 19314,	\acircumflex 3162, 19426, 19447,
18818, 18822, 18824, 18826,	19316, 19318, 19320, 19322,	19448, 19449, 19450, 19451
18828, 18830, 18832, 18835,	19324, 19326, 19329, 19331,	\AcPa 19356, 20548
18837, 18840, 18842, 18844,	19334, 19337, 19340, 19343,	\Acrobatmenu 2201, 4247, 6346,
18846, 18848, 18850, 18853,	19345, 19347, 19349, 19351,	9296, 10036, 10577, 11451
18855, 18857, 18859, 18861,	19353, 19355, 19357, 19359,	\active 936,
18863, 18865, 18867, 18869,	19361, 19363, 19366, 19369,	943, 1520, 4736, 4737, 4738,
18871, 18873, 18875, 18877,	19371, 19373, 19375, 19377,	4739, 4740, 4741, 4744,
18880, 18882, 18884, 18886,	19379, 19381, 19383, 19386,	4746, 4749, 4757, 14382,
18888, 18890, 18892, 18894,	19389, 19391, 19393, 19395,	14409
18896, 18898, 18900, 18902,	19398, 19400, 19402, 19404,	\add@accent 512
18904, 18906, 18908, 18910,	19406, 19438, 19440, 19442,	\addcontentsline 7580, 7652,
18912, 18914, 18916, 18918,	19443, 19444, 19445, 19446,	7973, 7978, 8072
18920, 18922, 18924, 18927,	19447, 19448, 19449, 19450,	\addtocontents 8018, 8073
18929, 18931, 18933, 18935,	19451, 19453, 19455, 19456,	\addtocounter 7286
18937, 18939, 18941, 18943,	19457, 19458, 19459, 19460,	\AddToDocumentProperties
18945, 18947, 18949, 18951,	19461, 19463, 19465, 19468,	2293, 3703, 3709, 3715,
18953, 18956, 18959, 18961,	19470, 19472, 19473, 19474,	3721, 3744, 3750
18964, 18967, 18970, 18973,	19475, 19476, 19477, 19478,	

\AddToHook . 5362, 5364, 7306, 8590
 \AddToHookNext . 7025, 7297
 \adl@LT@array 7146
 \advance 455, 456, 957, 4885, 5074, 5087, 5383, 5711, 5757, 6192, 6193, 6196, 6197, 6528, 6536, 6573, 7874, 7884, 7887, 7901, 9402, 9486, 9524, 9564, 9879, 9889, 10732, 11938, 12225, 12477, 12549, 12592, 12593, 13087, 13150, 13194, 13195, 13441, 13506, 13550, 13551, 14168, 14170, 14171, 14177, 14186, 14286, 14496
 \AE 14870, 15329, 15844
 \ae 14936, 15396, 15846
 \afterassignment 1529, 1535, 1541, 5967
 \AfterBeginDocument . 342, 356
 \aftergroup 7465
 \agemo 17490, 20725
 \ainferior 19856
 \alef 19572
 \alefhamza 19564
 \aleflowerhamza 19568
 \alefmadda 19562
 \alefmaqsura 19630
 \aleph 17501, 19878
 \Alph 6622, 6991
 \alph 6623, 7261, 7288
 \alpha 19777
 \amalg 17764, 19972
 \AMSautorefname 8591
 \anchor@spot . 5266, 5279, 5286, 5292, 5294, 8935, 9343, 9438, 10309, 10386, 10889, 11236, 11239, 11875, 12162
 \and 6452
 \angle 17793, 19984
 \AngleSign 17801, 20746
 \Anglesign 17800, 20745
 \Ankh 18627, 20267
 \APLbox 18365, 20226
 \APLdown 18563, 20821
 \APLdownarrowbox ... 18354, 20221
 \APLinput 18357, 20222
 \APLinv 18331, 20213
 \APLleftarrowbox 18346, 20218
 \APLrightarrowbox 18349, 20219
 \APLup 18548, 20818
 \APLuparrowbox 18351, 20220
 \appendix 6983, 6995
 \appendixautorefname 2961, 2979, 2997, 3015, 3033, 3051, 3069, 3101, 3102, 3127, 3145, 3163, 3181, 3199, 3217, 3235, 3253, 8601
 \apprge 18010, 20769
 \apprle 18007, 20768
 \approx 17883, 20021
 \approxeq 17888, 20023
 \Aquarius 18714, 20865
 \aquarius 18712, 20293
 \arabic . 6619, 6852, 6854, 6856, 6859, 6860, 6861, 6863, 6864, 6865, 6866, 6868, 6869, 6870, 6871, 6872, 6873, 6876, 6886, 6887, 8083, 8092, 8137, 8152
 \Aries 18684, 20855
 \aries 18682, 20283
 \ast 17780, 19979
 \Asterisk 18928, 20376
 \AsteriskBold 18905, 20365
 \AsteriskCenterOpen ... 18907, 20366
 \AsteriskRoundedEnds . 18952, 20388
 \asymp 17901, 20029
 \AtBeginDocument 343, 5329, 5333, 6381, 7129, 7304, 12254
 \AtBeginShipout ... 6474, 6486, 9835
 \AtBeginShipoutBox 6478, 6481, 9836, 9837
 \AtBeginShipoutFirst ... 6491, 10197, 11655, 11794
 \AtEndDocument 6390
 \AtEndOfPackage 353
 \AtVeryEndDocument ... 6721, 13034
 \author 6408, 6418
 \autopageref 4369, 8482
 \autoref . 629, 4368, 8501, 12249
 \ayn 19608

B

\b 283, 284, 788, 792, 798, 14634, 14646, 14658, 15079, 15108, 15137, 16987, 16989, 16999, 17001, 17071, 17073, 17079, 17081, 17107, 17109, 17143,

\baa 19574
 \babymgamma 16025, 19745
 \back@none ... 2896, 2906, 2919
 \back@page 2898, 2911
 \back@section ... 2897, 2903, 2909, 2915
 \back@slide 2899, 2908
 \backcite 7789
 \backcong 17897, 20027
 \backneg 18303, 20200
 \backprime 17325, 19823
 \backref 7820, 12253
 \backsim 17861, 20011
 \backsimeq 18208, 20159
 \barb 15731, 20607
 \bard 15495, 20599
 \bari 16039, 19746
 \barin 18299, 20198
 \barj 16010, 20639
 \barl 15753, 19731
 \barlambd 15760, 20612
 \barleftharpoon .. 19087, 20442
 \baro 16085, 16086, 18335, 18337, 20811
 \barp 16953, 19814
 \barrightharpoon . 19093, 20444
 \barsci 16951, 19813
 \barscu 16956, 19815
 \baru 16150, 19755
 \barwedge 18190, 20151
 \baselineskip ... 2204, 9457, 10908, 10940, 11638
 \bb@cite@choice 7695
 \bb@info 604
 \bbslash 18377, 20229
 \BCPdata 473, 480, 486
 \Beam 18361, 20224
 \because 17846, 20005
 \BeforeTeXIVht 2683
 \begin 590, 12275, 20923
 \belowpdfbookmark 14282
 \beta 19778
 \betaainferior 19808
 \beth 17503, 19879
 \between 17994, 20070
 \bfseries 564, 8360, 8380, 8397, 8529
 \bgroup . 649, 4852, 7451, 7464, 8848, 9853, 10309, 10929, 12781, 12873, 12894
 \bibcite . 7686, 7692, 7696, 7721, 7736, 7753, 7763

\Bicycle 19390, 20563
 \bigcircle 20252
 \bigdoublevee . . . 19149, 20467
 \bigdoublewedge . 19147, 20466
 \bigtriangledown . 18561, 20242
 \bigtriangleup . . . 18546, 20237
 \binampersand . . 15177, 20582
 \bindnasrepma . . 17515, 20728
 \Biohazard 18625, 20266
 \bitsetGetDec
 5435, 5568, 5586, 5600,
 5613, 5629, 5661, 5686
 \bitsetGetHex 5436
 \bitsetGetSetBitList 5424
 \bitsetIsEmpty 5565, 5583, 5597,
 5610, 5626, 5658, 5683
 \bitsetReset 5538, 5572, 5591,
 5605, 5618, 5634, 5666
 \bitsetSetValue 5404, 5414
 \blacksmiley 18640, 20271
 \Bleech 18549, 20819
 \BOOKMARK 14214, 14293
 \booknumberline 14198, 14203
 \bool 6902
 \bot 18134, 20132
 \Bowtie 18198, 20800
 \bowtie 18196, 20154
 \Box 18600, 20825
 \box 6199, 6481, 8862, 9867,
 11283, 11286
 \boxast 19133, 20459
 \boxbackslash 18343, 20217
 \boxbar 18583, 20251
 \boxbox 19137, 20461
 \boxbslash 19131, 20458
 \boxcirc 19135, 20460
 \boxdot 18118, 20126
 \boxempty 18598, 20257
 \boxminus 18114, 20124
 \boxplus 18112, 20123
 \boxslash 19129, 20457
 \boxtimes 18116, 20125
 \brokenvert 15258, 20588
 \bullet 17784, 19818
 \Bumpeq 17906, 20031
 \bumpeq 17910, 20033

C

\C 15056, 16575, 16578
 \c 789, 793,
 799, 3063, 3071, 3072, 3073,
 6431, 6438, 14632, 14644,
 14656, 14872, 14938, 15068,
 15094, 15123, 15144, 15331,

15398, 15529, 15531, 15577,
 15579, 15587, 15589, 15607,
 15609, 15643, 15645, 15659,
 15661, 15667, 15669, 15924,
 15926, 16635, 16638, 17003,
 17005, 17051, 17053
 \c@footnote 7330, 7413, 7421,
 7535
 \c@Hy@AnnotLevel 9879, 9880,
 9889
 \c@Hy@tempcnt 4870, 4871,
 4877, 4885
 \c@note 7877
 \c@overlay 7877
 \c@page 6528, 6536, 6553, 6573,
 6574, 6578, 6590, 6592,
 6597, 6604, 6606, 6608,
 6637, 7874, 7878, 7880,
 7884, 7887, 7888, 7901,
 7931
 \c@secnumdepth 14558, 14573,
 14588
 \c@slide 7877
 \c@tocdepth 3412, 3417
 \calc@bm@number 14421, 14494
 \calculate@pdfview 3886, 3889
 \Cancer 18693, 20858
 \cancer 18691, 20286
 \Cap 18226, 20167
 \cap 17822, 19995
 \capdot 19173, 20477
 \capitalacute 15147
 \capitalbreve 15154
 \capitalcaron 15153
 \capitalcedilla 15144
 \capitalcircumflex 15148
 \capitaldieresis 15150
 \capitaldotaccent 15156
 \capitalgrave 15146
 \capitalhungarumlaut 15151
 \capitalmacron 15155
 \capitalnewtie 15158
 \capitalogonek 15145
 \capitalring 15152
 \capitaltie 15157
 \capitaltilde 15149
 \Capricorn 18711, 20864
 \capricornus 18709, 20292
 \caption 7550, 7552, 7640, 7642
 \catcode 172, 173, 184, 185,
 186, 187, 206, 809, 810, 811,
 812, 813, 814, 815, 816, 817,
 818, 819, 820, 821, 822, 823,
 824, 825, 826, 827, 830, 831,

832, 833, 834, 835, 836, 837,
 838, 839, 840, 841, 842, 843,
 844, 845, 846, 847, 912, 936,
 943, 1520, 1649, 1650, 1783,
 1784, 1840, 1841, 1842,
 4621, 4623, 4735, 4736,
 4737, 4738, 4739, 4740,
 4741, 4744, 4746, 4749,
 4757, 4767, 4858, 4859,
 8616, 10970, 10971, 14311,
 14313, 14382, 14385, 14409,
 14412
 \ccnc 19399, 20566
 \ccnd 19401
 \ccsa 19403, 20567
 \cdot 20574
 \cdots 18293, 20195
 \CESign 19407, 20569
 \CEsign 19409, 20918
 \cf@encoding 1261
 \chapterautorefname 2962, 2980,
 2998, 3016, 3034, 3052,
 3070, 3099, 3128, 3146,
 3164, 3182, 3200, 3218,
 3236, 3254, 8602
 \chapternumberline 14200, 14205
 \char 13068, 14315, 14352
 \chardef 258,
 301, 2460, 2461, 2462, 2463,
 2741, 2743, 4544, 4576,
 11231, 11234, 11240
 \check@bm@number 14432,
 14440, 14487, 14495
 \CheckBox 6141
 \CheckCommand 7410
 \checkcommand
 42, 7526, 7533, 7540,
 7640, 7650, 7747, 7759,
 8072, 8075, 8137, 8394
 \CheckedBox 18603, 20826
 \Checkedbox 18601, 20258
 \checklateX 4, 7525, 7639, 7746,
 8071, 8393
 \Checkmark 18849, 20338
 \checkmark 18851, 20884
 \CheckmarkBold 18852, 20339
 \checkpackage 9, 8136
 \chi 19799
 \chiinferior 19812
 \ChoiceBox 5761
 \ChoiceMenu 6138
 \circ 17782, 19980
 \circeq 17942, 20047
 \circlearrowleft 18999, 20407

\circlearrowright .	19001, 20408	\closedniomega .	16093, 20662	\curlyesh	16141, 20673
\CircledA	18422, 20230	\closedrevepsilon .	16006, 20638	\curlyvee	18212, 20161
\circledast	18106, 20121	\closeout	14302	\curlywedge	18215, 20162
\circledbslash . . .	19114, 20893	\Cloud	18589, 20253	\curlyyogh	16186, 20686
\circledcirc	18102, 20120	\ClowerTips	20355	\curlyz	16179, 20685
\circleddash	18110, 20122	\clubsuit	18728, 18730, 20871	\CurrentBorderColor	
\CircleShadow . . .	18960, 20391	\codeof	7811		8919, 8921, 8948, 8950,
\circcplus	19156, 20470	\Coffeecup	18608, 20260		8958, 8960, 8965, 10376,
\citation	7781	\coloncolonquals	19193, 20485		10410, 10412, 10428, 10430,
\citeauthoryear . . .	7847, 7853	\colonquals	17934, 20043		10449, 10451, 10513, 10515,
\citeN	7844	\color@begingroup	8848, 9853		10532, 10534
\CJK@char	939	\color@endgroup	8855, 9860	\currentpdfbookmark . . .	14274
\CJK@charx	940	\columnwidth	7458	\curru	16526
\CJK@CJK	928	\comma@entry	5752, 5759, 5761	\curvearrowleft	17617, 19912
\CJK@eight	1139, 1142, 1256	\comma@parse	5751	\curvearrowright	17619, 19913
\CJK@five	1139, 1141, 1256	\complement	17733, 19958	\CutLeft	18815, 20878
\CJK@four	1138, 1141, 1255	\Conclusion	17684, 20737	\CutLine	18540, 20815
\CJK@hundred	1205	\cong	17878, 20019	\Cutline	18541, 20816
\CJK@hundredmillion	1168	\Congruent	17960, 20763	\Cutright	18816, 20879
\CJK@ignorespaces	938	\contentsline	8019, <u>8024</u> , 8073,	\CuttingLine	18537, 20235
\CJK@kern	926		8075	\cyr	609, 3081, 3083, 3086, 3089,
\CJK@minus	1130	\copy	5083, 5085, 5096, 5104,		3092, 3093, 3094, 3095,
\CJK@nine	1139, 1143, 1256		8858, 9837, 9863		3096, 3097, 3098, 3099,
\CJK@null	1232	\copyright	19721		3100, 3101, 3103, 3105,
\CJK@one	1138, 1140, 1255	\Corresponds	17949, 20761		3106, 3107, 3108, 3109,
\CJK@punctchar	941	\corresponds	17948, 20760		3110, 3111, 3112, 3113,
\CJK@punctcharx	942	\count@	955, 956, 957,		3114, 3115, 3116, 3117,
\CJK@seven	1139, 1142, 1256		958, 1530, 1888, 3428, 3429,		3118
\CJK@six	1139, 1142, 1256		3434, 3435, 5382, 5383,	\CYRA	16360, 16751, 16755
\CJK@ten	1140, 1141, 1142,		5398, 5694, 5709, 5711,	\cyra	3083, 3090, 3092, 3097,
	1143, 1220		5735, 5757, 5773, 10728,		3100, 3105, 3106, 3112,
\CJK@tenthsousand	1153, 1174		10729, 10730, 10731, 10732,		3116, 16427, 16753, 16757
\CJK@thousand	1190	\Cross	18868, 20347	\CYRABHCH	16715, 16720
\CJK@three	1138, 1141, 1255	\crossb	15728, 20605	\cyrabch	16717, 16723
\CJK@two	1138, 1140, 1255	\CrossClowerTips	18885	\CYRABHCHDSC	16719
\CJK@zero	1138, 1156, 1173,	\crossd	15492, 20597	\cyrabchdsc	16722
	1177, 1193, 1208, 1230	\CrossedBox	18607, 20828	\CYRABHDZE	16785
\CJKdigits	1015	\Crossedbox	18604, 20259	\cyrabhdze	16787
\CJKkern	927	\crossh	15541, 20601	\CYRABHHA	16670
\CJKnumber	1014	\CrossMaltese	18874, 20350	\cyrabhha	16672
\cl@ckpt	6941	\crossnilambda	15759, 20611	\CYRAE	16759
\CleaningA	18424, 20813	\CrossOpenShadow	18870, 20348	\cyrae	16761
\CleaningF	18435, 20231	\CrossOutline	18872, 20349	\CYRB	16362
\CleaningFF	18437, 20232	\cs	5022, 5027, 5031, 5040, 5044,	\cyrb	3097, 16429
\CleaningP	18459, 20233		5053	\CYRBYUS	16550
\CleaningPP	18461, 20234	\Cube	587	\cyrbyus	16552
\clickb	16207, 20692	\Cup	18229, 20168	\CYRC	16405
\clickc	16202, 20690	\cup	17824, 19996	\cyc	16472
\clickt	16144, 20674	\cupdot	18063, 20103	\CYRCH	16407, 16827
\clock	18309, 20203	\cupplus	18065, 20104	\cyrch	3089, 3090, 3098, 16474,
\ClockLogo	18312, 20810	\curlyc	15974, 20631		16829
\Clocklogo	18311, 20809	\curlyeqprec	18248, 20176	\CYRCHLDSC	16743
\close@pdflink	8929, 8954, 8963,	\curlyeqsucc	18252, 20178	\cyrchldsc	16745
	8995, 9032, 9065, 9320			\CYRCHRDSC	16701

\cyrchrdsc	16703	\CYRIOTBYUS	16554	\CYRNHK	16739
\CYRCHVCRS	16706	\cyriotbyus	16556	\cyrnhk	16741
\cyrchvcrs	16709	\CYRIOTE	16538	\CYRNJE	16347
\CYRD	16368	\cyriote	16540	\cyrnje	16517
\cyrd ... 3086, 3089, 3100, 3105,	3106, 16435	\CYRIOTLYUS	16546	\CYRO	16389, 16797
\CYRDJE	16329	\cyriotlyus	16548	\cyro ... 3086, 3089, 3092, 3093,	
\cyrdje	16499	\CYRISHRT	16378	3103, 3112, 3113, 3115,	
\CYRDZE 15038, 15055, 16322,	16335	\cyrishrt	16445	3116, 3117, 16456, 16799	
\cyrdze	16505	\CYRISHRTDSC	16602	\CYROMEGA	16530
\CYRDZHE	16358	\cyrishrtdsc	16604	\cyromega	16532
\cyrdzhe	16528	\CYRIZH	16570, 16575	\CYROMEGARND	16584
\CYRE ... 16324, 16327, 16370,	16763	\cyrizh	16572, 16578	\cyromegarnd	16586
\cyre ... 3083, 3089, 3090, 3103,	3115, 3116, 3117, 16437,	\CYRJE	16343	\CYROMEGATITLO ... 16588	
16494, 16497, 16765		\cyrje	16513	\cyromegatitlo	16590
\cyreref	16813	\CYRK	16351, 16381	\CYROT	16592
\CYREREV ... 16421, 16811		\cyrk ... 3092, 3093, 3095, 3109,		\cyrot	16594
\cyrerev	16488	3110, 3112, 3113, 3114,		\CYROTLD ... 16801, 16806	
\CYRERY ... 16416, 16835		16448, 16521		\cyrotld	16803, 16809
\cyrery 3081, 3083, 16483, 16837		\CYRKBEAK	16654	\CYRP	16391
\CYRF	16401	\cyrkbeak	16656	\cyrp ... 3086, 3089, 3090, 3094,	
\cyrf	16468	\CYRKDSC	16640	3095, 3101, 3103, 3107,	
\CYRFITA	16566	\cyrkdsc	16642	3108, 3109, 3110, 16458	
\cyrfita	16568	\CYRKHCRS	16650	\CYRpalochna	16725
\CYRG ... 16331, 16366		\cyrkhcrs	16652	\CYRPHK	16666
\cyrg ... 3099, 16433, 16501		\CYRKHK	16731	\cyrphk	16668
\CYRGDSC	16831	\cyrkhk	16733	\CYRPSI	16562
\cyrgdsc	16833	\CYRKOPPA	16596	\cyrpsi	16564
\CYRGHCRS	16618	\cyrkoppa	16598	\CYRR	16393
\cyrghcrs	16620	\CYRKSI	16558	\cyrr ... 3081, 3083, 3086, 3089,	
\CYRGHK	16623	\cyrksi	16560	3090, 3096, 3100, 3101,	
\cyrghk	16626	\CYRKVCRS	16645	3103, 3105, 3106, 3111,	
\CYRGUP	16614	\cyrkvcrs	16648	3112, 3113, 3114, 3115,	
\cyrgup	16616	\CYRL	16383	3116, 3117, 16460	
\CYRH	16403	\cylr ... 3097, 3099, 3101, 3103,		\CYRRTICK	16610
\cyrh	16470	16450		\cyrrtick	16612
\CYRHDSC	16692	\CYRLDSC	16735	\CYRS	16395, 16675
\cyrhdesc	16694	\cyrldesc	16737	\crys ... 3086, 3089, 3092, 3093,	
\CYRHHK	16839	\CYRLJE	16345	3096, 3111, 3112, 3113,	
\cyrhhk	16841	\cylrje	16515	3114, 3118, 16462, 16678	
\CYRHRDSN	16414	\CYRLYUS	16542	\CYRSCHWA ... 16767, 16772	
\cyrhrdsn . 16480, 16481, 20699		\cylrylus	16544	\cryscha	16769, 16775
\CYRI ... 16353, 16376, 16379,	16789, 16793	\CYRM	16385	\CYRSDSC ... 16674, 16675	
\cyri 3083, 3086, 3090, 3096, 3101,		\cylrm ... 3086, 3090, 3116, 3117,		\crysdesc	16677
3103, 16443, 16446, 16523,		16452		\CYRSEMISFTSN ... 16606	
16791, 16795		\CYRMDSC	16747	\cryssemitsn	16608
\CYRIE	16333	\cylrmdsc	16749	\CYRSFTSN	16419
\cyrie	16503	\CYRN	16387	\crysftsn ... 16485, 16486, 20700	
\CYRII ... 16338, 16341		\cylrn ... 3083, 3089, 3090, 3092,		\CYRSH	16409
\cyrii	16508, 16511	3093, 3095, 3103, 3109,		\cylrsh	16476
		3110, 16454		\CYRSHCH	16411
		\CYRNDSC	16658	\cylrshch	16478
		\cylrndsc	16660	\CYRSHHA	16711
		\CYRNG	16662	\cylrshha	16713
		\cylrng	16664	\CYRT	16397

\cyrt . . . 3086, 3089, 3095, 3097, 3109, 3110, 3111, 3112, 3113, 3114, 3115, 3116, 3117, 16464

\CYRTDSC 16680

\cyrtdesc 16682

\CYRTESE 16696

\cyrte 16698

\cyrthousands 16600

\CYRTSHE 16349

\cyrtshe 16519

\CYRU . . . 16356, 16399, 16815, 16819, 16823

\cyru . . . 3093, 3095, 3109, 3110, 3113, 3117, 16466, 16817, 16821, 16825

\CYRUK 16580

\cruk 16582

\CYRUSHRT 16355

\cyrushrt 16525

\CYRV 16364

\cdrv 3081, 3083, 16431

\CYRY 16684

\cyry 16686

\CYRYA 16425

\cyrya 16492

\CYRYAT 16534

\crysat 16536

\CYRYHCRS 16688

\crysahcrs 16690

\CYRYI 16340

\crysai 16510

\CYRYO 16326

\crysao 16496

\CYRYU 16423

\crysau 16490

\CYRZ . . . 16374, 16635, 16781

\crys . . . 3100, 3105, 3106, 16441, 16638, 16783

\CYRZDSC 16634

\crysdesc 16637

\CYRZH . . . 16372, 16727, 16777

\cryszh . . . 3083, 3103, 16439, 16729, 16779

\CYRZHDSC 16629

\cryszhdesc 16632

D

\d 790, 794, 800, 3159, 3163, 3165, 3166, 3167, 3168, 3169, 3171, 14635, 14647, 14659, 15062, 15109, 15138, 16983, 16985, 16995, 16997, 17043, 17045, 17067, 17069, 17075, 17077, 17095, 17097, 17103, 17105, 17139, 17141, 17151, 17153, 17159, 17161, 17187, 17189, 17207, 17209, 17227, 17229, 17245, 17247, 17249, 17251, 17257, 17259, 17261, 17263, 17265, 17267, 17273, 17275, 19438, 19443, 19448, 19453, 19458, 19463, 19468, 19473, 19478, 19483, 19488, 19493, 19498, 19503, 19508, 19513, 19518, 19523, 19528, 19533, 19538, 19543, 19548, 19553

\dad 19602

\dag 17303, 20711

\dagger 19817

\dal 19588

\daleth 17507, 19881

\damma 19642

\danger 18779, 20312

\dasheddownarrow 17718, 19951

\dashedleftarrow 17712, 20738

\dashedrightarrow 17717, 20739

\dasheduparrow 17713, 19949

\dashleftarrow 17710, 19948

\dashrightarrow 17715, 19950

\DashV 19291, 20530

\Dashv 19284, 20528

\dashV 20526

\dashv 18123, 20128

\DavidStar 18876, 20351

\davidstar 18878, 20885

\ddag 17307, 20713

\ddagger 14732, 17304, 17306, 20712

\ddots 18297, 20197

\DeclareFontEncoding . . . 14623, 15025

\DeclareFontFamily 860, 870

\DeclareFontShape 861, 871

\DeclareFontSubstitution . . . 862, 872

\DeclareLocalOptions 4181

\DeclareRobustCommand 4849, 4936, 4938, 4940, 4949, 6135, 6138, 6141, 6144, 6147, 6150, 6153, 6294, 6298, 6367, 6371, 8482, 14512

\DeclareTextAccent 14624, 14625, 14626, 14627, 14628, 14629, 14630, 14631, 14632, 14633, 14634, 14635

\DeclareVoidOption . . . 2680, 2694, 2705, 2721, 2727, 2732, 2746, 2756, 2761, 2767, 2773, 2802, 2819, 2826, 2832, 2837, 2842, 2857, 3339, 3347, 3355, 3365

\DefaultHeightofCheckBox . . . 6205, 12721, 13325, 13702

\DefaultHeightofChoiceMenu . . . 6207, 12539, 13140, 13496

\DefaultHeightofReset 6203, 12691, 13297, 13670

\DefaultHeightofSubmit 6201, 12671, 13274, 13647

\DefaultHeightofText 6209, 12511, 13114, 13463

\DefaultHeightofTextMultiline 6210, 12509, 13112, 13461

\DefaultOptionsofCheckBox 6215, 12723, 13327, 13704

\DefaultOptionsofComboBox 6218

\DefaultOptionsofListBox 6217

\DefaultOptionsofPopdownBox 6219

\DefaultOptionsofPushButton 6214, 12642, 13246, 13615

\DefaultOptionsofRadio 6220

\DefaultOptionsofReset 6213, 12694, 13300, 13673

\DefaultOptionsofSubmit 6212, 12674, 13277, 13650

\DefaultOptionsofText 6216, 12516, 13119, 13468

\DefaultWidthofCheckBox 6206, 12720, 13324, 13701

\DefaultWidthofChoiceMenu 6208, 12538, 13139, 13495

\DefaultWidthofReset 6204, 12690, 13296, 13669

\DefaultWidthofSubmit 6202, 12670, 13273, 13646

\DefaultWidthofText 6211, 12506, 13109, 13458

\define@key 2358, 2360, 2404, 2419, 2422, 2425, 2433, 2436, 2446, 2449, 2452, 2469, 2481, 2483, 2486, 2503, 2507, 2513, 2516, 2519, 2522, 2525, 2528, 2531, 2556, 2613, 2619, 2738, 2864, 2880, 2890,

2893, 2900, 2929, 2948,	\diamondsuit 18725, 18727,	\doteqdot 17919, 20037
2951, 3296, 3362, 3374,	20870	\dotminus 17853, 20008
3389, 3406, 3409, 3413,	\digamma 20698	\dotplus 17772, 19975
3441, 3446, 3450, 3453,	\dimen@ 1536, 1613, 1614, 1617,	\dots 524
3460, 3472, 3479, 3489,	1619, 4153, 4154, 4156,	\dottimes 19161, 20472
3492, 3495, 3499, 3515,	4163, 4164, 5073, 5074,	\doublebarwedge . 19184, 20481
3525, 3532, 3543, 3556,	5077, 5086, 5087, 5091,	\doublecap 18228, 20803
3573, 3663, 3672, 3702,	5968, 5977, 6764, 6765,	\doublecup 18231, 20804
3708, 3714, 3720, 3726,	8875, 8877, 10701, 10702,	\doublesqcap 19172, 20900
3731, 3737, 3743, 3749,	10704, 11273, 11288, 11291,	\doublesqcup 19177, 20901
3755, 3788, 3795, 3886,	11685, 11687, 11752, 11754,	\doublevav 16902
3887, 3900, 3907, 3917,	11846, 11848, 12130, 12132	\doublevee 19180, 20480
3958, 3959, 3962, 3965,	\dimexpr 470, 1294, 1916, 1918,	\doublewedge 19178, 20479
3968, 3971, 3974, 3977,	1926, 1931, 1934, 1936,	\doubleyod 16906
3980, 4003, 4117, 4120,	1950, 1952, 1955, 1956,	\DOWNarrow 18557, 20241
4866, 4895, 4901, 4913,	1963, 1966, 1969, 1970,	\Downarrow 17685, 19937
5376, 5464, 5520, 5822,	1971, 1972, 1982, 1987,	\downarrow 19887
5827, 5840, 5868, 5911,	1995, 1999, 2004, 2014,	\downdownarrows 17660, 19928
5914, 5917, 5921, 5924,	2017, 2022, 2025, 2030,	\downdownharpoons 19081,
5928, 5931, 5935, 5939,	2031, 5977	20440
5943, 5946, 5950, 5953,	\ding 586, 6018, 6021	\downharpoonleft 17643, 19921
5956, 5959, 5962, 5982,	\DingObject 13219	\downharpoonright 17640, 19920
5998, 6001, 6004, 6007,	\discretionary 651	\downmodels 19297, 20532
6010, 6013, 6043, 6046,	\div 20572	\downtherefore 17848, 20752
6049, 6052, 6071, 6077,	\divdot 19160, 20899	\downuparrows 17723, 19953
6091, 6096, 6102, 6119,	\divide 10729	\downupharpoons 19099, 20446
6124, 6130, 6734, 6745,	\divideontimes 18194, 20153	\downvdash 18131, 20782
7024, 10807, 10813, 11315,	\Divides 17774, 19976	\dp 5073, 5081, 5094, 6195, 6198,
11317, 11320, 11323, 11325,	\DividesNot 17776, 19977	7456, 9392, 9472, 9509,
11327, 11336, 11344, 11351,	\DJ 3171, 14891, 15487	9549, 11274, 11277, 11928,
11353, 11355, 11357, 11359,	\dj 3168, 3169, 15490	12210, 13436
11361, 11370, 11380, 11382,	\dlsh 17614, 19911	\dsbiological 18773, 20309
11384, 11385, 11391, 11400,	\do 956, 2376, 2381, 2386, 3513,	\dschemical 18771, 20308
11402, 11404, 11406, 11408,	3545, 3546, 3547, 3548,	\dscommercial 18775, 20310
11410, 11412, 11414, 11416,	3603, 3604, 3605, 3606,	\dsjuridical 18769, 20307
11418, 11420, 11422, 11424,	3607, 3608, 3611, 3612,	\dsmedical 18767, 20306
11426, 11428, 11430, 11431,	3613, 3614, 3615, 3616,	\dsmilitary 18764, 20305
11432, 11433, 11434, 11435,	3619, 3620, 3623, 3624,	\dtimes 19164, 20473
11436, 11437, 11438, 11439,	3625, 3626, 3627, 3630,	\dvipdfm@setdim 13433, 13483,
11440, 11441	3631, 3632, 3633, 3634,	13582, 13605, 13636, 13661,
\Deleatur 17456, 19869	3637, 3638, 3639, 3640,	13689, 13718
\Delta 19767	3641, 3644, 3645, 3646,	\dz 16238, 20696
\delta 19780	3647, 3648, 3651, 3652,	
\Denarius 17458, 20724	3655, 3656, 3657, 3660,	
\dest@name 5309	3661, 3667, 3668, 3669,	
\df@tag 8104, 8110	3670, 3996, 3997, 3998,	
\DH 14890, 15349	3999, 4000, 4001, 5424,	
\dh 14960, 15420, 15421, 20596	7272, 12543, 12605, 12843,	
\dhal 19590	12850, 12860, 13144, 13207,	
\DiamondandSolid 20396	13500, 13566, 14381, 14408	
\diameter 18301, 20199	\documentclass 2, 8732	
\Diamond 18573, 20822	\dospecials 14390, 14417	
\diamond 18571, 20246	\Doteq 17921, 20759	
\diamondddots 17347, 19826	\doteq 17914, 20035	

E

\Earth 18661, 20846
\earth 18659, 20276
\ECIRCUMFLEX 19433, 19517,
19518, 19519, 19520, 19521
\ecircumflex 19427, 19457, 19458,
19459, 19460, 19461
\Ecommerce 17498, 20727
\EdefEscapeName 3819, 3869,
9299, 10039, 10578, 11452,

\textcolor{red}{12604}, \textcolor{red}{12607}, \textcolor{red}{13206}, \textcolor{red}{13209},	\textcolor{red}{13562}, \textcolor{red}{13568}	\textcolor{red}{\eqcolon} 17856, 20009	\textcolor{red}{\FancyVerbLineautorefname} 2968, 2986, 3004, 3022,
\textcolor{red}{\EdefEscapeString} 761, 771		\textcolor{red}{\eqdot} 19189, 20483	3040, 3058, 3076, 3111,
\textcolor{red}{\EdefUnescapeName} 3820		\textcolor{red}{\eqnarray} 7219, 7222, 7244	3114, 3134, 3152, 3170,
\textcolor{red}{\EdefUnescapeString} 756, 7940		\textcolor{red}{\eqsim} 17870, 20015	3188, 3206, 3224, 3242,
\textcolor{red}{\egroup} 650, 8855, 9860, 10309,		\textcolor{red}{\eqslantgr} 19228, 20501	3260, 8608
10965, 12790, 12882, 12907		\textcolor{red}{\eqslantless} 19226, 20500	
\textcolor{red}{\EightAsterisk} 18958, 20390		\textcolor{red}{\equal} 7808	\textcolor{red}{\farsikaf} 19656
\textcolor{red}{\EightFlowerPetal} 18936, 20380		\textcolor{red}{\equalscolon} 17936, 20044	\textcolor{red}{\farsiya} 19660
\textcolor{red}{\EightFlowerPetalRemoved} 18955, 20389		\textcolor{red}{\equalsinferior} 19853	\textcolor{red}{\fatha} 19640
\textcolor{red}{\ighthnote} 18743, 20872		\textcolor{red}{\equalsuperior} 19837	\textcolor{red}{\fatsemi} 19154, 20469
\textcolor{red}{\eightinferior} 19849		\textcolor{red}{\equation} 7175, 7185, 7189, 7198	\textcolor{red}{\Fax} 19385, 20561
\textcolor{red}{\EightStar} 18915, 20370		\textcolor{red}{\equationautorefname} 2955, 2973, 2991, 3009,	\textcolor{red}{\fax} 17509, 19882
\textcolor{red}{\EightStarBold} 18917, 20371		3027, 3045, 3063, 3081,	\textcolor{red}{\Faxmachine} 19387, 20917
\textcolor{red}{\EightStarConvex} 18911, 20368		3082, 3121, 3139, 3157,	\textcolor{red}{\fbox} 13072, 13075
\textcolor{red}{\EightStarTaper} 18909, 20367		3175, 3193, 3211, 3229,	\textcolor{red}{\fcdice} 589, 20578
\textcolor{red}{\eightsuperior} 19833		3247, 8591, 8595	\textcolor{red}{\Female} 18658, 20845
\textcolor{red}{\einferior} 19857		\textcolor{red}{\equiv} 17958, 20054	\textcolor{red}{\female} 18652, 18655, 20842
\textcolor{red}{\ejective} 16190, 20687		\textcolor{red}{\Equivalence} 17690	\textcolor{red}{\FemaleFemale} 18781, 20313
\textcolor{red}{\ell} 17469, 19872		\textcolor{red}{\er} 15991, 20635	\textcolor{red}{\FemaleMale} 18785, 20315
\textcolor{red}{\em} 570		\textcolor{red}{\errmessage} 3293	\textcolor{red}{\Field@addtoks} 5890, 5922, 5925,
\textcolor{red}{\emgma} 16072, 20658		\textcolor{red}{\escapechar} 493, 4319, 7265,	6097, 6120
\textcolor{red}{\emph} 549		14241, 14419, 14470	\textcolor{red}{\Field@boolkey} 5377, 5465, 5884,
\textcolor{red}{\empty} 938, 3416		\textcolor{red}{\esh} 16131, 19754	5915, 5918
\textcolor{red}{\emptyset} 17741, 19962		\textcolor{red}{\EstimatedSign} 17497, 20726	\textcolor{red}{\Field@toks} 5888, 5889,
\textcolor{red}{\enc@html} 5826, 5829		\textcolor{red}{\eta} 19783	5891, 12782, 12799, 12810,
\textcolor{red}{\enc@update} 509		\textcolor{red}{\eTeX} 535, 12281	12821, 12831, 12848, 12866,
\textcolor{red}{\END} 1286, 1287, 1313, 1314,		\textcolor{red}{\eth} 15421, 20596	12874, 12879, 12895, 12904
1329, 1330, 1347, 1348,		\textcolor{red}{\Eur} 17455, 20723	\textcolor{red}{\Field@Width} 5801, 5948
1365, 1366, 1722, 1728,		\textcolor{red}{\EURcr} 17452, 20720	\textcolor{red}{\figureautorefname} 2958, 2976,
1733, 1835, 1837, 9182,		\textcolor{red}{\EurCr} 17451, 20719	2994, 3012, 3030, 3048,
9195, 9199, 9206, 9219,		\textcolor{red}{\EURdig} 17448, 20716	3066, 3096, 3124, 3142,
9223		\textcolor{red}{\EurDig} 17447, 20715	3160, 3178, 3196, 3214,
\textcolor{red}{\end} 591, 20924		\textcolor{red}{\EURrv} 17450, 20718	3232, 3250, 8598
\textcolor{red}{\endeqnarray} 7220, 7239, 7247		\textcolor{red}{\EurHv} 17449, 20717	\textcolor{red}{\filename@area} 5207
\textcolor{red}{\endequation} 7176, 7207		\textcolor{red}{\EURtm} 17454, 20722	\textcolor{red}{\filename@base} 5207
\textcolor{red}{\endForm} 5816		\textcolor{red}{\EurTm} 17453, 20721	\textcolor{red}{\filename@ext} 5204, 5205, 5207,
\textcolor{red}{\endinput} 64, 2691, 2786, 4365,		\textcolor{red}{\evensidemargin} 7958	5208
4496, 8354, 10898, 12273,		\textcolor{red}{\ExecuteOptions} 4168, 4169,	\textcolor{red}{\filename@parse} 5203
14502		4173	\textcolor{red}{\find@pdflink} 8901, 8952, 8962
\textcolor{red}{\endlinechar} 808, 829, 4734		\textcolor{red}{\exists} 17737, 19960	\textcolor{red}{\Finv} 17499, 19877
\textcolor{red}{\endNoHyper} 6328		\textcolor{red}{\exp} 479, 485, 2299	\textcolor{red}{\Fire} 19388, 20562
\textcolor{red}{\EndPreamble} 12276		\textcolor{red}{\ExplSyntaxOff} 490, 2311, 5057,	\textcolor{red}{\fivedots} 19323, 20543
\textcolor{red}{\endsubeqnarray} 7251, 7258		6918	\textcolor{red}{\FiveFlowerOpen} 18934, 20379
\textcolor{red}{\eng} 15620, 20603		\textcolor{red}{\ExplSyntaxOn} 232, 474, 2293,	\textcolor{red}{\FiveFlowerPetal} 18932, 20378
\textcolor{red}{\engma} 15621, 20604		5021, 6897	\textcolor{red}{\fiveinferior} 19846
\textcolor{red}{\ensuremath} 635		\textcolor{red}{\extravietnam} 3348	\textcolor{red}{\FiveStar} 18591, 20254
\textcolor{red}{\Envelope} 18831, 20330		\textcolor{red}{\extravietnamese} 3340	\textcolor{red}{\FiveStarCenterOpen} 18893,
\textcolor{red}{\enya} 16076, 20660		\textcolor{red}{\EyesDollar} 15172, 20581	20359
\textcolor{red}{\epsdice} 588, 20577			\textcolor{red}{\FiveStarConvex} 18901, 20363
\textcolor{red}{\epsi} 15995, 20636			\textcolor{red}{\FiveStarOpen} 18593, 20255
\textcolor{red}{\epsilonpsilon} 19781			\textcolor{red}{\FiveStarOpenCircled} 18891,
\textcolor{red}{\eqcirc} 17938, 20045			20358
			\textcolor{red}{\FiveStarOpenDotted} 18895,
			20360

\FiveStarOutline . 18897, 20361
 \FiveStarOutlineHeavy . 18899,
 20362
 \FiveStarShadow . 18903, 20364
 \fivesuperior 19830
 \Flag 18759, 20303
 \flap 16119, 20671
 \flapr 16118, 20670
 \flat 18748, 20298
 \Fld@additionalactions 13846,
 13889, 13893
 \Fld@DingDef 6018, 6021, 6040
 \Fld@additionalactions . 13846,
 13937, 13966, 14001, 14036,
 14071, 14106, 14138
 \Fld@align . 5805, 6005, 13915,
 13976, 14045
 \Fld@altname 5938, 5940, 13826,
 13828, 13899, 13901
 \Fld@cannotflags 5584,
 5586, 13910, 13943, 13971,
 14005, 14040, 14076, 14112
 \Fld@cannotnames 13897, 13912,
 13945, 13973, 14007, 14042,
 14078, 14114
 \Fld@bcolor . 5807, 6047, 13927,
 13929, 13992, 13994, 14021,
 14023, 14049, 14061, 14063
 \fld@bcolor 13980
 \Fld@bordercolor 5808,
 6050, 13923, 13925, 13951,
 13959, 13961, 13979, 13988,
 13990, 14017, 14019, 14048,
 14057, 14059, 14084, 14092,
 14094, 14120, 14128, 14130
 \Fld@bordersep 5809, 5999
 \Fld@borderstyle
 .. 5811, 5983, 5984, 5985,
 5995, 13916, 13949, 13977,
 14011, 14046, 14082, 14136
 \Fld@borderwidth
 .. 5810, 5963, 6189, 6192,
 6193, 6196, 6197, 12592,
 12593, 13194, 13195, 13550,
 13551, 13916, 13949, 13977,
 14011, 14046, 14082, 14136
 \Fld@calculate@code 6058, 12491,
 12995, 13449, 13859, 13861
 \Fld@calculate@sortkey .. 6090,
 6092, 13004
 \Fld@cbsymbol 5812, 6011, 13931
 \Fld@charsize 5802, 5803, 5960,
 12591, 13193, 13549, 13933,
 13998, 14027, 14067, 14118
 \Fld@checkedfalse 5798
 \Fld@checkequals .. 5902, 12544,
 12606, 12851, 12861, 13145,
 13208, 13501, 13567
 \Fld@choices
 .. 5691, 5699, 5701, 5705,
 5714, 5722, 5727, 5775,
 5777, 5785, 5786, 14000
 \Fld@color .. 5806, 6053, 13934,
 13999, 14028, 14068
 \Fld@default .. 5716, 5719, 5721,
 6002, 12504, 12520, 12536,
 12576, 12604, 12718, 12780,
 12798, 12812, 12820, 12827,
 12853, 12863, 12893, 12903,
 13107, 13124, 13137, 13178,
 13206, 13322, 13456, 13473,
 13493, 13534, 13562, 13699,
 14029, 14033, 14034, 14069
 \Fld@DingDef . 6011, 6014, 6016
 \Fld@disabledfalse 5799
 \Fld@export .. 5529, 5532, 5539,
 5831
 \Fld@findlength .. 12830, 12841
 \Fld@flags 5598, 5600, 5611, 5613,
 5627, 5629, 5659, 5661,
 5684, 5686, 13914, 13947,
 13975, 14009, 14044, 14080,
 14116
 \Fld@format@code .. 6056, 13851,
 13853
 \Fld@getmethodfalse 5851
 \Fld@getmethodtrue 5853
 \Fld@height 5957, 12507, 12525,
 12539, 12594, 12614, 12631,
 12671, 12691, 12721, 12731,
 13110, 13130, 13140, 13196,
 13224, 13238, 13274, 13297,
 13325, 13337, 13459, 13475,
 13496, 13552, 13564, 13598,
 13647, 13670, 13702, 13710
 \Fld@hiddenfalse 5487
 \Fld@hiddentreue 5488
 \Fld@invisiblefalse 5483
 \Fld@invisiblereue 5484
 \Fld@keystroke@code 6059,
 13847, 13849
 \Fld@listcount 12603, 12608,
 12611, 12616, 12621, 12626,
 13205, 13210, 13225, 13231,
 13561, 13569, 13573, 13578,
 13589, 13594
 \Fld@loc 5912
 \Fld@mappingname .. 5942, 5944,
 13830, 13832, 13903, 13905
 \Fld@maxlen .. 5804, 5951, 14072
 \Fld@menulength .. 5800, 5954,
 12541, 12545, 12591, 12842,
 12843, 12846, 13142, 13146,
 13193, 13498, 13502, 13549
 \Fld@name 5936, 12503, 12535,
 12639, 12717, 12779, 12784,
 12795, 12796, 12807, 12808,
 12817, 12818, 12826, 12847,
 12864, 12872, 12877, 12892,
 12901, 13106, 13136, 13243,
 13321, 13455, 13492, 13612,
 13698, 13825, 13898
 \Fld@norotatefalse 5500
 \Fld@norotatetrue 5499
 \Fld@noviewfalse 5503
 \Fld@noviewtrue 5504
 \Fld@nozoomfalse 5496
 \Fld@nozoomtrue 5495
 \Fld@onblur@code .. 6061, 13867,
 13869
 \Fld@onclick@code .. 6055, 6131,
 13965
 \Fld@onenter@code 6064, 13879,
 13881
 \Fld@onexit@code .. 6065, 13883,
 13885
 \Fld@onfocus@code 6060, 13863,
 13865
 \Fld@onmousedown@code 6062,
 13871, 13873
 \Fld@onmouseup@code .. 6063,
 13875, 13877
 \Fld@pageobjref .. 12482, 13080,
 13091, 13446, 13781, 13911,
 13944, 13972, 14006, 14041,
 14077, 14113
 \Fld@printfalse 5492
 \Fld@printtrue 5491
 \Fld@radiosymbol .. 5813, 6014,
 14025
 \Fld@rotation 5814,
 6044, 13919, 13921, 13950,
 13955, 13957, 13978, 13984,
 13986, 14013, 14015, 14047,
 14053, 14055, 14083, 14088,
 14090, 14119, 14124, 14126
 \Fld@submitflags .. 5566, 5568,
 14104
 \Fld@temp .. 6017, 6019, 6022,
 6023, 6032, 6033

\Fld@validate@code 6057, 13855, 13857
 \Fld@value .. 5717, 5724, 5726, 6008, 12505, 12520, 12537, 12575, 12576, 13108, 13124, 13138, 13177, 13178, 13457, 13473, 13494, 13533, 13534, 14070
 \Fld@width 5947, 12506, 12519, 12525, 12538, 12574, 12585, 12587, 12614, 12631, 12654, 12670, 12678, 12690, 12704, 12720, 12726, 12731, 13109, 13123, 13130, 13139, 13176, 13187, 13189, 13224, 13238, 13259, 13273, 13281, 13296, 13310, 13324, 13331, 13337, 13458, 13472, 13475, 13495, 13532, 13543, 13545, 13564, 13598, 13629, 13646, 13654, 13669, 13683, 13701, 13708, 13710
 \float@caption .. 7560, 7632
 \float@makebox .. 7634, 7635
 \floatingpenalty .. 7457
 \Florin .. 15743, 20608
 \flq .. 616
 \flqq .. 614
 \fmtname .. 7
 \fmtversion .. 7, 6363, 7126
 \font .. 5061
 \fontencoding .. 501, 505, 542, 13064
 \fontfamily .. 543, 13063
 \fontseries .. 544, 13065
 \fontshape .. 545, 4684, 13066
 \fontsize .. 546
 \Football .. 18800, 18802, 20877
 \footins .. 7451
 \footnoteautorefname .. 2956, 2974, 2992, 3010, 3028, 3046, 3064, 3085, 3088, 3122, 3140, 3158, 3176, 3194, 3212, 3230, 3248, 8592, 8596
 \footnotesep .. 7455, 7463
 \footnotesize .. 575, 7453
 \footnotetext .. 7413
 \footref .. 7482, 7483
 \forall .. 17731, 19957
 \Force .. 17562, 20733
 \forcecjktoken .. 446
 \foreignlanguage .. 601
 \Form .. 5815
 \Form@action 5825, 12771, 14102
 \Form@boolkey .. 5819
 \Form@htmlfalse .. 5818, 5837
 \Form@htmltrue .. 5830
 \Form@method 5849, 5857, 12771
 \Forward .. 18550, 20238
 \ForwardToIndex .. 18368, 20227
 \FourAsterisk .. 18879, 20352
 \fourinferior .. 19845
 \FourStar .. 18887, 20356
 \FourStarOpen .. 18889, 20357
 \foursuperior .. 19829
 \fourth .. 17345, 19825
 \frown .. 18321, 20208
 \frownie .. 18634, 20269
 \Frowny .. 18636, 20837
 \frq .. 617
 \frqq .. 615
 \fullnote .. 19362, 20551
 \futurelet .. 670, 1280

G

\G .. 15053, 15097, 15126, 15856, 15858, 15860, 15862, 15872, 15874, 15875, 15886, 15888, 15898, 15900, 15902, 15904
 \g .. 2296, 2300, 2308
 \g@addto@macro .. 6495, 6667, 7695, 7913, 7916, 7919, 7968, 9227, 10191, 10720, 11010, 11600, 11709, 11779, 12088, 12287
 \G@refundefinedtrue 4989, 8359, 8379, 8396, 8528
 \gaf .. 19658
 \Game .. 17511, 19883
 \Gamma .. 19766
 \gamma .. 19779
 \gammainferior .. 19809
 \Ganz .. 19364, 20914
 \GaPa .. 19350, 20545
 \Gauge .. 6147
 \ge .. 17970, 20059
 \Gemini .. 18690, 20857
 \gemini .. 18688, 20285
 \GenericError .. 658, 3696
 \GenericInfo .. 660, 3694
 \GenericWarning .. 252, 659, 3695
 \Gentsroom .. 19392, 20564
 \geq .. 17970, 20058
 \geqclosed .. 18180, 20798
 \geqq .. 17978, 20062
 \geqlant .. 19199, 20488
 \GetDocumentProperties .. 2293

\getpagerefnumber .. 7136
 \getrefbykeydefault .. 7091, 7092
 \gemode .. 10750, 10751, 10853
 \gg .. 17990, 20068
 \ggg .. 18240, 20173
 \ghayn .. 19610
 \gimel .. 17505, 19880
 \Gin@setfile .. 8170, 8171
 \glossary .. 623
 \glotstop .. 16188, 19763
 \glottal .. 16191, 20688
 \glq .. 612
 \glqq .. 610
 \gnapprox .. 19218, 20497
 \gneq .. 19214, 20495
 \gneqq .. 17984, 20065
 \gnsim .. 18272, 20187
 \grq .. 613
 \grqq .. 611
 \gtrapprox .. 19207, 20492
 \gtrclosed .. 18173, 20795
 \gtrdot .. 18236, 20171
 \gtreqless .. 18246, 20175
 \gtreqqless .. 19224, 20499
 \gtrless .. 18017, 20080
 \gtrsim .. 18008, 20076
 \guillemetleft .. 14816, 14999, 15271, 19414
 \guillemetright .. 14848, 15000, 15307, 19415
 \guillemotleft .. 14815, 15270
 \guillemotright .. 14847, 15306
 \guilsinglleft .. 14746, 15001, 17328, 19416
 \guilsinglright .. 14748, 15002, 17330, 19417

H

\H .. 15048, 15100, 15129, 15151, 15631, 15633, 15695, 15697, 16823, 16825
 \h .. 3161, 19440, 19445, 19450, 19455, 19460, 19465, 19470, 19475, 19480, 19485, 19490, 19495, 19500, 19505, 19510, 19515, 19520, 19525, 19530, 19535, 19540, 19545, 19550, 19555
 \H@footnotemark .. 7316, 7333, 7397, 7487, 7494, 7506, 7517
 \H@footnotetext .. 7315, 7325, 7357, 7396, 7435, 7495, 7509, 7517

\H@C@mpfootnotetext 7323, 7335,
 7337, 7398
\H@definecounter .. 8080, 8082
\H@endeqnarray .. 7220, 7240
\H@endequation .. 7176, 7213
\H@endsubeqnarray . 7251, 7259
\H@eqnarray 7219, 7225
\H@equation 7175, 7200
\H@item 6874, 6880, 7703, 7728
\H@newctr 8088, 8090
\H@old@part 14568, 14576
\H@old@schapter . 14538, 14547
\H@old@sect 14586, 14597, 14606
\H@old@spart ... 14578, 14584
\H@old@ssect 14524, 14529
\H@refstepcounter .. 6891, 6901,
 7151, 7199, 7294, 7555
\H@subeqnarray .. 7250, 7254
\ha 19626
\Haa 19584
\Halb 19367, 20915
\halfnote 19365, 20552
\halign 632
\hamza 19560
\HandCuffLeft .. 18610, 20261
\HandCuffRight .. 18612, 20262
\HandLeft 18614, 20263
\HandRight 18617, 20264
\HaPa 19352, 20546
\HAR@checkcitations 7824
\HAR@citetoaux 7780
\HAR@tempa 7825, 7826, 7827,
 7828, 7829, 7830
\hardsign 16481, 20699
\harvardcite .. 7774, 7811
\harvarditem 7799
\hateq 17946, 20049
\hausaB 15732, 19728
\hausab 15967, 20629
\hausaD 15736, 19729
\hausad 15981, 20634
\hausaK 15747, 19730
\hausak 15751, 20610
\hb@xt@ 5076, 5089
\hbar 15538, 19727
\hbox .. 1528, 1534, 1540, 2234,
 3427, 3433, 5077, 5091,
 5242, 5244, 5948, 6183,
 6184, 6185, 6186, 7953,
 8848, 9393, 9403, 9473,
 9487, 9510, 9525, 9550,
 9565, 9836, 9853, 10929,
 11277, 11291, 11929, 11939,
 12211, 12226, 12919, 13474,
 13563, 13597, 13627, 13655,
 13684, 13709, 14514
\hc@currentHref 7571
\HCode .. 12771, 12773, 12784,
 12793, 12805, 12813, 12815,
 12846, 12852, 12857, 12862,
 12876, 12881, 12885, 12888,
 12897
\hdotfor 17310, 19819
\headerps@out .. 6777, 11590,
 11601, 11696, 11710, 11771,
 11780, 11793, 11807, 11854,
 11972, 12089, 12288
\Heart 18723, 20868
\heartsuit . 18721, 18724, 20869
\hebalef 16847
\hebayin 16883
\hebbet 16849
\hebdalet 16843, 16853
\hebfinalkaf 16867
\hebfinalmem 16873
\hebfinalnun 16877
\hebfinalpe 16885
\hebfinaltsadi 16889
\hebgimel 16851
\hebhe 16855
\hebheth 16861
\hebkaf 16869
\heblamed 16871
\hebmem 16875
\hebnun 16879
\hebpe 16887
\hebqof 16893
\hebresh 16895
\hebsamekh 16881
\hebshin .. 16897, 16898, 20701
\hebsin 16898, 20701
\hebtav 16900
\hebtet 16863
\hebtysi .. 16891
\hebvav 16857
\hebyod 16865
\hebzayin 16859
\Hermaphrodite .. 18787, 20316
\hexagon 18363, 20225
\hexstar 18798, 20318
\hfill .. 6183, 6184, 6185, 6186,
 7714, 7748
\Hfootnoteautorefname .. 8592
\hinferior 19861
\hoffset 7954
\hookb 15966, 20628
\hookd 15980, 20633
\hookg 16013, 20640
\hookh 16033, 20645
\hookheng 16037, 20647
\hookleftarrow 17600, 19905
\hookrevespsilon .. 16002, 20637
\hookrightarrow .. 17602, 19906
\phantom 585
\href 624, 4849, 6354
\href@ .. 4852, 4855, 4860
\href@split 4860, 4861
\hspace 7458
\hskip .. 1539, 1626, 2279, 2280,
 4846, 6189, 12919
\hslash 17465, 19870
\hspace 620, 7814, 7815
\hss ... 5078, 5090, 7962, 14519
\ht 5082, 5086, 5095, 6191, 6194,
 9401, 9476, 9485, 9492,
 9513, 9523, 9530, 9553,
 9563, 9570, 11273, 11937,
 12224, 13434
\htrtaild 19816
\Huge 572
\huge 576
\Hurl 4935, 4937, 4939
\hv 15746, 20609
\hv@pdf@char ... 14310, 14375,
 14376, 14377, 14378
\hvtex@buffer ... 10620, 10624,
 10632, 10635, 10644, 10648,
 10664
\hvtex@gettoken . 10619, 10633,
 10637, 10646, 10650
\hvtex@gettoken@ 10620, 10622
\hvtex@par@dimension . 10615,
 10656
\hvtex@par@direction .. 10616,
 10659
\hvtex@par@duration ... 10617,
 10651
\hvtex@par@motion 10618, 10653
\hvtex@param@dimension 10628,
 10657, 10675, 10678
\hvtex@param@direction 10629,
 10660, 10686, 10694
\hvtex@param@duration 10630,
 10652, 10699, 10701
\hvtex@param@motion . 10631,
 10654, 10675, 10682
\hvtex@parse@trans 10604, 10626
\hvtex@produce@trans .. 10665,
 10671
\hvtex@token ... 10623, 10634,
 10640, 10647, 10652, 10655,
 10658, 10660

\hvtex@trans@code 10608, 10609, 10610, 10611, 10612, 10613, 10614, 10627, 10673, 10674, 10676, 10678, 10680, 10682, 10684, 10686, 10688, 10689, 10690, 10691, 10692, 10694
\hvtex@trans@effect@Blinds 10608
\hvtex@trans@effect@Box 10609
\hvtex@trans@effect@Dissolve 10610
\hvtex@trans@effect@Glitter 10611
\hvtex@trans@effect@R . . 10614
\hvtex@trans@effect@Split 10612
\hvtex@trans@effect@Wipe 10613
\hvtex@trans@par 10647, 10651, 10653, 10656, 10659
\hvtex@trans@params . . 10641, 10643, 10667
\Hy@@CleanupFile . 5242, 5244
\Hy@@DefNameKey . 2401, 2403
\Hy@escapeform 13791, 13804, 13810
\Hy@SectionAnchor 14509, 14512
\Hy@temp . . 3457, 3459, 6067, 6069
\Hy@@VersionCheck . . 274, 303
\Hy@abspage . 6515, 6601, 6717, 6803
\Hy@Acrobatmenu . . 4264, 4305, 9297, 10037, 10579, 11453
\Hy@activeanchorfalse 4732, 8943, 9345, 9360, 9439, 9449, 9765, 10294, 10311, 10387, 10400, 10915, 11877, 11892, 12164, 12178
\Hy@activeanchortrue 8939, 9342, 9356, 9437, 9446, 9761, 10290, 10308, 10385, 10397, 10905, 11874, 11888, 12161, 12174
\Hy@ActiveCarriageReturn 4768, 4771
\Hy@AllowHyphens 4842, 10903, 10935, 11260
\Hy@AlphNoErr 6984, 6997, 6999
\Hy@AnchorName . . 4973, 4975, 4978, 4980, 5005, 5007, 5011, 5016, 5018
\Hy@appendixstring 6979, 7001
\Hy@AtBeginDocument 345, 2540, 2601, 2687, 2782, 3377, 4150, 4219, 4236, 4361, 4367, 4492, 4655, 4719, 6261, 6377, 6810, 7771, 8443, 8843, 9234, 9848, 10369, 11806, 11852, 12936, 12969
\Hy@AtBeginDocumentHook 346, 351, 357, 358
\Hy@AtEndOfPackage 348, 796, 3341, 3349, 3356, 4375, 4383, 4607
\Hy@AtEndOfPackageHook 349, 352, 354, 355
\Hy@author 6420, 6424
\Hy@babelnormalise 4950, 4952
\Hy@backout . 4728, 6313, 6317, 7667
\Hy@backreffalse 412, 2920, 2942, 4373
\Hy@backreftrue 2913, 2917, 2939
\Hy@BeginAnnot 9878, 9895, 9937, 9975, 10008, 10038
\Hy@bibcite 7692, 7696
\Hy@bookmarksdepth 3412, 3417, 3429, 3435, 14153
\Hy@bookmarksnumberedfalse 413
\Hy@bookmarksopenfalse . . 414
\Hy@bookmarkstrue 415
\Hy@bookmarkstype 3447, 3449, 7986, 14164
\Hy@boolkey 2327, 2420, 2423, 2426, 2447, 2450, 2453, 2484, 2487, 2504, 2511, 2514, 2517, 2520, 2523, 2526, 2529, 2532, 2614, 2891, 2894, 2949, 3363, 3375, 3390, 3407, 3410, 3451, 3454, 3673, 3960, 3963, 3966, 3969, 3972, 3975, 3978, 3986, 4118, 4121, 6735
\Hy@BorderArrayPatch . . 11331, 11334, 11599, 12087
\Hy@breaklinks@unsupported 2492, 10881
\Hy@breaklinksfalse 416
\Hy@breaklinksunhbox . . 11227, 11281
\Hy@CatcodeWrapper 4616, 4673, 4722
\Hy@chapapp 6980, 7001, 7033, 14542, 14553
\Hy@chapterstring 6975, 6977, 6980, 7032
\Hy@CheckOptionValue 2371, 2408
\Hy@CJKbookmarksfalse 418
\Hy@cjkpu 949, 951, 972
\Hy@CleanupFile 5240, 9001, 9939, 10464, 11525
\Hy@colorlink 3369, 4676, 4684, 4688, 8844, 8924, 8994, 9031, 9064, 9319, 9343, 9366, 9397, 9410, 9438, 9454, 9479, 9495, 9517, 9534, 9557, 9574, 9849, 9928, 9968, 10001, 10031, 10058, 10386, 10408, 10478, 10504, 10539, 10572, 10591, 10933, 11206, 11208, 11875, 11898, 11933, 11946, 12162, 12184, 12219, 12232
\Hy@colorlinksfalse 3366
\Hy@ColorList 3512, 3513
\Hy@CounterExists . . 6838, 6851, 6855
\Hy@currentbookmarklevel 14159, 14169, 14170, 14176, 14183, 14275, 14278, 14283, 14287
\Hy@debugfalse 408
\Hy@debugtrue 407
\Hy@defaultbp 5963, 5965
\Hy@defaultbpAux 5967, 5970
\Hy@defaultdriver 4477, 4509, 4519, 4531
\Hy@DefFormAction 5823, 5825
\Hy@DefNameKey 2400, 3544, 3602, 3610, 3618, 3622, 3629, 3636, 3643, 3650, 3654, 3659, 3666, 3995
\Hy@DEST 11228, 11295
\Hy@destlabelfalse 419
\Hy@DestName 8888, 8895
\Hy@DestRename 5305, 5330, 5334
\Hy@DisableOption 2356, 4254, 4255, 4256, 4258, 4263, 4380, 4551, 4552, 4553, 4554, 4555, 4556, 4557, 4558, 4559, 4560, 4561, 4562, 4563, 4564, 4565, 4566, 4567, 4568, 4569, 4570, 4615, 4668, 4693, 4694, 4730, 4731, 5361, 6265, 6266,

6267, 6268, 6269, 6270,
 6271, 6272, 6273, 6274,
 6275, 6276, 6277, 6278,
 6279, 6280, 6281, 6282,
 6283, 6284, 6285, 6286,
 6287, 6288, 6444, 6669,
 7522, 8175, 8300, 8301,
 8767, 8871, 9166, 9167,
 9168, 9169, 9170, 9171,
 9172, 9173, 9174, 9175,
 9176, 9292, 9601, 9602,
 9603, 9604, 9605, 9606,
 9607, 9608, 9609, 9610,
 9611, 9612, 9876, 10094,
 10095, 10096, 10097, 10098,
 10099, 10100, 10101, 10102,
 10103, 10104, 10105, 10223,
 10371, 10831, 10832, 10833,
 10834, 10835, 10836, 10837,
 10838, 10839, 10840, 10841,
 10842, 11088, 11089, 11090,
 11091, 11092, 11093, 11094,
 11095, 11096, 11097, 11098,
 11099, 11681, 11995, 11996,
 11997, 11998, 11999, 12000,
 12001, 12002, 12003, 12004,
 12005, 12006
`\Hy@DistillerDestFix` 7927,
 10846, 10848
`\Hy@draftfalse` 375
`\Hy@drafttrue` 376
`\Hy@driver` 458, 2497, 2684,
 2696, 2708, 2711, 2723,
 2729, 2734, 2748, 2758,
 2763, 2769, 2776, 2779,
 2805, 2821, 2828, 2834,
 2845, 2859, 4385, 4388,
 4396, 4399, 4403, 4406,
 4408, 4412, 4418, 4422,
 4425, 4429, 4434, 4438,
 4441, 4445, 4449, 4453,
 4456, 4460, 4463, 4465,
 4469, 4475, 4480, 4482,
 4486, 4489, 4500, 4503,
 4506, 4509, 4518, 4519,
 4531, 4533, 4541, 4543,
 4545, 4547
`\Hy@dth@currentHref` 7296, 7299
`\Hy@DviErrMsg` 2651, 2653,
 2656, 2662, 2675
`\Hy@DviModetru`e .. 2660, 2665
`\Hy@DvipdfmxOutlineOpentru`e
 4577, 4584
`\Hy@EndAnnot` 9884, 9931, 9971,
 10004, 10034, 10061
`\Hy@endcolorlink` 3370, 4680,
 4685, 4689, 8853, 8930,
 9343, 9380, 9404, 9412,
 9438, 9462, 9483, 9497,
 9521, 9536, 9561, 9576,
 9858, 9886, 10386, 10459,
 10480, 10506, 10541, 10574,
 10593, 10960, 11220, 11875,
 11914, 11940, 11948, 12162,
 12198, 12223, 12234
`\Hy@EndWrap` 4617, 4619, 4620,
 4653
`\Hy@Error` 246, 262, 268,
 291, 2544, 2673, 2699, 2715,
 2750, 2789, 2796, 2807,
 2813, 2851, 4289, 4903,
 5173, 5524, 5648, 5844,
 5876, 6072, 6125, 12645,
 12698, 13250, 13304, 13619,
 13677
`\Hy@escapeform` . . 12524, 12610,
 12629, 12658, 12679, 12705,
 12730, 13128, 13214, 13236,
 13263, 13284, 13312, 13335,
 13480, 13572, 13601, 13633,
 13657, 13685, 13715, 13785,
 13815, 13822
`\Hy@escapestring` 13782, 13849,
 13853, 13857, 13861, 13865,
 13869, 13873, 13877, 13881,
 13885, 13931, 13965, 14025,
 14069, 14070, 14102
`\Hy@EveryPageAnchor` 7926,
 7969
`\Hy@EveryPageBoxHook`
 6472, 6476, 6480, 7968,
 10191, 10720, 11010
`\Hy@EveryPageHook` 6471, 6475,
 6667, 9227
`\Hy@ExchangeLeftParenthesis` .
 8641, 8647
`\Hy@ExchangeRightParenthesis`
 8651, 8657
`\Hy@false` 2198, 2337, 2905, 2941,
 5873
`\Hy@finalfalse` 376
`\Hy@finaltrue` 375
`\Hy@FirstPage` 4275
`\Hy@FirstPageHook`
 6473, 6487, 6488, 6492,
 6495, 6775, 6776, 11600,
 11709, 11779, 12088, 12287
`\Hy@float@caption` 7561, 7611,
 7625
`\Hy@float@currentHref`
 7615, 7618, 7620, 7626,
 7628, 7630
`\Hy@footnote@currentHref`
 6260, 7345, 7350, 7365,
 7370, 7373, 7385, 7387,
 7426, 7468, 7471
`\Hy@FormObjects` 13028, 13343,
 13398, 13408, 13726, 13777
`\Hy@frenchlinksfalse` 3368
`\Hy@Gin@setfile` 8170, 8172
`\Hy@GlobalStepCount` 456, 6601,
 7063, 7087, 7944
`\Hy@gtemp` 784,
 785, 4320, 4326, 4328, 5721,
 5722, 5726, 5727, 5738,
 5752, 7402, 7407, 8665,
 8667, 13842, 13844
`\Hy@href` 4852, 4854
`\Hy@href@nextactionraw`
 4889, 4912, 4914, 4915,
 4917, 4922, 4926, 4928,
 8990, 9027, 9060, 9315,
 9924, 9964, 9997, 10027,
 10054, 10423, 10493, 10561,
 11550, 11579
`\Hy@href@page` 4867, 4869, 4873,
 4874, 4876, 4883, 4886,
 9023, 9959, 11546
`\Hy@hyperfiguresfalse` 421
`\Hy@hyperfootnotestrue` 423
`\Hy@hyperindextrue` 424
`\Hy@hypertexnamesfalse` 2169
`\Hy@hypertexnamestrue` 425
`\Hy@ifStringEndsWith` 5208,
 5220
`\Hy@implicittrue` 426
`\Hy@Info` 249, 2345, 4331, 4333,
 4336, 4338, 4341, 4343,
 4346, 4348, 4351, 4353,
 4600, 4606, 4681, 4686,
 4690, 4811, 4838, 5431,
 6222, 6224, 6227, 6229,
 6232, 6234, 6237, 6239,
 6242, 6244, 6247, 6249,
 6252, 6254, 7772, 7991,
 8008
`\Hy@InfoNoLine` 250, 4356, 4358,
 4543, 8689, 12141
`\Hy@IsEmpty` 5312, 5313,
 5336
`\Hy@LastPage` 4278

\Hy@level 14165, 14167, 14178, 14183, 14184, 14185, 14215
\Hy@levelcheck 14166, 14181
\Hy@linkcounter 460, 462, 7063, 7064, 7087, 7088
\Hy@linkfileprefix 3491, 5192, 9383, 10259, 11918, 12201
\Hy@LinkMath 10924, 10926, 10931, 10963, 11252, 11254, 11259, 11261, 11267, 11269
\Hy@linktoc 2455, 2457, 2465, 2467, 2477, 8037
\Hy@linktoc@all 2463
\Hy@linktoc@none 2460
\Hy@linktoc@page 2455, 2462, 2465
\Hy@linktoc@section 2457, 2461, 2467
\Hy@linktocpagefalse 427
\Hy@localanchornamefalse 428
\Hy@LookForParentCounter 6950
\Hy@LT@currentHref 7153, 7164
\Hy@LT@footnotetext 7425, 7434
\Hy@make@anchor 8099, 8105, 8111
\Hy@make@df@tag@@ 8103, 8118
\Hy@make@df@tag@CC 8109, 8119
\Hy@MakeCurrentHref 7026, 7075, 7088
\Hy@MakeCurrentHrefAuto 7086, 7095, 8100, 14144, 14526, 14542, 14553, 14580, 14594
\Hy@MakeRemoteAction 4872, 9004, 9942, 11528
\Hy@maketitle@end 7498, 7503, 7505
\Hy@maketitle@optarg 7496, 7501
\Hy@Match 307, 309, 2867, 3501, 3559, 3576, 3922, 4013, 4019, 4049, 4050, 4053, 4064, 4079, 4917, 5985
\Hy@MaybeStopNow 2772, 4174, 4177
\Hy@Message 251, 2686, 2781, 4360, 4491, 10315, 10319, 10322, 10325, 10328, 10331, 10334, 10337, 12472, 12743, 12747, 12750, 12753, 12756, 12759, 12762, 12765, 12775, 12912, 13403
\Hy@naturalnamesfalse 430
\Hy@nestingfalse 431
\Hy@newline@author 6465
\Hy@newline@title 6464
\Hy@next 6617, 6627, 6632, 14552, 14561, 14564
\Hy@nextfalse 8185
\Hy@NextPage 4269
\Hy@nexttrue 8186, 8187, 8188
\Hy@NIL 4193, 4206, 4209
\Hy@number 3897, 3904
\Hy@numberline 14160, 14197, 14198, 14199, 14200
\Hy@ObsoletePaperOption 2429, 2437
\Hy@ocgcolor 8847, 8861, 9852, 9866
\Hy@ocgcolorlinksfalse 3367, 4663
\Hy@org@chapter 14550, 14565
\Hy@OrgMakeLabel 12256, 12263
\Hy@OutlineName 14431, 14483
\Hy@OutlineRerunCheck 14299, 14398, 14477
\Hy@PageAnchorSlide 7886, 7924, 7937
\Hy@PageAnchorSlidesPlain 7873, 7923, 7932
\Hy@pageanchortrue 434
\Hy@pagecounter 461, 463, 7944, 7946
\Hy@pageheight 4164, 11711, 11808
\Hy@param 4194, 4195, 4198, 4199, 7031, 7032, 7033, 7060, 7064
\Hy@pdf@majorminor@version 2639, 4260, 5698, 8685, 8699, 8726, 8747, 13837
\Hy@pdf@majorversion 2630, 2631, 2632, 2633, 2634, 2635, 2636, 2637, 2639, 6769, 8693, 8722, 8744, 8762, 8765
\Hy@pdf@minorversion 2630, 2631, 2632, 2633, 2634, 2635, 2636, 2637, 2638, 2639, 6770, 8693, 8723, 8745, 8762, 8766
\Hy@pdafalse 454
\Hy@pdfcenterwindowfalse 417
\Hy@pdfdisplaydoctitlefalse 453
\Hy@pdfescapeformfalse 420
\Hy@pdffitwindowfalse 422
\Hy@pdfmajorminor@version 2640, 8680, 8699
\Hy@pdfmajorversion 2640, 2648, 8722, 8744, 8760, 8765
\Hy@pdfmarkerrorfalse 11180
\Hy@pdfmarkerrortrue 11364, 11373
\Hy@pdfmenubartrue 429
\Hy@pdfminorversion 2640, 8677, 8678, 8723, 8745, 8761, 8766
\Hy@pdfnewwindowfalse 433
\Hy@pdfnewwindowsetfalse 432, 3983
\Hy@pdfnewwindowsettrue 3985, 4891
\Hy@pdfnewwindowtrue 4892
\Hy@pdfpagelabelsfalse 6502
\Hy@pdfpagelabelstrue 435
\Hy@pdfstringdef 783, 5696, 5704, 5909, 6002, 6008
\Hy@pdfstringfalse 436, 6290
\Hy@pdfstringtrue 637, 6262
\Hy@pdftoolbartrue 442
\Hy@pdfusetitlefalse 450
\Hy@pdfversion 2638
\Hy@pdfwindowuitrue 452
\Hy@pkg 4192, 4199
\Hy@plainpagesfalse 437
\Hy@PrevPage 4272
\Hy@ProvideTheHCounter 6931
\Hy@ps@CR 11761, 11768, 11773, 11774, 11791, 11812, 11813, 11814, 11820, 11827, 11834, 11841
\Hy@psdextrafalse 441
\Hy@pstringB 9082, 9087, 10136, 10148, 11153, 11169, 12060, 12076
\Hy@pstringD 9003, 9025, 9941, 9961, 11527, 11548
\Hy@pstringdef
. 8612, 8887, 8911, 8968, 9002, 9003, 9037, 9038, 9082, 9703, 9904, 9940, 9941, 9976, 9977, 10009, 10136, 10407, 10485, 10548, 10549, 11153, 11362, 11371, 11500, 11526, 11527, 11558, 11559, 12060, 13808, 14430, 14446
\Hy@pstringDest 8887, 8888, 9703, 9750, 11362, 11363, 11367, 11371, 11372, 11376
\Hy@pstringF
. 9000, 9001, 9002, 9019,

9037, 9053, 9058, 9938,
 9939, 9940, 9956, 9976,
 9990, 9995, 10463, 10464,
 10468, 10548, 10555, 10559,
 11524, 11525, 11526, 11543,
 11558, 11574, 11577
`\Hy@pstringName` 14430, 14431,
 14446, 14460
`\Hy@pstringP` 9038, 9058, 9977,
 9995, 10549, 10559, 11559,
 11577
`\Hy@pstringURI` ... 8968, 8986,
 10009, 10023, 10407, 10419,
 10485, 10489, 11500, 11512
`\Hy@PutCatalog` ... 6663, 6671,
6792
`\Hy@raisedlink`
 ... 2222, 6926, 7097, 7118,
 7119, 7120, 7123, 7165,
 7203, 7208, 7211, 7232,
 7348, 7368, 7439, 7466,
 7599, 7678, 7704, 7709,
 7729, 8101, 11588, 11694,
 11968, 12139, 14145, 14516,
 14543, 14554, 14581
`\Hy@raiselinksfalse` ... 438, 7773
`\Hy@RemoveDurPageAttr` 9206,
9219
`\Hy@RemovePercentCr` ... 4784,
 4788, 4793
`\Hy@RemoveTransPageAttr` ...
 ... 9181, 9195
`\Hy@reserved@a` ... 5108, 7223,
 7253, 12778, 12828, 12891
`\Hy@RestoreCatcodes` 205, 4170,
 4550
`\Hy@RestoreCatcodeSettings` ...
 ... 850, 857, 867, 881
`\Hy@RestoreLastskip`
 ... 2243, 8889, 9346, 9361,
 9440, 9450, 9752, 10295,
 10312, 10388, 10401, 10896,
 10916, 11878, 11893, 12165,
 12179
`\Hy@RestoreSavedSpaceFactor`
 ... 2218, 9391, 9471, 9508,
 9548, 11927, 12209
`\Hy@RestoreSpaceFactor`
 ... 2209, 2235, 2240, 9390,
 9398, 9405, 9470, 9480,
 9488, 9507, 9518, 9526,
 9547, 9558, 9566, 10930,
 10966, 11258, 11266, 11293,
 11926, 11934, 11941, 12208,
 12220, 12227, 12264, 12268
`\Hy@ReturnAfterElseFiFiEnd` ...
 ... 466, 1495
`\Hy@ReturnAfterFiFiEnd` ... 465,
 1487, 1501, 1594, 1601
`\Hy@ReturnEnd` ... 464, 465, 466,
 1507, 1606
`\Hy@safe@activesfalse` 467, 5141,
 8517
`\Hy@safe@activestrue`
 ... 467, 4309, 4764, 4801,
 4809, 4837, 4954, 5298,
 5308, 7030, 8030, 8409,
 8506, 12939, 12998, 14391,
 14418
`\Hy@SaveCatcodeSettings` ... 806,
 855, 865, 879
`\Hy@savet@currentHref` ... 7383,
 7386
`\Hy@savet@footnotemark` 7492,
 7507
`\Hy@savet@footnotetext` ... 7493,
 7510
`\Hy@savet@hook` ... 6448, 6460
`\Hy@savet@refstepcounter` 6919
`\Hy@SavedSpaceFactor`
 ... 2205, 2207, 2212, 2213,
 2219, 12261
`\Hy@SaveLastskip`
 ... 2243, 8885, 9334, 9349,
 9431, 9443, 9700, 10282,
 10298, 10378, 10391, 10886,
 10900, 11867, 11881, 12154,
 12168
`\Hy@SaveSavedSpaceFactor` ...
 ... 2217, 9389, 9469, 9506,
 9546, 11925, 12207
`\Hy@SaveSpaceFactor`
 ... 2206, 2226, 2237, 9388,
 9400, 9468, 9482, 9505,
 9520, 9545, 9560, 10928,
 10964, 11250, 11262, 11270,
 11924, 11936, 12206, 12222,
 12259, 12266
`\Hy@scanauthor` ... 6418, 6423
`\Hy@scanoptauthor` ... 6418, 6419
`\Hy@scanopttitle` ... 6409, 6410
`\Hy@scantitle` ... 6409, 6414
`\Hy@secnum@part` 14570, 14571,
 14573
`\Hy@sectionAnchorHref` ... 634,
 14507, 14531, 14599
`\Hy@sectionHShift` 14506, 14515,
 14527, 14595
`\Hy@setbreaklinks` ... 2489, 2493,
 2505, 8673, 9693
`\Hy@SetCatcodes` 181, 231, 4172
`\Hy@SetNewWindow`
 ... 3989, 9021, 9055, 9963,
 9992, 10556, 11542, 11573
`\Hy@setouterhbox` 11226, 11257
`\Hy@setpagesize` true ... 439
`\Hy@setpdfborder`
 ... 3592, 8917, 8973, 9008,
 9042, 9302, 9915, 9948,
 9983, 10015, 10045, 10427,
 10448, 10471, 10497, 10531,
 10565, 10584
`\Hy@setpdfhighlight`
 ... 3550, 8918, 8974, 9009,
 9043, 9303, 9916, 9949,
 9984, 10016, 10046
`\Hy@setpdfversiontrue` ... 2626
`\Hy@setref@link` ... 8365, 8368
`\Hy@SlidesFormatOptionalPage`
 ... 6531, 7872, 7891, 7895
`\Hy@SlidesPage` 6538, 7905, 7906,
 7912, 7914, 7917, 7920
`\Hy@StartlinkName` ... 8915, 8926
`\Hy@StepCount` 455,
 6578, 12545, 12608, 12843,
 13146, 13210, 13502, 13569,
 14279, 14284, 14360
`\Hy@stoppedearlyfalse` ... 4179,
 6837
`\Hy@stoppedearlytrue` 4176, 6834
`\Hy@StringLocalhost` 5238, 5239,
 5254
`\Hy@tabularx@hook` 7395, 7403
`\Hy@temp` 665,
 672, 2435, 2440, 2441, 2442,
 2443, 2444, 2445, 3456,
 3465, 3466, 3467, 3468,
 3469, 3470, 3471, 3513,
 3514, 3515, 3518, 3520,
 3523, 3533, 3536, 3537,
 3538, 3539, 3540, 3541,
 3557, 3570, 3574, 3589,
 3756, 3757, 3760, 3763,
 3766, 3791, 3799, 3800,
 3801, 3802, 3803, 3804,
 3805, 3806, 3807, 3981,
 3982, 4005, 4006, 4052,
 4053, 4060, 4064, 4296,
 4300, 4301, 4302, 4303,
 4391, 4393, 4396, 4401,

4403, 4406, 4420, 4422, 2902, 2903, 2905, 2906, 10441, 10522, 10524, 11017,
 4427, 4429, 4436, 4438, 2908, 2909, 2911, 2915, 11030, 11032
 4443, 4445, 4451, 4453, 2919, 2930, 2932, 2934, \Hy@unicodedefalse 447,
 4458, 4460, 4463, 4532, 2935, 2937, 2941, 4770, 764, 774, 2551, 2552, 2560,
 4533, 5421, 5425, 5426, 4771, 4782, 4786, 4956, 3733, 3739, 7936, 13839
 5437, 5521, 5522, 5523, 4960, 5120, 5122, 5828, \Hy@unicodetrue . . . 443, 2552,
 5525, 5529, 5841, 5842, 5829, 5869, 5870, 5873, 6728, 6728
 5843, 5845, 5849, 5850, 5877, 6607, 6609, 6647, \Hy@UseMakeTitleInfos . . 6466,
 5983, 5995, 6066, 6082, 6649, 6803, 6805, 7267, 9139, 9582, 10066, 10820,
 6083, 6084, 6085, 6086, 7269, 7270, 7273, 7274, 11049, 11976
 6087, 6088, 6089, 6095, 7275, 7298, 7300, 7556, \Hy@UseMakeTitleString . 6445,
 6101, 6107, 6108, 6109, 7561, 7566, 7985, 7986, 6467, 6468
 6110, 6111, 6112, 6113, 8004, 8005, 8011, 9367, \Hy@UseNameKey
 6114, 6115, 6116, 6117, 9368, 10263, 10416, 10417, .. 2413, 9104, 9105, 9106,
 6157, 6158, 6165, 6166, 11899, 11900, 12185, 12186, 9107, 9108, 9109, 9110,
 6173, 6174, 6558, 6561, 14163, 14164, 14187, 14189, 9111, 9130, 9652, 9653,
 6570, 6572, 6576, 6580, 14207, 14208, 14216, 14240, 9654, 9655, 9656, 9657,
 6624, 6626, 6934, 6935, 14242, 14243, 14245, 14246 9658, 9659, 9680, 10115,
 6956, 7179, 7185, 7476, \Hy@tempb 10116, 10117, 10118, 10119,
 7482, 8044, 8045, 8053, .. 5121, 5123, 5144, 6608, 10120, 10121, 10122, 10155,
 8054, 8255, 8257, 8261, 6609, 6648, 6649, 14188, 10780, 10781, 10782, 10783,
 8292, 8293, 8294, 8309, 14189, 14216 10784, 10785, 10786, 10787,
 8310, 8701, 8704, 8705, 11132, 11133, 11134, 11135,
 8721, 8740, 9097, 9126, 9128, 9622, 9627, 9633, 11136, 11137, 11138, 11139,
 9637, 9640, 9645, 9676, 11162, 12039, 12040, 12041,
 9678, 10108, 10151, 10153, 12042, 12043, 12044, 12045,
 11051, 11054, 11058, 11059, 12046, 12069 12046, 12069
 11065, 11066, 11072, 11102, \Hy@varioreref@undefined . 7130,
 11107, 11113, 11117, 11120, 7134, 8512
 11125, 11158, 11160, 11232, \Hy@VerboseAnchor
 11233, 11237, 11328, 11329, .. 4834, 8886, 9335, 9350,
 11337, 11338, 11442, 11443, 9432, 9444, 9701, 10283,
 12009, 12014, 12020, 12024, 10299, 10379, 10392, 10887,
 12027, 12032, 12065, 12067, 10901, 11868, 11882, 12155,
 12999, 13011, 13790, 13791, 12169
 14428, 14434, 14442, 14457 \Hy@verbosefalse 408, 451
\Hy@temp@A 697, \Hy@texhtfalse 440
 698, 1479, 1481, 1492, 1494, \Hy@texhtrue 2681, 4386
 1499, 1500, 1503, 3792, \Hy@theorem@refstepcounter
 3794, 4193, 4206, 4209, 7292, 7309
 6951, 6954, 6955, 6956, \Hy@TheSlideOptionalPage 7890,
 6957, 8204, 8205, 8206, 7894, 7899, 7908
 8213, 8241, 8242, 8243, \Hy@title 6411, 6415
 8252, 8279, 8702, 8713, \Hy@tocdestname . . 8024, 8032,
 8714, 8715, 8716, 8719, 8034
 8725, 8728, 8755 \Hy@toclevel . . 7996, 8000, 8013
\Hy@temp@B 1480, 1481, \Hy@toclinkend . . . 8025, 8041,
\Hy@temp@menu 9299, 8049, 8056, 8060, 8062
 9314, 10039, 10053, 10578, \Hy@toclinkstart . . . 8024, 8041,
 10581, 11452, 11461 8049, 8056, 8060, 8062
\Hy@tempa . . 2328, 2330, 2332, \Hy@true 2197, 2333, 2335, 2935,
 2333, 2335, 2337, 2339, 2937, 5870
 2342, 2345, 2346, 2901, \Hy@undefinedname
 .. 8900, 8907, 8909, 9891,
 9900, 9902, 10404, 10439, 9900, 9902, 10404, 10439

\HyField@FlagsChoice 5664,
12584, 13186, 13542
\HyField@FlagsPushButton 5589,
12653, 12676, 12703, 13258,
13279, 13309, 13628, 13652,
13682
\HyField@FlagsRadioButton . .
5616, 12580, 13182, 13538
\HyField@FlagsSubmit . . . 5537,
12677, 13280, 13653
\HyField@FlagsText 5632, 12518,
13122, 13471
\HyField@NeedAppearancefalse
. 5861, 5874
\HyField@NeedAppearancetrue
. . . 5864, 5867, 5871
\HyField@NewBitsetFlag . 5369,
5372, 5380
\HyField@NewFlag
. . . 5367, 5443, 5444, 5445,
5446, 5447, 5448, 5449,
5450, 5451, 5452, 5453,
5454, 5455, 5456, 5457,
5458, 5459, 5460, 5461,
5462, 5467, 5468, 5469,
5470, 5471, 5472, 5473,
5474, 5475, 5508, 5510,
5511, 5513, 5514, 5516,
5517, 5518, 5519
\HyField@NewFlagOnly . 5371,
5509, 5512, 5515
\HyField@NewOption 5368, 5374
\HyField@PDFAFlagWarning .
. . . 5477, 5485, 5489, 5493,
5497, 5501, 5505
\HyField@PDFChoices 5689,
12628, 13233, 13596
\HyField@PrintFlags
. 5418, 5564, 5582, 5596,
5609, 5625, 5657, 5682
\HyField@SetFlag 5410, 5550,
5556, 5561, 5595, 5623
\HyField@SetKeys . 5793, 12515,
12551, 12554, 12573, 12641,
12673, 12693, 12722, 13118,
13152, 13155, 13174, 13245,
13276, 13299, 13326, 13467,
13508, 13511, 13530, 13614,
13649, 13672, 13703
\HyField@TheAnnotCount . .
. 12479, 12488, 12497,
12527, 12616, 12633, 12661,
12683, 12709, 12733, 13443,
13448, 13451, 13482, 13579,
13604, 13635, 13660, 13688,
13717
\HyField@UseFlag
. 5400, 5541, 5542, 5543,
5544, 5545, 5546, 5547,
5548, 5551, 5552, 5553,
5554, 5557, 5558, 5559,
5562, 5573, 5574, 5575,
5576, 5577, 5578, 5579,
5580, 5581, 5592, 5593,
5594, 5606, 5607, 5608,
5619, 5620, 5621, 5622,
5624, 5635, 5636, 5637,
5638, 5639, 5640, 5641,
5642, 5653, 5656, 5667,
5668, 5669, 5670, 5672,
5674, 5675, 5678, 5681
\HyInd@@@wrindex . 8200, 8203,
8234, 8240
\HyInd@@hyperpage 8307, 8317
\HyInd@@wrindex . 8195, 8196
\HyInd@DefKey . . . 8253, 8267,
8280, 8289
\HyInd@EncapChar . 2952, 4167,
8190
\HyInd@hyperpage . 8304, 8306,
8313
\HyInd@key . . . 8254, 8258, 8269,
8282, 8294
\HyInd@org@wrindex 8194, 8198,
8208, 8214, 8216, 8219
\HyInd@pagelink . . . 8322, 8328,
8330, 8333
\HyInd@ParensLeft . 8177, 8205,
8242, 8279
\HyInd@ParensRight . 8178, 8206,
8213, 8243, 8252
\HyInd@removespaces . . . 8336,
8339, 8349
\HyInfo@AddonHandler . . . 3810,
3813
\HyInfo@AddonList . 3843, 3844,
3878, 3885
\HyInfo@Addons . . . 3864, 3880,
9163, 10091, 11081, 11085
\HyInfo@AddonUnsupportedtrue
. . . 9580, 10806, 11974
\HyInfo@do . . . 3812, 3845, 3868
\HyInfo@GenerateAddons 3862,
9140, 10067, 11050
\HyInfo@Key . 3820, 3821, 3839,
3841, 3842, 3845, 3848,
3855, 3869, 3873
\HyInfo@KevEscaped 3819, 3820
\HyInfo@tmp 3829, 3839
\HyInfo@trapped@false . . . 3760,
3779
\HyInfo@trapped@true . . . 3757,
3778
\HyInfo@trapped@unknown 3763,
3780
\HyInfo@TrappedUnsupported
. . . 3781, 3785, 9583, 10821,
11977
\HyInfo@Value 3833, 3836
\HyLang@addto 3264, 3280,
3298, 3340, 3348
\HyLang@afrikaans 2954
\HyLang@catalan 3138
\HyLang@danish 3228
\HyLang@DeclareLang 3278,
3307, 3308, 3309, 3310,
3311, 3312, 3313, 3314,
3315, 3316, 3317, 3318,
3319, 3320, 3321, 3322,
3323, 3324, 3325, 3326,
3327, 3328, 3329, 3330,
3331, 3332, 3333, 3334,
3335, 3336, 3337, 3338
\HyLang@dutch 3192
\HyLang@english 2972
\HyLang@french 2990
\HyLang@german 3008
\HyLang@greek 3174
\HyLang@italian 3026
\HyLang@magyar 3044
\HyLang@norsk 3210
\HyLang@portuges 3062
\HyLang@russian 3080
\HyLang@spanish 3120
\HyLang@swedish 3246
\HyLang@vietnamese 3156, 3340,
3348
\HyLinguex@OrgB 788, 792
\HyLinguex@OrgC 789, 793
\HyLinguex@OrgD 790, 794
\HyLinguex@Restore 791, 804,
858, 868
\HyNew@float@makebox 7612,
7635
\HyOpt@CheckDvi
. 2669, 2722, 2728, 2733,
2757, 2762, 2768, 2820,
2827, 2833, 2858
\HyOpt@CustomDriver 283,
2879, 2882, 4474, 4541

\HyOpt@DriverFallback
 .. 2863, 2866, 2867, 2875,
 4508, 4513

\HyOpt@DriverType
 .. 4473, 4476, 4510, 4520,
 4522, 4540, 4543

\HyOrg@addtoreset . 8124, 8126,
 8155

\HyOrg@appendix .. 6983, 7002

\HyOrg@author 6408, 6421, 6425

\HyOrg@elt 6936, 6942

\HyOrg@float@makebox .. 7613,
 7634

\HyOrg@hyperpage . 8180, 8182,
 8183

\HyOrg@make@df@tag@@ 8116

\HyOrg@make@df@tag@@@ 8117

\HyOrg@maketitle .. 7490, 7497,
 7502

\HyOrg@subequations 7282, 7287

\HyOrg@title .. 6407, 6412, 6416

\HyOrg@TX@endtabularx 7394

\HyOrg@url 4934

\HyPat@NonNegativeReal
 .. 3560, 3561, 3562, 3563,
 3579, 3581, 3914, 3925,
 3926, 3927, 3934, 3937,
 3938, 3939, 3940

\HyPat@ObjRef 4918, 4919,
 4932, 8674, 9694, 10882

\hyper@anchor 4238, 4944,
 4946, 4978, 4980, 5016,
 5018, 5261, 6303, 6318,
 6334, 7344, 7349, 7364,
 7369, 7437, 7440, 7467,
 7597, 7600, 7617, 7876,
 7931, 7941, 7946

\hyper@link . 4804, 4862, 4968,
 4997, 5108, 7688, 7775,
 7776, 7777, 7825, 7827,
 7829, 8370, 8385, 8503

\hyper@normalise . 4773, 4777,
 4781

\hyper@anchor 5288, 6306, 6320,
 6383, 6391, 8934, 9333,
 9430, 9757, 10297, 10377,
 10885, 11866, 12153

\hyper@anchorend 4226, 4234,
 4241, 6289, 6308, 6322,
 6337, 6927, 7099, 7166,
 7209, 7211, 7233, 7256,
 7680, 7707, 7710, 7730,
 7804, 8101, 8941, 9358,
 9448, 9764, 10292, 10399,

10907, 11890, 12176, 14145,
 14291, 14517, 14544, 14555,
 14582

\hyper@anchorstart
 .. 4240, 6289, 6307, 6321,
 6336, 6927, 7098, 7166,
 7203, 7233, 7256, 7678,
 7705, 7710, 7730, 7804,
 8101, 8937, 9348, 9442,
 9760, 10281, 10390, 10899,
 11880, 12167, 14145, 14291,
 14517, 14544, 14555, 14582

\hyper@chars
 .. 4798, 8969, 9338, 9352,
 9372, 9394, 9408, 9422,
 9502, 9542, 10248, 10269,
 10285, 10302, 10382, 10394,
 10486, 11501, 11884, 11904,
 11930, 11944, 11958, 12171,
 12190, 12213, 12230, 12245

\hyper@currentanchor 10904,
 10913, 10936, 10953

\hyper@currentlinktype 10937,
 10941, 10945

\hyper@destlabel@hook
 .. 5304, 5311

\hyper@hash 4750, 4751, 4799,
 5184, 5196, 5213, 5216,
 6256, 10242

\hyper@image 4940, 4941, 9420,
 10544, 11014, 11956, 12243

\hyper@last 6397, 6402

\hyper@link
 .. 4239, 5132, 6304, 6305,
 6319, 6329, 6335, 8955,
 9416, 9464, 9932, 10238,
 10510, 11018, 11952, 12239

\hyper@link@ 4246, 5109, 5115,
 6302, 6316, 6342

\hyper@linkend
 .. 4226, 4234, 4243, 6310,
 6324, 6339, 7389, 7672,
 7675, 8025, 8954, 9378,
 9461, 9931, 9933, 10274,
 10457, 10939, 11912, 12196

\hyper@linkfile 4245, 5209, 6312,
 6326, 6341, 8998, 9382,
 9540, 9935, 10258, 10461,
 11522, 11916, 12200

\hyper@linkstart
 .. 4242, 6309, 6323, 6338,
 7387, 7668, 7675, 8024,
 8945, 9364, 9452, 9892,
 9933, 10261, 10405, 10918,

11896, 12182

\hyper@linkurl
 .. 4244, 4939, 5184, 5191,
 5212, 5216, 6311, 6325,
 6340, 8966, 9383, 9385,
 9418, 9500, 10006, 10246,
 10259, 10483, 10545, 11015,
 11498, 11917, 11921, 11954,
 12201, 12203, 12241

\hyper@livelink 6304, 6329

\hyper@makecurrent 6923, 7028,
 7152, 7201, 7230, 7255,
 7295, 7384, 7573, 7627

\hyper@n@rmalise 4765, 4769

\hyper@nat@current 7669

\hyper@natanchorend 7680

\hyper@natanchorstart 7677

\hyper@natlinkbreak 7674

\hyper@natlinkend 7671

\hyper@natlinkstart 7666

\hyper@newdestlabel . 5296, 5318,
 5357, 5363, 5365

\hyper@normalise 4168, 4173,
 4742, 4852, 4855, 4936,
 4938, 4940, 4962, 5823

\hyper@pageduration 9202,
 9229, 10180, 10193, 10710,
 10722, 10993, 11012

\hyper@pagetransition 9178,
 9228, 10169, 10192, 10599,
 10721, 10976, 11011

\hyper@quote 6258, 9340, 9354,
 9369, 9374, 9395, 9409,
 9423, 10242, 10252, 10265,
 10288, 10306, 11872, 11886,
 11901, 11907, 11931, 11945,
 11959, 12159, 12172, 12187,
 12192, 12215, 12231, 12246

\hyper@readexternallink 5138,
 5149

\hyper@refstepcounter 6909,
 6913, 6921

\hyper@tilde 4759, 4760, 4761,
 6257

\hyperbaseurl 3488, 3489, 6353

\hypercalcbp 469, 469

\hypercalcbpdef 472

\hyperdef 4970, 6355

\HyperDestLabelReplace
 .. 5348, 5355, 5358

\HyperDestNameFilter
 .. 4149, 4838, 5029, 5042,
 5055, 5355, 8887, 8912,
 9340, 9354, 9374, 9418,

9703, 9905, 10242, 10252,
 10270, 10288, 10306, 10383,
 10395, 10444, 10527, 11362,
 11371, 11872, 11886, 11907,
 11954, 12159, 12172, 12192,
 12241, 14369, 14430, 14446
`\HyperDestRename` . 5328, 5346,
 5359
`\HyperFirstAtBeginDocument` .
 . 6380, 6382, 6398, 6401
`\hyperget` 5021
`\hypergetpageref` 7092
`\hypergetref` 7091
`\HyperGlobalCurrentHref` . . .
 . 7049, 7051, 7059, 7060,
 7064, 7067, 7071, 7078,
 7079, 7083
`\hyperimage` 4940, 8172
`\hyperindexformat` 8179
`\hyperlink` 4803, 6356, 8345
`\hyperlinkfileprefix` . 3491, 3492,
 3493, 12145
`\HyperLocalCurrentHref`
 . 7067, 7069, 7076, 7077,
 7078, 7079, 7081
`\hyperpage` 6362, 8180, 8181,
 8183, 8303
`\HyperRaiseLinkDefault` . 2204,
 2231
`\HyperRaiseLinkHook` 2203, 2232
`\HyperRaiseLinkLength` 2230,
 2231, 2234
`\hyperref` 4949, 6358, 8441, 8457,
 8466, 8488
`\hyperrefundefinedlink` 4983,
 4994
`\hypersetup` 2572, 2617, 3318,
 3796, 4169, 6352
`\hypertarget` 4942, 6357
`\HyPL@@CheckThePage` 6628,
 6646
`\HyPL@@CheckThePage` . 6604,
 6606
`\HyPL@Alpha` 6523
`\HyPL@alpha` 6524
`\HyPL@arabic` 6520
`\HyPL@CheckThePage` 6555,
 6603
`\HyPL@Entry` 6805, 6813, 6821,
 6823
`\HyPL@EveryPage` 6543, 6667
`\HyPL@Format` 6619, 6620, 6621,
 6622, 6623, 6635
`\HyPL@found` 6618, 6625, 6629,
 6636, 6646, 6648
`\HyPL@Labels` 6514, 6658, 6659,
 6661, 6663, 6714, 6715,
 6816, 6824, 6825
`\HyPL@LastNumber` 6518, 6574,
 6597
`\HyPL@LastPrefix` 6519, 6568,
 6599
`\HyPL@LastType` 6517, 6559,
 6598
`\HyPL@page` 6537, 6546, 6549,
 6555, 6564
`\HyPL@Prefix` 6564, 6566, 6568,
 6582, 6585, 6587, 6599,
 6613, 6651
`\HyPL@Roman` 6521
`\HyPL@roman` 6522
`\HyPL@SetPageLabels` 6657,
 6722, 6819
`\HyPL@SlidesOptionalPage` 6530,
 6534, 6539
`\HyPL@SlidesSetPage` 6525,
 6527, 6547, 6554
`\HyPL@StorePageLabel` 6582,
 6584, 6654, 6712, 6800
`\HyPL@thisLabel` 6511, 6513,
 6545, 6549, 6550
`\HyPL@Type`
 . 6552, 6559, 6563, 6581,
 6589, 6598, 6612, 6650
`\HyPL@Useless` 6655, 6661
`\HyPsd@@@autoref` . 1368, 1370,
 1373
`\HyPsd@@@CJKdigits` 1238,
 1241, 1249
`\HyPsd@@@nameref` 1350, 1352,
 1355
`\HyPsd@@@pageref` . 1332, 1334,
 1337
`\HyPsd@@@ref` . 1316, 1318, 1321
`\HyPsd@@@UTFviii@four` 1965,
 1968
`\HyPsd@@AppendItalcorr` 1509
`\HyPsd@@autoref` 1365, 1366
`\HyPsd@@autorefname` 1386,
 1389
`\HyPsd@@CJKdigits` 1230, 1232,
 1235
`\HyPsd@@CJKnumber`
 . 1131, 1133, 1136, 1189,
 1204, 1217, 1219, 1223
`\HyPsd@@ConvertToUnicode`
 . 1837

`\HyPsd@@ding` 2102, 2106, 2117
`\HyPsd@@GetNextTwoTokens` .
 1835
`\HyPsd@@GlyphProcessWarning`
 1695, 1698
`\HyPsd@@hspace` 1286, 1287
`\HyPsd@@LetCommand` . 1410,
 1431
`\HyPsd@@nameref` 1347, 1348
`\HyPsd@@pageref` 1329, 1330
`\HyPsd@@ProtectSpacesFi` 1454,
 1460
`\HyPsd@@ref` 1313, 1314
`\HyPsd@@RemoveBraces` . 1477
`\HyPsd@@RemoveBracesFi` 1474,
 1477
`\HyPsd@@RemoveCmdPrefix` .
 1652, 1655
`\HyPsd@@ReplaceFi` 1722, 1728,
 1733
`\HyPsd@@UTFviii@four` 1949,
 1954
`\HyPsd@add@accent` . 512, 1275
`\HyPsd@AfterCountRemove` .
 1529, 1609
`\HyPsd@AfterDimenRemove` .
 1535, 1612
`\HyPsd@AfterSkipRemove` 1541,
 1624
`\HyPsd@AMSclassfix` 619, 1296,
 1298
`\HyPsd@AppendItalcorr` . 1493,
 1500, 1509
`\HyPsd@autoref` 629, 1365
`\HyPsd@autorefname` 1377, 1383
`\HyPsd@CatcodeWarning`
 . 1545, 1569, 1572, 1575,
 1578, 1636
`\HyPsd@Char` 1839
`\HyPsd@CharOctByte` 1859,
 1861, 1864, 1873, 1878
`\HyPsd@CharSurrogate` 1853,
 1870
`\HyPsd@CharTwoByte` 1851,
 1858
`\HyPsd@CheckCatcodes` 683,
 1519
`\HyPsd@CJK@Unicode` 1013,
 1017
`\HyPsd@CJKActiveChars` 953,
 968
`\HyPsd@CJKdigit` 1242, 1252
`\HyPsd@CJKdigits` 1015, 1228
`\HyPsd@CJKhook` 636, 924, 935

\ifHy@bookmarksopen 368, 4589
 \ifHy@breaklinks 369, 2494, 10920, 10961, 11256, 11279
 \ifHy@CJKbookmarks 371, 929
 \ifHy@colorlinks 372, 4670, 6241, 11853
 \ifHy@destlabel 373, 5295
 \ifHy@draft 374, 4237
 \ifHy@DviMode 2650, 2670, 2865
 \ifHy@DvipdfmxOutlineOpen 4572, 14448
 \ifHy@frenchlinks 380, 4683
 \ifHy@chref@ismap 4900, 8987, 10024, 10420, 10490, 11513
 \ifHy@hyperfigures 378, 4330, 6221, 8169
 \ifHy@hyperfootnotes 381, 7313
 \ifHy@hyperindex 382, 4340, 6231, 8176
 \ifHy@hypertexnames 383, 7035, 7929
 \ifHy@implicit 384, 4355, 4697, 14500
 \ifHy@linktocpage 385, 2454, 2464
 \ifHy@localanchorname 386, 7068, 7080
 \ifHy@naturalnames 388, 7047
 \ifHy@nesting 389, 4335, 4943, 4977, 5015, 5270, 6226, 7338, 7358, 7436, 7596
 \ifHy@next 920, 8193
 \ifHy@ocgcolorlinks 392, 3380, 4656, 4666, 6246, 8679, 8768, 8846, 8854, 9768, 9851, 9859
 \ifHy@pageanchor 393, 7928
 \ifHy@pdfa 411, 4259, 4658, 5172, 5476, 6070, 6123, 6251, 8916, 8982, 9017, 9051, 9311, 9914, 9947, 9982, 10014, 10044, 10426, 10447, 10470, 10496, 10530, 10564, 10583, 11386, 12453, 12644, 12697, 13049, 13249, 13303, 13422, 13618, 13676, 13891, 13939, 14108
 \ifHy@pdfcenterwindow 370, 9102, 9650, 10113, 10778, 11130, 12037
 \ifHy@pdfdisplaydoctitle 410, 9103, 9651, 10114, 10779, 11131, 12038
 \ifHy@pdfescapeform 377, 13786, 13816
 \ifHy@pdffitwindow 379, 9101, 9649, 10112, 10777, 11129, 12036
 \ifHy@pdfmarkerror 11177, 11186
 \ifHy@pdfmenubar 387, 9099, 9647, 10110, 10775, 11127, 12034
 \ifHy@pdfnewwindow 391, 3992, 10467
 \ifHy@pdfnewwindowset 390, 3990
 \ifHy@pdfpagelabels 394, 6499, 6712, 6799
 \ifHy@pdfstring 395, 887
 \ifHy@pdftoolbar 403, 9098, 9646, 10109, 10774, 11126, 12033
 \ifHy@pdfusetitle 405, 6406
 \ifHy@pdfwindowui 409, 9100, 9648, 10111, 10776, 11128, 12035
 \ifHy@plainpages 396, 4345, 7930
 \ifHy@psdextra 402, 595, 877
 \ifHy@psize 397
 \ifHy@raiselinks 398, 9387, 9467, 9504, 9544, 11923, 12205
 \ifHy@seminarslides 399
 \ifHy@setpagesize 400, 9235, 10198, 10342, 11656
 \ifHy@setpdfversion 2618, 8684
 \ifHy@stoppedearly 362
 \ifHy@texht 401, 4416, 4695, 5887, 5920, 6094, 6118, 6289, 8353
 \ifHy@typexml 363
 \ifHy@unicode 404, 498, 533, 536, 596, 694, 706, 734, 742, 751, 948, 1639, 1660, 1673, 1702, 1708, 1975, 2043, 2093, 2533, 2573, 3677, 6736, 13838
 \ifHy@verbose 406, 4807, 4823, 4835, 5419, 8002, 8688
 \ifHyField@NeedAppearances 5860, 5862, 5865, 12455, 13051, 13424
 \ifHyInfo@AddonUnsupported 3808, 3822, 3863
 \IfHyperBoolean 2318
 \IfHyperBooleanExists 2312, 2319
 \ifin@ 6958
 \ifmeasuring@ 6920, 6924
 \ifmmode 10923, 11251
 \ifnum 1018, 1129, 1145, 1149, 1169, 1182, 1185, 1198, 1200, 1213, 1215, 1221, 1847, 1850, 1933, 1976, 1979, 1991, 2044, 2047, 2060, 2094, 2097, 2100, 2104, 2119, 2123, 2126, 2212, 2247, 2659, 2775, 2778, 2804, 3423, 3424, 4260, 4452, 4488, 4502, 4505, 4583, 4590, 4877, 5698, 5769, 5780, 6529, 6553, 6574, 6590, 6692, 6985, 6988, 7878, 7888, 8680, 8685, 8699, 8703, 8708, 8726, 8747, 9266, 9880, 9885, 10200, 10344, 10467, 10597, 10727, 10735, 10737, 10738, 10748, 10751, 10851, 10853, 10973, 11658, 11699, 12611, 12616, 12621, 12952, 13029, 13225, 13573, 13578, 13589, 13837, 13919, 13950, 13955, 13978, 13984, 14013, 14047, 14053, 14072, 14083, 14088, 14119, 14124, 14153, 14169, 14312, 14382, 14385, 14409, 14412, 14450, 14558, 14573, 14588
 \ifodd 1957, 1962, 7955
 \ifpatchable 7308
 \ifpdf 2652, 2695, 2706, 4395, 4478
 \ifpdfstringunicode 503, 506
 \ifportrait 9246
 \ifthenelse 7808
 \iftrue 1453, 1732, 5865, 14560
 \iftutex 757
 \ifvmode 2223, 2245, 2258
 \ifvoid 7159, 7163
 \ifvtex 2658, 2774, 2803, 4452, 4488, 4502, 4505
 \ifxetex 2655, 2747, 3676, 4421, 4485, 4573, 5060
 \ignorespaces 633, 7289, 7346, 7352, 7366, 7375, 7473, 7581, 7592, 7595, 7653, 7661, 7725, 7740, 7757, 7766, 7816
 \iiint 17831, 19999
 \iinferior 19804
 \iint 17829, 19998

\IJ	14779, 15568
\ij	14992, 15570
\Im	17467, 19871
\immediate	5363, 5365, 6379, 6705, 6804, 6812, 7720, 7735, 7752, 7762, 7781, 7811, 8770, 8785, 8800, 10856, 11696, 12915, 12971, 12974, 13035, 14302, 14368, 14399, 14478
\in	17748, 19965
\in@	6956
\incr@eqnum	7180, 7193
\index	622
\indexentry	8231, 8246, 8261, 8265, 8275
\Info	19405, 20568
\infty	17791, 19983
\input	856, 866, 880, 3343, 3351, 3358, 4545, 11591, 11697, 11796, 11973, 16318
\InputIfFileExists	4171, 14392, 14423, 14468, 14470
\inputlineno	4814, 5277
\insert	7451
\int	17826, 19997
\IntCalcAdd	1876
\IntCalcDec	1040, 2070
\intcalcDec	2052
\IntCalcDiv	1034, 1043, 1048, 1151, 1160, 1172, 1189, 1204, 1219, 1860, 1866, 1872
\intcalcDiv	1024, 1867, 1874, 1877
\IntCalcMod	1036, 1045, 1051, 1155, 1161, 1176, 1192, 1207, 1221, 1223, 1862, 1867, 1868, 1874, 1877, 1879
\intcalcMod	1026
\intcalcNum	2074, 2102, 2106
\IntCalcSub	2068, 2121, 2124, 2127, 2130
\intcalcSub	1854, 2050
\interfootnotelinepenalty	7454
\interleave	19308, 20537
\interlinepenalty	7454
\inva	15954, 20624
\invamp	17513
\invbackneg	18307, 20202
\invdiameter	19107, 20450
\inve	15813, 19732
\invglotstop	16198, 19765
\invh	16029, 20643
\invlegr	16104, 20666
\invm	16063, 20654
\invneg	19168, 20475
\invr	16099, 20664
\invscr	16126, 19753
\invscripta	15962, 20626
\invv	16161, 20678
\invw	16165, 20680
\invy	16169, 20682
\iota	19785
\ipagamma	16021, 19744
\isuperior	19828
\item	6874, 6877, 7748, 7760, 7803
\Itemautorefname	8593
\Itemautorefname	2957, 2975, 2993, 3011, 3029, 3047, 3065, 3094, 3095, 3123, 3141, 3159, 3177, 3195, 3213, 3231, 3249, 8593, 8594, 8597
\itshape	566
J	
\j	15575, 15833, 15940
\JackStar	18881, 20353
\JackStarBold	18883, 20354
\jarr	19638
\jeem	19582
\jeh	19654
\jinferior	20541
\jobname	12273, 14301, 14392, 14399, 14423, 14468, 14470, 14478
\Join	19151, 20468
\Jupiter	18669, 20850
\jupiter	18667, 20278
K	
\k	14660, 15009, 15011, 15016, 15018, 15070, 15101, 15130, 15145, 15463, 15465, 15509, 15511, 15559, 15561, 15562, 15699, 15701, 15829, 15831, 16678, 16720, 16723
\kaf	19618
\kanjiskip	444
\kappa	19786
\kasra	19644
\keepPDF@SetupDoc	11857, 11864
\kern	1533, 1614, 1619, 1631, 7950, 7951, 7952, 7954, 7955, 7960, 14515
\kernel@fnextchar	653
\Keyboard	18325, 20210
\kha	19586
\kinferior	19862
\Kutline	18539, 20814
\kv@define@key	3830
\KV@href@pdfnewwindow	4898
\KV@href@pdfnewwindow@de-	fault
\KV@Hyp@draft	2428
\KV@Hyp@nolinks	2428
\KV@Hyp@pdfnewwindow	4898
\KV@Hyp@pdfnewwindow@de-	fault
\kv@key	3816, 3819, 3826, 5696, 5699, 5701, 5705, 5709
\kv@parse	5695
\kv@parse@normalized	3847, 3854
\kv@processor@default	3850, 3857
\kv@set@family@handler	3809
\kv@value	3814, 5697, 5704, 5705
\kvsetkeys	2617, 2682, 2822, 3683, 3789, 4261, 4515, 4534, 4657, 5794, 8681, 11185, 12468, 12770, 12783, 12832, 12875, 12896, 13026, 13407
L	
\L	14772, 15599
\l	6903, 14785, 15601
\labdentalnas	16071, 20657
\label	621, 7975
\label@@hyperref	4985, 4987
\label@hook	5345
\label@hyperdef	4970, 5001
\label@hyperref	4950, 4984
\label@name	5310, 5320, 5346
\labelsep	7815
\labelwidth	7814
\Ladiesroom	19394, 20565
\lam	19620
\Lambda	19769
\lambda	19787
\lambdaabar	15761, 20613
\lambdadaslash	15762, 20614
\langle	18327, 20211
\language@group	605
\LARGE	573
\Large	574

\large	577	\leftharpoonup	17622, 19914	\literalps@out	2199, 10845, 10850,
\LargerOrEqual . . .	17973, 20767	\leftleftarrows	17654, 19925	10902, 10908, 10934, 10940,	
\lastnode type	2247	\leftleftharpoons	19072, 20437	11196, 11212, 11246, 11247,	
\lastskip	2246, 2254, 2261, 2269,	\leftModels	19293, 20907	11275, 11277, 11289, 11291,	
2273, 2280		\leftmodels	19286, 20905	11589, 11686, 11695, 11753,	
\LaTeX	530, 532, 12279, 12280	\leftmoon	18645, 20273	11766, 11847, 11971, 12131	
\LaTeXe	531, 12280	\leftpointright	18619, 20830	\ll	17986, 20066
\latfric	16053, 20651	\Leftrightarrow	17688, 19938	\llap	5075
\LayoutCheckField	6172, 12728,	\leftrightarrow	17563, 19888	\llbracket	18994, 20886
13332, 13713		\leftrightarrows	17652, 19924	\llcorner	18317, 20206
\LayoutChoiceField	6164, 12578,	\leftrightarrowtriangle	17729,	\Leftarrow	17701, 19944
13180, 13536		19956		\Ll	18238, 20172
\LayoutPushButtonField	6180,	\leftrightharpoon	19061, 20433	\llparenthesis	19103, 20448
12648, 12656, 13253, 13260,		\leftrightharpoons	17663, 19929	\lnapprox	19216, 20496
13622, 13631		\Leftscissors	18820, 20881	\lneq	19211, 20494
\LayoutTextField	6156, 12522,	\leftslice	19230, 20502	\lneqq	17982, 20064
13125, 13478		\leftspoon	18990, 20404	\lnsim	18270, 20186
\lbrackdbl	20405	\leftsquigarrow	17705, 19946	\Longleftarrow	19009, 20412
\lccode	958, 1741, 1742, 1743,	\lefttherefore	17343, 19824	\longleftarrow	19003, 20409
1744, 1745, 1746, 1747,		\leftthreetimes	18204, 20157	\Longleftrightarrow	19013, 20414
1748, 1749, 1750, 1897,		\LeftTorque	19054, 20890	\longleftrightarrow	19007, 20411
6030, 8190, 8191, 14226,		\Lefttorque	19055, 20891	\longlegr	19751
14227, 14228, 14229, 14230,		\leftVdash	19280, 20903	\Longmapsfrom	19017, 20416
14231, 14232, 14233, 14234,		\leftvdash	18125, 20780	\Longmapsto	19019, 20417
14235, 14236		\legacy	6899, 6904, 6906	\longmapsto	19015, 20415
\lcurvearrowdown	19047, 20429	\legm	16068, 20656	\Longrightarrow	19011, 20413
\lcurvearrowse	19039, 20426	\legr	16111, 20668	\longrightarrow	19005, 20410
\lcurvearrowsw	19042, 20427	\Leo	18696, 20859	\looparrowleft	17604, 19907
\ldots	523	\leo	18694, 20287	\looparrowright	17606, 19908
\le	17965, 20057	\leq	17965, 20056	\lower	5077, 9393, 9473, 9510,
\leadsto	19033, 20424	\leqclosed	18176, 20796	9550, 11277, 11929, 12211	
\leavevmode	630, 2201, 4247,	\leqq	17974, 20060	\lowercase	959, 1751, 1898, 2329,
4265, 4305, 5070, 5102,		\leqlant	19195, 20486	2901, 2931, 3756, 3792,	
5177, 6346, 7380, 7541,		\lessapprox	19203, 20490	5368, 5369, 5372, 5377,	
8502, 8902, 8970, 9005,		\lessclosed	18170, 20794	5401, 5411, 5465, 5521,	
9039, 9298, 9386, 9466,		\lessdot	18234, 20170	5841, 5915, 5918, 6031,	
9503, 9543, 9894, 9936,		\lesseqtr	18243, 20174	8192, 10972, 14237	
9974, 10007, 10240, 10249,		\lesseqqgtr	19221, 20498	\lozenge	18574, 20247
10303, 10462, 10487, 10517,		\lessgtr	18015, 20079		
10550, 10922, 11249, 11502,		\LessOrEqual	17968, 20766	\lrcorner	18319, 20207
11529, 11560, 11922, 12204,		\lessim	18005, 20075		
12523, 12649, 12657, 12696,		\LetLtxMacro	6293, 6297, 6366,	\LT@array	7144
12729, 13126, 13212, 13234,		6370		\LT@foot	7159, 7163
13254, 13261, 13282, 13302,		\Letter	18833, 20882	\LT@p@ftn	7412, 7415, 7419,
13333, 13479, 13571, 13600,		\LHD	18569, 20245	7429	
13623, 13632, 13656, 13675,		\lhd	18168, 20143		
13714, 14513		\lhooknarrow	19025, 20420		
\Leftarrow	17677, 19934	\lhooksearrow	19029, 20422		
\leftarrow	19884	\Libra	18702, 20861		
\leftarrowtail	17594, 19902	\libra	18700, 20289		
\leftarrowtriangle	17725, 19954	\Lightning	17612, 20736		
\leftbarharpoon	19084, 20441	\lightning	17610, 19910		
\LEFTCIRCLE	18576, 20248	\limits	4790		
\leftharpoondown	17625, 19915	\linferior	19863		

4137, 4138, 4139, 4143,
 4195, 4473, 4474, 4508,
 4518, 4617, 5122, 5123,
 5294, 5315, 5338, 5566,
 5584, 5598, 5611, 5627,
 5659, 5684, 5691, 5692,
 6017, 6055, 6056, 6057,
 6058, 6059, 6060, 6061,
 6062, 6063, 6064, 6065,
 6090, 6471, 6472, 6473,
 6476, 6488, 6497, 6514,
 6519, 6525, 6534, 6554,
 7208, 8034, 8045, 8054,
 8255, 8701, 8721, 8725,
 9326, 10230, 10317, 10926,
 11184, 11198, 11214, 11233,
 11254, 11321, 11588, 11694,
 11968, 12139, 12146, 12470,
 12491, 12504, 12745, 12780,
 12827, 12921, 12922, 12941,
 12948, 12964, 12995, 13038,
 13078, 13079, 13080, 13107,
 13432, 13449, 13456
`\ltx@firstofone` 2671, 4203, 5341,
 5358, 6401, 14254, 14266
`\ltx@firstoftwo` 330,
 338, 2061, 2314, 2321, 5233,
 7339, 7359
`\ltx@GlobalAppendToMacro` 905,
 5345
`\ltx@gobble` 255, 2677, 4196, 4223,
 4232, 4605, 5337, 5339,
 6306, 6307, 6318, 6320,
 6321, 6673, 12253, 12934,
 12950, 12955, 14252, 14264
`\ltx@gobblethree` 7910
`\ltx@gobbletwo` 5357, 5359, 6309,
 6323, 12935
`\ltx@ifclassloaded` .. 6526, 7871
`\ltx@ifempty` 5116
`\ltx@iffileloaded` 878, 6485
`\ltx@ifpackageloaded` 925, 13083
`\ltx@IfUndefined`
 261, 267, 306, 525,
 603, 643, 719, 754, 798, 799,
 800, 1295, 1390, 1391, 1515,
 2168, 4189, 4218, 4220,
 4902, 5306, 5337, 6446,
 6858, 6952, 6959, 6981,
 6996, 7249, 7683, 7889,
 8254, 8491, 8492, 8536,
 8537, 8539, 8540, 8686,
 8717, 8947, 8957, 10409,
 10512, 10898, 10941, 11020,

11205, 13081, 14549, 14559
`\ltx@ifundefined` 2118, 2313, 2314,
 2357, 5349, 7905, 8748
`\ltx@leftbracechar` 321
`\ltx@LocalAppendToMacro` 346,
 349, 6944, 6960, 6965
`\ltx@one` 6528, 6529, 6536, 7874,
 7878, 7884, 7887, 7888,
 7901, 8708, 13087
`\ltx@onellevel@sanitize` ... 6935,
 6954, 8293
`\ltx@returnAfterElseFi` .. 4772
`\ltx@returnAfterFi`
 .. 1689, 4776, 4792, 8312,
 8348, 8646, 8656, 13809
`\ltx@rightbracechar` 322
`\ltx@secondoftwo`
 ... 327, 2063, 2313, 2314,
 2323, 2325, 5127, 5231,
 7341, 7361, 12940, 12943,
 12946, 12949, 12953, 12954,
 12957
`\ltx@space` 324, 1446
`\ltx@zero` 1745, 1746, 1747, 1748,
 1749, 1750, 8696, 8703,
 12952, 13085
`\lz` 16060, 20653

M

`\m@ne` .. 4319, 4452, 4488, 4502,
 4505, 4826, 4885, 5383,
 7265, 9889, 14470, 14558,
 14571
`\mag` 9266, 10200, 10344, 11658
`\make@df@tag@@` .. 8116, 8118
`\make@df@tag@@@` .. 8117, 8119
`\make@stripped@name` .. 7263
`\makeatletter` 3, 848, 901
`\MakeButtonField` .. 6187, 12650,
 12659, 12681, 12701, 12707,
 13255, 13265, 13290, 13307,
 13314, 13624, 13627, 13655,
 13680, 13684
`\MakeCheckField` .. 6184, 12731,
 13337, 13710
`\MakeChoiceField` .. 6186, 12631,
 13238, 13598
`\MakeFieldObject` 12914, 13061,
 13071, 13074
`\MakeLinkTarget` 7299
`\MakeLowercase` 594
`\MakeLowercaseUnsupportedIn-`
`\PdfStrings` 473,
 594

`\MakeRadioField` .. 6183, 12614,
 13224, 13564
`\maketag@@@` 8105
`\MakeTextField` .. 6185, 12525,
 13130, 13475
`\maketitle` 7490, 7491
`\MakeUppercase` 593, 8438
`\MakeUppercaseUnsupportedIn-`
`\PdfStrings` 473,
 593
`\Male` 18666, 20849
`\male` 18662, 20277
`\MaleMale` 18783, 20314
`\ManFace` 19380, 20559
`\manstar` 18777, 20311
`\mapsto` 17598, 19904
`\Mars` 18665, 20848
`\mars` 18664, 20847
`\MathBSuppress` . 10250, 10254
`\mathclose` 7211
`\mathdisplay` 7183, 7192
`\mathdisplay@push` . 7181, 7190
`\mathdollar` 15171, 20580
`\mathellipsis` 17314, 20714
`\mathopen` 7202, 7231
`\mathparagraph` .. 15294, 20591
`\mathsection` 15261, 20589
`\mathsterling` ... 15250, 20586
`\mathunderscore` .. 15229, 20584
`\mathversion` 582
`\maxdimen` 3444, 12919
`\MaybeStopEarly`
 ... 459, 2685, 2780, 4359,
 4490, 6832, 6835
`\mbox` 631, 8856, 9861
`\mdseries` 565
`\meaning` 62,
 153, 159, 2177, 6430, 7060,
 7270, 14434, 14442, 14457
`\measuredangle` .. 17795, 19985
`\measuring@false` 6920
`\mediaheight` 10347, 10352, 10361
`\mediawidth` 10348, 10353, 10362
`\meem` 19622
`\Mercury` 18651, 20840
`\mercury` 18649, 20275
`\merge` 19182, 20902
`\MessageBreak` 263,
 269, 286, 287, 292, 293, 333,
 334, 1645, 1666, 1679, 1702,
 1707, 1709, 2351, 2352,
 2367, 2389, 2392, 2394,
 2472, 2473, 2496, 2497,
 2545, 2546, 2547, 2585,

2586, 2607, 2622, 2674,	\Mundus	19376, 20557	\neq	17954, 20052
2700, 2716, 2751, 2790,	\MVArrowDown . .	17561, 20732	\neqcirc	17940, 20046
2797, 2808, 2814, 2838,	\MVAt	15221, 19720	\neqdot	19191, 20484
2847, 2852, 2872, 2885,	\MVComma	15189, 19706	\neqsim	17872, 20016
2923, 3382, 3505, 3506,	\MVDivision	15195, 19709	\nequal	17957, 20762
3566, 3567, 3585, 3586,	\MVEight	15213, 19718	\nequiv	17961, 20055
3680, 3769, 3824, 3825,	\MVFive	15207, 19715	\neswarow	19023, 20419
3945, 3946, 4068, 4069,	\MVFour	15205, 19714	\netscape	9429
4070, 4091, 4093, 4101,	\MVMinus	15191, 19707	\Neural	18789
4102, 4109, 4159, 4399,	\MVMultiplication .	15365, 20595	\Neutral	20317
4400, 4408, 4409, 4425,	\MVNine	15215, 19719	\new@ifnextchar	654
4426, 4441, 4442, 4456,	\MVOne	15199, 19711	\new@pdflink	8881, 8935, 8938
4457, 4465, 4466, 4660,	\MVPeriod	15193, 19708	\new@refstepcounter	7174, 7205
4879, 4880, 4904, 4905,	\MVPlus	15187, 19705	\newblock	7819
4921, 4922, 5422, 5427,	\MVRightArrow . .	17557, 20730	\newcommand	4, 9,
5436, 5479, 5525, 5649,	\MVRrightarrow . .	17558, 20731	42, 2200, 5062, 5068, 5100,	
5762, 5834, 5845, 5877,	\MVSeven	15211, 19717	5305, 5328, 6350, 6354,	
5878, 5897, 5989, 5990,	\MVSix	15209, 19716	7292, 7612, 8137, 14274,	
5991, 5992, 6504, 6739,	\MVThree	15203, 19713	14277, 14282, 19704, 20576	
6754, 6755, 7979, 8009,	\MVTwo	15201, 19712	\newcount	460,
8010, 8011, 8012, 8013,	\MVZero	15197, 19710	461, 2205, 2643, 4870, 5800,	
8691, 8709, 8729, 8731,			6515, 12474, 12626, 13084,	
8737, 8739, 8742, 8750,			13231, 13438, 13594, 14309	
8906, 9899, 10438, 10521,	\nabla	17746, 19964	\newcounter	6875, 7314, 9767,
10809, 10815, 11029, 12928,	\name@of@eq	6892	14224	
12930, 14174, 14192, 14304	\nameref	628	\newdimen	457, 4381, 4382,
\MF	\napprox	17885, 20022	5058, 5801, 5802	
\mho	\napproxeq	17890, 20024	\NewDocumentCommand	2297,
\mid	\nasb	19634	8501	
\MineSign	\nasymp	17903, 20030	\NewExpandableDocumentCom-	
\mininferior	\natural	18750, 20299	mand	2306
\minusdot	\nbackcong	17899, 20028	\NewHook	7023
\minusinferior	\backsim	17863, 20012	\newif	362, 363, 364, 365,
\minussuperior	\backsimeq	18210, 20160	366, 367, 368, 369, 370, 371,	
\models	\nBumpeq	17908, 20032	372, 373, 374, 377, 378, 379,	
\moo	\nbumpeq	17912, 20034	380, 381, 382, 383, 384, 385,	
\Moon	\ncirceq	17944, 20048	386, 387, 388, 389, 390, 391,	
\MoonPha	\ncong	17881, 20020	392, 393, 394, 395, 396, 397,	
2091, 20579	\ncurlyeqprec	18250, 20177	398, 399, 400, 401, 402, 403,	
\Mountain	\ncurlyeqsucc	18254, 20179	404, 405, 406, 409, 410, 411,	
\MoveDown	\DashV	19294, 20531	920, 2618, 2650, 3808, 4572,	
\MoveUp	\Dashhv	19287, 20529	4900, 5375, 5463, 5796,	
\MP	\dashV	19281, 20527	5797, 5817, 5860, 6893,	
\mp	\dashhv	18126, 20129	6894, 6920, 7217, 10229,	
\mu	\Doteq	17922, 20038	11177	
\mugreek	\ndoteq	17916, 20036	\newlabel	2180, 5011, 6384, 6385,
\multimap	\downmodels	19299, 20533	6392, 6403	
\multimapboth	\downnvdash	18132, 20131	\newlabelxx	6386, 6387
\multimapdotbothA	\ne	17954, 20053	\newlength	14506
20147	\Nearrow	17695, 19941	\newline	528, 6451
\multimapdotbothB	\nearrow	17569, 19891	\newname	7266, 7275
20148	\neg	20570	\newsavebox	9697, 11225
\MultiplicationDot	\Neptune	18678, 20853	\newtie	14662, 14663, 15060,
\multiply	\neptune	18676, 20281	15111, 15140, 15158	

\newtoks	90, 5888, 11047, 11300, 11301	\nobreak	2250, 2259, 2270, 2278, 7381, 7542	\NotCongruent	... 17963, 20764
\newwrite 14397, 14476	\nobreakspace	. 642, 8495, 8498	\notdivides 17806, 20747
\nexists 17739, 19961	\NoChemicalCleaning	... 19121, 20454	\note 7919
\next	.. 7809, 7810, 7811, 10665, 10667, 10669	\noexpand 22, 93, 95, 108, 116, 169, 171, 172, 173, 176, 206, 909, 972, 1405, 1422, 1524, 1551, 1912, 2257, 2258, 2259, 2262, 2276, 2277, 2278, 2281, 3292, 3294, 3296, 3297, 3298, 3300, 3318, 3515, 3516, 3518, 3880, 4321, 4325, 4326, 4515, 4784, 4958, 5272, 5274, 5300, 5431, 5976, 6628, 6629, 6638, 6640, 6643, 6777, 6938, 6939, 6956, 7097, 7098, 7099, 7100, 7101, 7109, 7110, 7111, 7269, 7403, 7413, 7421, 7422, 7423, 7425, 7552, 7642, 7719, 7734, 7751, 7876, 8032, 8128, 8130, 8414, 8415, 8545, 8546, 8551, 8553, 8558, 8559, 8564, 8565, 9634, 11114, 11181, 11763, 12021, 12553, 12554, 12555, 12556, 13154, 13155, 13156, 13157, 13510, 13511, 13512, 13513, 13788	\notequiv	... 17964, 20765
\nfallingdoteq 20040	\noexpandQ 1551	\notin 17750, 19966
\nfallingdotseq 17927	\nofrenchguillemets	... 661, 663	\notni 17759, 20742
\nfss@text	8360, 8380, 8397, 8529	\NoHy@OrgPageRef	6297, 6299, 6370, 6372	\notowner 17757, 19969
\NG 15617	\NoHy@OrgRef	6293, 6295, 6366, 6368	\notperp 18984, 20401
\ng	15619, 15620, 15621, 20603, 20604	\NoHyper 6301	\notslash 18338, 20215
\ngeq 18003, 20074	\nohyperpage	6345, 8302, 8304, 8306	\noway 18807, 20321
\ngeqq 17980, 20063	\nolinkurl 4936	\nparallel 17809, 19990
\ngeqlang 19201	\nolinkurl@ 4936, 4937	\nperp 18139, 20784
\ngeqlant 20489	\NomFancyVerbLineautorefname 3112	\nprec 18039, 20091
\ngg 17992, 20069	\Nomfootnoteautorefname	3092	\nprecapprox 19260, 20517
\ngtr 17998, 20072	\Nomtheoremautorefname	3116	\npreccurlyeq 18256, 20180
\ngtrapprox 19209, 20493	\nonumber 7244, 7247	\nsubset 18073, 20108
\ngtrclosed 18283, 20808	\normalbaselineskip	6205, 6206, 6207, 6208, 6209, 6210	\nsupset 18081, 18262, 20112
\ngtrless 18019, 20081	\normalfont 560	\nsupseteq 18220, 20164
\ngtrsim 18013, 20078	\normalsize 578, 7588, 7660	\nsupseteqq 18047, 20095
\nhateq 17950, 20050	\notasymp 17905, 20758	\nsucc 18055, 20099
\ni 17754, 19968	\notbackslash	... 18341, 20216	\nsuccapprox 19240, 20507
\NibRight 18845, 20336			\nsucccurlyeq 19252, 20513
\NibSolidRight	... 18847, 20337			\nsuccsim 18037, 20090
\niepsilon 15993, 19739			\nsuperior 19264, 20519
\niota 16042, 19747			\nsucccurlyeq 18258, 20181
\nineinferior 19850			\nsucceq 18240, 20507
\ninesuperior 19834			\nsuccqq 19252, 20513
\ninferior 19865			\nsuccsim 19840
\niphι 16095, 19750			\nsupset 18224, 20166
\niupsilon 16153, 19756			\nsupseteq 18049, 20096
\nj 16075, 20659			\nsupseteqq 18057, 20100
\nLeftarrow 17669, 19931			\nsupseteqq 19276, 20525
\nleftarrow 17577, 19894			\nthickapprox 17887, 20756
\nleftModels 19296, 20908			\ntriangleleft 18278, 20190
\nleftmodels 19289, 20906			\ntriangleright 18285, 20192
\nLeftrightarrow 17671, 19932				
\nleftrightarrow 17608, 19909				
\nleftVdash 19283, 20904				
\nleftvdash 18128, 20781				
\nleq 18001, 20073				
\nleqq 17976, 20061				
\nleqlant 19197, 20487				
\nless 17996, 20071				
\nlessapprox 19205, 20491				
\nlessclosed 18280, 20807				
\nlessgr 18021, 20082				
\nlessim 18011, 20077				
\nll 17988, 20067				
\nmid 17804, 19988				
\nmodels 18161, 20791				
\noboundary 526				

\ntriangleright	18281, 20191	\o	14976, 15437, 15852	\oneinferior	19842
\ntrianglerighteq	18288, 20193	\oasterisk	18109, 20778	\onesuperior	19724
\ntriplesim	17895, 20026	\obackslash	19115, 20894	\oo	19342, 20544
\ntwoheadleftarrow	17583, 19897	\obar	19109, 20451	\openbullet	20250
\ntwoheadrightarrow	17590, 19900	\obeylines	11762	\openo	15969, 19735
\nu	19790	\OBJ@acroform . . .	13057, 13058	\openout	14399, 14478
\null	7800, 7808, 8402, 8525	\OBJ@Helv	13032, 13045, 13397	\oplus	18087, 20115
\number	1131, 1133, 1160, 1161, 1851, 1916, 1917, 1918, 1919, 1923, 1924, 1925, 1926, 1927, 1931, 1932, 1933, 1934, 1935, 1936, 1937, 1941, 1942, 1943, 1944, 1945, 1946, 1949, 1951, 1955, 1956, 1958, 1960, 1962, 1965, 1969, 1970, 1971, 1972, 1981, 1982, 1986, 1987, 1994, 1995, 1999, 2002, 2003, 2004, 2014, 2016, 2017, 2022, 2024, 2025, 2030, 2031, 4574, 4591, 5389, 6986, 6989, 7037, 7038, 7041, 7045, 8762, 8765, 8766, 9457, 9475, 9476, 9491, 9492, 9512, 9513, 9529, 9530, 9552, 9553, 9569, 9570	\OBJ@OCG@print	8799, 8802, 8810, 8837, 9785, 9787, 9800, 9804, 9813, 9842	\OpMode	2659, 2775, 2778, 2791, 2804, 2809, 4452, 4488, 4502, 4505, 10748, 10853, 11699
\numberline	7581, 7653, 14197, 14202	\OBJ@OCG@view 8784, 8802, 8836, 9769, 9771, 9784, 9804, 9841	\or	328, 978, 979, 980, 981, 982, 983, 984, 985, 986, 987, 988, 989, 990, 991, 992, 993, 994, 995, 996, 997, 998, 999, 1000, 1001, 1002, 1003, 1004, 1005, 1006, 1007, 1008, 1009, 1027, 1049, 1052, 1058, 1059, 1060, 1061, 1062, 1063, 1064, 1065, 1066, 1067, 1068, 1069, 1070, 1071, 1072, 1073, 1074, 1075, 1076, 1077, 1078, 1079, 1080, 1081, 1082, 1083, 1084, 1085, 1086, 1087, 1088, 1089, 1094, 1095, 1096, 1097, 1098, 1099, 1100, 1101, 1102, 1103, 1104, 1105, 1106, 1107, 1108, 1109, 1110, 1111, 1112, 1113, 1114, 1115, 1116, 1117, 1118, 1119, 1120, 1121, 1122, 1123, 1124, 1125, 1138, 1139, 1140, 1141, 1142, 1254, 1255, 1256, 2076, 2079, 2081, 2084, 5549, 5555, 5560, 5774, 7006, 7007, 7008, 7009, 7015, 7016, 7017, 7018, 8039, 8043, 10741, 14317, 14318, 14319, 14320, 14321, 14322, 14323, 14324, 14325, 14326, 14327, 14328, 14329, 14330, 14331, 14332, 14333, 14334, 14335, 14336, 14337, 14338, 14339, 14340, 14341, 14342, 14343, 14344, 14345, 14346, 14347, 14348
\nun	19624	\oinferior	19858	\OrnamentDiamondSolid . .	18974
\nupmodels	19303, 20535	\oint	17833, 20000	\oslash	18096, 20118
\nupvdash	18137, 20133	\ointclockwise . . .	17839, 20002	\otimes	18093, 20117
\nVDash	18165, 20142	\ointcclockwise . . .	17841, 20003	\ovee	17819, 19994
\nVdash	18162, 20141	\oldb	798	\overlay	7916
\nvDash	18158, 20140	\oldc	799		
\nvdash	18155, 20139	\oldd	800		
\Nvash	18149, 20137	\oldnewlabel . . .	6384, 6389, 6392		
\Nwarrow	17693, 19940	\olessthan	19123, 20455		
\nwarrown	17567, 19890	\OMEGA	12278		
\nwsearrow	19021, 20418	\Omega	19776		
O		\omega	19801		
\O	14907, 15367, 15849	\ominus	18090, 20116		
		\oneline	8006, 8007		

\owedge 17814, 19992
\owns 17756, 20741

P

\P 522
\p@ 1982, 1987, 5803, 5809, 9402,
9486, 9524, 9564, 10701,
11938, 12225, 12549, 13150,
13506
\p@equation 8112
\PackageError 61
\PackageInfo 8759, 12926
\PackageWarning 2621, 5760
\pageautorefname 2970, 2988,
3006, 3024, 3042, 3060,
3078, 3118, 3136, 3154,
3172, 3190, 3208, 3226,
3244, 3262, 8498, 8610
\pagename 8495
\pageref 627, 4369, 6297, 6298,
6370, 6371, 8484, 8488
\paperheight 4152, 9251, 9253,
9256, 9258, 9273, 9275,
9282, 9284, 10206, 10207,
10214, 10215, 10351, 10352,
10360, 10361, 11664, 11665,
11672, 11673
\paperwidth 9247, 9249, 9260,
9262, 9272, 9274, 9281,
9283, 10205, 10207, 10213,
10215, 10350, 10353, 10359,
10362, 11663, 11665, 11671,
11673
\par 7580, 7608, 7651, 7661,
7802, 7822
\paragraphautorefname
. 2966, 2984, 3002, 3020,
3038, 3056, 3074, 3107,
3109, 3132, 3150, 3168,
3186, 3204, 3222, 3240,
3258, 8606
\parallel 17807, 19989
\parenleftinferior 19854
\parenleftsuperior 19838
\parenrightinferior 19855
\parenrightsuperior 19839
\parr 17516, 20729
\partautorefname 2960, 2978,
2996, 3014, 3032, 3050,
3068, 3098, 3126, 3144,
3162, 3180, 3198, 3216,
3234, 3252, 8600
\partial 17735, 19959
\partnumberline 14199, 14204

\PassOptionsToPackage
. 2697, 2709, 2712, 2724,
2735, 2764, 2823, 2829,
2860, 2912, 2916, 2938,
4187, 4200, 4211, 4535
\patchcmd 7309
\pdf@addtoks 11303, 11325,
11331, 11340, 11347, 11351,
11353, 11355, 11357, 11359,
11367, 11376, 11380, 11382,
11384, 11387, 11396, 11400,
11402, 11404, 11406, 11408,
11410, 11412, 11414, 11416,
11418, 11420, 11422, 11424,
11426, 11428, 11430, 11431,
11432, 11433, 11434, 11435,
11436, 11437, 11438, 11439,
11440, 11445
\pdf@addtoksx 11297, 11307,
11323
\pdf@box 11225, 11257, 11265,
11273, 11274, 11277, 11281,
11283, 11286
\pdf@defaulttoks 11181, 11301,
11302, 11312
\pdf@docset 11047
\pdf@endanchor 8894, 8935, 8942
\pdf@escapestring 8665
\PDF@FinishDoc 2688, 2689,
2783, 2784, 4146, 4249,
4362, 4363, 4493, 4494,
6344, 6496, 6497, 9137,
9326, 9581, 10065, 10230,
10819, 11048, 11975, 12146
\pdf@ifdraftmode 6672, 8769,
9138, 9226, 13027, 14406
\pdf@linktype 11205, 11209,
11317, 11318
\pdf@objdef 11184, 11198, 11200,
11214, 11216, 11320, 11321
\pdf@rect 11192, 11211, 11229
\PDF@SetupDoc 4145, 4248,
6263, 6264, 6343, 9068,
9327, 9614, 10107, 10231,
10756, 11101, 11859, 12008,
12147
\PDF@SetupDox 9068
\pdf@toks 11181, 11202, 11218,
11300, 11304, 11308
\pdf@type 11183, 11188, 11202,
11218, 11295, 11315
\pdfbookmark 2200, 6349, 6350,
14275, 14280, 14285, 14289
\pdfcatalog 6675, 8806, 9083,
9125, 13058
\PDFdefaults 11311
\pdfdest 8896
\pdfendlink 8932, 13130, 13224,
13239, 13266, 13291, 13315,
13338
\pdfescapestring 13817
\pdfextension 2707, 4390, 4479
\PDFForm@Name 13825,
13828, 13832, 13835
\PDFForm@Check 12730, 12734,
13335, 13336, 13715, 13719,
13908
\PDFForm@List 12629, 12634,
13236, 13237, 13601, 13606,
13969
\PDFForm@Name 13121, 13175,
13248, 13329, 13470, 13531,
13617, 13706, 13824
\PDFForm@Push 12658, 12662,
13263, 13264, 13633, 13637,
13939
\PDFForm@Radio 12610, 12618,
13214, 13216, 13572, 13584,
14003
\PDFForm@Reset 12705, 12710,
13312, 13313, 13685, 13690,
14108
\PDFForm@Submit 12679,
12684, 13284, 13286, 13657,
13662, 14074
\PDFForm@Text 12524, 12528,
13128, 13129, 13480, 13483,
14038
\pdfhorigin 9243
\pdfinfo 9141
\pdflastannot 8716
\pdflastlink 8719, 12993, 13006
\pdflastmatch 4061
\pdflastobj 8713, 8784, 8799,
8805, 13057, 13378, 13387,
13397
\pdflastxform 8714, 12917, 12919
\pdflastximage 8715
\pdfinkmargin 8877, 8879
\pdfliteral 8857, 8859, 8864
\pdfm@box 9697, 13434, 13435,
13436, 13474, 13486, 13563,
13588, 13597, 13608, 13627,
13640, 13655, 13664, 13684,
13692, 13709, 13721
\pdfmajorversion 2643, 2644,
2647, 2648

\pdfmark 6795, 9634, 9643, 9673, 10889, 10909, 10948, 10983, 11000, 11034, 11071, 11083, 11114, 11123, 11154, 11178, 11454, 11469, 11484, 11496, 11503, 11530, 11561, 12021, 12030, 12061, 12484, 12493, 12525, 12614, 12631, 12659, 12681, 12707, 12731, 14438
 \pdfmark@ 11178, 11179
 \pdfmatch 325
 \pdfminorversion 8678
 \PDFNextPage 11467
 \PDFNextPage@ 11467, 11468
 \pdfobj 8770, 8785, 8800, 13035, 13344, 13379, 13388
 \pdfobjcompresslevel 8696, 8752
 \PDFOpen 11495
 \pdfoptionpdfminorversion 8677
 \pdfoutline 14484
 \pdfpageattr
 9182, 9186, 9187, 9197,
 9206, 9210, 9211, 9221
 \pdfpageheight 9253, 9262, 9270, 9275, 9284
 \pdfpageref 13095
 \pdfpagesresources 8833, 8834
 \pdfpagesattr 9072, 9074, 9076
 \pdfpagewidth 9249, 9258, 9269, 9274, 9283
 \PDFPreviousPage 11480
 \PDFPreviousPage@ 11481, 11483
 \pdfrefobj 13030, 13031, 13032
 \pdfrefxform 12919
 \pdfstartlink 8927, 8971, 9006,
 9040, 9300, 13129, 13215,
 13237, 13264, 13285, 13313,
 13336
 \pdfstrcmp 12952
 \pdfstringdef 491,
 784, 3706, 3712, 3718, 3724,
 3729, 3734, 3740, 3747,
 3753, 3833, 5721, 5726,
 5752, 6456, 6564, 6566,
 7902, 7938, 13842, 14207
 \pdfstringdefDisableCommands
 797, 899, 6347, 6449
 \pdfstringdefPostHook 780, 893
 \pdfstringdefPreHook 638, 893,
 905, 6448, 6460
 \pdfstringdefWarn 527, 528, 632,
 908, 1413, 1418, 1437, 1441
 \pdftexversion 13029
 \pdfvorigin 9244
 \pdfxform 12915
 \Peace 18834, 20331
 \peh 19650
 \penalty 1527, 2227, 4845
 \PencilRight 18841, 20334
 \PencilRightDown 18839, 20333
 \PencilRightUp 18843, 20335
 \pentagon 19313, 20539
 \perp 18982, 20400
 \phantom 583
 \phantomsection 4147, 6351,
 7981, 14143, 14194, 14574
 \Phi 19774
 \phi 19798
 \phiinferior 19811
 \Phone 18595, 20256
 \PhoneHandset 18825, 20327
 \Pi 19771
 \pi 19792
 \pinferior 19866
 \Pisces 18717, 20866
 \pisces 18715, 20294
 \pitchfork 18232, 20169
 \planck 15542, 20602
 \Plane 18829, 20329
 \Plus 18862, 20344
 \PlusCenterOpen 18866, 20346
 \plusinferior 19851
 \PlusOutline 18860, 20343
 \plussuperior 19835
 \PlusThinCenterOpen 18864,
 20345
 \Pluto 18681, 20854
 \pluto 18679, 20282
 \pm 20573
 \pointer 17720, 19952
 \PointingHand 18620, 20831
 \Pointinghand 18621, 20832
 \pounds 15251, 20587
 \Preamble 12274
 \prec 18023, 20083
 \precapprox 19258, 20516
 \preccurlyeq 18027, 20085
 \preceq 19234, 20504
 \preceqq 19246, 20510
 \precnapprox 19266, 20520
 \precneq 19242, 20508
 \precneqq 19254, 20514
 \precnsim 18274, 20188
 \precsim 18031, 20087
 \PrerenderUnicode 3697
 \prime 17319, 19820
 \process@me 6428, 6440, 6441,
 9071, 9080
 \ProcessKeyvalOptions 4216
 \prod 17762, 19971
 \prop 2296, 2300, 2308
 \proto 17788, 19982
 \protect 1525, 4955, 4989, 7581,
 7653, 7719, 7734, 7751,
 7807, 7814, 7815, 8019,
 8073, 8291, 8359, 8379,
 8385, 8396, 8410, 8528,
 9337, 9434, 10301, 10381,
 11870, 12157, 14214, 14508
 \protected 7244, 8024, 8025
 \protected@edef
 5120, 6530, 6624, 7267,
 7285, 7461, 7890, 7894,
 8903, 9896, 10435, 10518,
 11026
 \protected@file@percent 7971,
 8019
 \protected@write 2179, 5010,
 5317, 7787, 8230, 8245,
 8260, 8264, 8274, 14213
 \protected@xdef 7422, 7516
 \providecommand
 473, 4477, 4798, 4941,
 5304, 5363, 5365, 6380,
 6654, 6679, 6813, 6852,
 6854, 6856, 6859, 6860,
 6861, 6863, 6864, 6865,
 6866, 6868, 6869, 6870,
 6871, 6872, 6873, 6882,
 6883, 6884, 6885, 6886,
 6887, 7261, 7684, 7685,
 7700, 7971, 8591, 8592,
 8593, 8594, 8595, 8596,
 8597, 8598, 8599, 8600,
 8601, 8602, 8603, 8604,
 8605, 8606, 8607, 8608,
 8609, 8610, 8672, 8880,
 8898, 8899, 9325, 9428,
 9429, 9692, 9754, 9755,
 9756, 10227, 10343, 10373,
 10374, 10375, 10846, 11226,
 11227, 11587, 11595, 11596,
 11597, 11598, 11693, 11705,
 11706, 11707, 11708, 11760,
 11801, 11802, 11803, 11804,
 11967, 11969, 11970, 12082,
 12083, 12138, 12972, 12975,
 13781
 \psdaliasnames 20576, 20919

\psdmapshortnames 19704
 20575

\Psi 19775

\psi 19800

\PushButton 6144

\put@me@back 5267, 5280, 5290

\pwedge 16162, 20679

\pxfonts 19312

Q

\Q 1520, 13040

\qaf 19616

\quarternote 18739, 20295

\quotedblbase 14754, 14995,
 17300, 19410

\quotesinglbase 14764, 14997,
 17294, 19412

R

\r 14629, 14641, 14653, 14868,
 14934, 15046, 15091, 15120,
 15152, 15327, 15394, 15691,
 15693, 17239, 17241

\ra 19592

\Radiation 18624, 20833

\Radioactivity 18622, 20265

\raff 19636

\Rain 18805, 20320

\raise 2234, 5091, 9403, 9487,
 9525, 9565, 11291, 11939,
 12226

\rangle 18329, 20212

\rbrackdbl 20406

\rcurvearrowdown 19052, 20430

\rcurvearrowleft 19056, 20431

\rcurvearrowne 19036, 20425

\rcurvearrowright 19059, 20432

\rcurvearrowse 19045, 20428

\Re 17478, 19874

\ReadBookmarks
 4215, 4250, 4376, 4608,
 4720, 4722, 14373, 14405

\real@setref 8356, 8423

\realfootnote 7513

\Rectangle 18978, 20398

\RectangleBold 18980, 20399

\RectangleThin 18976, 20397

\recycle 18754, 20301

\Recycling 18756, 20873

\Ref 8441, 8450, 8458

\ref 626, 4368, 6293, 6294, 6366,
 6367, 7478, 7485, 8467,
 8475, 12249

\ref@one 4964, 4965

\refEFLINK 12250, 12251

\refstepcounter 6891, 6898, 6919,
 7122, 7148, 7174, 7199,
 7205, 7308, 7309, 7645

\rem@ptetc 10973, 10975

\renewcommand 2171, 8152, 8447,
 8454, 8463, 8472, 14289

\Request 18359, 20223

\RequirePackage 22, 232, 233,
 234, 235, 236, 237, 238, 239,
 240, 241, 242, 243, 244, 245,
 361, 923, 2598, 2683, 4193,
 4209, 4674, 4726, 4933,
 5366, 6333, 6470, 6720,
 8730, 10228, 12143, 14299

\RerunFileCheck 14301

\Reset 6153

\reset@font 8360, 8380, 8397,
 8529

\reve 15983, 19737

\reveject 16196, 20689

\revepsilon 15997, 19740

\revglotstop 16194, 19764

\Rewind 18564, 20243

\RewindToIndex 18371, 20228

\RHD 18555, 20240

\rhd 18171, 20144

\rho 19793

\rhoinferior 19810

\rhooknearrow 19027, 20421

\rhookrevespsilon 19741

\rhookswallow 19031, 20423

\Rightarrow 17682, 19936

\rightarrow 19886

\rightarrowtail 17596, 19903

\rightarrowtriangle 17727, 19955

\rightbarharpoon 19090, 20443

\RIGHTCIRCLE 18578, 20249

\rightharpoondown 17637, 19919

\rightharpoonup 17634, 19918

\rightleftarrows 17646, 19922

\rightleftharpoon 19063, 20434

\rightleftharpoons 17666, 19930

\rightModels 18154, 20788

\rightmodels 18143, 20786

\rightmoon 18647, 20274

\rightpointleft 18616, 20829

\rightrightarrowarrows 17658, 19927

\rightrightarrowharpoons 19078, 20439

\RightScissors 18819, 20880

\rightslice 19232, 20503

\rightsquigarrow 17707, 19947

\rightthreetimes 18206, 20158

\RightTorque 19049, 20888

\Righttorque 19050, 20889

\rightVdash 18146, 20787

\rightvdash 18122, 20779

\rinferior 19805

\riota 17491, 19876

\risingdoteq 20041

\risingdotseq 17930

\rlap 5088, 8858, 9863

\rm 571

\rmfamily 561

\Roman 6620

\roman 6621

\romannumeral 915, 916, 13040

\rotm 16064, 20655

\rotOmega 16155, 20677

\rotr 16100, 20665

\rotvara 15963, 20627

\rotw 16166, 20681

\roty 16170, 20683

\rrbracket 18997, 20887

\Rrightarrow 17703, 19945

\rrparenthesis 19105, 20449

\rtaild 19736

\rtimes 18202, 20156

\rule 7463

S

\S 15262, 20590

\sad 19600

\Sagittarius 18708, 20863

\sagittarius 18706, 20291

\Saturn 18672, 20851

\saturn 18670, 20279

\sbox 3693, 5071, 5103,
 6188, 9390, 9470, 9507,
 9547, 11226, 11265, 11926,
 12208, 12914

\scd 16912, 19802

\scdefault 4684

\scg 16018, 19743

\schwa 15986, 19738

\schwainferior 19860

\sci 16045, 19748

\ScissorHollowRight 18823,
 20326

\ScissorRight 18817, 20324

\ScissorRightBrokenBottom
 18813

\ScissorRightBrokenTop 18821,
 20325

\scn 16081, 19749

\Scorpio 18705, 20862

\scorpio 18703, 20290

\scr 16123, 19752

\scr@LT@array 7147
\scripta 15956, 19734
\scriptg 16015, 19742
\scriptsize 579
\scriptv 16157, 19757
\scrollmode .. 1463, 1472, 1485,
1592, 1725
\scshape 567
\scu 16930, 19803
\scy 16171, 19761
\Searrow 17697, 19942
\searrow 17572, 19892
\Sech 19372, 20555
\second 17321, 19821
\sectionautorefname 2963, 2981,
2999, 3017, 3035, 3053,
3071, 3100, 3129, 3147,
3165, 3183, 3201, 3219,
3237, 3255, 8603
\seen 19596
\selectfont 547, 4684, 13067
\SePa 19358, 20549
\set@display@protect 4310
\setbox 1528, 1534, 1540,
3427, 3433, 5075, 5088,
5948, 6478, 8848, 9836,
9853, 13474, 13563, 13597,
13627, 13655, 13684, 13709
\setcounter 4876
\setkeys 4851, 4896
\setlength 2231, 5059, 5960, 6764,
8875, 9243, 9244, 9249,
9253, 9258, 9262, 9269,
9270, 9274, 9275, 9283,
9284, 10347, 10348, 10352,
10353, 10361, 10362, 10701,
11685, 11752, 11846, 12130,
14527, 14595
\setminus 17778, 19978
\setpdfinkmargin .. 3887, 3888,
6762, 8873, 11683, 11750,
11844, 12128
\settowidth 12546, 13147, 13503
\SetupKeyvalOptions 2289, 4180
\seveninferior 19848
\sevensuperior 19832
\sffamily 562
\shadda 19646
\sharp 18752, 20300
\sheen 19598
\shortciteN 7850
\shuffle 19143, 20464
\Sigma 19772
\sigma 19795
\sim 17858, 20010
\simeq 17874, 20017
\sinferior 19867
\SixFlowerAlternate ... 18930,
20377
\SixFlowerAltPetal 18940, 20382
\SixFlowerOpenCenter . 18926,
20375
\SixFlowerPetalRemoved 18923,
20374
\sixinferior 19847
\SixStar 18913, 20369
\sixsuperior 19831
\SixteenStarLight 18921, 20373
\sixteenthnote ... 18746, 20297
\SKC 8585
\SKC@ref 8585
\SKC@ref 8582
\skip@ .. 1542, 1625, 1626, 1629,
1631, 2254, 2260, 2273,
2279
\slashc 15947, 19733
\slashdiv 19319, 20542
\slide 7913
\SliTeX 539
\slshape 568
\small 580
\smallin 17752, 19967
\smallowns 17760, 19970
\smash 2228
\smile 18323, 20209
\Smiley 18639, 20838
\smiley 18637, 20270
\Snowflake 18944, 20384
\SnowflakeChevron 18942, 20383
\SnowflakeChevronBold . 18946,
20385
\sofpasuq 16845
\softsign 16486, 20700
\spacefactor
.. 2207, 2213, 7381, 7390,
7542, 7544, 8883, 8891
\spadesuit . 18718, 18720, 20867
\Sparkle 18948, 20386
\SparkleBold 18950, 20387
\special@paper 4148
\SpecialDvipdfmxOutlineOpen
.. 2741, 2743, 4576, 4583
\sphericalangle .. 17797, 19986
\splitmaxdepth 7456
\splittopskip 7455
\sqcap 18083, 20113
\sqcup 18085, 20114
\sqdoublecap 19170, 20476
\sqdoublecup 19175, 20478
\sqsubset 18067, 20105
\sqsubseteqeq 18075, 20109
\sqsubsetneq 18264, 20184
\sqsupset 18071, 20107
\sqsupseteq 18079, 20111
\sqsupsetneq 18267, 20185
\SquareCastShadowBottomRight
..... 18969, 20394
\SquareCastShadowTopRight ..
..... 18972, 20395
\Squaredot 15298, 20593
\squaredots 17851, 20007
\SquareShadowBottomRight ..
..... 18963, 20392
\SquareShadowTopRight . 18966
\SquareTopRight 20393
\SS 14993, 19396
\ss .. 3010, 14922, 15008, 15382
\sslash 19310, 20538
\st@rredfalse 7182, 7191
\star 18192, 20152
\stepcounter . 6908, 7284, 7382,
7515, 14210
\stockheight . 4152, 4382, 9268,
9270, 10202, 10203, 10346,
10347, 11660, 11661
\stockwidth .. 4381, 9267, 9269,
9280, 10201, 10203, 10212,
10345, 10348, 10358, 11659,
11661, 11670
\stop@hyper 6315
\StringEncodingConvertTest 759,
769
\strip@period 2184
\strip@prefix 62, 2177, 4061, 6430,
7060, 7270, 14434, 14442,
14457
\strip@pt 470, 4164, 5977,
6765, 9249, 9253, 9258,
9262, 10704, 11687, 11754,
11848, 12132, 13933, 13998,
14027, 14067, 14118
\strip@pt@and@otherjunk 10908,
10940, 10975
\strutbox 7456
\sub@label 2171
\subeqnarray 7250, 7252
\subequations 7282, 7283
\subfig@oldlabel 2173
\Submit 6150
\SubmitObject 13287
\SubmitPOject 13287

\subparagraphautorefname
 .. 2967, 2985, 3003, 3021,
 3039, 3057, 3075, 3108,
 3110, 3133, 3151, 3169,
 3187, 3205, 3223, 3241,
 3259, 3260, 3267

\subpdfbookmark 14277

\subsection 11963

\subsectionautorefname 2964,
 2982, 3000, 3018, 3036,
 3054, 3072, 3105, 3130,
 3148, 3166, 3184, 3202,
 3220, 3238, 3256, 3604

\Subset 18218, 20163

\subset 18043, 20093

\subsetneq 18051, 20097

\subsetneqq 19270, 20522

\subsetneq 18059, 20101

\subsubsectionautorefname 2965,
 2983, 3001, 3019, 3037,
 3055, 3073, 3106, 3131,
 3149, 3167, 3185, 3203,
 3221, 3239, 3257, 3605

\succ 18025, 20084

\succapprox 19262, 20518

\succcurlyeq 18029, 20086

\succceq 19238, 20506

\succceqq 19250, 20512

\succcapprox 19268, 20521

\succcneq 19244, 20509

\succcneqq 19256, 20515

\succcnsm 18276, 20189

\succcsim 18035, 20089

\sukun 19648

\sum 17766, 19973

\Sun 18644, 20839

\sun 18642, 20272

\SunCloud 20319

\SunshineOpenCircled 18938,
 20381

\Supset 18222, 20165

\supset 18045, 20094

\supseteq 18053, 20098

\supseteqq 19274, 20524

\supsetneq 18061, 20102

\surd 19981

\Swallow 17699, 19943

\swallow 17575, 19893

T

\T 19576

\t 14661, 15081, 15110, 15139,
 15157

\T@pageref 8449, 8456, 8465,
 8474

\T@Ref 4698

\Ta 19604

\taa 19578

\tableautorefname 2959, 2977,
 2995, 3013, 3031, 3049,
 3067, 3097, 3125, 3143,
 3161, 3179, 3197, 3215,
 3233, 3251, 3599

\tagform@ 8111

\taild 15977, 20632

\tailinvr 16108, 20667

\taill 16057, 20652

\tailn 16080, 20661

\tailr 16114, 20669

\tails 16130, 20672

\tailt 16148, 20675

\tailz 16176, 20684

\Tape 18827, 20328

\tatweel 19612

\tau 19796

\Taurus 18687, 20856

\taurus 18685, 20284

\tcheh 19652

\Telefon 18597, 20824

\temp@online 8006, 8009

\Tent 18811, 20323

\tesh 16248, 20697

\TeX 529, 530, 537, 539, 12277,
 12279, 12281

\texorpdfstring 886, 6348

\text 480, 486

\textAcht 19371, 20554

\textAcPa 19357, 20548

\textacute 14625, 14637, 14649,
 14833, 15087, 15116, 15288

\textacutedbl 16296

\textacutemacron 15084, 15113,
 15142, 17018, 17021, 17122,
 17125

\textainferior 17408, 19856

\textaleph 17502, 19878

\textalpha 3177, 3178, 3179,
 3181, 3182, 3183, 3184,
 3185, 3186, 3187, 3188,
 3189, 3190, 19680, 19777

\textamalg 17765, 19972

\textampersand 519, 14696,
 15176, 15177, 15178, 20582,
 20583

\textangle 17794, 19984

\textangstrom 17494

\textAnkh 18628, 20267

\textaolig 19339, 19341, 20913

\textAPLbox 18366, 20226

\textAPLdownarrowbox 18355,
 20221

\textAPLinput 18358, 20222

\textAPLinv 18332, 20213

\textAPLleftarrowbox 18347,
 20218

\textAPLrightarrowbox 18350,
 20219

\textAPLuparrowbox 18352,
 20220

\textapprox 17884, 20021

\textapproxeq 17889, 20023

\textaquarius 18713, 18714,
 20293, 20865

\textaries 18683, 18684, 20283,
 20855

\textasciacute 15289

\textasciibreve 14672, 15095,
 15124, 16285

\textasciicaron 14630, 14642,
 14654, 14674, 15092, 15121,
 16271

\textasciicircum 14626, 14638,
 14650, 14712, 15088, 15117,
 15226

\textasciidieresis 14628, 14640,
 14652, 14809, 15090, 15119,
 15264

\textasciigrave 14624, 14636,
 14648, 14717, 15086, 15115,
 15231

\textasciimacron 14633, 14645,
 14657, 14823, 15099, 15128,
 15278

\textasciitilde 520, 4761, 14727,
 15243

\textast 17781, 19979

\textAsterisk 18929, 20376

\textAsteriskBold 18906, 20365

\textasteriskcentered 15186

\textAsteriskCenterOpen 18908,
 20366

\textAsteriskRoundedEnds
 18953, 20388

\textasymp 17902, 20029

\textbabygamma 16026, 19745

\textbackcong 17898, 20027

\textbackneg 18304, 20200

\textbackprime 17326, 19823

\textbacksim 17862, 20011

\textbacksimeq 18209, 20159

\textbackslash 515, 693, 2037,
14708, 14710, 15224

\textbaht 16909

\textbar . 14723, 15238, 15239,
20585

\textbarb 15730, 20606

\textbarc 15951, 20623

\textbard 15494, 20598

\textbardbl 17287, 17288, 20710

\textbardotlessj . . . 16008, 16009,
16010, 20639

\textbarglotstop . 16230, 16231

\textbari . 16039, 16040, 16041,
19746, 20648

\textbarin 18300, 20198

\textbarl . 15753, 15754, 19731

\textbarleftharpoon 19088, 20442

\textbaro 16085, 16087

\textbarp 16954, 19814

\textbarrevglotstop 16234, 16235

\textbarrightharpoon . . . 19094,
20444

\textbarsci 16952, 19813

\textbarscu 16957, 19815

\textbaru . 16150, 16151, 16152,
19755, 20676

\textbarwedge 18191, 20151

\textbbslash 18378, 18379,
20229, 20812

\textBeam 18362, 20224

\textbecause 17847, 17848,
20005, 20752

\textbeltl . 16051, 16052, 16053,
20651

\textBeta 16317

\textbeta . . . 15008, 19681, 19778

\textbetainferior . 16941, 19808

\textbeth 17504, 19879

\textbetween 17995, 20070

\textbf 554

\textBicycle 19391, 20563

\textbigcircle 15112, 15141,
18586, 18587, 20252, 20823

\textbigdoublevee 19150, 20467

\textbigdoublewedge 19148,
20466

\textbigtriangledown 18562,
18563, 20242, 20821

\textbigtriangleup 18547, 18548,
18549, 20237, 20818, 20819

\textBiohazard 18626, 20266

\textblacksmiley 18641, 20271

\textblank 18374

\textbot 18135, 18136, 20132,
20783

\textbowtie 18197, 18198, 20154,
20800

\textboxast 19134, 20459

\textboxbackslash 18344, 20217

\textboxbar 18584, 20251

\textboxbox 19138, 20461

\textboxbslash 19132, 20458

\textboxcircle 19136, 20460

\textboxdot 18119, 20126

\textboxempty 18599, 18600,
20257, 20825

\textboxminus 18115, 20124

\textboxplus 18113, 20123

\textboxslash 19130, 20457

\textboxtimes 18117, 20125

\textbraceleft . 513, 2038, 14721,
15236

\textbraceright . 514, 2038, 14725,
15241

\textbrokenbar 14805, 15257,
15258, 20588

\textbullet 14729, 17309, 19818

\textbulletoperator 17785

\textbullseye 16205, 16206,
16207, 16208, 20692, 20693

\textBumpeq 17907, 20031

\textbumpeq 17911, 20033

\textcancer 18692, 18693, 20286,
20858

\textCap 18227, 18228, 20167,
20803

\textcap 17823, 19995

\textcapdot 19174, 20477

\textcapricornus 18710, 18711,
20292, 20864

\textccnc 19400, 20566

\textccnd 19402

\textccsa 19404, 20567

\textcdj 16219

\textcdot 15007, 19422, 20574

\textcdots 18294, 20195

\textcedilla 14632, 14644, 14656,
14841, 15094, 15123, 15300

\textcelsius 14994, 17464

\textcent 14797, 15247

\textcentoldstyle 15949, 20622

\textCESign 19408, 19409,
20569, 20918

\textCheckedbox 18602, 18603,
20258, 20826

\textCheckmark 18850, 18851,
20338, 20884

\textCheckmarkBold 18853,
20339

\textChi 19677

\textchi 3178, 19701, 19799

\textchiinferior 16949, 19812

\textcirc 17783, 19980

\textcirceq 17943, 20047

\textcirclearrowleft 19000, 20407

\textcirclearrowright 19002,
20408

\textcircled 15083, 15112, 15141,
18381, 18383, 18385, 18387,
18389, 18391, 18393, 18395,
18397, 18399, 18401, 18403,
18405, 18407, 18409, 18411,
18413, 18415, 18417, 18419,
18421, 18426, 18428, 18430,
18432, 18434, 18440, 18442,
18444, 18446, 18448, 18450,
18452, 18454, 18456, 18458,
18464, 18466, 18468, 18470,
18472, 18474, 18476, 18478,
18480, 18482, 18484, 18486,
18488, 18490, 18492, 18494,
18496, 18498, 18500, 18502,
18504, 18506, 18508, 18510,
18512, 18514, 18516, 18518,
18520, 18522, 18524, 18526,
18528, 18530, 18532, 18534,
18536

\textCircledA 18423, 18424,
20230, 20813

\textcircledast 18107, 18108,
18109, 20121, 20777, 20778

\textcircledcirc 18103, 18104,
18105, 20120, 20775, 20776

\textcircleddash 18111, 20122

\textcircledP 17474

\textCircleShadow 18961, 20391

\textcircplus 19157, 20470

\textcircumflex 14676

\textcircumlow 15105, 15134,
19345

\textCleaningF 18436, 20231

\textCleaningFF 18438, 20232

\textCleaningP 18460, 20233

\textCleaningPP 18462, 20234

\textclock 18310, 18311, 18312,
20203, 20809, 20810

\textcloseepsilon 16212, 16213

\textcloseomega 16091, 16092,
16093, 16094, 20662, 20663

\textcloserevepsilon 16004,
16005, 16006, 20638

\textCloud 18590, 20253
 \textClowerTips 18886, 20355
 \textclubsuitblack 2159, 18729,
 18730, 20871
 \textclubsuitwhite 18738
 \textCoffeecup 18609, 20260
 \textcoloncolonequals 19194,
 20485
 \textcolonequals 17935, 20043
 \textcolonmonetary 17434
 \textcolor 592, 13025, 13072,
 13075, 13406
 \textcommatailz 15917, 15918
 \textcomplement 17734, 19958
 \textcompwordmark 17281
 \textcong 17879, 20019
 \textcopyleft 19397, 19398
 \textcopyright 14811, 15266,
 19721
 \textcorner 16305, 16306
 \textCR 14670, 15164
 \textcrb 15726, 15727, 15728,
 15730, 15731, 20605, 20606,
 20607
 \textcrd 15489, 15491, 15492,
 15494, 15495, 20597, 20598,
 20599
 \textcrg 15819, 20619
 \textcrh 15540, 20600
 \textcrinvglotstop 15780, 15781
 \textcrlambda 15757, 15758,
 15759, 15760, 15761, 15762,
 20611, 20612, 20613, 20614
 \textCross 18869, 20347
 \textCrossedbox 18605, 18606,
 18607, 20259, 20827, 20828
 \textCrossMaltese 18875, 20350
 \textCrossOpenShadow 18871,
 20348
 \textCrossOutline 18873, 20349
 \textcrtwo 15777, 15778
 \textctc 15972, 15973, 15974,
 20631
 \textctd 15915, 15916
 \textctesh 16139, 16140, 16141,
 20673
 \textctj 16220, 16221, 20694
 \textctjvar 16221, 20694
 \textctn 15935, 15936
 \textctt 15937, 15938
 \textctyogh 16184, 16185, 16186,
 20686
 \textctz 16177, 16178, 16179,
 20685
 \textCup 18230, 18231, 20168,
 20804
 \textcup 17825, 19996
 \textcupdot 18064, 20103
 \textcupplus 18066, 20104
 \textcurlyeqprec 18249, 20176
 \textcurlyeqsucc 18253, 20178
 \textcurlyvee 18213, 18214,
 20161, 20801
 \textcurlywedge 18216, 18217,
 20162, 20802
 \textcurrency 14801, 15253
 \textcurvearrowleft 17618, 19912
 \textcurvearrowright 17620,
 19913
 \textCuttingLine 18538, 18539,
 18540, 18541, 20235, 20814,
 20815, 20816
 \textdagger 14731, 17302, 17303,
 19817, 20711
 \textdaggerdbl 14733, 17305,
 17306, 17307, 20712, 20713
 \textdaleth 17508, 19881
 \textdanger 18780, 20312
 \textdasheddownarrow 17719,
 19951
 \textdasheduparrow 17714, 19949
 \textdashleftarrow 17711, 17712,
 19948, 20738
 \textdashrightarrow 17716,
 17717, 19950, 20739
 \textDashV 19292, 19293, 20530,
 20907
 \textDashv 19285, 19286, 20528,
 20905
 \textdashV 19279, 19280, 20526,
 20903
 \textdashv 18124, 18125, 20128,
 20780
 \textDavidStar 18877, 18878,
 20351, 20885
 \textdblig 15941, 15943, 20620
 \textdctzlig 16242, 16243
 \textddagger 14734
 \textddots 18298, 20197
 \textdegree 14825, 14994, 15280
 \textDeleatur 17457, 17458,
 19869, 20724
 \textDelta 19669, 19767
 \textdelta 3190, 19683, 19780
 \textDiamandSolid 18975, 20396
 \textdiameter 18302, 20199
 \textdiamond 18572, 18573,
 20246, 20822
 \textdiamondddots 17348, 19826
 \textdiamondsuitblack 2160,
 18736
 \textdiamondsuitwhite 18726,
 18727, 20870
 \textdigammagreek 20698
 \textdiscount 17342
 \textdiv 15005, 19420, 20572
 \textdivide 14974, 15005, 15435,
 19420
 \textdivideontimes 18195, 20153
 \textDivides 17775, 19976
 \textDividesNot 17777, 19977
 \textdivorced 18794
 \textdlsh 17615, 19911
 \textdollar 517, 14692, 15170,
 15171, 15172, 20580, 20581
 \textdong 17444
 \textdotaccent 14631, 14643,
 14655, 14678, 15093, 15122,
 16287
 \textdotbelow 14635, 14647,
 14659, 14702, 15109, 15138,
 16312
 \textdotdiv 17855, 20753
 \textdoteq 17915, 20035
 \textdoteqdot 17920, 17921,
 20037, 20759
 \textdotminus 17854, 17855,
 20008, 20753
 \textdotplus 17773, 19975
 \textdottimes 19162, 20472
 \textdoublebarpipe 15793, 15794,
 15795, 20618
 \textdoublebarpipevar 15795,
 20618
 \textdoublebarwedge 19185,
 20481
 \textdoublegrave 15097, 15126,
 16308
 \textdoublepipe 15789, 15790,
 15791, 20617
 \textdoublepipevar 15791, 20617
 \textdoublevee 19181, 19182,
 20480, 20902
 \textdoublevertline 17288, 20710
 \textdoublewedge 19179, 20479
 \textDOWNarrow 18558, 18559,
 20241, 20820
 \textDownarrow 17686, 19937
 \textdownarrow 17560, 17561,
 17562, 19887, 20732, 20733
 \textdowndownarrows 17661,
 19928

\textdownarrowdownharpoons 19082, 20440
\textdownharpoonleft 17644, 19921
\textdownharpoonright 17641, 19920
\textdownmodels 19298, 20532
\textdownstep 19328, 19329
\textdownuparrows 17724, 19953
\textdownupharpoons 19100, 20446
\textdsbiological 18774, 20309
\textdscchemical 18772, 20308
\textdcommercial 18776, 20310
\textdsjuridical 18770, 20307
\textdsmedical 18768, 20306
\textdsmilitary 18765, 18766, 20305, 20875
\textdtimes 19165, 20473
\textdyoghlig 16239, 16240
\textdzlig 16236, 16237, 16238, 20696
\textearth 18660, 18661, 20276, 20846
\textEightAsterisk 18959, 20390
\textEightFlowerPetal 18937, 20380
\textEightFlowerPetalRemoved 18956, 20389
\texteightinferior 17394, 19849
\textEightStar 18916, 20370
\textEightStarBold 18918, 20371
\textEightStarConvex 18912, 20368
\textEightStarTaper 18910, 20367
\texteightsuperior 17362, 19833
\texteinferior 17410, 19857
\textell 17470, 19872
\textellipsis 523, 524, 14736, 17313, 17314, 20714
\textemdash 727, 14738, 17285
\textemptyset 17742, 17743, 19962, 20740
\textEncodingNoboundary 526, 19664
\textendash 728, 14740, 17283
\textEnvelope 18832, 18833, 20330, 20882
\textEpsilon 3175
\textepsilon 3176, 3177, 3180, 3182, 3183, 3184, 3185, 3189, 3190, 19684, 19781
\texteqcirc 17939, 20045
\texteqcolon 17857, 20009
\texteqdot 19190, 20483
\texteqsim 17871, 20015
\texteqslantgr 19229, 20501
\texteqslantless 19227, 20500
\texteqqualscolon 17937, 20044
\texteqqualsinferior 17402, 19853
\texteqqualsuperior 17370, 19837
\textequiv 17959, 17960, 20054, 20763
\textEversed 15739
\textesh 16131, 16132, 19754
\textestimated 17496, 17497, 17498, 20726, 20727
\texteta 3175, 3176, 3178, 3181, 3183, 3184, 3185, 3188, 3189, 19686, 19783
\texteuro 14793, 17446, 17447, 17448, 17449, 17450, 17451, 17452, 17453, 17454, 17455, 20715, 20716, 20717, 20718, 20719, 20720, 20721, 20722, 20723
\textexclamdown 731, 14795, 15245
\textexists 17738, 19960
\textfallingdoteq 17926, 20039
\textfatsemi 19155, 20469
\textFax 19386, 19387, 20561, 20917
\textfax 17510, 19882
\textfemale 18654, 20841
\textFemaleFemale 18782, 20313
\textFemaleMale 18786, 20315
\textfi 729, 14768, 19347
\TextField 6135
\textFinv 17500, 19877
\textFire 19389, 20562
\textfishhookr 16116, 16117, 16118, 16119, 20670, 20671
\textfivedots 19324, 20543
\textfiveeighths 17544
\textFiveFlowerOpen 18935, 20379
\textFiveFlowerPetal 18933, 20378
\textfiveinferior 17388, 19846
\textfivesixths 17538
\textFiveStar 18592, 20254
\textFiveStarCenterOpen 18894, 20359
\textFiveStarConvex 18902, 20363
\textFiveStarOpen 18594, 20255
\textFiveStarOpenCircled 18892, 20358
\textFiveStarOpenDotted 18896, 20360
\textFiveStarOutline 18898, 20361
\textFiveStarOutlineHeavy 18900, 20362
\textFiveStarShadow 18904, 20364
\textfivesuperior 17356, 19830
\textfl 730, 14770, 19349
\textFlag 18760, 18761, 20303, 20874
\textflat 18749, 20298
\textflorin 14742, 15742, 15743, 20608
\textflq 616, 15001, 19416
\textflqq 614, 14999, 19414
\textforall 17732, 19957
\textForward 18551, 20238
\textForwardToIndex 18369, 20227
\textFourAsterisk 18880, 20352
\textfourfifths 17534
\textfourinferior 17386, 19845
\textFourStar 18888, 20356
\textFourStarOpen 18890, 20357
\textfoursuperior 17354, 19829
\textfourth 17346, 19825
\textfractionsolidus 14744, 17336
\textfrown 18322, 20208
\textfrownie 18635, 18636, 20269, 20837
\textfrq 617, 15002, 19417
\textfrqq 615, 15000, 19415
\textfullnote 19363, 19364, 20551, 20914
\textGame 17512, 19883
\textGamma 19668, 19766
\textgamma 3186, 3187, 3188, 19682, 19779
\textgammainferior 16943, 19809
\textGaPa 19351, 20545
\textge 17972, 20059
\textgemini 18689, 18690, 20285, 20857
\textGentsroom 19393, 20564
\textgeq 17971, 17973, 20058, 20767
\textgeqq 17979, 20062
\textgeqlant 19200, 20488
\textgg 17991, 20068
\textggg 18241, 20173

\textgimel 17506, 19880
\textglobfall 17574, 20735
\textglobrise 17571, 20734
\textglotstop 16188, 16189, 16190, 16191, 19763, 20687, 20688
\textglq 612, 14997, 19412
\textglqq 610, 14995, 19410
\textgnapprox 19219, 20497
\textgneq 19215, 20495
\textgneqq 17985, 20065
\textgnsim 18273, 20187
\textgravedbl 16300
\textgravemacron 15085, 15114, 15143, 17012, 17015, 17116, 17119
\textgreater 14706, 15220
\textgrq 613, 14998, 19413
\textgrqq 611, 14996, 19411
\textGslash 15816
\textgslash 15818, 15819, 20619
\textgrapprox 19208, 20492
\textgrdot 18237, 20171
\textgtreqless ... 18247, 20175
\textgtreqqless ... 19225, 20499
\textgtreqless ... 18018, 20080
\textgrsim 18009, 18010, 20076, 20769
\textguarani 17462
\texthalflength .. 16282, 16283
\texthalfnote 19366, 19367, 20552, 20915
\textHandCuffLeft 18611, 20261
\textHandCuffRight ... 18613, 20262
\textHandLeft ... 18615, 18616, 20263, 20829
\textHandRight .. 18618, 18619, 18620, 18621, 20264, 20830, 20831, 20832
\textHaPa 19353, 20546
\texthateq 17947, 17948, 17949, 20049, 20760, 20761
\texthausaB 15733, 19728
\texthausaD 15737, 19729
\texthausaK 15748, 19730
\texthbar . 15539, 15540, 15541, 15542, 19727, 20600, 20601, 20602
\texthdotfor 17311, 19819
\textheartsuitblack 2161, 18734
\textheartsuitwhite 18722, 18723, 18724, 20868, 20869
\textheng . 19330, 19332, 20910
\textHermaphrodite ... 18788, 20316
\texthexagon 18364, 20225
\texthexstar 18799, 20318
\textthinferior 17418, 19861
\texthookleftarrow 17601, 19905
\texthookrightarrow ... 17603, 19906
\textHslash 15537
\texthslash 17466, 19870
\textHT 14666, 15160
\texthtb . 15964, 15965, 15966, 15967, 20628, 20629
\texthtbardotlessj 16134, 16135
\texthtc 15734, 15735
\texthtd . 15978, 15979, 15980, 15981, 20633, 20634
\texthtg .. 16011, 16012, 16013, 20640
\texthth . 16031, 16032, 16033, 16034, 20645, 20646
\texthtcheng 16035, 16036, 16037, 20647
\texthtk . 15749, 15750, 15751, 20610
\texthtp 15767, 15768
\texthtq 16227, 16228
\texthttaild 16961, 16962, 19816
\texthtscg 16215, 16216
\texthtt 15772, 15773
\texthungarumlaut 14680, 15100, 15129, 16295
\texthvlig 15744, 15745, 15746, 20609
\textiiint 17832, 19999
\textiiinferior 16933, 19804
\textiiint 17830, 19998
\textIm 17468, 19871
\textin 17749, 19965
\textInfo 19406, 20568
\textinfty 17792, 19983
\textint .. 17827, 17828, 19997, 20750
\textinterleave ... 19309, 20537
\textinterrobang 17334
\textinterrobangdown .. 19321, 19322
\textinvamp 17514, 17515, 17516, 20728, 20729
\textinvbackneg .. 18308, 20202
\textinvbreve 15059, 15102, 15131, 15866, 15868, 15879, 15881, 15882, 15892, 15894, 15908, 15910
\textinvdiameter . 19108, 20450
\textinve 15814, 19732
\textinvglstop .. 16198, 16199, 19765
\textinvneg 19169, 20475
\textinvscr . 16126, 16127, 19753
\textiota 3175, 3176, 3177, 3179, 3182, 3190, 19688, 19785
\textipagamma .. 16022, 16023, 19744, 20642
\textisuperior ... 17352, 19828
\textit 556
\textJackStar ... 18882, 20353
\textJackStarBold 18884, 20354
\textjinferior 19318, 20541
\textJoin 19153, 20468
\textjupiter 18668, 18669, 20278, 20850
\textkappa ... 3177, 3179, 3182, 19689, 19786
\textKeyboard ... 18326, 20210
\textkinferior 17420, 19862
\textkra 15581
\textLadiesroom . 19395, 20565
\textLambda 19671, 19769
\textlambda 3182, 3190, 19690, 19787
\textlangle 18328, 20211
\textlatin 602, 7048
\textlbrackdbl ... 18993, 18994, 20405, 20886
\textlcurvearrowdown .. 19048, 19049, 19050, 20429, 20888, 20889
\textlcurvearrowse 19040, 20426
\textlcurvearrowsw 19043, 20427
\textle 17967, 20057
\textleadsto 19034, 20424
\textLeftarrow ... 17678, 19934
\textleftarrow ... 17552, 19884
\textleftarrowtail . 17595, 19902
\textleftarrowtriangle .. 17726, 19954
\textleftbarharpoon 19085, 20441
\textLEFTCIRCLE 18577, 20248
\textleftharpoondown .. 17626, 19915
\textleftharpoonup 17623, 19914
\textleftleftarrows 17655, 19925
\textleftleftharpoons ... 19073, 20437
\textleftmoon ... 18646, 20273
\textLeftrightarrow 17689, 19938

\textleftarrowrightarrow . 2164, 17564,
19888
\textleftarrowrightarrows 17653, 19924
\textleftarrowrightarrowtriangle 17730,
19956
\textleftarrowightharpoon . . . 19062,
20433
\textleftarrowightharpoons . . . 17664,
19929
\textleftslice 19231, 20502
\textleftspoon . . . 18991, 20404
\textleftsquigarrow 17706, 19946
\textlefttherefore . . . 17344, 19824
\textleftthreetimes 18205, 20157
\textlengthmark . . . 16279, 16280
\textleo . . . 18695, 18696, 20287,
20859
\textleq 17966, 17968, 20056,
20766
\textleqq 17975, 20060
\textleqlant 19196, 20486
\textless 14704, 15218
\textlessapprox 19204, 20490
\textlessdot 18235, 20170
\textlesseqgtr 18244, 20174
\textlesseqqgtr 19222, 20498
\textlessgtr 18016, 20079
\textlesssim 18006, 18007, 20075,
20768
\textLF 14668, 15162
\textLHD 18570, 20245
\textlhd 18169, 18170, 20143,
20794
\textlhookfour 19333, 19335,
20911
\textlhooknarrow 19026, 20420
\textlhooksearrow 19030, 20422
\textlhookt 15770, 15771
\textlhtlongi 16121, 16122
\textlhtlongy 16253, 16254
\textlibra 18701, 18702, 20289,
20861
\textlightning 17611, 17612,
19910, 20736
\textlinferior 17422, 19863
\textlira 17436
\textll 17987, 20066
\textllcorner 18318, 20206
\textLleftarrow 17702, 19944
\textlll 18239, 20172
\textllparenthesis 19104, 20448
\textlnapprox 19217, 20496
\textlneq 19212, 20494
\textlneqq 17983, 20064
\textlnot 14819, 15274
\textlnsim 18271, 20186
\textlogicalnot 14818, 15003,
15273, 19418
\textLongleftarrow 19010, 20412
\textlongleftarrow 19004, 20409
\textLongleftrightarrow . . . 19014,
20414
\textlongleftrightarrow 19008,
20411
\textlonglegr 16109, 16110,
16111, 19751, 20668
\textLongmapsfrom 19018, 20416
\textLongmapsto 19020, 20417
\textlongmapsto 19016, 20415
\textLongrightarrow 19012,
20413
\textlongrightarrow 19006, 20410
\textlongs 15725, 17243
\textlooparrowleft 17605, 19907
\textlooparrowright 17607, 19908
\textlozenge 18575, 20247
\textlptr 16265, 16266
\textlquill 17338
\textlrcorner 18320, 20207
\textltailm 16069, 16070, 16071,
16072, 20657, 20658
\textltailn 16073, 16074, 16075,
16076, 20659, 20660
\textltilde 16048, 16049, 16050,
20650
\textltimes 18200, 20155
\textlyoghlig 16058, 16059,
16060, 20653
\textmacronbelow 14634, 14646,
14658, 14715, 15108, 15137,
16314
\textmale 18663, 18664, 18665,
18666, 20277, 20847, 20848,
20849
\textMaleMale 18784, 20314
\textManFace 19381, 20559
\textmanstar 18778, 20311
\textmapsto 17599, 19904
\textmarried 18792
\textmd 555
\textmeasuredangle 17796, 19985
\textmercury 18650, 18651,
20275, 20840
\textmho 17489, 17490, 19875,
20725
\textmid 17803, 19987
\textMineSign 18763, 20304
\textmininferior 17424, 19864
\textminus 14750, 17769
\textminusdot 19159, 19160,
20471, 20899
\textminusinferior 17400, 19852
\textminussuperior 17368, 19836
\textmoo 19102, 20447
\textMoon 19379, 20558
\textMountain 18810, 20322
\textmp 17771, 19974
\textMu 3180
\textmu 3176, 3177, 3178, 3181,
3188, 3189, 14835, 15291,
19788
\textmu_greek 19691, 19789
\textmultimap 18187, 20149
\textmultimapboth 19142, 20463
\textmultimapdotbothA 18183,
20147
\textmultimapdotbothB 18185,
20148
\textmultiply 14905, 15004,
15363, 15364, 15365, 19419,
20594, 20595
\textMundus 19377, 20557
\textmusicalnote 18741, 18742,
18743, 20872
\textMVAt 15222, 19720
\textMVComma 15190, 19706
\textMVDivision 15196, 19709
\textMVEight 15214, 19718
\textMVFive 15208, 19715
\textMVFour 15206, 19714
\textMVMinus 15192, 19707
\textMVNine 15216, 19719
\textMVOne 15200, 19711
\textMVPPeriod 15194, 19708
\textMVPlus 15188, 19705
\textMVSSeven 15212, 19717
\textMVSix 15210, 19716
\textMVThree 15204, 19713
\textMVTtwo 15202, 19712
\textMVZero 15198, 19710
\textnabla 17747, 19964
\textnaira 17438
\textnapostrophe 15615
\textnapprox 17886, 17887,
20022, 20756
\textnapproxeq 17891, 20024
\textnasymp 17904, 17905,
20030, 20758
\textnatural 18751, 20299
\textnbackcong 17900, 20028
\textnbacksim 17864, 20012
\textnbacksimeq 18211, 20160

\textnBumpeq . . .	17909, 20032	\textnineinferior . . .	17396, 19850	\textnsubseteqq . . .	19273, 20523
\textnbumpeq . . .	17913, 20034	\textninesuperior . . .	17364, 19834	\textnsucc	18042, 20092
\textncirceq	17945, 20048	\textninferior	17426, 19865	\textnsuccapprox . . .	19265, 20519
\textncong	17882, 20020	\textniph	16096, 19750	\textnsuccurlyeq . . .	18259, 20181
\textncurlyeqprec	18251, 20177	\textniupsilon	16154, 16155, 19756, 20677	\textnsuccceq	19241, 20507
\textncurlyeqsucc	18255, 20179	\textnLeftarrow	17670, 19931	\textnsuccceqq	19253, 20513
\textnDashV	19295, 19296, 20531, 20908	\textnleftrarrow	17578, 19894	\textnsuccsim	18038, 20090
\textnDashv	19288, 19289, 20529, 20906	\textnLeftrightarrow	17672, 19932	\textnsuperior	17376, 19840
\textndashV	19282, 19283, 20527, 20904	\textnleftrightarrow	17609, 19909	\textnSupset	18225, 20166
\textndashv	18127, 18128, 20129, 20781	\textnleq	18002, 20073	\textnSupset	18050, 20096
\textnDoteq	17923, 20038	\textnleqq	17977, 20061	\textnsupseteq	18058, 20100
\textndoteq	17917, 20036	\textnleqslant	19198, 20487	\textnsupseteqq	19277, 20525
\textndownmodels	19300, 20533	\textnless	17997, 20071	\textntriangleleft . . .	18279, 18280, 20190, 20807
\textndownvdash . . .	18133, 20131	\textnlessapprox	19206, 20491	\textntrianglelefteq . . .	18286, 20192
\textne	17956, 20053	\textnlessgtr	18022, 20082	\textntriangleright . . .	18282, 18283, 20191, 20808
\textNearrow	17696, 19941	\textnlesssim	18012, 20077	\textntrianglerighteq . . .	18289, 18290, 20193
\textnearrow	17570, 17571, 19891, 20734	\textnll	17989, 20067	\textntriplesim . . .	17896, 20026
\textneg . . .	15003, 19418, 20570	\textnmid	17805, 17806, 19988, 20747	\textntwoheadleftarrow . . .	17584, 19897
\textneptune	18677, 18678, 20281, 20853	\textNoChemicalCleaning	19122, 20454	\textntwoheadrightarrow . . .	17591, 19900
\textneq	17955, 17957, 20052, 20762	\textnormal	550	\textnu	3177, 3179, 3183, 3184, 3185, 19692, 19790
\textneqcirc	17941, 20046	\textnotbackslash	18342, 20216	\textnumbersign	516, 14690, 15168
\textneqdot	19192, 20484	\textnotin	17751, 19966	\textnumero	17472
\textneqsim	17873, 20016	\textnotowner	17758, 17759, 19969, 20742	\textnupmodels	19304, 20535
\textnequiv	17962, 17963, 17964, 20055, 20764, 20765	\textnotperp	18985, 20401	\textnupdash	18138, 18139, 20133, 20784
\textneswarrow . . .	19024, 20419	\textnotslash	18339, 20215	\textnVDash	18166, 18167, 20142, 20793
\textNeutral	18790, 20317	\textnoway	18808, 20321	\textnvDash	18163, 18164, 20141, 20792
\textnewtie	15111, 15140, 16310	\textnparallel	17810, 17811, 19990	\textnvDash	18159, 18160, 18161, 20140, 20790, 20791
\textnexists	17740, 19961	\textnprec	18040, 20091	\textnvdash	18156, 18157, 20139, 20789
\textnfallingdoteq	17928, 20040	\textnprecapprox	19261, 20517	\textnVdash	18150, 20137
\textngeq	18004, 20074	\textnpreccurlyeq	18257, 20180	\textNwarrow	17694, 19940
\textngeqq	17981, 20063	\textnpreceq	19237, 20505	\textNwarrows	17568, 19890
\textngeqslant	19202, 20489	\textnpreceqq	19249, 20511	\textnwsearrow	19022, 20418
\textngg	17993, 20069	\textnprecsim	18034, 20088	\textobar	19110, 19111, 20451, 20892
\textngtr	17999, 20072	\textnqsubseteq	18261, 20182	\textobot	19119, 19120, 20453, 20896
\textngtrapprox . . .	19210, 20493	\textnqsupseteq	18263, 20183	\textobslash	19113, 19114, 19115, 19116, 20452, 20893, 20894, 20895
\textngtrless	18020, 20081	\textnRightarrow	17675, 19933	\textObullseye	16208, 20693
\textngtrsim	18014, 20078	\textnrightarrow	17580, 19895	\textodiv	19167, 20474
\textnhateq	17951, 20050	\textnrisingdoteq	17933, 20042		
\textni	17755, 17756, 19968, 20741	\textnrleg	15764, 15766, 20615		
\textNibRight	18846, 20336	\textnsim	17869, 20014		
\textNibSolidRight	18848, 20337	\textnsimeq	17877, 20018		
\textniepsilon	15994, 15995, 19739, 20636	\textnsqsubset	18070, 20106		
\textniota	16043, 16044, 19747, 20649	\textnsqsubseteq	18078, 20110		
		\textnsqsupset	18074, 20108		
		\textnsqsupseteq	18082, 20112		
		\textnSubset	18221, 20164		
		\textnsubset	18048, 20095		
		\textnsubseteq	18056, 20099		

\textdot . 18100, 18101, 20119,
20774

\textogonek 14682, 15101, 15130,
16291

\textgreaterthan 19127, 19128,
20456, 20898

\textohm 17487

\textoint 17837, 20001

\textoinferior 17412, 19858

\textoint . 17834, 17835, 20000,
20751

\textointclockwise 17840, 20002

\textointcclockwise ... 17842,
20003

\textolesthan ... 19124, 19125,
20455, 20897

\textOmega 19679, 19776

\textomega .. 3175, 3176, 3189,
19703, 19801

\textomicron . 3176, 3177, 3180,
3182, 3183, 3184, 3185,
3186, 3187

\textominus 18091, 18092, 20116,
20771

\textoneeighth 17540

\textonefifth 17528

\textonehalf 14852, 15311

\textoneinferior .. 17380, 19842

\textoneninth 17520

\textonequarter .. 14850, 15309

\textoneseventh 17518

\textonesixth 17536

\textonesuperior . 14843, 15302,
19724

\textonetenth 17522

\textonethird 17524

\textoo 19343, 20544

\textopenbullet .. 18581, 20250

\textopencorner .. 16303, 16304

\textopeno 15969, 15970, 15971,
19735, 20630

\textoplus 18088, 18089, 20115,
20770

\textordfeminine . 14813, 15268

\textordmasculine 14845, 15304

\textslash 18097, 18098, 20118,
20773

\texttimes 18094, 18095, 20117,
20772

\textovee . 17820, 17821, 19994,
20749

\textwedge 17815, 17816, 19992,
20748

\textparagraph 522, 14837,
15293, 15294, 20591

\textparallel 17808, 19989

\textparenleft . 735, 736, 14698,
15182

\textparenleftinferior ... 17404,
19854

\textparenleftsuperior .. 17372,
19838

\textparenright .. 14700, 15184

\textparenrightinferior .. 17406,
19855

\textparenrightsuperior . 17374,
19839

\textpartial 17736, 19959

\textPeace 18835, 20331

\textPencilRight . 18842, 20334

\textPencilRightDown .. 18840,
20333

\textPencilRightUp 18844, 20335

\textpentagon ... 19314, 20539

\textpercent .. 518, 14694, 15174

\textperiodcentered 14839,
15007, 15296, 15297, 15298,
19422, 20592, 20593

\textperp 18983, 20400

\textpertenthousand 17318

\textperthousand . 14752, 17316

\textpeseta 17440

\textpeso 17460

\textPhi 19676, 19774

\textphi 3182, 3186, 3187, 19700,
19798

\textphiinferior .. 16947, 19811

\textPhone 18596, 18597, 20256,
20824

\textPhoneHandset 18826, 20327

\textPi 3179, 3181, 19673, 19771

\textpi .. 3176, 3184, 3185, 3186,
3187, 19694, 19792

\textpinferior 17428, 19866

\textpipe . 15785, 15786, 15787,
20616

\textpipevar 15787, 20616

\textpisces 18716, 18717, 20294,
20866

\textpitchfork ... 18233, 20169

\textPlane 18830, 20329

\textPlus 18863, 20344

\textPlusCenterOpen .. 18867,
20346

\textplusinferior .. 17398, 19851

\textplusminus .. 14827, 15006,
15282, 19421

\textPlusOutline . 18861, 20343

\textplussuperior . 17366, 19835

\textPlusThinCenterOpen 18865,
20345

\textpluto 18680, 18681, 20282,
20854

\textpm .. 15006, 19421, 20573

\textpointer 17721, 19952

\textprec 18024, 20083

\textprecapprox .. 19259, 20516

\textpreccurlyeq .. 18028, 20085

\textpreceq .. 19235, 20504

\textpreceqq .. 19247, 20510

\textprecnapprox .. 19267, 20520

\textprecneq .. 19243, 20508

\textprecneqq .. 19255, 20514

\textprecnsim 18275, 20188

\textprecnsim 18032, 20087

\textprime 17320, 19820

\textprimstress .. 16273, 16274

\textprod 17763, 19971

\textproto 17789, 17790, 19982,
20743

\textPsi 19678, 19775

\textpsiprime .. 19702, 19800

\textPUaolig 19340, 19341, 20913

\textPUDblig 15942, 15943,
20620

\textPUfemale .. 18653, 18654,
18655, 18656, 18657, 18658,
20841, 20842, 20843, 20844,
20845

\textPUheng 19331, 19332, 20910

\textPULhookfour 19334, 19335,
20911

\textPUnreg 15765, 15766,
20615

\textPUqplig 15945, 15946, 20621

\textPUREvscr ... 16928, 16929,
20705

\textPURhooka .. 16959, 16960,
20706

\textPURhooke .. 16964, 16965,
20707

\textPURhookepsilon ... 16968,
16969, 20708

\textPURhookopeno 16972,
16973, 20709

\textPUScf . 19337, 19338, 20912

\textPUsck 16919, 16920, 20702

\textPUscm 16922, 16923, 20703

\textPUscp 16925, 16926, 20704

\textPUncrfemale 18796, 18797,
20876

\textqplig . 15944, 15946, 20621
\textquarternote . 18740, 20295
\textquestiondown .. 732, 14856,
 15315
\textquotedbl ... 14688, 15166
\textquotedblleft . 14756, 14996,
 17296, 19411
\textquotedblright 14758, 17298
\textquotefont ... 14760, 14998,
 17290, 19413
\textquoteright .. 14762, 17292
\textquotesingle 15180
\textRadioactivity 18623, 18624,
 20265, 20833
\textRain 18806, 20320
\textraiseglotstop 16262, 16263
\texttriangle 18330, 20212
\textbrackdbl ... 18996, 18997,
 20406, 20887
\textcurvearrowdown .. 19053,
 19054, 19055, 20430, 20890,
 20891
\textcurvearrowleft ... 19057,
 20431
\textcurvearrowne 19037, 20425
\textcurvearrowright .. 19060,
 20432
\textcurvearrowse 19046, 20428
\textRe 17479, 19874
\textrecipie 17481
\textRectangle ... 18979, 20398
\textRectangleBold 18981, 20399
\textRectangleThin 18977, 20397
\textrecycle 18755, 18756, 20301,
 20873
\textreferencemark 17332
\textregistered ... 14821, 15276
\textRequest 18360, 20223
\textrevapostrophe 16259, 16260
\textrevc 17548
\textrevE 15740
\textreve .. 15983, 15984, 19737
\textrevespsilon .. 15997, 15998,
 19740
\textrevglotstop .. 16194, 16195,
 16196, 19764, 20689
\textrevscr 16927, 16929, 20705
\textrevyogh .. 15775, 15776
\textRewind 18565, 20243
\textRewindToIndex ... 18372,
 20228
\textRHD 18556, 20240
\textrhdb . 18172, 18173, 20144,
 20795

\textrho 3180, 3181, 3186, 3187,
 3188, 3189, 19695, 19793
\textrhoinferior .. 16945, 19810
\textrhohooka 16958, 16960, 20706
\textrhoooke 16963, 16965, 20707
\textrhokepsilon 16967, 16969,
 20708
\textrhohooknearrow 19028, 20421
\textrhoopeno .. 16971, 16973,
 20709
\textrhokepsilon .. 16000,
 16001, 16002, 19741, 20637
\textrhohookschwa . 15989, 15990,
 15991, 20635
\textrhohookswallow 19032, 20423
\textRightarrow . 17683, 17684,
 19936, 20737
\textrightarrow ... 2163, 17556,
 17557, 17558, 19886, 20730,
 20731
\textrightarrowtail 17597, 19903
\textrightarrowtriangle . 17728,
 19955
\textrightarrowbarharpoon ... 19091,
 20443
\textRIGHTCIRCLE ... 18579,
 20249
\textrightharpoondown . 17638,
 19919
\textrightharpoonup ... 17635,
 19918
\textrightleftarrows 17647, 19922
\textrightleftharpoon ... 19064,
 20434
\textrightleftharpoons ... 17667,
 19930
\textrightmoon .. 18648, 20274
\textrightrightarrows ... 17659,
 19927
\textrightrightharpoons . 19079,
 20439
\textrightslice ... 19233, 20503
\textrightsquigarrow ... 17708,
 19947
\textrightthreetimes ... 18207,
 20158
\textrinferior 16935, 19805
\textring .. 14629, 14641, 14653,
 14684, 15091, 15120, 16289
\textringlow 15104, 15133, 16298
\textriota 17492, 19876
\textrisingdoteq .. 17931, 20041
\textrm 551
\textrptr 16268, 16269

\textrquill 17340
\textRightarrow . 17704, 19945
\textrrparenthesis 19106, 20449
\textrtaild 15975, 15976, 15977,
 19736, 20632
\textrtaill 16055, 16056, 16057,
 20652
\textrtailn 16078, 16079, 16080,
 20661
\textrtailr 16112, 16113, 16114,
 20669
\textrtails 16128, 16129, 16130,
 20672
\textrtailt 16146, 16147, 16148,
 20675
\textrtailz 16174, 16175, 16176,
 20684
\textrtimes 18203, 20156
\textsgittarius .. 18707, 18708,
 20291, 20863
\textsaturn 18671, 18672, 20279,
 20851
\textsc 557
\textscsa 16910, 16911
\textscb 16209, 16210
\textscd 16913, 19802
\textscce 16914, 16915
\textscf .. 19336, 19338, 20912
\textscg .. 16018, 16019, 19743
\textsch 16217, 16218
\textschwa . 15986, 15987, 19738
\textschwainferior 17416, 19860
\textsci .. 16045, 16046, 19748
\textScissorHollowRight 18824,
 20326
\textScissorRight . 18818, 18819,
 18820, 20324, 20880, 20881
\textScissorRightBrokenBottom
 18814, 18815, 18816,
 20878, 20879
\textScissorRightBrokenTop ..
 18822, 20325
\textscj 16916, 16917
\textscck .. 16918, 16920, 20702
\textscsl 16225, 16226
\textscm .. 16921, 16923, 20703
\textscn .. 16081, 16082, 19749
\textscraig .. 16088, 16089
\textscorpio 18704, 18705, 20290,
 20862
\textscp .. 16924, 16926, 20704
\textscr .. 16123, 16124, 19752
\textscripta 15956, 15957, 15958,
 19734, 20625

\textscriptg 16015, 16016, 16017, 19742, 20641
 \textscriptv 16157, 16158, 19757
 \textscu ... 16930, 16931, 19803
 \textscy ... 16171, 16172, 19761
 \textSearrow 17698, 19942
 \textsearrow 17573, 17574, 19892, 20735
 \textSech 19373, 20555
 \textsecond 17322, 19821
 \textsecstress 16276, 16277
 \textsection 14807, 15260, 15261, 15262, 20589, 20590
 \textSePa 19359, 20549
 \textservicemark 17483
 \textsetminus 14710, 17779, 19978
 \textseveneighths 17546
 \textseveninferior 17392, 19848
 \textsevensuperior 17360, 19832
 \textsf 552, 13072, 13075
 \textsharp 18753, 20300
 \textshuffle 19144, 20464
 \textSigma . 3178, 19674, 19772
 \textsigma ... 3175, 3176, 3190, 19697, 19795
 \textsim . 17859, 17860, 20010, 20754
 \textsizeq 17875, 20017
 \textsinferior 17430, 19867
 \textSixFlowerAlternate 18931, 20377
 \textSixFlowerAltPetal . 18941, 20382
 \textSixFlowerOpenCenter ... 18927, 20375
 \textSixFlowerPetalRemoved ... 18924, 20374
 \textsixinferior .. 17390, 19847
 \textSixStar 18914, 20369
 \textsixsuperior .. 17358, 19831
 \textSixteenStarLight .. 18922, 20373
 \textsixteenthnote 18747, 20297
 \textsl 558
 \textslashc 15948, 15949, 15951, 19733, 20622, 20623
 \textslashdiv 19320, 20542
 \textsmallin 17753, 19967
 \textsmallowns .. 17761, 19970
 \textsmile 18324, 20209
 \textsmiley 18638, 18639, 20270, 20838
 \textSnowflake .. 18945, 20384
 \textSnowflakeChevron . 18943, 20383
 \textSnowflakeChevronBold ... 18947, 20385
 \textSoccerBall .. 18801, 18802, 20877
 \textspadesuitblack 2162, 18719, 18720, 20867
 \textspadesuitwhite 18732
 \textSparkle 18949, 20386
 \textSparkleBold . 18951, 20387
 \textspphericalangle 17798, 17799, 17800, 17801, 19986, 20744, 20745, 20746
 \textsqcap 18084, 20113
 \textsqcup 18086, 20114
 \textsqdoublecap . 19171, 19172, 20476, 20900
 \textsqdoublecup . 19176, 19177, 20478, 20901
 \textsqsubset 18068, 20105
 \textsqsubseteq ... 18076, 20109
 \textsqsubsetneq . 18265, 18266, 20184, 20805
 \textsqsupset 18072, 20107
 \textsqsupseteq ... 18080, 20111
 \textsqsupsetneq . 18268, 18269, 20185, 20806
 \textSquareCastShadowBottom-Right 18970, 20394
 \textSquareCastShadowTo-pRight 18973, 20395
 \text squaredots .. 17852, 20007
 \textSquareShadowBottomRight 18964, 20392
 \textSquareTopRight ... 18967, 20393
 \textslash 19311, 19312, 20538, 20909
 \textstar 18193, 20152
 \textsterling 14799, 15249, 15250, 15251, 20586, 20587
 \textstmaryrdbaro 18336, 18337, 20811
 \textstretchc 16200, 16201, 16202, 16203, 20690, 20691
 \textstretchcvar .. 16203, 20691
 \textsub breve ... 15075, 15106, 15135, 17055, 17057
 \textsubcircum .. 15072, 15073, 15105, 15134, 17007, 17009, 17023, 17025, 17083, 17085, 17111, 17113, 17167, 17169, 17179, 17181
 \textsubring 15065, 15066, 15104, 15133, 16975, 16977
 \textSubset 18219, 20163
 \textsubset 18044, 20093
 \textsubseteq 18052, 20097
 \textsubsetneq ... 19271, 20522
 \textsubsetneqq ... 18060, 20101
 \textsubtilde 15076, 15077, 15107, 15136, 17027, 17029, 17059, 17061, 17175, 17177
 \textsublaut .. 15063, 15064, 15103, 15132, 17171, 17173
 \textsucc 18026, 20084
 \textsuccapprox ... 19263, 20518
 \textsucccurlyeq . 18030, 20086
 \textsuccceq 19239, 20506
 \textsuccceqq 19251, 20512
 \textsuccnapprox . 19269, 20521
 \textsuccneq 19245, 20509
 \textsuccneqq 19257, 20515
 \textsuccnsim ... 18277, 20189
 \textsuccsim 18036, 20089
 \textsum 17767, 19973
 \textsun . 18643, 18644, 20272, 20839
 \textSunCloud ... 18804, 20319
 \textSunshineOpenCircled 18939, 20381
 \textSupset 18223, 20165
 \textsupset 18046, 20094
 \textsupseteq 18054, 20098
 \textsupsetneqq ... 19275, 20524
 \textsupsetneq ... 18062, 20102
 \textsurd 17787, 19981
 \textSwallow 17700, 19943
 \textswallow 17576, 19893
 \TextSymbolUnavailable 14660, 14661, 14663
 \textTape 18828, 20328
 \texttau 3177, 3181, 3183, 3184, 3185, 19698, 19796
 \texttaurus 18686, 18687, 20284, 20856
 \texttctclig 16250, 16251
 \textTent 18812, 20323
 \textteshlig 16246, 16247, 16248, 20697
 \texttherefore ... 17844, 17845, 20004
 \textTheta . 3189, 19670, 19768
 \texttheta 19687, 19784
 \textthird 17324, 19822

\textThorn 14920, 15380, 19725
\textthorn 14989, 15449, 15451,
19726
\textthreeeighths 17542
\textthreefifths 17532
\textthreeinferior . 17384, 19844
\textthreequarters 14854, 15313
\textthreesuperior 14831, 15286,
19723
\texttie . 15110, 15139, 16316
\texttilde . 14627, 14639, 14651,
14686, 15089, 15118, 16293
\texttildelow 15107, 15136, 16302
\texttimes . 15004, 19419, 20571
\texttinferior 17432, 19868
\texttop . 18130, 18131, 20130,
20782
\texttrademark .. 14766, 17485
\texttriangle 17745, 19963
\texttriangleeq .. 17953, 20051
\texttriangleleft .. 18568, 20244
\texttriangleright .. 18554, 20239
\texttriplesim .. 17893, 17894,
20025, 20757
\textTslash 15675
\textTslash 15677
\textTslig 16244, 16245
\textTT 553
\textTumbler 18334, 20214
\textturna 15952, 15953, 15954,
20624
\textturnh 16027, 16028, 16029,
16030, 20643, 20644
\textturnk 16222, 16223, 16224,
20695
\textturnlongegr . 16102, 16103,
16104, 20666
\textturnnm 16061, 16062, 16063,
16064, 20654, 20655
\textturnmrleg .. 16066, 16067,
16068, 20656
\textturnr 16097, 16098, 16099,
16100, 20664, 20665
\textturnrrtail ... 16106, 16107,
16108, 20667
\textturnsck 16224, 20695
\textturnscripta .. 15960, 15961,
15962, 15963, 20626, 20627
\textturnt 16142, 16143, 16144,
20674
\textturnv 16159, 16160, 16161,
16162, 19758, 20678, 20679
\textturnw 16163, 16164, 16165,
16166, 19759, 20680, 20681
\textturny 16167, 16168, 16169,
16170, 19760, 20682, 20683
\textTwelveStar .. 18920, 20372
\texttwofifths 17530
\texttwoheaddownarrow 17593,
19901
\texttwoheadleftarrow .. 17582,
19896
\texttwoheadrightarrow . 17589,
19899
\texttwoheaduparrow .. 17586,
19898
\texttwoinferior .. 17382, 19843
\texttwonotes .. 18745, 20296
\texttwosuperior .. 14829, 15284,
19722
\texttwothirds 17526
\textudots 18296, 20196
\textuinferior 16937, 19806
\textulcorner 18314, 20204
\textuncrfemale .. 18795, 18797,
20876
\textunderscore 521, 4755, 4756,
4758, 14714, 15228, 15229,
20584
\textunlhd 18175, 18176, 18177,
20145, 20796, 20797
\textunrhd 18179, 18180, 18181,
20146, 20798, 20799
\textup 559
\textUParrow .. 18543, 18544,
20236, 20817
\textUparrow .. 17680, 19935
\textuparrow .. 17554, 19885
\textUpdownarrow 17692, 19939
\textupdownarrow .. 2165, 17566,
19889
\textupdownarrows 17650, 19923
\textupdownharpoonleftright ..
..... 19070, 20436
\textupdownharpoonrightleft ..
..... 19067, 20435
\textupdownharpoons .. 19097,
20445
\textupharpoonleft 17632, 19917
\textupharpoonright .. 17629,
19916
\textuplus 19146, 20465
\textupmodels .. 19302, 20534
\textUpsilon 19675, 19773
\textupsilon .. 3176, 3184, 3185,
3187, 19699, 19797
\textupspoon .. 19306, 20536
\textupstep 19325, 19326
\textupuparrows . 17657, 19926
\textupupharpoons 19076, 20438
\texturanus 18674, 18675, 20280,
20852
\texturcorner 18316, 20205
\textValve 19140, 20462
\textvarhexagon .. 19316, 20540
\textvarobar 19111, 20892
\textvarsigma 3180, 3186, 3187,
19696, 19794
\textVDash 18153, 18154, 20138,
20788
\textVdash 18145, 18146, 20135,
20787
\textvDash 18141, 18142, 18143,
20134, 20785, 20786
\textvdash 18121, 18122, 20127,
20779
\textvdotdot .. 17850, 20006
\textvdots 18292, 20194
\textvee 17818, 19993
\textveebar 18189, 20150
\textveedot 18987, 20402
\textveedoublebar 19188, 20482
\textvertline 15239, 20585
\textvibyi 16137, 16138
\textvibyy 16256, 16257
\textVier 19369, 20553
\textvinferior 16939, 19807
\textViPa 19355, 20547
\textvirgo 18698, 18699, 20288,
20860
\textvisiblespace 18376
\textVvDash 18148, 20136
\textwasylozenge .. 18306, 20201
\textwedge 17813, 19991
\textwedgedot ... 18989, 20403
\textWheelchair .. 18758, 20302
\textWomanFace .. 19383, 19384,
20560, 20916
\textwon 17442
\textwp 17477, 19873
\textwr .. 17866, 17867, 20013,
20755
\textWritingHand 18837, 18838,
20332, 20883
\textwynn 15782, 15783
\textXi 19672, 19770
\textxi .. 3175, 19693, 19791
\textxinferior 17414, 19859
\textXSolid 18855, 20340
\textXSolidBold .. 18857, 20341
\textXSolidBrush 18859, 20342
\textxswup 18766, 20875

\textyen 14803, 15255
\textYinYang . . . 18630, 18631,
18632, 18633, 20268, 20834,
20835, 20836
\textyogh . 16181, 16182, 19762
\textzeroinferior . 17378, 19841
\textzerosuperior . 17350, 19827
\textzerothirds 17550
\textzeta 19685, 19782
\textZwdr 19375, 20556
\textZwPa 19361, 20550
\TH . 14918, 14919, 15378, 15379
\th . 14987, 14988, 15449, 15450
\thaa 19580
\thanks 6453
\thebookmark@seq@number
14217
\thefootnote 7331, 7536
\theHchapter . 6863, 6864, 6865,
6866, 6999
\theHenumi 6882
\theHenumii 6883
\theHenumiii 6884
\theHenumiv 6885
\theHequation 6852, 6854, 7261,
7285, 7288
\theHfigure 6860, 6864
\theHHfootnote 6886, 6889
\theHHmpfootnote 6889
\theHItem . 6876, 6882, 6883,
6884, 6885
\theHmpfootnote 6887
\theHpage 7895
\theHparagraph 6870, 6871
\theHparentequation 7285, 7288
\theHpart 6856
\theHsection . 6852, 6859, 6866,
6868, 6872, 6873, 6997
\theHsubequation 7261
\theH subparagraph 6871
\theH subsection 6868, 6869
\theH subsubsection 6869, 6870
\theH table 6861, 6865
\theH theorem 6872
\theH thm 6873
\theHy@tempcnt 4871, 4879,
4886
\thempfn 7320, 7423, 7516, 7529
\theoremautorefname 2969, 2987,
3005, 3023, 3041, 3059,
3077, 3115, 3135, 3153,
3171, 3189, 3207, 3225,
3243, 3261, 8609
\thepage 2182, 4991, 6505, 6531,
6546, 7790, 7891, 7938,
8019, 8073, 8231, 8248,
8261, 8265, 8277, 8362,
8382, 8399, 8531
\therefore 17843, 20004
\Theta 19768
\theta 19784
\third 17323, 19822
>thispdfpagelabel 6510
\ThisShouldNotHappen . . 13795
\Thorn 14918, 15378, 19725
\thorn 14987, 15449, 19726
\threeinferior 19844
\threesuperior 19723
\tildel 16050, 20650
\times 20571
\tinferior 19868
\tiny 581
\ttitle 6407, 6409
\tl 2302, 5033, 5046
\TMP@EnsureCode
. 4618, 4625, 4626, 4627,
4628, 4629, 4630, 4631,
4632, 4633, 4634, 4635,
4636, 4637, 4638, 4639,
4640, 4641, 4642, 4643,
4644, 4645, 4646, 4647,
4648, 4649, 4650, 4651
\tocappendix 1301
\tocchapter 1300
\toclevel@chapter 3398
\toclevel@figure 3404
\toclevel@paragraph 3402
\toclevel@part 3394, 3396
\toclevel@section 3399
\toclevel@subparagraph 3403
\toclevel@subsection 3400
\toclevel@subsubsection 3401
\toclevel@table 3405
\tocparagraph 1305
\tocpart 1299
\tocsection 1302
\tocsubsection 1303
\tocsubsubsection 1304
\toks 8370, 8371, 8373, 14530,
14535, 14598, 14603
\toks@ 171, 208, 937, 960, 963,
965, 3273, 3274, 3276, 3867,
3871, 3872, 3880, 4313,
4314, 4513, 4515, 5125,
5130, 5136, 5142, 5143,
5146, 5246, 5251, 5255,
5259, 6626, 6628, 6714,
6716, 6775, 6787, 7107,
7112, 7401, 7404, 8112,
8113, 8335, 8340, 8342,
8345, 14529, 14535, 14597,
14603
\top 18129, 20130
\topmargin 7951
\triangle 17744, 19963
\triangleeq 17952, 20051
\triangleleft 18567, 20244
\trianglelefteq 18177, 20797
\triangleright 18553, 20239
\trianglerighteq 18181, 20799
\triplesim 17892, 20025
\tryhyper@link 4965, 4967
\ttfamily 563
\ttl@b 7118, 7123
\ttl@Hy@PatchSaveWrite . 7101,
7105
\ttl@Hy@refstepcounter 7117
\ttl@Hy@saveanchor 7096, 7120
\ttl@Hy@SavedCurrentHref 7100,
7111
\ttl@Hy@steplink 7094
\ttl@savewrite 7107, 7109
\Tumbler 18333, 20214
\turnv 19758
\turnw 19759
\turny 19760
\tw@ 4505, 5075, 5081, 5082,
5083, 5088, 5094, 5095,
5096, 14530, 14535, 14598,
14603
\TwelveStar 18919, 20372
\twoheaddownarrow 17592,
19901
\twoheadleftarrow 17581, 19896
\twoheadrightarrow 17588, 19899
\twoheaduparrow 17585, 19898
\twoinferior 19843
\twonotes 18744, 20296
\twosuperior 19722
\TX@endtabularx 7394, 7401,
7407
\typeout 5, 6, 7, 19, 26, 27,
36, 131, 155, 158, 159, 160,
5276, 20922

U

\U 15039, 16356, 16379, 16446,
16526, 16727, 16729, 16751,
16753, 16763, 16765
\u 15037, 15095, 15124, 15154,
15459, 15461, 15501, 15503,

\use	478, 484, 5024	\varovee	17821, 20749
\use@file	5207, 5209, 5216	\varowedge	17816, 20748
\usefont	548	\varparallel	19312, 20909
\UseHook	7073, 7089	\varparallelinv	18379, 20812
\utf@viii@undeferr	508	\varprop	17790, 20743
\UTFviii@four@octets	1903, 1912	\varsigma	19794
\UTFviii@loop	1891	\varsqsubsetneq	18266, 20805
\UTFviii@three@octets	1902	\varsqsupsetneq	18269, 20806
\UTFviii@tmp	1890	\vartimes	15364, 20594
\UTFviii@two@octets	1901	\vavyod	16904
V			
\v	14630, 14642, 14654, 14776, 14781, 14789, 14791, 15050, 15092, 15121, 15153, 15479, 15481, 15483, 15485, 15513, 15515, 15591, 15593, 15611, 15613, 15647, 15649, 15663, 15665, 15671, 15673, 15721, 15723, 15797, 15799, 15801, 15803, 15804, 15806, 15808, 15810, 15812, 15821, 15823, 15825, 15827, 15833, 15834, 15912, 15914	\VDash	18152, 20138
\V@@@footnotetext	7465	\Vdash	18144, 20135
\V@@@footnotetext	7450	\vDash	18140, 20134
\value	6529, 6985, 6986, 6988, 6989, 7736, 7763, 7955, 8130, 9885	\vdash	18120, 20127
\Valve	19139, 20462	\vdotdot	17849, 20006
\vara	15958, 20625	\vdots	18291, 20194
\varangle	17799, 20744	\vee	17817, 19993
\varbigcirc	18587, 20823	\veebar	18188, 20150
\varcurlyvee	18214, 20801	\veedot	18986, 20402
\varcurlywedge	18217, 20802	\veedoublebar	19187, 20482
\VarFlag	18761, 20874	\Venus	18657, 20844
\varg	16017, 20641	\venus	18656, 20843
\varhexagon	19315, 20540	\vfill	6183, 6184, 6185, 6186
\vari	16044, 20649	\VHF	17894, 20757
\varint	17828, 20750	\Vier	19368, 20553
\varnothing	17741, 17743, 20740	\vinferior	19807
\varoast	18108, 20777	\ViPa	19354, 20547
\varobslash	19116, 20895	\Virgo	18699, 20860
\varocircle	18105, 20776	\virgo	18697, 20288
\varodot	18101, 20774	\vod	16021, 16023, 20642
\varogreaterthan	19128, 20898	\voffset	7950
\varoint	17835, 20751	\voicedh	16034, 20646
\varolesthan	19125, 20897	\vpageref	8451, 8459, 8468, 8476
\varomega	16094, 20663	\vphantom	584
\varominus	18092, 20771	\Vr@f	8454
\varopeno	15971, 20630	\vr@f	8463
\varplus	18089, 20770	\vref@pagenum	7132
\varoslash	18098, 20773	\Vref@star	8447
\varotimes	18095, 20772	\vref@star	8472
Vv			
\vskip	2260, 2261	\vskip	2260, 2261
\vss	7964	\vtx@trans@special	10672, 10674, 10677, 10681, 10685, 10689, 10691, 10693, 10697, 10703, 10704, 10707
\VTeXInitMediaSize	10343, 10369	\VTeXOS	10736, 10737, 10738, 10740
\VTeXversion	6681, 6684, 6687, 10728, 10732	\VTeXvversion	6681, 6684, 6687, 10728, 10732
\Vvdash	18147, 20136		

W		
\wasylozenge	18305, 20201
\waw	19628
\wawhamza	19566
\wd	9475, 9491, 9512, 9529, 9552,	9552, 9569, 13435
\wedge	17812, 19991
\wedgedot	18988, 20403
\Wheelchair	18757, 20302
\with	15178, 20583
\WomanFace	19382, 20560
\Womanface	19384, 20916
\wp	17476, 19873
\wr	17865, 20013
\wreath	17867, 20755
\write	..	4826, 5363, 5365, 6379, 6804, 6812, 7720, 7735, 7752, 7762, 7781, 7811, 12971, 12974, 13002, 13017
\WriteBookmarks	..	4251, 4377, 4587, 4609, 14151, 14394, 14424, 14425, 14467, 14473
\WritingHand	...	18836, 20332
\Writinghand	...	18838, 20883
\wwwbrowser	.	9429, 9514, 9531
X		
\x	21, 25, 92, 98, 168, 169, 176, 178, 206, 209, 210, 211, 212, 213, 214, 215, 216, 217, 218, 219, 220, 221, 222, 223, 224, 225, 226, 227, 228, 273, 278, 279, 913, 919, 1400, 1428, 1843, 1845, 2255, 2265, 2274, 2284, 2373, 2374, 2379, 2395, 3284, 3287, 3291, 3304, 3415, 3416, 3419, 3420, 3421, 3425, 3428, 3434, 3870, 3876, 3879, 3882, 4152, 4153, 4158, 4159, 4267, 4268, 4269, 4272, 4275, 4278, 4311, 4312, 4314, 4315, 4514, 4517, 4825, 4831, 5222, 5223, 5224, 5236, 5247, 5248, 5249, 5250, 5253, 5254, 5299, 5302, 5384, 5398, 5423, 5427, 5430, 5440, 5975, 5979, 6429, 6430, 6435, 7108, 7115, 7148,
Y		
\y	278, 280, 287, 293, 2375, 2380, 2385, 3421, 3422, 3423, 3424, 4270, 4273, 4276, 4279, 4281, 4287, 5225, 5226, 5227, 5228, 5236, 6430, 6438, 7144, 7146, 7147, 7150, 7157, 11236, 11237, 11238, 11239
\ya	19632
\yahamza	19570
\YingYang	18632, 20835
Z		
\z	279, 280, 288, 294, 2377, 2379, 5228, 5236	
\z@	1129, 1169, 1182, 1198, 1221, 1294, 1528, 1540, 1613, 1617, 1629, 2207, 2212, 2269, 2563, 2566, 2743, 3427, 3433, 4154, 4583, 5071, 5081, 5082, 5085, 5094, 5095, 5103, 6682, 6685, 7463, 9251, 9256, 9260, 9268, 9272, 9273, 9281, 9282, 10201, 10205, 10206, 10212, 10214, 10345, 10346, 10351, 10358, 10359, 10727, 10751, 10973, 11288, 11659, 11660, 11664, 11670, 11671, 12475, 12542, 13143, 13499, 13919, 13950, 13978, 13984, 14013, 14053, 14072, 14083, 14119, 14124, 14228, 14230, 14231, 14232, 14234, 14235, 14236, 14570	
\z@skip	
\za	1
\zay	1
\zeroinferior	1
\zerosuperior	1
\zeta	1
\zref@extractdefault	1
\zref@ifrefcontainsprop	1
\zref@ifrefundefined	1
\zref@labelbyprops	1
\zref@refused	1
\Zwdr	19374, 2
\ZWNJ	1
\ZwPa	19360, 2